

LED Waterproof Fittings

Introducing our IP65 Ingress Protection Waterproof tubes, built dust-tight allowing it to resist rain and jets of water.



Product Features

- Luminous efficacy up to 120lm/W and 80lm/W
- Easy to install
- IP65, free from water and dirt
- Without opening the lampshade for direct wiring
- Perfect replacement for the whole set of T8 fluorescent lighting fixture
- Save up to 80% in electricity consumption compared to fluorescent lighting fixture

Applications

Widely used for Domestic and Commercial Lighting, Offices, Supermarkets, Shops, Hotels & similar environment


Waterproof Fitting-Tubes

36w VT-12023

 Box Qty.
10 Pcs

6387 - 4000K Day White
6399 - 6400K White

3800157625036
3800157626385



2 LED TUBES INCLUDED



Voltage/Frequency: AC:200-240V,50/60Hz

Beam Angle: 120°

On/Off: >10,000

Luminous Flux: 3400lm

Body Type: ABS+PC

Life span: 30,000 Hours

CRI: >80

IP Rating: IP65

Gross weight: 1.33 kg

PF: >0.9

LED Type: SMD

Dimension: 1260x112x63mm


Waterproof Fitting-Tubes

44w VT-15022

 Box Qty.
10 Pcs

6388 - 4000K Day White
6400 - 6400K White

3800157625043
3800157626392



2 LED TUBES INCLUDED



Voltage/Frequency: AC:200-240V,50/60Hz

Beam Angle: 120°

On/Off: >10,000

Luminous Flux: 4000lm

Body Type: ABS+PC

Life span: 30,000 Hours

CRI: >80

IP Rating: IP65

Gross weight: 1.65 kg

PF: >0.9

LED Type: SMD

Dimension: 1560x112x63mm


Waterproof Fitting-G Series

18w VT-6076

Box Qty.
12 Pcs

6283 - 4000K Day White

3800157616478



Voltage/Frequency: **AC:220-240V,50Hz**

Beam Angle: **120°**

On/Off: **>10,000**

Luminous Flux: **1440lm**

Body Type: **ABS+PC**

Life span: **20,000 Hours**

CRI: **>70**

IP Rating: **IP65**

Gross weight: **0.60 kg**

PF: **>0.5**

LED Type: **SMD**

Dimension: **600x65x58mm**

Waterproof Fitting-G Series

36w VT-1249


Box Qty.
12 Pcs

6285 - 4000K Day White

3800157616492

6284 - 6400K White

3800157616485



Voltage/Frequency: **AC:220-240V,50Hz**

Beam Angle: **120°**

On/Off: **>10,000**

Luminous Flux: **2880lm**

Body Type: **ABS+PC**

Life span: **20,000 Hours**

CRI: **>70**

IP Rating: **IP65**

Gross weight: **0.60 kg**

PF: **>0.9**

LED Type: **SMD**


Dimension: **1200x65x58mm**

Waterproof Fitting-G Series

48W VT-1574

 Box Qty.
12 Pcs

 6287 - 4000K Day White
 6286 - 6000K White

 3800157616515
 3800157616508


Voltage/Frequency: AC:220-240V,50Hz

Beam Angle: 120°

On/Off: >10,000

Luminous Flux: 3840lm

Body Type: ABS+PC

Life span: 20,000 Hours

CRI: >70

IP Rating: IP65

Gross weight: 1.1 kg

PF: >0.9

LED Type: SMD


Dimension: 1500x65x58mm

Waterproof Fitting

18W VT-6048

 Box Qty.
12 Pcs

 6198 - 4500K Day White
 6199 - 6000K White

 3800157603256
 3800157603263


Voltage/Frequency: AC:200-240V,50Hz

Beam Angle: 120°

On/Off: >10,000

Luminous Flux: 1440lm

Body Type: Plastic

Life span: 20,000 Hours

CRI: >70

IP Rating: IP65

Gross weight: 0.80 kg

PF: >0.9

LED Type: SMD


Dimension: 600x76x66mm

Waterproof Fitting
36w VT-1248

6200 - 4500K Day White
6201 - 6000K White

3800157603270
3800157603287

Box Qty.
12 Pcs




Voltage/Frequency:	AC:200-240V,50Hz	Beam Angle:	120°	On/Off:	>10,000
Luminous Flux:	2880lm	Body Type:	Plastic	Life span:	20,000 Hours
CRI:	>70	IP Rating:	IP65	Gross weight:	1.42 kg
PF:	>0.9	LED Type:	SMD	Dimension:	1200x76x66mm

Waterproof Fitting
48w VT-1548

6184 - 4500K Day White
6185 - 6000K White

3800157602389
3800157602396

Box Qty.
12 Pcs



Voltage/Frequency:	AC:200-240V,50/60Hz	Beam Angle:	120°	On/Off:	>10,000
Luminous Flux:	3920lm	Body Type:	Plastic	Life span:	20,000 Hours
CRI:	>70	IP Rating:	IP65	Gross weight:	1.86 kg
PF:	>0.7	LED Type:	SMD	Dimension:	1480x76x66mm

Waterproof Fitting

70w VT-1573

6266 - 4000K Day White
6267 - 6000K White

Box Qty.
6 Pcs

3800157612586
3800157612593



120+ LUMENS PER WATT

SUPER EFFICIENT

Voltage/Frequency: AC:200-240V,50/60Hz
Luminous Flux: 8400lm
CRI: >70
PF: >0.9

Beam Angle: 120°
Body Type: Aluminium
IP Rating: IP65
LED Type: SMD

On/Off: >10,000
Life span: 20,000 Hours
Gross weight: 2.75 kg
Dimension: 1500x86x70mm




Waterproof-Emergency Kit

36W VT-1250

Box Qty.
12 Pcs

6448 - 4000K Day White
6449 - 6500K White

3800157632126
3800157632133



**Waterproof
Emergency Kit**

Charging Time: 24 Hours
Emergency Operation Time: 3 Hours
Emergency Switch on time: <1 Second

Voltage/Frequency:	AC:220-240V,50/60Hz	PF:	>0.9	O/P Emmergency:	7W Max
Battery Type:	9.6V 2200mAh Ni-Cd	Beam Angle:	120°	Ambient Temp:	50 max
Luminous Flux:	2880lm	Body Type:	ABS+PC	Gross weight:	1.9 kg
LED Type:	SMD	IP Rating:	IP65	Dimension:	1200x76x66mm
CRI:	>70	Life span:	20,000 Hours		


Waterproof-Emergency Kit

48W VT-1550

Box Qty.
12 Pcs

6446 - 4000K Day White
6447 - 6500K White

3800157632102
3800157632119



**Waterproof
Emergency Kit**

Charging Time: 24 Hours
Emergency Operation Time: 3 Hours
Emergency Switch on time: <1 Second

Voltage/Frequency:	AC:220-240V,50/60Hz	PF:	>0.9	O/P Emmergency:	7W Max
Battery Type:	9.6V 2200mAh Ni-Cd	Beam Angle:	120°	Ambient Temp:	50 max
Luminous Flux:	3920lm	Body Type:	ABS+PC	Gross weight:	2.35 kg
LED Type:	SMD	IP Rating:	IP65	Dimension:	1500x76x66mm
CRI:	>70	Life span:	20,000 Hours		