

V-TAC[®]

INNOVATIVE LED LIGHTING



2017-Q1 Catalogue

Showroom Support

Vienna | Bucharest | Budapest
Paris | Frankfurt | Birmingham

Head Offices

Sofia | London

MORE THAN

1000

PRODUCTS

Our Mission

Provide the Ultimate LED Solutions

Founded in 2009, V-TAC has grown from strength to strength and has established itself as a global brand providing energy efficient lighting solutions covering more than 70 countries throughout Europe, Asia Pacific, Africa, Middle East and the USA.

As a result of its relentless pursuit towards excellence, V-TAC has been listed in London Stock Exchange Group's 1000 Companies to Inspire Europe 2016.

V-TAC believes in offering high quality LED solutions with strong product guarantees, competitively priced and easy to install products certified with DEKRA, GS, TUV, CE/EMC, ROHS and UL certifications. With over a 1000 value for money products in all categories, continued investment in people, systems and product innovations, V-TAC continues to explore uncharted territories.

Over the last eight years V-TAC has replaced 35 million standard lights with energy saving LED Lights, resulting in total customer savings of over a £150 million per year, which has led to the reduction of over 150 thousand tons of Carbon Emissions.


With a vision to provide affordable LED Lighting solutions to Residential, Industrial and Commercial sectors, V-TAC surges forward on the foundation of its three pronged approach – Design, Develop and Distribute at lighting speed EVERYDAY!

OUR APPROVALS FROM



CE/EMC





2010

11 Employees
2 Offices
\$ 1.50m Turnover

2011

20 Employees
3 Offices
\$ 8m Turnover

2012

25 Employees
3 Offices
\$ 18m Turnover

2013

55 Employees
4 Offices
\$ 30m Turnover

2014

75 Employees
5 Offices
\$ 50m Turnover

2015

110 Employees
6 Offices
\$ 75m Turnover

in **2016** we reached the
milestone that is

100 Million \$
T u r n o v e r

We know that good work only comes from partnerships with great clients like you!
We appreciate your business and We 'll continue to grow together!

LED Flood lights 01



Shiny White

02 : 05



Shiny Grey/Black

06 : 08



Sand Finish Black

09 : 12



Sand Finish Grey

13 : 16



Slim Series

17 : 19



I - Series

20 : 21



Italian Series

22 : 24



PIR Sensor Series

25 : 32



RGB Series

33 : 34



Big Power Series

36 : 38



Accessories

39 : 40

LED Bulbs 41



Vintage Series

42 : 47



Amber Cover

48 : 52



White Cover

53 : 54



Frost Cover

55 : 59



Clear Glass

60 : 69



Thermal Plastic

70 : 94



Blister Packing

95

LED Spotlights **97**



GU10-MR16

98 : 102



G4-G9

103 : 104



Accessories

105 : 118

LED PAR Bulbs **119**



AR111

120 : 122



Accessories

123



PAR 38

124



Accessories

125

LED Tubes **127**




Nano-Plastic

128 : 131



Glass Tubes

132



Commercial Tubes

133 : 134



Fixtures With LED

135 : 139



Batten Fittings

140

LED Water-proof Fitting **141**



Water-proof Fitting

142 : 144

LED Panels **145**



60 x 60 Panels

146 : 150



Big Panels

151 : 153



Accessories

154 : 160



Mini Panels

161 : 188

LED HighBays **189**



UFO Highbays

190 : 191



High Power

192



Streetlights

198 : 202

LED Strip Lights **203**



Strip Lights

204 : 214



Aluminum Profiles

215 : 210



Strip Controllers

217 : 218



SMD LED Modules

219 : 220



Power Supplies

221 : 224

LED Track Lights **225**



COB Track Lights

226 : 234



Accessories

235 : 240



COB Downlights

242 : 247



Zoom Lights

248 : 249



Step Lights

250 : 254

LED Downlights **241**

LED Dome Lights **255**



Dome Lights

255 : 268

LED Motion Sensor **269**



Infrared

270 : 274



Microwave

275 : 278

LED Table Lamps **279**



Desk Lamp

280 : 289



Floor Lamp

290 : 292



Solar Lights

294 : 295



Pool Lights

296



Outdoor Fixtures

297 : 300

Garden Lamps **301**



Wall Lamps

302 : 310



Ceiling Lamp

311 : 312



Stand Lamp

312 : 316



Power Supplies

318 : 322



Power Supplies

324 : 328

Wall Lights **317**

Display Screen **323**

LED / Decorative Pendants **329**



Pendants

330 : 391



Holders

392 : 406



Designer Sleek

407 : 417



Chandeliers

419 : 423



LED Flood Lights

V-TAC's LED Floodlights are ideal for lighting Driveways, Gardens and Buildings. These energy efficient lights emit Bright, Vibrant Light and are an eco friendly replacement for traditional Halogen Floodlights and Metal Halide fixtures.

Product Features




- Available in White , Warm White, Day White and RGB light output option
- Available from 10W up to 1000W
- Premium Quality Aluminium Alloy body
- Corrosion Resistant
- Fascia glass sealed with SILICONE RUBBER ensuring superior waterproof /airtight performance
- High Power LED chip
- Built in constant current driver
- Built in Power supply, No external ballast required

Applications

Widely used for Lighting Driveways, Gardens & Buildings, Commercial Bill Boards & Hoardings, Plazas, Sports Grounds & Parking Lots



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

10W VT-4911

EAN Code




5771 3000k Warm White
5772 4000K Day White
5773 6400K White

3800157614450
3800157614467
3800157614474



EQ. Watts:	50W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	White
Luminous Flux:	800lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	113x136x28mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

20W VT-4922

EAN Code



5789 3000k Warm White
5790 4000K Day White
5791 6400K White

3800157614634
3800157614641
3800157614658



EQ. Watts:	100W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	White
Luminous Flux:	1600lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	148x181x34mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



30W VT-4933
5807 3000k Warm White
5808 4000K Day White
5809 6400K White



EAN Code
3800157614818
3800157614825
3800157614832



EQ. Watts:	150W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	White
Luminous Flux:	2550lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	174 x 217 x 35mm

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



50W VT-4955
5825 3000k Warm White
5826 4000K Day White
5827 6400K White



EAN Code
3800157614993
3800157615006
3800157615013



EQ. Watts:	250W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	White
Luminous Flux:	4250lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	194 x 237 x 38mm

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



100W VT-49100

EAN Code



- 5843 3000k Warm White
- 5844 4000K Day White
- 5845 6400K White

- 3800157615174
- 3800157615181
- 3800157615198



EQ. Watts:	600W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	White
Luminous Flux:	8500lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	231x 293 x41mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



150W VT-49150

EAN Code

- 5855 3000k Warm White
- 5856 4000K Day White
- 5857 6400K White

- 3800157615297
- 3800157615303
- 3800157615310



EQ. Watts:	800W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	White
Luminous Flux:	12750lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	313 x 411x 51mm



200W VT-49200

EAN Code



5909 4000K Day White
5910 6400K White

3800157619431
3800157619448




EQ. Watts:	1000W	Beam Angle:	100°
Voltage/Frequency:	AC:200-240V/50Hz	Color of Fixture:	White
Luminous Flux:	17000lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	340 x 454x 56mm




LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

10W VT-4911

5774 3000k Warm White
5775 4000K Day White
5776 6400K White




EAN Code

3800157614481
3800157614498
3800157614504



EQ. Watts:	50W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey / Black
Luminous Flux:	800lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	113x136x28mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

20W VT-4922

5792 3000k Warm White
5793 4000K Day White
5794 6400K White



EAN Code

3800157614665
3800157614672
3800157614689



EQ. Watts:	100W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey / Black
Luminous Flux:	1600lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	148x181x34mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



30W VT-4933

5810 3000k Warm White
5811 4000K Day White
5812 6400K White



EAN Code

3800157614849
3800157614856
3800157614863



EQ. Watts:	150W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey / Black
Luminous Flux:	2550lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	174 x 217 x 35mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



50W VT-4955

5828 3000k Warm White
5829 4000K Day White
5830 6000k White

EAN Code



3800157615020
3800157615037
3800157615044



EQ. Watts:	250W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey / Black
Luminous Flux:	4250lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	194 x 237 x 38mm

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



100W VT-49100

5846 3000k Warm White
5847 4000K Day White
5848 6400K White



EAN Code

3800157615204
3800157615211
3800157615228



EQ. Watts:	600W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey / Black
Luminous Flux:	8500lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	231x 293 x41mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



150W VT-49150

5858 3000k Warm White
5859 4000K Day White
5860 6400K White




EAN Code

3800157615327
3800157615334
3800157615341



EQ. Watts:	800W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey / Black
Luminous Flux:	12750lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	313 x 411x 51mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

10W VT-4911

EAN Code




5777 3000k Warm White
5778 4000K Day White
5779 6400K White

3800157614511
3800157614528
3800157614535



EQ. Watts:	50W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	800lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	113x136x28mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

20W VT-4922

EAN Code




5795 3000k Warm White
5796 4000K Day White
5797 6400K White

3800157614696
3800157614702
3800157614719



EQ. Watts:	100W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	1600lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	148x181x34mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



30W VT-4933

5813 3000k Warm White
5814 4000K Day White
5815 6400K White




EAN Code

3800157614870
3800157614887
3800157614894



EQ. Watts:	150W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	2550lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	174 x 217 x 35mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



50W VT-4955

5831 3000k Warm White
5832 4000K Day White
5833 6400K White



EAN Code

3800157615051
3800157615068
3800157615075



EQ. Watts:	250W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	4250lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	194 x 237 x 38mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




100W VT-49100

EAN Code



5849 3000k Warm White
5850 4000K Day White
5851 6400K White

3800157615235
3800157615242
3800157615259



EQ. Watts:	600W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	8500lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	231x 293 x41mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




150W VT-49150

EAN Code

5861 3000k Warm White
5862 4000K Day White
5863 6400K White

3800157615358
3800157615365
3800157615372



EQ. Watts:	800W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	12750lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	313 x 411x 51mm



200W VT-49200

5911 4000K Day White
5912 6400K White



EAN Code

3800157619455
3800157619462




EQ. Watts:	1000W	Beam Angle:	100°
Voltage/Frequency:	AC:200-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	17000lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	340 x 454x 56mm




LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

10W VT-4911

EAN Code




5780 3000k Warm White
5781 4000K Day White
5782 6400K White

3800157614542
3800157614559
3800157614566



EQ. Watts:	50W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey
Luminous Flux:	800lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	113x136x28mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

20W VT-4922

EAN Code




5798 3000k Warm White
5799 4000K Day White
5800 6400K White

3800157614726
3800157614733
3800157614740



EQ. Watts:	100W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey
Luminous Flux:	1600lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	148x181x34mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

30W VT-4933

5816 3000K Warm White
5817 4000K Day White
5818 6400K White




EAN Code

3800157614900
3800157614917
3800157614924



EQ. Watts:	150W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey
Luminous Flux:	2550lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	174 x 217 x 35mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

50W VT-4955

5834 3000K Warm White
5835 4000K Day White
5836 6400K White



EAN Code

3800157615082
3800157615099
3800157615105



EQ. Watts:	250W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey
Luminous Flux:	4250lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	194 x 237 x 38mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



100W VT-49100

EAN Code



5852 3000k Warm White
5853 4000K Day White
5854 6400K White

3800157615266
3800157615273
3800157615280



EQ. Watts:	600W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey
Luminous Flux:	8500lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	231x 293 x41mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



150W VT-49150

EAN Code

5864 3000k Warm White
5865 4000K Day White
5866 6400K White

3800157615389
3800157615396
3800157615402



EQ. Watts:	800W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Grey
Luminous Flux:	12750lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	313 x 411x 51mm



200W VT-49200

EAN Code

5913 4000K Day White

3800157619479



5914 6400K White

3800157619486




EQ. Watts:	1000W	Beam Angle:	100°
Voltage/Frequency:	AC:200-240V/50Hz	Color of Fixture:	Grey
Luminous Flux:	17000lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	340 x 454x 56mm



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



100W VT-48100-1

EAN Code



5686 4500K Daywhite
5687 6000K White

3800157603454
3800157603461




EQ. Watts:	500W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	White
Luminous Flux:	8000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	353 x 268 x 46mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



100W VT-48100-1

EAN Code




5766 / 5713 4500K Daywhite
5767 / 5714 6000K White

3800157604543
3800157604550



EQ. Watts:	500W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Grey & Black
Luminous Flux:	8000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	353 x 268 x 46mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

200W VT-48202

EAN Code




5873 / 5729 4500K Daywhite
5874 / 5730 6000K White

3800157606127
3800157606134



EQ. Watts:	1000W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Grey & Black
Luminous Flux:	16000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	434 x 352 x 60 mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

300W VT-48302

EAN Code



5731 4500K Daywhite
5732 6000K White

3800157606141
3800157606158



EQ. Watts:	1500W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Grey & Black
Luminous Flux:	24000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	532 x 443 x 70 mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



20W VT-4820
5760 / 5718 Green

EAN Code
3800157604970





Green LED

EQ. Watts:	100W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Grey & Black
Luminous Flux:	1600lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.95	Dimension:	182 x 142 x 36mm

Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



20W VT-4820
5719 Blue

EAN Code
3800157604987



Blue LED

EQ. Watts:	100W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Grey & Black
Luminous Flux:	1600lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.95	Dimension:	182 x 142 x 36mm

Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.




10W VT-4611


5898 3000k Warm White
5899 4500k Day White
5900 6000k White

EAN Code

3800157619219
3800157619226
3800157619233



EQ. Watts:	20W	Beam Angle:	110°
Voltage/Frequency:	AC:200-240,50/60Hz	Color of Fixture:	White
Luminous Flux:	850lm	Body Type:	Die Cast aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	122 x 105 x 30mm




10W VT-4611


5875 3000k Warm White
5876 4500k Day White
5877 6000k White

EAN Code

3800157615976
3800157615983
3800157615990



EQ. Watts:	20W	Beam Angle:	110°
Voltage/Frequency:	AC:200-240,50/60Hz	Color of Fixture:	Black
Luminous Flux:	850lm	Body Type:	Die Cast aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	122 x 105 x 30mm




20W VT-4621


5878 3000k Warm White
5879 4500k Day White
5880 6000k White

EAN Code

3800157616003
3800157616010
3800157616027



EQ. Watts:	40W	Beam Angle:	110°
Voltage/Frequency:	AC:200-240,50/60Hz	Color of Fixture:	Black
Luminous Flux:	1700lm	Body Type:	Die Cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	168 x 135 x 30 mm







30W VT-4631

5881 3000k Warm White
5882 4500k Day White
5883 6000k White

EAN Code

3800157616034
3800157616041
3800157616058



EQ. Watts:	60w	Beam Angle:	110°
Voltage/Frequency:	AC:200-240,50/60Hz	Color of Fixture:	Black
Luminous Flux:	2550	Body Type:	Die Cast aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	213 x 168 x 32





50W VT-4651

5884 3000k Warm White
5885 4500k Day White
5886 6000k White

EAN Code

3800157616065
3800157616072
3800157616089



EQ. Watts:	100w	Beam Angle:	110°
Voltage/Frequency:	AC:200-240,50/60Hz	Color of Fixture:	Black
Luminous Flux:	4250	Body Type:	Die Cast aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	255 x 196 x 36mm





50W VT-4651

5904 3000k Warm White
5905 4500k Day White
5906 6000k White

EAN Code

3800157619370
3800157619387
3800157619394



EQ. Watts:	100w	Beam Angle:	110°
Voltage/Frequency:	AC:200-240,50/60Hz	Color of Fixture:	White
Luminous Flux:	4250	Body Type:	Die Cast aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	255 x 196 x 36




10W VT-4714

5655 3000K Warm White
5656 4500K Day White
5657 6000K White




EAN Code

3800157603027
3800157603034
3800157603041



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	18W	Beam Angle:	85°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	Grey
Luminous Flux:	800lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	137 x 87 x 60mm




20W VT-4724

5658 3000K Warm White
5659 4500K Day White
5660 6000K White




EAN Code

3800157603058
3800157603065
3800157603072



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	36W	Beam Angle:	90°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	Grey
Luminous Flux:	1600lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	218 x 142 x 60mm




30W VT-4734

5661 3000K Warm White
5662 4500K Day White
5663 6000K White




EAN Code

3800157603089
3800157603096
3800157603102



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	54W	Beam Angle:	90°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	Grey
Luminous Flux:	2400lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	274 x 188 x 73mm




50W VT-4754

5664 3000K Warm White
5665 4500K Day White
5666 6000K White




EAN Code

3800157603119
3800157603126
3800157603133



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	90W	Beam Angle:	100°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	Grey
Luminous Flux:	4000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	335 x 239 x 120mm



100W VT-47104

5667 3000K Warm White
5668 4500K Day White
5669 6000K White





EAN Code



3800157603140
3800157603157
3800157603164

EQ. Watts:	180W	Beam Angle:	100°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	Grey
Luminous Flux:	8000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	405 x 288 x 130mm


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



10W VT-4911

5786 3000k Warm White
5787 4000k Day White
5788 6400k White

EAN Code

3800157614603

3800157614610

3800157614627



Detection Angle: **120°**

Detection Distance: **2-8 Meters**




EQ. Watts:	50W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	White
Luminous Flux:	800lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	113x 178x 47mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



20W VT-4922

5804 3000k Warm White
5805 4000k Day White
5806 6400k White

EAN Code

3800157614788

3800157614795

3800157614801



Detection Angle: **120°**

Detection Distance: **2-8 Meters**




EQ. Watts:	100W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	White
Luminous Flux:	1600lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	181 x 205 x 57mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



30W VT-4933

5822 3000k Warm White
5823 4000k Day White
5824 6400k White

EAN Code



3800157614962
3800157614979
3800157614986

Detection Angle: 120°
Detection Distance: 2-8 Meters




EQ. Watts:	150W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	White
Luminous Flux:	2550lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	217 x 231 x 59mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



50W VT-4955

5840 3000k Warm White
5841 4000k Day White
5842 6400k White

EAN Code




3800157615143
3800157615150
3800157615167

Detection Angle: 120°
Detection Distance: 2-8 Meters



EQ. Watts:	250W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	White
Luminous Flux:	4250lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	237 x 251 x 62mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

10W VT-4911

5783 3000k Warm White
5784 4000k Day White
5785 6400k White

EAN Code




3800157614573
3800157614580
3800157614597

Detection Angle: 120°
Detection Distance: 2-8 Meters



EQ. Watts:	50W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	800lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	113x 178x 47mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

20W VT-4922

5801 3000k Warm White
5802 4000k Day White
5803 6400k White

EAN Code



3800157614757
3800157614764
3800157614771

Detection Angle: 120°
Detection Distance: 2-8 Meters



EQ. Watts:	100W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	1600lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	181 x 205 x 57mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



30W VT-4933

5819 3000k Warm White
5820 4000k Day White
5821 6400k White

EAN Code



3800157614931
3800157614948
3800157614955

Detection Angle: 120°
Detection Distance: 2-8 Meters



EQ. Watts:	150W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	2550lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	217 x 231 x59mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



50W VT-4955

5837 3000k Warm White
5838 4000k Day White
5839 6400k White

EAN Code


3800157615112
3800157615129
3800157615136

Detection Angle: 120°
Detection Distance: 2-8 Meters



EQ. Watts:	250W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V/50Hz	Color of Fixture:	Black
Luminous Flux:	4250lm	Body Type:	Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	237 x251x 62mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



The average illuminance effective figure

Max Lux: 117.7 lux


1.0m	18.100 / 415.000	3.400m / 9.400m
2.0m	4.537 / 100.000	6.800m / 17.700m
3.0m	3.025 / 66.667	10.200m / 26.667m
4.0m	2.269 / 50.000	13.600m / 35.556m
5.0m	1.815 / 40.000	17.000m / 45.455m
6.0m	1.517 / 33.333	20.400m / 55.556m
7.0m	1.305 / 28.571	23.800m / 65.455m
8.0m	1.146 / 25.000	27.200m / 75.556m
9.0m	1.022 / 22.222	30.600m / 85.556m
10.0m	0.913 / 20.000	34.000m / 95.556m

Max Lux: 117.7 lux

Beam Angle: 100°

Distance: 10m

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



10W VT-4810-1 PIR

5746 3000K Warm White
5747 4500K Day White
5748 6000K White


EAN Code
3800157608206
3800157608213
3800157608220

Detection Angle: 120°
Detection Distance: 2-8 Meters



EQ. Watts:	50W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	White
Luminous Flux:	800lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	133x178x47mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



The average illuminance effective figure

Max Lux: 117.7 lux


1.0m	18.100 / 415.000	3.400m / 9.400m
2.0m	4.537 / 100.000	6.800m / 17.700m
3.0m	3.025 / 66.667	10.200m / 26.667m
4.0m	2.269 / 50.000	13.600m / 35.556m
5.0m	1.815 / 40.000	17.000m / 45.455m
6.0m	1.517 / 33.333	20.400m / 55.556m
7.0m	1.305 / 28.571	23.800m / 65.455m
8.0m	1.146 / 25.000	27.200m / 75.556m
9.0m	1.022 / 22.222	30.600m / 85.556m
10.0m	0.913 / 20.000	34.000m / 95.556m

Max Lux: 117.7 lux

Beam Angle: 100°

Distance: 10m

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



20W VT-4820-1 PIR

5756 3000K Warm White
5749 4500K Day White
5750 6000K White


EAN Code
3800157611688
3800157608862
3800157608879

Detection Angle: 120°
Detection Distance: 2-8 Meters



EQ. Watts:	100W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	White
Luminous Flux:	1600lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	185x211x50mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




The average illuminance effective figure

0000-0001-9321-9999

[illegible]

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



30W VT-4830-1 PIR

5757 3000K Warm White

5751 4500K Day White

5752 6000K White

EAN Code

3800157611695

3800157608886

3800157608893


Detection Angle: **120°**

Detection Distance: **2-8 Meters**



EQ. Watts:	150W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	White
Luminous Flux:	2400lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	237x255x51mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




The average luminance effective figure

Phone: 949.440.8800

[illegible]

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



50W VT-4850-1 PIR

5758 3000K Warm White

5753 4500K Day White

5754 6000K White

EAN Code

3800157611701

3800157608909

3800157608916


Detection Angle: 120°

Detection Distance: **2-8 Meters**



EQ. Watts:	250W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	White
Luminous Flux:	4000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	237x255x51mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




The average illuminance effective figure

Beam Size: 117x100mm

1.0m	15.000 / 450 lx	0.400m	9.400 lx
2.0m	3.750 / 112.5 lx	0.800m	23.438 lx
3.0m	1.667 / 50 lx	1.200m	16.667 lx
4.0m	0.938 / 28.125 lx	1.600m	11.719 lx
5.0m	0.600 / 18.75 lx	2.000m	9.000 lx
6.0m	0.417 / 12.5 lx	2.400m	7.500 lx
7.0m	0.303 / 9.09 lx	2.800m	6.357 lx
8.0m	0.234 / 7.03 lx	3.200m	5.556 lx
9.0m	0.193 / 5.78 lx	3.600m	4.907 lx
10.0m	0.167 / 5.00 lx	4.000m	4.375 lx

Beam Size: 117x100mm

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



10W VT-4810 PIR

5723 3000K Warm White
5724 4500K Day White
5725 6000K White

EAN Code


3800157605724
3800157605731
3800157605748

Detection Angle: 120°
Detection Distance: 2-8 Meters



EQ. Watts:	50W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	800lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	133x178x47mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




The average illuminance effective figure

Beam Size: 147x117mm

1.0m	15.000 / 450 lx	0.400m	9.400 lx
2.0m	3.750 / 112.5 lx	0.800m	23.438 lx
3.0m	1.667 / 50 lx	1.200m	16.667 lx
4.0m	0.938 / 28.125 lx	1.600m	11.719 lx
5.0m	0.600 / 18.75 lx	2.000m	9.000 lx
6.0m	0.417 / 12.5 lx	2.400m	7.500 lx
7.0m	0.303 / 9.09 lx	2.800m	6.357 lx
8.0m	0.234 / 7.03 lx	3.200m	5.556 lx
9.0m	0.193 / 5.78 lx	3.600m	4.907 lx
10.0m	0.167 / 5.00 lx	4.000m	4.375 lx

Beam Size: 147x117mm

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



20W VT-4820 PIR

5697 3000K Warm White
5698 4500K Day White
5715 6000K White

EAN Code


3800157604338
3800157604345
3800157604949

Detection Angle: 120°
Detection Distance: 2-8 Meters



EQ. Watts:	100W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	1600lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	185x211x50mm


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



The average illuminance effective figure

0.00m	10000 lux	10000 lux	10000 lux
0.50m	40000 lux	40000 lux	40000 lux
1.00m	16000 lux	16000 lux	16000 lux
1.50m	9000 lux	9000 lux	9000 lux
2.00m	6300 lux	6300 lux	6300 lux
2.50m	5000 lux	5000 lux	5000 lux
3.00m	4400 lux	4400 lux	4400 lux
3.50m	3900 lux	3900 lux	3900 lux
4.00m	3600 lux	3600 lux	3600 lux
4.50m	3300 lux	3300 lux	3300 lux
5.00m	3000 lux	3000 lux	3000 lux
5.50m	2800 lux	2800 lux	2800 lux
6.00m	2600 lux	2600 lux	2600 lux
6.50m	2400 lux	2400 lux	2400 lux
7.00m	2200 lux	2200 lux	2200 lux
7.50m	2000 lux	2000 lux	2000 lux
8.00m	1900 lux	1900 lux	1900 lux
8.50m	1800 lux	1800 lux	1800 lux
9.00m	1700 lux	1700 lux	1700 lux
9.50m	1600 lux	1600 lux	1600 lux
10.00m	1500 lux	1500 lux	1500 lux

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



30W VT-4830 PIR

5699 3000K Warm White
5700 4500K Day White
5716 6000K White

EAN Code


3800157604352
3800157604369
3800157604956

Detection Angle: **120°**
Detection Distance: **2-8 Meters**



EQ. Watts:	150W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	2400lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	237x255x51mm


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



The average illuminance effective figure

0.00m	10000 lux	10000 lux	10000 lux
0.50m	40000 lux	40000 lux	40000 lux
1.00m	16000 lux	16000 lux	16000 lux
1.50m	9000 lux	9000 lux	9000 lux
2.00m	6300 lux	6300 lux	6300 lux
2.50m	5000 lux	5000 lux	5000 lux
3.00m	4400 lux	4400 lux	4400 lux
3.50m	3900 lux	3900 lux	3900 lux
4.00m	3600 lux	3600 lux	3600 lux
4.50m	3300 lux	3300 lux	3300 lux
5.00m	3000 lux	3000 lux	3000 lux
5.50m	2800 lux	2800 lux	2800 lux
6.00m	2600 lux	2600 lux	2600 lux
6.50m	2400 lux	2400 lux	2400 lux
7.00m	2200 lux	2200 lux	2200 lux
7.50m	2000 lux	2000 lux	2000 lux
8.00m	1900 lux	1900 lux	1900 lux
8.50m	1800 lux	1800 lux	1800 lux
9.00m	1700 lux	1700 lux	1700 lux
9.50m	1600 lux	1600 lux	1600 lux
10.00m	1500 lux	1500 lux	1500 lux

Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



50W VT-4850 PIR

5701 3000K Warm White
5702 4500K Day White
5717 6000K White

EAN Code

3800157604376
3800157604383
3800157604963

Detection Angle: **120°**
Detection Distance: **2-8 Meters**




EQ. Watts:	250W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	4000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP44
PF:	>0.9	Dimension:	237x255x51mm



A

RF
Remote Control
10W VT-4711
RGB 5894

EAN Code
3800157617512




EQ. Watts:	40W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Grey
Luminous Flux:	800lm	Body Type:	Die cast Aluminum
CRI:	> 80	IP Rating:	IP65
PF:	>0.9	Dimension:	115x87x85mm



A

Infrared
Remote Control
10W VT-4711
RGB 5895

EAN Code
3800157617529



EQ. Watts:	40W	Beam Angle:	100°
Voltage/Frequency:	AC:220-240V,50/60Hz	Color of Fixture:	Grey
Luminous Flux:	800lm	Body Type:	Die cast Aluminum
CRI:	> 80	IP Rating:	IP65
PF:	>0.95	Dimension:	115x87x85mm



RF


Remote Control

30W VT-4732

RGB 5755

EAN Code

3800157609517



EQ. Watts:	150W	Beam Angle:	120°
Voltage/Frequency:	AC: 90-240V, 50/60Hz	Color of Fixture:	Grey
Luminous Flux:	2400lm	Body Type:	Die cast Aluminum
CRI:	> 80	IP Rating:	IP65
PF:	>0.95	Dimension:	230x136x206mm



RF


Remote Control

50W VT-4752

RGB 5691

EAN Code

3800157603508



EQ. Watts:	250W	Beam Angle:	120°
Voltage/Frequency:	AC:100-240V,50/60Hz	Color of Fixture:	Grey
Luminous Flux:	4000lm	Body Type:	Die cast Aluminum
CRI:	> 80	IP Rating:	IP65
PF:	>0.95	Dimension:	230x136x206mm



Rechargeable

Portable

20W VT-4822


5692 4500K Day White
5735 6000K White

EAN Code

3800157603515
3800157606929



EQ. Watts:	80W	Beam Angle:	120°
Voltage/Frequency:	AC:85-265V,50/60Hz	Color of Fixture:	Green
Luminous Flux:	1600lm	Body Type:	Die cast Aluminum
CRI:	/	IP Rating:	IP54
PF:	>0.7	Dimension:	208 x 204 x 355mm



Wi-Fi Series

18W VT-4818


5745 6000K White

EAN Code

3800157608268



Power:	AC100-240V	Material:	ABS +Aluminum
Output:	18W	Image sensor:	1/4 " 1Megapixel CMOS
Detection Range:	0-12M	Video Compression:	H.264 /MJPEG dual video stream
Detect Angle:	180°	Max Image Resolution:	1280*720
Delay Time:	0-30S	Pixels:	1 million pixels
LED:	42PCS 0.2W	Size:	248x 162x 181mm
Luminous Flux:	600lm	Color of Fixture:	White



Wi-Fi Series

18W VT-4818

5917 6000K White



EAN Code

3800157620925




Power:	AC100-240V	Material:	ABS +Aluminum
Output:	18W	Image sensor:	1/4 " 1Megapixel CMOS
Detection Range:	0-12M	Video Compression:	H.264 /MJPEG dual video stream
Detect Angle:	180°	Max Image Resolution:	1280*720
Delay Time:	0-30S	Pixels:	1 million pixels
LED:	42PCS 0.2W	Size:	248x 162x 181mm
Luminous Flux:	600lm	Color of Fixture:	Black

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



300W VT-47300

EAN Code



5386 6000K White

3800230627438




EQ. Watts:	1200W	Beam Angle:	120°
Voltage/Frequency:	AC:90-240V,50/60Hz	Color of Fixture:	Grey
Luminous Flux:	24000lm	Body Type:	Die cast Aluminum
CRI:	> 70	IP Rating:	IP65
PF:	> 0.9	Dimension:	430 x 410 x 145mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



400W VT-47400

EAN Code



5649 6000K White

3800157601269




EQ. Watts:	1600W	Beam Angle:	120°
Voltage/Frequency:	AC:90-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	32000lm	Body Type:	Die cast Aluminum
CRI:	> 70	IP Rating:	IP65
PF:	> 0.9	Dimension:	555 x 540 x 179mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



500W VT-47500

5696 6000K White



EAN Code

3800157603812




EQ. Watts:	2000W	Beam Angle:	120°
Voltage/Frequency:	AC:100-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	40000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	555 x 540 x 179mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.



600W VT-47600

5726 4500K Day White

EAN Code

3800157605854



EQ. Watts:	3000W	Beam Angle:	120°
Voltage/Frequency:	AC:100-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	48000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	540x555x625mm



1000W VT-491000

EAN Code

5915 4500K Day White

3800157619752

5916 6000K White

3800157619769




120⁺⁺
LM/W
HIGH LUMENS




EQ. Watts:	8000W	Beam Angle:	100°
Voltage/Frequency:	AC: 100-240V	Color of Fixture:	Black
Luminous Flux:	120000lm	Body Type:	Die cast Aluminum
CRI:	>70	IP Rating:	IP65
PF:	>0.9	Dimension:	748 x 762 x 154mm


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




The Average Illuminance Effective Figure



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.





Tripod Stand for Flood Lights (Yellow)

Model No	VT-778
SKU Code	9104
EAN Code	3800230626202



Tripod Stand for Flood Lights (Black)

Model No	VT-778
SKU Code	9546
EAN Code	3800157604925

Waterproof Box Terminal Block



RESISTANT

IP65
RATED

Wire range:0.5-2.5mm² Inside Terminal Block

Model No:	VT-7224
SKU Code:	3578
EAN Code:	3800157605335
Voltage:	250V Max
Material:	Polypropylene (PP)
Size:	123x46x33mm



Model No	VT-792
SKU Code	3621
EAN Code	3800157607735

Wire range:4-6.5mm



RESISTANT

IP65
RATED

Wire range:0.5-2.5mm² Inside Terminal Block

Model No:	VT-7224
SKU Code:	5897
EAN Code:	3800157619202
Voltage:	250V Max
Material:	Polypropylene (PP)
Size:	123x46x33mm



Model No	VT-792
SKU Code	5896
EAN Code	3800157619196

Wire range:4-6.5mm

Billboard Stand
For Flood Lights

Model No	VT-794
SKU Code	3623
EAN Code	3800157607810

85cm Suitable For:
10w - 20w - 30w - 50w



Model No	VT-793
SKU Code	3622
EAN Code	3800157607803

87cm Suitable For:
70w - 100w - 120w - 150w - 200w





LED Bulbs

An extensive collection of LED Bulbs which have been retrofitted to suit most standard Lighting Fixtures, with a wide range of wattage from 2W to 40W

Product Features

- Lasts 20 times longer than Standard Bulbs
- Broad Range of holders like E27, E14, B22, B15, G24 and R7S
- Uses 80% less energy than Standard Bulbs
- Glass & Thermoplastic Body options available
- Excellent Heat Radiation Efficiency
- Customized exterior for stronger body
- High Power LED Chips
- Wide beam angle up to 300°
- Non – Flickering
- Dimmable & Non Dimmable options

Applications

Widely used in residential lighting. LED Bulbs are the best replacement for conventional incandescent or fluorescent bulbs.





Curve Filament - A60 Amber Cover

3W VT-2063

EAN Code


7219 2200K Warm White

3800157617277

A+



EQ. Watts:	65W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	800lm	Base:	E27
Commercial Type:	G95	Body Type:	Glass
LED Type:	Filament	Dimension:	95mm x 140mm
CRI:	>80		



Curve Filament - ST64 Amber Cover


5W VT-2066

EAN Code

7220 2200K Warm White

3800157617284

A+



EQ. Watts:	55W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	600lm	Base:	E27
Commercial Type:	G125	Body Type:	Glass
LED Type:	Filament	Dimension:	125mm x 165mm
CRI:	>80		



Curve Filament - ST64 Amber Cover


5W VT-2065

EAN Code

7218 2200K Warm White

3800157617260

A+



EQ. Watts:	65W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	800lm	Base:	E27
Commercial Type:	G125	Body Type:	Glass
LED Type:	Filament	Dimension:	125mm x 200mm
CRI:	>80		



Curve Filament - G95 Amber Cover


5W VT-2075

EAN Code

7217 2200K Warm White

3800157617253

A+



EQ. Watts:	30W	PF:	>0.5
Voltage/Frequency:	AC: 220-240v, 50Hz	Beam Angle:	300°
Luminous Flux:	300lm	Base:	E27
Commercial Type:	G95	Body Type:	Glass
LED Type:	Curve Filament	Dimension:	95 x 138 mm
CRI:	>80		

Old fashioned
in **New Style**



Curve Filament - G125 Amber Cover

5W VT-2085

EAN Code

7216 2200K Warm White

3800157610643

A+



EQ. Watts:	30W	PF:	>0.5
Voltage/Frequency:	AC: 220-240v, 50Hz	Beam Angle:	300°
Luminous Flux:	300lm	Base:	E27
Commercial Type:	G125	Body Type:	Glass
LED Type:	Curve Filament	Dimension:	125 x 175mm
CRI:	>80		



8 Filament - G80 Amber Cover

4W VT-2004

EAN Code


7148 2200K Warm White

3800157610636

A++



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E27
Commercial Type:	G80	Body Type:	Glass
LED Type:	Filament	Dimension:	80mm x 140mm
CRI:	>80		



S-Shape Filament - G95 Amber Cover


4W VT-2024

EAN Code


7146 2200K Warm White

3800157610612

A++



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E27
Commercial Type:	G95	Body Type:	Glass
LED Type:	Filament	Dimension:	95mm x 140mm
CRI:	>80		



Long Filament - G95 Amber Cover

7W VT-2027

EAN Code

7147 2200K Warm White

3800157610629

A+



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	700lm	Base:	E27
Commercial Type:	G95	Body Type:	Glass
LED Type:	Filament	Dimension:	95mm x 140mm
CRI:	>80		




16 Filament - G80 Amber Cover

8W VT-2019


EAN Code

7145 2200K Warm White

3800157610605



EQ. Watts:	65W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	800lm	Base:	E27
Commercial Type:	G95	Body Type:	Glass
LED Type:	Filament	Dimension:	95mm x 140mm
CRI:	>80		




Long Filament - G125 Amber Cover

4W VT-1956

EAN Code

4473 2200K Warm White

3800157609074




EQ. Watts:	55W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	600lm	Base:	E27
Commercial Type:	G125	Body Type:	Glass
LED Type:	Filament	Dimension:	125mm x 165mm
CRI:	>80		



T-30-Clear Glass

2W VT-2042
7251 2700k Warm White

EAN Code
3800157620826




EQ. Watts:	20W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	200lm	Base:	E27
Commercial Type:	T30	Body Type:	Glass
LED Type:	Filament	Dimension:	30mm x 136mm
CRI:	>80		



T-30-Amber Cover

2W VT-2052
7252 2700k Warm White

EAN Code
3800157620833



EQ. Watts:	20W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	200lm	Base:	E27
Commercial Type:	T30	Body Type:	Glass
LED Type:	Filament	Dimension:	30mm x 136mm
CRI:	>80		




T-30-300 Amber Cover

5W VT-2005

EAN Code

7142 2200K Warm White

3800157610575



EQ. Watts:	45W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	500lm	Base:	E27
Commercial Type:	T30-300	Body Type:	Glass
LED Type:	Filament	Dimension:	30mm x 300mm
CRI:	>80		




T-30-185 Amber Cover

6W VT-2006

EAN Code

7143 2200K Warm White

3800157610582



EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	600lm	Base:	E27
Commercial Type:	T30-185	Body Type:	Glass
LED Type:	Filament	Dimension:	30mm x 185mm
CRI:	>80		




T-30-300 Amber Cover

8W VT-2008


EAN Code

7144 2200K Warm White

3800157610599



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	700lm	Base:	E27
Commercial Type:	T30-300	Body Type:	Glass
LED Type:	Filament	Dimension:	30mm x 300mm
CRI:	>80		




Candle Filament - E14 Amber Cover

4W VT-1955


EAN Code

7113 2200K Warm White

3800157609883



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	350lm	Base:	E14
Commercial Type:	Candle	Body Type:	Glass
LED Type:	Filament	Dimension:	37 x 100mm
CRI:	>80		




Candle Filament - E14 Amber Cover

4W VT-1948


EAN Code

7115 2200K Warm White

3800157609906



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	350lm	Base:	E14
Commercial Type:	Candle	Body Type:	Glass
LED Type:	Filament	Dimension:	37 x 100mm
CRI:	>80		



Candle Flame Filament - E14 Amber Cover

4W VT-1949

EAN Code

7114 2200K Warm White

3800157609890



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	350lm	Base:	E14
Commercial Type:	Candle Flame	Body Type:	Glass
LED Type:	Filament	Dimension:	37 x 121mm
CRI:	>80		



Candle Filament - E14 Amber Cover

4W VT-1947

EAN Code

7116 2200K Warm White

3800157609913



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	350lm	Base:	E14
Commercial Type:	Candle Flame	Body Type:	Glass
LED Type:	Filament	Dimension:	37 x 121mm
CRI:	>80		



P45 Filament - E14 Amber Cover

4W VT-1953

EAN Code

4499 2200K Warm White

3800157609746



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	350lm	Base:	E14
Commercial Type:	P45	Body Type:	Glass
LED Type:	Filament	Dimension:	45 x 77mm
CRI:	>80		



G45 Filament - E27 Amber Cover

4W VT-1957

EAN Code

7100 2200K Warm White

3800157609753



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	350lm	Base:	E27
Commercial Type:	G45	Body Type:	Glass
LED Type:	Filament	Dimension:	45 x 75mm
CRI:	>80		



A60 - E27 Amber Cover

4W VT-1954

EAN Code

4498 2200K Warm White

3800157609739



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	350lm	Base:	E27
Commercial Type:	A60	Body Type:	Glass
LED Type:	Filament	Dimension:	60 x 107mm
CRI:	>80		



A67 - E27 Amber Cover

8W VT-1958

EAN Code

4472 2200K Warm White

3800157609067



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	720lm	Base:	E27
Commercial Type:	A67	Body Type:	Glass
LED Type:	Filament	Dimension:	67 x 123mm
CRI:	>80		



A67 - E27 Amber Cover

10W VT-2028

EAN Code

7157 2200K Warm White

3800157612227



EQ. Watts:	65W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HZ	Beam Angle:	300°
Luminous Flux:	900lm	Base:	E27
Commercial Type:	A67	Body Type:	Glass
LED Type:	Filament	Dimension:	67mm x 123mm
CRI:	>80		



G95 - E27 Amber Cover

6W VT-2026

EAN Code

7156 2200K Warm White

3800157612210



EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50HZ	Beam Angle:	300°
Luminous Flux:	500lm	Base:	E27
Commercial Type:	G95	Body Type:	Glass
LED Type:	Filament	Dimension:	95mm x 135mm
CRI:	>80		



Dimmable G125 - E27 Amber Cover

8W VT-2018D


EAN Code

7155 2200K Warm White

3800157612203



EQ. Watts:	60W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V, 50HzV	PF:	>0.5
Luminous Flux:	700lm	Beam Angle:	300°
Commercial Type:	G125	Base:	E27
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	125mm x 177mm




Dimmable ST64 - E27 Amber Cover

4W VT-1964D


EAN Code

4368 2200K Warm White

3800157602945



EQ. Watts:	30W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V, 50Hz	PF:	>0.5
Luminous Flux:	300lm	Beam Angle:	300°
Commercial Type:	ST64	Base:	E27
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	64mm x 139mm




ST64 - E27 Amber Cover

4W VT-1964


EAN Code

4361 2200K Warm White

3800157602747



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC:220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	350lm	Base:	E27
Commercial Type:	ST64	Body Type:	Glass
LED Type:	Filament	Dimension:	64mm x 139mm
CRI:	>80		



ST64 - E27 Amber Cover

6W VT-1966


EAN Code

4362 2200K Warm White

3800157602754



EQ. Watts:	45W	PF:	>0.5
Voltage/Frequency:	AC:220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	500lm	Base:	E27
Commercial Type:	ST64	Body Type:	Glass
LED Type:	Filament	Dimension:	64mm x 139mm
CRI:	>80		



ST64 - E27 Amber Cover

8W VT-1968

EAN Code

4421 2200K Warm White

3800157606356



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC:220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	700lm	Base:	E27
Commercial Type:	ST64	Body Type:	Glass
LED Type:	Filament	Dimension:	64mm x 139mm
CRI:	>80		



Candle - E14 White Cover

4W VT-1924

EAN Code

7101 2700k Warm White

3800157609760


7102 4000K Day White

3800157609777

7103 6400k White

3800157609784

A++



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	350lm	Base:	E14
Commercial Type:	Candle	Body Type:	Glass
LED Type:	Filament	Dimension:	37mm x 100mm
CRI:	>80		



Candle Flame - E14 White Cover

4W VT-1927

EAN Code

7104 2700k Warm White

3800157609791

7105 4000K Day White

3800157609807

7106 6400k White

3800157609814

A++



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	Candle	Body Type:	Glass
LED Type:	Filament	Dimension:	37mm x 121mm
CRI:	>80		



A60 - E27 White Cover

4W VT-1939

EAN Code

4489 2700k Warm White

3800157609647

4490 4000K Day White

3800157609654

4491 6400k White

3800157609661

A++



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	350lm	Base:	E27
Commercial Type:	A60	Body Type:	Glass
LED Type:	Filament	Dimension:	60mm x 107mm
CRI:	>80		



Candle - E14 Frost Cover


4W VT-1936

EAN Code

4474 2700k Warm White
4475 4000K Day White
4476 6400k White

3800157609081
3800157609098
3800157609104

A++



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	Candle	Body Type:	Glass
LED Type:	Filament	Dimension:	37mm x 100mm
CRI:	>80		



Candle - E14 Frost Cover


4W VT-1928

EAN Code

7107 2700k Warm White
7108 4000K Day White
7109 6400k White

3800157609821
3800157609838
3800157609845

A++



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	Candle	Body Type:	Glass
LED Type:	Filament	Dimension:	37mm x 100mm
CRI:	>80		



Candle Flame - E14 Frost Cover

4W VT-1937

EAN Code


4477 2700k Warm White
4478 4000K Day White
4479 6400k White

3800157609111
3800157609128
3800157609135

A++



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	Candle Flame	Body Type:	Glass
LED Type:	Filament	Dimension:	37mm x 121mm
CRI:	>80		



Dimmable Candle Flame - E14 Frost Cover

4W VT-2056D EAN Code
7177 2700k Warm White 3800157615532



EQ. Watts:	35W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V,50HZ	PF:	>0.5
Luminous Flux:	350lm	Beam Angle:	300°
Commercial Type:	Candle Flame	Base:	E14
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	35mm x 121mm



Dimmable Candle Flame - E14 Frost Cover

4W VT-1923 EAN Code
7110 2700k Warm White 3800157609852
7111 4000K Day White 3800157609869
7112 6400k White 3800157609876




EQ. Watts:	40W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V,50HzV	PF:	>0.5
Luminous Flux:	400lm	Beam Angle:	300°
Commercial Type:	Candle Flame	Base:	E14
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	37mm x 121mm



Dimmable Candle - E14 Frost Cover

4W VT-1937 EAN Code
7176 2700k Warm White 3800157615525



EQ. Watts:	35W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V,50HZ	PF:	>0.5
Luminous Flux:	350lm	Beam Angle:	300°
Commercial Type:	Candle	Base:	E14
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	35mm x 100mm



P45 - E14 Frost Cover

4W VT-1835

EAN Code

4492 2700k Warm White

3800157609678

4493 4000k Day White

3800157609685

4494 6400k White

3800157609692



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	P45	Body Type:	Glass
LED Type:	Filament	Dimension:	45mm x 77mm
CRI:	>80		



G45 - E27 Frost Cover

4W VT-1974

EAN Code

4495 2700k Warm White


3800157609708

4496 4000K Day White

3800157609715

4497 6400k White

3800157609722



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E27
Commercial Type:	G45	Body Type:	Glass
LED Type:	Filament	Dimension:	45mm x 75mm
CRI:	>80		



A60 - E27 Frost Cover

4W VT-1934

EAN Code

4486 2700k Warm White

3800157609616

4487 4000K Day White

3800157609623

4488 6400k White

3800157609630



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E27
Commercial Type:	A60	Body Type:	Glass
LED Type:	Filament	Dimension:	60mm x 107mm
CRI:	>80		



A60 - E27 Frost Cover

6W VT-1835

EAN Code

4480 2700k Warm White
4481 4000K Day White
4482 6400k White

3800157609142
3800157609159
3800157609166



EQ. Watts:	55W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	660lm	Base:	E27
Commercial Type:	A60	Body Type:	Glass
LED Type:	Filament	Dimension:	60mm x 107mm
CRI:	>80		



A67 - E27 Frost Cover

8W VT-1938

EAN Code

4483 2700k Warm White
4484 4000K Day White
4485 6400k White

3800157609586
3800157609593
3800157609609



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	800lm	Base:	E27
Commercial Type:	A67	Body Type:	Glass
LED Type:	Filament	Dimension:	67mm x 123mm
CRI:	>80		



A60 - E27 Frost Cover

10W VT-2023

EAN Code

7152 2700k Warm White
7153 4000K Day White
7154 6400k White

3800157612173
3800157612180
3800157612197



EQ. Watts:	75W	PF	>0.5
Voltage/Frequency:	AC: 220-240V,50HZ	Beam Angle:	300°
Luminous Flux:	1055lm	Base:	E27
Commercial Type:	A67	Body Type:	Glass
LED Type:	Filament	Dimension:	67mm x 123mm
CRI:	>80		



A60 - E27 Frost Cover

5W VT-2045

EAN Code

7178 2700k Warm White
7179 4000K Day White
7180 6400k White

3800157615549
3800157615556
3800157615563



EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	600lm	Base:	E27
Commercial Type:	A60	Body Type:	Glass
LED Type:	Filament	Dimension:	60mm x 107mm
CRI:	>80		



A60 - E27 Frost Cover

7W VT-2047

EAN Code

7181 2700k Warm White
7182 4000K Day White
7183 6400k White

3800157615570
3800157615587
3800157615594



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	840lm	Base:	E27
Commercial Type:	A60	Body Type:	Glass
LED Type:	Filament	Dimension:	60mm x 107mm
CRI:	>80		



A60 - E27 Frost Cover

9W VT-2049

EAN Code

7184 2700k Warm White
7185 4000K Day White
7186 6400k White

3800157615600
3800157615617
3800157615624



EQ. Watts:	80W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50HzV	Beam Angle:	300°
Luminous Flux:	1100lm	Base:	E27
Commercial Type:	A67	Body Type:	Glass
LED Type:	Filament	Dimension:	67mm x 123mm
CRI:	>80		



G125 - E27 Frost Cover

7W VT-2067

7189 2700k Warm White
7190 6400k White

EAN Code
3800157615655
3800157615662



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	840lm	Base:	E27
Commercial Type:	G125	Body Type:	Glass
LED Type:	Filament	Dimension:	125 x 177mm
CRI:	>80		



G125 - E27 Frost Cover

7W VT-2067D

7191 2700k Warm White

EAN Code
3800157615679



EQ. Watts:	55W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	750lm	Base:	E27
Commercial Type:	G125	Body Type:	Glass
LED Type:	Filament	Dimension:	125 x 177mm
CRI:	>80		




G95 - E27 Frost Cover

7W VT-2057

7187 2700k Warm White
7188 6400k White

EAN Code
3800157615631
3800157615648



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	840lm	Base:	E27
Commercial Type:	G95	Body Type:	Glass
LED Type:	Filament	Dimension:	95 x 135mm
CRI:	>80		



A60 - E27 Clear Glass

4W VT-1885

EAN Code

4259 2700K Warm White

3800230627179



EQ. Watts:	40W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E27
Commercial Type:	A60	Body Type:	Glass
LED Type:	Filament	Dimension:	60mm x 107mm
CRI:	> 80		



Dimmable A60 - E27 Clear Glass

4W VT-1885D

EAN Code

4364 2200K Warm White

3800157602907



EQ. Watts:	30W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V, 50Hz	PF:	> 0.5
Luminous Flux:	320lm	Beam Angle:	300°
Commercial Type:	A60	Base:	E27
LED Type:	Filament	Body Type:	Glass
CRI:	> 80	Dimension:	60mm x 107mm






A60 - B22 Clear Glass

5W VT-2035

EAN Code

7170 2700K Warm White

3800157615464



EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	600lm	Base:	B22
Commercial Type:	A60	Body Type:	Plastic
LED Type:	Filament	Dimension:	60 x 110mm
CRI:	>80		



A60 - E27 Clear Glass

6W VT-1887


EAN Code

4272 2700K Warm White

3800230627667

4303 4000K Day White

3800157600064



EQ. Watts:	55W	PF:	> 0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	550lm	Base:	E27
Commercial Type:	A60	Body Type:	Glass
LED Type:	Filament	Dimension:	60mm x 107mm
CRI:	> 80		




A60 - E27 Clear Glass

8W VT-1988

EAN Code

4363 2700K Warm White

3800157602891



EQ. Watts:	75W	PF:	>0.5
Voltage/Frequency:	AC:220-240V, 50/60Hz	Beam Angle:	300°
Luminous Flux:	1000lm	Base:	E27
Commercial Type:	A60	Body Type:	Glass
LED Type:	Filament	Dimension:	60mm x 105mm
CRI:	>80		



A67 - E27 Clear Glass

8W VT-1989

EAN Code

4406 2700K Warm White

3800157605342



EQ. Watts:	75W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	1000lm	Base:	E27
Commercial Type:	A67	Body Type:	Glass
LED Type:	Filament	Dimension:	67mm x 123mm
CRI:	>80		



A67 - E27 Clear Glass

8W VT-1978

EAN Code

4407 2700K Warm White

4408 4000K Day White

4409 6400KWhite

3800157606165

3800157606172

3800157606189



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	800lm	Base:	E27
Commercial Type:	A67	Body Type:	Glass
LED Type:	Filament	Dimension:	67mm x 123mm
CRI:	>80		



A67 - E27 Clear Glass

10W VT-1981

EAN Code

4410 2700K Warm White

4411 4000K Day White

4412 6400KWhite

3800157606196

3800157606202

3800157606219



EQ. Watts:	75W	PF	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	1055lm	Base:	E27
Commercial Type:	A67	Body Type:	Glass
LED Type:	Filament	Dimension:	67mm x 123mm
CRI:	>80		



ST26 - E14 Clear Glass

2W VT-1952

EAN Code

4444 3000K Warm White

3800157607858

4445 4000K Day White

3800157607865

4446 6400K White

3800157607872



EQ. Watts:	25W	PF:	> 0.4
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	180lm	Base:	E14
Commercial Type:	ST 26	Body Type:	Glass
LED Type:	Filament	Dimension:	26 x 58 mm
CRI:	>80		




Candle - B22 Clear Glass

4W VT-2064

EAN Code

7225 2700K Warm White

3800157617550



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50HZ	Beam Angle:	300°
Luminous Flux:	400lm	Base:	B22
Commercial Type:	Candle	Body Type:	Glass
LED Type:	Filament	Dimension:	35 x 100mm
CRI:	>80		




G45 - B22 Clear Glass

4W VT-2074

EAN Code

7226 2700K Warm White

3800157617567



EQ. Watts:	40W	PF	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	400lm	Base:	B22
Commercial Type:	G45	Body Type:	Glass
LED Type:	Filament	Dimension:	45 x 75mm
CRI:	> 80		



Candle - E14 Clear Glass

4W VT-1986

EAN Code

4301 2700K Warm White

3800230629951


4413 4000K Day White

3800157606226

4414 6400K White

3800157606233

A++



EQ. Watts:	40W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	Candle	Body Type:	Glass
LED Type:	Filament	Dimension:	37mm x 100mm
CRI:	> 80		



Candle - E14 Clear Glass


4W VT-1985

EAN Code

4307 2700K Warm White

3800157600347

A++



EQ. Watts:	40W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	Candle	Body Type:	Glass
LED Type:	Filament	Dimension:	37mm x 100mm
CRI:	> 80		



Candle Flame - E14 Clear Glass

4W VT-1997

EAN Code

4302 2700K Warm White

3800230629968

4429 4000K Day White

3800157606431

4430 6400K White

3800157606448

A++



EQ. Watts:	40W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	Candle Flame	Body Type:	Glass
LED Type:	Filament	Dimension:	37mm x 121mm
CRI:	> 80		



Candle Flame - E14 Clear Glass

4W VT-1985

EAN Code

4308 2700K Warm White
4431 4000K Day White
4432 6400K White

3800157600354
3800157606455
3800157606462

A++



EQ. Watts:	40W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	Candle Flame	Body Type:	Glass
LED Type:	Filament	Dimension:	37mm x 121mm
CRI:	> 80		



Dimmable Candle - E14 Clear Glass


4W VT-1986D

EAN Code

4365 2700K Warm White

3800157602914

A++



EQ. Watts:	30W	Dimmable:	Yes
Voltage/Frequency:	AC:220-240V, 50Hz	PF:	>0.5
Luminous Flux:	320lm	Beam Angle:	300°
Commercial Type:	Candle	Base:	E14
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	37mm x 100mm



Dimmable Candle Flame - E14 Clear Glass

4W VT-1997D

EAN Code

4366 2700K Warm White

3800157602921

A++




EQ. Watts:	30W	Dimmable:	Yes
Voltage/Frequency:	AC:220-240V, 50Hz	PF	>0.5
Luminous Flux:	320lm	Beam Angle:	300°
Commercial Type:	Candle Flame	Base:	E14
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	37mm x 121mm



Dimmable Candle - E14 Clear Glass

4W VT-1985D
4367 2700K Warm White

EAN Code
3800157602938



EQ. Watts:	30W	Dimmable:	Yes
Voltage/Frequency:	AC:220-240V, 50Hz	PF:	>0.5
Luminous Flux:	320lm	Beam Angle:	300°
Commercial Type:	Candle	Base:	E14
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	37mm x 100mm



Dimmable Candle Flame - E14 Clear Glass

4W VT-1995D
4388 2700K Warm White

EAN Code
3800157603973



EQ. Watts:	30W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V, 50Hz	PF:	> 0.5
Luminous Flux:	320lm	Beam Angle:	300°
Commercial Type:	Candle Flame	Base:	E14
LED Type:	Filament	Body Type:	Glass
CRI:	> 80	Dimension:	37mm x 121mm



G45 - E27 Clear Glass

4W VT-1980
4306 2700K Warm White
4427 4000K Day White
4428 6400K White

EAN Code
3800157600330
3800157606417
3800157606424



EQ. Watts:	40W	PF	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E27
Commercial Type:	G45	Body Type:	Glass
LED Type:	Filament	Dimension:	45mm x 75mm
CRI:	> 80		




Dimmable G45 - E27 Clear Glass

4W VT-1980D

EAN Code

4395 2700K Warm White

3800157604796



EQ. Watts:	30W	Dimmable:	Yes
Voltage/Frequency:	AC:220-240V,50Hz	PF:	>0.5
Luminous Flux:	320lm	Beam Angle:	300°
Commercial Type:	G45	Base:	E27
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	45mm x 75mm



P45 - E14 Clear Glass

4W VT-1996

EAN Code

4300 2700K Warm White

3800230629944

4425 4000K Day White

3800157606394

4426 6400K White

3800157606400



EQ. Watts:	40W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	P45	Body Type:	Glass
LED Type:	Filament	Dimension:	45mm x 77mm
CRI:	> 80		




Dimmable P45- E14 Clear Glass

4W VT-1996D

EAN Code

4394 2700K Warm White

3800157604314



EQ. Watts:	30W	Dimmable:	Yes
Voltage/Frequency:	AC:220-240V,50Hz	PF	>0.5
Luminous Flux:	320lm	Beam Angle:	300°
Commercial Type:	P45	Base:	E14
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	45mm x 77mm




Dimmable G125 - E27 Clear Glass

4W VT-1994D

EAN Code

4399 2700K Warm White

3800157605021



EQ. Watts:	30W	Dimmable:	Yes
Voltage/Frequency:	AC:220-240V,50Hz	PF:	>0.5
Luminous Flux:	320lm	Beam Angle:	300°
Commercial Type:	G125	Base:	E27
LED Type:	Filament	Body Type:	Glass
CRI:	>80	Dimension:	125mm x 165mm



G125 - E27 Clear Glass

6W VT-1983

EAN Code

4304 2700K Warm White

3800157600316



EQ. Watts:	60W	PF:	> 0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	550lm	Base:	E27
Commercial Type:	G125	Body Type:	Glass
LED Type:	Filament	Dimension:	125mm x 165mm
CRI:	> 80		



G95- E27 Clear Glass

6W VT-1993

EAN Code

4305 2700K Warm White

3800157600323



EQ. Watts:	60W	PF	> 0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	550lm	Base:	E27
Commercial Type:	G95	Body Type:	Glass
LED Type:	Filament	Dimension:	95mm x 135mm
CRI:	> 80		




G125 - E27 Clear Glass

10W VT-1979

EAN Code

4422 2700K Warm White
4423 4000K Day White
4424 6400KWhite

3800157606363
3800157606370
3800157606387



EQ. Watts:	75W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	300°
Luminous Flux:	1055lm	Base:	E27
Commercial Type:	G125	Body Type:	Glass
LED Type:	Filament	Dimension:	125mm x 165mm
CRI:	>80		






R7S Bulb

7W VT-1917

EAN Code

- 7123 3000k Warm White
- 7124 4000K Day White
- 7125 6400k White

- 3800157610032
- 3800157610049
- 3800157610056



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	360°
Luminous Flux:	470lm	Base:	R7S
Commercial Type:	R7S	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	25mm x 118mm
CRI:	>80		




R7S Bulb

10W VT-1990


EAN Code

- 4369 3000K Warm White
- 4389 4000K Day White
- 4390 6400K White

- 3800157602952
- 3800157604130
- 3800157604147



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC:220-240V, 50Hz	Beam Angle:	360°
Luminous Flux:	1000lm	Base:	R7S
Commercial Type:	R7S	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	25mm x 118mm
CRI:	>80		




Under these 4 modes you can choose the Brighter / dimmer key on the controller to make the speed faster/Slower.

RGB Bulb

10W VT-2022

EAN Code

7121 RGB + 3000k Warm White 3800157609975
 7150 RGB + 4000K Day White 3800157610711
 7151 RGB + 6400k White 3800157610728



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50HzV	Beam Angle:	200°
Luminous Flux:	470lm	Base:	E27
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 110mm
CRI:	>80		

A60 With Sensor Light

Our smart sensor bulbs are built in with photocells with transmits Signal to light source as per lumen conditions smartly and saves power by going onto Light mode, enabling you to save power and reduce consumption of power when not required.



9W VT-2016

4459 3000K Warm White
4460 4000K Day White
4461 6400KWhite

EAN Code

3800157608237
 3800157608244
 3800157608251



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	806lm	Base:	E27
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 112 mm
CRI:	>80		

A60 3-Step Dimming

Smart Dimming Technology Without A Dimmer!

At the click of button, change the lighting Power from 100% to 50% and if need to Reduce more click again to go to 15%.




9W VT-2011

4447 3000K Warm White
4448 4000K Day White
4449 6400KWhite

EAN Code

3800157607988
 3800157607995
 3800157608008



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	806lm	Base:	E27
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 112 mm
CRI:	>80		

DC24V

Ideal Use for marine, solar/wind systems, fishing, motor home/RV, buses, vehicles systems, etc.



9W VT-2059

7224 6400k White

EAN Code

3800157617543



EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	806lm-At 100% ON	Base:	E27
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 112 mm
CRI:	>80		



A60 - E27 Bulb

9W VT-1900

7240 2700k Warm White
7241 4000K Day White
7242 6400k White

EAN Code

3800157620130
3800157620147
3800157620154

A+

EQ. Watts:	60W	PF:	> 0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	806lm	Base:	E27
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 112mm
CRI:	>80		



A60 - B22 Bulb

9W VT-2069

7246 2700k Warm White

EAN Code

3800157620192

A+

EQ. Watts:	60W	PF:	> 0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	806lm	Base:	B22
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 112mm
CRI:	>80		



A60 - E27 Bulb

7W VT-2007

4376 3000K Warm White
4377 4000K Day White
4378 6400K White

EAN Code

3800157603850
3800157603867
3800157603874



EQ. Watts:	45W	PF:	>0.5
Voltage/Frequency:	AC:220-240V, 50Hz	Beam Angle:	200°
Luminous Flux:	470lm	Base:	E27
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 108mm
CRI:	>80		



A60 - E27 Bulb

10W VT-1853

4209 3000K Warm White
4226 4000K Day White
4227 6400K White

EAN Code

3800230623591
3800230626271
3800230626288



EQ. Watts:	60W	PF:	> 0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	806lm	Base:	E27
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 112mm
CRI:	> 80		



A60 - E27 Bulb

12W VT-1864

4228 3000K Warm White

4229 4000K Day White

4230 6400KWhite

EAN Code

3800230626295

3800230626301

3800230626318

A+



EQ. Watts:	75W	PF	> 0.7
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	1055lm	Base:	E27
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 118mm
CRI:	> 80		



Dimmabl A60 - E27 Bulb

12W VT-1864D

4275 3000K Warm White

EAN Code

3800230627872

A+



EQ. Watts:	75W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V,50Hz	PF	> 0.7
Luminous Flux:	1055lm	Beam Angle:	200°
Commercial Type:	A60	Base:	E27
LED Type:	SMD	Body Type:	Thermal Plastic
CRI:	> 80	Dimension:	60mm x 118mm



A65 - E27 Bulb

15W VT-2015

4453 3000K Warm White
4454 4000K Day White
4455 6400K White

EAN Code

3800157608091
3800157608107
3800157608114



EQ. Watts:	100W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	1500lm	Base:	E27
Commercial Type:	A65	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	65mm x 130mm
CRI:	>80		



A65 - E27 Bulb

17W VT-2017

4456 3000K Warm White
4457 4000K Day White
4458 6400K White

EAN Code

3800157608121
3800157608138
3800157608145



EQ. Watts:	125W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	1800lm	Base:	E27
Commercial Type:	A65	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	65mm x 130mm
CRI:	>80		






A60 - B22 Bulb

7W VT-1828

4175 3000K Warm White
4197 4000K Day White
4176 6400K White

EAN Code

3800230620859
3800230624437
3800230620866



EQ. Watts:	45W	PF:	> 0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	270°
Luminous Flux:	470lm	Base:	B22
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 108mm
CRI:	> 80		




A60 - B22 Bulb

10W VT-1853

4442 3000K Warm White
4443 4000K Day White
4324 6400K White

EAN Code

3800157607681
3800157607698
3800157601061




EQ. Watts:	60W	PF	> 0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	806lm	Base:	B22
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 108mm
CRI:	> 80		



A60 - B22 Bulb

12W VT-1864
7221 3000K Warm White
7222 4000K Day White
7223 6400K White

EAN Code
3800157617314
3800157617321
3800157617338




EQ. Watts:	75W	PF:	> 0.7
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	1055lm	Base:	B22
Commercial Type:	A60	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	60mm x 118mm
CRI:	> 80		



A65 - B22 Bulb

15W VT-2015
7229 3000K Warm White

EAN Code
3800157619554




EQ. Watts:	100W	PF	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	1500lm	Base:	B22
Commercial Type:	A65	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	65mm x 130mm
CRI:	>80		

**G45 - B22 Bulb****3W** VT-20537232 3000K Warm White
7233 6400K White

EAN Code

3800157619776

3800157619783




EQ. Watts:	25W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	180°
Luminous Flux:	250lm	Base:	B22
Commercial Type:	G45	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	45mm x 75mm
CRI:	> 80		

**G45 - B22 Bulb****6W** VT-1973

4441 3000K Warm White

EAN Code

3800157607674




EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	180°
Luminous Flux:	470lm	Base:	B22
Commercial Type:	G45	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	45mm x 82mm
CRI:	>80		

**Candle - B22 Bulb****3W** VT-20737230 2700k Warm White
7231 6400k White

EAN Code

3800157619578

3800157619585




EQ. Watts:	25W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50HZ	Beam Angle:	200°
Luminous Flux:	250lm	Base:	B22
Commercial Type:	Candle	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	37mm x 100mm
CRI:	> 80		



Candle - B22 Bulb

6W VT-1965
4440 3000K Warm White

EAN Code
3800157607667




EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	470lm	Base:	B22
Commercial Type:	Candle	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	37mm x 102mm
CRI:	>80		



Candle - E14 Bulb

3W VT-2033
7196 3000K Warm White
7197 4000K Day White
7198 6400KWhite

EAN Code
3800157615808
3800157615815
3800157615822




EQ. Watts:	25W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	250lm	Base:	E14
Commercial Type:	Candle	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	37mm x 100mm
CRI:	> 80		



Candle -E14 Bulb

4W VT-1818
4216 3000K Warm White
4166 4000K Day White
4122 6400KWhite

EAN Code
3800230624796
3800230620675
3800230620668



EQ. Watts:	30W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	320lm	Base:	E14
Commercial Type:	Candle	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	37mm x 100mm
CRI:	> 80		



Candle - E14 Bulb


6W VT-1855

4215 3000K Warm White
4258 4000K Day White
4241 6400K White

EAN Code

3800230624789
3800230627155
3800230626790

A+



EQ. Watts:	40W	PF	> 0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	200°
Luminous Flux:	470lm	Base:	E14
Commercial Type:	Candle	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	37mm x 102mm
CRI:	> 80		



Dimmable Candle - E14 Bulb


6W VT-1854D

4213 3000K Warm White

EAN Code

3800230624765

A+



EQ. Watts:	40W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V, 50Hz	PF:	> 0.5
Luminous Flux:	470lm	Beam Angle:	200°
Commercial Type:	Candle	Base:	E14
LED Type:	SMD	Body Type:	Thermal Plastic
CRI:	> 80	Dimension:	37mm x 102mm



Candle - E27 Bulb


6W VT-1821

4342 3000K Warm White
4343 4000K Day White
4344 6400K White

EAN Code

3800157601733
3800157601740
3800157601757

A+




EQ. Watts:	40W	PF	>0.5
Voltage/Frequency:	AC:220-240V, 50Hz	Beam Angle:	200°
Luminous Flux:	470lm	Base:	E27
Commercial Type:	Candle	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	37mm x 102mm
CRI:	>80		



Candle Flame - E14 Bulb

4W VT-1818 TP
4164 3000K Warm White
4156 4000K Day White
4354 6400K White

EAN Code
3800230620743
3800230620736
3800157602457




EQ. Watts:	30W	PF	> 0.4
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	320lm	Base:	E14
Commercial Type:	Candle Flame	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	38mm x 117mm
CRI:	> 80		



Candle Flame -E14 Bulb

6W VT-1855TP
4351 3000K Warm White
4352 4000K Day White
4353 6400K White

EAN Code
3800157602426
3800157602433
3800157602440




EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	470lm	Base:	E14
Commercial Type:	Candle Flame	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	37mm x 117mm
CRI:	>80		

**ST26-E14****2W** VT-2032

7237 2700k Warm White
 7238 4000K Day White
 7239 6400k White

EAN Code

3800157620109
 3800157620116
 3800157620123




EQ. Watts:	20W	PF	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	150°
Luminous Flux:	180lm	Base:	E14
Commercial Type:	ST26	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	25mm x 59mm
CRI:	> 80		

**T37 - E14 Bulb****9W** VT-2029

7173 2700k Warm White
 7174 4000K Day White
 7175 6400k White

EAN Code

3800157615495
 3800157615501
 3800157615518




EQ. Watts:	60W	PF:	>0.5
Voltage/Frequency:	AC:220-240V, 50Hz	Beam Angle:	230°
Luminous Flux:	750lm	Base:	E14
Commercial Type:	T37	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	37mm x 115mm
CRI:	>80		

**T37 - 27 Bulb****9W** VT-2089

7256 2700k Warm White
 7257 4000K Day White
 7258 6400k White

EAN Code

3800157621915
 3800157621922
 3800157621939




EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC:220-240V, 50Hz	Beam Angle:	230°
Luminous Flux:	750lm	Base:	E27
Commercial Type:	T37	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	37mm x 115mm
CRI:	>80		

**G45 - E27 Bulb****3W** VT-2053

7202 3000K Warm White
7203 4000K Day White
7204 6400K White

EAN Code

3800157615860
3800157615877
3800157615884

A+


EQ. Watts:	25W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	180°
Luminous Flux:	250lm	Base:	E27
Commercial Type:	G45	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	45mm x 75mm
CRI:	> 80		

**G45 - E27 Bulb****4W** VT-1830

4160 3000K Warm White
4162 4000K Day White
4207 6400K White

EAN Code

3800230621047
3800230621054
3800230624611

A+


EQ. Watts:	30W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	180°
Luminous Flux:	320lm	Base:	E27
Commercial Type:	G45	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	45mm x 75mm
CRI:	> 80		

**G45 - E27 Bulb****6W** VT-1879

4247 3000K Warm White
4248 4000K Day White
4249 6400K White

EAN Code

3800230627018
3800230627025
3800230627032

A+


EQ. Watts:	40W	PF	> 0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	180°
Luminous Flux:	470lm	Base:	E27
Commercial Type:	G45	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	45mm x 75mm
CRI:	> 80		

**P45 - E14 Bulb****3W** VT-2043

7199 3000K Warm White
7200 4000K Day White
7201 6400K White

EAN Code

3800157615839
3800157615846
3800157615853

A+


EQ. Watts:	25W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	180°
Luminous Flux:	250lm	Base:	E14
Commercial Type:	P45	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	45mm x 80mm
CRI:	> 80		

**P45 - E14 Bulb****4W** VT-1819

4123 3000K Warm White
4174 4000K Day White
4124 6400K White

EAN Code

3800230620996
3800230621009
3800230621016

A+


EQ. Watts:	30W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	180°
Luminous Flux:	320lm	Base:	E14
Commercial Type:	P45	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	45mm x 80mm
CRI:	> 80		

**P45 - E14 Bulb****6W** VT-1880

4250 3000K Warm White
4251 4000K Day White
4252 6400K White

EAN Code

3800230627049
3800230627056
3800230627063

A+


EQ. Watts:	40W	PF:	> 0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	180°
Luminous Flux:	470lm	Base:	E14
Commercial Type:	P45	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	45mm x 80mm
CRI:	> 80		



R39 - E14 Bulb

3W VT-1861
4219 3000K Warm White
4220 4000K Day White
4242 6400K White

EAN Code
3800230625472
3800230625489
3800230626806




EQ. Watts:	25W	PF:	> 0.4
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	120°
Luminous Flux:	210lm	Base:	E14
Commercial Type:	R39	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	39mm x 67mm
CRI:	> 80		



R50 - E14 Bulb

6W VT-1876
4243 3000K Warm White
4138 4000K Day White
4246 6400K White

EAN Code
3800230626813
3800230620897
3800230626967



EQ. Watts:	40W	PF	> 0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	120°
Luminous Flux:	400lm	Base:	E14
Commercial Type:	R50	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	50mm x 86mm
CRI:	> 80		



R63 - E27 Bulb


8W VT-1862

4221 3000K Warm White
4140 4000K Day White
4244 6400K White

EAN Code

3800230625496
3800230620903
3800230626820

A+



EQ. Watts:	60W	PF:	> 0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	120°
Luminous Flux:	500lm	Base:	E27
Commercial Type:	R63	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	63mm x 100mm
CRI:	> 80		



R80 - E27 Bulb


10W VT-1894

4339 3000K Warm White
4340 4000K Day White
4341 6400K White

EAN Code

3800157601702
3800157601719
3800157601726

A+




EQ. Watts:	75W	PF	>0.5
Voltage/Frequency:	AC:220-240V, 50Hz	Beam Angle:	120°
Luminous Flux:	800lm	Base:	E27
Commercial Type:	R80	Body Type:	PlasticThermal Plastic
LED Type:	SMD	Dimension:	80mm x 114mm
CRI:	>80		



PL - E27 Bulb

6W VT-2046
7211 3000k Warm White

EAN Code 3800157617031 **A+**




EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	120°
Luminous Flux:	480lm	Base:	E27
Commercial Type:	PL	Body Type:	Plastic + Aluminum
LED Type:	SMD	Dimension:	38 x 145mm
CRI:	>80		



PL - E27 Bulb

10W VT-2050
7215 3000k Warm White

EAN Code 3800157617079 **A+**




EQ. Watts:	85W	PF	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	120°
Luminous Flux:	820lm	Base:	E27
Commercial Type:	PL	Body Type:	Plastic + Aluminum
LED Type:	SMD	Dimension:	157 x 38mm
CRI:	>80		



PL - G24 Bulb

6W VT-2046
7210 3000k Warm White
7209 4000K Day White
7208 6400KWhite

EAN Code
3800157617024
3800157617017
3800157617000 **A+**




EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	120°
Luminous Flux:	480lm	Base:	G24
Commercial Type:	PL	Body Type:	Plastic + Aluminum
LED Type:	SMD	Dimension:	38 x 145mm
CRI:	>80		



PL - G24 Bulb

10W VT-2050
7214 3000k Warm White
7213 4000K Day White
7212 6400KWhite

EAN Code
3800157617062
3800157617055
3800157617048 **A+**



EQ. Watts:	85W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	120°
Luminous Flux:	820lm	Base:	G24
Commercial Type:	PL	Body Type:	Plastic + Aluminum
LED Type:	SMD	Dimension:	38 x 157mm
CRI:	>80		




G95 - E27 Globe Bulb

10W VT-1893

4276 3000K Warm White
4277 4000K Day White
4278 6400K White

EAN Code

3800230627889
3800230627896
3800230627902



EQ. Watts:	60W	PF:	> 0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	810lm	Base:	E27
Commercial Type:	G95	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	95mm x 133mm
CRI:	> 80		




Dimmable G95 - E27 Globe Bulb

10W VT-1893D

4279 3000K Warm White

EAN Code

3800230627919



EQ. Watts:	60W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V,50Hz	PF	> 0.5
Luminous Flux:	810lm	Beam Angle:	200°
Commercial Type:	G95	Base:	E27
LED Type:	SMD	Body Type:	Thermal Plastic
CRI:	> 80	Dimension:	95mm x 133mm

**G120 - E27 Globe Bulb****13W** VT-1883

EAN Code

4253 3000K Warm White


3800230627094

4273 4000K Day White

3800230627858

4274 6400K White

3800230627865

A+


EQ. Watts:	75W	PF:	> 0.7
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	200°
Luminous Flux:	1055lm	Base:	E27
Commercial Type:	G120	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	120mm x 158mm
CRI:	> 80		

**Dimmable****Dimmable G120 - E27 Globe Bulb****13W** VT-1884D

EAN Code

4254 3000K Warm White

3800230627100

A+

EQ. Watts:	75W	Dimmable:	Yes
Voltage/Frequency:	AC: 220-240V, 50Hz	PF	> 0.7
Luminous Flux:	1055lm	Beam Angle:	200°
Commercial Type:	G120	Base:	E27
LED Type:	SMD	Body Type:	Thermal Plastic
CRI:	> 80	Dimension:	120mm x 158mm

**G120 - E27 Globe Bulb****18W** VT-1899

EAN Code

4433 3000K Warm White


3800157606806

4434 4000K Day White

3800157606813

4435 6400K White

3800157606820

A+

EQ. Watts:	115W	PF	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	200°
Luminous Flux:	1800lm	Base:	E27
Commercial Type:	G120	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	120mm x 158mm
CRI:	>80		




Corn Shaped - E27 Bulb

20W VT-2021

EAN Code

7135 3000K Warm White
7136 4000K Day White
7137 6400k White

3800157610506
3800157610513
3800157610520



EQ. Watts:	135W	PF:	>0.7
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	1800lm	Base:	E27
Commercial Type:	Corn bulb	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	80mm x 150mm
CRI:	>80		




Corn Shaped - E27 Bulb

30W VT-2031

EAN Code

7138 4000K Day White
7139 6400k White

3800157610537
3800157610544



EQ. Watts:	160W	PF	>0.9
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	2700lm	Base:	E27
Commercial Type:	Corn bulb	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	118mm x 220mm
CRI:	>80		




Corn Shaped - E27 Bulb

40W VT-2041

EAN Code

7140 4000K Day White
7141 6400k White

3800157610551
3800157610568




EQ. Watts:	200W	PF	>0.9
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	200°
Luminous Flux:	3600lm	Base:	E27
Commercial Type:	Corn bulb	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	118mm x 220mm
CRI:	>80		

UFO Ceiling Lamp- E27

15W VT-2116

7158 3000k Warm White
7159 4000k Day White
7160 6400k White

EAN Code
3800157612494
3800157612500
3800157612517




EQ. Watts:	90W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	120°
Luminous Flux:	1350lm	Base:	E27
Commercial Type:	F150	Body Type:	PC
LED Type:	SMD	Dimension:	150 x 80 mm
CRI:	>80		

UFO Ceiling Lamp- E27

24W VT-2124

7161 3000k Warm White
7162 4000k Day White
7163 6400k White

EAN Code
3800157612524
3800157612531
3800157612548




EQ. Watts:	160W	PF	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	120°
Luminous Flux:	2610lm	Base:	E27
Commercial Type:	F200	Body Type:	PC
LED Type:	SMD	Dimension:	200 x 80mm
CRI:	>80		

UFO Ceiling Lamp- E27

36W VT-2136

7164 3000k Warm White
7165 4000k Day White
7166 6400k White

EAN Code
3800157612555
3800157612562
3800157612579



EQ. Watts:	190W	PF	>0.9
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	120°
Luminous Flux:	3240lm	Base:	E27
Commercial Type:	F250	Body Type:	PC
LED Type:	SMD2835	Dimension:	250 x 80mm
CRI:	>80		



ED-90 - E27 Bulb

40W VT-1940

- 7132 3000K Warm White
- 7133 4000K Day White
- 7134 6500K White

EAN Code
3800157610285
3800157610292
3800157610308



EQ. Watts:	250W	PF:	>0.9
Voltage/Frequency:	AC:100-240V,50Hz/60Hz	Beam Angle:	265°
Luminous Flux:	3500lm	Base:	E27
Commercial Type:	ED-90	Body Type:	Aluminum+PC
LED Type:	SMD	Dimension:	90mm x 220mm
CRI:	>80		






P45 - E14 Bulb

6W VT-1880
4331 3000K Warm White

EAN Code
3800157601184



EQ. Watts:	40W	PF:	> 0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	180°
Luminous Flux:	470lm	Base:	E14
Commercial Type:	P45	Body Type:	Thermal Plastic
LED Type:	SMD	Dimension:	45mm x80mm
CRI:	> 80		



A60 - E27 Filament Bulb

6W VT-1887
4332 2700K Warm White

EAN Code
3800157601191



EQ. Watts:	60W	PF	> 0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	550lm	Base:	E27
Commercial Type:	A60	Body Type:	Glass
LED Type:	Filament	Dimension:	60mm x107mm
CRI:	> 80		



B22-E14 Converter

SKU Code 3420



B22-E27 Converter

SKU Code 3419



E40-E27 Converter

SKU Code 3417



LED Spot Lights

Introducing sustainable & energy efficient substitute for the power consuming 35W and 50W Halogen Spotlights. An extensive range of LED SPOTLIGHTS (1.2W - 8W)

Product Features

- Lasts 20 times longer than Standard Bulbs
- Uses 80% less energy than Standard Bulbs
- Excellent Heat Radiation Efficiency
- Customized exterior for stronger body
- Choice of beam angle from 38° to 300°
- Non – Flickering
- Premium Quality Power Driver
- Broad Range of holders like GU10, MR16, G9 and G4
- Wide Voltage Range from AC: 180 – 240 V , 50/60 Hz & 12 v options
- Dimmable & Non Dimmable options



Applications

Perfect choice for Hotels, Bars, Commercial & Residential Lighting and Exhibition Stands

GU 10 with Lens

7W VT-2666

EAN Code

1657 3000K Warm White
1658 4500K Day White
1659 6000K White

3800157601641
3800157601658
3800157601665

A+



EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	38°
Luminous Flux:	550lm	Base:	GU10
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	50mm x 57mm



Dimmable

Dimmable GU 10 with Lens

7W VT-2886D

EAN Code

1666 3000K Warm White
1667 4500K Day White
1668 6000K White

3800157602075
3800157602082
3800157602099

A+



EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	38°
Luminous Flux:	550lm	Base:	GU10
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	50mm x 57mm
Dimmable:	Yes		



GU 10 with Lens

7W VT-2778

EAN Code

1672 3000K Warm White
1673 4500K Day White
1674 6000K White

3800157602136
3800157602143
3800157602150

A+



EQ. Watts:	45W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	110°
Luminous Flux:	500lm	Base:	GU10
LED Type:	SMD	Body Type:	Plastic
CRI:	> 80	Dimension:	50mm x 57mm




MR 16 with Lens

7W VT-1967

1663 3000K Warm White
1664 4500K Day White
1665 6000K White

EAN Code

3800157602044
 3800157602051
 3800157602068



EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC/DC: 12V,50Hz	Beam Angle:	38°
Luminous Flux:	550lm	Base:	GU5.3
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	50mm x 50mm


GU 10 with Lens

8W VT-2889

1693 3000k Warm White
1694 4000k Day White
1695 6400k White

EAN Code

3800157608947
 3800157608954
 3800157608961



EQ. Watts:	80W	PF	> 0.5
Voltage/Frequency:	AC: 220-240V,50Hz	Beam Angle:	38°
Luminous Flux:	750lm	Base:	GU10
LED Type:	SMD	Body Type:	Plastic
CRI:	> 80	Dimension:	50mm x 55mm

First time 8W GU10 with
750 lumens

Milky Cover GU10**7W** VT-2779**1682 3000K Warm White****1683 4500K Day White****1684 6000K White**

EAN Code

3800157605359

3800157605366

3800157605373

A+

EQ. Watts:	45W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	110°
Luminous Flux:	500lm	Base:	GU10
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	50mm x 57mm

**Dimmable****Dimmable Milky Cover GU10****7W** VT-2887D**1669 3000K Warm White****1670 4500K Day White****1671 6000K White**

EAN Code

3800157602105

3800157602112

3800157602129

A+

EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	110°
Luminous Flux:	500lm	Base:	GU10
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	50mm x 57mm


Dimmable: **Yes****Milky Cover MR16****7W** VT-1977**1688 3000K Warm White****1689 4500K Day White****1690 6000K White**

EAN Code

3800157606950

3800157606967

3800157606974

A+

EQ. Watts:	50W	PF:	>0.5
Voltage/Frequency:	AC/DC: 12V,50Hz	Beam Angle:	110°
Luminous Flux:	500lm	Base:	GU5.3
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	50mm x 50mm



Milky Cover GU10


5W VT-1975

1685 3000K Warm White
1686 4500K Day White
1687 6000K White

EAN Code

3800157606240
3800157606257
3800157606264

A+



EQ. Watts:	40W	PF:	>0.4
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	110°
Luminous Flux:	320lm	Base:	GU10
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	50mm x 58mm



Milky Cover GU10


3W VT-1933

7126 3000k Warm White
7127 4500k Day White
7128 6000k White

EAN Code

3800157610148
3800157610155
3800157610162

A+



EQ. Watts:	25W	PF	>0.4
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	110°
Luminous Flux:	210lm	Base:	GU10
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	50mm x 58mm



GU10 Spotlight

2W VT-2002

7167 3000K Warm White
7168 4500K Day White
7169 6000K White

EAN Code

3800157612807
 3800157612814
 3800157612821



EQ. Watts:	15W	PF:	>0.4
Voltage/Frequency:	AC: 12V,50Hz	Beam Angle:	38°
Luminous Flux:	180lm	Base:	GU10
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	35mm x 46.5mm


MR 11 Spot light

2W VT-1992

1679 3000K Warm White
1680 4500K Day White
1681 6000K White


EAN Code

3800157605038
 3800157605045
 3800157605052



EQ. Watts:	15W	PF:	>0.4
Voltage/Frequency:	AC/DC:12V,50Hz	Beam Angle:	38°
Luminous Flux:	140lm	Base:	GU4
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	35mm x 39mm





Recessed G53



7W VT-1969

- 4437 3000K Warm White
- 4438 4500K Day White
- 4439 6000K White

EAN Code
3800157607032
3800157607049
3800157607056

EQ. Watts:	45W	PF	> 0.5
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	110°
Luminous Flux:	550lm	Base:	Recessed G53
Commercial Type:	G53	Body Type:	Thermoplastic
LED Type:	SMD	Dimension:	75 x 23.5 mm
CRI:	> 80		




G4 Spot light 1pc Pack

1.5W VT-1942

- 4463 3000K Warm White
- 4464 4500K Day White
- 4465 6000K White

EAN Code
3800157608978
3800157608985
3800157608992



EQ. Watts:	15W	PF:	>0.4
Voltage/Frequency:	AC/DC:12V	Beam Angle:	300°
Luminous Flux:	100lm	Base:	G4
LED Type:	SMD	Body Type:	Plastic
CRI:	> 80	Dimension:	16mm x 47.7mm

G9 Spot light

2.5W VT-1946

1pc Pack


EAN Code

7205 3000K Warm White 3800157616317
7206 4500K Day White 3800157616324
7207 6000K White 3800157616331

3pc Blister Pack

EAN Code

4358 3000K Warm White 3800157602716
4359 4500K Day White 3800157602723
4360 6000K White 3800157602730



A⁺

EQ. Watts:	25W	PF	>0.4
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	200lm	Base:	G9
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	16mm x 48mm


G9 Spot light

3W VT-2003

EAN Code

7243 2700k Warm White 3800157620161
7244 4000K Day White 3800157620178
7245 6400k White 3800157620185

A⁺



EQ. Watts:	30W	PF	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	300°
Luminous Flux:	300lm	Base:	G9
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	17mm x 49mm


Milky Cover-G9

3W VT-2083D

EAN Code

7253 2700k Warm White 3800157621656
7254 4000K Day White 3800157621663
7255 6400k White 3800157621670

A⁺



EQ. Watts:	30W	PF:	>0.5
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	360°
Luminous Flux:	225lm	Base:	G9
LED Type:	SMD	Body Type:	Plastic
CRI:	>80	Dimension:	18.5 x 55.5mm
Dimmable:	Yes		



Dimmable

GU10 SOCKET

■ NOT INCLUDED ■



Gypsum Fitting

Model No:	VT-762	VT-763	VT-764
SKU Code:	3648	3649	3650
Base:	GU10	GU10	GU10
Material:	Gypsum	Gypsum	Gypsum
Shape:	Square	Square	Round
Color of Fixture:	White	White	White
Dimension:	290 x 140 x 80mm	190 x 140 x 80mm	Ø140 x 140 x 40mm
Cutting Size:	215 x 120mm	120 x 120mm	Ø100mm
EAN Code:	3800157618588	3800157618595	3800157618601

GU10 SOCKET

■ NOT INCLUDED ■



Gypsum Fitting

Model No:	VT-765	VT-771	VT-772
SKU Code:	3651	3652	3653
Base:	GU10	GU10	GU10
Material:	Gypsum	Gypsum	Gypsum
Shape:	Square	Round	Square
Color of Fixture:	White	White	White
Dimension:	170 x 120 x 35mm	Ø140 x 140 x 45mm	190 x 140 x 80mm
Cutting Size:	100 x 100mm	Ø103mm	121 x 121mm
EAN Code:	3800157618618	3800157618625	3800157618632

GU10 SOCKET
■ NOT INCLUDED ■



Gypsum Fitting

Model No:	VT-773	VT-776	VT-776
SKU Code:	3654	3640	3641
Base:	GU10	GU10	GU10
Material:	Gypsum	Gypsum	Gypsum
Shape:	Round	Round	Square
Color of Fixture:	White	White	White
Dimension:	Ø130 x 70mm	Ø120 x 40mm	190 x 140 x 60mm
Cutting Size:	Ø132mm	Ø50mm	120x 50mm
EAN Code:	3800157618649	3800157616348	3800157616355




GU10 SOCKET
■ NOT INCLUDED ■



Ferrum Fitting

Model No:	VT-778	VT-778	VT-778
SKU Code:	3584	3585	3586
Base:	GU10	GU10	GU10
Material:	Ferrum	Ferrum	Ferrum
Shape:	Round	Round	Round
Color of Fixture:	White	Satin Nickel	Chrome
Dimension:	Ø80 x 30mm	Ø80 x 30mm	Ø80 x 30mm
Cutting Size:	Ø65mm	Ø65mm	Ø65mm
EAN Code:	3800157607131	3800157607148	3800157607155




GU10 SOCKET
■ NOT INCLUDED ■



Zinc Alloy Fitting

Model No:	VT-779	VT-779	VT-779
SKU Code:	3590	3591	3592
Base:	GU10	GU10	GU10
Material:	Zinc alloy	Zinc alloy	Zinc alloy
Shape:	Square	Square	Square
Color of Fixture:	White	Satin Nickel	Chrome
Dimension:	82 x 82 x22mm	82 x 82 x22mm	82 x 82 x22mm
Cutting Size:	74 x74mm	74 x74mm	74 x74mm
EAN Code:	3800157607193	3800157607209	3800157607216




GU10 SOCKET
■ NOT INCLUDED ■



Zinc Alloy Fitting

Model No:	VT-779	VT-779	VT-779
SKU Code:	3587	3588	3589
Base:	GU10	GU10	GU10
Material:	Zinc Alloy	Zinc alloy	Zinc alloy
Shape:	Round	Round	Round
Color of Fixture:	White	Satin Nickel	Chrome
Dimension:	Ø82 x 25mm	Ø82 x 25mm	Ø82 x 25mm
Cutting Size:	Ø74mm	Ø74mm	Ø74mm
EAN Code:	3800157607162	3800157607179	3800157607186




GU10 SOCKET
■ NOT INCLUDED ■



Aluminium Fitting

Model No:	VT-774	VT-774	VT-774
SKU Code:	3642	3643	3644
Base:	GU10	GU10	GU10
Material:	Aluminium	Aluminium	Aluminium
Shape:	Round	Round	Round
Color of Fixture:	White	Satin Nickel	Metallic Grey
Dimension:	Ø81 x 34mm	Ø81 x 34mm	Ø81 x 34mm
Cutting Size:	Ø73mm	Ø73mm	Ø73mm
EAN Code:	3800157617086	3800157617093	3800157617109




GU10 SOCKET
■ NOT INCLUDED ■



Aluminium Fitting

Model No:	VT-775	VT-775	VT-775
SKU Code:	3645	3646	3647
Base:	GU10	GU10	GU10
Material:	Aluminium	Aluminium	Aluminium
Shape:	Round	Round	Round
Color of Fixture:	White	Satin Nickel	Metallic Grey
Dimension:	Ø95 x 32mm	Ø95 x 32mm	Ø95 x 32mm
Cutting Size:	Ø85mm	Ø85mm	Ø85mm
EAN Code:	3800157617116	3800157617123	3800157617130



GU10 SOCKET
■ NOT INCLUDED ■



Aluminium Fitting

Model No:	VT-7227	VT-7227	VT-7227
SKU Code:	3472	3473	3474
Holder:	GU10	GU10	GU10
Material:	Ferrum	Ferrum	Ferrum
Based:	Recessed	Recessed	Recessed
Body Color:	White	Satin Nickel	Chrome
Shape:	Square	Square	Square
Dimension:	82 x 82 x22mm	82 x 82 x22mm	82 x 82 x22mm
Cutting Size:	74 x74mm	74 x74mm	74 x74mm
EAN Code:	3800157605915	3800157605922	3800157605939



GU10 SOCKET
■ NOT INCLUDED ■



Ferrum Fitting

Model No:	VT-780	VT-780
SKU Code:	3593	3594
Base:	GU10	GU10
Material:	Ferrum	Ferrum
Shape:	Round	Round
Color of Fxture:	White	Satin Nickel
Dimension:	Ø100 x 45mm	Ø100 x 45mm
Cutting Size:	Ø90mm	Ø90mm
EAN Code:	3800157607223	3800157607230



GU10 SOCKET
■ NOT INCLUDED ■



Aluminum+Ferrum Fitting

Model No:	VT-781	VT-781
SKU Code:	3595	3596
Base:	GU10	GU10
Material:	Aluminum+Ferrum	Aluminum+Ferrum
Shape:	Round	Round
Color of Fixture:	White	Satin Nickel
Dimension:	Φ100 x 45mm	Φ100 x 38mm
Cutting Size:	Φ90mm	Φ90mm
EAN Code:	3800157607247	3800157607254


GU10 SOCKET
■ NOT INCLUDED ■



Aluminum+Ferrum Fitting

Model No:	VT-781	VT-781
SKU Code:	3597	3598
Base:	GU10	GU10
Material:	Aluminum+Ferrum	Aluminum+Ferrum
Shape:	Square	Square
Color of Fixture:	White	Satin Nickel
Dimension:	100 x 100 x 38mm	100 x 100 x 38mm
Cutting Size:	90 x 90mm	90 x 90mm
EAN Code:	3800157607261	3800157607278


GU10 SOCKET
■ NOT INCLUDED ■



Aluminium Fitting

Model No:	VT-782	VT-783	VT-784
SKU Code:	3599	3601	3603
Base:	GU10	GU10	GU10
Material:	Aluminum	Aluminum	Aluminum
Shape:	Round	Round	Round
Color of Fixture:	White	White	White
Dimension:	Ø91 x 25mm	173 x 91 x 25mm	255 x 91 x 25
Cutting Size:	Ø75mm	155 x 75mm	235 x 75
EAN Code:	3800157607285	3800157607308	3800157607322




GU10 SOCKET
■ NOT INCLUDED ■



Aluminium Fitting

Model No:	VT-782	VT-783	VT-784
SKU Code:	3600	3602	3604
Base:	GU10	GU10	GU10
Material:	Aluminum	Aluminum	Aluminum
Shape:	Round	Round	Round
Color of Fixture:	Aluminum Brush	Aluminum Brush	Aluminum Brush
Dimension:	Ø91 x 25mm	173 x 91 x 25mm	255 x 91 x 25mm
Cutting Size:	Ø75mm	155 x 75mm	235 x 75mm
EAN Code:	3800157607292	3800157607315	3800157607339




GU10 SOCKET
■ NOT INCLUDED ■



Aluminium Fitting

Model No:	VT-782	VT-783	VT-784
SKU Code:	3605	3607	3609
Base:	GU10	GU10	GU10
Material:	Aluminum	Aluminum	Aluminum
Shape:	Square	Square	Square
Color of Fixture:	White	White	White
Dimension:	91 x 91 x 25mm	173 x 91 x 25mm	255 x 91 x 25mm
Cutting Size:	75mm	155 x 75mm	235 x 75mm
EAN Code:	3800157607346	3800157607360	3800157607384



GU10 SOCKET
■ NOT INCLUDED ■



Aluminium Fitting

Model No:	VT-782	VT-783	VT-784
SKU Code:	3606	3608	3610
Base:	GU10	GU10	GU10
Material:	Aluminum	Aluminum	Aluminum
Shape:	Square	Square	Square
Color of Fixture:	Aluminum Brush	Aluminum Brush	Aluminum Brush
Dimension:	91 x 91 x 25mm	173 x 91 x 25mm	255 x 91 x 25mm
Cutting Size:	75mm	155 x 75mm	235 x 75mm
EAN Code:	3800157607353	3800157607377	3800157607391



GU10 SOCKET
■ NOT INCLUDED ■




Aluminium Fitting

Model No:	VT-785	VT-786
SKU Code:	3611	3612
Base:	GU10	GU10
Material:	Aluminum	Aluminum
Shape:	Round	Round
Color of Fxture:	White	White
Dimension:	Φ88 x 38mm	Φ88 x 38mm
Cutting Size:	Φ75mm	Φ75mm
EAN Code:	3800157607407	3800157607414

GU10 SOCKET
■ NOT INCLUDED ■



**IP54
RATED**
**Matt Glass
DIFFUSER**





**IP54
RATED**
**Matt Glass
DIFFUSER**



Aluminium Fitting

Model No:	VT-787	VT-787
SKU Code:	3613	3614
Base:	GU10	GU10
Material:	Zinc alloy+Ferrum +Glass	Zinc alloy+Ferrum + Glass
Shape:	Round	Round
Color of Fxture:	White	Satin Nickel
Dimension:	Φ84 x 38mm	Φ84 x 38mm
Cutting Size:	Φ75	Φ75mm
EAN Code:	3800157607421	3800157607438

GU10 SOCKET
■ NOT INCLUDED ■



IP54
RATED
Matt Glass
DIFFUSER






IP54
RATED
Matt Glass
DIFFUSER

Aluminium Fitting

Model No:	VT-787	VT-787
SKU Code:	3615	3616
Base:	GU10	GU10
Material:	Zinc alloy+Ferrum + Glass	Zinc alloy+Ferrum + Glass
Shape:	Square	Square
Color of Fixture:	White	Satin Nickel
Dimension:	84 x 84 x 38mm	84 x 84 x 38mm
Cutting Size:	Φ75mm	Φ75mm
EAN Code:	3800157607445	3800157607452

GU10 SOCKET
■ NOT INCLUDED ■



Aluminium Fitting

Model No:	VT-7227	VT-7227	VT-7227
SKU Code:	3469	3470	3471
Base:	GU10	GU10	GU10
Material:	Ferrum	Ferrum	Ferrum
Shape:	Recessed	Recessed	Recessed
Color of Fixture:	White	Satin Nickel	Chrome
Dimension:	Round	Round	Round
Cutting Size:	Φ82 x 25mm	Φ82 x 25mm	Φ82 x 25mm
EAN Code:	Φ74mm	Φ74mm	Φ74mm
	3800157605885	3800157605892	3800157605908



**SURFACE MOUNTED
GU10 FITTINGS**


Easy Installation
Elegant Design



GU10 SOCKET
■ NOT INCLUDED ■

GU10 Fittings
Surface Mounted


Model No	VT-796
Colour:	White
SKU Code:	3627
Holder:	GU10
Material:	Ferrum
Dimension:	142 x 100 mm
EAN Code:	3800157612043



GU10 SOCKET
■ NOT INCLUDED ■

GU10 Fittings
Surface Mounted


Model No	VT-796
Colour:	Black
SKU Code:	3628
Holder:	GU10
Material:	Ferrum
Dimension:	142 x 100 mm
EAN Code:	3800157612050



GU10 SOCKET
■ NOT INCLUDED ■

GU10 Fittings
Surface Mounted

Model No	VT-796
Colour:	Satin Nickle
SKU Code:	3629
Holder:	GU10
Material:	Ferrum
Dimension:	142 x 100 mm
EAN Code:	3800157612067






GU10 SOCKET
■ NOT INCLUDED ■

GU10 Fittings Surface Mounted


Model No	VT-797
Colour:	White
SKU Code:	3630
Holder:	GU10
Material:	Ferrum
Dimension:	142 x 100 x 100 mm
EAN Code:	3800157612074



GU10 SOCKET
■ NOT INCLUDED ■

GU10 Fittings Surface Mounted


Model No	VT-797
Colour:	Black
SKU Code:	3631
Holder:	GU10
Material:	Ferrum
Dimension:	142 x 100 x 100 mm
EAN Code:	3800157612081




GU10 SOCKET
■ NOT INCLUDED ■

GU10 Fittings Surface Mounted

Model No	VT-797
Colour:	Satin Nickle
SKU Code:	3632
Holder:	GU10
Material:	Ferrum
Dimension:	142 x 100 x 100 mm
EAN Code:	3800157612098





Aluminium Fitting

SKU CODE	3617	3618	3619
DESCRIPTION	1 x GU10 Track Fitting White	2 x GU10 Track Fitting White	3 x GU10 Track Fitting White
EAN CODE	3800157607469	3800157607476	3800157607483



GU10 Lamp Holder
With PVC Cable

5 PCS PACK
AVAILABLE
SKU-34235



GU10 Lamp Holder
With PVC Cable

SKU Code	3423
Material	Ceramic
Wire Length	150mm
EAN Code	3800157607827


ModelNo.	VT-791
SKU Code	3620
Material	Ceramic
Wire Length	158mm
EAN Code	3800157607704



MR16 Lamp Holder
With PVC Cable

5 PCS PACK

ModelNo.	VT-7889
SKU Code	36265
Material	Ceramic
Wire Length	150mm
EAN Code	3800157609999



LED PAR Bulbs & AR111

This versatile series great quality light source also boasts of an impressive hour lamp life which has a huge impact on replacement costs

Product Features

- Eco friendly and Power Saving alternative for Standard Halogen Par Lamps with a longer life.
- Each lamp is a direct retrofit for a comparable Halogen Par Lamp e.g. AR111, PAR 30 & PAR 38
- Exceptional Heat Radiation Efficiency
- Non - Flickering
- No UV Radiation
- Premium Quality Power Driver
- Creates better Lighting effect than the old halogen bulb
- Dimmable & Non Dimmable options available

Applications

Widely used in Showrooms, Exhibition Stands, Stores, Offices and Reception areas, Hotels, Bars and Commercial Lighting






AR111 with Driver

20W VT-1120

- 1243 3000K Warm White
- 1244 4500K Day White
- 1245 6000K White

EAN Code

- 3800157606004
- 3800157606011
- 3800157606028



EQ. Watts:	100W	PF:	> 0.7
Voltage/Frequency:	AC: 220-240V, 50/60Hz	Beam Angle:	20°
Luminous Flux:	1500lm	Base:	Die Cast Aluminum
Commercial Type:	AR111	Body Type:	IP20
LED Type:	COB	Dimension:	Ø111 x 61.5mm
CRI:	> 80		




AR111 with Driver

20W VT-1120

- 1246 3000K Warm White
- 1247 4500K Day White
- 1248 6000K White

EAN Code

- 3800157606035
- 3800157606042
- 3800157606059



EQ. Watts:	100W	PF:	> 0.7
Voltage/Frequency:	AC: 220-240V, 50/60Hz	Beam Angle:	40°
Luminous Flux:	1500lm	Base:	Die Cast Aluminum
Commercial Type:	AR111	Body Type:	IP20
LED Type:	COB	Dimension:	Ø111 x 61.5mm
CRI:	> 80		



Dimmable



Driver included in Set



94.5 x 45.5 x 28mm


G53 AR111

15W VT-1110 D

4099 3000K Warm White
4106 4500K Day White
4086 6000K White

EAN Code

3800230620088
3800230620071
3800230626486



EQ. Watts:	75W	Dimmable:	Yes
Voltage/Frequency:	AC: 220V, 50Hz	PF:	> 0.9
Luminous Flux:	780lm	Beam Angle:	20°
Commercial Type:	AR111	Base:	G53
LED Type:	COB	Body Type:	Plastic Clad Aluminum
CRI:	> 80	Dimension:	111 x 86 mm


G53 AR111

15W VT-1110

4257 3000K Warm White
4256 4500K Day White
4255 6000K White

EAN Code

3800230628664
3800230628657
3800230628640



EQ. Watts:	75W	PF:	> 0.9
Voltage/Frequency:	AC: 12V, 50Hz	Beam Angle:	40°
Luminous Flux:	780lm	Base:	G53
Commercial Type:	AR111	Body Type:	Plastic Clad Aluminum
LED Type:	COB	Dimension:	111 x 86 mm
CRI:	> 80		


G53 AR111

15W VT-1110

4084 3000K Warm White
4062 4500K Day White
4061 6000K White

EAN Code

3800230620064
3800230620057
3800230620040



EQ. Watts:	75W	PF:	>0.5
Voltage/Frequency:	AC: 12V, 50Hz	Beam Angle:	20°
Luminous Flux:	780lm	Base:	G53
Commercial Type:	AR111	Body Type:	Plastic Clad Aluminum
LED Type:	COB	Dimension:	111 x 86 mm
CRI:	> 80		




GU10 AR111

12W VT-1112

4224 3000K Warm White
4223 4500K Day White
4225 6000K White

EAN Code

3800230626257
3800230626219
3800230626264



EQ. Watts:	60W	PF:	> 0.9
Voltage/Frequency:	AC: 220-240V, 50Hz	Beam Angle:	40°
Luminous Flux:	650lm	Base:	GU10
Commercial Type:	AR111	Body Type:	Plastic Clad Aluminum
LED Type:	COB	Dimension:	111 x 91 mm
CRI:	> 80		



Dimmable




GU10 AR111

12W VT-1112



7234 2700k Warm White
7235 4000K Day White
7236 6400k White

EAN Code

3800157620055
3800157620062
3800157620079





EQ. Watts:	60W	Dimmable:	Yes
Voltage/Frequency:	AC: 200-240V, 50Hz	PF:	> 0.9
Luminous Flux:	650lm	Beam Angle:	40°
Commercial Type:	AR111	Base:	GU10
LED Type:	COB	Body Type:	Plastic Clad Aluminum
CRI:	> 80	Dimension:	111 x 91 mm




Aluminum Fitting

Model No. :	VT-7221	VT-7222	VT-7223
SKU Code :	3575	3576	3577
Color :	White	White	White
Holder :	1xAR111	2xAR111	3xAR111
Body Type :	Aluminum	Aluminum	Aluminum
Dimension :	174 x 174 mm	325 x 174 mm	475 x 174 mm
Cutting Size :	168x155mm	305 x 168 mm	455 x 168 mm
EAN Code :	3800157604765	3800157604772	3800157604789



Aluminum Fitting

Model No. :	VT-7221	VT-7222	VT-7223
SKU Code :	3581	3582	3583
Color :	Black	Black	Black
Holder :	1xAR111	2xAR111	3xAR111
Body Type :	Aluminum	Aluminum	Aluminum
Dimension :	174 x 174 mm	325 x 174 mm	475 x 174 mm
Cutting Size :	168x155mm	305 x 168 mm	455 x 168 mm
EAN Code :	3800157607063	3800157607070	3800157607087



PAR 38 - E27


15W VT-1215

4415 3000K Warm White
4416 4500K Day White
4417 6000K White

EAN Code

3800157606271
3800157606288
3800157606295

A+



EQ. Watts:	100W	PF:	> 0.5
Voltage/Frequency:	AC: 180-240V, 50/60Hz	Beam Angle:	30°
Luminous Flux:	1200lm	Base:	E27
LED Type:	SMD	Body Type:	Plastic Coated Aluminum
Commercial Type :	PAR38	IP Rating:	IP65
CRI:	> 80	Dimension:	Ø120 x 133mm




Green



Red



Blue



PAR 38 - E27


15W VT-1125

4418 Green
4419 Red
4420 Blue

EAN Code

3800157606301
3800157606318
3800157606325

A



EQ. Watts:	100W	PF:	> 0.5
Voltage/Frequency:	AC: 180-240V, 50/60Hz	Beam Angle:	30°
Luminous Flux:	1200lm	Base:	E27
LED Type:	SMD	Body Type:	Plastic Coated Aluminum
Commercial Type :	PAR38	IP Rating:	IP65
CRI:	> 80	Dimension:	Ø120 x 133mm





Garden Spike Single Head

VT-728 EAN Code
7044 3800157606332




Type:	Outdoor	Compatible:	PAR 38
Suitable:	VT-1125 Bulb	Color:	Black
Holder:	E27	IP Rating:	IP44
Material:	ABS	Dimension:	470 x 85 x 85mm



Garden Spike Double Head

VT-729 EAN Code
7045 3800157606349



Type:	Outdoor	Compatible:	PAR 38
Suitable:	VT-1125 Bulb	Color:	Black
Holder:	E27	IP Rating:	IP44
Material:	ABS	Dimension:	335 x 210 x 80mm

LED Nano Plastic Tubes

A revolutionary LED Lighting Solution



A clear nine point advantage over any conventional glass LED tube!



Nano plastic tube has better light transmittance



This product is almost unbreakable



Light emitted is softer



Light emitted is even across the angle and hence diffuses the glare



The luminous efficiency of the light can reach up to 92%



The bending endurance is twice better than the normal polycarbonate lens




The thickness of a Nano plastic tube is just 0.4 to 0.5 mm



This new material has super thermal conductivity



The internal convection holes can release a great amount of heat from the tube light



LED Tube Lights

Transform your existing space and make it more sustainable & beautify.

V-TAC LED Tube Series perfectly fit into existing linear fixtures and provide comparably better light levels to current Linear fluorescent systems .

Product Features

- Cost effective, safe retrofit for T8 Tubes
- Perfectly matches with the traditional daylight tube fixture
- Easy Installation
- No Lead or Mercury content hence Environment friendly
- No Ultraviolet or Infrared rays
- Non - flickering
- Long Lifespan, Low maintenance and energy saving
- Available in 60 cm, 120 cm, 150 cm & 180 cm
- Ballast or Starter NOT REQUIRED – DIRECT AC POWER



Applications

Widely used for Domestic and Commercial Lighting, Offices, Supermarkets, Shops, Hotels & similar environment



T8 - Nano Plastic

10W VT-6072


6229 3000K Warm White
6230 4500K Day White
6231 6400K White

EAN Code

3800157605212
3800157605229
3800157605236



EQ. Watts:	18W	PF:	>0.5	Holder:	G13
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	160°D	On/Off:	>15000
Luminous Flux:	800lm	Body Type:	Nano-Plastic	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	28mm x 600mm	Gross weight:	125 g
CRI:	>80	Instant start :	0-100% in <1s		



Dummy Starter
Included



T8 - Nano Plastic

14W VT-9077


6272 4000k Day White
6262 6400K White

EAN Code

3800157615419
3800157612128



EQ. Watts:	25W	PF:	>0.5	Holder:	G13
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	1200lm	Body Type:	Nano-Plastic	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	28mm x 900mm	Gross weight:	145.6 g
CRI:	>80	Instant start :	0-100% in <1s		



Dummy Starter
Included



T8 - Nano Plastic

18W VT-1277


EAN Code

6263 3000k Warm White
6273 4000k Day White
6264 6400K White

3800157612135
3800157615426
3800157612159



EQ. Watts:	36W	PF:	>0.5	Holder:	G13
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	1600lm	Body Type:	Nano-Plastic	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	28mm x 1200mm	Gross weight:	200 g
CRI:	>80	Instant start :	0-100% in <1s		



Dummy Starter
Included



T8 - Nano Plastic

22W VT-1577


EAN Code

6265 3000k Warm White
6309 4000k Day White
6310 6400K White

3800157612159
3800157617437
3800157617444



EQ. Watts:	55W	PF:	>0.5	Holder:	G13
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	1900lm	Body Type:	Nano-Plastic	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	28mm x1500mm	Gross weight:	283.4 g
CRI:	>80	Instant start :	0-100% in <1s		



Dummy Starter
Included



60CM
10W VT-6085


6299 3000k Warm White
6301 4000k Day White
6302 6400K White



Dummy Starter
Included

EAN Code

3800157617345
3800157617352
3800157617369



120⁺⁺
LM/W
HIGH LUMENS

EQ. Watts:	25W	PF:	>0.5	Holder:	G13
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	1200lm	Body Type:	Nano-Plastic	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	28mm x 600mm	Gross weight:	125 g
CRI:	>80	Instant start :	0-100% in <1s		



120CM

18W VT-1285


6303 3000k Warm White
6304 4000k Day White
6305 6400K White



Dummy Starter
Included

EAN Code

3800157617376
3800157617383
3800157617390



120⁺⁺
LM/W
HIGH LUMENS

EQ. Watts:	45W	PF:	>0.5	Holder:	G13
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	2300lm	Body Type:	Nano-Plastic	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	28mm x 1200mm	Gross weight:	200 g
CRI:	>80	Instant start :	0-100% in <1s		



150CM

22W VT-1585


6306 3000k Warm White
6307 4000k Day White
6308 6400K White



Dummy Starter
Included

EAN Code

3800157617406
3800157617413
3800157617420



120⁺⁺
LM/W
HIGH LUMENS

EQ. Watts:	75W	PF:	>0.5	Holder:	G13
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	3000lm	Body Type:	Nano-Plastic	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	28mm x1500mm	Gross weight:	283.4 g
CRI:	>80	Instant start :	0-100% in <1s		



T8 - Shoplite Nano Plastic

18W VT-6077
6313 4000k Day White
6314 6400k White

EAN Code
3800157618656
3800157618663



120⁺⁺
LM/W
HIGH LUMENS

EQ. Watts:	36W	PF:	>0.5	Holder:	G13
Voltage/Frequency:	AC: 200-240V 50/60Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	2500lm	Body Type:	Nano Plastic	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	18.5mm x 549mm	Gross weight:	250 g
CRI:	>80	Instant start :	0-100% in <1s		



T8 - Shoplite Nano Plastic

36W VT-12077
6315 4000k Day White
6316 6400k White

EAN Code
3800157618670
3800157618687




120⁺⁺
LM/W
HIGH LUMENS

EQ. Watts:	72W	PF:	>0.5	Holder:	G13
Voltage/Frequency:	AC: 200-240V 50/60Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	4500lm	Body Type:	Nano Plastic	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	18.5mm x 1149mm	Gross weight:	400 g
CRI:	>80	Instant start :	0-100% in <1s		

**T5 - Glass with PET****8W** VT-60056318 4000k Day White
6319 6500k White


EAN Code

3800157619271
3800157619288

EQ. Watts:	14W	PF:	>0.9	Holder:	G5
Voltage/Frequency:	AC:200-240V, 50/60Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	800lm	Body Type:	Glass with PET	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	18.5mm x 549mm	Gross weight:	128 g
CRI:	>80	Instant start :	0-100% in <1s		

**T5 - Glass with PET****16W** VT-12256320 4000k Day White
6321 6500k White


EAN Code

3800157619295
3800157619301

EQ. Watts:	28W	PF:	>0.9	Holder:	G5
Voltage/Frequency:	AC:200-240V, 50/60Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	1600lm	Body Type:	Glass with PET	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	18.5mm x 1149mm	Gross weight:	213 g
CRI:	>80	Instant start :	0-100% in <1s		

**T8 - Aluminum Body****40W** VT-18406251 4500K Day White
6250 6000K White

EAN Code

3800157607834
3800157607841

EQ. Watts:	80W	PF:	>0.9	Holder:	G13
Voltage/Frequency:	AC:85-265V,50Hz	Beam Angle:	120°	On/Off:	>15000
Luminous Flux:	3600lm	Body Type:	Aluminum+PC	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	28mm x 1800mm	Gross weight:	700g
CRI:	>80	Instant start :	0-100% in <1s		




T8 - Glass Bread Tube

18W VT-1228
SKU 6322



EAN Code
3800157619318



EQ. Watts:	36W	PF:	>0.9	Holder:	G13
Voltage/Frequency:	AC:180-240V, 50/60Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	990lm	Body Type:	Glass with PET	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	26mm x 1200mm	Gross weight:	380 g
CRI:	>95	Instant start :	0-100% in <1s		




T8 - Glass Meat Tube

18W VT-1228
SKU 6323



EAN Code
3800157619325



EQ. Watts:	36W	PF:	>0.9	Holder:	G13
Voltage/Frequency:	AC:180-240V, 50/60Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	1530lm	Body Type:	Glass with PET	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	26mm x 1200mm	Gross weight:	380 g
CRI:	>95	Instant start :	0-100% in <1s		




T8 - Glass Vegetable



18W VT-1228
SKU 6324



EAN Code
3800157619332



EQ. Watts:	36W	PF:	>0.9	Holder:	G13
Voltage/Frequency:	AC:180-240V, 50/60Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	990lm	Body Type:	Glass with PET	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	26mm x 1200mm	Gross weight:	380 g
CRI:	>95	Instant start :	0-100% in <1s		




T8 - Glass Seafood Tube

18W VT-1228
SKU 6325

EAN Code
3800157619349



EQ. Watts:	36W	PF:	>0.9	Holder:	G13
Voltage/Frequency:	AC:180-240V, 50/60Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	1530lm	Body Type:	Glass with PET	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	26mm x 1200mm	Gross weight:	380 g
CRI:	>95	Instant start :	0-100% in <1s		



T8 - Glass Plant Growing Tube

18W VT-1228
SKU 6326

EAN Code
3800157619356



EQ. Watts:	36W	PF:	>0.9	Holder:	G13
Voltage/Frequency:	AC:180-240V, 50/60Hz	Beam Angle:	160°	On/Off:	>15000
Luminous Flux:	860lm	Body Type:	Glass with PET	Life span:	20,000 Hours
LED Type:	SMD	Dimension:	26mm x 1200mm	Gross weight:	380 g
CRI:	>95	Instant start :	0-100% in <1s		

**30CM - Prismatic****10W** VT-8013

4987 3000K Warm White

4988 4500K Day White


4989 6000K White

EAN Code

3800157601955

3800157601962

3800157601979

**A+**

EQ. Watts:	50W	PF:	> 0.5	On/Off:	>15000
Voltage/Frequency:	AC:200-240V,50Hz	Beam Angle:	110°	Life span:	20,000 Hours
Luminous Flux:	800lm	Body Type:	Aluminum+Plastic	Gross weight:	260 g
LED Type:	SMD	Dimension:	300 x 75 x 25mm		
CRI:	>80	Instant start :	0-100% in <1s		

**60CM - Prismatic****20W** VT-8020

4990 3000K Warm White

4991 4500K Day White


4992 6000K White

EAN Code

3800157601986

3800157601993

3800157602006

**A+**

EQ. Watts:	100W	PF:	> 0.5	On/Off:	>15000
Voltage/Frequency:	AC:200-240V,50Hz	Beam Angle:	110°	Life span:	20,000 Hours
Luminous Flux:	1600lm	Body Type:	Aluminum+Plastic	Gross weight:	420 g
LED Type:	SMD	Dimension:	600 x 75 x 25mm		
CRI:	>80	Instant start :	0-100% in <1s		

**120CM - Prismatic****40W** VT-8040

4993 3000K Warm White

4994 4500K Day White


4995 6000K White

EAN Code

3800157602013

3800157602020

3800157602037

**A+**

EQ. Watts:	200W	PF:	>0.9	On/Off:	>15000
Voltage/Frequency:	AC:200-240V,50Hz	Beam Angle:	110°	Life span:	20,000 Hours
Luminous Flux:	3200lm	Body Type:	Aluminum+Plastic	Gross weight:	840 g
LED Type:	SMD	Dimension:	1200 x 75 x 25mm		
CRI:	>80	Instant start :	0-100% in <1s		




150CM - Prismatic

50W VT-8050

6254 4500k Day White
6253 6000k White

EAN Code

3800157609579
3800157609562



EQ. Watts:	250W	PF:	>0.9	On/Off:	>15000
Voltage/Frequency:	AC: 200-240V, 50Hz	Beam Angle:	110°	Life span:	20,000 Hours
Luminous Flux:	4000 lm	Body Type:	Aluminum+Plastic	Gross weight:	1000g
LED Type:	SMD	Dimension:	1500 x 75 x 25mm		
CRI:	>80	Instant start :	0-100% in <1s		




180CM - Prismatic

60W VT-8060


6311 4500k Day White
6312 6000k White

EAN Code

3800157617574
3800157617581



EQ. Watts:	300W	PF:	>0.9	On/Off:	>15000
Voltage/Frequency:	AC: 200-240V, 50Hz	Beam Angle:	110°	Life span:	20,000 Hours
Luminous Flux:	4800lm	Body Type:	Aluminum+Plastic	Gross weight:	1200g
LED Type:	SMD	Dimension:	1800 x 75 x 25mm		
CRI:	>80	Instant start :	0-100% in <1s		



120CM - Linear Light

36W VT-12042

6202 4500K Day White
6203 6000K White

8071 Wire
8072 Joint

EAN Code

3800157604024
3800157604031



EQ. Watts:	80W	PF:	>0.9	On/Off:	>15000
Voltage/Frequency:	AC:85-265V/50-60Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	2900lm	Body Type:	IRON+PC	Gross weight:	700 g
LED Type:	SMD	Dimension:	1187 x 54 x36mm		
CRI:	>80	Instant start :	0-100% in <1s		




**30CM - T5 Tube
With Fitting****4W** VT-3033

EAN Code

6166 3000K Warm White
6167 4500K Day White
6168 6000K White

3800230629159
3800230629166
3800230629173




EQ. Watts:	8W	PF:	> 0.5	On/Off:	>15000
Voltage/Frequency:	AC:200~240V, 50/60Hz	Beam Angle:	141°	Life span:	20,000 Hours
Luminous Flux:	330lm	Body Type:	Plastic	Gross weight:	140 g
LED Type:	SMD	Dimension:	305 x 28 x 36mm		
CRI:	>80	Instant start :	0-100% in <1s		

**60CM - T5 Tube
With Fitting****7W** VT-6073

EAN Code

6169 3000K Warm White
6170 4500K Day White
6171 6000K White

3800230629180
3800230629197
3800230629203




EQ. Watts:	14W	PF:	> 0.5	On/Off:	>15000
Voltage/Frequency:	AC:200~240V, 50/60Hz	Beam Angle:	141°	Life span:	20,000 Hours
Luminous Flux:	630lm	Body Type:	Plastic	Gross weight:	210 g
LED Type:	SMD	Dimension:	605 x 28 x 36mm		
CRI:	>80	Instant start :	0-100% in <1s		

**120CM - T5 Tube
With Fitting****14W** VT-1273

EAN Code

6172 3000K Warm White
6173 4500K Day White
6174 6000K White

3800230629210
3800230629227
3800230629234




EQ. Watts:	28W	PF:	> 0.5	On/Off:	>15000
Voltage/Frequency:	AC:200~240V, 50/60Hz	Beam Angle:	141°	Life span:	20,000 Hours
Luminous Flux:	1260 lm	Body Type:	Plastic	Gross weight:	300 g
LED Type:	SMD	Dimension:	1230 x 28 x 36mm		
CRI:	>80	Instant start :	0-100% in <1s		

**Cabinet Light****10W** VT-8112

5068 3000K Warm White
5069 4500K Day White
5070 6000K White

EAN Code

3800157606714
3800157606721
3800157606738




EQ. Watts:	50W	PF:	> 0.5	On/Off:	>15000
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	110°	Life span:	20,000 Hours
Luminous Flux:	800lm	Body Type:	Aluminum Body, Plastic Diffuser	Gross weight:	600 g
LED Type:	SMD	Dimension:	579 x 78 x 35mm		
CRI:	>80	Instant start :	0-100% in <1s		

**Wall Fitting****10W** VT-8111

5071 3000K Warm White
5072 4500K Day White
5073 6000K White

EAN Code

3800157606745
3800157606752
3800157606769




EQ. Watts:	20W	PF:	> 0.5	On/Off:	>15000
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	900lm	Body Type:	Aluminum+PC	Gross weight:	240 g
LED Type:	SMD	Dimension:	600 x 32 x 25mm		
CRI:	>80	Instant start :	0-100% in <1s		

**Wall Fitting****20W** VT-8121

5074 3000K Warm White
5075 4500K Day White
5076 6000K White

EAN Code

3800157606776
3800157606783
3800157606790



EQ. Watts:	40W	PF:	> 0.5	On/Off:	>15000
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	1800lm	Body Type:	Aluminum+PC	Gross weight:	370 g
LED Type:	SMD	Dimension:	1200x 32 x 25mm		
CRI:	>80	Instant start :	0-100% in <1s		




MODEL No.	VT-16010	VT-12020	VT-15020	VT-18011
SKU Code	6052	6054	6056	6151
Body Type	Aluminum	Aluminum	Aluminum	Aluminum
IP Rating	IP20	IP20	IP20	IP20
Size	600mm	1200mm	1500mm	1800mm
EAN Code	3800230624642	3800230624666	3800230624680	3800230627926



MODEL No.	VT-16011	VT-12021	VT-15021
SKU Code	6053	6055	6057
Body Type	Aluminum	Aluminum	Aluminum
IP Rating	IP20	IP20	IP20
Size	600mm x 2	1200mm x 2	1500mm x 2
EAN Code	3800230624659	3800230624673	3800230624697

Batten Fixtures for our T8 LED Tubes so they can be used in a variety of different applications such as public areas like hotels, restaurants or hospitals.



Waterproof Fittings

An IP65 Ingress Protection Waterproof tubes provides evidence of its dust-tightness and complete resistance to rain and jets of water.

Product Features

- Luminous efficacy up to 120lm/W and 80lm/W
- Easy to install
- IP65, free from water and dirt
- Without opening the lampshade for direct wiring
- Perfect replacement for the whole set of T8 fluorescent lighting fixture
- Save up to 80% in electricity consumption compared to fluorescent lighting fixture



Applications

Parking lots, Gas stations, Tunnels, Warehouse etc.



60CM - Fitting


18W VT-6076

6283 4500k Day White
6282 6000k White



EAN Code

3800157616478
3800157616461



EQ. Watts:	100W	PF:	>0.5	On/Off:	>10000
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	1440lm	Body Type:	ABS+PC	Gross weight:	560 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	600 x 86 x 70mm		



120CM - Fitting


36W VT-1249

6285 4500k Day White
6284 6000k White



EAN Code

3800157616492
3800157616485



EQ. Watts:	200W	PF:	>0.9	On/Off:	>10000
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	2880lm	Body Type:	ABS+PC	Gross weight:	916 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1200 x 86 x 70mm		



150CM - Fitting


48W VT-1574

6287 4500k Day White
6286 6000k White



EAN Code

3800157616515
3800157616508



EQ. Watts:	250W	PF:	>0.9	On/Off:	>10000
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	3840lm	Body Type:	ABS+PC	Gross weight:	1150 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1500 x 86 x 70mm		



120CM - Fitting

36W VT-1248


6200 4500K Daywhite
6201 6000K White

EAN Code

3800157603270
3800157603287



EQ. Watts:	120W	PF:	>0.9	On/Off:	>10000
Voltage/Frequency:	AC:200-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	2800lm	Body Type:	Plastic	Gross weight:	1450 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1200 x 86 x 72mm		



150CM - Fitting

48W VT-1548

6184 4500K Daywhite
6185 6000K White

EAN Code

3800157602389
3800157602396



EQ. Watts:	90W	PF:	>0.9	On/Off:	>10000
Voltage/Frequency:	AC:200-240V,50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	4000lm	Body Type:	Plastic	Gross weight:	1800 g
LED Type:	SMD	Dimension:	IP65		
CRI:	>75	Instant start :	1480 x 86 x 72mm		





120CM - Fitting

60W VT-1260 SMD

6179 4500K Daywhite
6062 6000K White

EAN Code


3800157601610
3800230625212



120⁺⁺
LM/W
HIGH LUMENS



EQ. Watts:	500W	PF:	> 0.9	On/Off:	>10000
Voltage/Frequency:	AC: 200-240V, 50Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	7200lm	Body Type:	Plastic + Aluminium	Gross weight:	2100 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1200 x 86 x 70mm		



150CM - Fitting

70W VT-1573

6266 4500K Day White
6267 6000K White

EAN Code


3800157612586
3800157612593



120⁺⁺
LM/W
HIGH LUMENS



EQ. Watts:	600W	PF:	> 0.9	On/Off:	>10000
Voltage/Frequency:	AC:200-240V, 50/60Hz	Beam Angle:	120°	Life span:	20,000 Hours
Luminous Flux:	8400lm	Body Type:	Plastic + Aluminium	Gross weight:	2750 g
LED Type:	SMD	IP Rating:	IP65		
CRI:	>70	Dimension:	1500x 86 x70mm		





LED Panels

Uniform radiance coupled with consistent illumination and zero hot or cold spots, just pure systematic radiance with the V-TAC LED Light Panels. Practical, Economical and friendly


Product Features

- Ultra Slim Design
- Contemporary & Elegant Design
- Higher Light Transmission Rate
- Exterior shell, cannot be easily damaged
- No infrared, does not attract flies
- Easy to install
- No Lead or Mercury content hence Environment friendly
- Dimmable options available in selected models

Applications

- Office Lighting (Conference Room, Hospitals, Hotels, Shopping Malls, Showroom and lobby cabin etc.) Kitchen and Domestic Lighting





60 x 60 LED Panel


45W VT-6060

60286 3000K Warm White
60246 4000K Day White
60256 6400K White

EAN Code
3800230624482
3800230623652
3800230623584

6 Pack

A



EQ. Watts:	150W	PF:	> 0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°
Luminous Flux:	3600lm	Body Type:	Aluminum+PMMA+PS
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	595 x 595 x14mm

Drivers for Panels (EMC Approved)

SKU:	6019	6029	}	Compatible with	Compatible with
Type:	Dimmable	Tridonic		60286 / 62206	6222
Power:	45W	45W		60246 / 6218 6	6217
EAN Code:	3800157604017	N/A		60256 / 62196	6221



60 x 60 LED Panel



45W VT-6068

EAN Code

62206 3000K Warm White


3800157619516

62186 4000K Day White

3800157609265

62196 6400K White

3800157609272



EQ. Watts:	150W	PF:	> 0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°
Luminous Flux:	3600lm	Body Type:	Aluminum+PMMA+PS
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	595 x 595 x14mm



62 x 62 LED Panel



45W VT-6069

EAN Code

6222 3000K Warm White


3800157604918

6217 4000K Day White

3800157604857

6221 6400K White


3800157604901



EQ. Watts:	150W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°
Luminous Flux:	3600lm	Body Type:	Aluminum+PMMA+PS
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	620 x 620 x14mm

Drivers for Panels (EMC Approved)

SKU:	6019	6029	}	Compatible with	Compatible with
Type:	Dimmable	Tridonic		60286 / 62206	6222
Power:	45W	45W		60246 / 6218 6	6217
EAN Code:	3800157604017	N/A		60256 / 62196	6221



120⁺⁺
LM/W
HIGH LUMENS

60 x 60 LED Panel


29W VT-6129

EAN Code

62406 / 6240 3000K Warm White 3800157619608 / 3800157608169
62416 / 6241 4000K Day White 3800157609289 / 3800157608176
62426 / 6242 6400K White 3800157609296 / 3800157608183

A⁺⁺

EQ. Watts:	150W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	3600lm	Body Type:	Aluminum+PMMA+PC
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	595 x 595 x13mm



120⁺⁺
LM/W
HIGH LUMENS

60 x 60 LED Panel

45W VT-6145

EAN Code


63776 3000K Warm White 3800157622158
62366 / 6236 4000K Day White 3800157615723 / 3800157607612
62376 / 6237 6400K White 3800157615730 / 3800157607629

A⁺⁺

EQ. Watts:	250W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	5400lm	Body Type:	Aluminum+PMMA+PC
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	595 x 595 x13mm

Drivers for Panels (EMC Approved)

SKU:	6268	6269
Type:	Dimmable	Dimmable
Power:	29W	45W
EAN Code:	3800157614412	3800157614429



60 x 60 LED Panel

36W VT-6136

6376 3000K Warm White
6238 4000K Day White
6239 6400K White


120⁺⁺
LM/W
HIGH LUMENS

EAN Code

3800157622141
3800157607636
3800157607643



EQ. Watts:	180W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	4320lm	Body Type:	Aluminum+PMMA+PC
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	595 x 595 x13mm



62 x 62 LED Panel

36W VT-6137

63786 3000K Warm White
62436 / 6243 4000K Day White
63796 6400K White

120⁺⁺
LM/W
HIGH LUMENS

EAN Code

3800157622165
3800157619622 / 3800157608190
3800157622172



EQ. Watts:	180W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	4320lm	Body Type:	Aluminum+PMMA+PC
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	620 x 620 x13mm

Drivers for Panels (EMC Approved)

SKU: 6019
Type: Dimmable
Power: 45W
EAN Code:



120⁺⁺
LM/W
HIGH LUMENS

IP65
RATED

60 x 60 LED Panel


40W VT-6140

6331 4000K Day White
6330 6400k White


EAN Code

3800157620093
3800157620086

A⁺⁺



EQ. Watts:	180W	PF:	> 0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°
Luminous Flux:	4960lm	Body Type:	Aluminum+PS
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	595 x 595 x14mm



30 x 120 LED Panel

29W VT-12031 EAN Code
6256 3000k Warm White 3800157610414
6257 4000K Day White 3800157610421
6258 6400K White 3800157610438

A++

120⁺⁺
lm/w

HIGH LUMENS

EQ. Watts:	250W	PF:	>0.9
Voltage/Frequency:	AC:200-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	3400lm	Body Type:	Aluminum+PMMA+PS
LED Type:	SMD	Shape:	Rectangle
CRI:	>80	Dimension:	1195 x 295 x14mm

Drivers for Panels (EMC Approved)

SKU:	6019	6029
Type:	Dimmable	Tridonic
Power:	45W	45W
EAN Code:	3800157604017	N/A



30 x 120 LED Panel


45W VT-12030

60696 / 6069 3000K Warm White
60266 / 6026 4000K Day White
60276 / 6027 6400K White



EAN Code

3800157609326 / 3800230628466
3800157609302 / 3800230623638
3800157609319 / 3800230623621



EQ. Watts:	150W	PF:	> 0.9
Voltage/Frequency:	AC:200-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	3600lm	Body Type:	Aluminum+PMMA+PS
LED Type:	SMD	Shape:	Rectangle
CRI:	>80	Dimension:	1195 x 295 x14mm



30 x 120 LED Panel


45W VT-12032

6329 4000K Day White



EAN Code


3800157619615



EQ. Watts:	150W	PF:	> 0.9
Voltage/Frequency:	AC:200-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	3600lm	Body Type:	Aluminum+PMMA+PS
LED Type:	SMD	Shape:	Rectangle
CRI:	>80	Dimension:	1195 x 295 x14mm

Drivers for Panels (EMC Approved)

SKU:	6019	6029
Type:	Dimmable	Tridonic
Power:	45W	45W
EAN Code:	3800157604017	N/A



60 x 120 LED Panel

45W VT-12045


6332 4000K Day White
6333 6400K White

EAN Code


3800157620321
3800157620338

A++

120⁺⁺
lm/W
HIGH LUMENS



EQ. Watts:	400W	PF:	>0.9
Voltage/Frequency:	AC:200-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	5400lm	Body Type:	Aluminum+PMMA+PS
LED Type:	SMD	Shape:	Rectangle
CRI:	>80	Dimension:	1195 x 595 x14mm



Drivers for Panels (EMC Approved)

SKU: 6088
Type: EMC Approved -Dimmable
Power: 72W
EAN Code: 3800157602334

60 x 120 LED Panel


72W VT-12060

6051 4000K Day White
6050 6400K White

EAN Code

3800230624543
3800230624536

A+




EQ. Watts:	210W	PF:	> 0.9
Voltage/Frequency:	AC: 170-240V, 50Hz	Beam Angle:	120°
Luminous Flux:	5700lm	Body Type:	Aluminum+PMMA+PS
LED Type:	SMD 2835	Shape:	Rectangle
CRI:	>80	Dimension:	1195 x 595 x14mm



LED Surface Panel

36W VT-6050 EAN Code

6091 3000K Warm White 3800157604048
6092 4000K Day White 3800157604055
6093 6400K White 3800157604062




EQ. Watts:	110W	PF:	>0.9
Voltage/Frequency:	AC:100-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	2880lm	Body Type:	Die Cast Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø500mm x 40mm



LED Surface Panel

48W VT-6148 EAN Code

6261 3000K Warm White 3800157612111
6260 6400K White 3800157612104



EQ. Watts:	300W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	110°
Luminous Flux:	3850lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø600 x 40mm



DALI
Constant Current Dimming Driver





DALI
Multi-current Driver



DALI
Master

Model No:	VT-24030	VT-24045	VT-24050
SKU Code:	3110	3106	3107
Voltage:	AC:220V	20-39V -1050mp	N/A
Watts:	Max 30	40W/45W	<10W
EAN Code:	3800157622103	3800157606868	3800157606844





DALI
Touch Panel Controller



DALI
Bus Power Supply

Model No:	VT-24049	VT-24048
SKU Code:	3108	3109
Watts:	0.1W	4W
EAN Code:	3800157606851	



Driver for LED Panels

120⁺⁺
LM/W
HIGH LUMENS



45W

SKU Code:

6270

Type:

Non-Dimmable

Voltage:

200-240V

Watts:

45W

EAN Code:

3800157614436



29W



6271

Non-Dimmable

200-240V

29W

3800157614443

Drivers for LED Panels



SKU Code

6268

Type

Dimmable

Voltage

200-240V

Watts

29W

EAN Code

3800157614412

6269

Dimmable

200-240V

45W

3800157614429

6328

Dimmable

200-240V

70W

3800157619592



120⁺⁺
LM/W
HIGH LUMENS



120⁺⁺
LM/W
HIGH LUMENS



In order to make the slim panels more compatible, V-TAC has developed accessories so that the products can be installed in different types of option. This allows all our panels to be installed in three different types as required by the clients. They are :

- Recessed type
- Suspended mounted
- Surface mounted

Below are the accessories which support in making this type of installation possible:



Hanging Wires Fittings Kit for Suspended Panels

PRODUCT SKU : 6018

EAN CODE: 3800230623669

Adjustable height from 0.3 to 1m

This product can be used for all sizes of panels , that is

- 300 x 300
- 600 x 600
- 1200 x 300
- 1200 x 600

Case for External mounting for panels



Mounting for 1200x 600

Product SKU: 9989



Mounting for 620 x 620

Product SKU: 9997

Case for External mounting for panels



Mounting for 300 x 300

Product SKU: [9970](#)

EAN Code: 3800230623690



Mounting for 600 x 600

Product SKU : [9967](#)

EAN Code: 3800230623676



Mounting for 1205 x 310x156mm

Product SKU : [9969](#)

EAN Code: 3800230623683



Extension Frame for 625 x 625

Product SKU : [9968](#)

EAN Code: 3800230623706




Mounting for 600 x 600

Product SKU : 6327

EAN Code: 3800157619424


Installation Instruction for the Surface Mounted fixture of led Panel light

Here shows two installation methods, it should be installed differently according to your brought installation accessories.

Ceiling Mounted Type


1

1. Install and fix the 3 pieces of Aluminum profile into together in screws




2

2. Install the fixed fixture with 3 sides on the ceiling




3

3. place the led panel into the fixture.



5

4. Install the last L shape Aluminum profile to the fixed fixtures with 3 sides



6

5. turn on the power and light the luminaire, finish the installation

Emergency Pack SLIM & SLEEK

3Hr LED emergency lighting kit, designed to suit a wide range of LED types and circuits. The models have sealed Ni-Cd batteries able to guarantee high efficiency with high temperatures. The LED emergency lighting kit can be use for LED panel lighting, LED downlighting and Ceiling lamp, thus allowing any lighting spot to be qualified for emergency in a simple and quick way, where needed..



VT-518

SKU Code 60303

Suitable for 45W LED Panels


EAN Code

3800157617451



Voltage:	AC:220-240V,50/60Hz	Battery:	NI-CD, 7,12V, 4000 mAh
Led output power:	10W Max	Color of Fixture:	Aluminum+PMMA+PS
Panel output power:	45W	Body Type:	Square
Charging time:	≤ 36 hours	Size:	465 x52 x 33mm
Working time:	3 hours	Emergency switch on time:	<1 Second

Wire diagram:





LED Panel

6W VT-609

EAN Code

4875 3000K Warm White

3800157601801


4876 4000K Day White

3800157601818

4877 6400K White

3800157601825

A



EQ. Watts:	24W	Beam Angle:	120°
Voltage/Frequency:	DC:30-42V,50Hz	Body Type:	Plastic + Aluminium Heat Sink
Luminous Flux:	400lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø120mm x 25mm
CRI:	>80	Cutting Size:	Ø105mm
PF:	>0.5		



LED Panel

12W VT-1209

EAN Code

4878 3000K Warm White

3800157601832


4879 4000K Day White

3800157601849

4880 6400K White

3800157601856

A



EQ. Watts:	48W	Beam Angle:	120°
Voltage/Frequency:	DC:30-42V,50Hz	Body Type:	Plastic + Aluminium Heat Sink
Luminous Flux:	900lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø170mm x 25mm
CRI:	>80	Cutting Size:	Ø155mm
PF:	>0.7		

Available with Surface Fitting

6W	SKU	12W	SKU
VT-609	9921	VT-1209	9921






LED Panel

18W VT-1809

EAN Code

4881 3000K Warm White
4882 4000K Day White
4883 6400K White

3800157601863
3800157601870
3800157601887



EQ. Watts:	72W	Beam Angle:	120°
Voltage/Frequency:	DC:30-42V,50Hz	Body Type:	Plastic + Aluminium Heat Sink
Luminous Flux:	1350lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø225mm x 25mm
CRI:	>80	Cutting Size:	Ø205mm
PF:	>0.7		




LED Panel

24W VT-2409

EAN Code

4884 3000K Warm White
4885 4000K Day White
4886 6400K White

3800157601894
3800157601900
3800157601917



EQ. Watts:	100W	Beam Angle:	120°
Voltage/Frequency:	DC:30-42V,50Hz	Body Type:	Plastic + Aluminium Heat Sink
Luminous Flux:	1600lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø300mm x 25m
CRI:	>80	Cutting Size:	Ø285mm
PF:	>0.7		

Available with Surface Fitting

18W SKU
VT-1809 9923

24W SKU
VT-2409 9924






LED Panel

3W VT-307 RD

6292 3000k Warm White
6293 4000k Day White
6294 6400K White

EAN Code

3800157616751
3800157616768
3800157616775



EQ. Watts:	25W	Beam Angle:	120°
Voltage/Frequency:	AC: 85-265V,50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	210lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø84mm x 12mm
CRI:	>80	Cutting Size:	Ø73mm
PF:	> 0.5		


LED Panel

6W VT-607 RD

4854 / 48549 3000K Warm White
4855 / 48559 4000K Daywhit
4856 / 48569 6400K White

EAN Code

3800230629753
3800230629760
3800230629777



EQ. Watts:	45W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	420lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø120mm x 12mm
CRI:	>80	Cutting Size:	Ø105mm
PF:	> 0.5		


LED Panel

12W VT-1207 RD

4857 / 48579 3000K Warm White
4858 / 48589 4000K Day White
4859 / 48599 6400K White

EAN Code

3800230629784
3800230629791
3800230629807



EQ. Watts:	75W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	1000lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø170mm x 12mm
CRI:	>80	Cutting Size:	Ø155mm
PF:	> 0.6		



LED Panel


18W VT-1807 RD

EAN Code

4860 / 48609 3000K Warm White
4861 / 48619 4000K Day White
4862 / 48629 6400K White

3800230629814
3800230629821
3800230629838

A+



EQ. Watts:	110W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	1500lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø225mm x 12mm
CRI:	>80	Cutting Size:	Ø205mm
PF:	> 0.6		



LED Panel


24W VT-2407 RD

EAN Code

4872 / 48729 3000K Warm White
4873 / 48739 4000K Day White
4874 / 48749 6400K White

3800157601559
3800157601566
3800157601573

A+



EQ. Watts:	150W	Beam Angle:	120°
Voltage/Frequency:	AC:200-240V,50Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	2000lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø300mm x 12mm
CRI:	>80	Cutting Size:	Ø285mm
PF:	>0.9		




LED Panel

3W VT-307 SQ

6295 3000k Warm White
6296 4000K Day White
6297 6400K White

EAN Code

3800157616782
3800157616799
3800157616805



EQ. Watts:	25W	Beam Angle:	120°
Voltage/Frequency:	AC: 85-265V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	210lm	Shape:	Square
LED Type:	SMD	Dimension:	84 x 84 x 12mm
CRI:	>80	Cutting Size:	73 x 73mm
PF:	> 0.5		




LED Panel

6W VT-607 SQ

4863 / 48639 3000K Warm White
4864 / 48649 4000K Day White
4865 / 48659 6400K White

EAN Code

3800230629845
3800230629852
3800230629869



EQ. Watts:	45W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	420lm	Shape:	Square
LED Type:	SMD	Dimension:	120 x120 x 12mm
CRI:	>80	Cutting Size:	105mm x105mm
PF:	> 0.5		




LED Panel

12W VT-1207 SQ

4866 / 48669 3000K Warm White
4867 / 48679 4000K Day White
4868 / 48689 6400K White

EAN Code

3800230629876
3800230629883
3800230629890



EQ. Watts:	75W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	1000lm	Shape:	Square
LED Type:	SMD	Dimension:	170 x170 x 12mm
CRI:	>80	Cutting Size:	155mm x155mm
PF:	> 0.6		






LED Panel

18W VT-1807 SQ


EAN Code

4869 / 48699 3000K Warm White
4870 / 48709 4000K Day White
4871 / 48719 6400K White

3800230629906
3800230629913
3800230629920



EQ. Watts:	110W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	1500lm	Shape:	Square
LED Type:	SMD	Dimension:	225 x 225 x 12mm
CRI:	>80	Cutting Size:	205mm x205mm
PF:	> 0.6		




LED Panel

24W VT-2407 SQ

EAN Code

4887 / 48879 3000K Warm White
4888 / 48889 4000K Day White
4889 / 48899 6400K White

3800157602198
3800157602204
3800157602211



EQ. Watts:	150W	Beam Angle:	120°
Voltage/Frequency:	AC:200-240V,50Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	2000lm	Shape:	Square
LED Type:	SMD	Dimension:	300 x300 x 12mm
CRI:	>80	Cutting Size:	285mm x285mm
PF:	>0.9		

Dimmable Drivers
for Premium Panels



SKU Code:	8073	8074	8075
Watts:	6W	12W	18W
Description:	LED Driver Dimmable	LED Driver Dimmable	LED Driver Dimmable
EAN Code:	3800157605823	3800157605830	3800157605847
Size:	110x42xH26mm	110x42xH26mm	110x42xH26mm

Compatible with

48549 /48559 /48569/ 48639 /48649/ 48659

Compatible with

48579 /48589 /48599/ 48669 /48679/
48689

Compatible with

48609 /48619 /48629/ 48699 /48709/
48719




SKU Code:	8076	8070
Watts:	24W	18w +24W
Description:	LED Driver Dimmable	LED Driver Dimmable
EAN Code:	3800157605946	3800157616836
Size:	132x45xH26mm	132x45xH26mm

Compatible with

48729 /48739 /48749/ 48879 /48889/ 48899

Compatible with

4860 /4861 /4862 /4872 /4873 /4874
4869 /4870 /4871 /4887 /4888 /4889



LED Panel

8W VT-800 RD

4823 3000K Warm White
4822 4000K Day White
4821 6400K White


EAN Code

3800230622594
3800230624963
3800230622587

A⁺

100⁺⁺
LM/W
HIGH LUMENS

EQ. Watts:	24W	Beam Angle:	120°
Voltage/Frequency:	AC:110-265V, 50/60Hz	Body Type:	Aluminum(PKW)
Luminous Flux:	800lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø145mm x 20mm
CRI:	>80	Cutting Size:	Ø125mm
PF:	>0.9		



LED Panel

8W VT-800 SQ

4820 3000K Warm White
4819 4000K Day White
4818 6400K White

EAN Code

3800230622570
3800230624970
3800230622563


A⁺

100⁺⁺
LM/W
HIGH LUMENS

EQ. Watts:	24W	Beam Angle:	120°
Voltage/Frequency:	AC:110-265V, 50/60Hz	Body Type:	Aluminum(PKW)
Luminous Flux:	800lm	Shape:	Square
LED Type:	SMD	Dimension:	120 x120 x 20mm
CRI:	>80	Cutting Size:	105 x105mm
PF:	>0.9		

Drivers for Panels (EMC Approved)

SKU:	8036	8058
Type:	Non-dimmable	Dimmable
Power:	8W	8W
EAN Code:	3800230625519	3800230625540




LED Panel

15W VT-1500 RD
4829 3000K Warm White
4828 4000K Day White
4827 6400K White

EAN Code
3800230622631
3800230624987
3800230622624

A⁺
100⁺⁺ LM/W
HIGH LUMENS

EQ. Watts:	45W	Beam Angle:	120°
Voltage/Frequency:	AC:110-265V, 50/60Hz	Body Type:	Aluminum(PKW)
Luminous Flux:	1500lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø180mm x 20mm
CRI:	>80	Cutting Size:	Ø160mm
PF:	>0.9		



LED Panel

15W VT-1500 SQ
4826 3000K Warm White
4825 4000K Day White
4824 6400K White


EAN Code
3800230622617
3800230624994
3800230622600

A⁺
100⁺⁺ LM/W
HIGH LUMENS

EQ. Watts:	45W	Beam Angle:	120°
Voltage/Frequency:	AC:110-265V, 50/60Hz	Body Type:	Aluminum(PKW)
Luminous Flux:	1500lm	Shape:	Square
LED Type:	SMD	Dimension:	160 x160 x 20mm
CRI:	>80	Cutting Size:	140 x140mm
PF:	>0.9		

Drivers for Panels (EMC Approved)

SKU:	8037	8059
Type:	Non-dimmable	Dimmable
Power:	15W	15W
EAN Code:	3800230625526	3800230625557



LED Panel

22W VT-2200 RD


4832 3000K Warm White
4834 4000K Day White
4833 6400K White

EAN Code

3800230622679
3800230625007
3800230622662

A⁺
100⁺⁺
LM/W
HIGH LUMENS

EQ. Watts:	70W	Beam Angle:	120°
Voltage/Frequency:	AC: 110-265V, 50/60Hz	Body Type:	Aluminum (PKW)
Luminous Flux:	2200lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø240mm x 20mm
CRI:	> 80	Cutting Size:	Ø220mm
PF:	> 0.9		



LED Panel

22W VT-2200 SQ

4832 3000K Warm White
4831 4000K Day White
4830 6400K White

EAN Code

3800230622655
3800230625014
3800230622648

A⁺
100⁺⁺
LM/W
HIGH LUMENS

EQ. Watts:	70W	Beam Angle:	120°
Voltage/Frequency:	AC: 110-265V, 50/60Hz	Body Type:	Aluminum(PKW)
Luminous Flux:	2200lm	Shape:	Square
LED Type:	SMD	Dimension:	220 x220 x 20mm
CRI:	>80	Cutting Size:	195 x195mm
PF:	> 0.9		

Drivers for Panels (EMC Approved)

SKU:	8038	8060
Type:	Non-Dimmable	Dimmable Driver
Power:	22W	22W
EAN Code:	3800230625533	3800230625564




LED Panel

8W VT-888 RD

EAN Code

4931 3000K Warm White
4932 4000K Day White
4933 6400K White

3800157606479
3800157606486
3800157606493



EQ. Watts:	40W	Beam Angle:	110°
Voltage/Frequency:	AC:220-240V,50/60Hz	Body Type:	Die Cast Aluminum
Luminous Flux:	800lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø100mm x 27mm
CRI:	>80	Cutting Size:	Ø90mm
PF:	>0.9		




LED Panel

15W VT-1515 RD

EAN Code

4934 3000K Warm White
4935 4000K Day White
4936 6400K White

3800157606509
3800157606516
3800157606523



EQ. Watts:	100W	Beam Angle:	110°
Voltage/Frequency:	AC:220-240V,50/60Hz	Body Type:	Die Cast Aluminum
Luminous Flux:	1500lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø145mm x 27mm
CRI:	>80	Cutting Size:	Ø135mm
PF:	>0.9		




LED Panel

22W VT-2222 RD

4937 3000K Warm White
4938 4000K Day White
4939 6400K White

EAN Code

3800157606530
3800157606547
3800157606554



EQ. Watts:	120W	Beam Angle:	110°
Voltage/Frequency:	AC:220-240V,50/60Hz	Body Type:	Die Cast Aluminum
Luminous Flux:	2200lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø170mm x 27mm
CRI:	>80	Cutting Size:	Ø160mm
PF:	>0.9		




LED Panel

29W VT-2929 RD

4940 3000K Warm White
4941 4000K Day White
4942 6400K White

EAN Code

3800157606561
3800157606578
3800157606585



EQ. Watts:	200W	Beam Angle:	110°
Voltage/Frequency:	AC:220-240V,50/60Hz	Body Type:	Die Cast Aluminum
Luminous Flux:	2800lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø200mm x 27mm
CRI:	>80	Cutting Size:	Ø185mm
PF:	>0.9		




LED Panel

8W VT-888 SQ

EAN Code

4943 3000K Warm White
4944 4000K Day White
4945 6400K White

3800157606592
3800157606608
3800157606615



EQ. Watts:	40W	Beam Angle:	110°
Voltage/Frequency:	AC:220-240V,50/60Hz	Body Type:	Die Cast Aluminum
Luminous Flux:	800lm	Shape:	Square
LED Type:	SMD	Dimension:	95 x 95x 27mm
CRI:	>80	Cutting Size:	85mm x 85mm
PF:	>0.9		




LED Panel

15W VT-1515 SQ

EAN Code

4946 3000K Warm White
4947 4000K Day White
4948 6400K White

3800157606622
3800157606639
3800157606646



EQ. Watts:	100W	Beam Angle:	110°
Voltage/Frequency:	AC:220-240V,50/60Hz	Body Type:	Die Cast Aluminum
Luminous Flux:	1500lm	Shape:	Square
LED Type:	SMD	Dimension:	145 x145 x 27mm
CRI:	>80	Cutting Size:	135mm x 135mm
PF:	>0.9		




LED Panel

22W VT-2222 SQ

4949 3000K Warm White
4797 4000K Day White
4798 6400K White

EAN Code

3800157606653
3800157606660
3800157606677



EQ. Watts:	120W	Beam Angle:	110°
Voltage/Frequency:	AC:220-240V,50/60Hz	Body Type:	Die Cast Aluminum
Luminous Flux:	2200lm	Shape:	Square
LED Type:	SMD	Dimension:	170 x170 x 27mm
CRI:	>80	Cutting Size:	160mm x 160mm
PF:	>0.9		




LED Panel

29W VT-2929 SQ

4952 3000K Warm White
4953 4000K Day White
4954 6400K White

EAN Code

3800157606684
3800157606691
3800157606707



EQ. Watts:	200W	Beam Angle:	110°
Voltage/Frequency:	AC:220-240V,50/60Hz	Body Type:	Die Cast Aluminum
Luminous Flux:	2800lm	Shape:	Square
LED Type:	SMD	Dimension:	200 x 200 x 27mm
CRI:	>80	Cutting Size:	185mm x 185mm
PF:	>0.9		


LED SurfacePanel

6W VT-605 RD

EAN Code

4904 3000K Warm White
4905 4000K Day White
4906 6400K White

3800157605380
3800157605397
3800157605403



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	420lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø90mm x 24mm


LED SurfacePanel

12W VT-1205 RD

EAN Code

4910 3000K Warm White
4911 4000K Day White
4912 6400K White

3800157605441
3800157605458
3800157605465



EQ. Watts:	60W	PF:	>0.6
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	900lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø140mm x 24mm


LED SurfacePanel

18W VT-1805 RD


EAN Code

4916 3000K Warm White
4917 4000K Day White
4918 6400K White

3800157605502
3800157605519
3800157605526



EQ. Watts:	75W	PF:	>0.6
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	1440lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø190mm x 24mm

**LED SurfacePanel****6W** VT-605 SQ


4907 3000K Warm White
 4908 4000K Day White
 4909 6400K White

EAN Code

3800157605410
 3800157605427
 3800157605434



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	420lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	90 x 90 x 24mm

**LED SurfacePanel****12W** VT-1205 SQ


4913 3000K Warm White
 4914 4000K Day White
 4915 6400K White

EAN Code

3800157605472
 3800157605489
 3800157605496



EQ. Watts:	60W	PF:	>0.6
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	900lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	140 x 140 x 24mm

**LED SurfacePanel****18W** VT-1805 SQ

4919 3000K Warm White
 4920 4000K Day White
 4921 6400K White

EAN Code

3800157605533
 3800157605540
 3800157605557



EQ. Watts:	75W	PF:	>0.6
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	1440lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	190 x 190 x 24mm



100⁺⁺
LM/W
HIGH LUMENS



LED Panel


8W VT-1408 RD

4805 3000K Warm White
4804 4000K Day White
4803 6400K White

EAN Code

3800230622730
3800230622723
3800230622716

A⁺



EQ. Watts:	24W	PF:	> 0.9
Voltage/Frequency:	AC: 110-265V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	800lm	Body Type:	Aluminum(PKW)
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø115mm x 35mm



100⁺⁺
LM/W
HIGH LUMENS



LED Panel


15W VT-1415 RD

4811 3000K Warm White
4810 4000K Day White
4809 6400K White

EAN Code

3800230622792
3800230622785
3800230622778

A⁺



EQ. Watts:	45W	PF:	>0.9
Voltage/Frequency:	AC: 110-265V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	1500lm	Body Type:	Aluminum(PKW)
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø175mm x 35mm



100⁺⁺
LM/W
HIGH LUMENS



LED Panel


22W VT-1422 RD

4817 3000K Warm White
4816 4000K Day White
4815 6400K White

EAN Code

3800230622853
3800230622846
3800230622839

A⁺



EQ. Watts:	66W	PF:	> 0.9
Voltage/Frequency:	AC: 110-265V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	2200lm	Body Type:	Aluminum (PKW)
LED Type:	SMD 5630	Shape:	Round
CRI:	> 80	Dimension:	Ø235mm x 35mm



100⁺⁺
lm/w
HIGH LUMENS

Surface

LED Panel

8W VT-1408 SQ

4802 3000K Warm White

4801 4000K Day White


4800 6400K White

EAN Code

3800230622709

3800230622693

3800230622686



EQ. Watts:	24W	PF:	> 0.9
Voltage/Frequency:	AC: 110-265V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	800lm	Body Type:	Aluminum(PKW)
LED Type:	SMD 5630	Shape:	Square
CRI:	>80	Dimension:	115 x 115 x 35mm



100⁺⁺
lm/w
HIGH LUMENS

Surface

LED Panel

15W VT-1415 SQ

4808 3000K Warm White

4807 4000K Day White


4806 6400K White

EAN Code

3800230622761

3800230622754

3800230622747



EQ. Watts:	45W	PF:	> 0.9
Voltage/Frequency:	AC: 110-265V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	1500lm	Body Type:	Aluminum(PKW)
LED Type:	SMD 5630	Shape:	Square
CRI:	>80	Dimension:	175 x 175 x 35mm



100⁺⁺
lm/w
HIGH LUMENS

Surface

LED Panel

22W VT-1422 SQ

4814 3000K Warm White

4813 4000K Day White


4812 6400K White

EAN Code

3800230622822

3800230622815

3800230622808



EQ. Watts:	66W	PF:	> 0.9
Voltage/Frequency:	AC: 110-265V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	2200lm	Body Type:	Aluminum (PKW)
LED Type:	SMD 5630	Shape:	Square
CRI:	> 80	Dimension:	235 x 235 x 35mm




Round Chrome

6W VT-607CH

6334 3000k Warm White
6335 4000K Day White
6336 6400k White

EAN Code

3800157621182
3800157621199
3800157621205



EQ. Watts:	40W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	420lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø120mm x 25mm
CRI:	>80	Cutting Size:	Ø105mm
PF:	> 0.5		




Round Chrome

12W VT-1207CH

6340 3000k Warm White
6341 4000K Day White
6342 6400k White

EAN Code

3800157621243
3800157621250
3800157621267



EQ. Watts:	75W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	1000lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø170mm x 25mm
CRI:	>80	Cutting Size:	Ø155mm
PF:	> 0.6		




Round Chrome

18W VT-1807CH

6346 3000k Warm White
6347 4000K Day White
6348 6400k White

EAN Code

3800157621304
3800157621311
3800157621328



EQ. Watts:	110W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	1500lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø225mm x 25mm
CRI:	>80	Cutting Size:	Ø205mm
PF:	> 0.6		




Round Chrome

24W VT-2407CH

6352 3000k Warm White
6353 4000K Day White
6354 6400k White

EAN Code

3800157621366
3800157621373
3800157621380



EQ. Watts:	145W	Beam Angle:	120°
Voltage/Frequency:	AC:200-240V,50Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	2000lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø300mm x 25mm
CRI:	>80	Cutting Size:	Ø285mm
PF:	>0.9		




Round-Satin Nickel

6W VT-607SN

6337 3000k Warm White
6338 4000K Day White
6339 6400k White

EAN Code

3800157621212
3800157621229
3800157621236



EQ. Watts:	40W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	420lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø120mm x 25mm
CRI:	>80	Cutting Size:	Ø105mm
PF:	> 0.5		




Round-Satin Nickel

12W VT-1207SN

6343 3000k Warm White
6344 4000K Day White
6345 6400k White

EAN Code

3800157621274
3800157621281
3800157621298



EQ. Watts:	75W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	1000lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø170mm x 25mm
CRI:	>80	Cutting Size:	Ø155mm
PF:	> 0.6		




Round-Satin Nickel

18W VT-1807SN

6349 3000k Warm White
6350 4000K Day White
6351 6400k White

EAN Code

3800157621335
3800157621342
3800157621359



EQ. Watts:	110W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	1500lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø225mm x 25mm
CRI:	>80	Cutting Size:	Ø205mm
PF:	> 0.6		




Round-Satin Nickel

24W VT-2407SN

6355 3000k Warm White
6356 4000K Day White
6357 6400k White

EAN Code

3800157621397
3800157621403
3800157621410



EQ. Watts:	145W	Beam Angle:	120°
Voltage/Frequency:	AC:200-240V,50Hz	Body Type:	Aluminum+PMMA+PS
Luminous Flux:	2000lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø300mm x 25mm
CRI:	>80	Cutting Size:	Ø285mm
PF:	>0.7		




Round Chrome

6W VT-605CH

6358 3000k Warm White
6359 4000K Day White
6360 6400k White

EAN Code

3800157621427
3800157621434
3800157621441



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	420lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø90mm x 24mm




Round Chrome

12W VT-1205CH

6364 3000k Warm White
6365 4000K Day White
6366 6400k White

EAN Code

3800157621489
3800157621496
3800157621502



EQ. Watts:	60W	PF:	>0.6
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	1000lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø140mm x 24mm




Round Chrome

18W VT-1805CH

6370 3000k Warm White
6371 4000K Day White
6372 6400k White

EAN Code

3800230629876
3800230629883
3800230629890



EQ. Watts:	75W	PF:	>0.6
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	1500lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø190mm x 24mm




Round-Satin Nickel

6W VT-605SN

6361 3000k Warm White
6362 4000K Day White
6363 6400k White

EAN Code

3800157621458
3800157621465
3800157621472



EQ. Watts:	35W	PF:	>0.5
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	420lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø90mm x 24mm




Round-Satin Nickel

12W VT-1205SN

6367 3000k Warm White
6368 4000K Day White
6369 6400k White

EAN Code

3800157621519
3800157621526
3800157621533



EQ. Watts:	60W	PF:	>0.6
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	1000lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø140mm x 24mm




Round-Satin Nickel

18W VT-1805SN

6373 3000k Warm White
6374 4000K Day White
6375 6400k White

EAN Code

3800157621571
3800157621588
3800157621595



EQ. Watts:	75W	PF:	>0.6
Voltage/Frequency:	AC:85-265V,50/60Hz	Beam Angle:	120°
Luminous Flux:	1500lm	Body Type:	Aluminum
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø190mm x 24mm

**LED Panel****8W** VT-809 SQ

4922 3000K Warm White

4923 4000K Day White


4924 6400K White

EAN Code

3800157605564

3800157605571


3800157605588



Twin LED

Surface
Mounted

EQ. Watts:	24W	PF:	>0.9
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	800lm	Body Type:	PKW
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	150 x 150 x 40mm

**LED Panel****15W** VT-1509 SQ

4925 3000K Warm White

4926 4000K Day White


4927 6400K White

EAN Code

3800157605595

3800157605601


3800157605618



Twin LED

Surface
Mounted

EQ. Watts:	45W	PF:	>0.9
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	1500lm	Body Type:	PKW
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	200 x 200 x 40mm

**LED Panel****22W** VT-2209 SQ

4928 3000K Warm White

4929 4000K Day White


4930 6400K White

EAN Code

3800157605625

3800157605632

3800157605649



Twin LED

Surface
Mounted


EQ. Watts:	66W	PF:	>0.9
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	2200lm	Body Type:	PKW
LED Type:	SMD	Shape:	Square
CRI:	>80	Dimension:	240 x 240 x 40mm

**LED Panel****8W** VT-809

4890 3000K Warm White
4891 4000K Day White
4892 6400K White

EAN Code

3800157602594
3800157602600
3800157602617




EQ. Watts:	24W	PF:	>0.9
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	800lm	Body Type:	PKW
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø150mm x 40mm

**LED Panel****15W** VT-1509

4893 3000K Warm White
4894 4000K Day White
4895 6400K White

EAN Code

3800157602624
3800157602631
3800157602648




EQ. Watts:	45W	PF:	>0.9
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	1500lm	Body Type:	PKW
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø200mm x 40mm

**LED Panel****22W** VT-2209

4896 3000K Warm White
4897 4000K Day White
4898 6400K White

EAN Code

3800157602655
3800157602662
3800157602679



EQ. Watts:	66W	PF:	>0.9
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	2200lm	Body Type:	PKW
LED Type:	SMD	Shape:	Round
CRI:	>80	Dimension:	Ø240mm x 40mm




LED Panel

6W VT-602G RD

4740 3000K Warm White
6277 4000K Day White
4739 6400K White

EAN Code

3800230622891
3800157615754
3800230622884



EQ. Watts:	45W	Beam Angle:	120°
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Body Type:	Glass+Aluminum
Luminous Flux:	420lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø100mm x40mm
CRI:	>80	Cutting Size:	Ø75mm
PF:	>0.5		




LED Panel

12W VT-1202G RD

4744 3000K Warm White
6279 4000K Day White
4743 6400K White

EAN Code

3800230622938
3800157615778
3800230622921



EQ. Watts:	75W	Beam Angle:	120°
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Body Type:	Glass+Aluminum
Luminous Flux:	840lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø160mm x40mm
CRI:	>80	Cutting Size:	Ø120mm
PF:	> 0.5		




LED Panel

18W VT-1881G RD

4760 3000K Warm White
6281 4000K Day White
4759 6400K White

EAN Code

3800230622976
3800157615792
3800230622969



EQ. Watts:	95W	Beam Angle:	120°
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Body Type:	Glass+Aluminum
Luminous Flux:	1260lm	Shape:	Round
LED Type:	SMD	Dimension:	Ø198mm x40mm
CRI:	>80	Cutting Size:	Ø145mm
PF:	> 0.5		




LED Panel

6W VT-602G SQ

4738 3000K Warm White
6276 4000K Day White
4737 6400K White

EAN Code

3800230622877
3800157615761
3800230622860



EQ. Watts:	45W	Beam Angle:	120°
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Body Type:	Glass+Aluminum
Luminous Flux:	420lm	Shape:	Round
LED Type:	SMD	Dimension:	100 x 100 x 40mm
CRI:	>80	Cutting Size:	75mm x 75mm
PF:	>0.5		




LED Panel

12W VT-1202G SQ

4742 3000K Warm White
6278 4000K Day White
4741 6400K White

EAN Code

3800230622914
3800157615761
3800230622907



EQ. Watts:	75W	Beam Angle:	120°
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Body Type:	Glass+Aluminum
Luminous Flux:	840lm	Shape:	Round
LED Type:	SMD	Dimension:	160 x 160 x 40mm
CRI:	>80	Cutting Size:	120mm x 120mm
PF:	> 0.5		




LED Panel

18W VT-1881G SQ

4746 3000K Warm White
6280 4000K Day White
4745 6400K White

EAN Code

3800230622952
3800157615785
3800230622945



EQ. Watts:	95W	Beam Angle:	120°
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Body Type:	Glass+Aluminum
Luminous Flux:	1260lm	Shape:	Round
LED Type:	SMD	Dimension:	198x 198 x 40mm
CRI:	>80	Cutting Size:	145mm x 145mm
PF:	> 0.5		



LED Highbays

Designed to provide drastic reductions in both energy consumption and maintenance requirements, V-TAC's LED High Bay Series provide uniform light with no dark patches and good colour rendering. Available models 50W - 200W

Product Features

- Powerful LED light source with a unique design
- Extensive Options can replace all types of Standard MH High bays
- Aluminium Diffuser with multiple Beam Angle's to choose from 45°D / 90°D / 120°D
- Shatter Proof Perspex Lens
- High Thermal Conductivity, Low Luminous Decay, Pure Colours & No Heavy Shade
- The unique design of Radiator fuses with the Lamp Box perfectly hence diffuses the heat conduction efficiently which reduces the temperature of inside lamp & ensures the LED long life span
- Non - Flickering
- No UV Radiation

Applications

- Perfect fit for Industrial Usage, Warehouse & Super Markets, Workshop's, Factories, Warehouse's, Highway, toll Stations, Gas Stations, Malls, Exhibition Halls, Stadium's & other vast areas





120⁺⁺
LM/W
HIGH LUMENS

UFO Highbay
With Mean Well Driver

100W VT-9120

5550 4500K Day White
5551 6400k White


120°
BEAM ANGLE



EAN Code

3800157619714
3800157619721


IP65
RATED



A++

EQ. Watts:	800W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°
Luminous Flux:	12000lm	Body Type:	Diecast Aluminum
LED Type:	SMD	IP Rating:	IP65
CRI:	>70	Dimension:	ø280 x 162 mm

Luminous Intensity Distribution Curve



120⁺⁺
LM/W
HIGH LUMENS

UFO Highbay
With Mean Well Driver

150W VT-9170

5552 4500K Day White
5553 6400k White


120°
BEAM ANGLE



EAN Code

3800157619738
3800157619745


IP65
RATED



A++

EQ. Watts:	1200W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°
Luminous Flux:	18000lm	Body Type:	Diecast Aluminum
LED Type:	SMD	IP Rating:	IP65
CRI:	>70	Dimension:	ø360 x 168 mm

Luminous Intensity Distribution Curve





120⁺⁺
LM/W
HIGH LUMENS

120°
BEAM ANGLE

IP65
RATED

UFO Highbay


100W VT-9111

5543 4500K Day White
5544 6400K White


EAN Code

3800157610476
3800157610483

A++



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	900W	PF:	>0.9
Voltage/Frequency:	AC: 100-265V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	13500lm	Body Type:	Aluminum
LED Type:	SMD	IP Rating:	IP65
CRI:	> 70	Dimension:	Ø320mm x 149mm



120⁺⁺
LM/W
HIGH LUMENS

120°
BEAM ANGLE

IP65
RATED

UFO Highbay


150W VT-9166

5545 6400K White


EAN Code

3800157610490

A++



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts	1500W	PF	>0.9
Voltage/Frequency	AC: 100-277V, 50/60Hz	Beam Angle	120°
Luminous Flux	21750lm	Body Type	Aluminum
LED Type	SMD	IP Rating	IP65
CRI	>70	Dimension	Ø320mm x 149mm



120⁺⁺
LM/W
HIGH LUMENS

120°
BEAM ANGLE

60°
BEAM ANGLE

LED Highbay



50W VT-9052

5540 4500K Day White
5539 6000K White

EAN Code

3800157608831
3800157608824

A⁺⁺



EQ. Watts:	300W	PF:	> 0.9
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Beam Angle:	60°/120°
Luminous Flux:	6200lm	Body Type:	Aluminum Diecasting
LED Type:	SMD	IP Rating:	IP44
CRI:	>70	Dimension:	60°:348x 346mm 120°:445x 308mm



120⁺⁺
LM/W
HIGH LUMENS

120°
BEAM ANGLE

60°
BEAM ANGLE

LED Highbay



70W VT-9073

5535 4500K Day White
5536 6000K White

EAN Code

3800157608824
3800157608831

A⁺⁺



EQ. Watts:	630W	PF:	> 0.9
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Beam Angle:	60°/120°
Luminous Flux:	8680lm	Body Type:	Aluminum Diecasting
LED Type:	SMD	IP Rating:	IP44
CRI:	>70	Dimension:	60°:348x 346mm 120°:445x 308mm



120⁺⁺
LM/W
HIGH LUMENS

120°
BEAM ANGLE

60°
BEAM ANGLE

LED Highbay


100W VT-9104

5534 4500K Day White
5532 6000K White


EAN Code

3800157608725
3800157607780

A++



Luminous Intensity Distribution Curve



EQ. Watts:	900W	PF:	> 0.9
Voltage/Frequency:	AC: 100-265V, 50/60Hz	Beam Angle:	90°/120°
Luminous Flux:	12000lm	Body Type:	Aluminum
LED Type:	SMD	IP Rating:	IP44
CRI:	> 70	Dimension:	90°:428x 345mm 120°:535x 306mm



120⁺⁺
LM/W
HIGH LUMENS

120°
BEAM ANGLE

60°
BEAM ANGLE

LED Highbay


150W VT-9155

5537 4500K Day White
5538 6000K White


EAN Code

3800157608848
3800157608855

A++



Luminous Intensity Distribution Curve



EQ. Watts:	1350W	PF:	>0.9
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Beam Angle	90°/120°
Luminous Flux:	18600lm	Body Type	Aluminum Diecasting
LED Type:	SMD	IP Rating	IP44
CRI:	>70	Dimension	90°:428 x 345mm 120°:535 x 306mm




UFO Highbay

50W VT-9053

5554 4500K Day White
5555 6400K White

EAN Code

3800157620895
3800157620901



EQ. Watts:	250w	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°
Luminous Flux:	4000lm	Body Type:	Diecast Aluminum
LED Type:	SMD	IP Rating:	IP44
CRI:	>70	Dimension:	ø221x 85 mm




UFO Highbay

100W VT-9106

5546 4500K Day White
5547 6400K White

EAN Code

3800157619677
3800157619684



EQ. Watts:	500W	PF:	>70
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	120°
Luminous Flux:	8000lm	Body Type:	Diecast Aluminum
LED Type:	SMD	IP Rating:	IP44
CRI:	>70	Dimension:	ø280 x 91 mm




UFO Highbay

150W VT-9156

5548 4500K Day White
5549 6400K White

EAN Code

3800157619691
3800157619707



EQ. Watts:	800W	PF	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle	120°
Luminous Flux:	12000lm	Body Type	Diecast Aluminum
LED Type:	SMD	IP Rating	IP44
CRI:	>70	Dimension	ø360 x 98 mm



E40
HOLDER

LED LOWBAY

85W VT-9185
5541 4500K Day White
5542 6000K White





EAN Code
3800157610001
3800157610018

- Warehouses, shipping docks, stairwells and parking garages.
- Lightweight, Compact structure
- Indoor and outdoor
- Replacement of 500W CFL

EQ. Watts:	500W	PF:	> 0.9
Voltage/Frequency:	AC: 220-240V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	6800lm	Body Type:	Aluminum
LED Type:	SMD	IP Rating:	IP20
CRI:	> 80	Dimension:	222mm x 270mm

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM






UFO
SHAPE

LED HIGHBAYS

120⁺⁺
LM/W
HIGH LUMENS



HIGH POWER
SMD



LED Street Lights

Light the path to the future with LED Street Lights. This state of the art LED Technology provides uniform Brightness and Illumination. No mercury means they are environmentally friendly

Product Features

- Perfect replacement for traditional lights
- Saves 80% Electricity cost, Better Efficiency, Longer Life Span
- Dedicated IP65 Sealed Optical Cavities
- Optically Optimized Glass Lenses
- Uniformity in Light Distribution – Maximizes Efficiency
- Fully Operational in Extreme Weather up to -20° Celsius
- Low maintenance & Low Power consumption
- Reduced CO² emissions



Applications

- Out Door Applications like Streets, Projects, Cross Roads, Tunnels, Car Parks, Industrial Facilities etc




LED Street Light

30W VT-15135ST
5480 6000K White


120⁺⁺ LM/W
HIGH LUMENS



EAN Code
3800157616164



Luminous Intensity Distribution Curve




LED Street Light

50W VT-15165ST
5482 6000K White


120⁺⁺ LM/W
HIGH LUMENS



EAN Code
3800157616168



Luminous Intensity Distribution Curve



EQ. Watts:	450W	Beam Angle:	100°
Voltage/Frequency:	AC:100-240V, 50/60Hz	Color of Fixture:	Black/Grey
Luminous Flux:	6200lm	Body Type:	Aluminum Diecasting
LED Type:	SMD	IP Rating:	IP65
CRI:	>70	Dimension:	477 x 220 x 55mm
PF:	>0.95		





LED Street Light

100W VT-15115ST
5481 6000K White

120⁺⁺ lm/W
HIGH LUMENS



EAN Code
3800157616171



EQ. Watts:	900W	Beam Angle:	100°
Voltage/Frequency:	AC:100-240V, 50/60Hz	Color of Fixture:	Black/Grey
Luminous Flux:	12400lm	Body Type:	Aluminum Diecasting
LED Type:	SMD	IP Rating:	IP65
CRI:	>70	Dimension:	566 x 268 x 62mm
PF:	>0.95		



LED Street Light

30W VT-15131ST


5471 3000K Warm White
5472 4500K Day White
5473 6000K White

120⁺⁺
LM/W
HIGH LUMENS



EAN Code

3800157608732
3800157608749
3800157608756



EQ. Watts:	270W	Beam Angle:	100°
Voltage/Frequency:	AC:100-240V, 50/60Hz	Color of Fixture:	Black/Grey
Luminous Flux:	3720lm	Body Type:	Aluminum Diecasting
LED Type:	SMD	IP Rating:	IP65
CRI:	>70	Dimension:	400 x 180 x 55mm
PF:	>0.95		



LED Street Light

50W VT-15151ST


5474 3000K Warm White
5475 4500K Day White
5476 6000K White

120⁺⁺
LM/W
HIGH LUMENS



EAN Code

3800157608763
3800157608770
3800157608787



EQ. Watts:	450W	Beam Angle:	100°
Voltage/Frequency:	AC:100-240V, 50/60Hz	Color of Fixture:	Black/Grey
Luminous Flux:	6200lm	Body Type:	Aluminum Diecasting
LED Type:	SMD	IP Rating:	IP65
CRI:	>70	Dimension:	477 x 216 x 55mm
PF:	>0.95		



LED Street Light

100W VT-15105ST


5477 4500K Day White
5478 6000K White

120⁺⁺
LM/W
HIGH LUMENS



EAN Code

3800157608794
3800157608800



EQ. Watts:	900W	Beam Angle:	100°
Voltage/Frequency:	AC:100-240V, 50/60Hz	Color of Fixture:	Black/Grey
Luminous Flux:	12400lm	Body Type:	Aluminum Diecasting
LED Type:	SMD	IP Rating:	IP65
CRI:	>70	Dimension:	566 x 268 x 62mm
PF:	>0.95		



LED Street Light



100W VT-15104 ST

5468 6000K White

120⁺⁺ LM/W
HIGH LUMENS

EAN Code

3800157607797



LED Street Light



120W VT-15121ST

5479 6000K White

120⁺⁺ LM/W
HIGH LUMENS

EAN Code

3800157608817



LED Street Light

Adapter

VT-795


EAN Code

3624

3800157608152

Color: **Dark grey**

Body: **Diecast Aluminium**



Total length= 325mm

Lower part inner = Ø65mm


Outer = Ø85mm.

Length of lower part = 215mm

Length of upper part = 185mm.



Compatible with all our street light models, this adapter allows the angle of the streetlight to be adjusted as per client's requirements





LED Strip Lights

Add an extensive array of lights and colors to any setting or interior, rejuvenate and transform the ambience of any environment at the flick of a switch with V-TAC's LED Strip Light Series. Easy installation with minimal space requirement makes this the right choice for Restaurants, Auditoriums and Meeting Rooms etc.

Product Features

- LED strip is a low Voltage flexible Ribbon available in DC:12V
- Flexible & easy installation
- Exceptionally low power consumption
- Multiple visual effects in unending colours and shades
- Available in DC:12V and 220V with different color range from Warm White to RGB
- Available in IP20 and IP65 rating
- Available in 8mm or 10mm width
- Available in 1 or 1.5 meter rigid bar options with different options of Aluminium Profiles



Applications

- Ideal for illuminating Borders, Edges, Cabinets, Bars and any area with limited space for installation.



3000lm/m
HIGH LUMENS

CRI >80

240
LED/M

IP20
RATED

5M ROLL



2835-NON WP | 240 LED/M

A++

18W 2835-NON WP

EAN Code

2164 3000K Warm White
2165 4500K Day White
2166 6000K White

3800157610117
3800157610124
3800157610131

LED Type:	2835	lm/M:	3000lm
Watt/M:	18W	lm/LED:	20-22 lm
Current/M:	1.5A	Beam Angle:	120°
Voltage:	DC:12V	IP Rating:	IP20
LED Qty:	240	Width:	10mm



CRI >80

204
LED/M

IP20
RATED

5M ROLL



2835-NON WP | 204 LED/M

A+

18W 2835-NON WP

EAN Code

2461 3000K Warm White
2462 4500K Day White
2463 6000K White

3800157612234
3800157612241
3800157612258

LED Type:	2835	lm/M:	1700lm
Watt/M:	18W	lm/LED:	9-11 lm
Current/M:	1.5A	Beam Angle:	120°
Voltage:	DC:12V	IP Rating:	IP20
LED Qty:	204	Width:	8mm



3000lm/m
HIGH LUMENS

CRI >95

120
LED/M

IP20
RATED

5M ROLL

5730-NON WP | 120 LED/M **A++**

18W 5730-NON WP

- 2162 3000K Warmwhite
- 2163 4500K Day White
- 2161 6000K White

EAN Code
3800157610094
3800157610100
3800157610087

LED Type:	5730	lm/M:	3000lm
Watt/M:	18W	lm/LED:	20-22 lm
Current/M:	1.5A	Beam Angle:	120°
Voltage:	DC:12V	IP Rating:	IP20
LED Qty:	120	Width:	8mm



30 LED/M **A+**
4.8W 5050 - WP

500
lm/M



LED Type:	5050	Color:	SKU Code:	EAN Code:
Watt/M:	4.8W	White	2144	3800230621399
Current/M:	0.4A	Warm White	2145	3800230621412
Voltage:	DC:12V	Day White	2460	3800157612166
LED Qty:	30	Red	2129	3800157619974
lm/LED:	14lm-16lm	RGB	2118	3800230621528
Beam Angle:	120°			
IP Rating:	IP65			
Width:	10mm			



30 LED/M **A+**
4.8W 5050 - NON WP

500
lm/M




LED Type:	5050	Color:	SKU Code:	EAN Code:
Watt/M:	4.8W	White	2133	3800230621382
Current/M:	4A	Warm White	2135	3800230621405
Voltage:	DC: DC:12V	RGB	2124	3800230621535
LED Qty:	30			
lm/LED:	14lm-16lm			
Beam Angle:	120°			
IP Rating:	IP20			
Width:	10mm			



60 LED/M **A+**
9.6W 5050 - WP



LED Type:	5050	Color:	SKU Code:	EAN Code:
Watt/M:	10.8W	White	2148	3800230621498
Current/M:	0.8A	Warm White	2149	3800230621511
Voltage:	DC:12V	Day White	2150	3800230621474
LED Qty:	60	Red	2152	3800230624775
lm/LED:	14lm-16lm	Green	2153	3800230621450
Beam Angle:	120°	Blue	2151	3800230621436
IP Rating:	IP65	RGB	2155	3800230621559
Width:	10mm			



60 LED/M **A+**
9.6W 5050 - NON WP



LED Type:	5050	Color:	SKU Code:	EAN Code:
Watt/M:	10.8W	White	2126	3800230621481
Current/M:	0.8A	Warm White	2122	3800230621504
Voltage:	DC:12V	Day White	2143	3800230621467
LED Qty:	60	Red	2128	3800230624468
lm/LED:	14lm-16lm	Green	2138	3800230621443
Beam Angle:	120°	Blue	2137	3800230621429
IP Rating:	IP20	Yellow	2156	3800230628824
Width:	10mm	RGB	2120	3800230621542



60 LED/M **A+**
3.6W 3528 - WP

400 lm/M **IP65**
RATED



LED Type:	3528	Color:	SKU Code:	EAN Code:
Watt/M:	3.6W	White	2031	3800230621146
Current/M:	0.3A	Warm White	2032	3800230621177
Voltage:	DC:12V	Day White	2043	3800230621191
LED Qty:	60	Red	2036	3800230621276
lm/LED:	5lm -6lm	Green	2034	3800230621238
Beam Angle:	120°	Blue	2035	3800230621245
IP Rating:	IP65	Yellow	2033	3800230621207
Width:	8mm			



60 LED/M **A+**
3.6W 3528 - NON WP

400 lm/M **IP20**
RATED



LED Type:	3528	Color:	SKU Code:	EAN Code:
Watt/M:	3.6W	White	2005	3800230621153
Current/M:	0.3A	Warm White	2016	3800230621160
Voltage:	DC:12V	Day White	2041	3800230621184
LED Qty:	60	Red	2015	3800230621269
lm/LED:	5lm -6lm	Green	2011	3800230621221
Beam Angle:	120°	Blue	2013	3800230621252
IP Rating:	IP20	Yellow	2009	3800230621214
Width:	8mm			



120 LED/M **A+**
7.2W 3528 - WP



LED Type:	3528	Color:	SKU Code:	EAN Code:
Watt/M:	7.2W	White	2037	3800230621290
Current/M:	0.6A	Warm White	2038	3800230621313
Voltage:	DC:12V	Day White	2044	3800230621337
LED Qty:	120	Red	2039	3800230621375
lm/LED:	5lm -6lm	Blue	2027	3800230621351
Beam Angle:	120°			
IP Rating:	IP65			
Width:	8mm			



120 LED/M **A+**
7.2W 3528 - NON WP



LED Type:	3528	Color:	SKU Code:	EAN Code:
Watt/M:	7.2W	White	2002	3800230621283
Current/M:	0.6A	Warm White	2025	3800230621306
Voltage:	DC:12V	Day White	2042	3800230621320
LED Qty:	120	Red	2030	3800230621368
lm/LED:	5lm -6lm			
Beam Angle:	120°			
IP Rating:	IP20			
Width:	8mm			



204 LED/M **A+**
18W 3014 - NON WP

1700
lm/M



LED Type:	3014	Color:	SKU Code:	EAN Code:
Watt/M:	18W	White	2403	3800230628053
Current/M:	1.5A	Warm White	2404	3800230628060
Voltage:	DC:12V	Day White	2405	3800157600309
LED Qty:	204			
lm/LED:	9-11lm			
Beam Angle:	120°			
IP Rating:	IP20			
Width:	10mm			



60 LED/M **A+**
10.8W 5050 - NON WP

900
lm/M



LED Type:	5050	Color:	SKU Code:	EAN Code:
Watt/M:	10.8W	RGB	2159(RGB+W)	3800230629623
Current/M:	1.2A			
Voltage:	DC:12V			
LED Qty:	30:30			
lm/LED:	15lm			
Beam Angle:	120°			
IP Rating:	IP20			
Width:	10mmaa			



60 LED/M **A+**
9W 5050 - NON WP




600
LED/M




LED Type:	5050	Color:	SKU Code:	EAN Code:
Watt/M:	9W	White	2430	3800230621566
Current/M:	0.3A	Warm White	2431	3800230621573
Voltage:	DC:24V	Day White	2459	3800157612036
LED Qty:	60			
lm/LED:	14lm-16lm			
Beam Angle:	120°			
IP Rating:	IP20			
Width:	10mm			



INTRODUCING
LED NEON FLEX



Model No:	VT-555	VT-555	VT-555
SKU Code:	2512	2513	2514
Color / Temperature:	White	Warm White	Day White
Lumen lm/M:	320±5%	320±5%	320±5%
FPC Width MM:	7.5	7.5	7.5
Power W/M:	8-10W	8-10W	8-10W
Jacket Dia:	9 x16.5 mm	9 x16.5 mm	9 x16.5 mm
EAN Code:	3800157605656	3800157605663	3800157605670



Model No:	VT-555	VT-555	VT-555
SKU Code:	2515	2516	2517
Color / Temperature:	Blue	RED	Green
Lumen lm/M:	320±5%	320±5%	320±5%
FPC Width MM:	7.5	7.5	7.5
Power W/M:	8-10	8-10	8-10
Jacket Dia:	9 x16.5 mm	9 x16.5 mm	9 x16.5 mm
EAN Code:	3800157605687	3800157605694	3800157605700



Model No:	VT-555	VT-555	VT-555
SKU Code:	2518	2529	2531
Color / Temperature:	Yellow	Pink	Violet
Lumen lm/M:	320±5%	320±5%	320±5%
FPC Width MM:	7.5	7.5	7.5
Power W/M:	8-10	8-10	8-10
Jacket Dia:	9 x16.5 mm	9 x16.5 mm	9 x16.5 mm
EAN Code:	3800157605717	3800157619523	3800157619547



Item:	Profile
SKU Code:	2527
EAN Code:	3800157608404



Item:	Power cord without plug	Pin	End safe cap
SKU Code:	3331	3333	3334
EAN Code:	3800157608268	3800157607889	3800157607896



LED Strip Sets

PLUG AND PLAY

LED STRIP LIGHT set is a complete kit where we provide you with 5 meters of LED STRIP LIGHT ,along with the POWER SUPPLY and CONNECTOR and REMOTE CONTROL (optional) ,to make it a complete kit . Available and made in different colour options as per requirement.






- LED Strip
- Remote control (included)
- Driver (included)
- Packing: Blister Pack, 5 meters roll

SKU Code:	Description:	EAN Code:
2351	LED Strip Set SMD3528 60 LEDs 4500K IP20	3800230621634
2350	LED Strip Set SMD5050 30 LEDs RGB IP20	3800230621641
2352	LED Strip Set SMD5050 30 LEDs RGB IP65	3800230621658
2353	LED Strip Set SMD5050 60 LEDs RGB IP20	3800230621665
2354	LED Strip Set SMD5050 60 LEDs RGB IP65	3800230621672
2355	LED Strip Set SMD5050 60 LEDs White IP20	3800230621689
2356	LED Strip Set SMD5050 60 LEDs White IP65	3800230621696

LED Strip ACCESSORIES







SKU Code:	Description:	EAN Code:
3500	Flexible Connector - LED Strip 3528	3800230622051
3501	Flexible Connector - LED Strip 5050	3800230622068
3502	Flexible Connector - LED Strip 5050 RGB	3800230622075
3503	Connector - LED Strip 3528	3800230622082
3504	Connector - LED Strip 5050	3800230622099
3505	Connector - LED Strip 5050 RGB	3800230622105
3507	Flexible Connector - LED Strip 3528 DC Female	3800230622112
3508	Flexible Connector - LED Strip 5050 DC Female	N/A
3509	Connector - LED Strip 3528 Cross Type	N/A
3510	Connector - LED Strip 5050 Cross Type	N/A
3511	Connector - LED Strip 5050 L Type	N/A
3512	Connector - LED Strip DC Female	N/A








Aluminum Profiles

Model No:	VT-7101	VT-7101	VT-7102
SKU Code	9981	9982	9983
Dimension:	16.76 x 10.3 x 1000 mm	16.76 x 10.3 x 1000 mm	16.9 x 12.48 x 1000 mm
Color of Fixture:	Transparent	Matt	Transparent
EAN Code:	3800230622129	3800230622136	3800230622143







Aluminum Profiles

Model No:	VT-7102	VT-7103	VT-7104
SKU Code	9984	Transparent: 9985 / Matt : 9986	9987
Dimension:	16.9 x 12.48 x 1000 mm	26.5 x 9 x 1000 mm	19 x 19 x 1000 mm
Color of Fixture:	Matt	Transparent / Matt	Matt
EAN Code:	3800230622150	Transparent : 3800230622167 Matt: 3800230622174	3800230622181



Aluminum Profiles

Model No:	VT-7105	VT-7105	VT-7109
SKU Code	9990	9991	9947
Dimension:	24.6 x 7.85 x 1000 mm	24.6 x 7.85 x 2000 mm	22x17x1000mm
Color of Fixture:	Milky	Milky	Milky
EAN Code:	3800230628077	3800230628794	3800157617208



Aluminum Profiles

Model No:	VT-7106	VT-7107	VT-7108
SKU Code	1000mm:9992 / 2000mm: 9993	9994	9995
Dimension:	17.5 x 7.8 x1000 / 2000 mm	60 x 35.1 x 1000 mm	ø20.54 x 1000 mm
Color of Fixture:	Milky / Milky	Milky	Milky
EAN Code:	1000mm : 3800230628800 2000mm : 3800230628817	3800157601399	3800157601405



Strip Controllers

SKU Code:	3300	3303	3304
Model No:	VT-2402	VT-2404	VT-2401
Description:	Dimmer for LED Strip with Remote Control	Radio Controller with Remote Control 4 Buttons	Infrared Controller with Remote Control 24 Buttons
Max Current /Watt:	8A, 96W	12A, 144W	6A, 72W
Input Voltage:	DC 12/24 V	DC 12/24 V	DC 12/24 V
Size:	115 x 55 x 35 mm	105 x 65 x 20 mm	65 x 35 x 22 mm
EAN Code:	3800230622198	3800230622204	3800230622211



Strip Controllers

SKU Code:	3307	3312	3317
Model No:	VT- DMX 512	VT-2405	VT-2401
Description:	DMX 512 Controller	Radio Controller with Touch Remote Control	Infrared Controller with Remote Control 44 Buttons
Max Current /Watt:	4A x3, 360W	3A x4, 144W	6A, 72W
Input Voltage:	DC:12V	DC 12/24 V	DC 12/24 V
Size:	165 x 75 x 25 mm	130 x 65 x 25 mm	125 x 56 x 7 mm
EAN Code:	3800230622266	3800230622273	3800230622228



Strip Controllers

SKU Code:	3625	3318	3320
Model No:	VT-2472	N/A	N/A
Description:	Infrared Controller with Remote Control 24 Buttons	Radio Controller with Remote Control	Mini RF Controller
Max Current /Watt:	6A, 72W	500W	N/A
Input Voltage:	DC 12/24 V	DC:12V	DC:12V
Size:	N/A	120 x 75 x 25 mm	N/A
EAN Code:	3800157609920	3800230622235	3800230628022



Strip Controllers

SKU Code:	3319	3321	3663
Model No:	N/A	N/A	VT-2410
Description:	24B Mini Controller	Wi-Fi Single Controller	Wi-Fi Single Controller
Max Current /Watt:	N/A	N/A	6A 216W/432W
Input Voltage:	DC:12V	DC:12V	DC 12/24 V
EAN Code:	3800230628015	3800230628039	3800157619509



Strip Controllers

SKU Code:	3322	3326	3327
Description:	Wi-Fi RGB Controller	5050 60 RGB with LED Controller	RGB+W Amplifier
Input Voltage:	DC:12V	DC:12V	DC:12V
EAN Code:	3800230628046	3800230629630	3800157601047



Strip Controllers

SKU Code:	3328	3009	3018
Description:	360W RF Controller	5050 RGB Strip Amplifier	5050 RGB Strip Mini-Amplifier
Input Voltage:	DC:12V	DC:12V	DC:12V
EAN Code:	3800157601054	3800230622259	3800230622242



Complete range of modules for
SIGNAGE INDUSTRY

Model No:	VT-50503
Watts:	0.72W/PC
Lumens:	66lm/PC
Beam Angle:	160 °
CRI:	75
Voltage/Frequency:	DC:12V
Unit Size:	67 x 15 x 8.5mm
IP Rating:	IP67
Material:	ABS + PCB

SKU Code:	EAN Code:
WHITE: 5116	3800157610209
RED: 5117	3800157610216
BLUE: 5118	3800157610223
BLACK: 5119	3800157610230



Model No:	VT-28353
Watts:	1W/PC
Lumens:	100lm/PC
Beam Angle:	120 °
CRI:	75
Voltage/Frequency:	DC:12V
Unit Size:	53x12x4.6mm
IP Rating:	IP67
Material:	ABS+Aluminum Plate

SKU Code:	EAN Code:
WHITE: 5120	3800157610247
RED: 5121	3800157610254
BLUE: 5122	3800157610261
GREEN: 5123	3800157610278





Model No:	VT-28356
Watts	1.5
Voltage/Frequency	DC 12V
Luminous Flux	120-150lm
LED Type	SMD2835
CRI	75
Beam Angle	120°
Color of Fixture	White
Body Type	ABS+Aluminium
Dimension	87 x 15 x 10mm
IP Rating	IP67

SKU Code:	EAN Code:
WARM WHITE: 5124	3800157621687
WHITE: 5125	3800157621694
RED: 5126	3800157621700
BLUE: 5127	3800157621717
GREEN: 5128	3800157621724



Model No:	VT-28358
Watts	1.44
Voltage/Frequency	DC 12V
Luminous Flux	120-135lm
LED Type	SMD2835
CRI	75
Beam Angle	160°
Color of Fixture	White
Body Type	ABS+Aluminium
Dimension	37x 37 x 6.8mm
IP Rating	IP68

SKU Code:	EAN Code:
WARM WHITE: 5129	3800157621731
WHITE: 5130	3800157621748
RED: 5131	3800157621755
BLUE: 5132	3800157621762
GREEN: 5133	3800157621779



Model No:	VT-50501
Watts	0.24
Voltage/Frequency	DC 12V
Luminous Flux	20-22lm
LED Type	SMD5050
CRI	75
Beam Angle	120°
Body Type	PVC
IP Rating	IP68

SKU Code:	EAN Code:
WARM WHITE: 5135	3800157621793
WHITE: 5136	3800157621809
RED: 5137	3800157621816
YELLOW: 5138	3800157621823
BLUE: 5139	3800157621830
GREEN: 5140	3800157621847



Model No:	VT-50506
Watts	0.72
Voltage/Frequency	DC 12V
Luminous Flux	20-22lm
LED Type	SMD5050
CRI	75
Beam Angle	120°
Body Type	ABS + PCB
Dimension	68 x 19.5 x 5.7mm
IP Rating	IP67

SKU Code:	EAN Code:
RGB: 5134	3800157621786

LED Strip Power Supply

Metal Driver (SMPS) Series

Product Features:

- Switching Metal Power Supply for all types of strip lights, led lighting , led display , etc
- With short circuit protection, over load protection , stable output voltage
- Built in EMI Filter
- High efficiency , low temperature
- 100% load tested
- Protection Rating : IP20
- CE, ROHS, EMC approved

Model:	SKU Code:	Watts	Current Capacity	Output	Unit Size	EAN Code:
VT-20025	3050	25W	2.1A	DC:12V	85x 58 x 34 mm	3800230621726
VT-20040	3058	40W	3.3A	DC:12V	108 x 78 x 35 mm	3800230625731
VT-20045	3051	45W	3.8A	DC:12V	110 x 78 x 35 mm	3800230621733
VT-20060	3052	60W	5A	DC:12V	110 x 78 x 36 mm	3800230621740
VT-20075	3053	75W	6A	DC:12V	160 x 98 x 38 mm	3800230621757
VT-20100	3060	100W	8.3A	DC:12V	199 x 98 x 42 mm	3800230625755
VT-20120	3054	120W	10A	DC:12V	160 x 98 x 42 mm	3800230621764
VT-20150	3055	150W	12.5A	DC:12V	199 x 98 x 42 mm	3800230621771
VT-20200	3061	200W	16.5A	DC:12V	200 x 110 x 50 mm	3800230625762
VT-20250	3056	250W	20A	DC:12V	200 x 110 x 50 mm	3800230621788
VT-20350	3057	350W	30A	DC:12V	215 x 115 x 50 mm	3800230621795
VT-20500	3062	500W	42A	DC:12V	215 x 115 x 50 mm	3800157608411

LED Strip Power Supply

Rainproof Power Supply Series

Product Features:

- RAIN PROOF DRIVER for all types of STRIP LIGHTS, LED LIGHTING, LED DISPLAY, etc.
- Industrial specifications and standards.
- With short circuit protection, over load protection and stable output voltage.
- Built in EMI Filter.
- High efficiency and low temperature.
- 100% load tested.
- Protection Rating: IP44
- CE, ROHS and EMC approved.



Model:	SKU Code:	Watts	Current Capacity	Output	Unit Size	EAN Code:
VT-21060	3070	60W	5A	DC:12V	155 x 105 x 50 mm	3800230621801
VT-21080	3069	80W	6.6A	DC:12V	155 x 105 x 50 mm	3800230621818
VT-21120	3071	120W	10A	DC:12V	195 x 115 x 53 mm	3800230621825
VT-21150	3072	150W	12.5A	DC:12V	195 x 115 x 53 mm	3800230621832
VT-21250	3073	250W	20A	DC:12V	233 x 153 x 66 mm	3800230621856
VT-21300	3081	300W	25A	DC:12V	233 x 153 x 66 mm	3800157601542
VT-21400	3074	400W	33A	DC:12V	233 x 153 x 66 mm	3800230621863
VT-21080	3075	80W	3.3A	DC:24V	155 x 105 x 50 mm	3800230621870
VT-21150	3076	150W	6.2A	DC:24V	195 x 115 x 53 mm	3800230621880
VT-21200	3078	200W	8.3A	DC:24V	233 x 153 x 66mm	3800230621849
VT-21400	3077	400W	16.6A	DC:24V	232 x 153 x 65 mm	3800230621894



LED Strip Power Supply

Waterproof Power Supply Series

Product Features:

LED STRIP LIGHT set is a complete kit where we provide you with 5 meters of LED STRIP LIGHT, along with the POWER SUPPLY and CONNECTOR and REMOTE CONTROL (optional), to make it a complete kit. Available and made in different colour options as per requirement.

- LED Strip
- Remote control (included)
- Driver (included)
- Packing: Blister Pack, 5 meters roll

Model:	SKU Code:	Watts	Current Capacity	Output	Unit Size	EAN Code:
VT-22030	3100	30W	2.5A	DC:12V	201 x 30.5 x 20 mm	3800230621900
VT-22045	3090	45W	3.75A	DC:12V	250 x 40 x 23 mm	3800230621917
VT-22060	3091	60W	5A	DC:12V	180 x 72 x 45 mm	3800230621924
VT-22100	3092	100W	8.5A	DC:12V	253 x 72 x 45 mm	3800230621931
VT-22120	3093	120W	10A	DC:12V	253 x 72 x 45 mm	3800230621948
VT-22150	3094	150W	12.5A	DC:12V	253 x 72 x 45 mm	3800230621955
VT-22200	3098	200W	16.6A	DC:12V	200 x 120 x 53 mm	3800230625779
VT-22300	3219	300W	25A	DC:12V	201 x 30.5 x 20 mm	3800157604932
VT-22360	3099	360W	30A	DC:12V	256 x 102 x 65 mm	3800230625786
VT-22020	3214	20W	0.83A	DC:24V	201 x 30.5 x 20 mm	3800230621962
VT-22030	3215	30W	1.25A	DC:24V	201 x 30.5 x 20 mm	3800230629562
VT-22045	3095	45W	1.88A	DC:24V	250 x 40 x 23 mm	3800230621979
VT-22101	3101	100W	4.2A	DC:24V	201 x 30.5 x 20 mm	3800157605991
VT-22150	3096	150W	6.25A	DC:24V	253 x 72 x 45 mm	3800230621986
VT-22200	3097	200W	8.3A	DC:24V	231 x 120 x 53 mm	3800230621993



LED STRIP POWER SUPPLY

Plastic Adaptor Series

Product Features:

- Plastic DRIVER for all types of STRIP LIGHTS, LED LIGHTING, LED DISPLAY, etc.
- With specifications and Industrial standards.
- With short circuit protection, over load protection and stable output voltage.
- Built in EMI Filter.
- High efficiency and low temperature.
- 100% load tested.
- Protection Rating: IP 20.
- CE, Rosh, EMC approved.
- Options available with BS STANDARD 3 PIN PLUG.


Model:	SKU Code:	Watts	Current Capacity	Output	Voltage / Frequency	EAN Code:
VT-23018	3017	18W	1.5A	DC:12V	AC 110-240V, 50/60Hz	3800230622006
VT-23002 W 1	3030	24W	2A	DC:12V	AC 85-240V, 50/60Hz	3800230625298
VT-23030	3007	30W	2.5A	DC:12V	AC 110-240V, 50/60Hz	3800230622013
VT-23042	3016	42W	3.5A	DC:12V	AC 110-240V, 50/60Hz	3800230622020
VT-23003 W 1	3031	42W	3.5A	DC:12V	AC 85-240V, 50/60Hz	3800230625304
VT-23060	3008	60W	5A	DC:12V	AC 110-240V, 50/60Hz	3800230622037
VT-23005 W 1	3032	60W	5A	DC:12V	AC 85-240V, 50/60Hz	3800230625311
VT-23080	3019	78W	6.5A	DC:12V	AC 110-240V, 50/60Hz	3800230622044



Plastic Adaptor Series (EMC Approved)



Model:	SKU Code:	Watts	Current Capacity	Output	Voltage / Frequency	EAN Code:
VT-23024	3036	24W	2A	DC:12V	AC 110-240V, 50/60Hz	3800157601474
VT-23024 W 1	3038	24W	2A	DC:12V	AC 110-240V, 50/60Hz	3800157601535
VT-23060	3035	60W	5A	DC:12V	AC 110-240V, 50/60Hz	3800157601085
VT-23060 W 1 W1	3037	60W	5A	DC:12V	AC 110-240V, 50/60Hz	3800157601528
VT-23078	3034	78W	6.5A	DC:12V	AC 110-240V, 50/60Hz	3800157601078



LED Track Lights

Perfect ecological alternative to Old Halogen Lights, Track lights are the extensive range of modern LED Track Lights! Delivering high performance, excellent durability and remarkable light output to serve the general Commercial and Retail market.

Product Features

- Available from 10W up to 45W
- Saves 80% energy
- No Ultraviolet or Infrared Rays
- Totally flexible, Compact & Adjustable design
- No Lead or Mercury content hence Environment friendly
- Provides Uniform Radiance & Enhances appeal of any environment.
- Enhances measurable levels of performance as compared to older versions of high wattage halogen & HID light sources in retail & Commercial Lighting applications.



Applications

- Perfect choice for Exhibition Stands, Hotels, Bars, Commercial & Residential Lighting.



COB Series

10W VT-4512



EAN Code

1332 3000k Warm White
1333 4000K Day White
1334 6400k White

3800157620604
3800157620611
3800157620628



EQ. Watts:	65W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	24°
Luminous Flux:	800lm	Color of Fixture:	Black + White
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>80		



Dimension=mm



COB Series

25W VT-4528



EAN Code



1335 3000k Warm White
1336 4000K Day White
1337 6400k White

3800157620635
3800157620642
3800157620659



EQ. Watts:	150W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	24°
Luminous Flux:	2100lm	Base:	Black + White
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>80		





COB Series

35W VT-4537

EAN Code

1338 3000k Warm White
1339 4000K Day White
1340 6400k White

3800157620666
3800157620673
3800157620680



EQ. Watts:	200W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	24°
Luminous Flux:	2850lm	Base:	Black + WHITE
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>80		



COB Series

15W VT-4615

1298 3000k Warm White
1299 4000K Day White
1300 6400k White



EAN Code

3800157619851
 3800157619868
 3800157619875

A+



EQ. Watts:	100W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	24°
Luminous Flux:	1350lm	Color of Fixture:	White
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>95	Dimension:	180 x 97 x 155mm



COB Series

15W VT-4615

1301 3000k Warm White
1302 4000K Day White
1303 6400k White



EAN Code

3800157619882
 3800157619899
 3800157619905

A+



EQ. Watts:	100W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	24°
Luminous Flux:	1350lm	Base:	Black
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>95	Dimension:	180 x 97 x 155mm





COB Series

30W VT-4635



1292 3000k Warm White
1293 4000K Day White
1294 6400k White

EAN Code

3800157619790
3800157619806
3800157619813



EQ. Watts:	200W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	24°
Luminous Flux:	2700lm	Color of Fixture:	White
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>95	Dimension:	180 x 140 x 215mm



COB Series

30W VT-4635



1295 3000k Warm White
1296 4000K Day White
1297 6400k White

EAN Code

3800157619820
3800157619837
3800157619844




EQ. Watts:	200W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50Hz	Beam Angle:	24°
Luminous Flux:	2700lm	Base:	Black
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>95	Dimension:	180 x 140 x 215mm





LUMINOUS INTENSITY DISTRIBUTION



SUITABLE FOR 4-LINE TRACKS

FITS INTO ANY EUROPEAN STANDARD 3-PHASE TRACK


4-Line Tracks

33W VT-4535

1233 3000K Warm White
1234 4000K Day White
1235 5000K White

EAN Code


3800157603720
3800157603737
3800157603744



Eq. Watts:	100W	PF:	> 0.9
Voltage/Frequency:	AC: 100-240V,50/60Hz	Beam Angle:	25°
Luminous Flux:	1800lm	Color of Fixture:	Black
LED Type:	SMD	Body Type:	Die Cast Aluminum
CRI:	> 95	Dimension:	112 x 165 x 205mm



LUMINOUS INTENSITY DISTRIBUTION



SUITABLE FOR 4-LINE TRACKS

FITS INTO ANY EUROPEAN STANDARD 3-PHASE TRACK


4-Line Tracks

45W VT-4545

1236 3000K Warm White
1237 4000K Day White
1238 5000K White

EAN Code

3800157603751
3800157603768
3800157603775




Eq. Watts:	135W	PF:	>0.9
Voltage/Frequency:	AC: 100-240V,50/60Hz	Beam Angle:	25°
Luminous Flux:	2300lm	Base:	Black
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>95	Dimension:	112 x 165 x 218mm



4-LINE TRACK

23W VT-4521T
1202 5000K White

EAN Code
3800157600187




EQ. Watts:	100W	PF:	>0.9
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	46°
Luminous Flux:	1500lm	Color of Fixture:	Black
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>80	Dimension:	80 x 185mm



4-LINE TRACK

23W VT-4521T
1201 5000K White

EAN Code
3800157600170




EQ. Watts:	100W	PF:	>0.9
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	46°
Luminous Flux:	1500lm	Base:	White
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>80	Dimension:	80 x 185mm



4-LINE TRACK

35W VT-4540T
1191 3000K Warm White
1192 4000K Day White

EAN Code
3800230629548
3800230629555



EQ. Watts:	200W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	22°
Luminous Flux:	2600lm	Base:	Black
LED Type:	COB	Body Type:	Aluminum
CRI:	>70	Dimension:	225 x 185 x 138mm



4-LINE TRACK

33W VT-4534

- 1242 3000K Warm White
- 1231 4000K Day White
- 1232 5000K White



EAN Code

- 3800157604000
- 3800157602525
- 3800157602532



EQ. Watts:	100W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	22°
Luminous Flux:	2300lm	Color of Fixture:	Black
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>80	Dimension:	106 x 208 x 206mm

LUMINOUS INTENSITY DISTRIBUTION



4-LINE TRACK

33W VT-4534

- 1241 3000K Warm White
- 1229 4000K Day White
- 1230 5000K White



EAN Code

- 3800157603997
- 3800157602501
- 3800157602518



EQ. Watts:	100W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	22°
Luminous Flux:	2300lm	Base:	White
LED Type:	COB	Body Type:	Die Cast Aluminum
CRI:	>80	Dimension:	106 x 208 x 206mm

LUMINOUS INTENSITY DISTRIBUTION





4-LINE TRACK

45W VT-4546

EAN Code



1249 3000K Warm White
1250 4500K Day White
1251 6000K White

3800157607490
3800157607505
3800157607513

A

EQ. Watts:	250W	PF:	>0.95
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	20°
Luminous Flux:	3250lm	Base:	White
LED Type:	COB	Body Type:	PC + Aluminum
CRI:	>80	Dimension:	110 x 255mm

LUMINOUS INTENSITY DISTRIBUTION



4-LINE TRACK

45W VT-4546

EAN Code



1252 3000K Warm White
1253 4500K Day White
1254 6000K White

3800157607520
3800157607537
3800157607544

A

EQ. Watts:	250W	PF:	>0.95
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	20°
Luminous Flux:	3250lm	Color of Fixture:	White
LED Type:	COB	Body Type:	PC + Aluminum
CRI:	>80	Dimension:	110 x 255mm

LUMINOUS INTENSITY DISTRIBUTION





4-LINE TRACK

35W VT-4536

1255 3000K Warm White
1256 4500K Day White
1257 6000K White



EAN Code

3800157607551
3800157607568
3800157607575



EQ. Watts:	120W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	24°
Luminous Flux:	3450lm	Base:	White
LED Type:	COB	Body Type:	Aluminum
CRI:	>80	Dimension:	92 x 165 x 192mm

LUMINOUS INTENSITY DISTRIBUTION



4-LINE TRACK

35W VT-4536

1285 3000K Warm White
1286 4000K Day White
1287 6000K White



EAN Code

3800157618694
3800157618700
3800157618717



EQ. Watts:	120W	PF:	>0.9
Voltage/Frequency:	AC:220-240V,50/60Hz	Beam Angle:	24°
Luminous Flux:	3450lm	Base:	White
LED Type:	COB	Body Type:	Aluminum
CRI:	>80	Dimension:	92 x 165 x 192mm

LUMINOUS INTENSITY DISTRIBUTION





Track Fittings

SKU code:	3545	3546	3555
Description:	GU10 Fitting	GU10 Fitting	E27- PAR20 Fitting
Track Line:	2 Line Black	2 Line White	2 Line Black
EAN code:	3800230628305	3800230628312	3800230628404



Track Fittings

SKU code:	3556	3549	3550
Description:	E27- PAR20 Fitting	E27- PAR30 Fitting	E27- PAR30 Fitting
Track Line:	2 Line White	2 Line Black	2 Line White
EAN code:	3800230628411	3800230628343	3800230628350



PAR 20-30-38
Compatible



PAR 20-30-38
Compatible



Track Fittings

SKU code:	3569	3568	3572
Description:	E27- PAR38 Fitting	E27 Fitting	E27 Fitting
Track Line:	2 Line White	2 Line White	2 Line Black
EAN code:	3800157604246	3800157602419	3800157604277



Track Fittings

SKU code:	3544	3543	3554
Description:	GU10 Fitting	GU10 Fitting	E27-PAR20 Fitting
Track Line:	4 Line White	4 Line Black	4 Line White
EAN code:	3800230628299	3800230628282	3800230628398



Track Fittings

SKU code:	3553	3548	3547
Description:	E27- PAR20 Fitting	E27- PAR 30 Fitting	E27- PAR30 Fitting
Track Line:	4 Line Black	4 Line White	4 Line Black
EAN code:	3800230628381	3800230628336	3800230628329



PAR 20-30-38
Compatible



PAR 20-30-38
Compatible



Track Fittings

SKU code:	3570	3567	3574
Description:	E27- PAR38 Fitting	E27 Fitting	E27 Fitting
Track Line:	4 Line White	4 Line White	4 Line Black
EAN code:	3800157604252	3800157602402	3800157604291

SKU Code
Description
EAN Code



3656
4I Track Light Accessory Mini Black
3800157619110



3655
4I Track Light Accessory Mini White
3800157619103

SKU Code
Description
EAN Code



3522
4I Track Light Accessory White
3800230623232



3523
4I Track Light Accessory Black
3800230623195

SKU Code
Description
EAN Code



3524
4T Track Light Accessory Black
3800230623201



3525
4T Track Light Accessory White
3800230623249



3526
4X Track Light Accessory Black
3800230623218



SKU Code

3527

Description

4X Track Light Accessory White

EAN Code

3800230623256



3528

4L Track Light Accessory Black

3800230623225



3529

4L Track Light Accessory White

3800230623263



SKU Code

3635

Description

2I Track Accessory-Black

EAN Code

3800157612715



3636

2I Track Accessory-white

3800157612722



3637

2L Track Accessory-Black

3800157612739



SKU Code

3638

Description

2L Track Accessory-white

EAN Code


3800157612746




3639

2T Track Accessory-Black

3800157612753



SKU Code **3557**
Description **130mm 4 Line Black**
EAN Code **3800230628428**



SKU Code **3558**
Description **130mm 4 Line White**
EAN Code **3800230628435**



SKU Code **3559**
Description
EAN Code **3800230628442**



SKU Code **3560**
Description **Flexible Joint 4 Line White**
EAN Code **3800230628459**



SKU Code **3565**
Description **Hanging Track Line Kit 1m Black**
EAN Code **3800157600019**



SKU Code **3566**
Description **Hanging Track Line Kit 1m White**
EAN Code **3800157600026**

2Core
TRACK




SKU Code	3633	3634
Description	2M 2 Core Track-Black	2M 2 Core Track-white
EAN Code	3800157612692	3800157612708

EU Standard




SKU Code	9944	9945	9952
Description	1 Meter Black 4 Core Track	1 Meter White 4 Core Track	1.5 Meters Black 4 Core Track
EAN Code	3800230623133	3800230623164	3800230623140

EU Standard



SKU Code	9953	9954	9955
Description	1.5 Meters White 4 Core Track	2 Meters Black 4 Core Track	2 Meters White 4 Core Track
EAN Code	3800230623171	3800230623157	3800230623188



LED Downlights

Swap outdated CFL Lights with high quality LED Down Lights for long- lasting energy efficiency and instant brightness. Choose from a wide range of 3W to 40W

Product Features

- Innumerable styles & Elegant appearance
- Non - Flickering
- No UV Radiation
- Best Quality LED Chips from companies like CREE & SAMSUNG
- Premium Quality Power Driver with lowest power factor saver & high RA
- Easy Installation
- Varied finishes with strong die cast Aluminium body
- Low Maintenance
- All down lights come with premium quality power



Applications

Residences, Showrooms, Hotels & Boutiques etc.



Reflector Downlight

10W VT-26101


1270 3000K Warm White
1271 4500K Day White
1272 6000K White

EAN Code


3800157611923
3800157611930
3800157611947



120⁺⁺
LM/W
HIGH LUMENS



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	90W	Beam Angle:	120 °
Voltage/Frequency:	AC: 100-277V, 50/60Hz	Body Type:	PKW (White)
Luminous Flux:	1200lm	Shape:	Round
LED Type:	COB	Dimension:	Ø 135mm x 71mm
CRI:	>80	Cutting Size:	Ø120mm
PF	> 0.5		



Reflector Downlight

20W VT-26201


1273 3000K Warm White
1274 4500K Day White
1275 6000K White

EAN Code


3800157611954
3800157611961
3800157611978



120⁺⁺
LM/W
HIGH LUMENS



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	180W	Beam Angle:	120 °
Voltage/Frequency:	AC: 100-277V, 50/60Hz	Body Type:	PKW (White)
Luminous Flux:	2400lm	Shape:	Round
Commercial Type:	COB	Dimension:	Ø 180mm x 83mm
CRI:	>80	Cutting Size:	Ø167mm
PF:	> 0.5		



Reflector Downlight

30W VT-26301


1276 3000K Warm White
1277 4500K Day White
1278 6000K White

EAN Code


3800157611985
3800157611992
3800157612005



120⁺⁺
LM/W
HIGH LUMENS



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Reflector Downlight

40W VT-26451


1279 4500K Day White
1280 6000K White

EAN Code


3800157612012
3800157612029



120⁺⁺
LM/W
HIGH LUMENS



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts: 350W

Beam Angle: 120 °

Voltage/Frequency: AC: 100-277V, 50/60Hz

Body Type: PKW (White)

Luminous Flux: 4800lm

Shape: Round

Commercial Type: COB

Dimension: Ø 220mm x 103mm

CRI: >80

Cutting Size: Ø207mm

PF: > 0.9




Reflector Downlight

10W VT-2610


- 1102 3000K Warm White
- 1101 4500K Day White
- 1100 6000K White

EAN Code

- 3800230622396
- 3800230622389
- 3800230622372



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	25W	Beam Angle:	120 °
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	PKW (White)
Luminous Flux:	730lm	Shape:	Round
LED Type:	COB	Dimension:	Ø 135mm x 71mm
CRI:	>80	Cutting Size:	Ø105mm
PF	> 0.5		




Reflector Downlight

20W VT-2620


- 1108 3000K Warm White
- 1104 4500K Day White
- 1103 6000K White

EAN Code

- 3800230625410
- 3800230622419
- 3800230622402



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	50W	Beam Angle:	120 °
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	PKW (White)
Luminous Flux:	1500lm	Shape:	Round
Commercial Type:	COB	Dimension:	Ø 182mm x 90mm
LED Type:	>80	Cutting Size:	Ø160mm
CRI:	> 0.5		



Reflector Downlight


30W VT-2630

1107 3000K Warm White
1106 4500K Day White
1105 6000K White


EAN Code

3800230625021
3800230622433
3800230622426

A+



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	75W	Beam Angle:	120 °
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	PKW (White)
Luminous Flux:	2400lm	Shape:	Round
LED Type:	COB	Dimension:	Ø 222mm x 111mm
CRI:	>80	Cutting Size:	Ø205mm
PF	> 0.9		



Reflector Downlight


40W VT-2645

1163 3000K Warm White
1164 4500K Day White
1165 6000K White


EAN Code

3800230627285
3800230627292
3800230627308

A+



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



EQ. Watts:	100W	Beam Angle:	120 °
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	PKW (White)
Luminous Flux:	3200lm	Shape:	Round
Commercial Type:	COB	Dimension:	Ø 222mm x 111mm
LED Type:	≥80	Cutting Size:	Ø205mm
CRI:	> 0.9		



COB Downlight

3W VT-1123 RD

EAN Code

5098 3000K Warm White

3800157609401

5099 4500K Day White

3800157609418

5107 6000K White

3800157609425



EQ. Watts:	24W	Beam Angle:	60 °
Voltage/Frequency:	AC: 85-265V, 50/60Hz	Body Type:	Aluminum
Luminous Flux:	200lm	Shape:	Round
LED Type:	COB	Dimension:	Ø45 x 35mm
CRI:	>80	Cutting Size:	Ø36mm
PF	> 0.5		



COB Downlight

3W VT-1123 SQ

EAN Code

5108 3000K Warm White

3800157609432

5109 4500K Day White

3800157609449

5110 6000K White

3800157609456



EQ. Watts:	24W	Beam Angle:	60 °
Voltage/Frequency:	AC: 85-265V, 50/60Hz	Body Type:	Aluminum
Luminous Flux:	200lm	Shape:	Square
Commercial Type:	COB	Dimension:	45 x 45 x 35mm
LED Type:	>80	Cutting Size:	36 x 36 mm
CRI:	> 0.5		



COB Downlight

3W VT-1133 RD

EAN Code

5092 3000K Warm White

3800157609340

5093 4500K Day White


3800157609357

5094 6000K White

3800157609364



EQ. Watts:	24W	Beam Angle:	60 °
Voltage/Frequency:	AC: 85-265V, 50/60Hz	Body Type:	Aluminum
Luminous Flux:	200lm	Shape:	Round
LED Type:	COB	Dimension:	Ø55 x 42mm
CRI:	>80	Cutting Size:	Ø45mm
PF	> 0.5		

**COB Downlight****3W** VT-1133 SQ

5095 3000K Warm White

5096 4500K Day White

5097 6000K White

EAN Code

3800157609371

3800157609388

3800157609395



EQ. Watts:	24W	Beam Angle:	60 °
Voltage/Frequency:	AC: 85-265V, 50/60Hz	Body Type:	Aluminum
Luminous Flux:	200lm	Shape:	Square
Commercial Type:	COB	Dimension:	55 x 55 x 42mm
LED Type:	>80	Cutting Size:	45 x 45mm
CRI:	> 0.5		

**COB Downlight****8W** VT-2908 RD

1116 3000K Warm White

1117 4000K Day White

1118 6000K White

EAN Code


380023062514

3800230625151

3800230625168



EQ. Watts:	32W	Beam Angle:	24 °
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Body Type:	Powder Coating Die cast
Luminous Flux:	550lm	Shape:	Round
LED Type:	COB	Dimension:	Ø103 x 75mm
CRI:	>80	Cutting Size:	Ø90mm
PF	> 0.5		

**COB Downlight****8W** VT-2908 SQ

1113 3000K Warm White

1114 4000K Day White

1115 6000K White

EAN Code

3800230625175

3800230625182

3800230625199



EQ. Watts:	32W	Beam Angle:	24 °
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Body Type:	Powder Coating Die cast
Luminous Flux:	550lm	Shape:	Square
Commercial Type:	COB	Dimension:	103 x 103 x 75mm
LED Type:	>80	Cutting Size:	90 x 90mm
CRI:	> 0.5		





Custom Angle

7W VT-2807

1110 5000K Day White

EAN Code

3800230622440



EQ. Watts:	18W	Beam Angle:	20 °
Voltage/Frequency:	AC: 170-240V, 50/60Hz	Body Type:	Ivory White
Luminous Flux:	550lm	Shape:	Zoom
LED Type:	COB.CREE	Dimension:	Ø100 x 76mm
CRI:	>80	Cutting Size:	Ø86mm
PF:	> 0.8		



Custom Angle

22W VT-2822

1111 5000K Day White

EAN Code

3800230622457



EQ. Watts:	55W	Beam Angle:	25 °
Voltage/Frequency:	AC: 170-240V, 50/60Hz	Body Type:	Ivory White
Luminous Flux:	1570lm	Shape:	Zoom
LED Type:	COB.CREE	Dimension:	Ø158 x 150mm
CRI:	>80	Cutting Size:	Ø140mm
PF:	> 0.8		



Custom Angle

30W VT-2830

1112 4000K Day White

EAN Code

3800230622464



EQ. Watts:	75W	Beam Angle:	25 °
Voltage/Frequency:	AC: 170-240V, 50/60Hz	Body Type:	Ivory White
Luminous Flux:	2100lm	Shape:	Zoom
LED Type:	COB.CREE	Dimension:	Ø190 x 160mm
CRI:	>80	Cutting Size:	Ø175mm
PF:	> 0.9		




Zoom Light

30W VT-2930


- 1306 3000K Warm White
- 1307 4500K Day White
- 1289 6000K White

EAN Code
3800157619936
3800157619943
3800157619646



235mm

A+



EQ. Watts:	170W	Beam Angle:	99°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	Aluminum, White
Luminous Flux:	2450lm	Shape:	Rectangle
LED Type:	COB	Dimension:	235 x 146 x 139mm
CRI:	≥80	Cutting Size:	220 x 132mm
PF:	> 0.9		




Zoom Light

33W VT-2933

- 1304 3000K Warm White
- 1305 4500K Day White
- 1288 6000K White


EAN Code
3800157619912
3800157619929
3800157619639



140mm

Ø165mm

A+



EQ. Watts:	200W	Beam Angle:	24°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	Aluminum, White
Luminous Flux:	2650lm	Shape:	Round
LED Type:	COB	Dimension:	Ø 165x140mm
CRI:	≥80	Cutting Size:	Ø 155
PF:	> 0.9		



Step Light

2W VT-1142

1315 3000k Warm White
1314 4000K Day White

EAN Code

3800157620437
3800157620420



Ø150mm



27mm

EQ. Watts:	10W	PF:	0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	55 °
Luminous Flux:	60LM	Color of Fixture:	White
Body Type:	PC	Shape:	Round
CRI:	>80	Dimension:	ø150 x 27mm



Step Light

2W VT-1142

1317 3000k Warm White
1316 4000K Day White

EAN Code

3800157620451
3800157620444



Ø150mm



27mm

EQ. Watts:	10W	PF:	0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	55 °
Luminous Flux:	60LM	Color of Fixture:	Black
Body Type:	PC	Shape:	Round
CRI:	>80	Dimension:	ø150 x 27mm



Step Light

2W VT-1142

1319 3000k Warm White
1318 4000K Day White

EAN Code

3800157620475
3800157620468




Ø150mm



27mm

EQ. Watts:	10W	PF:	0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	55 °
Luminous Flux:	60LM	Color of Fixture:	Grey
Body Type:	PC	Shape:	Round
CRI:	>80	Dimension:	ø150 x 27mm




Step Light

2W VT-1152

1321 3000k Warm White
1320 4000K Day White

EAN Code

3800157620499
3800157620482



EQ. Watts:	10W	PF:	0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	55 °
Luminous Flux:	60lm	Color of Fixture:	White
Body Type:	PC	Shape:	Square
CRI:	>80	Dimension:	124 x 124 x 27mm




Step Light

2W VT-1152


1323 3000k Warm White
1322 4000K Day White

EAN Code

3800157620512
3800157620505



EQ. Watts:	10W	PF:	0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	55 °
Luminous Flux:	60lm	Color of Fixture:	Black
Body Type:	PC	Shape:	Square
CRI:	>80	Dimension:	124 x 124 x 27mm




Step Light

2W VT-1152

1325 3000k Warm White
1324 4000K Day White

EAN Code

3800157620536
3800157620529




EQ. Watts:	10W	PF:	0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	55 °
Luminous Flux:	60lm	Color of Fixture:	Grey
Body Type:	PC	Shape:	Square
CRI:	>80	Dimension:	124 x 124 x 27mm

Step Light

3W VT-1162
1327 3000k Warm White
1326 4000K Day White

EAN Code
3800157620550
3800157620543




EQ. Watts:	15W	PF:	0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	55 °
Luminous Flux:	110LM	Color of Fixture:	White
Body Type:	PC	Shape:	Rectangle
CRI:	>80	Dimension:	230 x 80 x 28mm

Step Light

3W VT-1162
1329 3000k Warm White
1328 4000K Day White

EAN Code
3800157620574
3800157620567




EQ. Watts:	15W	PF:	0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	55 °
Luminous Flux:	110LM	Color of Fixture:	White
Body Type:	PC	Shape:	Rectangle
CRI:	>80	Dimension:	230 x 80 x 28mm

Step Light

3W VT-1162
1331 3000k Warm White
1330 4000K Day White

EAN Code
3800157620598
3800157620581




EQ. Watts:	15W	PF:	0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	55 °
Luminous Flux:	110LM	Color of Fixture:	White
Body Type:	PC	Shape:	Rectangle
CRI:	>80	Dimension:	230 x 80 x 28mm




Step Light

3W VT-1109 RD
1207 3000K Warm White
1208 4200K Day White

EAN Code
3800157600231
3800157600248



LUMINOUS INTENSITY DISTRIBUTION




EQ. Watts:	12W	Beam Angle:	15 °
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Color of Fixture:	PKW (White)
Luminous Flux:	120lm	Shape:	Round
Body Type:	Aluminum	Dimension:	Ø80 x 51mm
CRI:	> 80	Cutting Size:	Ø62mm
PF:	> 0.5		




Step Light

3W VT-1109 SQ
1209 3000K Warm White
1210 4200K Day White
1223 6000K White

EAN Code
3800157600255
3800157600262
3800157601504



LUMINOUS INTENSITY DISTRIBUTION



EQ. Watts:	12W	Beam Angle:	15°
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Color of Fixture:	PKW (White)
Luminous Flux:	120lm	Shape:	Square
Body Type:	Aluminum	Dimension:	80 x 80 x 51mm
CRI:	> 80	Cutting Size:	62 x 62mm
PF:	> 0.5		




Step Light with Sensor

3W VT-8035

EAN Code

5570 4500k Day White

3800157617291



EQ. Watts:	15W	PF:	> 0.5
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Beam Angle:	45 °
Luminous Flux:	100lm	Color of Fixture:	PKW (White)
Body Type:	Die cast Aluminum	Shape:	Square
CRI:	> 80	Dimension:	85 x 85 x 42mm




Step Light

3W VT-1143

EAN Code

1284 4000k Day White

3800157617307



EQ. Watts:	15W	Beam Angle:	83 °
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Color of Fixture:	PKW (White)
Luminous Flux:	100lm	Shape:	Square
Body Type:	Die cast Aluminum	Dimension:	85 x 85 x 43mm
CRI:	> 80	Cutting Size:	72 x 72mm
PF:	> 0.5		



LED Dome Lights

Introducing a customized innovation to an old problem LED DOME LIGHTS, Compact and Easy to install elegant replacement for traditional full round Dome Lights, Creates a perfect fusion between bright and dark spots for ambience of any environment


Product Features

- 80% Electricity savings as compared to traditional Incandescent Bulbs
- 20,000 hours Lifespan
- Non – Flickering
- No UV Radiation
- Easy Installation
- Premium Quality LED Chip
- Premium Quality Power Driver
- Instant start 0-100% in 0.01 seconds
- Extreme Weather toleration (-20 to + 45 Degrees Centigrade)

Applications

- Mostly used in Parking Lots, Passage's in big areas, Exterior Walls of Prestigious Buildings for ambience, Airports, Ports and Malls








LED Oval Dome Light

8W VT-8038

- 1308 3000k Warm White
- 1309 4000K Day White
- 1310 6400k White



EAN Code

- 3800157620260
- 3800157620277
- 3800157620284






EQ. Watts:	40W	Beam Angle:	120°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	PC
Luminous Flux:	560lm	Shape:	Rectangle
LED Type:	SMD	IP Rating:	IP54
CRI:	>70	Color of Fixture	Black
PF:	> 0.5	Dimension:	190 x 100 x 45 48mm



LED Oval Dome Light

8W VT-8038

- 1311 3000k Warm White
- 1312 4000K Day White
- 1313 6400k White




EAN Code

- 3800157620291
- 3800157620307
- 3800157620314



EQ. Watts:	40W	Beam Angle:	120°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	PC
Luminous Flux:	560lm	Shape:	Rectangle
LED Type:	SMD	IP Rating:	IP54
CRI:	>70	Color of Fixture	White
PF:	> 0.5	Dimension:	190 x 100 x 45 48mm



LED Dome Light

15W VT-8033
5566 4000K Day White

EAN Code
3800157610353




EQ. Watts:	95W	Beam Angle:	120°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	PC
Luminous Flux:	1250lm	Shape:	Round
LED Type:	SMD	IP Rating:	IP44
CRI:	>80	Dimension:	Ø 220mm x 48mm
PF:	> 0.6		

EASY TO USE
PLUG AND PLAY

Luxurious Finish
SURFACE MOUNTED

TRIMLESS



LED Dome Light

15W VT-8033
5567 4000K Day White

EAN Code
3800157610360



EQ. Watts:	95W	Beam Angle:	120°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	PC
Luminous Flux:	1250lm	Shape:	Square
LED Type:	SMD	IP Rating:	IP44
CRI:	>80	Dimension:	220 x 220 x 48mm
PF:	> 0.6		




Led Dome Light

12W VT-8031

5563 4000K Day White
5562 6500K White

EAN Code

3800157610322
3800157610315



EQ. Watts:	65W	Beam Angle:	120°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	Metal + PMMA
Luminous Flux:	800lm	Shape:	Round
LED Type:	SMD	IP Rating:	IP20
CRI:	>80	Dimension:	Ø 250 x 80mm
PF:	> 0.6		



MAXIMUM LIGHT OUTPUT AND
ENERGY EFFICIENT




Led Dome Light

24W VT-8032

5565 4000K Day White
5564 6500K White

EAN Code

3800157610339
3800157610346



EQ. Watts:	125W	Beam Angle:	120°
Voltage/Frequency:	AC: 220-240V, 50Hz	Body Type:	Metal + PMMA
Luminous Flux:	1700lm	Shape:	Round
LED Type:	SMD	IP Rating:	IP20
CRI:	>80	Dimension:	Ø 320 x 95mm
PF:	> 0.6		



SENSOR
INSIDE



Led Dome Light


12W VT-8008

4984 4500K Day White
4985 6000K White

EAN Code

3800157601290
3800157601306

A



Sensor Type:	Microwave	Detection Distance:	*10%/50%/100%
Color:	White	Time Delay:	10s/1min/5min/10min/30min
Detection Range:	Max.(0 x H): 10m x 4m, 360°	Luminous Flux:	840lm
Voltage:	AC: 200-240V,50/60Hz	Body Type:	ABS+Plastic+PMMA
Rated Load:	12W	IP Rating:	IP65
EQ. Watts:	60W	Dimension:	Ø300 x 100mm



Without Sensor



Led Dome Light


12W VT-8007

4983 4500K Day White

EAN Code

3800157601283

A



EQ. Watts:	40W	Beam Angle:	110°
Voltage/Frequency:	AC: 200-240V, 50/60Hz	Color of Fixture:	White
Luminous Flux:	840lm	Body Type:	ABS+Plastic+PMMA
IP Rating:	IP65	Shape:	Full Round
CRI:	>70	Dimension:	Ø300 x 100mm
PF:	>0.9		




SENSOR
INSIDE

IP65
RATED
Led Dome Light

12W VT-8008
4981 3000K Warm White
4971 4500K Day White
4980 6000K White

EAN Code
3800230629586
3800230629036
3800230629579




Sensor Type:	Microwave	Detection Distance:	*10%/50%/100%
Color:	Black	Time Delay:	*10s/1min/5min/10min/30min
Detection Range:	Max.(0 x H): 10m x 4m, 360°	Luminous Flux:	840lm
Voltage:	AC: 200-240V,50/60Hz	Body Type:	ABS+Plastic+PMMA
Rated Load:	12W	IP Rating:	IP65
EQ. Watts:	60W	Dimension:	Ø300 x 100mm



IP65
RATED
Without Sensor
Led Dome Light

12W VT-8007
4970 4500K Day White

EAN Code
3800230629029



EQ. Watts:	40W	Beam Angle:	110°
Voltage/Frequency:	AC: 200-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	840lm	Body Type:	ABS+Plastic+PMMA
IP Rating:	IP65	Shape:	Full Round
CRI:	>70	Dimension:	Ø300 x 100mm
PF:	>0.9		



SENSOR INSIDE

Built In LED

IP54 RATED

Led Dome Light


16W VT-8001C

1281 3000K Warm White
4965 4500K Day White
1282 6000K White

EAN Code

3800157612678
3800230625809
3800157612685

A+



96 mm
Ø 296 mm

Sensor Type:	Microwave	Detection Distance:	*1-8m (radius)
Color:	White	Time Delay:	*10 sec to 12 min
Detection Range:	360°	Luminous Flux:	1300lm
Voltage:	AC: 220-240V,50Hz	Body Type:	PC Cover
Rated Load:	16W	IP Rating:	IP54
EQ. Watts:	100W	Dimension:	Ø296 x 96mm



SENSOR INSIDE


Led Dome Light

Max.**60W** VT-8002C

4966

EAN Code

3800230625816



96 mm
Ø 296 mm

Sensor Type:	Microwave	Detection Distance:	*1-8m (radius)
Color:	White	Time Delay:	*10 sec to 12 min
Detection Range:	360°	Body Type:	ABS+Plastic+PMMA
Voltage:	AC: 220-240V,50Hz	IP Rating:	IP44
Rated Load:	Uses Max. 60W(E27)	Dimension:	Ø296 x 96mm
EQ. Watts:	As per E27 bulb		




Led Dome Light

12W VT-8017

5057 3000K Warm White
5058 4500K Day White
5059 6000K White

EAN Code
3800157605250
3800157605267
3800157605274



Sensor Type	PIR Sensor
Color	White
Detection Range	360°
Voltage	AC: 110-240V, 50Hz
Rated Load	12W (24PCS LED)
EQ. Watts	60W
Detection Distance	max.6m(<24°C)
Time Delay	*10 sec to 3 min
Luminous Flux	800lm
Body Type	ABS+Plastic+PMMA
IP Rating	IP20
Dimension	Ø290 x 60mm





Led Dome Light


8W VT-8014

1267 3000K Warm White
1266 4500K Day White
1268 6000K White



EAN Code

3800157611893
3800157611886
3800157611909




EQ. Watts:	20W	Beam Angle:	110°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	Black
Luminous Flux:	560lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Full Oval
CRI:	>70	Dimension:	126 x 187 x 76mm
PF:	>0.5		



Led Dome Light

12W VT-8016

5056 4500K Day White
5055 6000K White



EAN Code

3800157603980
3800157603348



EQ. Watts:	40W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	Black
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Full Oval
CRI:	>70	Dimension:	245 x 165 x 96mm
PF:	>0.5		



Led Dome Light


8W VT-8014

1264 3000K Warm White
1263 4500K Day White
1265 6000K White



EAN Code

3800157611862
3800157611855
3800157611879




EQ. Watts:	20W	Beam Angle:	110°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	White
Luminous Flux:	560lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Full Oval
CRI:	>70	Dimension:	126 x 187 x 76mm
PF:	>0.5		



Led Dome Light

12W VT-8016

5054 4500K Day White
5053 6000K White



EAN Code

3800157603331
3800157603324



EQ. Watts:	40W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	White
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Full Oval
CRI:	>70	Dimension:	245 x 165 x 96mm
PF:	>0.5		




Led Dome Light

12W VT-8009
4972 4500K Day White



EAN Code
3800230629043



EQ. Watts:	40W	Beam Angle:	110°
Voltage/Frequency:	AC: 200-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Half-Oval
CRI:	>70	Dimension:	290 x 200 x 100mm
PF:	>0.9		




Led Dome Light

12W VT-8010
4973 4500K Day White
1269 6000K White



EAN Code
3800230629050
3800157611916



EQ. Watts:	40W	Beam Angle:	110°
Voltage/Frequency:	AC: 200-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Full Oval
CRI:	>70	Dimension:	290 x 200 x 100mm
PF:	>0.9		




Led Dome Light

8W VT-8014

4999 3000K Warm White
1259 4500K Day White
4997 6000K White

EAN Code

3800157602556
3800157611817
3800157602259



EQ. Watts:	20W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	White
Luminous Flux:	560lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Round
CRI:	>70	Dimension:	Ø180 x 82mm
PF:	>0.5		




Led Dome Light

12W VT-8015

4998 3000K Warm White
5050 4500K Day White
4996 6000K White

EAN Code

3800157602549
3800157603294
3800157602228



EQ. Watts:	40W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	White
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Round
CRI:	>70	Dimension:	Ø220 x 105mm
PF:	>0.5		




Led Dome Light

8W VT-8014

1261 3000K Warm White
1260 4500K Day White
1262 6000K White

EAN Code

3800157611831
3800157611824
3800157611848



EQ. Watts:	20W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	Black
Luminous Flux:	560lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Round
CRI:	>70	Dimension:	Ø180 x 82mm
PF:	>0.5		




Led Dome Light

12W VT-8015

5052 4500K Day White
5051 6000K White

EAN Code

3800157603317
3800157603300



EQ. Watts:	40W	Beam Angle:	120°
Voltage/Frequency:	AC: 200-240V, 50Hz	Color of Fixture:	Black
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Round
CRI:	>70	Dimension:	Ø220 x 105mm
PF:	>0.5		



Led Dome Light


12W VT-8006

4969 4500K Day White

IP65
RATED

EAN Code
3800230629012

A



EQ. Watts:	40W	Beam Angle:	110°
Voltage/Frequency:	AC: 200-240V,50/60Hz	Color of Fixture:	Black
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Half-Round
CRI:	>70	Dimension:	Ø300 x 100mm
PF:	>0.9		



Led Dome Light


12W VT-8006

4986 4500K Day White

IP65
RATED

EAN Code
3800157601313

A



EQ. Watts:	40W	Beam Angle:	110°
Voltage/Frequency:	AC: 200-240V,50/60Hz	Color of Fixture:	White
Luminous Flux:	840lm	Body Type:	Plastic Clad Aluminum
IP Rating:	IP65	Shape:	Half-Round
CRI:	>70	Dimension:	Ø300 x 100mm
PF:	>0.9		



Motion Sensor

Many areas like lobbies, parking garages, staircases remain unused for long hours, but do need lighting to be lit automatically in case of movement. A motion sensor is a device which detects movements, and in some cases light conditions and then transmits a signal for illumination.

Product Features

- Power saving
- Available for in-door and out door purposes
- Compatible with most of our models
- Proven quality from reliable suppliers
- Wide range of models to choose from




Applications

- Outdoor Areas like parking garages, Gardens compounds and yards
- Indoor areas like walkways, lobbies and staircases.



Infrared Sensor

Max **1000W** VT-8027 EAN Code
5086 3800157609173




Sensor Type:	Infrared	Time Delay:	*10sec±3sec-15min±1min
Color:	White	Ambient Light:	*<3-2000LUX
Detection Range:	360°	Body Type:	PC
Voltage:	AC: 220-240V,50Hz	Detector:	One
Rated Load:	Max.1000W	IP Rating:	IP20
Detection Distance:	Max.6m (<24° C)	Dimension:	120x35mm



Infrared Sensor -

Max **1000W** VT-8027 EAN Code
5087 3800157609180



Sensor Type:	Infrared	Time Delay:	*10sec±3sec-15min±1min
Color:	Black	Ambient Light:	*<3-2000LUX
Detection Range:	360°	Body Type:	PC
Voltage:	AC: 220-240V,50Hz	Detector:	One
Rated Load:	Max.1000W	IP Rating:	IP20
Detection Distance:	Max.6m (<24° C)	Dimension:	120x35mm



Infrared Sensor

Max. **400W** VT-8028
5088



EAN Code
3800157609197



Sensor Type:	Infrared	Time Delay:	*10sec±3sec-15min±1min
Color:	White	Ambient Light:	*<3-2000LUX
Detection Range:	12m-180°	Body Type:	PC
Voltage:	AC: 220-240V,50/60Hz	IP Rating:	IP44
Rated Load:	Max.400W	Dimension:	80x55x70mm
Detection Distance:	6m or 12m		



Infrared Sensor

Max. **400W** VT-8028
5089



EAN Code
3800157609203




Sensor Type:	Infrared	Time Delay:	*10sec±3sec-15min±1min
Color:	Black	Ambient Light:	*<3-2000LUX
Detection Range:	12m-180°	Body Type:	PC
Voltage:	AC: 220-240V,50/60Hz	IP Rating:	IP44
Rated Load:	Max.400W	Dimension:	80x55x70mm
Detection Distance:	Max.12m (<24° C)		



Infrared Sensor-PIR Sensor Moving Head

Max. **400W** VT-8030 EAN Code
5091 3800157609227




Sensor Type:	Infrared	Time Delay:	*10sec±3sec-15min±1min
Color:	White	Ambient Light:	*<3-2000LUX
Detection Range:	360°	Body Type:	PC
Voltage:	AC: 220-240V,50/60Hz	IP Rating:	IP20
Rated Load:	Max.400W	Dimension:	98 x 73 x 82mm
Detection Distance:	Max.8m (<24° C)		



Infrared Sensor

Max. **300W** VT-8029 EAN Code
5090 3800157609210



Sensor Type:	Infrared	Time Delay:	*10sec±3sec-5min±1min
Color:	White	Ambient Light:	*<3-2000LUX
Detection Range:	360°	Body Type:	PC
Voltage:	AC: 220-240V,50/60Hz	IP Rating:	IP20
Rated Load:	Max.300W	Dimension:	76 x 75.6mm
Detection Distance:	Max.6m (<24° C)		



Infrared Sensor

Max. **300W** VT-8003
4967



EAN Code
3800230625823



Sensor Type:	Infrared	Time Delay:	*10 sec to 7min
Color:	White	Ambient Light:	*<3-2000LUX
Detection Range:	180°	Body Type:	PC
Voltage:	AC: 220-240V,50/60 Hz	Detector:	One
Rated Load:	Max.300W	IP Rating:	IP44
Detection Distance:	max.12m (<24° C)	Dimension:	86.4 x 60.4 x 98mm



Infrared Sensor

Max. **300W** VT-8003
5077



EAN Code
3800157606875




Sensor Type:	Infrared	Time Delay:	*10 sec to 7min
Color:	Black	Ambient Light:	*<3-2000LUX
Detection Range:	180°	Body Type:	PC
Voltage:	AC: 220-240V,50/60 Hz	Detector:	One
Rated Load:	Max.300W	IP Rating:	IP44
Detection Distance:	max.12m (<24° C)	Dimension:	86.4 x 60.4 x 98mm



Infrared Sensor

Max. **60W** VT-8005
4982

EAN Code
3800157600071




Sensor Type:	Infrared	Time Delay:	*10sec±3sec-5min±1min
Color:	White	Ambient Light:	*<3-2000LUX
Detection Range:	360°	Body Type:	PC
Voltage:	AC: 110-240V, 50/60Hz	IP Rating:	IP20
Rated Load:	Max.60W(E27)	Dimension:	Ø55.5 x 116.5mm
Detection Distance:	Max.6m (<24° C)		




Infrared Sensor

Max. **300W** VT-8004
4968

EAN Code
3800230625830



Sensor Type:	Infrared	Time Delay:	*10 sec to 7 min
Color:	White	Ambient Light:	*<3-2000LUX
Detection Range:	360°	Body Type:	PC
Voltage:	AC: 220-240V,50Hz	Detector:	Three
Rated Load:	Max.300W	IP Rating:	IP20
Detection Distance:	max.12m (<24° C)	Dimension:	88 x 55mm




Infrared Sensor

Max.200W VT-8036
5571

EAN Code
3800157620246

Sensor Type:	Microwave	Time Delay:	*10sec±3sec-5min±1min
Color:	White	Ambient Light:	*<25-2000LUX
Detection Range:	180° - 360°	Body Type:	PC
Voltage:	AC: 220-240V,50/60Hz	IP Rating:	IP20
Rated Load:	Max.200W	Dimension:	Ø55.5 x 116.5mm
Detection Distance:	5m /10m		



Infrared Sensor

Max.200W VT-8036
5572

EAN Code
3800157620253


Sensor Type:	Microwave	Time Delay:	*10sec±3sec-5min±1min
Color:	Black	Ambient Light:	*<25-2000LUX
Detection Range:	180° - 360°	Body Type:	PC
Voltage:	AC: 220-240V,50/60Hz	IP Rating:	IP20
Rated Load:	Max.200W	Dimension:	Ø55.5 x 116.5mm
Detection Distance:	5m /10m		



Housing for Microwave sensor

VT-8021
5079


EAN Code
3800157606899



Sensor Type:	Microwave
Color:	White
IP Rating:	IP65
Dimension:	Ø134 x 66.5mm



VT-8021




VT-8018



Microwave Sensor

Max.300W VT-8018
5078

EAN Code
3800157606882



Sensor Type:	Microwave	Time Delay:	*10 sec to 12 min
Color:	White	Ambient Light:	*<3-2000LUX
Detection Range:	360°	Body Type:	Plastic
Voltage:	AC: 220-240V,50/60Hz	Detector:	One
Rated Load:	Max.300W	IP Rating:	IP20
Detection Distance:	*1-8m (radius)	Dimension:	76x37x 27mm



Photocell Sensor

VT-8019

5081



EAN Code

3800157608015



Sensor Type:	Photocell	Time Delay:	*5 sec to 8 min
Color:	White	Ambient Light:	*<5-15LUX
Detection Range:	360°	Body Type:	Plastic
Voltage:	AC: 220-240V, 50Hz	Detector:	One
Rated Load:	Max.500/800W	IP Rating:	IP44
		Dimension:	35.5 x 46 x 44.1mm

Infrared Sensor


Max. 800W VT-8022

5082



EAN Code

3800157608022



Sensor Type:	IR Motion	Time Delay:	*5 sec to 8 min
Color:	White	Ambient Light:	*10 Lux/2000 Lux
Detection Range:	180°	Body Type:	PC
Voltage:	AC: 220-240V , 50Hz	Detector:	Three
Rated Load:	Max.500/800W	IP Rating:	IP44
Detection Distance:	3m/6m(choice) (<24°C)	Dimension:	36.8 x 25.5 x 55.4mm


Microwave Sensor

Max. 1200W VT-8023

5083

EAN Code

3800157608039




Sensor Type:	Microwave	Time Delay:	*10 sec to 12 min
Color:	White	Ambient Light:	*<3-2000LUX
Detection Range:	180°	Body Type:	Plastic
Voltage:	AC: 220-240V, 50/60Hz	Detector:	One
Rated Load:	Max.1200W	IP Rating:	IP20
Detection Distance:	*5m - 15m	Dimension:	80 x 80 x 32mm



ON/OFF VIA
MOVING HAND

Motion Sensor

Max. **300/500W** VT-8025
5084



EAN Code
3800157608046


Sensor Type:	IR Sensor	Detection Distance:	5cm/6cm (<24°C)
Color:	White	Body Type:	Plastic
Detection Range:	360°	Detector:	One
Voltage:	AC: 110-240V, 50/60Hz	IP Rating:	IP20
Rated Load:	Max.300/500W	Dimension:	35.5 x 78.2 x 20.6mm



ON/OFF VIA THE OPENING
AND CLOSING OFF THE DOOR

Motion Sensor

Max. **300/500W** VT-8026
5085



EAN Code
3800157608053

Sensor Type:	IR Sensor	Detection Distance:	5cm/6cm (<24°C)
Color:	White	Body Type:	Plastic
Detection Range:	360°	Detector:	One
Voltage:	AC: 110-240V, 50/60Hz	IP Rating:	IP20
Rated Load:	Max.300/500W	Dimension:	35.5 x 78.2 x 18.7mm





LED Table Lamps

Our most cozy and favorite corners, be it at work or at home, while you are working, or relaxing and reading a book, always deserve the best lighting conditions. To cater to this need we bring to you an exclusive range of LED table lamps designed with a touch of class, these lamps deliver very smooth lighting with suitable functions to set the right mood and ambiance.

Product Features

- Energy efficient ways of keeping it that way.
- Adjustable direction.
- Multiple functions like dimming, color changing.
- With USB charging functionality.
- Sleek and modern design.



Applications

- Table lamps can be used in any space, though they are most often found in bedrooms, living rooms at home next to sofas, chairs or beds. It is also a good accessory to be a part of the office decor.



SILVER

4W VT-1014

EAN Code

3800157616980



7098 { 3000K Warm White
4000K Day White
5000K White

Voltage/Frequency:	AC: 100-240V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	550lm	Color:	White + Silver
IP Rating:	IP20	Body Type:	ABS + PC + Aluminum
CRI:	> 80	Dimension:	200 x 50 x 263mm
PF:	>0.45		



GOLD

4W VT-1014

EAN Code

3800157616997



7099 { 3000K Warm White
4000K Day White
5000K White

Voltage/Frequency:	AC: 100-240V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	550lm	Color:	White + Gold
IP Rating:	IP20	Body Type:	ABS + PC + Aluminum
CRI:	> 80	Dimension:	200 x 50 x 263mm
PF:	>0.45		



BLACK

4W VT-1014

EAN Code

3800157617215



8500 { 3000K Warm White
4000K Day White
5000K White

Voltage/Frequency:	AC: 100-240V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	550lm	Color:	Black
IP Rating:	IP20	Body Type:	ABS + PC + Aluminum
CRI:	> 80	Dimension:	200 x 50 x 263mm
PF:	>0.45		



Dimmable

GREY

7W VT-1007D
7034 5000K White

EAN Code
3800157603836



Touch Control



6 Steps Dimming




1 hour timer



Eye Protection



Anti-radiation



Voltage/Frequency:	AC: 100-240V, 50/60Hz	PF:	>0.45
Luminous Flux:	400lm	Beam Angle:	120°
IP Rating:	IP20	Color:	Grey
CRI:	> 80	Body Type:	ABS
		Dimension:	170 x 135 x 415mm



Dimmable

PINK

7W VT-1007D
7042 5000K White

EAN Code
3800157605311



Touch Control



6 Steps Dimming




1 hour timer



Eye Protection



Anti-radiation



Voltage/Frequency:	AC: 100-240V, 50/60Hz	PF:	>0.45
Luminous Flux:	400lm	Beam Angle:	120°
IP Rating:	IP20	Color:	Pink
CRI:	> 80	Body Type:	ABS
		Dimension:	170 x 135 x 415mm



Dimmable

BLUE

7W VT-1007D
7043 5000K White

EAN Code
3800157605328



Touch Control



6 Steps Dimming




1 hour timer



Eye Protection



Anti-radiation



Voltage/Frequency:	AC: 100-240V, 50/60Hz	PF:	>0.45
Luminous Flux:	400lm	Beam Angle:	120°
IP Rating:	IP20	Color:	Blue
CRI:	> 80	Body Type:	ABS
		Dimension:	170 x 135 x 415mm



WHITE

7W VT-1009D

EAN Code

3800157605281



7039 { 3000K Warm White
4000K Day White
5000K White



Voltage/Frequency:	AC: 100-240V, 50/60Hz	PF:	>0.45
Luminous Flux:	650lm	Beam Angle:	120°
IP Rating:	IP20	Color:	White
CRI:	> 80	Body Type:	ABS + Aluminum
		Dimension:	240 x 396 x 180mm



Black and White

7W VT-1009D

EAN Code

3800157605298



7040 { 3000K Warm White
4000K Day White
5000K White



Voltage/Frequency:	AC: 100-240V, 50/60Hz	PF:	>0.45
Luminous Flux:	650lm	Beam Angle:	120°
IP Rating:	IP20	Color:	Black + White
CRI:	> 80	Body Type:	ABS + Aluminum
		Dimension:	240 x 396 x 180mm



White with Silver

7W VT-1010D

EAN Code

3800157603829



7033 { 3000K Warm White
4000K Day White
5000K White



Voltage/Frequency:	AC: 100-240V, 50/60Hz	PF:	>0.45
Luminous Flux:	700lm	Beam Angle:	120°
IP Rating:	IP20	Color:	White with Silver
CRI:	> 80	Body Type:	ABS + Aluminum
		Dimension:	325 x 425 x 205mm



Dimmable

WHITE

7W VT-1008D

7035 5000K White

EAN Code

3800157603843



Voltage/Frequency:	AC: 100-240V, 50/60Hz	PF:	>0.45
Luminous Flux:	400lm	Beam Angle:	120°
IP Rating:	IP20	Color:	White
CRI:	> 80	Body Type:	ABS
		Dimension:	170 x 352 x 113mm



TOUCH DIMMING

WHITE

5W VT-1015

7051 4000K Day White

EAN Code

3800157610650



Voltage/Frequency:	AC: 100-240V, 50/60Hz	PF:	>0.45
Luminous Flux:	360lm	Beam Angle:	90°
IP Rating:	IP20	Color:	White
CRI:	> 80	Body Type:	ABS + Metal
		Dimension:	210 x 136 x 32mm



TOUCH DIMMING

BLACK

5W VT-1015

7052 4000K Day White

EAN Code

3800157610667



Voltage/Frequency:	AC: 100-240V, 50/60Hz	PF:	>0.45
Luminous Flux:	360lm	Beam Angle:	90°
IP Rating:	IP20	Color:	White
CRI:	> 80	Body Type:	ABS + Metal
		Dimension:	210 x 136 x 32mm



WHITE

7W VT-1017

7053 4000K Day White

A+

EAN Code

3800157610674



Voltage/Frequency:	AC: 100-240V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	500lm	Color:	White
IP Rating:	IP20	Body Type:	ABS + Metal
CRI:	> 80	Dimension:	376 x 166 x 270mm
PF:	>0.45		



BLACK

7W VT-1017

7054 4000K Day White

A+

EAN Code

3800157610681



Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	500lm	Color:	Black
IP Rating:	IP20	Body Type:	ABS + Metal
CRI:	>80	Dimension:	376 x 166 x 270mm
PF:	>0.45		



Light Wooden

6W VT-1012

SKU 7049

EAN Code

3800157610452



RECHARGEABLE



TOUCH DIMMING

Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	360°
Luminous Flux:	230lm	Color:	Light Wooden
IP Rating:	IP20	Body Type:	ACRYLIC + ABS
CRI:	>80	Dimension:	Ø108 x 172mm
PF:	>0.45		



MATT WHITE

6W VT-1012

SKU 7050

EAN Code

3800157610469



RECHARGEABLE



TOUCH DIMMING

Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	360°
Luminous Flux:	230lm	Color:	Matt White
IP Rating:	IP20	Body Type:	ACRYLIC + ABS
CRI:	>80	Dimension:	Ø108 x 172mm
PF:	>0.45		

Mood Lighting

Control your lights the way you want



BLUETOOTH
SPEAKER



Dimmable

Dimmable Table Lamp With Smart Speakers



RED 8509 3000K RGB
EAN Code 3800157621601



BLUE 8510 3000K RGB
EAN Code 3800157621618




BLACK 8511 3000K RGB
EAN Code 3800157621625




PINK 8512 3000K RGB
EAN Code 3800157621632



WHITE 8513 3000K RGB
EAN Code 3800157621649



Ø 95 x 122 mm



Color:	RGB + WW	Frequency response:	87-108 MHz
Watts:	5W	The sensitivity:	90db
Beam angle:	360°	Signal to noise ratio:	>80db
Voltage:	AC: 100-240v, 50/60Hz	Material:	ABS
Rating input:	DC: 5V	Built-in lithium battery:	2000 mAh
USB output:	5V 2A	Charging time:	2~3 hours
Transmission distance:	<10m	Working time:	3~4 hours (minimum), 20~24 hours (maximum)
Dimmable:	Yes		



PURPLE

5W VT-1035

SKU 8501



TOUCH DIMMING

EAN Code
3800157620345



EQ. Watts:	30W	PF:	>0
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	90°
Luminous Flux:	300lm	Color:	Chrome + Purple
IP Rating:	IP20	Body Type:	PC + Metal
CRI:	>80	Dimension:	



PURPLE Wall Lamp

7W VT-1036

SKU 8504

EAN Code
3800157620376



EQ. Watts:	40W	PF:	>0
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	90°
Luminous Flux:	360lm	Color:	Chrome + Purple
IP Rating:	IP20	Body Type:	PC + Metal
CRI:	>80		



WHITE

5W VT-1035

SKU 8502



TOUCH DIMMING

EAN Code
3800157620352



EQ. Watts:	30W	PF:	>0
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	90°
Luminous Flux:	300lm	Color:	Chrome + White
IP Rating:	IP20	Body Type:	PC + Metal
CRI:	>80		



WHITE Wall Lamp

7W VT-1036

SKU 8505

EAN Code
3800157620383



EQ. Watts:	40W	PF:	>0
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	90°
Luminous Flux:	360lm	Color:	Chrome + White
IP Rating:	IP20	Body Type:	PC + Metal
CRI:	>80		



BLUE

5W VT-1035

SKU 8503



TOUCH DIMMING

EAN Code

3800157620369



EQ. Watts:	30W	PF:	>0
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	90°
Luminous Flux:	300lm	Color:	Chrome + Blue
IP Rating:	IP20	Body Type:	PC + Metal
CRI:	>80		



BLUE Wall Lamp

7W VT-1036

SKU 8506

EAN Code

3800157620390



EQ. Watts:	40W	PF:	>0
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	90°
Luminous Flux:	360lm	Color:	Chrome + Blue
IP Rating:	IP20	Body Type:	PC + Metal
CRI:	>80		



SLIVER

Max. **60W** VT-7500
7056

EAN Code
3800157610704



Max. Watts:	60W	Color:	White
Voltage/Frequency:	AC:220-240V,50Hz	Body Type:	ABS + Metal
Holder:	E27	Dimension:	Ø250 x H1800mm
IP Rating:	IP20		

BLACK

Max. **60W** VT-7500
7055

EAN Code
3800157610698



Max. Watts:	60W	Color:	Black
Voltage/Frequency:	AC:220-240V,50Hz	Body Type:	ABS + Metal
Holder:	E27	Dimension:	Ø250 x H1800mm
IP Rating:	IP20		



WHITE

Max. **60W** VT-7600

EAN Code

3704 Floor Lamp

3800157610773

Max. Watts:	60W	Color:	White
Voltage/Frequency:	AC:220-240V,50Hz	Body Type:	Aluminum + Glass
Holder:	E27	Dimension:	200 x 200 x 1600mm
IP Rating:	IP20		



BLACK

Max. **60W** VT-7600

EAN Code

3703 Floor Lamp

3800157610766

Max. Watts:	60W	Color:	Matt Black
Voltage/Frequency:	AC:220-240V,50Hz	Body Type:	Aluminum + Glass
Holder:	E27	Dimension:	200 x 200 x 1600mm
IP Rating:	IP20		



WHITE

7W VT-7700

8507 4000K Day White

Built In LED

EAN Code

3800157620406



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	420lm	Color:	White
IP Rating:	IP20	Body Type:	ABS + Metal
CRI:	> 80	Dimension:	220 x440 x H1035.5mm



BLACK

7W VT-7700

8508 4000K Day White

Built In LED

EAN Code

3800157620413



EQ. Watts:	40W	PF:	>0.5
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	420lm	Color:	Black
IP Rating:	IP20	Body Type:	ABS + Metal
CRI:	>80	Dimension:	220 x440 x H1035.5mm



LED Outdoor Lights

Transform the exteriors of a Building or a Garden into a Beautiful piece of Architecture.

Simultaneously help navigate obstacles at night, prevent accidents and provide security.

Product Features

- Perfect replacement for traditional fittings as they are more flexible & efficient
- Work perfectly in extreme temperatures from -20° to $+45^{\circ}$ without any adverse effects
- Specifically designed for Outdoor use
- IP65/67 Protection Rating to ensure safety
- Low Maintenance
- Outstanding Colour options and settings

Applications

- Used for Gardens, Outdoor Residential Areas, Walkways & Passages, Driveways, Fountains, Lawns, Entrance, Patio or Terrace and similar environments



White
1.5W VT-767

3000k Warm White }
4000k Day White } 7096

EAN Code
3800157616966



Watts:	1.5W	Sensing Range	2-6 mtrs
Voltage:	3.7V Lithium Battery 1200mA	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	200lm	Working Time:	Min 8 hrs and Max 24 hrs
Color:	4000k + 3000k	Protection Rating:	IP65
No. of LED:	10pcs (Front 8pcs, Back 2 pcs)	Material:	High quality Mono crystal Silicon
Detecting Angle:	120°	Dimension:	152 x 96 x 83.4mm



Black
1.5W VT-767

3000k Warm White }
4000k Day White } 7097

EAN Code
3800157616973



Watts:	1.5W	Sensing Range	2-6 mtrs
Voltage:	3.7V Lithium Battery 1200mA	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	200lm	Working Time:	Min 8 hrs and Max 24 hrs
Color:	4000k + 3000k	Protection Rating:	IP65
No. of LED:	10pcs (Front 8pcs, Back 2 pcs)	Material:	High quality Mono crystal Silicon
Detecting Angle:	120°	Dimension:	152 x 96 x 83.4mm

White & Grey

2W VT-718

9853 3000K Warm White
9854 4000K Day White
9852 6000K White

EAN Code

3800157622806
3800157622813
3800157622790



Watts:	2W	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	200lm	Working Time:	Min 5-8 hrs and Max 24 hrs
Color:	3000k, 4000k, 6000k	Protection Rating:	IP65
No. of LED:	18pcs (SMD 2835)	Material:	ABS + PC
Voltage:	3.7V Lithium Battery 1200 mAh	Size:	162 x 147 x 130mm
Detecting Angle:	120°	Housing color:	White + Grey
Sensing Range	2-6 mtrs		



White & Black

3W VT-768

3000k Warm White } 7523
4000k Day White }

EAN Code

3800157619363



Watts:	3W	Sensing Range	2-6 mtrs
Voltage:	400lm	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	4000k + 3000k	Working Time:	Min 5-8 hrs and Max 24 hrs
Color:	30pcs (Front 28pcs, Back 2 pcs)	Protection Rating:	IP65
No. of LED:	3.7V Lithium Battery 2000mA	Material:	ABS + PC
Detecting Angle:	60°	Dimension:	140 x 212 x 109.2



18W VT-1233

5103 RGB
5106 3000K Warm White
5102 6000K White

EAN Code

3800230627124
3800157601115
3800230627117



EQ. Watts:	100W	Body Type:	Thick Glass
Voltage/Frequency:	AC: 12V, 50/60Hz	IP Rating:	IP68
Luminous Flux:	1100lm	Dimension:	D: 168mm x 105mm
Beam AngleRI:	120°		



18W VT-1235

5105 3000K Warmwhite
5104 6000K White

EAN Code

3800157601108
3800157601092



EQ. Watts:	100W	Body Type:	PVC Case
Voltage/Frequency:	AC: 12V, 50/60Hz	IP Rating:	IP68
Luminous Flux:	1100lm	Dimension:	D: 298mm x 76mm
Beam AngleRI:	180°		



Wall Fixtures

Model No:	VT-722	VT-726
SKU:	4793	7032
Type:	Wall	Wall
Holder:	2 x GU10	E27
Material:	304SS, Glass	304SS Lampbody, Frosted PC
Color of Fixture:	Silver	Satin Nickle
IP Rating:	IP44	IP44
Dimension:	Ø60 x 156mm	Ø102 x 200mm
EAN Code:	3800230625281	3800157603713



Wall Fixtures

Model No:	VT-7621	VT-7622
SKU:	7501	7500
Type:	Wall	Wall
Holder:	GU10	2 x GU10
Material:	Stainless Steel	Stainless Steel
Color of Fixture:	Stainless Steel Brush	Stainless Steel Brush
IP Rating:	IP44	IP44
Dimension:	Ø93 x 85 x 118mm	Ø93 x 85 x 163mm
EAN Code:	3800157617604	3800157617598



Wall Fixtures

Model No:	VT-7621 PIR Sensor	VT-7622 PIR Sensor	VT-7631
SKU:	7502	7503	7505
Type:	Wall	Wall	Wall
Holder:	GU10	2 x GU10	GU10
Material:	Stainless Steel	Stainless Steel	Stainless Steel
Color of Fixture:	Stainless Steel Brush	Stainless Steel Brush	Stainless Steel Brush
IP Rating:	IP44	IP44	IP44
Dimension:	Ø110 x 67 x 163mm	Ø110 x 67 x 220mm	Ø110 x 60 x 125mm
EAN Code:	3800157617611	3800157617628	3800157617642



Wall Fixtures

Model No:	VT-7632	VT-7641	VT-7642
SKU:	7504	7506	7507
Type:	Wall	Wall	Wall
Holder:	2 x GU10	GU10	2 x GU10
Material:	Stainless Steel	Stainless Steel	Stainless Steel
Color of Fixture:	Stainless Steel Brush	Stainless Steel Brush	Stainless Steel Brush
IP Rating:	IP44	IP44	IP44
Dimension:	Ø110 x 60 x 178mm	Ø105 x 76 x 118mm	Ø105 x 76 x 207mm
EAN Code:	3800157617635	3800157617659	3800157617666



IP44
RATED



IP44
RATED

Wall Fixtures

Model No:	VT-7651	VT-7651
SKU:	7508	7510
Type:	Wall	Wall
Holder:	GU10	GU10
Material:	Aluminium	Aluminium
Color of Fixture:	Black	Black
IP Rating:	IP44	IP44
Dimension:	Ø92 x 68 x 80mm	92 x 68 x 80mm
EAN Code:	3800157617673	3800157617697



LIGHTS



IP44
RATED



LIGHTS



IP44
RATED



LIGHTS



IP44
RATED

Wall Fixtures

Model No:	VT-7652	VT-7652	VT-7662
SKU:	7509	7511	7512
Type:	Wall	Wall	Wall
Holder:	2 x GU10	2 x GU10	2 x GU10
Material:	Aluminium	Aluminium	Stainless Steel
Color of Fixture:	Black	Black	Black
IP Rating:	IP44	IP44	IP44
Dimension:	Ø92 x 68 x 150mm	92 x 68 x 150mm	85 x 87 x 250mm
EAN Code:	3800157617680	3800157617703	3800157617710



Underground Fixtures

Model No:	VT-721 UG	VT-7677	VT-7677
SKU:	4791	7515	7516
Type:	Underground	Underground	Underground
Holder:	GU10	GU10	GU10
Material:	Aluminum, 304SS, Glass	Stainless Steel	Stainless Steel
Color of Fixture:	Black Lamp Body	Black	Black
IP Rating:	IP65	IP65	IP65
Dimension:	101 x 109 x 145mm	Ø110 x 110 x 120mm	110 x 110 x 120mm
EAN Code:	3800230625267	3800157617741	3800157617758



Garden Spikes

Model No:	VT-723 UG	VT-769	VT-770
SKU:	4792	7517	7518
Type:	Garden Spike	Garden Spike	Garden Spike
Holder:	GU10	GU10	GU10
Material:	Aluminum, 304SS, Glass	Aluminium	Stainless Steel
Color of Fixture:	Black Lamp Body	Black	Silver
IP Rating:	IP67	IP44	IP44
Dimension:	Ø95 x 317mm	95 x 95 x 335mm	60 x 60 x 420mm
EAN Code:	3800230625274	3800157617765	3800157617772



Garden Lamps

VTAC LED presents, the perfect outdoor lighting to make your garden glow after the sun goes down. Step outside with our wide range of contemporary outdoor lighting and decorate your pathways, walls, floors and ceilings with our modern designs.

Product Features

- Traditional Garden Lamps designed to fit the Modern day requirements
- Available in different designs, shapes and sizes
- Waterproof Lamps available in series of IP rating from IP 44 to IP 66
- Easy installation
- Applicable with GU10 -E27 base lights
- Suitable for Walls, Floor, Pathways and Ceiling Lights



Applications

Suitable for Outdoor Lighting





Wall Lamp

PLASTIC
DIFFUSER

VT-745
7064

EAN Code
3800157614399

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP54
Holder:	E27
Color of Fixture:	Matt Black
Body Type:	Aluminium + Plastic
Size:	145 x 265mm




Wall Lamp

PLASTIC
DIFFUSER

VT-745
7065

EAN Code
3800157614405

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP54
Holder:	E27
Color of Fixture:	Dark Grey
Body Type:	Aluminium + Plastic
Size:	145 x 265mm





Wall Lamp

**PLASTIC
DIFFUSER**


VT-754

EAN Code

7077

3800157616300

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	White
Body Type:	Aluminium + Plastic
Size:	245 x 180 x 93mm



Wall Lamp

**PLASTIC
DIFFUSER**


VT-754

EAN Code

7076

3800157616294

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminium + Plastic
Size:	245 x 180 x 93mm




Wall Lamp



VT-7670 EAN Code
7513 3800157617727

Voltage:	AC: 220-240V
Max.Watts:	14W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	White
Body Type:	Stainless Steel + PC
Size:	250 x 90 x 100mm




Wall Lamp



VT-7680 EAN Code
7514 3800157617734

Voltage:	AC: 220-240V
Max.Watts:	14W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	White
Body Type:	Stainless Steel + PC
Size:	250 x 90 x 100mm





Wall Lamp


VT-730

EAN Code

7046

3800157610391

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminum + Glass
Size:	200 x 238mm



Wall Lamp


VT-731

EAN Code

7047

3800157610407

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminum + Glass
Size:	200 x 238mm




Wall Lamp



VT-751
7070

EAN Code
3800157616232

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminium + Glass
Size:	215 x375 x 170mm




Wall Lamp



VT-751
7071

EAN Code
3800157616249

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	White
Body Type:	Aluminium + Glass
Size:	215 x375 x 170mm




Wall Lamp



VT-749 EAN Code
7066 3800157616195

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminium + Glass
Size:	208 x 360 x170 mm




Wall Lamp



VT-749 EAN Code
7067 3800157616201

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	White
Body Type:	Aluminium + Glass
Size:	208 x 360 x170 mm






Wall Lamp

VT-750 EAN Code
7068 3800157616218


Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminium + Glass
Size:	208 x 360 x170 mm



Wall Lamp

VT-750 EAN Code
7069 3800157616225

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	White
Body Type:	Aluminium + Glass
Size:	208 x 360 x170 mm




Wall Lamp - Short up

VT-760 EAN Code
7519 3800157617789



Voltage:	AC: 220-240V
Max.Watts:	60W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Matt Black
Body Type:	Aluminium + Glass
Size:	225 x 400 x 148mm




Wall Lamp - Short up

VT-760 EAN Code
7520 3800157617796



Voltage:	AC: 220-240V
Max.Watts:	60W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Matt White
Body Type:	Aluminium + Glass
Size:	225 x 400 x 148mm






Wall Lamp - Long up

VT-761 EAN Code
7521 3800157617802


Voltage:	AC: 220-240V
Max.Watts:	60W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Matt Black
Body Type:	Aluminium + Glass
Size:	245 x 445 x 185mm



Wall Lamp - Long up

VT-761 EAN Code
7522 3800157617819

Voltage:	AC: 220-240V
Max.Watts:	60W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Matt White
Body Type:	Aluminium + Glass
Size:	245 x 445 x 185mm






Ceiling Lamp

VT-752 EAN Code
7072 3800157616256


Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminium + Glass
Size:	170 x 170 x 840mm



Ceiling Lamp

VT-752 EAN Code
7073 3800157616263

Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	White
Body Type:	Aluminium + Glass
Size:	170 x 170 x 840mm






Ceiling Lamp

VT-735 EAN Code
7058 3800157612616


Voltage:	AC: 220-240V
Max.Watts:	60W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminum + Glass
Size:	170 x 720mm



Stand Lamp

VT-736 EAN Code
7059 3800157612623

Voltage:	AC: 220-240V
Max.Watts:	60W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminum + Glass
Size:	170 x 600mm






Stand Lamp

VT-753 EAN Code
7074 3800157616270


Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminium + Glass
Size:	170 x 170 x 403mm



Stand Lamp

VT-753 EAN Code
7075 3800157616287


Voltage:	AC: 220-240V
Max.Watts:	40W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	White
Body Type:	Aluminium + Glass
Size:	170 x 170 x 403mm



Stand Lamp

VT-754 EAN Code
7057 3800157612609

Voltage:	AC: 220-240V
Max.Watts:	60W
IP Rating:	IP65
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminum + Glass
Size:	170 x 290mm






Stand Lamp

VT-737 EAN Code
7060 3800157612630


Voltage:	AC: 220-240V
Max.Watts:	60W
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminum + Glass
Size:	345 x 1365mm



Stand Lamp

VT-738 EAN Code
7061 3800157612647

Voltage:	AC: 220-240V
Max.Watts:	60W x 2
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminum + Glass
Size:	480 x 1410mm






Stand Lamp

VT-739 EAN Code
7062 3800157612654


Voltage:	AC: 220-240V
Max.Watts:	60W x 2
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminum + Glass
Size:	500 x 1990mm




Stand Lamp

VT-740 EAN Code
7063 3800157612661

Voltage:	AC: 220-240V
Max.Watts:	60W x 3
IP Rating:	IP44
Holder:	E27
Color of Fixture:	Black
Body Type:	Aluminum + Glass
Size:	500 x 1990mm







LED Wall Lights

Presenting modern wall lights, the perfect replacement from the old tradition lights. A combination which can be applied for indoor and outdoor lighting. Style up your bedroom, hall or even pathways with the soft light illuminated from our design.

Product Features

- Modern Wall lights available in sleek and stylish designs.
- Adjustable Beam Angle.
- Available in Black, Grey & White Colors
- Easy installation
- Perfect for Halls, Pathways, Bedroom, Kitchen & Terrace



Applications

Suitable for Residential lighting, Hotels, Restaurants, Resorts, Residential Lighting and similar environment



Wall Lamp


6W VT-741

7524 3000k Warm White
7525 4000K Day White



EAN Code

3800157620017
3800157620024



EQ. Watts:	50W	PF:	0.55
Voltage/Frequency:	AC220-240V, 50/60 Hz	Beam Angle:	360°
Luminous Flux:	660lm	Color of Fixture:	White
IP Rating:	IP20	Shape:	Die-cast Aluminum
CRI:	>80	Dimension:	ø 135 mm



Wall Lamp


9W VT-743

7526 3000k Warm White
7527 4000K Day White



EAN Code

3800157620031
3800157620048



EQ. Watts:	75W	PF:	0.55
Voltage/Frequency:	AC220-240V, 50/60 Hz	Beam Angle:	360°
Luminous Flux:	990lm	Color of Fixture:	White
IP Rating:	IP20	Shape:	Die-cast Aluminum
CRI:	>80	Dimension:	ø 180 mm




Black Wall Light-
Adjustable Beam Angle

6W VT-759
7078 3000K Warm White
7087 4000K Day White

EAN Code

3800157616379
3800157616874



EQ. Watts:	50W	PF:	>0.45
Voltage/Frequency:	AC: 110-240V, 50/60Hz	Beam Angle:	10~120°
Luminous Flux:	660lm	Color of Fixture:	Black
IP Rating:	IP65	Body Type:	Aluminium
CRI:	> 80	Dimension:	100 x 100 x 100mm

UP AND DOWN LIGHTS




White Wall Light-
Adjustable Beam Angle

6W VT-759
7079 3000K Warm White
7088 4000K Day White

EAN Code

3800157616386
3800157616881



EQ. Watts:	50W	PF:	>0.45
Voltage/Frequency:	AC: 110-240V, 50/60Hz	Beam Angle:	10~120°
Luminous Flux:	660lm	Color of Fixture:	White
Body Type:	IP65	Body Type:	Aluminium
CRI:	> 80	Dimension:	100 x 100 x 100mm

UP AND DOWN LIGHTS




Grey Wall Light-
Adjustable Beam Angle

6W VT-759
7080 3000K Warm White
7089 4000K Day White

EAN Code

3800157616393
3800157616898



EQ. Watts:	50W	PF:	>0.45
Voltage/Frequency:	AC: 110-240V, 50/60Hz	Beam Angle:	10~120°
Luminous Flux:	660lm	Color of Fixture:	Grey
IP Rating:	IP65	Body Type:	Aluminium
CRI:	> 80	Dimension:	100 x 100 x 100mm

UP AND DOWN LIGHTS




Black Wall Light-
Adjustable Beam Angle

6W VT-756

7081 3000K Warm White
7090 4000K Day White

EAN Code

3800157616409
3800157616904



EQ. Watts:	50W	PF:	>0.45
Voltage/Frequency:	AC: 110-240V, 50/60Hz	Beam Angle:	10~120°
Luminous Flux:	660lm	Color of Fixture:	Black
IP Rating:	IP65	Body Type:	Aluminium
CRI:	> 80	Dimension:	140 x 100 x 115mm

UP AND DOWN LIGHTS




White Wall Light-
Adjustable Beam Angle

6W VT-756

7082 3000K Warm White
7091 4000K Day White

EAN Code

3800157616416
3800157616911



EQ. Watts:	50W	PF:	>0.45
Voltage/Frequency:	AC: 110-240V, 50/60Hz	Beam Angle:	10~120°
Luminous Flux:	660lm	Color of Fixture:	White
Body Type:	IP65	Body Type:	Aluminium
CRI:	> 80	Dimension:	140 x 100 x 115mm

UP AND DOWN LIGHTS




Grey Wall Light-
Adjustable Beam Angle

6W VT-756

7083 3000K Warm White
7092 4000K Day White

EAN Code

3800157616423
3800157616928



EQ. Watts:	50W	PF:	>0.45
Voltage/Frequency:	AC: 110-240V, 50/60Hz	Beam Angle:	10~120°
Luminous Flux:	660lm	Color of Fixture:	Grey
IP Rating:	IP65	Body Type:	Aluminium
CRI:	> 80	Dimension:	140 x 100 x 115mm


UP AND DOWN LIGHTS



Wall Light-Rotatable

5W VT-757
7086 3000K Warm White
7093 4000K Day White

EAN Code
3800157616454
3800157616935




EQ. Watts:	45W	PF:	>0.45
Voltage/Frequency:	AC: 110-240V, 50/60Hz	Beam Angle:	10-360°
Luminous Flux:	560lm	Color of Fixture:	White
IP Rating:	IP44	Body Type:	Aluminium
CRI:	> 80	Dimension:	D:140 x 65mm-close D:140 x 105mm-open



Black Wall Light

5W VT-758
7084 3000K Warm White
7094 4000K Day White

EAN Code
3800157616430
3800157616942



EQ. Watts:	45W	PF:	>0.45
Voltage/Frequency:	AC: 110-240V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	560lm	Color of Fixture:	Black
Body Type:	IP44	Body Type:	Aluminium
CRI:	> 80	Dimension:	100 x 80 x 100mm


UP AND DOWN LIGHTS



White Wall Light

5W VT-758
7085 3000K Warm White
7095 4000K Day White


EAN Code
3800157616447
3800157616959



EQ. Watts:	45W	PF:	>0.45
Voltage/Frequency:	AC: 110-240V, 50/60Hz	Beam Angle:	120°
Luminous Flux:	560lm	Color of Fixture:	White
IP Rating:	IP44	Body Type:	Aluminium
CRI:	> 80	Dimension:	100 x 80 x 100mm

UP AND DOWN LIGHTS





LED Display Screen

VTAC LED's Display screen series perfectly designed for the best video output and display of images and information. Offering Display color of 281 trillions(synchronized). The perfect product for advertising and marketing.

Product Features

- Powerful LED display screen available in Indoor and Outdoor series
- Displays digital content such as Video, Images & Information
- Good Brand Value addition for Advertising
- Easy Installation
- Easy Installation

Applications

Suitable for Outdoor and Indoor Advertising, Hotel conference room, Restaurants, Showrooms, Casinos, Government facilities, Theaters, Retail outlets, Traffic control room, Security monitoring room, Stage background, HD cinema, Shopping malls, Railway stations, Airports.





Outdoor Display Screen

P6 Outdoor LED Finished Cabinet

SKU 11078 EAN Code 3800157617475 **A++**



Screen Parameter

Pixel Density	27777dots/sqm
Brightness	6500nits
Optimum View Distance	more than 6m
Gray Scale	16bits
Display Color	281 Trillions(synchronized)
Operation Power	220V-240V
Max Power Consumption	1350W/sqm
Control Mode	Synchronized
Refresh Frequency	400-800HZ
Fram Frequency	60HZ
Surport Signal Input	S-Video,RGBHV,YUV etc.
Control Distance	Utp140m, Single Mode Fiber 15km
Operating Humidity	10%-90%
Life Span(50% Brightness)	100000hrs
IP(Front/rear)	IP65/IP45

LED Cabinet Parameter

Cabinet Size(L*h*d)	768*768mm
Cabinet Resolution	128*128
Module Quantity Each Cabinet	4*4=16
Average Power Consumption	800w/cabinet
Cabinet Material	Iron
Cabinet Size	25kg/cabinet

LED Module Parameter

Pixel Pitch	6mm
Led Specification	SMD3535
Led Configuration	SMD 3 in 1
Module Size	192*192mm
Module Resolution	32*32=1024dot
Drive Method	1/8 scan constant current
Drive IC	SM16106



Indoor Display Screen

P5 Indoor LED Finished Cabinet

SKU EAN Code
11077 3800157617468 **A++**



Screen Parameter

Pixel Density	40000dots/sqm
Brightness	1800nits
Optimum View Distance	more than 5m
Gray Scale	16bits
Display Color	281 trillions(synchronized)
Operation Power	220V-240V
Max Power Consumption	750W/sqm
Control Mode	Synchronized
Refresh Frequency	400-700HZ
Fram Frequency	60HZ
Surport Signal Input	S-Video,RGBHV,YUV etc.
Control Distance	UTP140M,SINGLE MODE FIBER 15KM
Life Span(50% Brightness)	100000hrs
IP(Front/rear)	IP20

LED Cabinet Parameter

Cabinet Size(L*h*d)	640*640mm
Cabinet Resolution	128*128
Module Quantity Each Cabinet	2*4=8
Average Power Consumption	300w/cabinet
Cabinet Material	Iron
Cabinet Size	8kg/cabinet

LED Module Parameter

Pixel Pitch	5mm
Led Specification	SMD3528
Led Configuration	SMD 3 in 1
Module Size	320*160mm
Module Resolution	64*32=2048dot
Drive Method	1/16 scan constant current
Drive IC	SM16106



Indoor Display Screen

P4 Indoor LED Display Screen

SKU EAN Code
11079 3800157619493



-  Plug & Play
-  Ideal For Renting Purpose
-  Portable Moving For Events



Screen Parameter

Pixel Density	62500dots/sqm
Brightness	1100nits
Optimum View Distance	more than 5m
Gray Scale	16bits
Display Color	281 trillions(synchronized)
Operation Power	AC 220V-240V/ 50/60Hz
Power Consumption	300W/cabinet
Control Mode	Synchronized
Refresh Frequency	400-700HZ
Surport Signal Input	S-Video,RGBHV,YUV etc.
Control Distance	UTP140M,SINGLE MODE FIBER 15KM
Life Span(50% Brightness)	100000hrs
IP(Front)	IP40
Control System	PCTV nonlinearity card, DVI display card Linsn control system

LED Cabinet Parameter

Cabinet Size(L*h*d)	512*512*85mm
Cabinet Resolution	128*128
Module Quantity Each Cabinet	2*4=8
Power Consumption	300w/cabinet
Cabinet Material	Iron
Cabinet Weight	8kg/cabinet

LED Module Parameter

Pixel Pitch	4mm
Led Specification	SMD2121
Led Configuration	SMD 3 in 1
Module Size	256*128mm
Module Resolution	64*32=2048dot
Drive Method	1/16 scan constant current
Drive IC	SM16106
Power Consumption	25-30W



Media Player

SKU

11088

EAN Code

3800157622820

Features:

- | | |
|---|-----------------------|
| ✓ LED Display Player with Industrial PC | ✓ Input - AC:120-260V |
| ✓ One TS802 sending card inside | ✓ 1 x Audio In |
| ✓ Dual Display - Supports Max 1280*800 | ✓ 1 x Audio Out |
| ✓ Supports SD Memory Card/USB/HDMI Out/Internet | ✓ 1 x DVI In |
| ✓ USB and SD Card Memory Playing | ✓ 1 x HDMI Out |
| ✓ Compact and Easy to Install | ✓ 4 USB Interface |
| ✓ 7" Touch Screen with windows 10 Inside | |
| ✓ Size - 320*180*50mm | |

Accessories:



Sending Box

SKU 500082



Sending Card 802

SKU 500081



Bright Displaying
Light Weight **Cabinet**
High-definition



Stylish Pendants

Includes all mounting hardware for quick and easy installation and Filament vintage style bulb recommended (sold separately)

Product Features

- Stylish pendant lamps and holders available in various shapes and sizes.
- Most suitable with A60, Candle, ST-64 & Globe Bulb Series.
- Easy to Install.
- Vibrant & elegant colors available.
- Applicable with E14 & E27 base, up to 60W applicable.
- Pendant lamps available in Copper, Glass,
- Pendant holders available in Bottle Shape, Chrome, Wooden, Concrete, Metal & Porcelain series.


Applications

Perfect choice for Hotels, Bars, Commercial & Residential Lighting.




VT-7350
Huge Transparent

SKU: 3879
EAN Code: 3800157620970
Material: Glass + Metal
Size: 330 x 260 x 1000mm




VT-7350
Huge Black

SKU: 3880
EAN Code: 3800157620987
Material: Glass + Metal
Size: 330 x 260 x 1000mm




**VT-7306****Transparent chrome****3 wire suspension**

SKU: 3883
EAN Code: 3800157621014
Material: Glass
Size: Ø300 x 265 x 1000mm




**VT-7292****Gun Grey- 3 wire suspension**

SKU: 3887
EAN Code: 3800157621052
Material: Glass
Size: Ø300 x 265 x 1000mm

**VT-7380****Gun Grey- 3 wire suspension**

SKU: 3888
EAN Code: 3800157621069
Material: Glass
Size: Ø380 x 330 x 1000mm



VT-7303


Amber Gobe Shape

SKU: 3866

EAN Code: 3800157620765

Material: Glass + Metal

Size: 300 x 280 x 1000mm






VT-7302

Transparent Globe Glass


SKU: 3865
EAN Code: 3800157620758
Material: Glass + Metal
Size: 300 x 280 x 1000mm



VT-7229

Transparent Artistic Shape


SKU: 3867
EAN Code: 3800157620772
Material: Glass + Metal
Size: 265 x 190 x 1000mm






VT-7304
Double Glass- Amber + White

SKU: 3875
EAN Code: 3800157620932
Material: Glass + Metal
Size: 250 x 420 x 1000mm



VT-7181
Double Glass- Amber + White


SKU: 3878
EAN Code: 3800157620963
Material: Glass + Metal
Size: 180 x 350 x 1000mm






VT-7304
Double Glass- Gungrey+White

SKU: 3876
EAN Code: 3800157620949
Material: Glass + Metal
Size: 250 x 420 x 1000mm



VT-7181
Double Glass- Gungrey+White

SKU: 3877
EAN Code: 3800157620956
Material: Glass + Metal
Size: 180 x 350 x 1000mm





VT-7281
White Glass

SKU: 3884
EAN Code: 3800157621021
Material: Glass + Metal
Size: 285 x440 x1000mm






VT-7281
Black Glass

SKU: 3885
EAN Code: 3800157621038
Material: Glass + Metal
Size: 285 x440 x1000mm



VT-7281
Amber Glass


SKU: 3886
EAN Code: 3800157621045
Material: Glass + Metal
Size: 285 x440 x1000mm






VT-7210
Transparent Glass

SKU: 3730
EAN Code: 3800157611039
Material: Glass + Metal
Size: 245 x 230 x 1100mm



VT-7140
Amber Glass


SKU: 3736
EAN Code: 3800157611091
Material: Glass + Metal
Size: 140 x 240 x 1130mm






VT-7140
Transparent Glass

SKU: 3735
EAN Code: 3800157611084
Material: Glass + Metal
Size: 140 x 240 x1130mm



VT-7185
Transparent Glass


SKU: 3738
EAN Code: 3800157611114
Material: Glass + Metal
Size: 180 x 230 x1110mm






VT-7250
Transparent Glass

SKU: 3739
EAN Code: 3800157611121
Material: Glass + Metal
Size: 250 x 330 x 1220mm



VT-7290
Amber Glass



SKU: 3741
EAN Code: 3800157611145
Material: Glass + Metal
Size: 260 x 260 x 1150mm






VT-7300
Transparent Glass

SKU: 3737
EAN Code: 3800157611107
Material: Glass + Metal
Size: 300 x 250 x 1150mm



VT-7320
Amber Glass


SKU: 3740
EAN Code: 3800157611138
Material: Glass + Metal
Size: 250 x 280 x 1180mm






VT-7150
Amber Glass

SKU: 3732
EAN Code: 3800157611053
Material: Glass + Metal
Size: 145 x 160 x 1050mm



VT-7150
Green Glass


SKU: 3734
EAN Code: 3800157611077
Material: Glass + Metal
Size: 145 x 160 x 1050mm






VT-7150
Red Glass

SKU: 3731
EAN Code: 3800157611046
Material: Glass + Metal
Size: 145 x 160 x 1050mm



VT-7150
Clear Glass

SKU: 3733
EAN Code: 3800157611060
Material: Glass + Metal
Size: 145 x 160 x 1050mm






VT-7220
Transparent Glass

SKU: 3727
EAN Code: 3800157611008
Material: Glass + Metal
Size: 220 x 280 x 1150mm



VT-7220
Amber Glass


SKU: 3726
EAN Code: 3800157610995
Material: Glass + Metal
Size: 220 x 280 x 1150mm






VT-7130
Transparent Glass

SKU: 3818
EAN Code: 3800157615433
Material: Glass + Wood
Size: 135 x 240 x 1150mm



VT-7170
Transparent Glass

SKU: 3819
EAN Code: 3800157615440
Material: Glass + Wood
Size: 165 x 220 x 1100mm






3D Glass

VT-7015

Glass


SKU: 3830
EAN Code: 3800157616652
Material: Glass
Size: 150 x 140 x 1200mm



VT-7240

Transparent Glass


SKU: 3820
EAN Code: 3800157615457
Material: Glass + Wood
Size: 235 x 140 x 1050mm






VT-7422
Black

SKU: 3728
EAN Code: 3800157611015
Material: Aluminum
Size: 230 x 310x 1150mm



VT-7422
White

SKU: 3729
EAN Code: 3800157611022
Material: Aluminum
Size: 230 x 310x 1150mm






VT-7180

Transparent V Shape


SKU: 3863
EAN Code: 3800157620734
Material: Glass + Metal
Size:



VT-7226


Transparent Globe Shape

SKU: 3864
EAN Code: 3800157620741
Material: Glass + Metal
Size: 350 x 230mm




**VT-7142****Transparent Cone Shape**

SKU: 3861
EAN Code: 3800157620710
Material: Glass + Metal
Size: 140 x 160mm

**VT-7143****Transparent V Shape**

SKU: 3862
EAN Code: 3800157620727
Material: Glass + Metal
Size: 185 x 140 mm





VT-7400


Modern 6 Bulb Chandelier -Movable

SKU: 3889

EAN Code: 3800157621076

Material: Metal

Size:





VT-7200


Matt Grey

SKU: 3822

EAN Code: 3800157616577

Material: Metal


Size: 200 x 270 x 1300mm






VT-7332
Black Metal Globe Mesh

SKU: 3859
EAN Code: 3800157620697
Material: Metal
Size: Ø290 x 100 x 1340mm



VT-7252
Black Metal V Shape

SKU: 3860
EAN Code: 3800157620703
Material: Metal
Size: Ø290 x 100 x 1340mm






VT-7200
Champagne Gold

SKU: 3821
EAN Code: 3800157616560
Material: Metal
Size: 200 x 270 x 1300mm



VT-7200
Matt White


SKU: 3823
EAN Code: 3800157616584
Material: Metal
Size: 200 x 270 x 1300mm






VT-7131
Champagne Gold

SKU: 3824
EAN Code: 3800157616591
Material: Metal
Size: 130 x 250 x 1300mm



VT-7131
Matt Black


SKU: 3825
EAN Code: 3800157616607
Material: Metal
Size: 130 x 250 x 1300mm






VT-7131
Matt White

SKU: 3826
EAN Code: 3800157616614
Material: Metal
Size: 130 x 250 x 1300mm



VT-7132
Champagne Gold


SKU: 3827
EAN Code: 3800157616621
Material: Metal
Size: 130 x 220 x 1300mm






VT-7132
Matt Black

SKU: 3828
EAN Code: 3800157616638
Material: Metal
Size: 130 x 220 x 1300mm



VT-7132
Matt White

SKU: 3829
EAN Code: 3800157616645
Material: Metal
Size: 130 x 220 x 1300mm



LED Pendants | Copper Series



VT-8300

Rose Gold

SKU: 3710
EAN Code: 3800157610834
Material: Iron with Electric
Copper Paint
Size: Ø300mm





VT-8150
Rose Gold

SKU: 3713
EAN Code: 3800157610865
Material: Iron with Electric Copper Paint
Size: Ø150mm



VT-8220
Rose Gold

SKU: 3711
EAN Code: 3800157610841
Material: Iron with Electric Copper Paint
Size: Ø220mm





VT-8150
Chrome

SKU: 3712
EAN Code: 3800157610865
Material: Iron with Electric
Copper Paint
Size: Ø150mm



VT-8255
Rose Gold

SKU: 3709
EAN Code: 3800157610827
Material: Iron with Electric
Copper Paint
Size: Ø250mm





VT-8180
Chrome

SKU: 3707
EAN Code: 3800157610803
Material: Iron with Electric
Copper Paint
Size: Ø180mm



VT-8180
Rose Gold

SKU: 3708
EAN Code: 3800157610810
Material: Iron with Electric
Copper Paint
Size: Ø180mm





VT-8170
Rose Gold

SKU: 3714
EAN Code: 3800157610872
Material: Iron with Electric Copper Paint
Size: Ø170mm



VT-8230
Rose Gold

SKU: 3715
EAN Code: 3800157610889
Material: Iron with Electric Copper Paint
Size: Ø230mm





VT-8175
Chrome

SKU: 3705
EAN Code: 3800157610780
Material: Iron with Electric
Copper Paint
Size: Ø170mm



VT-8175
Rose Gold


SKU: 3706
EAN Code: 3800157610797
Material: Iron with Electric
Copper Paint
Size: Ø170mm





VT-8200
Rose Gold

SKU: 3716
EAN Code: 3800157610896
Material: Iron with Electric Copper Paint
Size: Ø200mm



VT-8250
Rose Gold

SKU: 3717
EAN Code: 3800157610902
Material: Iron with Electric Copper Paint
Size: Ø250mm






VT-7205

White Glass


SKU:	3759
EAN Code:	3800157611329
Material:	Glass + Wood
Size:	190 x 320 x 1120mm






VT-7115
White Glass

SKU: 3758
EAN Code: 3800157611312
Material: Glass + Wood
Size: 170 x 320 x 1120mm



VT-7177
Clear Glass


SKU: 3760
EAN Code: 3800157611336
Material: Glass + Wood
Size: 170 x 320 x 1120mm






VT-7162
White

SKU: 3868
EAN Code: 3800157620789
Material: Aluminum
Size: Ø160 x350 x600mm



VT-7162
Black


SKU: 3869
EAN Code: 3800157620796
Material: Aluminum
Size: Ø160 x350 x600mm





VT-7330


SKU: 3849
EAN Code: 3800157618984
Material: Concrete and Iron
Size: 400 x 250 x 1100mm






VT-7253

SKU: 3848
EAN Code: 3800157618977
Material: Concrete and Iron
Size: 250 x 310 x 1200mm



VT-7121


SKU: 3847
EAN Code: 3800157618960
Material: Concrete and Iron
Size: 120 x 380 x 1300mm





VT-7155


SKU: 3850
EAN Code: 3800157618991
Material: Concrete
Size: 160 x 290 x 1250mm





VT-7202

SKU: 3853
EAN Code: 3800157619028
Material: Concrete
Size: 180 x 160 x 1100mm




E27 Holder | Max 60W



VT-7291

SKU: 3854
EAN Code: 3800157619035
Material: Concrete with Wood
Size: 265 x 260 x 1050mm




*Bulbs not included



VT-7132

White


SKU: 3858
EAN Code: 3800157619073
Material: Concrete with Wood
Size: 290 x 250 x 1150mm



VT-7125

Grey


SKU: 3855
EAN Code: 3800157619042
Material: Concrete with Wood
Size: 120 x 210 x 1080mm






VT-7125
Green

SKU: 3856
EAN Code: 3800157619059
Material: Concrete with Wood
Size: 120 x 210 x 1080mm



VT-7125
Red


SKU: 3857
EAN Code: 3800157619066
Material: Concrete with Wood
Size: 120 x 210 x 1080mm






VT-7160

SKU: 3851
EAN Code: 3800157619004
Material: Concrete
Size: 160 x 150 x 2000mm



VT-7171


SKU: 3852
EAN Code: 3800157619011
Material: Concrete
Size: 180 x 130 x 2000mm





VT-7141
Champagne Gold

SKU: 3831
EAN Code: 3800157616669
Material: Metal
Size: 250 x 190 x 1250mm




E27 Holder | **Max 60W**



VT-7141
Matt Black

SKU: 3832
EAN Code: 3800157616676
Material: Metal
Size: 250 x 190 x 1250mm




**Bulbs not included*




VT-7161
Champagne Gold

SKU: 3833
EAN Code: 3800157616683
Material: Metal
Size: 225 x 225x 1250mm



VT-7161
Matt Black

SKU: 3834
EAN Code: 3800157616690
Material: Metal
Size: 225 x 225x 1250mm






VT-7320

Champagne Gold


SKU: 3835
EAN Code: 3800157616706
Material: Metal
Size: 320 x 320x 1350mm



VT-7320

Matt Black

SKU: 3836
EAN Code: 3800157616713
Material: Metal
Size: 320 x 320x 1350mm






VT-7321

Champagne Gold


SKU: 3837
EAN Code: 3800157616720
Material: Metal
Size: 320 x 320x 1350mm



VT-7321

Matt Black


SKU: 3838
EAN Code: 3800157616737
Material: Metal
Size: 320 x 320x 1350mm






VT-7225
Red Bronze

SKU: 3816
EAN Code: 3800157612760
Material: Aluminum+ Sand finish
Size: 260 x 330 x 1100 mm



VT-7340
Red Bronze

SKU: 3817
EAN Code: 3800157612777
Material: Aluminum+ Sand finish
Size: 360 x 420 x 1200mm





VT-7520


Sand Black

SKU: 3700

EAN Code: 3800157610735

Material: Aluminum + Sand finish


Size: 220 x 310 x 1375mm






VT-7520
Sand Grey

SKU: 3701
EAN Code: 3800157610742
Material: Aluminum + Sand finish
Size: 220 x 310 x 1375mm



VT-7520
Sand White


SKU: 3702
EAN Code: 3800157610759
Material: Aluminum + Sand finish
Size: 220 x 310 x 1375mm






VT-7425
White

SKU: 3756
EAN Code: 3800157611299
Material: Aluminum + Wooden Top
Size: 250 x 200x 1100mm



VT-7425
Black

SKU: 3757
EAN Code: 3800157611305
Material: Aluminum + Wooden Top
Size: 250 x 200x 1100mm






VT-7525

White


SKU: 3761
EAN Code: 3800157611343
Material: Iron + Wooden Top
Size: 250 x 400x 1200mm



VT-7525

Black


SKU: 3762
EAN Code: 3800157611350
Material: Iron + Wooden Top
Size: 250 x 400x 1200mm






VT-7535
White

SKU: 3763
EAN Code: 3800157611367
Material: Iron + Wooden Top
Size: 350 x 300x 1100mm



VT-7535
Black


SKU: 3764
EAN Code: 3800157611374
Material: Iron + Wooden Top
Size: 350 x 300x 1100mm






VT-7545
White

SKU: 3765
EAN Code: 3800157611381
Material: Iron + Wooden Top
Size: 350 x 300x 1100mm



VT-7545
Black


SKU: 3766
EAN Code: 3800157611398
Material: Iron + Wooden Top
Size: 350 x 300x 1100mm






VT-7777
Rose Gold

SKU: 3751
EAN Code: 3800157611244
Material: Metal
Size: 300 x 90x 1000mm



VT-7777
Matt Gold


SKU: 3752
EAN Code: 3800157611251
Material: Metal
Size: 300 x 90x 1000mm





VT-7424
Black

SKU: 3753
EAN Code: 3800157611268
Material: Metal
Size: 360 x 170x 1080mm




Adjustable
Height



VT-7201
Black


SKU: 3845
EAN Code: 3800157617192
Material: Metal
Size: 220 x 140x 600-1600mm






VT-7251
Globe Pendant

SKU: 3839
EAN Code: 3800157616744
Material: Acrylic glass
Size: 250 x 250x 1300mm



VT-7118
Rope

SKU: 3754
EAN Code: 3800157611275
Material: Rope
Size: 45x 57x 1500mm





VT-7558
Green

SKU: 3767
EAN Code: 3800157611404
Material: Glass
Size: Ø72 x 280x 1150mm



VT-7558
Blue

SKU: 3768
EAN Code: 3800157611411
Material: Glass
Size: Ø72 x 280x 1150mm




VT-7558
Red

SKU: 3769
EAN Code: 3800157611428
Material: Glass
Size: Ø72 x 280x 1150mm



VT-7558
Amber

SKU: 3770
EAN Code: 3800157611435
Material: Glass
Size: Ø72 x 280x 1150mm



VT-7558
Transparent

SKU: 3771
EAN Code: 3800157611442
Material: Glass
Size: Ø72 x 280x 1150mm



VT-7558
Pink

SKU: 3772
EAN Code: 3800157611459
Material: Glass
Size: Ø72 x 280x 1150mm



VT-7558
Yellow

SKU: 3773
EAN Code: 3800157611466
Material: Glass
Size: Ø72 x 280x 1150mm




VT-7558
Rose

SKU: 3774
EAN Code: 3800157611473
Material: Glass
Size: Ø72 x 280x 1150mm



VT-7558
Grey

SKU: 3775
EAN Code: 3800157611480
Material: Glass
Size: Ø72 x 280x 1150mm



VT-7558
Brown

SKU: 3776
EAN Code: 3800157611497
Material: Glass
Size: Ø72 x 280x 1150mm



VT-7778
White Wire

SKU: 3720
EAN Code: 3800157610933
Material: Wooden
Size: Ø73 x 102x 100mm





VT-7778
Black Wire

SKU: 3721
EAN Code: 3800157610940
Material: Wooden
Size: Ø73 x 102x 100mm



VT-7778
Blue Wire

SKU: 3722
EAN Code: 3800157610957
Material: Wooden
Size: Ø73 x 102x 100mm





VT-7778
Red Wire



SKU: 3723
EAN Code: 3800157610964
Material: Wooden
Size: Ø73 x 102x 100mm

VT-7778
Purple Wire

SKU: 3724
EAN Code: 3800157610971
Material: Wooden
Size: Ø73 x 102x 100mm

VT-7778
Green Wire


SKU: 3725
EAN Code: 3800157610988
Material: Wooden
Size: Ø73 x 102x 100mm






VT-7555
Red Bronze

SKU: 3840
EAN Code: 3800157617147
Base: E27
Size: Ø50x90x900mm



VT-7555
Brown Bronze

SKU: 3841
EAN Code: 3800157617154
Base: E27
Size: Ø50x90x900mm





VT-7555
Brass Bronze

SKU: 3842
EAN Code: 3800157617161
Base: E27
Size: Ø50x90x900mm




VT-7555
Bronze

SKU: 3843
EAN Code: 3800157617178
Base: E27
Size: Ø50x90x900mm



VT-7555
Gold

SKU: 3844
EAN Code: 3800157617185
Base: E27
Size: Ø50x90x900mm





VT-7998
White

SKU: 3803
EAN Code: 3800157612340
Base: E27
Size: Ø47x64x680mm




VT-7998
Black

SKU: 3804
EAN Code: 3800157612357
Base: E27
Size: Ø47x64x680mm



VT-7998
Green

SKU: 3805
EAN Code: 3800157612364
Base: E27
Size: Ø47x64x680mm





VT-7998
Blue

SKU: 3806
EAN Code: 3800157612371
Base: E27
Size: Ø47x64x680mm




VT-7998
Red

SKU: 3807
EAN Code: 3800157612388
Base: E27
Size: Ø47x64x680mm



VT-7998
Grey

SKU: 3808
EAN Code: 3800157612395
Base: E27
Size: Ø47x64x680mm






VT-7998
Yellow

SKU: 3809
EAN Code: 3800157612401
Base: E27
Size: Ø47x64x680mm



VT-7998
Brown

SKU: 3810
EAN Code: 3800157612418
Base: E27
Size: Ø47x64x680mm





VT-799

White

SKU: 3795
EAN Code: 3800157612265
Base: E27
Size: Ø47x64mm



VT-799

Black


SKU: 3796
EAN Code: 3800157612272
Base: E27
Size: Ø47x64mm



VT-799

Green

SKU: 3797
EAN Code: 3800157612289
Base: E27
Size: Ø47x64mm





VT-799

Blue

SKU: 3798
EAN Code: 3800157612296
Base: E27
Size: Ø47x64mm



VT-799

Red


SKU: 3799
EAN Code: 3800157612302
Base: E27
Size: Ø47x64mm



VT-799

Grey

SKU: 3800
EAN Code: 3800157612319
Base: E27
Size: Ø47x64mm






VT-799
Yellow

SKU: 3801
EAN Code: 3800157612326
Base: E27
Size: Ø47x64mm



VT-799
Brown

SKU: 3802
EAN Code: 3800157612333
Base: E27
Size: Ø47x64mm





VT-7668
Green

SKU: 3742
EAN Code: 3800157611152
Base: E27
Size: Ø50x95x1050mm






VT-7668
Red

SKU: 3743
EAN Code: 3800157611169
Base: E27
Size: Ø50x95x1050mm



VT-7668
Blue

SKU: 3744
EAN Code: 3800157611176
Base: E27
Size: Ø50x95x1050mm





VT-7668
Yellow

SKU: 3745
EAN Code: 3800157611183
Base: E27
Size: Ø50x95x1050mm






VT-7668
White

SKU: 3746
EAN Code: 3800157611190
Base: E27
Size: Ø50x95x1050mm



VT-7668
Black

SKU: 3747
EAN Code: 3800157611206
Base: E27
Size: Ø50x95x1050mm





VT-7668
Grey

SKU: 3748
EAN Code: 3800157611213
Base: E27
Size: Ø50x95x1050mm






VT-7668
Brown


SKU: 3749
EAN Code: 3800157611220
Base: E27
Size: Ø50x95x1050mm



VT-7668
Beige


SKU: 3750
EAN Code: 3800157611237
Base: E27
Size: Ø50x95x1050mm






VT-7999
Gold Aluminum

SKU: 3811
EAN Code: 3800157612425
Base: E27
Size: Ø50 x 100mm



VT-7999
Gold Aluminum


SKU: 3812
EAN Code: 3800157612432
Base: E27
Size: Ø50 x 100mm



VT-7999
Bronze Aluminum


SKU: 3813
EAN Code: 3800157612449
Base: E27
Size: Ø50 x 100mm





VT-7999
Bronze Aluminum

SKU: 3814
EAN Code: 3800157612456
Base: E27
Size: Ø50 x 100mm



VT-7999
Rose Gold Aluminum

SKU: 3815
EAN Code: 3800157612463
Base: E27
Size: Ø50 x 100mm



VT-7338

Base:
Size:

E27
Ø39x 60mm



White

SKU: 3755

EAN Code:

3800157611282



Black

SKU: 3782

EAN Code:

3800157611558



Blue -E27

SKU: 3783

EAN Code:

3800157611565



Brown

SKU: 3784

EAN Code:

3800157611572



Green

SKU : 3785

EAN Code:

3800157611589



Grey

SKU: 3786

EAN Code:

3800157611596

VT-7448


Rose Gold Set

SKU: 3777

EAN Code: 3800157611503

Base: E27

Size: Ø39x 60mm



Light Blue

SKU: 3787

EAN Code:

3800157611602



Orange

SKU: 3788

EAN Code:

3800157611619



Pink -E27

SKU: 3789

EAN Code:

3800157611626



Purple

SKU: 3790

EAN Code:

3800157611633



Red

SKU: 3791

EAN Code:

3800157611640



Rose Red -E27

SKU: 3792

EAN Code:

3800157611657




Yellow

SKU: 3793

EAN Code:

3800157611664



Beige

SKU: 3794

EAN Code:

3800157611671

VT-7228

Base: E27
Length: 1000mm

**Brown****SKU: 3475****EAN Code:**

3800157607919

**Blue****SKU: 3476****EAN Code:**

3800157607926

**White****SKU: 3477****EAN Code:**

3800157607933

**Black****SKU: 3478****EAN Code:**

3800157607940

**Pink****SKU: 3479****EAN Code:**

3800157607957

**Red****SKU: 3480****EAN Code:**

3800157607964

**Grey****SKU: 3481****EAN Code:**

3800157607971

**Light Blue****SKU: 3482****EAN Code:**

3800157609463

**Purple****SKU: 3483****EAN Code:**

3800157609470

**Orange****SKU: 3484****EAN Code:**

3800157609487

**Yellow****SKU: 3485****EAN Code:**

3800157609494

**Green****SKU: 3486****EAN Code:**

3800157609500



Designer Sleek

LED Pendants



Chrome Finish


10W VT-7018



SKU
3890 4000k Day White

EAN Code
3800157621083

Built In LED



EQ. Watts:	100W	Beam Angle:	120°
Voltage/Frequency:	220-240V, 50Hz	No. of LED:	90
Luminous Flux:	1350lm	Material :	Stainless steel + Metal +PMMA
LED Type:	SMD	Unit GW :	1.38KG
CRI:	>80	Life Span:	20,000h
PF:	≥0.8	Size :	940 x 55 x 800mm



Chrome Finish


24W VT-7024



SKU
3891 4000k Day White

EAN Code
3800157621090

Built In LED



EQ. Watts:	130W	Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	120
Luminous Flux:	1800lm	Material :	Stainless steel+metal+PMMA
LED Type:	SMD	Unit GW :	1.59KG
CRI:	>80	Life Span:	20,000h
PF:	≥0.8	Size :	1220 x 55 x 800mm




Chrome Finish

36W VT-7036




SKU
3892 4000k Day White

EAN Code
3800157621106 Built In LED



EQ. Watts:	200W	Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	180
Luminous Flux:	2700lm	Material :	Stainless steel+metal+PMMA
LED Type:	SMD	Unit GW :	1.82KG
CRI:	>80	Life Span:	20,000h
PF:	≥0.8	Size :	1820 x 55 x 800mm




Chrome Finish

36W VT-7037



SKU
3893 4000k Day White

EAN Code
3800157621113 Built In LED



EQ. Watts:	200W	Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	180
Luminous Flux:	2700lm	Material :	Stainless steel+metal+PMMA
LED Type:	SMD	Unit GW :	2.24KG
CRI:	>80	Life Span:	20,000h
PF:	≥0.8	Size :	940 x 120*60mm



Chrome Finish

8W VT-7008

A+


SKU

3894 4000k Day White

EAN Code

3800157621120

Built In LED



EQ. Watts:	50W	Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	40
Luminous Flux:	600	Material :	metal+PMMA
LED Type:	SMD	Unit GW :	0.72KG
CRI:	>80	Life Span:	20,000H
PF:	≥0.5	Size :	500 x 55 x 185mm



Chrome Finish

12W VT-7012

A


SKU

3895 4000k Day White

EAN Code

3800157621137

Built In LED



EQ. Watts:	70W	Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	60
Luminous Flux:	900lm	Material :	metal+PMMA
LED Type:	SMD	Unit GW :	0.82KG
CRI:	>80	Life Span:	20,000h
PF:	≥0.5	Size :	640 x 55 x 185mm


**Chrome Finish****8W** VT-7009CH**A⁺**

SKU

3900 4000k Day White

EAN Code

3800157621854

Built In LED

EQ. Watts:

Beam Angle:

120°Voltage/Frequency: **AC:220-240V,50Hz**

No. of LED:

40Luminous Flux: **600lm**

Material :

Stainless steel+aluminum+PMMA

LED Type:

SMD

Unit GW :

0.8

CRI:

>80

Life Span:

20,000h

PF:

≥0.8

Size :


455 x 45 x 190mm**Gold Finish****8W** VT-7009**A⁺**

SKU

3901 4000k Day White

EAN Code

3800157621861

Built In LED

EQ. Watts:

Beam Angle:

120°Voltage/Frequency: **AC:220-240V,50Hz**

No. of LED:

40Luminous Flux: **600lm**

Material :

Stainless steel+aluminum+PMMA

LED Type:

SMD

Unit GW :

0.8

CRI:

>80

Life Span:

20,000h

PF:

≥0.8

Size :

455 x 45 x 190mm




Chrome Finish
Ceiling Lamp

12W VT-7014



SKU
3902 4000k Day White

EAN Code
3800157621878 Built In LED



EQ. Watts:		Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	60
Luminous Flux:	900lm	Material :	Stainless steel+metal+PMMA
LED Type:	SMD	Unit GW :	1.08
CRI:	>80	Life Span:	20,000H
PF:	≥0.8	Size :	640 x 65 x65mm




Chrome Finish
Ceiling Lamp

18W VT-7021



SKU
3903 4000k Day White

EAN Code
3800157621885 Built In LED



EQ. Watts:		Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	90
Luminous Flux:	1350lm	Material :	Stainless steel+metal+PMMA
LED Type:	SMD	Unit GW :	1.28
CRI:	>80	Life Span:	20,000h
PF:	≥0.8	Size :	940 x 65 x65mm




Glass Wall Fixture

12W VT-7013



SKU **Built In LED**
3896 4000k Day White

EAN Code
3800157621144



EQ. Watts:	70W	Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	60
Luminous Flux:	900lm	Material :	Stainless steel+metal+glass
LED Type:	SMD	Unit GW :	1.01KG
CRI:	>80	Life Span:	20,000H
PF:	≥0.8	Size :	685 x 55 x 65mm




Glass Wall Fixture

18W VT-7019



SKU **Built In LED**
3897 4000k Day White

EAN Code
3800157621151



EQ. Watts:	100W	Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	90
Luminous Flux:	1350lm	Material :	Stainless steel+metal+glass
LED Type:	SMD	Unit GW :	1.50KG
CRI:	>80	Life Span:	20,000h
PF:	≥0.8	Size :	985 x 55 x 65mm




Glass Hanging Pendant

18W VT-7020


A

SKU **Built In LED**
3898 4000k Day White

EAN Code
3800157621168



EQ. Watts:	100W	Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	90
Luminous Flux:	1350lm	Material :	Stainless steel+metal+glass
LED Type:	SMD	Unit GW :	1.98KG
CRI:	>80	Life Span:	20,000h
PF:	≥0.8	Size :	985 x 55 x 800mm



Glass Ceiling Surface SKU **Built In LED**
3899 4000k Day White


36W VT-7038



EAN Code
3800157621175




EQ. Watts:	200W	Beam Angle:	120°
Voltage/Frequency:	AC:220-240V,50Hz	No. of LED:	180
Luminous Flux:	2700lm	Material :	Stainless steel+metal+glass
LED Type:	SMD	Unit GW :	3.53KG
CRI:	>80	Life Span:	20,000h
PF:	≥0.8	Size :	985 x 120 x75mm



Modern Circular

Chandeliers



Soft Light Chandelier


40W VT-40-1



SKU
3874 3000k Warm White

EAN Code
3800157620888 Built In LED

EQ. Watts:	480W	Beam Angle:	120°
Voltage/Frequency:	AC100-240V/50HZ	No. of LED:	240pcs
Luminous Flux:	3300lm	Material :	Steel+PC
LED Type:	SMD-2835	Unit GW :	3.90kgs
CRI:	>80	Life Span:	20,000h
PF:	>0.9	Size :	L.400 x W.400 x H.1000mm





Soft Light Chandelier (Slim 2 Step) SKU
60W VT-60-2 3872 3000k Warm White



Built In LED

EAN Code
3800157620864

EQ. Watts:	300W	Beam Angle:	120°
Voltage/Frequency:	AC100-240V/50HZ	No. of LED:	340pcs
Luminous Flux:	5500lm	Material :	Acrylic+Aluminum+Steel
LED Type:	SMD-2835	Unit GW :	5.8kgs
CRI:	>80	Life Span:	20,000h
PF:	>0.9	Size :	L.600 x W.600 x H.1200mm





Soft Light Chandelier (Slim 3 Step) SKU
70W VT-70-3 3873 3000k Warm White



Built In LED

EAN Code
3800157620871

EQ. Watts:	350W	Beam Angle:	120°
Voltage/Frequency:	AC100-240V/50HZ	No. of LED:	360pcs
Luminous Flux:	6000lm	Material :	Acrylic+Aluminum+Steel
LED Type:	SMD-2835	Unit GW :	6.70kgs
CRI:	>80	Life Span:	20,000h
PF:	>0.9	Size :	L.600 x W.600 x H.1200mm



Soft Light Chandelier (2 Step)

70W VT-70-2





Built In LED

SKU
3870 3000k Warm White

EAN Code
3800157620840

EQ. Watts:	350W	Beam Angle:	120°
Voltage/Frequency:	AC:100-240V/50HZ	No. of LED:	420pcs
Luminous Flux:	5600lm	Material :	Acrylic+Aluminum+Steel
LED Type:	SMD	Unit GW :	6.30kgs
CRI:	>80	Life Span:	20,000h
PF:	>0.9	Size :	L.600 x W.600 x H.1200mm



Soft Light Chandelier (3 Step)

80W VT-80-3




Built In LED

SKU
3871 3000k Warm White

EAN Code
3800157620857

EQ. Watts:	400W	Beam Angle:	120°
Voltage/Frequency:	AC:100-240V/50HZ	No. of LED:	510pcs
Luminous Flux:	5900lm	Material :	Acrylic+Aluminum+Steel
LED Type:	SMD	Unit GW :	7.30kgs
CRI:	>80	Life Span:	20,000h
PF:	>0.9	Size :	L.600 x W.600 x H.1200mm



Easy-Elegant-*Stylish*

add luxury 
TO YOUR HOME

V-TAC®
GALLERY

SKU		SKU		SKU		SKU		SKU	
1100	244	1244	120	1289	249	1334	226	2016	208
1101	244	1245	120	1292	229	1335	226	2025	209
1102	244	1246	120	1293	229	1336	226	2027	209
1103	244	1247	120	1294	229	1337	226	2030	209
1104	244	1248	120	1295	229	1338	227	2031	208
1105	245	1249	233	1296	229	1339	227	2032	208
1106	245	1250	233	1297	229	1340	227	2033	208
1107	245	1251	233	1298	228	1657	98	2034	208
1108	244	1252	233	1299	228	1658	98	2035	208
1110	248	1253	233	1300	228	1659	98	2036	208
1111	248	1254	233	1301	228	1663	99	2037	209
1112	248	1255	234	1302	228	1664	99	2038	209
1113	247	1256	234	1303	228	1665	99	2039	209
1114	247	1257	234	1304	249	1666	98	2041	208
1115	247	1259	266	1305	249	1667	98	2042	209
1116	247	1260	267	1306	249	1668	98	2043	208
1117	247	1261	267	1307	249	1669	100	2044	209
1118	247	1262	267	1308	256	1670	100	2118	206
1163	245	1263	264	1309	256	1671	100	2120	207
1164	245	1264	264	1310	256	1672	98	2122	207
1165	245	1265	264	1311	256	1673	98	2124	206
1191	231	1266	263	1312	256	1674	98	2126	207
1192	231	1267	263	1313	256	1679	102	2128	207
1201	231	1268	263	1314	250	1680	102	2129	206
1202	231	1269	265	1315	250	1681	102	2133	206
1207	253	1270	242	1316	250	1682	100	2135	206
1208	253	1271	242	1317	250	1683	100	2137	207
1209	253	1272	242	1318	250	1684	100	2138	207
1210	253	1273	242	1319	250	1685	101	2143	207
1223	253	1274	242	1320	251	1686	101	2144	206
1229	232	1275	242	1321	251	1687	101	2145	206
1230	232	1276	243	1322	251	1688	100	2148	207
1231	232	1277	243	1323	251	1689	100	2149	207
1232	232	1278	243	1324	251	1690	100	2150	207
1233	230	1279	243	1325	251	1693	99	2151	207
1234	230	1280	243	1326	252	1694	99	2152	207
1235	230	1281	261	1327	252	1695	99	2153	207
1236	230	1282	261	1328	252	2002	209	2155	207
1237	230	1284	254	1329	252	2005	208	2156	207
1238	230	1285	234	1330	252	2009	208	2159	210
1241	232	1286	234	1331	252	2011	208	2161	205
1242	232	1287	234	1332	226	2013	208	2162	205
1243	120	1288	249	1333	226	2015	208	2163	205

SKU		SKU		SKU		SKU		SKU	
2164	204	3037	211	3215	224	3502	215	3576	123
2165	204	3038	211	3219	224	3503	215	3577	123
2166	204	3050	222	3300	218	3504	215	3578	40
2350	215	3051	222	3303	218	3505	215	3581	123
2351	215	3052	222	3304	218	3507	215	3582	123
2352	215	3053	222	3307	218	3508	215	3583	123
2353	215	3054	222	3312	218	3509	215	3584	106
2354	215	3055	222	3317	218	3510	215	3585	106
2355	215	3056	222	3318	218	3511	215	3586	106
2356	215	3057	222	3319	219	3512	215	3587	107
2403	210	3058	222	3320	218	3522	237	3588	107
2404	210	3060	222	3321	219	3523	237	3589	107
2405	210	3061	222	3322	219	3524	237	3590	107
2430	210	3062	222	3326	219	3525	237	3591	107
2431	210	3069	223	3327	219	3526	237	3592	107
2459	210	3070	223	3328	219	3527	238	3593	109
2460	206	3071	223	3331	214	3528	238	3594	109
2461	204	3072	223	3333	214	3529	238	3595	110
2462	204	3073	223	3334	214	3543	236	3596	110
2463	204	3074	223	3417	96	3544	236	3597	110
2512	213	3075	223	3419	96	3545	235	3598	110
2513	213	3076	223	3420	96	3546	235	3599	111
2514	213	3077	223	3423	118	3547	236	3600	111
2515	213	3078	223	3469	114	3548	236	3601	111
2516	213	3081	223	3470	114	3549	235	3602	111
2517	213	3090	224	3471	114	3550	235	3603	111
2518	214	3091	224	3472	109	3553	236	3604	111
2527	214	3092	224	3473	109	3554	236	3605	112
2529	214	3093	224	3474	109	3555	235	3606	112
2531	214	3094	224	3475	406	3556	235	3607	112
3007	211	3095	224	3476	406	3557	239	3608	112
3008	211	3096	224	3477	406	3558	239	3609	112
3009	219	3097	224	3478	406	3559	239	3610	112
3016	211	3098	224	3479	406	3560	239	3611	113
3017	211	3099	224	3480	406	3565	239	3612	113
3018	219	3100	224	3481	406	3566	239	3613	113
3019	211	3101	224	3482	406	3567	236	3614	113
3030	211	3106	155	3483	406	3568	235	3615	114
3031	211	3107	155	3484	406	3569	235	3616	114
3032	211	3108	155	3485	406	3570	236	3617	118
3034	211	3109	155	3486	406	3572	235	3618	118
3035	211	3110	155	3500	215	3574	236	3619	118
3036	211	3214	224	3501	215	3575	123	3620	118

SKU		SKU		SKU		SKU		SKU	
3621	40	3709	359	3754	387	3801	399	3844	393
3622	40	3710	357	3755	405	3802	399	3845	386
3623	40	3711	358	3756	381	3803	394	3847	368
3624	202	3712	359	3757	381	3804	394	3848	368
3625	218	3713	358	3758	365	3805	394	3849	367
3627	117	3714	361	3759	364	3806	395	3850	369
3628	117	3715	361	3760	365	3807	395	3851	373
3629	117	3716	363	3761	382	3808	395	3852	373
3630	116	3717	363	3762	382	3809	396	3853	370
3631	116	3720	390	3763	383	3810	396	3854	370
3632	116	3721	390	3764	383	3811	403	3855	371
3633	240	3722	390	3765	384	3812	403	3856	372
3634	240	3723	391	3766	384	3813	403	3857	372
3635	238	3724	391	3767	388	3814	404	3858	371
3636	238	3725	391	3768	388	3815	404	3859	352
3637	238	3726	344	3769	388	3816	378	3860	352
3638	238	3727	344	3770	388	3817	378	3861	349
3639	238	3728	347	3771	388	3818	345	3862	349
3640	106	3729	347	3772	389	3819	345	3863	348
3641	106	3730	338	3773	389	3820	346	3864	348
3642	108	3731	343	3774	389	3821	353	3865	334
3643	108	3732	342	3775	389	3822	351	3866	333
3644	108	3733	343	3776	389	3823	353	3867	334
3645	108	3734	342	3777	405	3824	354	3868	366
3646	108	3735	339	3782	405	3825	354	3869	366
3647	108	3736	338	3783	405	3826	355	3870	422
3648	105	3737	341	3784	405	3827	355	3871	423
3649	105	3738	339	3785	405	3828	356	3872	420
3650	105	3739	340	3786	405	3829	356	3873	421
3651	105	3740	341	3787	405	3830	346	3874	419
3652	105	3741	340	3788	405	3831	374	3875	335
3653	105	3742	400	3789	405	3832	374	3876	336
3654	106	3743	400	3790	405	3833	375	3877	336
3655	237	3744	400	3791	405	3834	375	3878	335
3656	237	3745	401	3792	405	3835	376	3879	330
3663	219	3746	401	3793	405	3836	376	3880	330
3700	379	3747	401	3794	405	3837	377	3883	331
3701	380	3748	402	3795	397	3838	377	3884	337
3702	380	3749	402	3796	397	3839	387	3885	337
3705	362	3750	402	3797	397	3840	392	3886	337
3706	362	3751	385	3798	398	3841	392	3887	332
3707	360	3752	385	3799	398	3842	393	3888	332
3708	360	3753	386	3800	398	3843	393	3889	350

SKU		SKU		SKU		SKU		SKU	
3890	408	4224	122	4331	95	4416	124	4464	103
3891	409	4225	122	4332	95	4417	124	4465	103
3892	410	4226	74	4339	87	4418	124	4472	50
3893	411	4227	74	4340	87	4419	124	4473	45
3894	412	4228	75	4341	87	4420	124	4474	54
3895	412	4229	75	4342	81	4421	52	4475	54
3896	415	4230	75	4343	81	4422	69	4476	54
3897	415	4241	81	4344	81	4423	69	4477	54
3898	416	4242	86	4351	82	4424	69	4478	54
3899	417	4243	86	4352	82	4425	67	4479	54
3900	413	4244	87	4353	82	4426	67	4480	57
3901	413	4246	86	4354	82	4427	66	4481	57
3902	414	4247	84	4358	104	4428	66	4482	57
3903	414	4248	84	4359	104	4429	64	4483	57
4061	121	4249	84	4360	104	4430	64	4484	57
4062	121	4250	85	4361	52	4431	65	4485	57
4084	121	4251	85	4362	52	4432	65	4486	56
4086	121	4252	85	4363	61	4433	91	4487	56
4099	121	4253	91	4364	60	4434	91	4488	56
4106	121	4254	91	4365	65	4435	91	4489	53
4122	80	4255	121	4366	65	4437	103	4490	53
4123	85	4256	121	4367	66	4438	103	4491	53
4124	85	4257	121	4368	51	4439	103	4492	56
4138	86	4258	81	4369	70	4440	80	4493	56
4140	87	4259	60	4376	74	4441	79	4494	56
4156	82	4272	61	4377	74	4442	77	4495	56
4160	84	4273	91	4378	74	4443	77	4496	56
4162	84	4274	91	4388	66	4444	63	4497	56
4164	82	4275	75	4389	70	4445	63	4498	50
4166	80	4276	90	4390	70	4446	63	4499	49
4174	85	4277	90	4394	67	4447	72	4737	188
4175	77	4278	90	4395	67	4448	72	4738	188
4176	77	4279	90	4399	68	4449	72	4739	187
4197	77	4300	67	4406	62	4453	76	4740	187
4207	84	4301	64	4407	62	4454	76	4741	188
4209	74	4302	64	4408	62	4455	76	4742	188
4213	81	4303	61	4409	62	4456	76	4743	187
4215	81	4304	68	4410	62	4457	76	4744	187
4216	80	4305	68	4411	62	4458	76	4745	188
4219	86	4306	66	4412	62	4459	72	4746	188
4220	86	4307	64	4413	64	4460	72	4759	187
4221	87	4308	65	4414	64	4461	72	4760	187
4223	122	4324	77	4415	124	4463	103	4797	174

SKU		SKU		SKU		SKU		SKU	
4798	174	4860	164	4908	176	4953	174	5070	139
4800	178	4861	164	4909	176	4954	174	5071	139
4801	178	4862	164	4910	175	4965	261	5072	139
4802	178	4863	165	4911	175	4966	261	5073	139
4803	177	4864	165	4912	175	4967	273	5074	139
4804	177	4865	165	4913	176	4968	274	5075	139
4805	177	4866	165	4914	176	4969	268	5076	139
4806	178	4867	165	4915	176	4970	260	5077	273
4807	178	4868	165	4916	175	4971	260	5078	276
4808	178	4869	166	4917	175	4972	265	5079	276
4809	177	4870	166	4918	175	4973	265	5081	277
4810	177	4871	166	4919	176	4980	260	5082	277
4811	177	4872	164	4920	176	4981	260	5083	277
4812	178	4873	164	4921	176	4982	274	5084	278
4813	178	4874	164	4922	185	4983	259	5085	278
4814	178	4875	161	4923	185	4984	259	5086	270
4815	177	4876	161	4924	185	4985	259	5087	270
4816	177	4877	161	4925	185	4986	268	5088	271
4817	177	4878	161	4926	185	4987	135	5089	271
4818	168	4879	161	4927	185	4988	135	5090	272
4819	168	4880	161	4928	185	4989	135	5091	272
4820	168	4881	162	4929	185	4990	135	5092	246
4821	168	4882	162	4930	185	4991	135	5093	246
4822	168	4883	162	4931	171	4992	135	5094	246
4823	168	4884	162	4932	171	4993	135	5095	247
4824	169	4885	162	4933	171	4994	135	5096	247
4825	169	4886	162	4934	171	4995	135	5097	247
4826	169	4887	166	4935	171	4996	266	5098	246
4827	169	4888	166	4936	171	4997	266	5099	246
4828	169	4889	166	4937	172	4998	266	5107	246
4829	169	4890	186	4938	172	4999	266	5108	246
4830	170	4891	186	4939	172	5050	266	5109	246
4831	170	4892	186	4940	172	5051	267	5110	246
4832	170	4893	186	4941	172	5052	267	5116	220
4833	170	4894	186	4942	172	5053	264	5117	220
4834	170	4895	186	4943	173	5054	264	5118	220
4835	170	4896	186	4944	173	5055	263	5119	220
4854	163	4897	186	4945	173	5056	263	5120	220
4855	163	4898	186	4946	173	5057	262	5121	220
4856	163	4904	175	4947	173	5058	262	5122	220
4857	163	4905	175	4948	173	5059	262	5123	220
4858	163	4906	175	4949	174	5068	139	5124	221
4859	163	4907	176	4952	174	5069	139	5125	221

SKU		SKU		SKU		SKU		SKU	
5126	221	5547	194	5698	31	5778	9	5821	28
5127	221	5548	194	5699	32	5779	9	5822	26
5128	221	5549	194	5700	32	5780	13	5823	26
5129	221	5550	190	5701	32	5781	13	5824	26
5130	221	5551	190	5702	32	5782	13	5825	3
5131	221	5552	190	5713	17	5783	27	5826	3
5132	221	5553	190	5714	17	5784	27	5827	3
5133	221	5554	194	5715	31	5785	27	5828	7
5134	221	5555	194	5716	32	5786	25	5829	7
5135	221	5562	258	5717	32	5787	25	5830	7
5136	221	5563	258	5718	19	5788	25	5831	10
5137	221	5564	258	5719	19	5789	2	5832	10
5138	221	5565	258	5723	31	5790	2	5833	10
5139	221	5566	257	5724	31	5791	2	5834	14
5140	221	5567	257	5725	31	5792	6	5835	14
5386	36	5570	254	5726	37	5793	6	5836	14
5468	201	5571	275	5729	18	5794	6	5837	28
5471	200	5572	275	5730	18	5795	9	5838	28
5472	200	5649	36	5731	18	5796	9	5839	28
5473	200	5655	22	5732	18	5797	9	5840	26
5474	200	5656	22	5735	34	5798	13	5841	26
5475	200	5657	22	5745	35	5799	13	5842	26
5476	200	5658	22	5746	29	5800	13	5843	4
5477	200	5659	22	5747	29	5801	27	5844	4
5478	200	5660	22	5748	29	5802	27	5845	4
5479	201	5661	23	5749	29	5803	27	5846	8
5480	198	5662	23	5750	29	5804	25	5847	8
5481	199	5663	23	5751	30	5805	25	5848	8
5482	198	5664	23	5752	30	5806	25	5849	11
5532	193	5665	23	5753	30	5807	3	5850	11
5534	193	5666	23	5754	30	5808	3	5851	11
5535	192	5667	24	5755	34	5809	3	5852	15
5536	192	5668	24	5756	29	5810	7	5853	15
5537	193	5669	24	5757	30	5811	7	5854	15
5538	193	5686	17	5758	30	5812	7	5855	4
5539	192	5687	17	5760	19	5813	10	5856	4
5540	192	5691	34	5771	2	5814	10	5857	4
5541	195	5692	34	5772	2	5815	10	5858	8
5542	195	5693	36	5773	2	5816	14	5859	8
5543	191	5694	36	5774	6	5817	14	5860	8
5544	191	5695	37	5775	6	5818	14	5861	11
5545	191	5696	37	5776	6	5819	28	5862	11
5546	194	5697	31	5777	9	5820	28	5863	11

SKU		SKU		SKU		SKU		SKU	
5864	15	6055	140	6254	136	6307	130	6351	182
5865	15	6056	140	6256	151	6308	130	6352	180
5866	15	6057	140	6257	151	6309	129	6353	180
5875	20	6062	144	6258	151	6310	129	6354	180
5876	20	6069	152	6260	154	6311	136	6355	182
5877	20	6088	153	6261	154	6312	136	6356	182
5878	20	6091	154	6262	128	6313	131	6357	182
5879	20	6092	154	6263	129	6314	131	6358	183
5880	20	6093	154	6264	129	6315	131	6359	183
5881	21	6151	140	6265	129	6316	131	6360	183
5882	21	6166	138	6266	144	6318	132	6361	184
5883	21	6167	138	6267	144	6319	132	6362	184
5884	21	6168	138	6268	156	6320	132	6363	184
5885	21	6169	138	6269	156	6321	132	6364	183
5886	21	6170	138	6270	156	6322	133	6365	183
5894	33	6171	138	6271	156	6323	133	6366	183
5895	33	6172	138	6272	128	6324	133	6367	184
5896	40	6173	138	6273	129	6325	134	6368	184
5897	40	6174	138	6276	188	6326	134	6369	184
5898	20	6179	144	6277	187	6327	159	6370	183
5899	20	6184	143	6278	188	6328	156	6371	183
5900	20	6185	143	6279	187	6329	152	6372	183
5904	21	6200	143	6280	188	6330	150	6373	184
5905	21	6201	143	6281	187	6331	150	6374	184
5906	21	6202	137	6282	142	6332	153	6375	184
5909	5	6203	137	6283	142	6333	153	7044	125
5910	5	6217	147	6284	142	6334	179	7045	125
5911	12	6221	147	6285	142	6335	179	7100	49
5912	12	6222	147	6286	142	6336	179	7101	53
5913	16	6229	128	6287	142	6337	181	7102	53
5914	16	6230	128	6292	163	6338	181	7103	53
5915	38	6231	128	6293	163	6339	181	7104	53
5916	38	6236	148	6294	163	6340	179	7105	53
5917	35	6237	148	6295	165	6341	179	7106	53
6019	146	6238	149	6296	165	6342	179	7107	54
6026	152	6239	149	6297	165	6343	181	7108	54
6027	152	6240	148	6299	130	6344	181	7109	54
6029	146	6241	148	6301	130	6345	181	7110	55
6050	153	6242	148	6302	130	6346	180	7111	55
6051	153	6243	149	6303	130	6347	180	7112	55
6052	140	6250	132	6304	130	6348	180	7113	48
6053	140	6251	132	6305	130	6349	182	7114	48
6054	140	6253	136	6306	130	6350	182	7115	48

SKU		SKU		SKU		SKU		SKU	
7116	49	7168	102	7217	43	8073	167	48579	163
7121	71	7169	102	7218	42	8074	167	48589	163
7123	70	7170	61	7219	42	8075	167	48599	163
7124	70	7173	83	7220	42	8076	167	48609	164
7125	70	7174	83	7221	78	9104	39	48619	164
7126	101	7175	83	7222	78	9546	39	48629	164
7127	101	7176	55	7223	78	9921	161	48639	165
7128	101	7177	55	7224	72	9923	162	48649	165
7132	94	7178	58	7225	63	9924	162	48659	165
7133	94	7179	58	7226	63	9944	240	48669	165
7134	94	7180	58	7229	78	9945	240	48679	165
7135	92	7181	58	7230	79	9947	217	48689	165
7136	92	7182	58	7231	79	9952	240	48699	166
7137	92	7183	58	7232	79	9953	240	48709	166
7138	92	7184	58	7233	79	9954	240	48719	166
7139	92	7185	58	7234	122	9955	240	48729	164
7140	92	7186	58	7235	122	9967	158	48739	164
7141	92	7187	59	7236	122	9968	158	48749	164
7142	47	7188	59	7237	83	9969	158	48879	166
7143	47	7189	59	7238	83	9970	158	48889	166
7144	47	7190	59	7239	83	9981	216	48899	166
7145	45	7191	59	7240	73	9982	216	60246	146
7146	44	7196	80	7241	73	9983	216	60256	146
7147	44	7197	80	7242	73	9984	216	60266	152
7148	44	7198	80	7243	104	9985	216	60276	152
7150	71	7199	85	7244	104	9986	216	60286	146
7151	71	7200	85	7245	104	9987	216	60303	160
7152	57	7201	85	7246	73	9989	157	60696	152
7153	57	7202	84	7251	46	9990	217	62186	147
7154	57	7203	84	7252	46	9991	217	62196	147
7155	51	7204	84	7253	104	9992	217	62206	147
7156	51	7205	104	7254	104	9993	217	62366	148
7157	50	7206	104	7255	104	9994	217	62376	148
7158	93	7207	104	7256	83	9995	217	62406	148
7159	93	7208	89	7257	83	9997	157	62416	148
7160	93	7209	89	7258	83	11077	325	62426	148
7161	93	7210	89	8036	168	11078	324	62436	149
7162	93	7211	88	8037	169	11079	326	500081	327
7163	93	7212	89	8038	170	11088	327	500082	327
7164	93	7213	89	8058	168	36265	118		
7165	93	7214	89	8059	169	48549	163		
7166	93	7215	88	8060	170	48559	163		
7167	102	7216	43	8070	167	48569	163		

Lumens (lm)

Lumens is the standard by which the amount of brightness / light emitted by a light source is measured.

lm/w

This calculation denotes the amount of lumens emitted per watt of electricity used.

Watts (W)

The watt (abbreviated W) is the International System of Units' (SI) standard unit of power (energy per unit time), the equivalent of one joule per second. The watt is used to specify the rate at which electrical energy is dissipated, or the rate at which electromagnetic energy is radiated, absorbed, or dissipated.

EQ.Watts

This equation is used while shifting from an old lighting fixture and replacing the same with an LED fixture, hence the shift can be made based on the Wattage of lamp requirement.

Voltage / Frequency

Voltage denotes the electric power required for the effective working of the said product and frequency denotes the Horse Power of the said product.

CRI

The Color Rendering Index (CRI) is a scale from 0 to 100 percent indicating how accurate a "given" light source is at rendering color when compared to a "reference" light source. The higher the CRI, the better the color rendering ability.

PF

Power Factor is the ratio of the actual electrical power dissipated by an AC circuit to the product of the r.m.s. values of current and voltage. The difference between the two is caused by reactance in the circuit and represents power that does no useful work.

Beam Angle

A beam angle refers to the angle of light produced by a light source.

Recessed

A recessed light or down light is a light fixture that is installed into a hollow opening in a ceiling.

Surfaced

The finished housing is exposed, not flush with surface.

RD

Round

SQ

Square

WP

Waterproof

NON WP

NON-Waterproof

IP Rating

IP Ratings (Ingress Protection) A two-digit number established by the International Electro Technical Commission, is used to provide an Ingress Protection rating to a piece of electronic equipment or to an enclosure for electronic equipment.

Here are some of the easy to follow references to help you decide which IP Rating you need or have.

IP20: Not protected from liquids.

IP44: Protected from water spray from any direction.

IP45: Protected from low pressure water jets from any direction.

IP65: Protected from low pressure water jets from any direction and dust ingress.

IP66: Protected from high pressure water jets from any direction.

IP67: Protected from immersion between 15 centimeters and 1 meter in depth.

IP68: Protected from long term immersion up to a specified pressure.

5050/30

A number that signifies the size of the chip and number of chips on the LED strip where 5.0mm x 5.0mm being the size of the chip and 30 being the number of chips in one metre length of the strip.

5050/60

A number that signifies the size of the chip and number of chips on the LED strip where 5.0mm x 5.0mm is the size of the chip and 60 being the number of chips in one metre length of the strip.

5630/60

A number that signifies the size of the chip and number of chips on the LED strip where 5.6mm x 3.0mm is the size of the chip and 60 being the number of chips in one metre length of the strip.

5630/72

A number that signifies the size of the chip and number of chips on the LED strip where 5.6mm x 3.0mm is the size of the chip and 72 being the number of chips in one metre length of the strip.

3528/60

A number that signifies the size of the chip and number of chips on the LED strip where 3.5mm x 2.8mm is the size of the chip and 60 being the number of chips in one metre length of the strip.

3528/120

A number that signifies the size of the chip and number of chips on the LED strip where 3.5mm x 2.8mm is the size of the chip and 120 being the number of chips in one metre length of the strip.

3014/204

A number that signifies the size of the chip and number of chips on the LED strip where 3.0mm x 1.4mm is the size of the chip and 204 being the number of chips in one metre length of the strip.


PKW

Stands for Powder Coating White which is the housing exterior color for lighting fixtures.

RGB

(Red, Green, and Blue) When you use RGB Color Changing LED Lights, you no longer have to decide which color to use. You can either allow the lights to cycle through a continuous color changing pattern, or stop the controller at any color you like. The possibilities are endless. Change your color scheme with the seasons, or simply at your whim with RGB Color Changing LED lights.

Color Temperature Scale Application



The term used in general illumination is CORRELATED COLOUR TEMPERATURE (CCT). CCT relates to the colour of light produced by a light source, and uses the Kelvin temperature measurement scale (SI unit of absolute temperature). It describes the relative colour appearance of a white light source, indicating whether it appears more yellow/gold ("warm") or more blue ("cool"), in terms of the range of available shades of white.

Many people are now familiar with the idea of a "warm" white or a "cool" white being offered by fluorescent and other light bulbs. These bulbs have vastly different colour temperatures. The "warm" bulb often has a colour temperature of 3,000K and casts a more orange/red light on objects. Because you normally associate warmth with red or orange objects, this accounts for the "warm" descriptive name, even though it is a cooler (lower) temperature on the Kelvin scale. A "cool" white bulb commonly has a colour temperature of 4,100K and higher on the Kelvin scale. This is in the low range of blue colour, similar to ice, therefore earning the "cool" description.

Certificates



DIALux Partner



TUV



RoHS



The LIA Member



CE / LVD



Europe Office

1, Iliansko Shanssee Blvd,
Sofia 1220, Bulgaria
www.v-tac.eu

UK Office

Unit No. 9, Armstrong Way,
Western Industrial Park,
Southall, London,
UB24SD, UK.
www.v-tac.co.uk

Middle East Office

Unit# 407/8/9 Jumeirah
Bay Towers,
Plot# X3, JLT,
P.O. Box 45244, Dubai.
www.vtacexports.com

Showrooms

Vienna

Seilergasse 4,
1010 Wien, Vienna.
Austria.

Bucharest

Bulevardul Unirii, numărul 33
(vis-a-vis de Institutul
Bancar Român) Romania.

Budapest

Magyarország, 1138
Budapest, Népfürdő utca 13,
Hungary.

Paris

45Avenue Victor
Hugo a AUBERVILLIERS
(Seine Saint-Denis).
Paris-France.

Frankfurt

Mainzer Landstraße 275,
60326 Frankfurt, Germany

Birmingham

Unit 1, Ground Floor
Left Hand Side,
32-34 Constitution Hill,
Hockley, Birmingham,
B19 3JT. UK