
V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOWNLIGHT | Reflector Downlights

Introducing V-TAC's LED reflector downlights — available in 12° & 38° beam angles & CRI rating of >90, to achieve any residential, retail, or hospitality lighting need.

- 30,000-hour lifespan
- Input Voltage – AC:220–240V,50Hz
- Body Material – Aluminium
- Includes Quick Connector for easy wiring



12° NARROW BA | 38° WIDE BA

5 YEAR WARRANTY


FLICKER FREE

UGR<19

REAL COLOR SERIES CRI >90



Model	Beam Angle	SKU	Watts	Lumen	Box Qty
VT-2-04	12°	972 | 2700K WARM WHITE 971 | 4000K DAY WHITE 970 | 5700K WHITE	4w	320	100 pcs
VT-2-04-1	38°	987 | 2700K WARM WHITE 986 | 4000K DAY WHITE 985 | 5700K WHITE	4w	320	100 pcs




*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated


V-TAC® INNOVATIVE LED LIGHTING






Model	Beam Angle	SKU	Watts	Lumen	Box Qty
VT-2-12	12°	975 | 2700K WARM WHITE 974 | 4000K DAY WHITE 973 | 5700K WHITE	12w	960	50 pcs
VT-2-12-1	38°	990 | 2700K WARM WHITE 989 | 4000K DAY WHITE 988 | 5700K WHITE	12w	960	50 pcs






Model	Beam Angle	SKU	Watts	Lumen	Box Qty
VT-2-16	12°	978 | 2700K WARM WHITE 977 | 4000K DAY WHITE 976 | 5700K WHITE	16w	1280	50 pcs
VT-2-16-1	38°	993 | 2700K WARM WHITE 992 | 4000K DAY WHITE 991 | 5700K WHITE	16w	1280	50 pcs





Model	Beam Angle	SKU	Watts	Lumen	Box Qty
VT-2-21	12°	981 | 2700K WARM WHITE 980 | 4000K DAY WHITE 979 | 5700K WHITE	20w	1600	20 pcs
VT-2-21-1	38°	996 | 2700K WARM WHITE 995 | 4000K DAY WHITE 994 | 5700K WHITE	20w	1600	20 pcs





Model	Beam Angle	SKU	Watts	Lumen	Box Qty
VT-2-36	12°	984 | 2700K WARM WHITE 983 | 4000K DAY WHITE 982 | 5700K WHITE	36w	2880	20 pcs
VT-2-36-1	38°	999 | 2700K WARM WHITE 998 | 4000K DAY WHITE 997 | 5700K WHITE	36w	2880	20 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated







LED DOWNLIGHT | Reflector Downlight – Black Housing

Introducing V-TAC's LED reflector downlights with black housing— available in 10w, 20w & 30w & CRI rating of >80, to achieve any residential, retail, or hospitality lighting need.

- AC:85-265V,50/60Hz
- CRI >80
- 30,000-hour lifespan
- 120° Beam Angle
- 85% Energy Saving
- Aluminium Material
- 120° Beam Angle
- Aluminium Material
- 85% Energy Saving

5 YEAR WARRANTY



Model	Shape	SKU	Watts	Lumen	Dimension	Box Qty
VT-2-13	Round	20051 | 3000K WARM WHITE 20052 | 4000K DAY WHITE 20053 | 6400K WHITE	10w	800		40 pcs
VT-2-13-N	Round	2120051 | 3000K WARM WHITE 2120052 | 4000K DAY WHITE	10w	1200		40 pcs
VT-2-23	Round	20054 | 3000K WARM WHITE 20055 | 4000K DAY WHITE 20056 | 6400K WHITE	20w	1600		20 pcs
VT-2-23-N	Round	2120054 | 3000K WARM WHITE 2120055 | 4000K DAY WHITE 2120056 | 6400K WHITE	20w	2000		20 pcs
VT-2-33	Round	20057 | 3000K WARM WHITE 20058 | 4000K DAY WHITE 20059 | 6400K WHITE	30w	2400		10 pcs
VT-2-33-N	Round	2120058 | 4000K DAY WHITE	30w	3250		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOWNLIGHT | Adjustable Downlight



Our new reflector downlights feature adjustable beam angle direction. CRI rating of >90, to achieve any residential, retail, or hospitality lighting need.

- Adjustable Angle
- AC:220-240V,50/60Hz
- 24° Beam Angle
- IP20
- 30,000-hour lifespan
- IP20
- CRI>90
- 30,000-hour lifespan

5 YEAR WARRANTY

REAL COLOR SERIES CRI >90



Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
	VT-419	20049 | 4000K DAY WHITE	18w	1450		20 pcs
	VT-436	20050 | 4000K DAY WHITE	2×18w	2900		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOWNLIGHTS | Fire Rated Downlight

Our new Fire-Rated Spotlight Fittings are available in Chrome, Nickel, and White finish. With 3000K, 4000K and 6400K options, built with Aluminium alloy and iron. Efficient replacement for traditional downlight fittings.

- CRI >80
- 30,000-hour lifespan
- 70° Beam Angle
- Iron+Aluminium Alloy
- Integrated COB LED (Non-replaceable).
- Isolate driver with terminal for easy and speedy installation
- Designed to retain 30,60,90 minutes of fire integrity of ceiling and subsequent load bearing floors.

5 YEAR WARRANTY | QUICK CONNECTOR | IP65 RATING | DIMMABLE LIGHT CONTROL | 30-60-90 MIN Fire Rated



Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
 Chrome	VT-885-C	8175 | 3000K WARM WHITE 8176 | 4000K DAY WHITE 8180 | 6400K WHITE	5w	500	 Ø81.5mm Cutting Size Ø57mm	60 pcs
 Nickel	VT-885-N	8173 | 3000K WARM WHITE 8174 | 4000K DAY WHITE 8179 | 6400K WHITE	5w	500	 Ø81.5mm Cutting Size Ø57mm	60 pcs
 White	VT-885-W	8177 | 3000K WARM WHITE 8178 | 4000K DAY WHITE 8181 | 6400K WHITE	5w	500	 Ø81.5mm Cutting Size Ø57mm	60 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOWNLIGHTS | Fire Rated Downlight-3PC Pack

Our new 3PC Pack Fire-Rated Spotlight Fittings are available in Chrome, Nickel, and White finish. With 3000K, 4000K and 6400K options, built with Aluminium alloy and iron. Efficient replacement for traditional downlight fittings.

- CRI >80
- 30,000-hour lifespan
- 70° Beam Angle
- Iron+Aluminium Alloy
- Integrated COB LED (Non-replaceable).
- Isolate driver with terminal for easy and speedy installation
- Designed to retain 30,60,90 minutes of fire integrity of ceiling and subsequent load bearing floors.

5 YEAR WARRANTY | QUICK CONNECTOR | IP65 RATING | DIMMABLE LIGHT CONTROL | 30-60-90 MIN Fire Rated



Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
 Chrome	VT-885-C	8874 | 3000K WARM WHITE 8875 | 4000K DAY WHITE 8876 | 6400K WHITE	5w	500	 Ø81.5mm Cutting Size Ø57mm	20 pcs
 Nickel	VT-885-N	8197 | 3000K WARM WHITE 8198 | 4000K DAY WHITE 8199 | 6400K WHITE	5w	500	 Ø81.5mm Cutting Size Ø57mm	20 pcs
 White	VT-885-W	8182 | 3000K WARM WHITE 8183 | 4000K DAY WHITE 8184 | 6400K WHITE	5w	500	 Ø81.5mm Cutting Size Ø57mm	20 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED DOWNLIGHTS | Fire Rated Downlight-10PC Pack

Our new 10PC Pack Fire-Rated Spotlight Fittings are available in Chrome, Nickel, and White finish. With 3000K, 4000K and 6400K options, built with Aluminium alloy and iron. Efficient replacement for traditional downlight fittings.

- CRI >80
- 30,000-hour lifespan
- 70° Beam Angle
- Iron+Aluminium Alloy
- Integrated COB LED (Non-replaceable).
- Isolate driver with terminal for easy and speedy installation
- Designed to retain 30,60,90 minutes of fire integrity of ceiling and subsequent load bearing floors.

5 YEAR WARRANTY | QUICK CONNECTOR | IP65 RATING | DIMMABLE LIGHT CONTROL | 30-60-90 MIN Fire Rated



Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
 Chrome	VT-885-C	8913 | 3000K WARM WHITE 8914 | 4000K DAY WHITE 8915 | 6400K WHITE	5w	500	 Ø81.5mm Cutting Size Ø57mm	6 pcs
 Satin Nickle	VT-885-N	8890 | 3000K WARM WHITE 8891 | 4000K DAY WHITE 8912 | 6400K WHITE	5w	500	 Ø81.5mm Cutting Size Ø57mm	6 pcs
 White	VT-885-W	8887 | 3000K WARM WHITE 8888 | 4000K DAY WHITE 8889 | 6400K WHITE	5w	500	 Ø81.5mm Cutting Size Ø57mm	6 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOWNLIGHTS | Fire Rated Downlight

An innovative addition to our Fire-Rated Downlight series, this new model has an accessible switch for colour temperature tuning so users can easily achieve any lighting mood in any room.

- IP65 Rating.
- Integrated SMD LED (Non-replaceable).
- Dimmable
- AC:200-240V,50Hz
- Body Type: Aluminium
- 60° Beam Angle
- CRI >80
- LED provided by samsung
- 30,000-hour lifespan
- Cutting size:75mm

3 YEAR WARRANTY

QUICK CONNECTOR

DIMMABLE LIGHT CONTROL

EASY TOGGLE SWITCH

3000K 4000K 6400K

EASY ACCESS FOR COLOR CHANGING WITH BUTTON


Included Bezels



Chrome | Satin Nickle | White

30-60-90 MIN Fire Rated



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-18D	881 | 3IN1	8w	720	 Cutting Size Ø75mm	30 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED CABINET LIGHT
LED Cabinet Light

2 YEAR WARRANTY


MOTION PIR SENSOR

Enjoy the convenience of V-TAC's new LED cabinet lights with built-in PIR sensor. Ideal for wardrobes, bookshelves, drawers, and tool cabinets. Fully powered by batteries (3xAAA Battery not included), designed for a neat installation.





Model	SKU	Watts	Lumen	Box Qty
VT-80	813 | 4000K DAY WHITE	1.5w	80	50 pcs




LED CABINET LIGHT
LED Cabinet Light

5 YEAR WARRANTY


MOTION PIR SENSOR

Enjoy the convenience of V-TAC's new LED cabinet lights with built-in PIR sensor. Ideal for wardrobes, bookshelves, drawers, and tool cabinets. Fully powered by batteries(4xAA Battery not included), designed for a neat installation.





Model	SKU	Watts	Lumen	Box Qty
VT-81	814 | 4000K DAY WHITE	1.5w	135	50 pcs



*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



LED DOWNLIGHTS

Swap outdated CFL Lights with high-quality LED Down Lights for long-lasting and energy-efficient lighting. Choose from a wide range of 3w to 40w variations.

Key Features

- Innumerable styles & elegant appearance
- Non – Flickering
- Premium quality power driver with lowest power factor saver & high RA
- Easy Installation
- Varied finishes with strong die cast aluminium body
- Low maintenance

Application

Residences, showrooms, hotels & boutiques etc.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING



LED DOWNLIGHTS

LED COB Hotel Downlight

- AC:220-240V,50Hz
- PF: >0.6
- CRI: >95
- 0-27° Beam Angle
- On/0ff: >20000
- Life span:30,000-hour
- Body Type: Aluminium

POWERED BY CREE LED

UGR<19

REAL COLOR SERIES CRI >95

Model	SKU	Watts	Lumen	Size	Box Qty
VT-2907	1479 - 3000K WARM WHITE 1480 - 4000K DAY WHITE	6w	400	Ø65mm, 82mm, Cutting Size Ø55mm	24
VT-2911	1481 - 3000K WARM WHITE 1482 - 4000K DAY WHITE	10w	650	Ø85mm, 96mm, Cutting Size Ø75mm	16
VT-2916	1483 - 3000K WARM WHITE 1484 - 4000K DAY WHITE	15w	1000	Ø105mm, 113mm, Cutting Size Ø95mm	12
VT-2936	1477 - 3000K WARM WHITE 1478 - 4000K DAY WHITE	35w	2300	Ø160mm, 176mm, Cutting Size Ø150mm	8



Side Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- Life span:20,000-hour
- 30° Beam Angle
- LED Type :COB-CREE
- Body Type: Die Cast Aluminium
- Size: 80×80×25mm

Model	SKU	Watts	Lumen	Box Qty
VT-2903	1485 - 3000K WARM WHITE	3w	180	40
VT-2903-N	211485 - 3000K WARM WHITE	3w	150	40

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



Side Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- Life span:20,000-hour
- 30° Beam Angle
- LED Type :COB-CREE
- Body Type: Die Cast Aluminium
- Size: 90×60×30mm

Model	SKU	Watts	Lumen	Box Qty
VT-2913	1486 - 3000K WARM WHITE	3w	180	40



Side Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- Life span:20,000-hour
- 30° Beam Angle
- LED Type :COB-CREE
- Body Type: Die Cast Aluminium
- Size: 120×120×45mm

Model	SKU	Watts	Lumen	Box Qty
VT-2943	1487 - 3000K WARM WHITE	3w	180	20
VT-2943-N	211487 - 3000K WARM WHITE	3w	150	20



Dual Side Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- Life span:20,000-hour
- 120° Beam Angle
- LED Type :CREE Chip
- Body Type: Die Cast Aluminium
- Size: 300×50×35mm

Model	SKU	Watts	Lumen	Box Qty
VT-2953	1488 - 3000K WARM WHITE	3+6w	180+500	30



Dual Side Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- Life span:20,000-hour
- 120° Beam Angle
- LED Type :COB-CREE
- Body Type: Die Cast Aluminium
- Size: 140×30mm

Model	SKU	Watts	Lumen	Box Qty
VT-2963	1489 - 3000K WARM WHITE	3+6w	180+500	30

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING










LED DOWNLIGHTS

Reflector Series – High Lumen


- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- Life span:20,000-hour
- Body Type: PKW
- 120° Beam Angle

120 lm/W

Model	SKU	Watts	Lumen	Size	Box Qty
VT-2610	1100 – 6000K WHITE	10w Regular Lumen	730	 Cutting Size Ø105mm	27
VT-26101	1270 – 3000K WARM WHITE 1271 – 4000K DAY WHITE 1272 – 6400K WHITE	10w	1200	 Cutting Size Ø120mm	27
VT-26201	1273 – 3000K WARM WHITE 1274 – 4000K DAY WHITE 1275 – 6400K WHITE	20w	2400	 Cutting Size Ø167mm	18
VT-26301	1276 – 3000K WARM WHITE 1277 – 4000K DAY WHITE 1278 – 6400K WHITE	30w	3600	 Cutting Size Ø207mm	12
VT-26301-N	211276 – 3000K WARM WHITE 211277 – 4000K DAY WHITE 211278 – 6500K WHITE	30w	3100	 Cutting Size Ø207mm	12
VT-26451	1453 – 3000K WARM WHITE 1279 – 4000K DAY WHITE 1280 – 6400K WHITE	40w	4800	 Cutting Size Ø207mm	12
VT-26451-N	211279 – 4000K DAY WHITE 211280 – 6400K WHITE	40w	4200	 Cutting Size Ø207mm	12

V-TAC®
INNOVATIVE LED LIGHTING


ESSENTIALS



LED DOWNLIGHTS

Reflector Downlight

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 50° Beam Angle
- Body Type: PC




Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-8407	7610 - 3000K WARM WHITE 7611 - 4000K DAY WHITE 7612 - 6000K WHITE	7W White	560	Ø90×46mm	Ø75mm	50



LED DOWNLIGHTS

Fire Rated Downlight With White Bezel

- AC:220-240V,50Hz
- 38° Beam Angle
- Life span:30,000-hour
- Body Type: Aluminium



V-TAC SMART APP
CCT and Dimming
VIA SMART PHONE APP

30-60-90 MIN
Fire Rated

IP65
RATING

QUICK
CONNECTOR

5 YEAR
WARRANTY


Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-7710	1424 - 3 IN 1	10w	850	Ø83×57mm		40

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

essentials

V-TAC®
INNOVATIVE LED LIGHTING

LED DOWNLIGHTS Fire Rated Downlight



30-60-90 MIN
Fire Rated

DIMMABLE

FLICKER FREE

IP65 RATING

- AC:200-240V,50/60Hz
- Size: Ø90×45mm
- Cutting size: Ø65mm
- Unit Color: White
- LED Chip Type: SMD

Model	SKU	Watts	Lumen
VT-DL0508	7614 - 4IN1	5W/8W	5W 2700K-460lm 3000K-500lm 4000K-520lm 6400K-540lm 8W 2700K-720lm 3000K-720lm 4000K-800lm 6400K-840lm

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS www.tuv.com ID 1111227954 RoHS COMPLIANT CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Fire Rated Fitting-GU10



30-60-90 MIN Fire Rated

Model:	VT-703-WH
SKU:	8916
Material:	Steel
Color:	White
IP Rating:	IP20
Dimension:	Ø90×106mm
Cutting Size	Ø75mm
Box Qty:	60

Twist & Lock

Fire Rated Fitting-GU10



30-60-90 MIN Fire Rated

Model:	VT-703-N
SKU:	8917
Material:	Steel
Color:	Satin Nickle
IP Rating:	IP20
Dimension:	Ø90×106mm
Cutting Size	Ø75mm
Box Qty:	60

Twist & Lock

Fire Rated Fitting-GU10




30-60-90 MIN Fire Rated

Model:	VT-703-C
SKU:	8918
Material:	Steel
Color:	Chrome
IP Rating:	IP20
Dimension:	Ø90×106mm
Cutting Size	Ø75mm
Box Qty:	60

Twist & Lock

Fire Rated Fitting-GU10






30-60-90 MIN Fire Rated

Model:	VT-701-SN
SKU:	3680
Material:	Steel
Color:	Satin Nickel
IP Rating:	IP20
Dimension:	Ø80mmx115mm
Cutting Size	65mm
Box Qty:	50

Fire Rated Fitting-GU10






30-60-90 MIN Fire Rated

Model:	VT-701-W
SKU:	3681
Material:	Steel
Color:	White
IP Rating:	IP20
Dimension:	Ø80mmx115mm
Cutting Size	65mm
Box Qty:	50

Fire Rated Fitting-GU10






30-60-90 MIN Fire Rated

Model:	VT-701-CH
SKU:	3682
Material:	Steel
Color:	Chrome
IP Rating:	IP20
Dimension:	Ø80mmx115mm
Cutting Size	65mm
Box Qty:	50

Fire Rated Fitting-GU10






30-60-90 MIN Fire Rated

Model:	VT-702-SN
SKU:	3683
Material:	Steel
Color:	Satin Nickel
IP Rating:	IP65
Dimension:	Ø86mmx115mm
Cutting Size	65mm
Box Qty:	40

IP65 RATING

Fire Rated Fitting-GU10






30-60-90 MIN Fire Rated

Model:	VT-702-W
SKU:	3684
Material:	Steel
Color:	White
IP Rating:	IP65
Dimension:	Ø86mmx115mm
Cutting Size	65mm
Box Qty:	40

IP65 RATING

Fire Rated Fitting-GU10





30-60-90 MIN Fire Rated

Model:	VT-702-CH
SKU:	3685
Material:	Steel
Color:	Chrome
IP Rating:	IP65
Dimension:	Ø86mmx115mm
Cutting Size	65mm
Box Qty:	40

IP65 RATING

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS


V-TAC® INNOVATIVE LED LIGHTING

Can for Fire Rated Downlight

NEW



Model: VT-703-IP20
SKU: 11281
Material: Iron
Color: Black
IP Rating: IP20
Dimension: 90×120mm
Cutting Size 80mm
Box Qty: 60




IP20 RATING

Can for Fire Rated Downlight

NEW



Model: VT-703-IP65
SKU: 11286
Material: Iron
Color: Black
IP Rating: IP65
Dimension: 90×120mm
Cutting Size 80mm
Box Qty:



IP65 RATING

White Bezel-IP20 Push and Lock

NEW



IP20 RATING 5 pcs Pack

SKU: 11277
Dimension: 90mm
Unit Color: White
Body Type: Iron
IP Rating: IP20

Black Bezel-IP20 Push and Lock

NEW



IP20 RATING 5 pcs Pack

SKU: 11278
Dimension: 90mm
Unit Color: Black
Body Type: Iron
IP Rating: IP20

Satin Nickel Bezel-IP20 Push and Lock

NEW



IP20 RATING 5 pcs Pack

SKU: 11279
Dimension: 90mm
Unit Color: Satin Nickel
Body Type: Iron
IP Rating: IP20

Chrome Bezel-IP20 Push and Lock

NEW



IP20 RATING 5 pcs Pack

SKU: 11280
Dimension: 90mm
Unit Color: Chrome
Body Type: Iron
IP Rating: IP20

White Bezel-IP65 Push and Lock

NEW



IP65 RATING 5 pcs Pack

SKU: 11282
Dimension: 90mm
Unit Color: White
Body Type: Iron
IP Rating: IP65

Black Bezel-IP65 Push and Lock

NEW



IP65 RATING 5 pcs Pack

SKU: 11283
Dimension: 90mm
Unit Color: Black
Body Type: Iron
IP Rating: IP65

Satin Nickel Bezel-IP65 Push and Lock

NEW



IP65 RATING 5 pcs Pack

SKU: 11284
Dimension: 90mm
Unit Color: Satin Nickel
Body Type: Iron
IP Rating: IP65

Chrome Bezel-IP65 Push and Lock

NEW



IP65 RATING 5 pcs Pack

SKU: 11285
Dimension: 90mm
Unit Color: Chrome
Body Type: Iron
IP Rating: IP65