
V-TAC®
INNOVATIVE LED LIGHTING


SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Linear 3IN1 Lights


Discover V-TAC's reliable 40w suspended linear lights with a staggering lifespan of 30,000-hours. Designed with a toggle switch, 3IN1 color-changing light. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung.

- 30,000-hour Lifespan
- AC:200-240V,50/60Hz
- Toggle switch – 3IN1 CCT
- Aluminium Body
- 1.5 Meter Wire Length





5 YEAR WARRANTY




Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
		VT-7-44	20060 | 3IN1	40w	3200	12

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED LINEAR LIGHTS | Up & Down Linear Lights (Non-Linkable)



This modern range of suspended linear lights has up & down illumination for a more evenly distributed light that creates a subtle ambient yet sufficient lighting for any commercial lighting. Linear up & down lights are offered in two colors variants Silver and White.

- 30,000-hour Lifespan
- AC:100–240V,50Hz
- Aluminium Body
- 1–10V Dimmable
- 1.5 Meter Wire Length
- UP-110°-Down-50° Beam Angle

1–10V DIMMABLE

5 YEAR WARRANTY




Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Silver	VT-7-61-S	607 | 4000K DAY WHITE	UP 30w DOWN 30w	UP-3300 DOWN-3300	8
	White	VT-7-61-W	606 | 4000K DAY WHITE	UP 30w DOWN 30w	UP-3300 DOWN-3300	8

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Up & Down Linear Hanging Lights



This modern range of suspended linear lights has up & down illumination for a more evenly distributed light that creates a subtle ambient yet sufficient lighting for any commercial lighting. Linear up & down lights are offered in two colors variants Silver and White.

- 30,000-hour Lifespan
- AC:100–240V,50/60Hz
- Aluminium Body
- Linkable with connectors
- 1–10V Dimmable
- UP-110°-Down-50° Beam Angle

1–10V DIMMABLE

5 YEAR WARRANTY



Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Silver	VT-7-62-S	609 | 4000K DAY WHITE	UP 30w DOWN 30w	UP-3300 DOWN-3300	4
	White	VT-7-62-W	608 | 4000K DAY WHITE	UP 30w DOWN 30w	UP-3300 DOWN-3300	4

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED LINEAR LIGHTS | Linear Hanging Lights (Non-Dimmable)



Discover V-TAC's reliable 40w suspended linear lights with a staggering lifespan of 30,000-hours. Designed with excellent heat dissipation. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung. Linear lights are offered in three colors variants Black, Silver and White.

- 30,000-hour Lifespan
- AC:200–240V,50/60Hz
- 1.5 Meter Wire Length
- Aluminium Body
- 120° Beam Angle

LINKABLE
UP TO 12 METERS TOGETHER

5 YEAR WARRANTY




Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Black	VT-7-40-B	882 | 3000K WARM WHITE 374 | 4000K DAY WHITE 600 | 6000K WHITE	40w	3200	12
	Black	VT-7-40-B-N	21882 | 3000K WARM WHITE 21374 | 4000K DAY WHITE 21600 | 6400K WHITE	40W	3270	12
	Silver	VT-7-40-S	375 | 4000K DAY WHITE 601 | 6000K WHITE	40w	3200	12
	Silver	VT-7-40-S-N	21375 | 4000K DAY WHITE	40W	3300	12
	White	VT-7-40-W	376 | 4000K DAY WHITE 602 | 6000K WHITE	40w	3200	12
	White	VT-7-40-W-N	21376 | 4000K DAY WHITE 21602 | 6400K WHITE	40W	3360	12

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Slim Up & Down Linear Lights




This modern range of suspended linear lights has up & down illumination for a more evenly distributed light that creates a subtle ambient yet sufficient lighting for any commercial lighting. Linear up & down lights are offered in three colors variants Black, Silver and White.

- 30,000-hour Lifespan
- AC:200-240V,50/60Hz
- Aluminium Body
- 120° Beam Angle
- Linkable with connectors
- 0-10V Dimmable
- 1.5 Meter Wire Length

LINKABLE
UP TO 12 METERS TOGETHER

0-10V DIMMABLE

5 YEAR WARRANTY




Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Black	VT-7-60-B	379 | 4000K DAY WHITE	UP 20w DOWN 40w	UP-2000 DOWN-4000	9
	Silver	VT-7-60-S	378 | 4000K DAY WHITE	UP 20w DOWN 40w	UP-2000 DOWN-4000	9
	White	VT-7-60-W	377 | 4000K DAY WHITE	UP 20w DOWN 40w	UP-2000 DOWN-4000	9

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED LINEAR LIGHTS | Slim Linear Hanging Lights



Discover V-TAC's reliable 40w suspended linear lights with a staggering lifespan of 30,000-hours. Designed with excellent heat dissipation. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung. Linear lights are offered in three colors variants Silver and White.

- 30,000-hour Lifespan
- UGR<19
- Linkable with connectors
- 120° Beam Angle
- Aluminium Body
- 0-10V Dimmable
- 1.5 Meter Wire Length

LINKABLE
UP TO 12 METERS TOGETHER

0-10V DIMMABLE

5 YEAR WARRANTY



Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Silver	VT-7-43-S	384 | 4000K DAY WHITE	40w	3400	12
	Silver	VT-7-43-S-N	21384 | 4000K DAY WHITE	40W	3590	10
	White	VT-7-43-W	383 | 4000K DAY WHITE	40w	3400	12
	White	VT-7-43-W-N	21383 | 4000K DAY WHITE	40W	3510	10


*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Slim Recessed Linear Lights

Our new range of linear lights are also available for recessed installation, complete with necessary accessories for a seamless & continuous lighting system. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung. Linear lights are offered in two colors variants Silver and White.



- 30,000-hour Lifespan
- AC:200-240V,50/60Hz
- Linkable with connectors
- Aluminium Body
- 120° Beam Angle

LINKABLE
UP TO 12 METERS TOGETHER

5 YEAR WARRANTY



Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Silver	VT-7-41-S	380 | 4000K DAY WHITE 603 | 6000K WHITE	40w	3200	9
	Silver	VT-7-41-S-N	21380 | 4000K DAY WHITE	40W	3800	9
	White	VT-7-41-W	381 | 4000K DAY WHITE 604 | 6000K WHITE	40w	3200	9
	White	VT-7-41-W-N	21381 | 4000K DAY WHITE	40W	3620	9

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED LINEAR LIGHTS | Slim Linear Connector Lights

- Smart connectors designed for V-TACs range of recessed linear lights
- Robust Aluminium body
- Fitted with high efficiency Samsung LEDss that offer up to 80% in energy savings
- Allows flexible linking with linear lights

5 YEAR WARRANTY

Product	Model	SKU	Watts	Lumen	Box Qty
	VT-7-41-L	SILVER: 386 | 4000K DAY WHITE WHITE: 385 | 4000K DAY WHITE	8w	800	8
	VT-7-41-LN	SILVER: 388 | 4000K DAY WHITE WHITE: 387 | 4000K DAY WHITE	10w	1000	8
	VT-7-41-LW	SILVER: 390 | 4000K DAY WHITE WHITE: 389 | 4000K DAY WHITE	12w	1000	8
	VT-7-41-T	SILVER: 392 | 4000K DAY WHITE WHITE: 391 | 4000K DAY WHITE	14w	1200	4
	VT-7-41-X	SILVER: 394 | 4000K DAY WHITE WHITE: 393 | 4000K DAY WHITE	16w	1600	4


*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Recessed Linear Lights

Our new range of linear lights are also available for recessed installation, complete with necessary accessories for a seamless & continuous lighting system. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung.



- 30,000-hour Lifespan
- AC:200-240V,50/60Hz
- Linkable with connectors
- Aluminium Body
- 120° Beam Angle

LINKABLE
UP TO 12 METERS TOGETHER

5 YEAR WARRANTY



Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	White	VT-7-42-W	382 | 4000K DAY WHITE	40w	4000	9

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED LINEAR LIGHTS | Recessed Linear Connector Lights

- Smart connectors designed for V-TACs range of recessed linear lights
- Robust Aluminium body
- Fitted with high efficiency Samsung LEDss that offer up to 80% in energy savings
- Allows flexible linking with linear lights

5 YEAR WARRANTY

Product	Model	SKU	Watts	Lumen	Box Qty
	VT-7-42-L	WHITE: 395 | 4000K DAY WHITE	10w	1000	8
	VT-7-42-LN	WHITE: 396 | 4000K DAY WHITE	10w	1000	8
	VT-7-42-LW	WHITE: 397 | 4000K DAY WHITE	12w	1000	8
	VT-7-42-T	WHITE: 398 | 4000K DAY WHITE	14w	1200	4
	VT-7-42-X	WHITE: 399 | 4000K DAY WHITE	16w	1600	4


*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Linear Surfaced Lights

Discover V-TAC's reliable 40w linear lights with a staggering lifespan of 30,000-hours. Designed with excellent heat dissipation. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung. Linear lights are offered in three colors variants Silver and White.




- 30,000-hour Lifespan
- UGR<19
- Linkable with connectors
- 120° Beam Angle
- Aluminium Body
- 0-10V Dimmable
- 1.5 Meter Wire Length

LINKABLE
UP TO 12 METERS TOGETHER

0-10V DIMMABLE

5 YEAR WARRANTY



Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	color	VT-7-46	20462 | 3000K WARM WHITE 20463 | 4000K DAY WHITE 20464 | 6400K WHITE	40W	3400	12


*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

PRO SERIES

V-TAC®
INNOVATIVE LED LIGHTING

LED LINEAR TRUNKING LIGHT | Master Trunking

V-TAC's new Linear Trunking Light is a set of highly efficient, continuous linear light fixtures with a staggering 160 lm/w rating & a plug-and-play system. It provides an efficient, linkable modular system which means that each unit can be easily connected to the Linear Master Trunking through L, T, and X node connectors. 90°, 120°, and double asymmetric lenses are available for maximum adaptability in any space. Perfect suspended lighting for supermarkets, warehouses, service centers, and gymnasiums. No warm-up time, instant start-up. The sustained color temperature throughout long periods of usage.






5 YEAR WARRANTY

DIMMABLE LIGHT CONTROL

160 lm/W



Beam Angle	Light Distribution (IES)	Model	SKU	Watts	Lumen	Box Qty
WIDE 90°		VT-4551D	1360 | 4000K DAY WHITE	50w	8000	2
FLAT 120°		VT-4551D-120	1361 | 4000K DAY WHITE	50w	8000	2
DOUBLE ASYMMETRIC		VT-4551D-DL	1362 | 4000K DAY WHITE	50w	8000	2


*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

PRO SERIES

LED LINEAR TRUNKING LIGHT | Follow Trunking

V-TAC's new Linear Trunking Light is a set of highly efficient, continuous linear light fixtures with a staggering 160 lm/w rating & a plug-and-play system. It provides an efficient, linkable modular system which means that each unit can be easily connected to the Linear Master Trunking through L, T, and X node connectors. 90°, 120°, and double asymmetric lenses are available for maximum adaptability in any space. Perfect suspended lighting for supermarkets, warehouses, service centers, and gymnasiums. No warm-up time, instant start-up. The sustained color temperature throughout long periods of usage.






5 YEAR WARRANTY

DIMMABLE LIGHT CONTROL

160 lm/W



Beam Angle	Light Distribution (IES)	Model	SKU	Watts	Lumen	Box Qty
WIDE 90°		VT-4550D	1363 | 4000K DAY WHITE	50w	8000	2
FLAT 120°		VT-4550D-120	1364 | 4000K DAY WHITE	50w	8000	2
DOUBLE ASYMMETRIC		VT-4550D-DL	1365 | 4000K DAY WHITE	50w	8000	2

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

PRO SERIES

V-TAC® INNOVATIVE LED LIGHTING

Linear Track Module



SKU	Box Qty
1382	5

End Cap



SKU	Box Qty
1366	200

Suspended Cord



SKU	Box Qty
1367	100

8 Wire-Feed In Male Connector



SKU	Box Qty
1368	200

L Node Connector



SKU	Box Qty
1383	8

T Node Connector



SKU	Box Qty
1384	2

X Node Connector



SKU	Box Qty
1385	2

S Line-Follow Trunking Rail



SKU	Box Qty
1451	10

S Line-PC Blank Cover



SKU	Box Qty
1452	35

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated



LED DOME & DOWN LIGHTS

V-TAC's LED Bulkhead range is inclusive of IP65-rated 2D bulkheads made of state-of-the-art polycarbonate resins for a premium water and dustproof surface-mounted luminaire.
Each model has powerful combinations of two useful features: the emergency battery backup and the microwave sensor with 120'D detection angle. Together with the new elegant designs, this luminaire's highlight is its competitive outdoor effectiveness in efficiency and security.

Key Features


- Built-in power eliminates the need for an external power supply
- IP65 and strong PC covers for durability
- 3-hour Emergency Operation Time
- Microwave sensors: up to 10m detection
- upto 30,000hr lifespan
- Fully compatible with daylight sensors
- Equipped with a green LED charging indicator

Application

Suitable for open areas constantly exposed to dust and moisture like parking lots, corridors, airports, and malls.

5 YEAR WARRANTY

IP65 RATING



V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED DOME LIGHTS | CCT Bulkhead

Our resilient IP65 CCT Bulkhead make a good choice for outdoor residential, business, and industrial areas that need constant lighting since they can withstand weather and dust.

POLYCARBONATE PC

5 YEAR WARRANTY

IP65 RATING





IK08 RATING

- SMD LED Chip
- AC:200-240V,50/60Hz
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body
- CRI >80
- PF >0.5
- IP65 Rating

ON 1 2

EASY TOGGLE SWITCH FOR COLOR CHANGING
3000K - 4000K - 6400K



Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
	VT-14	20088 | 3IN1	14w	1400		10 pcs
	VT-14-CH	20092 | 3IN1	14w	1400		10 pcs
	VT-24	20093 | 3IN1	20w	1850		10 pcs
	VT-24-CH	20097 | 3IN1	20w	1850		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | CCT Bulkhead with Emergency Battery

These IP65 LED bulkheads are equipped with Ni-Cad batteries that automatically charges while in use. These fixtures can operate up to three (3) hrs on emergency situations.

- Battery Charging Current:60mA
- Battery Discharging Current:200mA
- Battery Type:Ni-CD, 9.6V 1.0Ah
- Emergency Operation Time:>3 Hours
- Emergency Standby Watts:>1.5W
- Charging Indication:Green LED
- Including Test Button, Battery Protection circuit & Inhibiting Mode
- AC:200-240V,50/60Hz
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body
- IP65 Rating

3 YEAR WARRANTY

IP65 RATING

Emergency Battery Backup



IK08 RATING

ON 1 2

EASY TOGGLE SWITCH FOR COLOR CHANGING 3000K - 4000K - 6400K

POLYCARBONATE PC



Model	SKU	Watts	Lumen	Dimension	Color	Box Qty
VT-14SE	20090 | 3IN1	14w	1400		White	10 pcs
VT-24SE	20095 | 3IN1	20w	1850		White	10 pcs

Changeable Eyelid Half Cover For 14W



SKU
11225

Changeable Chrome Rim For 14W



SKU
11230

Changeable Chrome Rim For 20W



SKU
11231

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOME LIGHTS | CCT Bulkhead with Sensor

This range of CCT Bulkhead are recommended for purposes of increasing security in garages, walkways, and parking areas. With competitive detection range and dimmable functions, these Dome Lights exhibit exceptional performance in outdoor security lighting.

- Detection Angle:Ceiling/Wall Mounted-360°/120°
- Detection Distance:3-6M, 6-10M Optional
- Detection Range:Max D10M*6M
- Hold Time:5s,90s,5min,10min customized
- Daylight Sensor:Day,2lux,10lux,50lux optional
- Dimmable Function:Yes,0%,10%,20%,30% optional
- Standby period:0s,10s,10min optional
- Manual Override:Available by dial switch
- Detection Motion Speed:0.5-3m/s
- AC:200-240V,50/60Hz
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body
- IP65 Rating

Microwave Sensor

IP65 RATING



5 YEAR WARRANTY

IK08 RATING

EASY TOGGLE SWITCH FOR COLOR CHANGING
3000K - 4000K - 6400K

POLYCARBONATE PC



Model	SKU	Watts	Lumen	Dimension	Color	Box Qty
VT-14SS	20089 | 3IN1	14w	1400		White	10 pcs
VT-24SS	20094 | 3IN1	20w	1850		White	10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | CCT Bulkhead with Emergency Battery+Sensor

Our 3-in-1 CCT Bulkhead range is equipped with the complete package for a remarkable and reliable indoor/ outdoor emergency and security lighting. With reliable Ni-Cd emergency battery back up, advanced microwave sensor, and optional dimmable functions, this range has impressive lighting abilities to make outdoor locations of residential, business, and industrial areas safer and easier to navigate.

- Emergency Operation Time:>3 Hours
- Emergency Standby Watts:>1.5W
- Battery Charging Current:60mA
- Battery Discharging Current:200mA
- Battery Type:Ni-CD, 9.6V 1.0Ah
- Charging Indication:Green LED
- Including,Test Button, Battery Protection circuit & Inhibiting Mode
- Detection Angle:Ceiling/Wall Mounted-360°/120°
- Detection Distance:3-6M, 6-10M Optional
- IP65 Rating
- Detection Range:Max D10M*6M
- Hold Time:5s,90s,5min,10min customized
- Daylight Sensor:Day,2lux,10lux,50lux optional
- Dimmable Function:Yes,0%,10%,20%,30% optional
- Stand-by period:0s,10s,10min optional
- Manual Override:Available by dial switch
- Detection Motion Speed:0.5-3m/s
- AC:200-240V,50/60Hz
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body

3in1 Bulkhead | Emergency Battery Backup | Microwave Sensor

IP65 RATING



3 YEAR WARRANTY

IK08 RATING

ON 1 2 EASY TOGGLE SWITCH FOR COLOR CHANGING 3000K - 4000K - 6400K

POLYCARBONATE PC



Model	SKU	Watts	Lumen	Dimension	Color	Box Qty
VT-14SES	20091 | 3IN1	14w	1400		White	10 pcs
VT-24SES	20096 | 3IN1	20w	1850		White	10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED DOME LIGHTS | 2D Bulkhead

Our resilient IP65 LED bulkheads make a good choice for outdoor residential, business, and industrial areas that need constant lighting since they can withstand weather, dust, and vandalism.

- SMD LED Chip
- AC:200-240V,50/60Hz
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body
- CRI >80
- PF >0.5
- IP65 Rating



POLYCARBONATE PC

IP65 RATING

5 YEAR WARRANTY

IK08 RATING



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-08	815 | 4000K DAY WHITE	8w	720		10 pcs
VT-15	801 | 4000K DAY WHITE 802 | 6400K WHITE	15w	1400		10 pcs

Chrome Bezel For 15W-17W



SKU
11241

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | 2D Bulkhead with Emergency Battery

These IP65 LED bulkheads are equipped with Ni-Cad batteries that automatically charges while in use. These fixtures can operate up to three (3) hrs on emergency situations.

3 YEAR WARRANTY



- AC:200-240V,50/60Hz
- >1.2 Watts Emergency Standby Watts
- 60mA Battery Charging Current
- 200mA Battery Discharging Current
- Ni-CD AA, 7.2V 1.0Ah Battery Type
- Including battery protection circuit & inhibiting mode
- Green LED Charging indicate
- >3 hrs Emergency Operation time
- 30,000-hour lifespan
- SMD LED Type
- PC Body
- IP65 Rating

IP65 RATING

IK08 RATING

POLYCARBONATE PC



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-11	816 | 4000K DAY WHITE	10w	720		10 pcs
VT-17	806 | 4000K DAY WHITE	17w	1400		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED DOME LIGHTS | 2D Bulkhead with Sensor

5 YEAR WARRANTY

IP65 RATING




IK08 RATING

POLYCARBONATE PC

This range of LED bulkheads are recommended for purposes of increasing security in garages, walkways, and parking areas. With competitive detection range and dimmable functions, these bulkheads exhibit exceptional performance in outdoor security lighting.

- AC:200-240V,50/60Hz
- 120° / 360° Detection Angle
- 3m, 5m, 8m, 10m (optional) Detection Distance
- Max D10Mx4M Detection Range
- 10S, 1min, 5min, 10min customized Hold Time
- Day, 10Lux, 30Lux, 50Lux optional Day light Sensor
- Yes, 0, 10%, 20%, 30% optional Dimmable Function
- 0.5~3m/s Detection Motion Speed
- >3 hrs Emergency Operation time
- 30,000-hour lifespan
- SMD LED Type
- PC Body
- IP65 Rating



Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
	VT-09	818 | 4000K DAY WHITE	8w	720		10 pcs
	VT-16	803 | 3000K WARM WHITE 804 | 4000K DAY WHITE 805 | 6400K WHITE	15w	1400		10 pcs
	VT-22	819 | 4000K DAY WHITE	15w	1450		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | 2D Bulkhead with Emergency Battery+Sensor

Our 3-in-1 LED bulkhead range is equipped with the complete package for a remarkable and reliable indoor/ outdoor emergency and security lighting. With reliable Ni-Cad emergency battery back up, advanced microwave sensor, and optional dimmable functions, this range has impressive lighting abilities to make outdoor locations of residential, business, and industrial areas safer and easier to navigate.

3 YEAR WARRANTY



IP65 RATING

IK08 RATING

POLYCARBONATE PC

- AC:200-240V,50/60Hz
- >1.2 Watts Emergency Standby Watts
- 60mA Battery Charging Current
- 200mA Battery Discharging Current
- Ni-CD AA, 7.2V 1.0Ah Battery Type
- Green LED Charging indicate
- Including battery protection circuit & inhibiting mode
- 120° / 360° Detection Angle
- Yes, 0, 10%, 20%, 30% optional Dimmable Function
- 3m, 5m, 8m, 10m (optional) Detection Distance
- 0.5~3m/s Detection Motion Speed
- >3 hrs Emergency Operation time
- 30,000-hour lifespan
- SMD LED Type
- PC Body
- IP65 Rating



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12	817 | 4000K DAY WHITE	10w	720		10 pcs
VT-19	812 | 4000K DAY WHITE	17w	1400		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOME LIGHTS | Slim Dome Light

A new addition to our Dome Light Lights series, V-TAC's new Slim IP65 LED Dome Lights are re-designed with a sleeker, more compact built for a modern look – perfect lighting for outdoor areas in residential, business, and industrial zones.





- AC:220-240V,50/60Hz
- 110° Beam Angle
- 30,000-hour lifespan
- IP65 Rating
- PC Body
- CRI >80
- PF >0.5

IP65 RATING

5 YEAR WARRANTY

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12S	935 | 3000K WARM WHITE 820 | 4000K DAY WHITE 936 | 6400K DAY WHITE	12w	1440		10 pcs
VT-12S-N	21820 | 4000K DAY WHITE	12w	1480		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | Slim Dome Light with Emergency Backup


- AC:220-240V,50/60Hz
- 110° Beam Angle
- SMD LED chip type
- PC Body
- 30,000-hour lifespan
- CRI >80
- Battery type -Ni-Cd 9.6V,1.0Ah
- Battery Charging Current – 60mA
- Battery Discharge Current – 200mA
- > 3 Hours emergency operation time
- IP65 Rating

3 YEAR WARRANTY

IP65 RATING

Emergency Battery Backup

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12SE	822 | 4000K DAY WHITE	14w	1440		10 pcs

LED DOME LIGHTS | Slim Dome Light with Sensor


- 360°Ceiling/120°Wall Mounted
- Detection Motion Speed – 0.5-3m/s
- Hold Time – 30s, 40s, 50s customized
- Daylight sensor -Day, 2lux, 10lux, 50lux optional
- Dimmable – Yes, 0, 10%,20% optional
- Manual Override by dial switch
- Stand by period – 0s, 10s, 10m optional
- AC:220-240V,50/60Hz
- 110° Beam Angle
- 30,000-hour lifespan
- CRI >80
- Microwave Sensor
- 3-6m detection distance
- 10mx6m detection range

5 YEAR WARRANTY

IP54 RATING

Microwave Sensor

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12SS	937 | 3000K WARM WHITE 821 | 4000K DAY WHITE 938 | 6400K DAY WHITE	12w	1440		10 pcs

LED DOME LIGHTS | Slim Dome Light with Emergency+Sensor


- 3-6m detection distance
- 10mx6m detection range
- 360°Ceiling/120°Wall Mounted
- 0.5-3m/s detection motion speed
- 30s, 40s, 50s customized (time delay)
- Daylight sensor -Day: 7-20LUX
- Dimmable – Yes, 0, 10%,20% optional
- Manual Override
- Standby – 0s, 10s, 10m optional
- > 3 Hours emergency operation time
- Battery type -Ni-Cd 9.6V,1.0Ah
- Battery Charging Current – 60mA
- Battery Discharge Current – 200mA
- AC:220-240V,50/60Hz
- 110° Beam Angle
- 30,000-hour lifespan

3 YEAR WARRANTY

IP54 RATING

3in1 Bulkhead / Emergency Battery Backup / Microwave Sensor

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12SES	823 | 4000K DAY WHITE	14w	1440		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED DOME LIGHTS | Bulkhead CCT Changeable

Our resilient IP65 LED bulkheads make a good choice for outdoor residential, business, and industrial areas that need constant lighting since they can withstand weather, dust. This new model has an easy switch for colour temperature tuning to achieve any lighting mood in any room. No need to worry about which colour temperature for any room when you can have it all – readily available with just a flick of a switch.

5 YEAR WARRANTY

IP65 RATING

- AC:200-240V,50/60Hz
- CRI >80
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body
- Built in Switch for CCT Changing

EASY TOGGLE SWITCH




3000K 4000K 6400K

EASY ACCESS FOR COLOR CHANGING WITH BUTTON

POLYCARBONATE PC



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-2-17	20016 | 3 IN 1	15w	1400		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | Dome Light – Sensor

- Input: AC:110–240V, 50/60Hz
- 120° Beam Angle
- 20,000-hour lifespan
- SMD LED Chip
- CRI >80
- 3 year warranty
- Detection Distance – 6m Max
- Detection Range – 360°
- Time Delay – Min-10sec±3sex, Max-3min±30sec
- Detection motion Speed – 0.6–1.5m/s
- Ambient Light – <3–2000lux(adjustable)
- Instant start
- IP20 Rating



MOTION PIR SENSOR

POLYCARBONATE PC

IK08 RATING

3 YEAR WARRANTY



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-13	807 | 3000K WARM WHITE 808 | 4000K DAY WHITE 809 | 6400K WHITE	12w	800		10 pcs
VT-13-N	21808 | 4000K DAY WHITE 21809 | 6400K WHITE	12w	800		10 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOME LIGHT | Ceiling Lights

- AC:220-240V,50/60Hz
- IP Rating:IP44
- CRI:>80
- Warranty:3 Years
- 110° Beam Angle
- Body Type: PC



IK08 RATING

3 YEAR WARRANTY

POLYCARBONATE PC

V-TAC® GENERATION

Model	Shape	SKU	Watts	Lumen	Dimension	Box Qty
VT-8033RD	Round	13889 | 3000K WARM WHITE 55669 | 4000K DAY WHITE 13899 | 6500K WHITE	15w	1500	47.5mm, Ø 200 mm	20 pcs
VT-8033RD-N	Round	2113889 | 3000K WARM WHITE 2155669 | 4000K DAY WHITE 2113899 | 6500K WHITE	15w	1850	47.5mm, Ø 200 mm	20 pcs
VT-8066RD	Round	13929 | 3000K WARM WHITE 13939 | 4000K DAY WHITE 13949 | 6500K WHITE	25w	2500	50 mm, Ø300 mm	10 pcs
VT-8066RD-N	Round	2113949 | 6500K WHITE	25w	2850	50 mm, Ø300 mm	10 pcs
VT-8033SQ	Square	13909 | 3000K WARM WHITE 55679 | 4000K DAY WHITE 13919 | 6500K WHITE	15w	1500	47.5 mm, 200 mm	20 pcs
VT-8033SQ-N	Square	2113909 | 3000K WARM WHITE	15w	1700	47.5 mm, 200 mm	20 pcs
VT-8066SQ	Square	13959 | 3000K WARM WHITE 13969 | 4000K DAY WHITE 13979 | 6500K WHITE	25w	2500	50 mm, 300 mm	10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING




LED DOWNLIGHT | Reflector Downlight

Our new reflector downlights feature a quick connector for easy wiring and installation. The beam angle direction can be also be easily adjusted by tilting the downlight itself.

- Adjustable Angle
- AC:85-265V,50/60Hz
- Body type Aluminium
- 120° Beam Angle
- LED (COB chip) provided by Samsung
- CRI >80

5 YEAR WARRANTY



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-2-10	839 | 3000K WARM WHITE 840 | 4000K DAY WHITE 841 | 6400K WHITE	10w	900		40 pcs
VT-2-20	842 | 3000K WARM WHITE 843 | 4000K DAY WHITE 844 | 6400K WHITE	20w	1600		20 pcs
VT-2-30	845 | 3000K WARM WHITE 846 | 4000K DAY WHITE 832 | 6400K WHITE	30w	2400		10 pcs






*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

LED BATTEN FITTINGS | Waterproof Fitting-G Series

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/Off: >10,000
- Life span:20,000-hour
- Body Type: PC
- Dimension :600×65×58mm

IP65 RATING




Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-6076	6283 – 4000K DAY WHITE 6282 – 6400K WHITE	18w	1440		12
VT-1249	6285 – 4000K DAY WHITE 6284 – 6400K WHITE	36w	2880		12
VT-1249-N	216285 – 4500K DAY WHITE 216284 – 6400K WHITE	36W	4320		12
VT-1574	6287 – 4000K DAY WHITE 6286 – 6400K WHITE	48w	3840		12
VT-1574-N	216287 – 4500K DAY WHITE 216286 – 6400K WHITE	48W	5760		12







DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

LED BATTEN FITTINGS | Waterproof Fitting-S Series

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15,000
- Life span:20,000-hour
- Body Type: PC
- Dimension :600×60×35mm

IP65 RATING








Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-1518	6472 - 4000K DAY WHITE 6473 - 6500K WHITE	18w	1530		20
VT-1518-N	216473 - 6500K WHITE	18w	1900		20
VT-1239	6469 - 4000K DAY WHITE 6470 - 6500K WHITE	36w	3000		20
VT-1239-N	216470 - 6500K WHITE	36w	3900		20
VT-1549	6467 - 4000K DAY WHITE 6468 - 6500K WHITE	48w	4000		20
VT-1549-N	216468 - 6500K WHITE	48w	5200		20

LED BATTEN FITTINGS | Waterproof Fitting F Series

- AC:200-240V,50Hz
- PF: >0.9
- CRI: >70
- 120° Beam Angle
- On/Off: >10,000
- Life span:20,000-hour
- Body Type: Plastic+ABS
- Dimension :600×76×66mm

IP65 RATING



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-6048	6198 - 4500K DAY WHITE 6199 - 6000K WHITE	18w	1440		12
VT-6048-N	216198 - 4000K DAY WHITE	18w	1900		12
VT-1248	6200 - 4500K DAY WHITE 6201 - 6000K WHITE	36w	2880		12
VT-1548	6184 - 4500K DAY WHITE 6185 - 6000K WHITE	48w	3840		12

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

HERMETIC | Waterproof Fitting




Airtight waterproof empty fittings (tubes excluded) is recognized by praiseworthy protection from dampness andrainfall, in this way you can effectively utilize it for indoor and outdoor lighting.Hermetic fittings is easy to install – you can install it yourself utilizing essential devices.

Model	SKU	Body Type	Size	Box Qty
VT-6028-N	6717	Plastic+ABS	666×68×58mm	16
VT-6029-N	6719	Plastic+ABS	666×96×58mm	12
VT-12028-N	6711	Plastic+ABS	1276×68×58mm	16
VT-12023-N	6709	Plastic+ABS	1576×68×58mm	16
VT-15028-N	6713	Plastic+ABS	1290×116×66mm	10
VT-15022-N	6715	Plastic+ABS	1590×116×66mm	10



Waterproof Suspension Kit

SKU	Box Qty
8119	50





LED DOME LIGHTS

Create a better ambience in any environment with V-TAC's LED Dome Lights. These compact and easy to install lights make a perfect replacement for traditional dome lights.

Key Features

- Non – flickering
- No UV radiation
- Easy installation
- Premium quality LED chip
- Premium quality power driver
- Instant start 0–100% in 0.01 seconds
- Extreme weather toleration (-20 to + 45 degrees centigrade)

Application

Mostly used in parking lots, passage's in big areas, exterior walls of prestigious buildings for ambience, airports, ports and malls

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING



IP44
RATING

SENSOR
COMPATIBLE

LED DOME LIGHTS
White Frame


- AC:220-240V,50Hz
- PF: >0.7
- CRI: >80
- 120° Beam Angle
- On/0ff:
- Life span:25,000 Hours
- Body Type: PC

Model	SKU	Watts	Lumen	Size	Shape
VT-8618W-RD	7615 - 3000K WARM WHITE 7616 - 4000K DAY WHITE 7617 - 6500K WHITE	18W	1530	Ø225mm	Round
VT-8624W-RD	7618 - 3000K WARM WHITE 7619 - 4000K DAY WHITE 7620 - 6500K WHITE	24W	2040	Ø295mm	Round
VT-8630W-RD	7621 - 3000K WARM WHITE 7622 - 4000K DAY WHITE 7623 - 6500K WHITE	30W	2550	Ø420mm	Round
VT-8618W-SQ	7624 - 3000K WARM WHITE 7625 - 4000K DAY WHITE 7626 - 6500K WHITE	18W	1530	225×225mm	Square
VT-8624W-SQ	7627 - 3000K WARM WHITE 7628 - 4000K DAY WHITE 7629 - 6500K WHITE	24W	2040	295×295mm	Square
VT-8630W-SQ	7630 - 3000K WARM WHITE 7631 - 4000K DAY WHITE 7632 - 6500K WHITE	30W	2550	420×420mm	Square

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



IP44
RATING

SENSOR
COMPATIBLE

LED DOME LIGHTS
Black Frame

- AC:220-240V,50Hz
- PF: >0.7
- CRI: >80
- 120° Beam Angle
- On/0ff:
- Life span:25,000 Hours
- Body Type: PC

Model	SKU	Watts	Lumen	Size	Shape
VT-8618B-SQ	7642 - 3000K WARM WHITE 7643 - 4000K DAY WHITE 7644 - 6500K WHITE	18W	1530	225×225mm	Square
VT-8624B-SQ	7645 - 3000K WARM WHITE 7646 - 4000K DAY WHITE 7647 - 6500K WHITE	24W	2040	295×295mm	Square
VT-8630B-SQ	7648 - 3000K WARM WHITE 7649 - 4000K DAY WHITE 7650 - 6500K WHITE	30W	2550	420×420mm	Square
VT-8618B-RD	7633 - 3000K WARM WHITE 7634 - 4000K DAY WHITE 7635 - 6500K WHITE	18W	1530	Ø225mm	Round
VT-8624B-RD	7636 - 3000K WARM WHITE 7637 - 4000K DAY WHITE 7638 - 6500K WHITE	24W	2040	Ø295mm	Round
VT-8630B-RD	7639 - 3000K WARM WHITE 7640 - 4000K DAY WHITE 7641 - 6500K WHITE	30W	2550	Ø420mm	Round

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING



IP44
RATING

LED DOME LIGHTS

White Frame with Sensor

Microwave Sensor


- AC:220-240V,50Hz
- PF: >0.7
- CRI: >80
- 120° Beam Angle
- On/0ff:
- Life span:25,000 Hours
- Body Type: PC

Model	SKU	Watts	Lumen	Size	Shape
VT-8618S-W-RD	7659 - 3000K WARM WHITE 7660 - 4000K DAY WHITE 7661 - 6500K WHITE	18W	1530	Ø225mm	Round
VT-8624S-W-RD	7662 - 3000K WARM WHITE 7663 - 4000K DAY WHITE 7664 - 6500K WHITE	24W	2040	Ø295mm	Round
VT-8630S-W-RD	7665 - 4000K DAY WHITE	30W	2550	Ø420mm	Round
VT-8618S-W-SQ	7666 - 4000K DAY WHITE	18W	1530	225×225mm	Square
VT-8624S-W-SQ	7667 - 4000K DAY WHITE	24W	2040	295×295mm	Square
VT-8630S-W-SQ	7668 - 4000K DAY WHITE	30W	2550	420×420mm	Square

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



IP44
RATING

LED DOME LIGHTS
Black Frame with Sensor

Microwave Sensor

- AC:220-240V,50Hz
- PF: >0.7
- CRI: >80
- 120° Beam Angle
- On/0ff:
- Life span:25,000 Hours
- Body Type: PC

Model	SKU	Watts	Lumen	Size	Shape
VT-8618S-B-RD	7669 - 4000K DAY WHITE	18W	1530	Ø225mm	Round
VT-8624S-B-RD	7670 - 4000K DAY WHITE	24W	2040	Ø295mm	Round
VT-8630S-B-RD	7671 - 4000K DAY WHITE	30W	2550	Ø420mm	Round
VT-8618S-B-SQ	7672 - 4000K DAY WHITE	18W	1530	225×225mm	Square
VT-8624S-B-SQ	7673 - 4000K DAY WHITE	24W	2040	295×295mm	Square
VT-8630S-B-SQ	7674 - 4000K DAY WHITE	30W	2550	420×420mm	Square

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING



3 IN 1 COLOR CHANGING



EASY TOGGLE SWITCH FOR COLOR CHANGING
3000K - 4000K - 6400K

LED DOME LIGHTS

Starry Cover

- AC:175-265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8412-S	7602 - 3IN1	12w	720	Ø255×55mm	5
VT-8412-S-N	217602 - 3IN1	12w	1200	260×55mm	5
VT-8418-S	7604 - 3IN1	18w	1080	Ø310×55mm	5
VT-8418-S-N	217604 - 3IN1	18w	1800	310×55mm	5
VT-8424-S	7606 - 3IN1	24w	1440	Ø350×55mm	5
VT-8424-S-N	217606 - 3IN1	24w	2600	Ø350×55mm	5
VT-8436-S	7608 - 3IN1	36w	2160	Ø480×65mm	5
VT-8436-S-N	217608 - 3IN1	36w	3900	500×80mm	5

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



3 IN 1 COLOR CHANGING



EASY TOGGLE SWITCH
FOR COLOR CHANGING
3000K - 4000K - 6400K

LED DOME LIGHTS
Milky Cover

- AC:175–265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- On/Off: >15000
- Life span:20,000-hour
- Body Type: Plastic

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8412-M	7603 – 3IN1	12w	720	Ø255×55mm	5
VT-8412-M-N	217603 – 3IN1	12w	1200	260×55mm	5
VT-8418-M	7605 – 3IN1	18w	1080	Ø310×55mm	5
VT-8418-M-N	217605 – 3IN1	18w	1800	Ø310×55mm	5
VT-8424-M	7607 – 3IN1	24w	1440	Ø350×55mm	5
VT-8424-M-N	217607 – 3IN1	24w	2600	Ø350×55mm	5
VT-8436-M	7609 – 3IN1	36w	2160	Ø480×65mm	5
VT-8436-M-N	217609 – 3IN1	36w	3900	500×80mm	5

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING



LED DOME LIGHTS

Starry Cover with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8472	14951 - 3IN1	3000K- 36W 4000K- 72W 6400K- 36W	3000K | 2520 4000K | 5040 6400K | 2520	Ø670×75mm	5
VT-8472-N	2114951- 3IN1	3000K- 36W 4000K- 72W 6400K- 36W	7200	670×80mm	5



LED DOME LIGHTS

Diamond Cover with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8404	14931 - 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	3000K | 1400 4000K | 2800 6400K | 1400	Ø388.5×75mm	5
VT-8404-N	2114931 - 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	4000	Ø388.5×75mm	5
VT-8557	14921 - 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	Ø500×75mm	5
VT-8557-N	2114921- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	6000	Ø500×75mm	5

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8405	14941 - 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	3000K | 1400 4000K | 2800 6400K | 1400	Ø393×75mm	5
VT-8405-N	2114941- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	4000	393×80mm	5
VT-8556	14911 - 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	Ø493.9×75mm	5
VT-8556-N	2114911 - 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	6000	Ø493.9×75mm	5



LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8402	14761- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	3000K | 1400 4000K | 2800 6400K | 1400	410×75mm	10
VT-8402-N	2114761- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	4000	410×75mm	10
VT-8502	14751- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	510×75mm	6
VT-8502-N	2114751- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	6000	510×80mm	6

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING



LED DOME LIGHTS


LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8403	14601- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	3000K | 1400 4000K | 2800 6400K | 1400	395×75mm	5
VT-8403-N	2114601- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	4000	395×80mm	5
VT-8503	14611- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	498×80mm	5
VT-8503-N	2114611- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	6000	500×90mm	5



LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8401	14741- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	3000K | 1400 4000K | 2800 6400K | 1400	465×75mm	10
VT-8401-N	2114741- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	4000	465×75mm	10
VT-8555	14551- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	Ø565×75mm	5
VT-8555-N	2114551- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	6000	Ø565×75mm	5

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: PMMA+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8473	76011 - 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	Ø480×75mm	6



LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8504	14621- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	500×85mm	6

DEKRA TÜV SÜD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING





LED DOME LIGHTS

LED Oval Dome Lights Black

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

IP54 RATING

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8014-OV-B	1267 - 3000K WARM WHITE 1266 - 4000K DAY WHITE 1268 - 6400K WHITE	8w	560		10
VT-8016-B	5056 - 4500K DAY WHITE	12w	840		10




LED DOME LIGHTS

LED Oval Dome Lights White

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

IP54 RATING

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8014-OV-W	1264 - 3000K WARM WHITE 1263 - 4000K DAY WHITE 1265 - 6400K WHITE	8w	560		10

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



LED DOME LIGHTS

LED Round Dome Lights White

IP54 RATING

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8014-RD-W	4999 - 3000K WARM WHITE 1259 - 4000K DAY WHITE 4997 - 6400K WHITE	8w	560	Ø180×82mm	10
VT-8015-W	4998 - 3000K WARM WHITE 5050 - 4000K DAY WHITE	12w	840	Ø220×105mm	10



LED DOME LIGHTS

LED Round Dome Lights Black

IP54 RATING

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8014-RD-B	1261 - 3000K WARM WHITE 1262 - 6400K WHITE	8w	560	Ø180×82mm	10
VT-8015-B	1349 - 3000K WARM WHITE 5052 - 4000K DAY WHITE	12w	840	Ø220×105mm	10



LED DOME LIGHTS

LED Oval Dome Lights

IP54 RATING

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8010-W	1351 - 3000K WARM WHITE	12w	840	242×165×96mm	10

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING



LED DOME LIGHTS

LED Oval Dome Lights

IP54 RATING

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8010-B	1350 - 3000K WARM WHITE 4973 - 4000K DAY WHITE 1269 - 6400K WHITE	12w	840	Ø242×96mm	10



LED DOME LIGHTS

LED Rectangle Dome Lights

IP54 RATING

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC


Model	SKU	Watts	Lumen	Size	Box Qty
VT-8038-B	1308 - 3000K WARM WHITE	8w Black	560	190×100×55mm	20
VT-8038-W	1311 - 3000K WARM WHITE	8w White	560	190×100×55mm	20



LED DOME LIGHTS

Dome Sensor

- AC:220-240V,50/60Hz
- Sensor Type: Microwave
- Rated Load: Max. 60W(E27)
- 360° Detection Range
- Time Delay: Min. 10sec±3sec,Max. 12min±1min
- Detection Distance:1-8m(radius) adjustable
- Body Type: PC



Model	SKU	Box Qty
VT-8002C	4966	5

