INTRODUCING

SOLAR PANELS



LED LIGHTING Q2-2022

CATALOG

The latest edition of our 2022 catalog contains all the information you need about the brand new item.

V-TAC®
INNOVATIVE LED LIGHTING

2009

V-TAC was founded with the vision of providing energy-efficient LED lighting solutions worldwide

2011

Began our EU expansion by opening the first V-TAC warehouse and office in Sofia, Bulgaria

2012

Manufacturing joint venture with MEKA Lighting

2013

Started building our distribution network in the UK from our office in Southall, London.

2015

Launched our in-house product testing lab in Sofia, Bulgaria.

2016

Achieved $100M Annual Turnover- Manufacturing Joint Venture with DASHER Lighting for decorative lighting



2017

In-brand Partnership with Samsung and launched the V-TAC PRO Series

2018

- Partnership with Tuya and launched new Smart Series
- Unveiled the new V-TAC Showroom in Slough, UK
- Launched new product groups

2019

Opened new 2500 square meter showroom in Bulgaria.

2020

- New website launch
- Opened new showroom in Ireland.

Since 2018, we at V-TAC have been successfully developing and launching the esteemed PRO Series – a product of our partnership with Samsung, a global pioneer in the LED industry. Boasting of LEDs provided by Samsung and a five-year warranty, this great feat resulted in the continuous growth of the PRO series catalogue to meet and exceed our customers' requirements and expectations throughout the years.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

Driven by our mission to continuously improve quality of life through lighting, we have further improved our products and launched the Evolution Series in 2019. The range included V-TAC's bestselling lamps and luminaries, upgraded with a staggering 160 lumen-per- watt rating, offering efficient options even for intensive lighting requirements.

evolution

V-TAC proudly introduces Solar Panels to its broad catalogue of innovations to improve energy efficiency in residential, commercial, and industrial establishments.

SOLAR ENERGY

We have developed a number of new series in the past few years.

V-TAC SMART HOME

Wi-Fi supported home solutions to convert any device into a smart device, and ultimately convert any home into a smart home. Have systematic, unified control on all your smart devices through the official V-TAC app, Amazon Alexa and Google Home.

V-TAC SMART LIGHT

Wi-Fi-supported home lighting system simultaneously controlled through the V-TAC app; works with Amazon Alexa & Google Home.

Download Our Retail Catalogue:
HTTPS://TINYURL.COM/VTAC-DIGITAL

SCAN ME

DIGITAL

Long-lasting, fast-charging data cables for everyday use. Includes a wide range of cable finishes and connectors for different usage types.

ELECTRICAL

Insect Killer, Robot Vacuum Cleaner & Convection Heaters, Sockets — all designed to bring convenience and safety to modern electrical needs.

AUDIO

New series of wireless speakers devices with various modes & wireless controls for a dynamic sound experience & maximum portability.

In 2020, we finished the upgrade and expansion of our Warehouse in Bulgaria with the Warehouse Management System (WMS) which allowed us to accommodate more stock, thereby enabling us to maintain fulfillment of orders despite logistic challenges due to Brexit and the global pandemic. Along with this development, both the PRO Series & Evolution Series have been growing and will continue to improve in the years ahead to offer the best lighting solutions in residential, commercial, and industrial projects.



V-TAC



V-TAC

11
EVERGREEN
EVERGREEN
EVERGREEN

V-TAC®
INNOVATIVE LED LIGHTING

SOLAR ENERGY

10

Solar Panels

14

LED Solar Lights

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

THE PRO-SERIES IS A SUBSTANTIAL RANGE OF PRODUCTS, CONSTRUCTED WITH ALL NEW SAMSUNG CHIPS. THIS SERIES IS THE IDEAL PRODUCT RANGE FOR PROFESSIONAL USE.

26
LED Floodlights

76
LED Street Lights

96
LED Highbay Lights

108
LED Panels

120
LED Tubes & Fittings

142
LED Linear Lights

158
LED Track Lights

172
LED Dome Lights

202
LED Emergency Lights



206
LED Strip Lights

208
LED Spotlights

216
LED Bulbs

V-TAC SMART LIGHT

V-TAC SMART HOME

WORKS WITH alexa

works with Ok Google

V-TAC MEETS THE GROWING IOT DEMAND FOR HOME LIGHTING WITH THE NEW SMART LIGHT SERIES — A COLLECTION OF WI-FI-SUPPORTED LED LIGHTING SOLUTIONS THAT CAN BE FULLY CONTROLLED VIA AMAZON ALEXA OR GOOGLE HOME.

241
Smart Bulbs

242
Smart Spotlights

243
Smart Dome Light

244
Smart Strip Lights

244
Smart Panel

245
IR Remote Control

245
Smart Thermostat

245
Smart Fan

246
Robot Vacuum Cleaner

248
Smart Plugs

248
Smart Socket

249
Gateway & Temperature Humidity Scheduler

V-TAC®
INNOVATIVE LED LIGHTING

essentials

V-TAC'S WIDE RANGE OF ESSENTIAL LED PRODUCTS, FOR DIVERSE APPLICATIONS. OUR PRODUCTS HAVE BEEN TESTED AND APPROVED BY TOP EU LABS ENSURING HIGH QUALITY LED'S.

250
LED Bulbs

298
LED Spotlights & Fittings

332
LED Floodlights

342
LED Panels

366
LED Tubes $ Fittings

378
LED High Bay Lights

382
LED Strip Lights

420
LED Track Lights

426
LED Downlights

434
LED Dome Lights

448
LED Wall Lights

476
LED Floor & Table Lamps`

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

V-TAC'S WIDE RANGE OF ESSENTIAL LED PRODUCTS, FOR DIVERSE APPLICATIONS. OUR PRODUCTS HAVE BEEN TESTED AND APPROVED BY TOP EU LABS ENSURING HIGH QUALITY LED'S.

490
LED Emergency Lights

494
Motion Sensors

504
LED Outdoor Lights

512
Garden Lamps

526
Decorative Pendants

550
Decorative Lights



584
LED Display Screen

V-TAC® SMART ELECTRICAL AUDIO

V-TAC INTRODUCES ITS ALL-NEW EXTENSIVE RANGE OF SMART PRODUCTS. SMART CAMERAS THAT ARE FULLY COMPATIBLE WITH ANY SMART DEVICE (MOBILE PHONES, TABLETS, OR PCS) THROUGH WI-FI INTEGRATION. SELF-POWERED WIRELESS SWITCHES THAT FUNCTION USING AN RF RECEIVER, MAKING THEIR USE A HASSLE FREE EXPERIENCE.

590
Smart Cameras

597
Smart Switches

600
Sockets and Adapters

623
Cable Tie

625
UVC Lamps

628
Electrical Solutions



632
Fans

642
Wireless Speakers

COMING SOON

651
SOLAR INVERTERS

V-TAC®

INNOVATIVE LED LIGHTING

SOLAR ENERGY

SOLAR PANELS

V-TAC proudly introduces Solar Panels to its broad catalogue of innovations to improve energy efficiency in residential, commercial, and industrial establishments. Converting sunlight directly into electricity, create a photovoltaic (PV) system with our new monocrystalline solar panels – proven more efficient as they are made of a single silicon crystal, hence the higher efficiency. The electrons that generate a flow of electricity have more room to move, and as a result, monocrystalline solar cells are more efficient than their polycrystalline solar cell counterparts. Our Solar Panels are also engineered for a positive power tolerance, ensuring that they will always produce more power equal to or greater than their rated power. PID Resistance make sure that our solar panels maintain their power efficiency despite high voltages, high temperatures, high humidity, and other potential factors. The excellent performance in the low- light environment is attributed to the solar panels' advanced glass and cell surface textured design.

• Monocrystalline solar panels
• Half-Cell Modules – reduces mechanical stress & resistive losses; optimises efficiency
• PID Resistance – maintains efficiency for a long period of time
• Low Light Performance – works and produces enough power even in low-light conditions; ideal despite cloudy or snowy weather conditions
• Weatherproof junction box included
• Resilience to Weather – Certified to withstand wind loads of up to 2400 Pa and snow loads of up to 5400 Pa. Frames topped with anodic oxidation layer resistant to corrosion
• ISO & IEC Certified

Residential

Commercial

Industrial

V-TAC®
INNOVATIVE LED LIGHTING

SOLAR ENERGY

450W 36V MONO HALF SOLAR PANEL

Model	SKU	Watts
VT-450	11353	450W

Positive tolerance
Positive tolerance of up to 5W delivers higher output reliability.

High Efficiency
Higher module conversion efficiency benefit from half cell structure (low resistance characteristic).

PID Resistance
Excellent Anti-PID performance guarantee limited power degradation for mass production.

Low-light Performance
Advanced glass and cell surface textured design ensure excellent performance in low-light environment.

Severe Weather Resilience
Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).

Durability Against Extreme Environmental Conditions
High salt mist and ammonia resistance certified by TUV NORD.

- Rated Maximum Power (Pmax):450W
- Tolerance (Tol):0-+3%
- Voltage at Pmax (Vmp):41.50V
- Current at Pmax (Imp):10.85A
- Open-Circuit Voltage (Voc):49.30V-3%
- Short-Circuit Current (Isc):11.60A+3%
- Nominal Operating Cell Temperature (NOCT):45+2 C
- Maximum System Voltage:1500VDC
- Maximum Series Fuse Rating:20A
- Operating Temperature:- 40Cto+85 C
- Output Cables:4mm² cable 55cm(Including MC4 connector)
- Application Class:Class A
- Cell Technology:Mono-si
- Aluminium Alloy & Tempered Glass
- Size:2094×1038×35mm

SOLAR ENERGY

V-TAC® INNOVATIVE LED LIGHTING

545W 36V MONO HALF SOLAR PANEL



Model	SKU	Watts
VT-545	11354	545W

Positive tolerance
Positive tolerance of up to SW delivers higher output reliability.

High Efficiency
Higher module conversion efficiency benefit from half cell structure (low resistance characteristic).

PID Resistance
Excellent Anti-PID performance guarantee limited power degradation for mass production.

Low-light Performance
Advanced glass and cell surface textured design ensure excellent performance in low-light environment.

Severe Weather Resilience
Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).

Durability Against Extreme Environmental Conditions
High salt mist and ammonia resistance certified by TUV NORD.

- Rated Maximum Power (Pmax):545W
- Tolerance (Tol):0-+3%
- Voltage at Pmax (Vmp):41.93V
- Current at Pmax (Imp):13A
- Open-Circuit Voltage (Voc):49.90±3%
- Short-Circuit Current (Isc):13.92±3%
- Nominal Operating Cell Temperature (NOCT):45+2 C
- Maximum System Voltage:1500VDC
- Maximum Series Fuse Rating:25A
- Operating Temperature:- 40Cto+85 C
- Output Cables:4mm² cable 55cm(Including MC4 connector)
- Application Class:Class A
- Cell Technology:Mono
- Aluminium Alloy & Tempered Glass
- Size:2279×1134×35mm

LED SOLAR LIGHTS

Transform the exteriors of a Building or a Garden into a Beautiful piece of Architecture. Simultaneously help navigate obstacles at night, prevent accidents and provide security.

Key Feature

- Perfect replacement for traditional fittings as they are more flexible & efficient
- Work perfectly in extreme temperatures from -20° to +45° without any adverse effects
- Specifically designed for Outdoor use
- IP65 Protection Rating to ensure safety
- Low Maintenance
- Outstanding Colour options and settings

Application

Used for gardens, outdoor residential areas, walkways & passages, driveways, fountains, lawns, entrance, patio or terrace and similar environments

V-TAC®
INNOVATIVE LED LIGHTING

SOLAR ENERGY

SOLAR ENERGY

V-TAC®
INNOVATIVE LED LIGHTING

LED SOLAR STREETLIGHT | Solar Streetlight

- DC:9V, 50W Solar Panel
- CRI: >80
- Lumens: 3000lm
- 6.4V 30000mAh Battery
- Beam Angle: 120°
- IP65 Rating
- Warranty: 5 Years
- Charging Time: 4-6 Hours
- Working Time: 8-10 Hours

SAMSUNG LED
Illuminated

5 YEAR WARRANTY

IP65 RATING

SOLAR LIGHTS

Model	SKU	Watts	Lumen	Box Qty
VT-ST303	20341 | 6400K WHITE	300w	3000	1 pc pcs

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

SOLAR ENERGY

LED SOLAR STREETLIGHT | Integrated Solar Panel Street Light

- Charging Time: 4–6 Hours
- Working Time: 8–10 hours in always mode, 12 hours in induction mode
- IP Rating: IP65
- Body Type: Polycrystalline Silicon Panel

IP65 RATING

Model	SKU	Watts	Solar Panel Watts	Lumen	Dimension	No.of LED	Battery	Box Qty
VT-20201ST	6755 – 4000K DAY WHITE 6756 – 6400K WHITE	200W	DC:6V,33W	Always Mode-1400 Sensor Mode-2300	680×320×50mm	200	LiFePO4–3.2V,30AH	3
VT-30301ST	6757 – 4000K DAY WHITE 6758 – 6400K WHITE	300W	DC:6V,40W	Always Mode-2000 Sensor Mode-3500	900×320×50mm	300	LiFePO4–3.2V,40AH	2
VT-40401ST	6759 – 4000K DAY WHITE 6760 – 6400K WHITE	400W	DC:6V,50W	Always Mode-2200 Sensor Mode-4300	1000×320×50mm	400	LiFePO4–3.2V,60AH	2

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

SOLAR ENERGY

V-TAC® INNOVATIVE LED LIGHTING

LED SOLAR LIGHTS | Solar Garden Light with Sensor

- LiFePO4 3.2V 15000 mAh Battery
- No. of LED: 252pcs
- Detecting Angle: 120°
- Sensing Range: <6M
- Charging Time: 6-8 Hours
- Working Time: 10-12 Hours
- IP Rating: IP65
- Body Type: ABS

IP65 RATING

MOTION SENSOR

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-45W	5150 – 4000K DAY WHITE 5151 – 6500K WHITE	7.5w	1000		5
VT-65W	5152 – 4000K DAY WHITE 5153 – 6500K WHITE	10w	1500		4

Pole for Solar Garden Light

11258

- Size: 3 meter (1000×3pcs)



LED SOLAR LIGHTS | Solar Garden Light with Sensor

- LiFePO4 32700, 6.4V 6000mAh Battery
- No. of LED: 120pcs
- Detecting Angle: 120°
- Sensing Range: <8Mtr
- Charging Time: 8 Hours
- Working Time: Constant Lighting Mode: 3 nights+ Sensor Mode: 5 nights+
- IP Rating: IP65
- Body Type: Aluminium+ABS

IP65 RATING

MOTION SENSOR



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-130W	5505 – 4000K DAY WHITE 5506 – 6400K WHITE	20w	2000		4

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC

www.tuv.com ID 1111227954

ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

SOLAR ENERGY

LED SOLAR LIGHTS | LED Solar Streetlight High Lumen

- 9.6V LiFe P04, 12000mAh Battery
- No. of LED: 90pcs
- Detecting Angle: 120°
- Sensing Range: 8-12m
- Charging Time: 8-10-hour
- Working Time: Min 36 hrs and Max 120 hrs
- IP Rating: IP65
- Body Type: ABS+PC and Aluminium

MOTION SENSOR

120 lm/W

IP65 RATING

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-ST42	5503 - 4000K DAY WHITE 5504 - 6000K WHITE	40W	4800	289.7×73.6×706.1mm	4

LED Solar Streetlight

IP65 RATING

MOTION SENSOR

- 7.4V Lithium,10800mAh Battery
- No. of LED: 40pcs
- Detecting Angle: 120°
- Sensing Range: 3-8M
- Charging Time: 6-7 Hours
- Working Time: 2-36 Hours
- Body Type: ABS+PC
- Size:413×232×58mm

Model	SKU	Watts	Lumen	Box Qty
VT-ST15	8549 - 4000K DAY WHITE 8548 - 6000K WHITE	10w	1600	10

LED Solar Streetlight

IP65 RATING

ULTRAVIOLET PROTECTION

- Li-ion 6.4V/27.5AH Battery
- Charging Time: 4-6 hrs Sunlight Charging
- Working Time: 12-15Hours
- Body Type: Aluminium
- Size:

Model	SKU	Watts	Lumen	Box Qty
VT-ST200	5502 - 4000K DAY WHITE	50W Solar Panel	4000	1

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

SOLAR ENERGY

V-TAC®
INNOVATIVE LED LIGHTING

Solar Tri-Proof Light with Sensor

IP65 RATING

- DC 3.7V/18,000 mAh Battery
- Charging Time: 4–6 Hours
- Working Time: 8–10 Hours
- Body Type: PC
- Size:1185×80×65mm

CCT CHANGING
With Remote Control
TIMER FUNCTION



Model	SKU	Watts	Lumen	Box Qty
VT-120018	6500 – 3IN1	18w	1000	10

Solar Bulb with Sensor

RECHARGEABLE

IP20 RATING

- 3.7V, 2200mAh Battery
- Charging Time: 8 Hours
- Working Time: 6 Hours
- Body Type: Plastic
- Size:72×158mm

Model	SKU	Watts	Lumen	Box Qty
VT-2417	2857 – 3IN1	7w	500	40

Solar Ceiling Light

IK08 RATING

IP65 RATING

COLOR CHANGING
WITH REMOTE

- DC 3.2V, 10000 mAh Battery
- Charging Time: 4–6 Hours
- Working Time: 8 Hours
- Body Type: PC
- Size:Ø320×100mm

Model	SKU	Watts	Lumen	Box Qty
VT-8415	7613 – 3IN1	15w	900	8

V-TAC®
INNOVATIVE LED LIGHTING

SOLAR ENERGY

LED SOLAR LIGHTS | LED Floodlight with Solar Panel

- Voltage/Frequency: DC:3.2V
- Charging Time: 4 Hours
- Working Time: 8 Hours
- IP Rating: IP65
- Body Type: Aluminium



IP65 RATING

ULTRAVIOLET PROTECTION

Model	SKU	Watts	Lumen	Battery	Dimension	Box Qty
VT-25W	8573 – 4000K DAY WHITE 94006 – 6000K WHITE	12W Solar Panel	550	5000mAh	205×50×170mm	8
VT-40W	8574 – 4000K DAY WHITE 94008 – 6000K WHITE	16W Solar Panel	1050	10000mAh	247×65×210mm	6
VT-60W	8575 – 4000K DAY WHITE 94010 – 6000K WHITE	20W Solar Panel	1650	10000mAh	270×70×238mm	5
VT-100W	8576 – 4000K DAY WHITE 94012 – 6000K WHITE	35W Solar Panel	2450	15000mAh	325×85×280mm	2
VT-200W	8577 – 4000K DAY WHITE 94026 – 6000K WHITE	40W Solar Panel	3100	20000mAh	353×90×304mm	2
VT-300W	8578 – 4000K DAY WHITE 94027 – 6000K WHITE	50W Solar Panel	4200	25000mAh	437×90×356mm	2

PIR Sensor Solar Floodlight

IP65 RATING

MOTION SENSOR

- 3.7V Lithium, 3000mAh Battery
- No. of LED: 30pcs
- Detecting Angle: 180°
- Sensing Range: 2-6M
- Charging Time: 6-7 Hours
- Working Time: 2-36 Hours
- Body Type: ABS+PC
- Size:217.4×149.3×33.7mm

Model	SKU	Watts	Lumen	Box Qty
VT-777-5	8547 – 4000K DAY WHITE	5w	500	18

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

SOLAR ENERGY

V-TAC® INNOVATIVE LED LIGHTING

PIR Sensor Solar Floodlight

IP65 RATING

MOTION SENSOR

- 3.7V Lithium, 3000mAh Battery
- No. of LED: 60pcs
- Detecting Angle: 180°
- Sensing Range: 2-6M
- Charging Time: 6-7 Hours
- Working Time: 2-36 Hours
- Body Type: ABS+PC
- Size:300×215×35mm

Model	SKU	Watts	Lumen	Box Qty
VT-787-10	8550 - 4000K DAY WHITE	10w	1100	8

Solar Floodlight

IP65 RATING

MOTION SENSOR

- Li-ion 18650, 3.7V, 7200mAh Battery
- No. of LED:
- Detecting Angle: 120°
- Sensing Range: ≤8Mtr
- Charging Time: 6-7 Hours
- Working Time: Max 24 Hours
- Body Type: Aluminium
- Size:232×166×33mm

Model	SKU	Watts	Lumen	Box Qty
VT-788-10	8674 - 4000K DAY WHITE	10w	1100	10

Solar Wall Light-IP65

IP65 RATING

MOTION SENSOR

- 3.7V Lithium 1200mAh Battery
- No. of LED: 14pcs (Front 12pcs, Back 2 pcs)
- Detecting Angle: 120°
- Sensing Range: 2-6M
- Charging Time: 6-7 hrs Sunlight Charging
- Working Time: Min 8 hrs and Max 24 hrs
- Body Type: ABS+PC
- Size:144.5×96×79mm

Model	SKU	Watts	Lumen	Box Qty
VT-767-2-W	8276 - 4000K DAY WHITE	1.5w	220	20

Solar Wall Light-IP65

IP65 RATING

MOTION SENSOR

- 3.7V Lithium 1200mAh Battery
- No. of LED: 14pcs (Front 12pcs, Back 2 pcs)
- Detecting Angle: 120°
- Sensing Range: 2-6M
- Charging Time: 6-7 hrs Sunlight Charging
- Working Time: Min 8 hrs and Max 24 hrs
- Body Type: ABS+PC
- Size:144.5×96×79mm

Model	SKU	Watts	Lumen	Box Qty
VT-767-2-B	8277 - 4000K DAY WHITE	1.5w	220	20

V-TAC®
INNOVATIVE LED LIGHTING

SOLAR ENERGY

Solar Wall Light-IP65

IP65 RATING

MOTION SENSOR

- 3.7V Lithium 2000mAh Battery
- No. of LED: 30pcs (Front 28pcs, Back 2 pcs)
- Detecting Angle: 120°
- Sensing Range: 2-6M
- Charging Time: 6-7 hrs Sunlight Charging
- Working Time: Min 5-8 hrs and Max 24 hrs
- Body Type: ABS+PC
- Size:140×212×109.2mm

Model	SKU	Watts	Lumen	Box Qty
VT-768	7523 - DAY+WARM WHITE	3w	400	12

Solar Wall Light-IP65

IP65 RATING

MOTION SENSOR

- 3.7V Lithium 4000mAh Battery
- No. of LED: 60pcs (Front 56pcs, Back 4 pcs)
- Detecting Angle: 120°
- Sensing Range: 2-6M
- Charging Time: 6-7 hrs Sunlight Charging
- Working Time: 5 hrs to 4 nights- 3 modes
- Body Type: ABS+PC
- Size:270×221×109.2mm

Model	SKU	Watts	Lumen	Box Qty
VT-767-7-W	8278 - 4000K DAY WHITE	7w	800	20

Solar Wall Light-IP65

IP65 RATING

MOTION SENSOR

- 3.7V Lithium 4000mAh Battery
- No. of LED: 60pcs (Front 56pcs, Back 4 pcs)
- Detecting Angle: 120°
- Sensing Range: 2-6M
- Charging Time: 6-7 hrs Sunlight Charging
- Working Time: 5 hrs to 4 nights- 3 modes
- Body Type: ABS+PC
- Size:270×221×109.2mm

Model	SKU	Watts	Lumen	Box Qty
VT-767-7-B	8279 - 4000K DAY WHITE	7w	800	20



DEKRA TÜV SÜD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

SOLAR ENERGY

V-TAC®
INNOVATIVE LED LIGHTING

Solar Wall Light-Remote Control

- 3.7V, 1200mAh 18650 Lithium Battery
- Charging Time: 4-6 hrs Sunlight Charging
- Working Time: Min 3 hrs and Max 12 hrs
- Body Type: PC
- Size:160×230mm
- Lumen: 60-75Lm

IP44 RATING

Model	SKU	Watts
VT-969	93575 - 3IN1	0.8w



Solar Wall Light-Remote Control

- 3.7V, 1200mAh 18650 Lithium Battery
- Charging Time: 4-6 hrs Sunlight Charging
- Working Time: Min 3 hrs and Max 12 hrs
- Body Type: PC
- Size:160×230mm
- Lumen: 60-75Lm

IP44 RATING

Model	SKU	Watts
VT-972	93578 - 3IN1	0.8w

Solar Wall Lamp

IP44 RATING

- 3.7V, 2200mAh Battery
- Charging Time: 5-6 Hours
- Working Time: 10-12 Hours
- Body Type: Aluminum Die-Casting
- Size:20×15.5×25.5mm
- Lumen: 110

Model	SKU	Watts
VT-982-S	2889 - 3IN1	2w

Solar Stand Lamp

IP44 RATING

- 3.7V, 2200mAh Battery
- Charging Time: 5-6 Hours
- Working Time: 10-12 Hours
- Body Type: Aluminum Die-Casting
- Size:15.5×15.5×27mm
- Lumen: 110

Model	SKU	Watts
VT-983-S	2890 - 3IN1	2w



V-TAC®
INNOVATIVE LED LIGHTING

SOLAR ENERGY

Solar Wall Lamp

IP44 RATING

- 3.7V, 2200mAh Battery
- Charging Time: 5-6 Hours
- Working Time: 10-12 Hours
- Body Type: Aluminum Die-Casting
- Size:22×17.5×25mm
- Lumen: 110

Model	SKU	Watts
VT-982	2892 - 3000K+6000K WARM WHITE+WHITE	2w

Solar Stand Lamp

IP44 RATING

- 3.7V, 2200mAh Battery
- Charging Time: 5-6 Hours
- Working Time: 10-12 Hours
- Body Type: Aluminum Die-Casting
- Size:17.5×17.5×27mm
- Lumen: 110

Model	SKU	Watts
VT-983	2893 - 3000K+6000K WARM WHITE+WHITE	2w



Solar Lawn Lamp

IP44 RATING

- 3.7V, 2200mAh Battery
- Charging Time: 5-6 Hours
- Working Time: 10-12 Hours
- Body Type: Aluminum Die-Casting
- Size:21×19×33mm
- Lumen: 110

Model	SKU	Watts
VT-984	2894 - 3000K+6000K WARM WHITE+WHITE	2w



Solar Lawn Lamp

IP44 RATING

- 3.7V, 2200mAh Battery
- Charging Time: 5-6 Hours
- Working Time: 10-12 Hours
- Body Type: Aluminum Die-Casting
- Size:21×19×33mm
- Lumen: 110

Model	SKU	Watts
VT-984-S	2891 - 3IN1	2w



DEKRA TÜV SÜD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

SOLAR ENERGY

V-TAC®
INNOVATIVE LED LIGHTING

Solar Bollard Lights

IP65 RATING

- 3.7V, 2000mAh Battery
- Charging Time: 12–15 Hours
- Working Time: 12 Hours
- Body Type: ABS+PC
- Size:705.7×155mm
- Lumen: 400

Model	SKU	Watts
VT-945	6666 – 3000K WARM WHITE 6665 – 4000K DAY WHITE	5w

2IN1 Garden Light

IP65 RATING

- 3.7V, 1000mAh Battery
- Charging Time: 4–5 Hours
- Working Time: 30–36 Hours
- Body Type: ABS+PC
- Size:148×800mm
- Lumen: 260

Model	SKU	Watts
VT-943	6668 – 3000K WARM WHITE 6667 – 4000K DAY WHITE	3w



Solar Garden Light – Adjustable

IP65 RATING

- 7.4V, 2000mAh Battery
- Charging Time: 4–5 Hours
- Working Time: 30–36 Hours
- Body Type: ABS+PC+Metal
- Size:264×1290.55mm
- Lumen: 500

Model	SKU	Watts
VT-948	6670 – 3000K WARM WHITE 6669 – 4000K DAY WHITE	8w



Solar Spike Light

IP65 RATING

- 3.7V Li-on 1200mAh Battery
- Charging Time: 6–8 Hours
- Working Time: 10–12 Hours
- Body Type: ABS
- Size:140×150×280mm
- Lumen: 40

Model	SKU	Watts
VT-952	6660 – 3000K WARM WHITE 6661 – 4000K DAY WHITE 6662 – 6400K WHITE	2w



V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated

LED FLOODLIGHTS

V-TAC's LED Floodlights are manufactured with industry-leading components to deliver exceptional performance, making them the perfect choice for efficient outdoor lighting. Each unit is designed and made of die-cast Aluminium for extreme durability. With the IP65 rating, all the floodlights in this series are also water and dust proof.

This extensive range of floodlights is ready to impress in terms of efficiency brought on by the Samsung LEDs. The PIR series comes with an auto-cutoff function(Manual Override)

Key Features

• 10w to 1000w
• IP65 rating — high-quality components to ensure waterproof/airtight performance
• Modern and strong Die-cast Aluminium body with a minimalistic design, for high-end support and design
• Product category includes high lumen, slimline, PIR series, rechargeable, work floodlight, and sports floodlights
• Select units include a 1-meter wire for convenience and easy installation

Application

Recommended for any outdoor lighting application in residential, commercial, and industrial areas

5 YEAR WARRANTY

IP65 RATING

120 Lumen/W

INNOVATIVE LED LIGHTING

LED FLOODLIGHTS | High Lumen Slimline Pro Series

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Body Type: Die Cast Aluminium
- 100° Beam Angle
- CRI >70
- PF>0.9
- 25,000-hour lifespan
- On/Off Cycle >15000

evolution
EFFICIENCY
185
LUMENS/W

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

NEW



Model	SKU	Watts	Useful lumens	Box Qty
VT-30185	20449 | 4000K DAY WHITE 20450 | 6400K WHITE	30w	4720	10 pcs

NEW



Model	SKU	Watts	Useful lumens	Box Qty
VT-50185	20451 | 4000K DAY WHITE 20452 | 6400K WHITE	50w	7870	10 pcs

NEW



Model	SKU	Watts	Useful lumens	Box Qty
VT-100185	20453 | 4000K DAY WHITE 20454 | 6400K WHITE	100w	15750	4 pcs

NEW



Model	SKU	Watts	Useful lumens	Box Qty
VT-150185	20455 | 4000K DAY WHITE 20456 | 6400K WHITE	150w	23600	2 pcs

NEW



Model	SKU	Watts	Useful lumens	Box Qty
VT-200185	20457 | 4000K DAY WHITE 20458 | 6400K WHITE	200w	31500	2 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

INNOVATIVE LED LIGHTING

LED FLOODLIGHTS | High Lumen Slimline Pro Series

evolution
EFFICIENCY
160
LUMENS/W

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Body Type: Die Cast Aluminium
- 100° Beam Angle
- CRI >70
- PF>0.9
- 25,000-hour lifespan
- On/Off Cycle >15000

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING



Model	SKU	Watts	Useful lumens	Box Qty
VT-32	20402 | 4000K DAY WHITE 20403 | 6500K WHITE	30w	4100	10 pcs



Model	SKU	Watts	Useful lumens	Box Qty
VT-52	20404 | 4000K DAY WHITE 20405 | 6500K WHITE	50w	6850	10 pcs



Model	SKU	Watts	Useful lumens	Box Qty
VT-132	20406 | 4000K DAY WHITE 20407 | 6500K WHITE	100w	13700	4 pcs



Model	SKU	Watts	Useful lumens	Box Qty
VT-162	20408 | 4000K DAY WHITE 20409 | 6500K WHITE	150w	20500	2 pcs



Model	SKU	Watts	Useful lumens	Box Qty
VT-302	20410 | 4000K DAY WHITE 20411 | 6500K WHITE	200w	27350	2 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHT | Light Sensor

- Sensor Floodlights are convenient and easy to install.
- The lights are powered directly from the power source.
- They will automatically function according to daylight levels.
- Floodlights will be off if natural light is above 140lux, and on if natural light is below 140lux.
- There is no need to turn the light on or off.
- Light Sensor does not work when motion is detected.



- Diecast Aluminium body
- 100° beam angle
- 25,000-hours lifespan
- >15000 On/Off Cycles
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-37	20169 | 3000K WARM WHITE 20170 | 4000K DAY WHITE 20171 | 6500K WHITE	30w	3000	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-57	20172 | 3000K WARM WHITE 20173 | 4000K DAY WHITE 20174 | 6500K WHITE	50w	5000	10 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-117	20175 | 3000K WARM WHITE 20176 | 4000K DAY WHITE 20177 | 6500K WHITE	100w	10000	4 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-167	20178 | 3000K WARM WHITE 20179 | 4000K DAY WHITE 20180 | 6500K WHITE	150w	15000	2 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-272	20181 | 3000K WARM WHITE 20182 | 4000K DAY WHITE 20183 | 6500K WHITE	200w	20000	2 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

evolution

LED FLOODLIGHTS | Evolution Series

Only from V-TAC – the super bright series – the first and only LED floodlights rated at 160 lumens per watt offer you superior efficiency and great energy savings.

- Aluminium body
- 100° beam angle
- 30,000-hour lifespan
- CRI: >70
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

SuperBRIGHT 160 LUMENS/W

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

evolution

V-TAC®
INNOVATIVE LED LIGHTING





Model	SKU	Watts	Lumen	Box Qty
VT-4961	5918 | 4000K DAY WHITE 5919 | 6400K WHITE	50w	8000lm	10 pcs

1 METER WIRE





Model	SKU	Watts	Lumen	Box Qty
VT-49161	5920 | 4000K DAY WHITE 5921 | 6400K WHITE	100w	16000lm	4 pcs

1 METER WIRE





Model	SKU	Watts	Lumen	Box Qty
VT-49261	5922 | 4000K DAY WHITE 5923 | 6400K WHITE	200w	32000lm	2 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHT | Direct Connection

- Instant Start in 1 second
- Operation in Outside Temperature (-20 to+40° C)
- Protection Rating IP65
- Only connect with waterproof cable hose

- Diecast Aluminium body
- 100° beam angle
- 25,000-hours lifespan
- >15000 On/Off Cycles
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-118	20304 | 3000K WARM WHITE 20305 | 4000K DAY WHITE 20306 | 6500K WHITE	10w	735	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-128	20307 | 3000K WARM WHITE 20308 | 4000K DAY WHITE 20309 | 6500K WHITE	20w	1510	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-138	20310 | 3000K WARM WHITE 20311 | 4000K DAY WHITE 20312 | 6500K WHITE	30w	2340	10 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-158	20313 | 3000K WARM WHITE 20314 | 4000K DAY WHITE 20315 | 6500K WHITE	50w	4000	10 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHT | Direct Connection with PIR Sensor (Black Body)

- Instant Start in 1second
- Operation in Outside Temperatures (-20 to +40° C)
- With manual override function.
- When the lock sensor function, avoid long time lighting in extreme weather.



- Diecast Aluminium body
- 100° beam angle
- 25,000-hours lifespan
- >15000 On/Off Cycles
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-118S-B	20256 | 3000K WARM WHITE 20257 | 4000K DAY WHITE 20258 | 6500K WHITE	10w	735	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-128S-B	20259 | 3000K WARM WHITE 20260 | 4000K DAY WHITE 20261 | 6500K WHITE	20w	1510	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-138S-B	20262 | 3000K WARM WHITE 20263 | 4000K DAY WHITE 20264 | 6500K WHITE	30w	2340	10 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-158S-B	20265 | 3000K WARM WHITE 20266 | 4000K DAY WHITE 20267 | 6500K WHITE	50w	4000	10 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHT | Direct Connection with PIR Sensor (White Body)

- Instant Start in 1second
- Operation in Outside Temperatures (-20 to +40° C)
- With manual override function.
- When the lock sensor function, avoid long time lighting in extreme weather.



- Diecast Aluminium body
- 100° beam angle
- 25,000-hours lifespan
- >15000 On/Off Cycles
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-118S-W	20268 | 3000K WARM WHITE 20269 | 4000K DAY WHITE 20270 | 6500K WHITE	10w	735	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-128S-W	20271 | 3000K WARM WHITE 20272 | 4000K DAY WHITE 20273 | 6500K WHITE	20w	1510	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-138S-W	20274 | 3000K WARM WHITE 20275 | 4000K DAY WHITE 20276 | 6500K WHITE	30w	2340	10 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-158S-W	20277 | 3000K WARM WHITE 20278 | 4000K DAY WHITE 20279 | 6500K WHITE	50w	4000	10 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHT | PIR Sensor (Black Body)



- Instant Start in 1second
- Operation in Outside Temperatures (-20 to +40° C)
- With manual override function.
- When the lock sensor function, avoid long time lighting in extreme weather.
- Easy Installation with Extra Long 1 Meter cable Included.

- Diecast Aluminium body
- 100° beam angle
- 25,000-hours lifespan
- >15000 On/Off Cycles
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-118S-1-B	20280 | 3000K WARM WHITE 20281 | 4000K DAY WHITE 20282 | 6500K WHITE	10w	735	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-128S-1-B	20283 | 3000K WARM WHITE 20284 | 4000K DAY WHITE 20285 | 6500K WHITE	20w	1510	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-138S-1-B	20286 | 3000K WARM WHITE 20287 | 4000K DAY WHITE 20288 | 6500K WHITE	30w	2340	10 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-158S-1-B	20289 | 3000K WARM WHITE 20290 | 4000K DAY WHITE 20291 | 6500K WHITE	50w	4000	10 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHT | PIR Sensor (White Body)



- Instant Start in 1second
- Operation in Outside Temperatures (-20 to +40° C)
- With manual override function.
- When the lock sensor function, avoid long time lighting in extreme weather.
- Easy Installation with Extra Long 1 Meter cable Included.

- Diecast Aluminium body
- 100° beam angle
- 25,000-hours lifespan
- >15000 On/Off Cycles
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-118S-1-W	20292 | 3000K WARM WHITE 20293 | 4000K DAY WHITE 20294 | 6500K WHITE	10w	735	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-128S-1-W	20295 | 3000K WARM WHITE 20296 | 4000K DAY WHITE 20297 | 6500K WHITE	20w	1510	20 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-138S-1-W	20298 | 3000K WARM WHITE 20299 | 4000K DAY WHITE 20300 | 6500K WHITE	30w	2340	10 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-158S-1-W	20301 | 3000K WARM WHITE 20302 | 4000K DAY WHITE 20303 | 6500K WHITE	50w	4000	10 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHTS | Slimline White Body high lumen

The V-TAC LED High Lumen Floodlight offers energy-efficient, high output illumination for a wide range of lighting applications. This series consumes around 80% less energy than traditional outdoor lighting thanks to pioneering optics research and the latest LED technology from Samsung.

- Die-cast aluminium body
- 100° beam angle
- 30,000-hour lifespan
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

120 lm/W
Brighter & energy-efficient
50% better than normal LED

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING





Model	SKU	Watts	Lumen	Box Qty
VT-56-W	762 | 4000K DAY WHITE 763 | 6400K WHITE	50w	6000	8 pcs
VT-56-W-N	21762 | 4000K DAY WHITE	50w	5750	8 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-106-W	768 | 4000K DAY WHITE	100w	12000	4 pcs
VT-106-W-N	21768 | 4000K DAY WHITE	100w	11500	4 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-156-W	774 | 4000K DAY WHITE 775 | 6400K WHITE	150w	18000	2 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-206-W	787 | 4000K DAY WHITE 788 | 6400K WHITE	200w	24000	2 pcs
VT-206-W-N	21787 | 4000K DAY WHITE	200w	23000	2 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-306-W	793 | 4000K DAY WHITE 794 | 6400K WHITE	300w	36000	2 pcs
VT-306-W-N	21793 | 4000K DAY WHITE	300w	34500	2 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED FLOODLIGHTS | Slimline Black Body high lumen

The V-TAC LED High Lumen Floodlight offers energy-efficient, high output illumination for a wide range of lighting applications. This series consumes around 80% less energy than traditional outdoor lighting thanks to pioneering optics research and the latest LED technology from Samsung.

- Die-cast aluminium body
- 100° beam angle
- 30,000-hour lifespan
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

120 lm/W
Brighter & energy-efficient
50% better than normal LED

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING





Model	SKU	Watts	Lumen	Box Qty
VT-56-B	760 | 4000K DAY WHITE 761 | 6400K WHITE	50w	6000	8 pcs
VT-56-B-N	21760 | 4000K DAY WHITE 21761 | 6500K WHITE	50w	5750	8 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-106-B	766 | 4000K DAY WHITE 767 | 6400K WHITE	100w	12000	4 pcs
VT-106-B-N	21766 | 4000K DAY WHITE 21767 | 6500K WHITE	100w	11500	4 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-156-B	772 | 4000K DAY WHITE 773 | 6400K WHITE	150w	18000	2 pcs
VT-156-B-N	21772 | 4000K DAY WHITE 21773 | 6500K WHITE	150w	17300	2 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-206-B	778 | 4000K DAY WHITE 779 | 6400K WHITE	200w	24000	2 pcs
VT-206-B-N	21778 | 4000K DAY WHITE 21779 | 6500K WHITE	200w	23000	2 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-306-B	791 | 4000K DAY WHITE 792 | 6400K WHITE	300w	36000	2 pcs
VT-306-B-N	21791 | 4000K DAY WHITE 21792 | 6500K WHITE	300w	34500	2 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-405	964 | 4000K DAY WHITE 965 | 6400K WHITE	400w	48000	1 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-505	966 | 4000K DAY WHITE 967 | 6400K WHITE	500w	60000	1 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-1055	968 | 4000K DAY WHITE 969 | 6400K WHITE	1000w	120000	1 pcs
VT-1055-N	21969 | 6500K WHITE	1000w	120000	1 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED FLOODLIGHTS | Slimline Grey Body high lumen

The V-TAC LED High Lumen Floodlight offers energy-efficient, high output illumination for a wide range of lighting applications. This series consumes around 80% less energy than traditional outdoor lighting thanks to pioneering optics research and the latest LED technology from Samsung.

- Die-cast aluminium body
- 100° beam angle
- 30,000-hour lifespan
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

120 lm/W
Brighter & energy-efficient
50% better than normal LED

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING





Model	SKU	Watts	Lumen	Box Qty
VT-56-G	764 | 4000K DAY WHITE 765 | 6400K WHITE	50w	6000	8 pcs
VT-56-G-N	21764 | 4000K DAY WHITE 21765 | 6500K WHITE	50w	5750	8 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-106-G	770 | 4000K DAY WHITE 771 | 6400K WHITE	100w	12000	4 pcs
VT-106-G-N	21770 | 4000K DAY WHITE 21771 | 6500K WHITE	100w	11500	4 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-156-G	777 | 6400K WHITE	150w	18000	2 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-206-G	789 | 4000K DAY WHITE 790 | 6400K WHITE	200w	24000	2 pcs
VT-206-G-N	21789 | 4000K DAY WHITE 21790 | 6500K WHITE	200w	23000	2 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-306-G	795 | 4000K DAY WHITE 796 | 6400K WHITE	300w	36000	2 pcs
VT-306-G-N	21796 | 6500K WHITE	300w	34500	2 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHTS | Slimline White Body

V-TAC's PRO Series LED floodlights are equipped with Samsung LEDs for a well-diffused, high-performance outdoor lighting encased in a die-cast IP65 body for durability. Available in 10W to 300W in a clean, ivory white finish. Select models come with a one (1) meter wire.

- Die-cast body
- 100° beam angle
- 30,000-hour lifespan
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING





Model	SKU	Watts	Lumen	Box Qty
VT-10-W	427 | 3000K WARM WHITE 428 | 4000K DAY WHITE 429 | 6400K WHITE	10w	800	20 pcs
VT-10-W-N	21427 | 3000K WARM WHITE	10w	735	20 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-20-W	442 | 3000K WARM WHITE 443 | 4000K DAY WHITE 444 | 6400K WHITE	20w	1600	20 pcs
VT-20-W-N	21442 | 3000K WARM WHITE	20w	1510	20 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-30-W	403 | 3000K WARM WHITE 404 | 4000K DAY WHITE 405 | 6400K WHITE	30w	2400	10 pcs
VT-30-W-N	21403 | 3000K WARM WHITE 21404 | 4000K DAY WHITE	30w	2340	10 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-30-1-W	950 | 6400K WHITE	30w	2400	10 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated





Model	SKU	Watts	Lumen	Box Qty
VT-50-W	409 | 3000K WARM WHITE 410 | 4000K DAY WHITE 411 | 6400K WHITE	50w	4000	8 pcs
VT-50-W-N	21409 | 3000K WARM WHITE 21410 | 4000K DAY WHITE 21411 | 6500K WHITE	50w	4000	8 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-50-1-W	952 | 6400K WHITE	50w	4000	8 pcs





1 METER WIRE

Model	SKU	Watts	Lumen	Box Qty
VT-100-W	415 | 3000K WARM WHITE 416 | 4000K DAY WHITE 417 | 6400K WHITE	100w	8000	4 pcs
VT-100-W-N	21415 | 3000K WARM WHITE 21416 | 4000K DAY WHITE 21417 | 6500K WHITE	100w	8200	4 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING





Model	SKU	Watts	Lumen	Box Qty
VT-150-W	478 | 3000K WARM WHITE 479 | 4000K DAY WHITE 480 | 6400K WHITE	150w	12000	2 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-200-W	420 | 4000K DAY WHITE 421 | 6400K WHITE	200w	16000	2 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-300-W	486 | 4000K DAY WHITE 487 | 6400K WHITE	300w	24000	2 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHTS | Slimline Black Body

V-TAC's PRO Series LED floodlights are equipped with Samsung LEDs for a well-diffused, high-performance outdoor lighting encased in a die-cast IP65 body for durability. Available in 10W to 300W in a classic, jet black finish. Select models come with a one (1) meter wire.

- Die-cast body
- 100° beam angle
- 30,000-hour lifespan
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating



IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.





Model	SKU	Watts	Lumen	Box Qty
VT-10-B	424 | 3000K WARM WHITE 425 | 4000K DAY WHITE 426 | 6400K WHITE	10w	800	20 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-20-B	439 | 3000K WARM WHITE 440 | 4000K DAY WHITE 441 | 6400K WHITE	20w	1600	20 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-30-B	400 | 3000K WARM WHITE 401 | 4000K DAY WHITE 402 | 6400K WHITE	30w	2400	10 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-50-B	406 | 3000K WARM WHITE 407 | 4000K DAY WHITE 408 | 6400K WHITE	50w	4000	8 pcs
VT-50-B-N	21406 | 3000K WARM WHITE 21407 | 4000K DAY WHITE 21408 | 6500K WHITE	50w	4000	8 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated





Model	SKU	Watts	Lumen	Box Qty
VT-10-1-B	947 | 6400K WHITE	10w	800	20 pcs
VT-10-1-B-N	21947 | 6500K WHITE	10w	735	20 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-20-1-B	20012 | 4000K DAY WHITE 948 | 6400K WHITE	20w	1600	20 pcs
VT-20-1-B-N	21948 | 6500K WHITE	20w	1510	20 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-30-1-B	20013 | 4000K DAY WHITE 949 | 6400K WHITE	30w	2400	10 pcs
VT-30-1-B-N	21949 | 6400K WHITE	30w	2340	10 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-50-1-B	20014 | 4000K DAY WHITE 951 | 6400K WHITE	50w	4000	8 pcs
VT-50-1-B-N	2120014 | 4000K DAY WHITE 21951 | 6500K WHITE	50w	4000	8 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING





Model	SKU	Watts	Lumen	Box Qty
VT-100-B	412 | 3000K WARM WHITE 413 | 4000K DAY WHITE 414 | 6400K WHITE	100w	8000	4 pcs
VT-100-B-N	21412 | 3000K WARM WHITE 21413 | 4000K DAY WHITE 21414 | 6400K WHITE	100w	8200	4 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-150-B	475 | 3000K WARM WHITE 476 | 4000K DAY WHITE 477 | 6400K WHITE	150w	12000	2 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-200-B	418 | 4000K DAY WHITE 419 | 6400K WHITE	200w	16000	2 pcs
VT-200-B-N	21419 | 6500K WHITE	200w	16500	2 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-300-B	422 | 4000K DAY WHITE 423 | 6400K WHITE	300w	24000	2 pcs
VT-300-B-N	21422 | 4000K DAY WHITE	300w	24800	2 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHTS | Slimline Grey Body

V-TAC's PRO Series LED floodlights are equipped with Samsung LEDs for a well-diffused, high-performance outdoor lighting encased in a die-cast IP65 body for durability. Available in 10w to 300 watts, in a modern, neutral grey finish. Select models come with a one (1) meter wire.

- Die-cast body
- 100° beam angle
- 30,000-hour lifespan
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating



IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.





Model	SKU	Watts	Lumen	Box Qty
VT-10-G	430 | 3000K WARM WHITE 431 | 4000K DAY WHITE 432 | 6400K WHITE	10w	800	20 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-20-G	445 | 3000K WARM WHITE 446 | 4000K DAY WHITE 447 | 6400K WHITE	20w	1600	20 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-30-G	454 | 3000K WARM WHITE 455 | 4000K DAY WHITE 456 | 6400K WHITE	30w	2400	10 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-50-G	463 | 3000K WARM WHITE 464 | 4000K DAY WHITE 465 | 6400K WHITE	50w	4000	8 pcs
VT-50-G-N	21464 | 4000K DAY WHITE	50w	4000	8 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated





Model	SKU	Watts	Lumen	Box Qty
VT-100-G	472 | 3000K WARM WHITE 473 | 4000K DAY WHITE 474 | 6400K WHITE	100w	8000	4 pcs
VT-100-G-N	21473 | 4000K DAY WHITE	100w	8200	4 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-150-G	481 | 3000K WARM WHITE 482 | 4000K DAY WHITE 483 | 6400K WHITE	150w	12000	2 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-200-G	484 | 4000K DAY WHITE 485 | 6400K WHITE	200w	16000	2 pcs





Model	SKU	Watts	Lumen	Box Qty
VT-300-G	488 | 4000K DAY WHITE 489 | 6400K WHITE	300w	24000	2 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED FLOODLIGHTS | PIR Sensor White Body

Incorporating security features, V-TAC offers a new range of LED floodlights equipped with PIR sensors and Samsung LEDs for an even better, high-end performance. Can be used as a regular floodlight through the Auto Cut-off function(manual override). Widely used for security lighting in residential, commercial, and industrial areas.

- 30,000-hour lifespan
- 100° Beam Angle
- AC:220-240V,50Hz
- CRI: >80
- PF>0.7 for 10,20w; 0.9 for 30,50w
- On/Off cycle: >15000
- Instant start in <1sec
- Die-cast Aluminium Body
- Detection range:120°
- Detection distance:2-8m
- Time delay: MIN12+-3sec MAX6+-2min
- Installation height: 1.8-2.5m

MOTION PIR SENSOR

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

1 METER WIRE





Model	SKU	Watts	Lumen	Box Qty
VT-10-S-W	433 | 3000K WARM WHITE 434 | 4000K DAY WHITE 435 | 6400K WHITE	10w	800	20 pcs

1 METER WIRE





Model	SKU	Watts	Lumen	Box Qty
VT-20-S-W	448 | 3000K WARM WHITE 449 | 4000K DAY WHITE 450 | 6400K WHITE	20w	1600	20 pcs

1 METER WIRE





Model	SKU	Watts	Lumen	Box Qty
VT-30-S-W	457 | 3000K WARM WHITE 458 | 4000K DAY WHITE 459 | 6400K WHITE	30w	2400	20 pcs

1 METER WIRE





Model	SKU	Watts	Lumen	Box Qty
VT-50-S-W	466 | 3000K WARM WHITE 467 | 4000K DAY WHITE 468 | 6400K WHITE	50w	4000	10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED FLOODLIGHTS | PIR Sensor Black Body

Incorporating security features, V-TAC offers a new range of LED floodlights equipped with PIR sensors and Samsung LEDs for an even better, high-end performance. Can be used as a regular floodlight through the Auto Cut-off function(manual override). Widely used for security lighting in residential, commercial, and industrial areas.

- 30,000-hour lifespan
- 100° Beam Angle
- AC:220-240V,50Hz
- CRI: >80
- PF>0.7 for 10,20w; 0.9 for 30,50w
- On/Off cycle: >15000
- Instant start in <1sec
- Die-cast Aluminium Body
- Detection range:120°
- Detection distance:2-8m
- Time delay: MIN12+-3sec MAX6+-2min
- Installation height: 1.8-2.5m

MOTION PIR SENSOR

IP65 RATING

5 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

1 METER WIRE





Model	SKU	Watts	Lumen	Box Qty
VT-10-S-B	436 | 3000K WARM WHITE 437 | 4000K DAY WHITE 438 | 6400K WHITE	10w	800	20 pcs

1 METER WIRE





Model	SKU	Watts	Lumen	Box Qty
VT-20-S-B	451 | 3000K WARM WHITE 452 | 4000K DAY WHITE 453 | 6400K WHITE	20w	1600	20 pcs

1 METER WIRE





Model	SKU	Watts	Lumen	Box Qty
VT-30-S-B	460 | 3000K WARM WHITE 461 | 4000K DAY WHITE 462 | 6400K WHITE	30w	2400	20 pcs

1 METER WIRE





Model	SKU	Watts	Lumen	Box Qty
VT-50-S-B	469 | 3000K WARM WHITE 470 | 4000K DAY WHITE 471 | 6400K WHITE	50w	4000	10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED FLOODLIGHTS | Rechargeable Floodlight

A strong, reliable, and portable lamp — V-TAC's new compact and rechargeable LED floodlights can easily be recharged through the micro socket & USB port making it perfect for home projects, garages, warehouses, car repair shops, parking lots, camping and more.

- IP Rating – IP44
- AC:100-240V
- On/Off cycle: >15000
- CRI>80
- Rechargeable
- 30,000-hour lifespan
- PF>0.9
- Beamangle: 100



SOS FLASH

USB PORT

MICRO SOCKET

Model	SKU	Watts	Lumen	Plug	Box Qty
VT-10-R	20038 | 4000K DAY WHITE 503 | 6400K WHITE	10w	700	micro usb cable without SOS Flash	20 pcs
VT-11-R	20037 | 4000K DAY WHITE 502 | 6400K WHITE	10w	700	micro usb cable	20 pcs
VT-20-R	20039 | 4000K DAY WHITE 504 | 6400K WHITE	20w	1400	micro usb cable	20 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED FLOODLIGHTS | Work Floodlight

V-TAC's heavy-duty, reliable LED work floodlight is designed with dual voltage AC:85-265V and comes with a 3-meter wire. Includes a EU/BS plug for optional direct connections. With an adjustable stand and carry handle, our work light is ideally suited for garages, workshops, basements, car repair shops and more.

- Input AC:85-265V,50Hz
- CRI >80
- PF >0.9
- 30,000-hour lifespan
- 100° Beam Angle
- Material: Die-cast Aluminium
- 3 Meter wire length
- IP44



WIDE VOLTAGE
85V- 265V

3 METER WIRE

LINKABLE

Model	SKU	Watts	Lumen	Plug	Box Qty
VT-51	945 | 4000K DAY WHITE 946 | 6400K WHITE	50w	4000	EU Plug	8 pcs
VT-51-BS	20065 | 6400K WHITE	50w	4000	BS Plug	8 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED FLOODLIGHTS | Grey Glass-Yellow Work Floodlight

V-TAC's LED Work Light is designed with a wide voltage range: 100–265VAC and comes with a 1.5-meter wire. A built-in BS plug – for optional direct connections – makes this floodlight an ideal tool for construction sites, facade lighting, lobbies, garages, passages, parking lots and other locations.

- AC:100–265V,50/60Hz
- 100° beam angle
- 30,000-hour lifespan
- CRI >80
- PF >0.9
- IP65 Rating
- Material: Die-cast Aluminium
- On/Off cycle: >15000
- 1.5 meter wire with BS plug



WIDE VOLTAGE 100-265V

1.5 METER WIRE

IP65 RATING

Model	SKU	Watts	Lumen	Plug	Box Qty
VT-58	20121 | 6400K WHITE	50w	5000	BS Plug	10 pcs
VT-108	20122 | 6400K WHITE	100w	10000	BS Plug	4 pcs
VT-108-N	2120122 | 6400K WHITE	100w	9400	BS Plug	4 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED FLOODLIGHTS | Slim Floodlight H-stand

A powerful, slim-built floodlight with a heavy-duty H-stand for high quality outdoor lighting performance. The floodlight can be tilted/ rotated and comes with a three-meter wire for maximum portability. Perfect for industrial areas – construction sites, repair shops and garages, warehouses, etc.

- Input AC:220-240V,50Hz
- CRI >80
- PF >0.9
- 25,000-hour lifespan
- 100° Beam Angle
- Material: Die-cast Aluminium
- On/Off cycle: >15000
- H-stand with 3 meter wire (EU Plug)



IP65 RATING

3 METER WIRE

Model	SKU	Watts	Lumen	Plug	Box Qty
VT-109	20124 | 4000K DAY WHITE 20125 | 6400K WHITE	100w	8000	EU Plug	10 pcs
VT-109-N	2120124 | 4000K DAY WHITE 2120125 | 6400K WHITE	100w	8200	EU Plug	10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED FLOODLIGHTS | Sports Light

The new LED Sports Light with Samsung LEDs offers a variety of light distribution options up to 67500 lumens. Excellent energy efficiency, low maintenance costs, and a strong, unbreakable exterior that can withstand ball strikes remarkably well compared to traditional fluorescent and HID options.

- LED provided by Samsung
- Saves 80% energy
- IP65 Rating
- MEAN WELL driver
- Contains no lead or mercury
- -hour lifespan of 30,000-hour lifespan



120 lm/W
Brighter & energy-efficient
50% better than normal LED

5 YEAR WARRANTY

DIMMABLE LIGHT CONTROL

MEAN WELL

IP65 RATING

Model	SKU	Watts	Lumen	Beam Angle	Box Qty
VT-500D	490 | 5000K WHITE	500w	67500	45°	1 pcs
VT-501D	493 | 5000K WHITE	500w	67500	110°	1 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED FLOODLIGHTS | Super Pro Series

Available in 250W, 500W, and 1000W, our heavy-duty IP66 LED Floodlights are perfect for industrial lighting. Never worry about efficiency — these floodlights are equipped with critically acclaimed LEDs provided by Samsung and excellent MEAN WELL drivers to ensure optimal energy saving and temperature dissipation.

- 60° & 120° Beam Angle (Rotatable)
- CRI: >70
- PF: > 0.9
- AC: 100–277V
- Material: Die-cast Aluminium
- 50,000-hour lifespan

120 lm/W
Brighter & energy-efficient
50% better than normal LED

5 YEAR WARRANTY

IP66 RATING

MEAN WELL
Your Reliable Power Partner

IK08 RATING

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING



Model	SKU	Watts	Lumen	Beam Angle	Box Qty
VT-253D	494 | 4000K DAY WHITE 500 | 6400K WHITE	250w	30000	120°	1 pcs
VT-252D	495 | 4000K DAY WHITE 501 | 6400K WHITE	250w	30000	60°	1 pcs



Model	SKU	Watts	Lumen	Beam Angle	Box Qty
VT-503D	496 | 4000K DAY WHITE	500w	60000	120°	1 pcs
VT-502D	497 | 4000K DAY WHITE	500w	60000	60°	1 pcs



Model	SKU	Watts	Lumen	Beam Angle	Box Qty
VT-1003D	498 | 4000K DAY WHITE	1000w	120000	120°	1 pcs
VT-1002D	499 | 4000K DAY WHITE	1000w	120000	60°	1 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated

LED STREETLIGHT

Light the path to a brighter future — V-TAC's LED street lights are equipped with premium-quality LEDs from Samsung and high performance drivers from DALI, Inventronics, and MEAN WELL to provide uniform brightness and illumination on highways, streets, tunnels, plazas, industrial facilities, car parks, etc. Includes Class I & Class II Type III-M lenses.

Key Features

- Modern and efficient replacement for traditional streetlights
- Saves 80% on electricity cost
- Low maintenance; longer lifespan
- Weatherproof body – IP65/66 sealed optical cavities
- Optimally designed glass lenses to prevent eye strain
- Uniform light distribution maximizes efficiency
- Fully operational, even in extreme weather conditions
- DALI, Inventronics, MEAN WELL drivers

Application

Engineered for streets, public parks, roads & highways, crossroads, tunnels, car parks, industrial facilities, etc.

5 YEAR WARRANTY **IP65 RATING** **120 Lumen/W**



V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED STREETLIGHTS | LED Streetlight with Light Sensor

- IP65 Rating
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V, 50Hz
- Body Type: Aluminium
- 100° Beam Angle
- CRI >70
- PF>0.9
- 30,000-hour lifespan



5 YEAR WARRANTY

IP65 RATING

IN-HOUSE TOOLING

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-39ST-S	20430 | 4000K DAY WHITE 20431 | 6500K WHITE	30w	3000	pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-59ST-S	20432 | 4000K DAY WHITE 20433 | 6500K WHITE	50w	5000	pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-139ST-S	20434 | 4000K DAY WHITE 20435 | 6500K WHITE	100w	11000	pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-169ST-S	20436 | 4000K DAY WHITE 20437 | 6500K WHITE	150w	16500	pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED STREETLIGHTS | LED Streetlights Adjustable

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V, 50Hz
- Body Type: Aluminium
- 100° Beam Angle
- CRI >70
- PF>0.9
- 30,000-hour lifespan

5 YEAR WARRANTY

IP65 RATING

IN-HOUSE TOOLING

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-39ST	20422 | 4000K DAY WHITE 20423 | 6500K WHITE	30w	3000	pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-59ST	20424 | 4000K DAY WHITE 20425 | 6500K WHITE	50w	5000	pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-79ST	20438 | 4000K DAY WHITE 20439 | 6500K WHITE	70w	7500	pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-139ST	20426 | 4000K DAY WHITE 20427 | 6500K WHITE	100w	11000	pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-169ST	20428 | 4000K DAY WHITE 20429 | 6500K WHITE	150w	16500	pcs

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED STREETLIGHTS | CLASS II, TYPE III-M LENS

The new Class II Type III-M lens from V-TAC offers a wide beam angle of 150×80° — Primarily designed for lighting highways, general parking areas, and other spaces where a widely-lit area is required. Available from 80W to 200W, select models available with DALI drivers.

10 KV SURGE PROTECTION

- AC:175–265V,50HZ
- 30,000-hour lifespan
- 150 × 80° Beam Angle
- CRI: >70
- PF: > 0.9
- Die-cast Aluminium

130 lm/W
Brighter & energy-efficient
50% better than normal LED

5 YEAR WARRANTY

INVENTRONICS DRIVER

IP65 RATING

IK08 RATING

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING



Model	SKU	Watts	Lumen	Box Qty
VT-80ST	541 | 4000K DAY WHITE	80w	10400	1 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-120ST	542 | 4000K DAY WHITE	120w	15600	1 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-160ST	543 | 4000K DAY WHITE	160w	20800	1 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-200ST	544 | 4000K DAY WHITE	200w	26000	1 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED GARDEN LIGHTS | CLASS II, TYPE III-M LENS

The LED Garden Light series offers our high lumen 50W & 100W upright and suspended lighting for outdoor applications. Equipped with high-quality LEDs from Samsung and drivers from Mean Well, these efficient, energy-saving garden lights are great alternatives to traditional lighting options.

10 KV SURGE PROTECTION

- AC:176–265V,50HZ
- Die-cast Aluminium
- 30,000-hour lifespan
- Beam Angle: 150×80° | 160×100° (Suspended Light)
- Instant start: 0–100% in <1sec
- On/off cycle: >20,000 times
- CRI: >70
- PF: > 0.9
- IK08 rating

130 lm/W
Brighter & energy-efficient
50% better than normal LED

5 YEAR WARRANTY

INVENTRONICS DRIVER

IP65 RATING

IK08 RATING

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

STREET LIGHT

SUSPENDED

GARDEN LIGHT



Model	SKU	Watts	Lumen	Box Qty
VT-895	8679 | 5700K WHITE	50w	6750	1 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-55-1	782 | 4000K DAY WHITE	50w	6500	1 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-105	783 | 4000K DAY WHITE	100w	13000	1 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-115ST	545 | 4000K DAY WHITE	100w	13000	1 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED STREETLIGHTS | Class I, Inventronics Driver Streetlight

The Class I Type LED streetlight offers a high lumen output and superbly efficient performance , further improved with the industry-leading Inventronics driver. Primarily designed for lighting highways, general parking areas, and other spaces where [wide area lighting/a widely-litarea] is required. Ranges 50W to 150W.

- AC: 90-305V,50Hz
- 30,000-hour lifespan
- 153×70° Beam Angle
- CRI: >70
- PF: > 0.9
- Die-cast Aluminium

140 lm/W
Brighter & energy-efficient
50% better than normal LED

5 YEAR WARRANTY

INVENTRONICS DRIVER

IP65 RATING

IK08 RATING

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING



Model	SKU	Watts	Lumen	Box Qty
VT-53ST	953 | 5700K WHITE	50w	7000	2 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-103ST	954 | 5700K WHITE	100w	14000	2 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-153ST	955 | 5700K WHITE	150w	21000	1 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED STREETLIGHTS | High Lumens

With options ranging from 100W up to 200W, V-TAC's innovative selection of streetlights introduces the new dimmable series with Samsung LEDs and world-renowned Inventronics drivers. Streetlights can be easily tailored for many night lighting needs of different areas and regions.

- AC:200-240V
- Die-cast Aluminium
- 30,000-hour lifespan
- CRI: >70
- PF: > 0.9
- 153×70° Beam Angle

140 lm/W
Brighter & energy-efficient
50% better than normal LED

5 YEAR WARRANTY

INVENTRONICS DRIVER

IP65 RATING

IK08 RATING

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING



Model	SKU	Watts	Lumen	Box Qty
VT-102ST	883 | 4000K DAY WHITE 884 | 5700K WHITE	100w	14000	1 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-122ST	885 | 4000K DAY WHITE 886 | 5700K WHITE	120w	16800	1 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-152ST	887 | 4000K DAY WHITE 888 | 5700K WHITE	150w	21000	1 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-202ST	889 | 4000K DAY WHITE 890 | 5700K WHITE	200w	28000	1 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED STREETLIGHTS | Slim Streetlight

The Slim Streetlight series from V-TAC offers a sleeker, leaner design without compromising the high lumen output that V-TAC streetlights are known for. Primarily designed for road lighting in highways, general parking areas, and other spaces where a wide-area lighting is required. Available in 30w to 150w.

- Input AC:120-240V,50/60Hz
- CRI >70
- PF >0.9
- 30,000-hour lifespan
- 110° Beam Angle
- Material aluminium

120 lm/W
Brighter & energy-efficient
50% better than normal LED



5 YEAR WARRANTY

IP65 RATING

IK08 RATING

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

Model	SKU	Watts	Lumen	Box Qty
VT-34ST	956 | 4000K DAY WHITE 957 | 6400K WHITE	30w	3600	4 pcs
VT-34ST-N	21956 | 4000K DAY WHITE 21957 | 6500K WHITE	30w	4050	4 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-54ST	958 | 4000K DAY WHITE 959 | 6400K WHITE	50w	6000	4 pcs
VT-54ST-N	21958 | 4000K DAY WHITE 21959 | 6500K WHITE	50w	6850	4 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-104ST	960 | 4000K DAY WHITE 961 | 6400K WHITE	100w	12000	2 pcs
VT-104ST-N	21960 | 4000K DAY WHITE 21961 | 6500K WHITE	100w	13500	2 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-154ST	962 | 4000K DAY WHITE 963 | 6400K WHITE	150w	18000	2 pcs
VT-154ST-N	21962 | 4000K DAY WHITE 21963 | 6500K WHITE	150w	20300	2 pcs



*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED STREETLIGHTS | Streetlight-Grey

Retaining the classic design of the V-TAC streetlight, the grey streetlight series boasts of high-quality LEDs from Samsung with superb energy efficiency. Available in 30W to 150W, and impressive lumen output of up to 18000.

- AC: 175-265V,50Hz
- Die-cast Aluminium
- 30,000-hour lifespan
- 110° Beam Angle
- CRI: >70
- PF: > 0.9

120 lm/W
Brighter & energy-efficient
50% better than normal LED

5 YEAR WARRANTY

IP65 RATING

IK07 RATING

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

Model	SKU	Watts	Lumen	Box Qty
VT-30ST	525 | 4000K DAY WHITE 526 | 6400K WHITE	30w	3600	4 pcs
VT-30ST-N	21525 | 4000K DAY WHITE	30w	2810	4 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-50ST	527 | 4000K DAY WHITE 528 | 6400K WHITE	50w	6000	4 pcs
VT-50ST-N	21527 | 4000K DAY WHITE 21528 | 6500K WHITE	50w	4700	4 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-100ST	529 | 4000K DAY WHITE 530 | 6400K WHITE	100w	12000	2 pcs
VT-100ST-N	21529 | 4000K DAY WHITE 21530 | 6500K WHITE	100w	9400	2 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-150ST	531 | 4000K DAY WHITE 532 | 6400K WHITE	150w	18000	2 pcs
VT-150ST-N	21531 | 4000K DAY WHITE	150w	14100	2 pcs



*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED STREETLIGHTS

Retaining the classic design of the V-TAC streetlight in Iron Grey finish, this series boasts of high-quality LEDs from Samsung with superb energy efficiency. Available in 30W to 120W, and impressive lumen output of up to 12000

- AC:200-240V
- Die-cast Aluminium
- Beam Angle: 110° | 65×135° (with lens)
- CRI: >70
- PF: > 0.9
- 30,000-hour lifespan

3 YEAR WARRANTY

IP65 RATING

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

Model	SKU	Watts	Lumen	Box Qty
VT-31ST	537 | 4000K DAY WHITE 538 | 6400K WHITE	30w	3000	4 pcs
VT-31ST-N	21537 | 4000K DAY WHITE 21538 | 6400K WHITE	30w	2350	4 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-51ST	539 | 4000K DAY WHITE 540 | 6400K WHITE	50w	5000	4 pcs
VT-51ST-N	21539 | 4000K DAY WHITE 21540 | 6400K WHITE	50w	4200	4 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-101ST	535 | 4000K DAY WHITE 536 | 6400K WHITE	100w	10000	2 pcs
VT-101ST-N	21535 | 4000K DAY WHITE 21536 | 6400K WHITE	100w	8400	2 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-121ST	533 | 4000K DAY WHITE 534 | 6400K WHITE	120w	12000	2 pcs





Model	SKU
VT-795	3624

Compatible with 100W,120W and 150W models, this adapter allows the angle of the streetlight to be adjusted as per client's requirements.



Model	SKU
VT-795-1	3668

Compatible with 30W and 50W models, this adapter allows the angle of the streetlight to be adjusted as per client's requirements.

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated

LED HIGHBAY LIGHTS

Our world-class Highbay range includes models with drivers from MEAN WELL and Samsung — both key players in the LED driver market that boasts exceptional energy-saving features.

With up to a staggering 180++ lumen-per-watt rating and drivers that provide a lifespan of up to 50,000-hour lifespan, V-TAC's new generation of LED Highbays are the strongest and most efficient LED Highbays available in the market today. Available in 100W to 500W.

Key Features

- Professional upgraded drivers from MEAN WELL and Samsung
- Strong and durable Die-cast Aluminium body
- IP65 rating
- SMD LED
- Compatible with Daylight Sensors
- Up to 30,000-hour lifespan
- Available reflectors for a customized beam angle: Aluminium & PC transparent

Application

Recommended for lighting in warehouses, factories, gymnasiums, or any large open area with high ceiling

5 YEAR WARRANTY **IP65 RATING** **120 Lumen/W**

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

REFLECTOR HIGHBAYS | SAMSUNG Power Supply

USING SAMSUNG POWER SUPPLY

With our latest in-branding program with Samsung, these Highbays offer a high lumen output of up to 180 lm/w and boasts efficiency in every lumen with Samsung's cutting edge drivers. With strong, IP65-rated die-cast Aluminium enclosing and unparalleled lighting performance, these LED Highbays are sure to take the industrial lighting market by storm.

- 120 lm/w
- 30,000 & 50,000-hour lifespan
- AC:220-240V,50Hz
- PF: >0.9
- CRI:>80
- Die cast Aluminium

180 lm/w
Brighter & energy-efficient
50% better than normal LED

5 YEAR WARRANTY

1-10V DIMMABLE

IP65 RATING

IK08 RATING

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING



120 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-103	577 | 4000K DAY WHITE 578 | 6400K WHITE	100w	12000	1 pcs



120 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-105	583 | 4000K DAY WHITE 584 | 6400K WHITE	100w	12000	1 pcs



evolution 160 LUMENS/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-113	20024 | 4000K DAY WHITE 20025 | 6000K WHITE	100w	16000	1 pcs



V-TAC PERFORMANCE 180 LUMENS/WATT

Model	SKU	Watts	Lumen	Box Qty
VT-9-108	575 | 4000K DAY WHITE 576 | 6400K WHITE	100w	18000	1 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated



V-TAC PERFORMANCE 180 LUMENS/WATT

MW MEAN WELL
Your Reliable Power Partner

Powerful performance with ultra-efficient energy management. With a staggering high lumen rating of 180 lm/w matched with the highly acclaimed MEAN WELL driver and IP65 Aluminium body.

Model	SKU	Watts	Lumen	Box Qty
VT-9-102	566 | 4000K DAY WHITE 567 | 6400K WHITE	100w	18000	2 pcs



V-TAC PERFORMANCE 180 LUMENS/WATT

MW MEAN WELL
Your Reliable Power Partner

Powerful performance with ultra-efficient energy management. With a staggering high lumen rating of 180 lm/w matched with the highly acclaimed MEAN WELL driver and IP65 Aluminium body.

Model	SKU	Watts	Lumen	Box Qty
VT-9-120	568 | 4000K DAY WHITE 569 | 6400K WHITE	120w	21600	2 pcs

Aluminium Reflector-90°

SKU
570

Aluminium Reflector-120°

SKU
571

PC Transparent Reflector-120°

SKU
574

PC Dustproof Cover

SKU
586

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED HIGHBAY LIGHTS | MEAN WELL Driver

MW MEAN WELL *Your Reliable Power Partner*

This advanced LED Highbays are ready to impress with its high lumen ratings and LED chips from Samsung. This range is equipped with drivers from MEAN WELL — a key player in the LED driver industry for a strong and efficient performance.

- Available in 100 – 500 watts
- 50,000-hour lifespan
- On/Off cycle: >25000
- Instant start: 0–100% in <1s
- AC:95–265V,50/60Hz
- Die cast Aluminium
- PF: >0.9
- CRI:>80

120 lm/W

Brighter & energy-efficient
50% better than normal LED

5 YEAR WARRANTY

1–10V DIMMABLE

IP65 RATING

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

DALI
Dimming



120 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-106	585 | 4000K DAY WHITE	100w	12000	1 pcs



120 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-100	564 | 4000K DAY WHITE 565 | 6400K WHITE	100w	12000	4 pcs



120 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-101	562 | 4000K DAY WHITE 563 | 6400K WHITE	100w	12000	4 pcs



120 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-150	560 | 4000K DAY WHITE 561 | 6400K WHITE	150w	18000	2 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING



120 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-114	20063 | 4000K DAY WHITE 20064 | 5000K WHITE	100w	12000	1 pcs



140 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-151N	55811 | 4000K DAY WHITE 55911 | 6400K WHITE	150w	21000	1 pcs



120 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-151	558 | 4000K DAY WHITE 559 | 6400K WHITE	150w	18000	2 pcs



120 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-200	580 | 4000K DAY WHITE 581 | 6400K WHITE	200w	24000	1 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED HIGHBAYS | PRO UFO Series 90°

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:175-265V, 50Hz
- Body Type: Die Cast Aluminium
- 90° Beam Angle
- CRI >70
- PF>0.9
- 30,000-hour lifespan
- On/Off Cycle >15000

5 YEAR WARRANTY

IP65 RATING

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

NEW



IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-9-116S	20319 | 4000K DAY WHITE 20320 | 6500K WHITE	100w	11500	4 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-9-156S	20321 | 4000K DAY WHITE 20322 | 6500K WHITE	150w	17300	4 pcs

NEW



Model	SKU	Watts	Lumen	Box Qty
VT-9-206S	20323 | 4000K DAY WHITE 20324 | 6500K WHITE	200w	23000	4 pcs



120 lm/W

Model	SKU	Watts	Lumen	Box Qty
VT-9-500	509 | 4000K DAY WHITE	500w	60000	1 pcs

140LM/W Highbay Sensor

SKU
20123

- Rated Voltage: AC:100/277V, 50/60Hz
- Working Mode: On/Off Function, 1-10V step dimming
- IP Rating: IP65
- Hold Time: 5s/30s/1min/3min/5min/10min/20min/30min
- Stand-by Dim Level: 10%/20%/30%/50%
- Stand-by Period: 0s/10s/1min/3min/5min/10min/30min/+∞
- Detection Area: 25%/50%/75%/100%
- Detection Angle: 360°(ceiling mounting)
- Daylight Sensor: 5lux/15lux/30lux/50lux/100lux/150lux/Disable (Ambient light diffusion)
- Compatible with VT-9-151N and VT-9-200N

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LOW BAY LIGHTS

Our series of LED LowBay fixtures allow parallel lighting on supermarket aisles, workshops, warehouses, and factories. Lowbay light has proven to be approximately 50% more efficient than perpendicular lighting layout, it also decreases eye strain. This range offers ample light with promising 120 lm/w options and impressive energy-saving features compared to its traditional counterparts. Available in 100w to 200w.

- AC:220-240v,50HZ
- On/off: >20,000 times
- IP54 rating
- Lifespan – 30,000 hrs
- Aluminium body
- Heat and Shock Resistant.
- Ideal for workshops, supermarkets, warehouses, etc.
- PF: >0.9
- CRI:>80
- Beam Angle: 112°

120 lm/w
Brighter & energy-efficient
50% better than normal LED

5 YEAR WARRANTY

IK07 RATING

IP54 RATING

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING



Model	SKU	Watts	Lumen	Box Qty
VT-9-112	891 | 4000K DAY WHITE 892 | 6000K WHITE	100w	12000	6 pcs
VT-9-112-N	21891 | 4000K DAY WHITE 21892 | 6500K WHITE	100w	9800	9 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-9-152	893 | 4000K DAY WHITE 894 | 6000K WHITE	150w	18000	6 pcs
VT-9-152-N	21893 | 4000K DAY WHITE	150w	14500	6 pcs



Model	SKU	Watts	Lumen	Box Qty
VT-9-202	895 | 4000K DAY WHITE 896 | 6000K WHITE	200w	24000	6 pcs
VT-9-202-N	21895 | 4000K DAY WHITE 21896 | 6500K WHITE	200w	19500	6 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated

LED PANELS

The PRO Series LED panels range are all made with top-quality PMMA diffusers which provides a uniformly distributed light and prevents the panels from turning yellow.

It proves its durability with exteriors composed of an innovative combination of Aluminium+PMMA+PP, and its energy-saving upgrade through the improved driver box and Samsung LEDs. Both frameless and big panels are inclusive of a quick connector for easy installation.

Key Features

- Inclusive of a quick connector
- Flicker-free; stable drivers eliminate flashes
- Better light quality: less false colour plots
- 80% lower power consumption than conventional downlights
- Standard dimensions for big panels available
- Choose from square and round frameless mini panels

Application

Widely used in offices, schools, hospitals, and commercial establishments

5 YEAR WARRANTY

120 Lumen/W



V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED PANELS | PRO 60×60

Our LED panels are made with high-quality PMMA diffusers which prevents them from turning yellow over time and makes it emit strong and evenly distributed light. Also available in the TP(a)-rated panel to meet fire safety standards. All our LED panels have quick connectors that will save installation time and costs.

- IP20 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:200–240V, 50/60Hz
- Body Type: Aluminium + PMMA + PP
- 110° Beam Angle
- CRI >80
- PF>0.9
- 50,000-hour lifespan
- On/Off Cycle >25000



5 YEAR WARRANTY

QUICK CONNECTOR

FLICKER FREE



	Model	SKU	Watts	Lumen	Box Qty
PMMA Diffuser	VT-629-N	21200471 | 4000K DAY WHITE	26w	3480	6 pcs
PMMA Diffuser	VT-629	20047 | 4000K DAY WHITE 20048 | 6400K WHITE	29w	3480	6 pcs
PMMA Diffuser	VT-645-N	2163300 | 4000K DAY WHITE 2163411 | 6400K WHITE	40w	4950	6 pcs
PMMA Diffuser	VT-645	632 | 3000K WARM WHITE 633 | 4000K DAY WHITE 634 | 6400K WHITE	45w	3600	6 pcs
UGR<19	VT-649	20119 | 4000K DAY WHITE	45w	3600	6 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED PANELS
PRO 60×60 High Lumen

- IP20 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:200–240V, 50/60Hz
- Body Type: Aluminium
- 110° Beam Angle
- CRI >80
- PF>0.9
- 30,000-hour lifespan
- On/Off Cycle >15000

5 YEAR WARRANTY

120 lm/W



Model	SKU	Watts	Lumen	Box Qty
VT-629-1	20419 | 4000K DAY WHITE	29w	3480	6 pcs



LED PANELS
PRO 60×60

- IP20 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:200–240V, 50/60Hz
- Body Type: Aluminium
- 110° Beam Angle
- CRI >80
- PF>0.9
- 30,000-hour lifespan
- On/Off Cycle >15000

5 YEAR WARRANTY

Model	SKU	Watts	Lumen	Box Qty
VT-645-1	20421 | 4000K DAY WHITE 20420 | 6400K WHITE	45w	4830	6 pcs



*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED BACKLIT PANEL | Evolution Panels Series

evolution 160 LUMENS/W

This 25w LED panel delivers 4000 lumens through its impressive 160 lm/w rating. With the flexibility to be installed recessed or surface-mounted, it is sure to be one of the best preferred panels in the market.

- SMD LED Type
- 20,000-hour lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- CRI: >80
- FE+PS

2 IN 1 RECESSED OR SURFACE

2 YEAR WARRANTY

Model	SKU	Watts	Lumen	Box Qty
VT-6125	6600 | 3000K WARM WHITE 6601 | 4000K DAY WHITE 6602 | 6400K WHITE	25w	4000	1 pcs



*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED PANELS | High Lumen 120×60

120 lm/W

- IP20 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:200-240V, 50/60Hz
- Body Type: Aluminium + PMMA + PP
- 110° Beam Angle
- CRI >80
- PF>0.9
- 50,000-hour lifespan
- On/Off Cycle >25000

5 YEAR WARRANTY

QUICK CONNECTOR



Model	SKU	Watts	Lumen	Box Qty
VT-646-N	21748 | 4000K DAY WHITE 21749 | 6400K WHITE	40w	5400	2 pcs
VT-646	748 | 4000K DAY WHITE 749 | 6400K WHITE	45w	5400	2 pcs



*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED MINI PANELS | Round Adjustable Panel

V-TAC's new innovative adjustable mini panels are equipped with adjustable clips for a flexible cutting size of up to 200 mm. Built with the most stable drivers in the market, have low maintenance panels without the flashes and the flickers. These slim & modern panels lights up all the way to the edges, giving a contemporary lighting effect.

- Adjustable(Cut out) Panel
- SMD LED Type
- 20,000-hour lifespan
- 120° Beam Angle
- AC:85-265V,50/60Hz
- CRI: >80
- Aluminium Body
- On/Off Cycle: >15000

5 YEAR WARRANTY

QUICK CONNECTOR

Model	SKU	Watts	Lumen	Cutting Size	Dimension	Box Qty
VT-610RD	727 | 3000K WARM WHITE 728 | 4000K DAY WHITE 729 | 6400K WHITE	12w	750	75-100mm	Φ 120mm 32 mm	20 pcs
VT-619RD	733 | 3000K WARM WHITE 734 | 4000K DAY WHITE 735 | 6400K WHITE	18w	1350	75-100mm	Φ 170mm 32 mm	20 pcs
VT-625RD	739 | 3000K WARM WHITE 740 | 4000K DAY WHITE 741 | 6400K WHITE	24w	1800	75-200mm	Φ 223mm 32 mm	20 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED MINI PANELS | Square Adjustable Panel

V-TAC's new innovative adjustable mini panels are equipped with adjustable clips for a flexible cutting size of up to 200 mm. Built with the most stable drivers in the market, have low maintenance panels without the flashes and the flickers. These slim & modern panels lights up all the way to the edges, giving a contemporary lighting effect.

- Adjustable(Cut out) Panel
- SMD LED Type
- 20,000-hour lifespan
- 120° Beam Angle
- AC:85-265V,50/60Hz
- CRI: >80
- Aluminium Body
- On/Off Cycle: >15000

5 YEAR WARRANTY

QUICK CONNECTOR

Model	SKU	Watts	Lumen	Cutting Size	Dimension	Box Qty
VT-610SQ	730 | 3000K WARM WHITE 731 | 4000K DAY WHITE 732 | 6400K WHITE	12w	750	75-100mm		20 pcs
VT-619SQ	736 | 3000K WARM WHITE 737 | 4000K DAY WHITE 738 | 6400K WHITE	18w	1350	75-100mm		20 pcs
VT-625SQ	742 | 3000K WARM WHITE 743 | 4000K DAY WHITE 744 | 6400K WHITE	24w	1800	75-200mm		20 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED MINI PANELS | Round Edge Series

V-TAC's Round Edge Panel has an elegant, classic design that lights up all the way to the edges — giving a contemporary lighting effect that is ideal for residential, office, or commercial indoor areas. The quick connector feature lessens set-up time brought by complicated wirings.

- Quick Connector
- SMD LED Type
- 30,000-hour lifespan
- 120° Beam Angle
- AC:220-240V,50Hz
- CRI: >80
- ABS+Plastic Body

5 YEAR WARRANTY

QUICK CONNECTOR

Model	SKU	Watts	Lumen	Cutting Size	Dimension	Box Qty
VT-608RD	628 | 6400K WHITE	8w	800	ø 72 mm		100 pcs
VT-615RD	622 | 6400K WHITE	15w	1500	ø 95 mm		40 pcs
VT-620RD	614 | 3000K WARM WHITE 615 | 4000K DAY WHITE	20w	2000	ø 140 mm		40 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED MINI PANELS | Square Edge Series

V-TAC's Squre Edge Panel has an elegant, classic design that lights up all the way to the edges — giving a contemporary lighting effect that is ideal for residential, office, or commercial indoor areas. The quick connector feature lessens set-up time brought by complicated wirings.

- Quick Connector
- SMD LED Type
- 30,000-hour lifespan
- 120° Beam Angle
- AC:220-240V,50Hz
- CRI: >80
- ABS+Plastic Body

5 YEAR WARRANTY

QUICK CONNECTOR

Model	SKU	Watts	Lumen	Cutting Size	Dimension	Box Qty
VT-615SQ	617 | 3000K WARM WHITE 618 | 4000K DAY WHITE 619 | 6400K WHITE	15w	1500	95X 95mm		40 pcs
VT-620SQ	611 | 3000K WARM WHITE 612 | 4000K DAY WHITE 613 | 6400K WHITE	20w	2000	142X 142mm		40 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED MINI PANELS | Round Premium Series Panel

V-TAC's efficient & trendy Premium Series Mini Panels are now upgraded with premium-quality Samsung LEDs for an even better lighting output and performance. Built with the most stable drivers in the market, have low maintenance panels without flashes and flickers.

- SMD LED Type
- 30,000-hour lifespan
- 120° Beam Angle
- AC:85-265V,50/60Hz
- CRI: >80
- Aluminium Body

5 YEAR WARRANTY

QUICK CONNECTOR

Model	SKU	Watts	Lumen	Cutting Size	Dimension	Box Qty
VT-606RD	706 | 3000K WARM WHITE 708 | 6400K WHITE	6w	420	ø110mm		40 pcs
VT-612RD	712 | 3000K WARM WHITE 713 | 4000K DAY WHITE 714 | 6400K WHITE	12w	1000	ø160mm		20 pcs
VT-618RD	718 | 3000K WARM WHITE 719 | 4000K DAY WHITE	18w	1500	ø210mm		20 pcs
VT-624RD	724 | 3000K WARM WHITE 726 | 6400K WHITE	24w	2000	ø280mm		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED MINI PANELS | Square Premium Series Panel

V-TAC's efficient & trendy Premium Series Mini Panels are now upgraded with premium-quality Samsung LEDs for an even better lighting output and performance. Built with the most stable drivers in the market, have low maintenance panels without flashes and flickers.

- SMD LED Type
- 30,000-hour lifespan
- 120° Beam Angle
- AC:85-265V,50/60Hz
- CRI: >80
- Aluminium Body

5 YEAR WARRANTY

QUICK CONNECTOR

Model	SKU	Watts	Lumen	Cutting Size	Dimension	Box Qty
VT-606SQ	703 | 3000K WARM WHITE 704 | 4000K DAY WHITE 705 | 6400K WHITE	6w	420	110×110mm		40 pcs
VT-612SQ	709 | 3000K WARM WHITE 710 | 4000K DAY WHITE 711 | 6400K WHITE	12w	1000	160×160mm		20 pcs
VT-618SQ	715 | 3000K WARM WHITE 716 | 4000K DAY WHITE 717 | 6400K WHITE	18w	1500	210×210mm		20 pcs
VT-624SQ	721 | 3000K WARM WHITE 722 | 4000K DAY WHITE 723 | 6400K WHITE	24w	2000	280×280mm		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated

LED TUBES & BATTEN FITTING

V-TAC's extensive range of efficient tubes & fixtures boasts of premium quality LED provided by Samsung, a staggering lifespan of up to 30,000-hour lifespan, an unbreakable body built with the most durable material, and a wide range of lengths and sizes for different applications.

More innovative additions in this range include
1) TP(a) rated fixtures compatible with emergency packs & microwave sensors
2) Batten Fittings with CCT-changing Switch
3) Linkable T5 Batten Fittings, and more.
4) Waterproof Fittings

Key Features

- LED provided by Samsung
- Built with strong, durable materials
- TP(a) Rated fittings for select models
- Programmable DIP Switch Driver for select models
- Emergency Pack & Sensor Compatibility
- Linkable/Continuous T5 fittings
- CCT Changing Switch for select models

Application

Used for general purpose lighting in residences, commercial establishments, supermarkets, and offices

V-TAC®
INNOVATIVE LED LIGHTING

evolution

T8-NANO PLASTIC TUBES | Evolution Tubes Series

Together with its impressive a++ energy rating, our led tubes offer a staggering 160 lumen per watt output and five years warranty — making it one of the most superior in the competitive led market.

- Nano Plastic
- 30,000-hour lifespan
- CRI – >80
- Flicker Free
- PF – 0.9
- On/Off Cycle – >15000 time
- Input Voltage – AC:220-240V,50Hz
- Beam angle:160 °

evolution 160 LUMENS/W

5 YEAR WARRANTY

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-1607	6474 | 3000K WARM WHITE 6475 | 4000K DAY WHITE 6476 | 6400K WHITE	7w	1120lm		25 pcs
VT-1612	6477 | 3000K WARM WHITE 6478 | 4000K DAY WHITE 6479 | 6400K WHITE	12w	1920lm		25 pcs
VT-1615	6481 | 4000K DAY WHITE 6482 | 6400K WHITE	15w	2400lm		25 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED TUBES | G13-T8 – High Lumen Nano Plastic Tube

This modern range of high lumen LED tubes with Samsung LEDs are the perfect retrofit for fluorescent fixtures.This range offers strong and ample light with promising 120 lm/w options and impressive energy-saving features compared to its traditional counterparts.

120 lm/w

5 YEAR WARRANTY

- Nano Plastic Body
- 30,000-hour lifespan
- 160° Beam Angle
- 15000 On/Off
- AC:220–240V,50Hz
- CRI – >80
- >0.5 PF
- <0.5 s Instant Start



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-062	798 | 3000K WARM WHITE 686 | 4000K DAY WHITE 687 | 6400K WHITE	10w Rotatable	1100		25 pcs
VT-062-N	21798 | 3000K WARM WHITE 21686 | 4000K DAY WHITE 21687 | 6500K WHITE	7.5w	850		25 pcs
VT-122	688 | 3000K WARM WHITE 672 | 4000K DAY WHITE 673 | 6400K WHITE	18w	2250		25 pcs
VT-122-N	21688 | 3000K WARM WHITE 21672 | 4000K DAY WHITE 21673 | 6500K WHITE	16.5w	1850		25 pcs
VT-152	799 | 3000K WARM WHITE 674 | 4000K DAY WHITE 675 | 6400K WHITE	22w	3000		25 pcs
VT-152-N	21674 | 3000K WARM WHITE 21675 | 4000K DAY WHITE 21799 | 6500K WHITE	24w	3000		25 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED TUBES | G13-T8 -Nano Plastic Tube

This modern range of LED tubes with Samsung LEDs are the perfect retrofit for fluorescent fixtures. These sets of tubes are available in standard lengths for general purpose lighting in residences, commercial establishments, supermarkets, and offices.

- Nano Plastic Body
- 30,000-hour lifespan
- 160° Beam Angle
- 15000 On/Off
- AC:220-240V,50Hz
- CRI – >80
- >0.5 PF
- <0.5 s Instant Start

5 YEAR WARRANTY

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-061	650 | 3000K WARM WHITE 651 | 4000K DAY WHITE 652 | 6400K WHITE	10w Rotatable	850		25 pcs
VT-061-N	21650 | 3000K WARM WHITE 21651 | 4000K DAY WHITE 21652 | 6500K WHITE	9w	850		25 pcs
VT-121	653 | 3000K WARM WHITE 654 | 4000K DAY WHITE 655 | 6400K WHITE	18w	1700		25 pcs
VT-121-N	21654 | 4000K DAY WHITE	18w	1850		25 pcs
VT-151	656 | 3000K WARM WHITE 657 | 4000K DAY WHITE 658 | 6400K WHITE	22w	2000		25 pcs
VT-151-N	21657 | 4000K DAY WHITE 21658 | 6500K WHITE	20w	2100		25 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED BATTEN FITTING | Single and Double Batten Fitting

This modern range of batten fittings offers durability and can house one to two LED tubes. These luminaires are available in standard lengths for general purpose lighting in residences, commercial establishments, supermarkets, and offices.

- SMD LED Type
- 30,000-hour lifespan
- 160° Beam Angle
- AC:220-240V,50Hz
- CRI: >80
- Nano Plastic Body

5 YEAR WARRANTY

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12026	6442 | 4000K DAY WHITE	18w Single	1700		10 pcs
VT-15023	6438 | 4000K DAY WHITE	22w Single	2000		10 pcs
VT-12027	6444 | 4000K DAY WHITE	36w Double	3400		10 pcs
VT-15024	6440 | 4000K DAY WHITE	44w Double	4000		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

evolution

LED BATTEN FITTING | Slim Fittings-Evolution Series

- Plastic Body
- 30,000-hour lifespan
- CRI – >80
- Flicker Free
- PF – >0.9
- On/Off Cycle – >15000 time
- Input Voltage – AC:220-240V,50Hz
- Beam angle:120 °

evolution 160 LUMENS/W

5 YEAR WARRANTY

QUICK CONNECTOR

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-8315	6487 | 3000K WARM WHITE 6488 | 4000K DAY WHITE 6489 | 6400K WHITE	15w	2400	600×24.4×74.1mm	30 pcs
VT-8315-N	20359 | 3000K WARM WHITE 20360 | 4000K DAY WHITE 20361 | 6500K WHITE	15w	2250	600×75×24mm	30 pcs
VT-8330	6490 | 3000K WARM WHITE 6491 | 4000K DAY WHITE 6492 | 6400K WHITE	30w	4800	1200×24.4×74.1mm	30 pcs
VT-8330-N	20362 | 3000K WARM WHITE 20363 | 4000K DAY WHITE 20364 | 6500K WHITE	30w	4650	1200×75×24mm	30 pcs
VT-8338	6493 | 3000K WARM WHITE 6494 | 4000K DAY WHITE 6495 | 6400K WHITE	38w	6080	1500×24.4×74.1mm	30 pcs
VT-8338-N	20365 | 3000K WARM WHITE 20366 | 4000K DAY WHITE 20367 | 6500K WHITE	38w	5900	1500×45×24mm	30 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED BATTEN FITTING | Slim Fittings

5 YEAR WARRANTY

- SMD LED Type
- 30,000-hour lifespan
- 120° Beam Angle
- 15000 On/Off
- AC:220-240V,50Hz
- CRI: >80
- PF >0.5(10W, 20W) >0.9(40W, 50W,60W)
- Plastic Body
- <1s Instant Start

QUICK CONNECTOR

120 lm/W

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-8-10	659 | 3000K WARM WHITE 660 | 4000K DAY WHITE 661 | 6400K WHITE	10w	1200	300×74.1×24.4mm	10 pcs
VT-8-10-N	20344 | 3000K WARM WHITE 20345 | 4000K DAY WHITE	10w	1000	300×75×24mm	30 pcs
VT-8-20	662 | 3000K WARM WHITE 663 | 4000K DAY WHITE 664 | 6400K WHITE	20w	2400	600×74.1×24.4mm	10 pcs
VT-8-20-N	20347 | 3000K WARM WHITE 20348 | 4000K DAY WHITE 20349 | 6500K WHITE	20w	2050	600×75×24mm	30 pcs
VT-8-40	665 | 3000K WARM WHITE 666 | 4000K DAY WHITE 667 | 6400K WHITE	40w	4800	1200×74.1×24.4mm	10 pcs
VT-8-40-N	20350 | 3000K WARM WHITE 20351 | 4000K DAY WHITE 20352 | 6500K WHITE	40w	4300	1200×75×24mm	30 pcs
VT-8-50	668 | 4000K DAY WHITE 669 | 6400K WHITE	50w	6000	1500×74.1×24.4mm	10 pcs
VT-8-50-N	20354 | 4000K DAY WHITE 20355 | 6500K WHITE	50w	6000	1500×75×24mm	30 pcs
VT-8-60	670 | 4000K DAY WHITE 671 | 6400K WHITE	60w	7200	1800×74.1×24.4mm	10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED BATTEN FITTING | LED Batten Fittings IP20

V-TAC's all new range of LED Batten Fittings designed with LED chip by Samsung deliver high performance light output.

120 lm/W

5 YEAR WARRANTY

QUICK CONNECTOR

- SMD LED Chip
- 30,000-hour lifespan
- 120° Beam Angle
- AC:220-240V, 50Hz
- 120LM/W
- CRI >80
- PF >0.9 (Above 24W models)
- Built with safety belt for easy installation
- Instant Start 0-100% in <1s
- On/Off Cycles >15000

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-8-24	20066 | 4000K DAY WHITE 20067 | 6400K WHITE	24w	2880		12 pcs
VT-8-28	20070 | 4000K DAY WHITE 20071 | 6400K WHITE	28w	3360		10 pcs
VT-8-44	20068 | 4000K DAY WHITE 20069 | 6400K WHITE	40w	4800		12 pcs
VT-8-54	20072 | 4000K DAY WHITE 20073 | 6400K WHITE	50w	6000		10 pcs
VT-8-64	20074 | 4000K DAY WHITE 20075 | 6400K WHITE	60w	7200		8 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

LED BATTEN FITTING | LED Batten Fitting TP(a)

V-TAC's all-new range of LED Batten Fittings designed with LED chip by Samsung deliver high-performance light output. These fittings are built strong using the materials Iron + Polycarbonate and are also TP(a) rated to meet the fire safety standards. Optional microwave sensor Primarily designed for LED Batten Fittings is also available.

- Tp(A) Rated
- 30,000-hour lifespan
- CRI – >80
- PF – 0.9
- On/Off Cycle – >15000 time
- Input Voltage – AC:220–240V,50Hz
- Programmable DIP Switch Driver

5 YEAR WARRANTY

FLICKER FREE

TP(a) Polycarbonate

Compatible Emergency Pack

Sensor Compatible

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-8-80	757 | 4000K DAY WHITE	80w	8600		10 pcs

Microwave Sensor (Optional)

SKU
759

Detection area: 4M (@3M MOUNTING HEIGHT)
Detection angle: 150°(WALL) 360°(CEILING)
Hold time: 5S / 30S / 90S / 3MIN / 30MIN
Emergency Pack designed for V-TAC's range of Samsung Batten LED Tube

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED BATTEN FITTING | Batten Fitting CCT

The new Batten Fittings series from V-TAC boasts of its colour tuning feature with an easy-to-access, built-in switch — enabling users to gradually customise the light from a warm 3000-kelvin white light up to the standard 6400-kelvin white. Choose and switch to your preferred colour temperature anytime.

EASY TOGGLE SWITCH

EASY ACCESS FOR COLOR CHANGING WITH BUTTON

- PC+Aluminium+Steel
- 30,000-hour lifespan
- CRI – >80
- Flicker Free
- PF – 0.9
- On/Off Cycle – >20000 time
- Input Voltage – AC:220-240V,50Hz
- Beam angle:120 °

5 YEAR WARRANTY

FLICKER FREE

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-8-43	517 | 3IN1	40w	4000		10 pcs
VT-8-63	519 | 3IN1	60w	6000		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED BATTEN FITTING | Slim Batten Fitting

TP(a) Polycarbonate

Sensor Compatible

120 lm/W

5 YEAR WARRANTY

FLICKER FREE

V-TAC's all new range of LED Batten fittings designed with LED chip by Samsung deliver high-performance light output of 120 lumens/watt. These fittings are built strong using the materials Iron + Polycarbonate and are also TP(a) rated to meet the fire safety standards. Optional emergency pack and microwave sensor Primarily designed for LED Batten are also available.

- Tp(A) Rated
- 30,000-hour lifespan
- CRI – >80
- PF – 0.9
- On/Off Cycle – >15000 time
- Input Voltage – AC:220-240V,50Hz
- Programmable DIP Switch Driver(Applicable for 60W only)

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-8-41	753 | 4000K DAY WHITE	40w	4800		4 pcs
VT-8-61	754 | 4000K DAY WHITE	60w	7200		4 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED BATTEN FITTING | T5 Batten Fitting

- 30,000-hour lifespan
- On/Off switch
- On/Off Cycle – >15000 time
- Body:PC
- Input Voltage – AC:220-240V
- CRI – >80
- Instant start -0-100% in <1 sec
- Beam angle:120 °

5 YEAR WARRANTY

LINKABLE
UP TO 100 WATTS TOGETHER

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-035	689 | 3000K WARM WHITE 690 | 4000K DAY WHITE 691 | 6400K WHITE	4w	360	320×30mm	25 pcs
VT-035-N	21689 | 3000K WARM WHITE 21690 | 4000K DAY WHITE 21691 | 6500K WHITE	4w	360	307 x36×90mm	25 pcs
VT-065	692 | 3000K WARM WHITE 693 | 4000K DAY WHITE 694 | 6400K WHITE	7w	630	580×30mm	25 pcs
VT-065-N	21692 | 3000K WARM WHITE	7w	630	567×36×90mm	25 pcs
VT-125	695 | 3000K WARM WHITE 696 | 4000K DAY WHITE 697 | 6400K WHITE	16w	1440	1180×30mm	25 pcs
VT-125-N	21695 | 3000K WARM WHITE 21696 | 4000K DAY WHITE 21697 | 6500K WHITE	16w	1440	1167×36×90mm	25 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

LED BATTEN FITTING | Waterproof Fittings

With its IP65 rating and tough exterior, the Waterproof Fittings are the optimal choice for a strong and durable fitting for indoor and outdoor lighting. Available in 4ft, 5ft, and 6ft, these Waterproof Fittings are ideal for illuminating open spaces that are frequently exposed to dust and moisture.

- SMD LED Type
- 30,000-hour lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- CRI: >70
- PF: >0.9

160 LUMENS/W

5 YEAR WARRANTY

IP65 RATING



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-1524	6485 | 4500K DAY WHITE 6486 | 6400K WHITE	24w	3840		12 pcs
VT-1532	6483 | 4500K DAY WHITE 6484 | 6400K WHITE	32w	5120		12 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED BATTEN FITTING | Waterproof Fittings-180CM

- SMD LED Type
- 30,000-hour lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- CRI: >80
- PF: >0.9

5 YEAR WARRANTY

IP65 RATING



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-180	680 | 4000K DAY WHITE 681 | 6400K WHITE	60w	5400		9 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED BATTEN FITTING | Waterproof Fittings-High Lumens

- SMD LED Type
- 30,000-hour lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- CRI: >80
- PF: >0.9

5 YEAR WARRANTY

IP65 RATING

120 lm/W

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-160	678 | 4000K DAY WHITE 679 | 6400K WHITE	60w	7200		9 pcs
VT-160-N	21678 | 4000K DAY WHITE 21679 | 6000K WHITE	60w	7200		9 pcs
VT-170	676 | 4000K DAY WHITE 677 | 6400K WHITE	70w	8400		9 pcs
VT-170-N	21676 | 4000K DAY WHITE 21677 | 6000K WHITE	70w	8400		6 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED BATTEN FITTING | Waterproof Fitting with Sensor

- SMD LED Chip
- 20,000-hour lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- On/Off Cycles >15000
- Body Type: PC
- CRI >80
- PF >0.9
- IP65
- SS Clips

POLYCARBONATE PC

5 YEAR WARRANTY

120 lm/W

IP65 RATING

Microwave Sensor

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-120136S	20468 | 4000K DAY WHITE 20469 | 6400K WHITE	36w	4320		12 pcs
VT-150148S	20470 | 4000K DAY WHITE 20471 | 6400K WHITE	48w	5760		12 pcs

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED BATTEN FITTING | Emergency Waterproof Fittings

- 20,000-hour lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- Battery Type:9.6V 2200mAh Ni-Cd battery
- Charging Time:24Hours
- Working Time:3Hours
- Emergency Power: 6-7W
- SMD LED Chip
- Body Type: PC
- On/Off Cycles >15000
- CRI >80
- PF >0.9
- IP65
- SS Clips

POLYCARBONATE PC

3 YEAR WARRANTY

120 lm/W

Emergency Battery Backup

IP65 RATING

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-120136E	20223 | 4000K DAY WHITE 20222 | 6400K WHITE	36w	4320		12 pcs
VT-120136E-N	2120223 | 4000K DAY WHITE 2120222 | 6400K WHITE	36w	4320		12 pcs
VT-150148E	20221 | 4000K DAY WHITE 20220 | 6400K WHITE	48w	5760		12 pcs
VT-150148E-N	2120221 | 4000K DAY WHITE 2120220 | 6400K WHITE	48w	5760		12 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED BATTEN FITTING | Opaque Cover – M Series SS Clips

Promoting efficiency with its high lumen (120 lm/W) rating, this new addition to V-TAC's fixtures range is reinforced with secure, stainless steel clips for easier maintenance. The opaque cover allows a brighter, well-distributed light that is perfect for task lighting.

POLYCARBONATE PC

- SMD LED Chip
- 20,000-hour lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- On/Off Cycles >15000
- Body Type: PC
- CRI >80
- PF >0.9
- IP65
- SS Clips

IP65 RATING

120 lm/W

3 YEAR WARRANTY

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-120136-T	20219 | 4000K DAY WHITE 20218 | 6400K WHITE	36w	4320		12 pcs
VT-150148-T	20213 | 4000K DAY WHITE 20212 | 6400K WHITE	48w	5760		12 pcs

Microwave Sensor

SKU
6622

- Rod antenna – DIP Switch
- Max Watts: 100W
- Hold Time: 5s/1min/3min/10min
- Daylight threshold: 30Lux/Disable
- Detection Area: 50%/100%
- Automatic On/Off control with daylight sensor.
- Optional detection range, hold time and daylight threshold.
- Loop in and loop out for easy installation.
- Operating Voltage: AC:220-240V, 50/60Hz
- Detection Range: ø4-10m/13.12-32.8ft (ceiling mounted)
- Compatible with V-TAC's LED Waterproof Fitting – M Series SS Clips

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED BATTEN FITTING | Milky Cover – M Series SS Clips

- SMD LED Chip
- 20,000-hour lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- On/Off Cycles >15000
- Body Type: PC
- CRI >80
- PF >0.9
- IP65
- SS Clips

POLYCARBONATE PC

IP65 RATING

120 lm/W

3 YEAR WARRANTY

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-120136-M	20217 | 4000K DAY WHITE 20216 | 6400K WHITE	36w	4320	1285×365×255mm	12 pcs
VT-120136-M-N	2120217 | 4000K DAY WHITE 2120216 | 6400K WHITE	36w	4320	1285×365×255mm	12 pcs
VT-150148-M	20215 | 4000K DAY WHITE 20214 | 6400K WHITE	48w	5760	1585×365×255mm	12 pcs
VT-150148-M-N	2120215 | 4000K DAY WHITE 2120214 | 6400K WHITE	48w	5760	1585×365×255mm	12 pcs

Emergency Pack

SKU
8343

- Input Voltage: AC:220-240V,50/60Hz
- Charging Time: 24 Hours
- Emergency Power: 6-7W
- Emergency Operation time: 3 Hours
- Battery Type: Ni-Cd 9.6V 2200mAh
- Size: 212×40×30mm
- Compatible with V-TAC's LED Waterproof Fitting – M Series SS Clips Milky Cover

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED BATTEN FITTING | Transparent Cover – M Series

Promoting efficiency with its high lumen (120 lm/W) rating, this new addition to V-TAC's fixtures range. The transparent cover allows a brighter, well-distributed light that is perfect for task lighting.

- SMD LED Chip
- 20,000-hour lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- On/Off Cycles >15000
- CRI >80
- PF >0.9
- IP65
- Body Type: ABS+PC

IP65 RATING

120 lm/W

3 YEAR WARRANTY

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-60018-T	20209 | 4000K DAY WHITE 20208 | 6400K WHITE	18w	2160		12 pcs
VT-120036-T	20205 | 4000K DAY WHITE 20204 | 6400K WHITE	36w	4320		12 pcs
VT-150048-T	20201 | 4000K DAY WHITE 20200 | 6400K WHITE	48w	5760		12 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED BATTEN FITTING | Milky Cover -M Series

- SMD LED Chip
- 20,000-hour lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- On/Off Cycles >15000
- CRI >80
- PF >0.9
- IP65
- Body Type: ABS+PC

IP65 RATING

120 lm/W

3 YEAR WARRANTY



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-60018-M	20211 | 4000K DAY WHITE 20210 | 6400K WHITE	18w	2160	685×365×255mm	12 pcs
VT-60018-M-N	2120211 | 4000K DAY WHITE 2120210 | 6400K WHITE	18w	2160	685×365×255mm	12 pcs
VT-120036-M	20207 | 4000K DAY WHITE 20206 | 6400K WHITE	36w	4320	1285×365×255mm	12 pcs
VT-120036-M-N	2120207 | 4000K DAY WHITE 2120206 | 6400K WHITE	36w	4320	1285×365×255mm	12 pcs
VT-150048-M	20203 | 4000K DAY WHITE 20202 | 6400K WHITE	48w	5760	1585×365×255mm	12 pcs
VT-150048-M-N	2120203 | 4000K DAY WHITE 2120202 | 6400K WHITE	48w	5760	1585×365×255mm	12 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated



LED LINEAR LIGHTS

V-TAC LED Linear Lights are an energy-efficient, low-maintenance alternative to traditional linear fluorescent in industrial, commercial, and light assembly applications. It is the optimal solution for conventional lighting systems and excellent for new installations due to its low installation cost.

Key Features

- Saves 80% energy
- No Ultraviolet or Infrared Rays
- Flexible, Compact & Adjustable design
- No Lead or Mercury content hence environment friendly
- Provides Uniform Radiance & Enhances appeal of any environment
- Continuous row modular system

Application

Ideal for lighting applications in residential, commercial, and hospitality locations.

5 YEAR WARRANTY



V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Linear 3IN1 Lights

Discover V-TAC's reliable 40w suspended linear lights with a staggering lifespan of 30,000-hours. Designed with a toggle switch, 3IN1 color-changing light. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung.

- 30,000-hour Lifespan
- AC:200-240V,50/60Hz
- Toggle switch – 3IN1 CCT
- Aluminium Body
- 1.5 Meter Wire Length





5 YEAR WARRANTY



Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
		VT-7-44	20060 | 3IN1	40w	3200	12

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED LINEAR LIGHTS | Up & Down Linear Lights (Non-Linkable)



This modern range of suspended linear lights has up & down illumination for a more evenly distributed light that creates a subtle ambient yet sufficient lighting for any commercial lighting. Linear up & down lights are offered in two colors variants Silver and White.

- 30,000-hour Lifespan
- AC:100–240V,50Hz
- Aluminium Body
- 1–10V Dimmable
- 1.5 Meter Wire Length
- UP-110°-Down-50° Beam Angle

1–10V DIMMABLE

5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Silver	VT-7-61-S	607 | 4000K DAY WHITE	UP 30w DOWN 30w	UP-3300 DOWN-3300	8
	White	VT-7-61-W	606 | 4000K DAY WHITE	UP 30w DOWN 30w	UP-3300 DOWN-3300	8

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Up & Down Linear Hanging Lights



This modern range of suspended linear lights has up & down illumination for a more evenly distributed light that creates a subtle ambient yet sufficient lighting for any commercial lighting. Linear up & down lights are offered in two colors variants Silver and White.

- 30,000-hour Lifespan
- AC:100–240V,50/60Hz
- Aluminium Body
- Linkable with connectors
- 1–10V Dimmable
- UP-110°-Down-50° Beam Angle

1–10V DIMMABLE

5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Silver	VT-7-62-S	609 | 4000K DAY WHITE	UP 30w DOWN 30w	UP-3300 DOWN-3300	4
	White	VT-7-62-W	608 | 4000K DAY WHITE	UP 30w DOWN 30w	UP-3300 DOWN-3300	4

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED LINEAR LIGHTS | Linear Hanging Lights (Non-Dimmable)

Discover V-TAC's reliable 40w suspended linear lights with a staggering lifespan of 30,000-hours. Designed with excellent heat dissipation. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung. Linear lights are offered in three colors variants Black, Silver and White.

- 30,000-hour Lifespan
- AC:200-240V,50/60Hz
- 1.5 Meter Wire Length
- Aluminium Body
- 120° Beam Angle

LINKABLE
UP TO 12 METERS TOGETHER

5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Black	VT-7-40-B	882 | 3000K WARM WHITE 374 | 4000K DAY WHITE 600 | 6000K WHITE	40w	3200	12
	Black	VT-7-40-B-N	21882 | 3000K WARM WHITE 21374 | 4000K DAY WHITE 21600 | 6400K WHITE	40W	3270	12
	Silver	VT-7-40-S	375 | 4000K DAY WHITE 601 | 6000K WHITE	40w	3200	12
	Silver	VT-7-40-S-N	21375 | 4000K DAY WHITE	40W	3300	12
	White	VT-7-40-W	376 | 4000K DAY WHITE 602 | 6000K WHITE	40w	3200	12
	White	VT-7-40-W-N	21376 | 4000K DAY WHITE 21602 | 6400K WHITE	40W	3360	12

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Slim Up & Down Linear Lights



This modern range of suspended linear lights has up & down illumination for a more evenly distributed light that creates a subtle ambient yet sufficient lighting for any commercial lighting. Linear up & down lights are offered in three colors variants Black, Silver and White.

- 30,000-hour Lifespan
- AC:200-240V,50/60Hz
- Aluminium Body
- 120° Beam Angle
- Linkable with connectors
- 0-10V Dimmable
- 1.5 Meter Wire Length

LINKABLE
UP TO 12 METERS TOGETHER

0-10V DIMMABLE

5 YEAR WARRANTY



Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Black	VT-7-60-B	379 | 4000K DAY WHITE	UP 20w DOWN 40w	UP-2000 DOWN-4000	9
	Silver	VT-7-60-S	378 | 4000K DAY WHITE	UP 20w DOWN 40w	UP-2000 DOWN-4000	9
	White	VT-7-60-W	377 | 4000K DAY WHITE	UP 20w DOWN 40w	UP-2000 DOWN-4000	9

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED LINEAR LIGHTS | Slim Linear Hanging Lights



Discover V-TAC's reliable 40w suspended linear lights with a staggering lifespan of 30,000-hours. Designed with excellent heat dissipation. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung. Linear lights are offered in three colors variants Silver and White.

- 30,000-hour Lifespan
- UGR<19
- Linkable with connectors
- 120° Beam Angle
- Aluminium Body
- 0-10V Dimmable
- 1.5 Meter Wire Length

LINKABLE
UP TO 12 METERS TOGETHER

0-10V DIMMABLE

5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Silver	VT-7-43-S	384 | 4000K DAY WHITE	40w	3400	12
	Silver	VT-7-43-S-N	21384 | 4000K DAY WHITE	40W	3590	10
	White	VT-7-43-W	383 | 4000K DAY WHITE	40w	3400	12
	White	VT-7-43-W-N	21383 | 4000K DAY WHITE	40W	3510	10

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Slim Recessed Linear Lights

Our new range of linear lights are also available for recessed installation, complete with necessary accessories for a seamless & continuous lighting system. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung. Linear lights are offered in two colors variants Silver and White.



- 30,000-hour Lifespan
- AC:200-240V,50/60Hz
- Linkable with connectors
- Aluminium Body
- 120° Beam Angle

LINKABLE
UP TO 12 METERS TOGETHER

5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	Silver	VT-7-41-S	380 | 4000K DAY WHITE 603 | 6000K WHITE	40w	3200	9
	Silver	VT-7-41-S-N	21380 | 4000K DAY WHITE	40W	3800	9
	White	VT-7-41-W	381 | 4000K DAY WHITE 604 | 6000K WHITE	40w	3200	9
	White	VT-7-41-W-N	21381 | 4000K DAY WHITE	40W	3620	9

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED LINEAR LIGHTS | Slim Linear Connector Lights

- Smart connectors designed for V-TACs range of recessed linear lights
- Robust Aluminium body
- Fitted with high efficiency Samsung LEDss that offer up to 80% in energy savings
- Allows flexible linking with linear lights

5 YEAR WARRANTY

Product	Model	SKU	Watts	Lumen	Box Qty
	VT-7-41-L	SILVER: 386 | 4000K DAY WHITE WHITE: 385 | 4000K DAY WHITE	8w	800	8
	VT-7-41-LN	SILVER: 388 | 4000K DAY WHITE WHITE: 387 | 4000K DAY WHITE	10w	1000	8
	VT-7-41-LW	SILVER: 390 | 4000K DAY WHITE WHITE: 389 | 4000K DAY WHITE	12w	1000	8
	VT-7-41-T	SILVER: 392 | 4000K DAY WHITE WHITE: 391 | 4000K DAY WHITE	14w	1200	4
	VT-7-41-X	SILVER: 394 | 4000K DAY WHITE WHITE: 393 | 4000K DAY WHITE	16w	1600	4

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Recessed Linear Lights

Our new range of linear lights are also available for recessed installation, complete with necessary accessories for a seamless & continuous lighting system. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung.



- 30,000-hour Lifespan
- AC:200-240V,50/60Hz
- Linkable with connectors
- Aluminium Body
- 120° Beam Angle

LINKABLE
UP TO 12 METERS TOGETHER

5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	White	VT-7-42-W	382 | 4000K DAY WHITE	40w	4000	9

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED LINEAR LIGHTS | Recessed Linear Connector Lights

- Smart connectors designed for V-TACs range of recessed linear lights
- Robust Aluminium body
- Fitted with high efficiency Samsung LEDss that offer up to 80% in energy savings
- Allows flexible linking with linear lights

5 YEAR WARRANTY

Product	Model	SKU	Watts	Lumen	Box Qty
	VT-7-42-L	WHITE: 395 | 4000K DAY WHITE	10w	1000	8
	VT-7-42-LN	WHITE: 396 | 4000K DAY WHITE	10w	1000	8
	VT-7-42-LW	WHITE: 397 | 4000K DAY WHITE	12w	1000	8
	VT-7-42-T	WHITE: 398 | 4000K DAY WHITE	14w	1200	4
	VT-7-42-X	WHITE: 399 | 4000K DAY WHITE	16w	1600	4

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED LINEAR LIGHTS | Linear Surfaced Lights

Discover V-TAC's reliable 40w linear lights with a staggering lifespan of 30,000-hours. Designed with excellent heat dissipation. Perfect replacement for traditional and inefficient linear lighting fixtures with the efficient LED provided by Samsung. Linear lights are offered in three colors variants Silver and White.



- 30,000-hour Lifespan
- UGR<19
- Linkable with connectors
- 120° Beam Angle
- Aluminium Body
- 0-10V Dimmable
- 1.5 Meter Wire Length

LINKABLE
UP TO 12 METERS TOGETHER

0-10V DIMMABLE

5 YEAR WARRANTY



Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
	color	VT-7-46	20462 | 3000K WARM WHITE 20463 | 4000K DAY WHITE 20464 | 6400K WHITE	40W	3400	12

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

PRO SERIES

V-TAC®
INNOVATIVE LED LIGHTING

LED LINEAR TRUNKING LIGHT | Master Trunking

V-TAC's new Linear Trunking Light is a set of highly efficient, continuous linear light fixtures with a staggering 160 lm/w rating & a plug-and-play system. It provides an efficient, linkable modular system which means that each unit can be easily connected to the Linear Master Trunking through L, T, and X node connectors. 90°, 120°, and double asymmetric lenses are available for maximum adaptability in any space. Perfect suspended lighting for supermarkets, warehouses, service centers, and gymnasiums. No warm-up time, instant start-up. The sustained color temperature throughout long periods of usage.



5 YEAR WARRANTY

DIMMABLE LIGHT CONTROL

160 lm/W

Beam Angle	Light Distribution (IES)	Model	SKU	Watts	Lumen	Box Qty
WIDE 90°		VT-4551D	1360 | 4000K DAY WHITE	50w	8000	2
FLAT 120°		VT-4551D-120	1361 | 4000K DAY WHITE	50w	8000	2
DOUBLE ASYMMETRIC		VT-4551D-DL	1362 | 4000K DAY WHITE	50w	8000	2

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

PRO SERIES

LED LINEAR TRUNKING LIGHT | Follow Trunking

V-TAC's new Linear Trunking Light is a set of highly efficient, continuous linear light fixtures with a staggering 160 lm/w rating & a plug-and-play system. It provides an efficient, linkable modular system which means that each unit can be easily connected to the Linear Master Trunking through L, T, and X node connectors. 90°, 120°, and double asymmetric lenses are available for maximum adaptability in any space. Perfect suspended lighting for supermarkets, warehouses, service centers, and gymnasiums. No warm-up time, instant start-up. The sustained color temperature throughout long periods of usage.



5 YEAR WARRANTY

DIMMABLE LIGHT CONTROL

160 lm/W

Beam Angle	Light Distribution (IES)	Model	SKU	Watts	Lumen	Box Qty
WIDE 90°		VT-4550D	1363 | 4000K DAY WHITE	50w	8000	2
FLAT 120°		VT-4550D-120	1364 | 4000K DAY WHITE	50w	8000	2
DOUBLE ASYMMETRIC		VT-4550D-DL	1365 | 4000K DAY WHITE	50w	8000	2

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

PRO SERIES

V-TAC® INNOVATIVE LED LIGHTING

Linear Track Module

SKU	Box Qty
1382	5

End Cap

SKU	Box Qty
1366	200

Suspended Cord

SKU	Box Qty
1367	100

8 Wire-Feed In Male Connector

SKU	Box Qty
1368	200

L Node Connector

SKU	Box Qty
1383	8

T Node Connector

SKU	Box Qty
1384	2

X Node Connector

SKU	Box Qty
1385	2

S Line-Follow Trunking Rail

SKU	Box Qty
1451	10

S Line-PC Blank Cover

SKU	Box Qty
1452	35

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated

LED TRACKLIGHTS

Color has a massive influence on purchasing decisions and setting the mood in any room. Our innovative LED track lights are the premier choice for retail lighting with Samsung's state-of-the-art COB technology.

The >90 CRI rating of these track lights provides vivid colors, highly enhancing any product's appeal to consumers. Single and 4-linear track lights are included in this new generation of track lights from V-TAC.

Key Features

- Saves 80% energy
- No Ultraviolet or Infrared Rays
- Totally flexible, Compact & Adjustable design
- No Lead or Mercury content hence environment friendly
- Provides Uniform Radiance & Enhances appeal of any environment.
- Enhances measurable levels of performance as compared to older versions of high wattage halogen & HID light sources in retail & Commercial Lighting applications.

Application

Ideal for lighting applications in residential, commercial, and hospitality locations.

5 YEAR WARRANTY

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED TRACKLIGHTS | Linear Tracklights-Black Body

REAL COLOR SERIES CRI >90

Experience true colours through our LED Linear Tracklights efficient set of track lights with CRI >90, UGR<19 and flicker free. The latest LED technology from Samsung, and five years of warranty.

- 30,000-hour Lifespan
- 30° Beam Angle
- AC:220-240V,50Hz
- Flicker Free
- High CRI of > 90
- Aluminium Body
- UGR<19

FLICKER FREE UGR<19 5 YEAR WARRANTY



Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
		VT-416-B	20000 | 2700K WARM WHITE 20001 | 4000K DAY WHITE	12W	960	40
		VT-431-B	20006 | 2700K WARM WHITE 20007 | 4000K DAY WHITE	25W	2000	20

*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED TRACKLIGHTS | Linear Tracklights-White Body

Experience true colours through our LED Linear Tracklights efficient set of track lights with CRI >90, UGR<19 and flicker free. The latest LED technology from Samsung, and five years of warranty.

REAL COLOR SERIES CRI >90

- 30,000-hour Lifespan
- 30° Beam Angle
- AC:220-240V,50Hz
- Flicker Free
- High CRI of > 90
- Aluminium Body
- UGR<19

FLICKER FREE UGR<19 5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
		VT-416-W	20003 | 2700K WARM WHITE 20004 | 4000K DAY WHITE	12W	960	40
		VT-431-W	20009 | 2700K WARM WHITE 20010 | 4000K DAY WHITE	25W	2000	20

*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED TRACKLIGHTS | 4 Line Tracklights-Black Body

REAL COLOR SERIES CRI >90

A complete range of durable 7w to 20w 4-line LED track lights with Aluminium body equipped with LED Chip by Samsung. These COB LEDs are also renowned for its high-CRI rating, perfect for retail lighting. Available in a stylish, ebony black finish.

- COB LED Type
- 30,000-hour Lifespan
- 24° Beam Angle
- AC:220-240V,50Hz
- PF: >0.9
- High CRI of > 90
- Aluminium Body

5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
		VT-407-B	353 | 3000K WARM WHITE 354 | 4000K DAY WHITE 355 | 5000K WHITE	7w	420	40
		VT-415-B	359 | 3000K WARM WHITE 360 | 4000K DAY WHITE 361 | 5000K WHITE	15w	1050	40
		VT-420-B	365 | 3000K WARM WHITE 366 | 4000K DAY WHITE 367 | 5000K WHITE	20w	1400	40

*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED TRACKLIGHTS | 4 Line Tracklights-White Body

REAL COLOR SERIES CRI >90

A complete range of durable 7w to 20w 4-line LED track lights with Aluminium body equipped with LED Chip by Samsung. These COB LEDs are also renowned for its high-CRI rating, perfect for retail lighting. Available in a stylish, clean white finish.

- COB LED Type
- 30,000-hour Lifespan
- 24° Beam Angle
- AC:220-240V,50Hz
- PF: >0.9
- High CRI of > 90
- Aluminium Body

5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
		VT-407-W	350 | 3000K WARM WHITE 351 | 4000K DAY WHITE 352 | 5000K WHITE	7w	490	40
		VT-415-W	356 | 3000K WARM WHITE 357 | 4000K DAY WHITE 358 | 5000K WHITE	15w	1200	40
		VT-420-W	362 | 3000K WARM WHITE 363 | 4000K DAY WHITE 364 | 5000K WHITE	20w	1600	40

*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED TRACKLIGHTS | 4 Line Tracklights

REAL COLOR SERIES CRI >90

Experience true colours through our LED Tracklights efficient set of track lights with CRI >90, the latest LED technology from Samsung, and five years of warranty.

- COB LED Type
- 30,000-hour Lifespan
- 24° Beam Angle
- AC:220-240V,50Hz
- PF: >0.9
- High CRI of > 90
- Aluminium Body

5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
		VT-418	939 | 3000K WARM WHITE 940 | 4000K DAY WHITE	18w	1260	20
		VT-430	941 | 3000K WARM WHITE 942 | 4000K DAY WHITE	30w	2100	20

*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED TRACKLIGHTS | 4 Line Shutter Tracklights

REAL COLOR SERIES CRI >90

These durable 4-line LED track lights are equipped with shutters for flexibility — easily adjust them to achieve desired beam angle. These COB LEDs are also renowned for its high-CRI rating, perfect for retail lighting. Available in white and black body.

- COB LED Type
- 30,000-hour Lifespan
- 24°-60° Adjustable
- AC:220-240V,50Hz
- PF: >0.9
- High CRI of > 90
- Aluminium Body

5 YEAR WARRANTY

Product	Unit Color	Model	SKU	Watts	Lumen	Box Qty
		VT-433-B	371 | 3000K WARM WHITE 372 | 4000K DAY WHITE 373 | 5000K WHITE	33w	2640	8
		VT-433-W	368 | 3000K WARM WHITE 369 | 4000K DAY WHITE 370 | 5000K WHITE	33w	2640	8

*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

V-TAC®
INNOVATIVE LED LIGHTING

MAGNETIC
TRACK LIGHTS

LED MAGNETIC TRACKLIGHTS

Magnetic light is a kind of track light that is designed by using magnets' fast adsorption characteristic. It consists of two parts: track magnet and light. The track has four ways: surface mounted, recessed, borderless embedded installation, suspension. The light has anti-glare line light, anti-glare high power light, soft light lamp, suspension light, and decorative lamp. The light can be used alone or assembled at will. Lighting effect can achieve point, line, the surface combination can meet the needs of various lighting effects. Its convenient installation, fashionable style, and can greatly enhance the decorative effect, in line with the modern architectural design concept, is a fashionable, high-end LED lights leading the trend in the future, is the ideal choice of office, exhibition hall, exclusive stores, hotels, villas, and clubs.

*Suitable for 10–12 hours daily, usage of the product for 24 hours a day would void warranty

MAGNETIC
TRACK LIGHTS

V-TAC®
INNOVATIVE LED LIGHTING

MAGNETIC LINEAR SPOTLIGHT

- SMD LED Type
- DC:24V
- CRI: >90
- 30° Beam Angle
- 30,000-hour Lifespan
- Aluminium Body

3 YEAR WARRANTY

UGR<19

REAL COLOR SERIES CRI >90

Model	SKU	Watts	Lumen	Box Qty
VT-4141	7958 | 3000K WARM WHITE 7959 | 4000K DAY WHITE	1w	35	40



MAGNETIC LINEAR SPOTLIGHT

- SMD LED Type
- DC:24V
- CRI: >90
- 30° Beam Angle
- 30,000-hour Lifespan
- Aluminium Body

3 YEAR WARRANTY

UGR<19

REAL COLOR SERIES CRI >90



Model	SKU	Watts	Lumen	Box Qty
VT-4143	7960 | 3000K WARM WHITE 7961 | 4000K DAY WHITE	3w	240	36



*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

V-TAC®
INNOVATIVE LED LIGHTING

MAGNETIC TRACK LIGHTS

MAGNETIC LINEAR LIGHT

- SMD LED Type
- DC:24V
- CRI: >90
- 30° Beam Angle
- 30,000-hour Lifespan
- Aluminium Body

3 YEAR WARRANTY

UGR<19

REAL COLOR SERIES CRI >90

Model	SKU	Watts	Lumen	Box Qty
VT-4210	7962 | 3000K WARM WHITE 7963 | 4000K DAY WHITE	10w	700	16



MAGNETIC LINEAR LIGHT

- SMD LED Type
- DC:24V
- CRI: >90
- 30° Beam Angle
- 30,000-hour Lifespan
- Aluminium Body

3 YEAR WARRANTY

UGR<19

REAL COLOR SERIES CRI >90

Model	SKU	Watts	Lumen	Box Qty
VT-4220	7964 | 3000K WARM WHITE 7965 | 4000K DAY WHITE	20w	1200	8



*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

MAGNETIC
TRACK LIGHTS

V-TAC®
INNOVATIVE LED LIGHTING

MAGNETIC SPOTLIGHT

- COB LED Type
- DC:24V
- CRI: >90
- 36° Beam Angle
- 30,000-hour Lifespan
- Aluminium Body

3 YEAR WARRANTY

UGR<19

REAL COLOR SERIES CRI >90

Model	SKU	Watts	Lumen	Box Qty
VT-4215	7966 | 3000K WARM WHITE 7967 | 4000K DAY WHITE	15w	900	16



MAGNETIC PENDANT LIGHT

- COB LED Type
- DC:24V
- CRI: >90
- 36° Beam Angle
- 30,000-hour Lifespan
- Aluminium Body

3 YEAR WARRANTY

UGR<19

REAL COLOR SERIES CRI >90

Model	SKU	Watts	Lumen	Box Qty
VT-4315	7968 | 3000K WARM WHITE 7969 | 4000K DAY WHITE	15w	1000	12



*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

V-TAC® INNOVATIVE LED LIGHTING

MAGNETIC TRACK LIGHTS

MAGNETIC LINEAR LIGHT

- SMD LED Type
- DC:24V
- CRI: >90
- 100° Beam Angle
- 30,000-hour Lifespan
- Aluminium Body

3 YEAR WARRANTY

REAL COLOR SERIES CRI >90

Model	SKU	Watts	Lumen	Box Qty
VT-4121	7954 | 3000K WARM WHITE 7955 | 4000K DAY WHITE	20w	1600	12



MAGNETIC LINEAR LIGHT

- SMD LED Type
- DC:24V
- CRI: >90
- 100° Beam Angle
- 30,000-hour Lifespan
- Aluminium Body

3 YEAR WARRANTY

REAL COLOR SERIES CRI >90

Model	SKU	Watts	Lumen	Box Qty
VT-4131	7956 | 3000K WARM WHITE 7957 | 4000K DAY WHITE	30w	2700	12



*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

MAGNETIC TRACK LIGHTS

V-TAC® INNOVATIVE LED LIGHTING

Track Rail-0.5M

SKU	Box Qty
7950	9

Track Rail-1M

SKU	Box Qty
7951	9

Track Rail-1.5M

SKU	Box Qty
7953	6

Track Rail-2M

SKU	Box Qty
7952	6

Recessed Kit for Magnetic Tracklight

SKU	Box Qty
7970	75

Track Connector

SKU	Box Qty
7971	180

90'D Corner Connector

SKU	Box Qty
7972	27

Outer Corner Connector

SKU	Box Qty
7973	27

Cross Connector

SKU	Box Qty
7974	36

T Type Connector

SKU	Box Qty
7975	36

Pendant Track Rail Accessory

SKU	Box Qty
7977	150

Track Cover

SKU	Box Qty
7978	200

Live End Connector

SKU	Box Qty
7979	200

Transformer

SKU	Box Qty
11144	30

Transformer

SKU	Box Qty
11145	30

*Suitable for 10-12 hours daily, usage of the product for 24 hours a day would void warranty

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated

LED DOME & DOWN LIGHTS

V-TAC's LED Bulkhead range is inclusive of IP65-rated 2D bulkheads made of state-of-the-art polycarbonate resins for a premium water and dustproof surface-mounted luminaire.
Each model has powerful combinations of two useful features: the emergency battery backup and the microwave sensor with 120'D detection angle. Together with the new elegant designs, this luminaire's highlight is its competitive outdoor effectiveness in efficiency and security.

Key Features

- Built-in power eliminates the need for an external power supply
- IP65 and strong PC covers for durability
- 3-hour Emergency Operation Time
- Microwave sensors: up to 10m detection
- upto 30,000hr lifespan
- Fully compatible with daylight sensors
- Equipped with a green LED charging indicator

Application

Suitable for open areas constantly exposed to dust and moisture like parking lots, corridors, airports, and malls.

5 YEAR WARRANTY

IP65 RATING



V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED DOME LIGHTS | CCT Bulkhead

Our resilient IP65 CCT Bulkhead make a good choice for outdoor residential, business, and industrial areas that need constant lighting since they can withstand weather and dust.

POLYCARBONATE PC

5 YEAR WARRANTY

IP65 RATING

- SMD LED Chip
- AC:200-240V,50/60Hz
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body
- CRI >80
- PF >0.5
- IP65 Rating

ON 1 2

EASY TOGGLE SWITCH FOR COLOR CHANGING
3000K - 4000K - 6400K

IK08 RATING

Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
	VT-14	20088 | 3IN1	14w	1400		10 pcs
	VT-14-CH	20092 | 3IN1	14w	1400		10 pcs
	VT-24	20093 | 3IN1	20w	1850		10 pcs
	VT-24-CH	20097 | 3IN1	20w	1850		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | CCT Bulkhead with Emergency Battery

These IP65 LED bulkheads are equipped with Ni-Cad batteries that automatically charges while in use. These fixtures can operate up to three (3) hrs on emergency situations.

- Battery Charging Current:60mA
- Battery Discharging Current:200mA
- Battery Type:Ni-CD, 9.6V 1.0Ah
- Emergency Operation Time:>3 Hours
- Emergency Standby Watts:>1.5W
- Charging Indication:Green LED
- Including Test Button, Battery Protection circuit & Inhibiting Mode
- AC:200-240V,50/60Hz
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body
- IP65 Rating

3 YEAR WARRANTY

IP65 RATING

Emergency Battery Backup

IK08 RATING

EASY TOGGLE SWITCH FOR COLOR CHANGING
3000K - 4000K - 6400K

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Color	Box Qty
VT-14SE	20090 | 3IN1	14w	1400		White	10 pcs
VT-24SE	20095 | 3IN1	20w	1850		White	10 pcs

Changeable Eyelid Half Cover For 14W

SKU
11225

Changeable Chrome Rim For 14W

SKU
11230

Changeable Chrome Rim For 20W

SKU
11231

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOME LIGHTS | CCT Bulkhead with Sensor

This range of CCT Bulkhead are recommended for purposes of increasing security in garages, walkways, and parking areas. With competitive detection range and dimmable functions, these Dome Lights exhibit exceptional performance in outdoor security lighting.

- Detection Angle:Ceiling/Wall Mounted-360°/120°
- Detection Distance:3-6M, 6-10M Optional
- Detection Range:Max D10M*6M
- Hold Time:5s,90s,5min,10min customized
- Daylight Sensor:Day,2lux,10lux,50lux optional
- Dimmable Function:Yes,0%,10%,20%,30% optional
- Standby period:0s,10s,10min optional
- Manual Override:Available by dial switch
- Detection Motion Speed:0.5-3m/s
- AC:200-240V,50/60Hz
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body
- IP65 Rating

Microwave Sensor

IP65 RATING

5 YEAR WARRANTY

IK08 RATING

EASY TOGGLE SWITCH FOR COLOR CHANGING
3000K - 4000K - 6400K

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Color	Box Qty
VT-14SS	20089 | 3IN1	14w	1400		White	10 pcs
VT-24SS	20094 | 3IN1	20w	1850		White	10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | CCT Bulkhead with Emergency Battery+Sensor

Our 3-in-1 CCT Bulkhead range is equipped with the complete package for a remarkable and reliable indoor/ outdoor emergency and security lighting. With reliable Ni-Cd emergency battery back up, advanced microwave sensor, and optional dimmable functions, this range has impressive lighting abilities to make outdoor locations of residential, business, and industrial areas safer and easier to navigate.

- Emergency Operation Time:>3 Hours
- Emergency Standby Watts:>1.5W
- Battery Charging Current:60mA
- Battery Discharging Current:200mA
- Battery Type:Ni-CD, 9.6V 1.0Ah
- Charging Indication:Green LED
- Including,Test Button, Battery Protection circuit & Inhibiting Mode
- Detection Angle:Ceiling/Wall Mounted-360°/120°
- Detection Distance:3-6M, 6-10M Optional
- IP65 Rating
- Detection Range:Max D10M*6M
- Hold Time:5s,90s,5min,10min customized
- Daylight Sensor:Day,2lux,10lux,50lux optional
- Dimmable Function:Yes,0%,10%,20%,30% optional
- Stand-by period:0s,10s,10min optional
- Manual Override:Available by dial switch
- Detection Motion Speed:0.5-3m/s
- AC:200-240V,50/60Hz
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body

3in1 Bulkhead | Emergency Battery Backup | Microwave Sensor

IP65 RATING

3 YEAR WARRANTY

IK08 RATING

ON 1 2 EASY TOGGLE SWITCH FOR COLOR CHANGING 3000K - 4000K - 6400K

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Color	Box Qty
VT-14SES	20091 | 3IN1	14w	1400		White	10 pcs
VT-24SES	20096 | 3IN1	20w	1850		White	10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED DOME LIGHTS | 2D Bulkhead

Our resilient IP65 LED bulkheads make a good choice for outdoor residential, business, and industrial areas that need constant lighting since they can withstand weather, dust, and vandalism.

- SMD LED Chip
- AC:200-240V,50/60Hz
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body
- CRI >80
- PF >0.5
- IP65 Rating

POLYCARBONATE PC

IP65 RATING

5 YEAR WARRANTY

IK08 RATING

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-08	815 | 4000K DAY WHITE	8w	720		10 pcs
VT-15	801 | 4000K DAY WHITE 802 | 6400K WHITE	15w	1400		10 pcs

Chrome Bezel For 15W-17W

SKU
11241

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | 2D Bulkhead with Emergency Battery

These IP65 LED bulkheads are equipped with Ni-Cad batteries that automatically charges while in use. These fixtures can operate up to three (3) hrs on emergency situations.

3 YEAR WARRANTY

- AC:200-240V,50/60Hz
- >1.2 Watts Emergency Standby Watts
- 60mA Battery Charging Current
- 200mA Battery Discharging Current
- Ni-CD AA, 7.2V 1.0Ah Battery Type
- Including battery protection circuit & inhibiting mode
- Green LED Charging indicate
- >3 hrs Emergency Operation time
- 30,000-hour lifespan
- SMD LED Type
- PC Body
- IP65 Rating

IP65 RATING

IK08 RATING

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-11	816 | 4000K DAY WHITE	10w	720		10 pcs
VT-17	806 | 4000K DAY WHITE	17w	1400		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOME LIGHTS | 2D Bulkhead with Sensor

5 YEAR WARRANTY

IP65 RATING

IK08 RATING

POLYCARBONATE PC

This range of LED bulkheads are recommended for purposes of increasing security in garages, walkways, and parking areas. With competitive detection range and dimmable functions, these bulkheads exhibit exceptional performance in outdoor security lighting.

- AC:200-240V,50/60Hz
- 120° / 360° Detection Angle
- 3m, 5m, 8m, 10m (optional) Detection Distance
- Max D10Mx4M Detection Range
- 10S, 1min, 5min, 10min customized Hold Time
- Day, 10Lux, 30Lux, 50Lux optional Day light Sensor
- Yes, 0, 10%, 20%, 30% optional Dimmable Function
- 0.5~3m/s Detection Motion Speed
- >3 hrs Emergency Operation time
- 30,000-hour lifespan
- SMD LED Type
- PC Body
- IP65 Rating

Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
	VT-09	818 | 4000K DAY WHITE	8w	720		10 pcs
	VT-16	803 | 3000K WARM WHITE 804 | 4000K DAY WHITE 805 | 6400K WHITE	15w	1400		10 pcs
	VT-22	819 | 4000K DAY WHITE	15w	1450		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | 2D Bulkhead with Emergency Battery+Sensor

Our 3-in-1 LED bulkhead range is equipped with the complete package for a remarkable and reliable indoor/ outdoor emergency and security lighting. With reliable Ni-Cad emergency battery back up, advanced microwave sensor, and optional dimmable functions, this range has impressive lighting abilities to make outdoor locations of residential, business, and industrial areas safer and easier to navigate.

3 YEAR WARRANTY

IP65 RATING

IK08 RATING

POLYCARBONATE PC

- AC:200-240V,50/60Hz
- >1.2 Watts Emergency Standby Watts
- 60mA Battery Charging Current
- 200mA Battery Discharging Current
- Ni-CD AA, 7.2V 1.0Ah Battery Type
- Green LED Charging indicate
- Including battery protection circuit & inhibiting mode
- 120° / 360° Detection Angle
- Yes, 0, 10%, 20%, 30% optional Dimmable Function
- 3m, 5m, 8m, 10m (optional) Detection Distance
- 0.5~3m/s Detection Motion Speed
- >3 hrs Emergency Operation time
- 30,000-hour lifespan
- SMD LED Type
- PC Body
- IP65 Rating

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12	817 | 4000K DAY WHITE	10w	720		10 pcs
VT-19	812 | 4000K DAY WHITE	17w	1400		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOME LIGHTS | Slim Dome Light

A new addition to our Dome Light Lights series, V-TAC's new Slim IP65 LED Dome Lights are re-designed with a sleeker, more compact built for a modern look – perfect lighting for outdoor areas in residential, business, and industrial zones.

- AC:220-240V,50/60Hz
- 110° Beam Angle
- 30,000-hour lifespan
- IP65 Rating
- PC Body
- CRI >80
- PF >0.5

IP65 RATING

5 YEAR WARRANTY

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12S	935 | 3000K WARM WHITE 820 | 4000K DAY WHITE 936 | 6400K DAY WHITE	12w	1440		10 pcs
VT-12S-N	21820 | 4000K DAY WHITE	12w	1480		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | Slim Dome Light with Emergency Backup

- AC:220-240V,50/60Hz
- 110° Beam Angle
- SMD LED chip type
- PC Body
- 30,000-hour lifespan
- CRI >80
- Battery type -Ni-Cd 9.6V,1.0Ah
- Battery Charging Current – 60mA
- Battery Discharge Current – 200mA
- > 3 Hours emergency operation time
- IP65 Rating

3 YEAR WARRANTY

IP65 RATING

Emergency Battery Backup

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12SE	822 | 4000K DAY WHITE	14w	1440		10 pcs

LED DOME LIGHTS | Slim Dome Light with Sensor

- 360°Ceiling/120°Wall Mounted
- Detection Motion Speed – 0.5-3m/s
- Hold Time – 30s, 40s, 50s customized
- Daylight sensor -Day, 2lux, 10lux, 50lux optional
- Dimmable – Yes, 0, 10%,20% optional
- Manual Override by dial switch
- Stand by period – 0s, 10s, 10m optional
- AC:220-240V,50/60Hz
- 110° Beam Angle
- 30,000-hour lifespan
- CRI >80
- Microwave Sensor
- 3-6m detection distance
- 10mx6m detection range

5 YEAR WARRANTY

IP54 RATING

Microwave Sensor

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12SS	937 | 3000K WARM WHITE 821 | 4000K DAY WHITE 938 | 6400K DAY WHITE	12w	1440		10 pcs

LED DOME LIGHTS | Slim Dome Light with Emergency+Sensor

- 3-6m detection distance
- 10mx6m detection range
- 360°Ceiling/120°Wall Mounted
- 0.5-3m/s detection motion speed
- 30s, 40s, 50s customized (time delay)
- Daylight sensor -Day: 7-20LUX
- Dimmable – Yes, 0, 10%,20% optional
- Manual Override
- Standby – 0s, 10s, 10m optional
- > 3 Hours emergency operation time
- Battery type -Ni-Cd 9.6V,1.0Ah
- Battery Charging Current – 60mA
- Battery Discharge Current – 200mA
- AC:220-240V,50/60Hz
- 110° Beam Angle
- 30,000-hour lifespan

3 YEAR WARRANTY

IP54 RATING

3in1 Bulkhead | Emergency Battery Backup | Microwave Sensor

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-12SES	823 | 4000K DAY WHITE	14w	1440		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED DOME LIGHTS | Bulkhead CCT Changeable

Our resilient IP65 LED bulkheads make a good choice for outdoor residential, business, and industrial areas that need constant lighting since they can withstand weather, dust. This new model has an easy switch for colour temperature tuning to achieve any lighting mood in any room. No need to worry about which colour temperature for any room when you can have it all – readily available with just a flick of a switch.

5 YEAR WARRANTY

IP65 RATING

- AC:200-240V,50/60Hz
- CRI >80
- 30,000-hour lifespan
- 120° Beam Angle
- PC Body
- Built in Switch for CCT Changing

EASY TOGGLE SWITCH

3000K 4000K 6400K

EASY ACCESS FOR COLOR CHANGING WITH BUTTON

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-2-17	20016 | 3 IN 1	15w	1400		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS | Dome Light – Sensor

- Input: AC:110–240V, 50/60Hz
- 120° Beam Angle
- 20,000-hour lifespan
- SMD LED Chip
- CRI >80
- 3 year warranty
- Detection Distance – 6m Max
- Detection Range – 360°
- Time Delay – Min-10sec±3sex, Max-3min±30sec
- Detection motion Speed – 0.6–1.5m/s
- Ambient Light – <3–2000lux(adjustable)
- Instant start
- IP20 Rating

MOTION PIR SENSOR

POLYCARBONATE PC

IK08 RATING

3 YEAR WARRANTY

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-13	807 | 3000K WARM WHITE 808 | 4000K DAY WHITE 809 | 6400K WHITE	12w	800		10 pcs
VT-13-N	21808 | 4000K DAY WHITE 21809 | 6400K WHITE	12w	800		10 pcs

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED DOME LIGHT | Ceiling Lights

- AC:220-240V,50/60Hz
- IP Rating:IP44
- CRI:>80
- Warranty:3 Years
- 110° Beam Angle
- Body Type: PC

IK08 RATING

3 YEAR WARRANTY

POLYCARBONATE PC

V-TAC® GENERATION

Model	Shape	SKU	Watts	Lumen	Dimension	Box Qty
VT-8033RD	Round	13889 | 3000K WARM WHITE 55669 | 4000K DAY WHITE 13899 | 6500K WHITE	15w	1500	47.5mm, Ø 200 mm	20 pcs
VT-8033RD-N	Round	2113889 | 3000K WARM WHITE 2155669 | 4000K DAY WHITE 2113899 | 6500K WHITE	15w	1850	47.5mm, Ø 200 mm	20 pcs
VT-8066RD	Round	13929 | 3000K WARM WHITE 13939 | 4000K DAY WHITE 13949 | 6500K WHITE	25w	2500	50 mm, Ø300 mm	10 pcs
VT-8066RD-N	Round	2113949 | 6500K WHITE	25w	2850	50 mm, Ø300 mm	10 pcs
VT-8033SQ	Square	13909 | 3000K WARM WHITE 55679 | 4000K DAY WHITE 13919 | 6500K WHITE	15w	1500	47.5 mm, 200 mm	20 pcs
VT-8033SQ-N	Square	2113909 | 3000K WARM WHITE	15w	1700	47.5 mm, 200 mm	20 pcs
VT-8066SQ	Square	13959 | 3000K WARM WHITE 13969 | 4000K DAY WHITE 13979 | 6500K WHITE	25w	2500	50 mm, 300 mm	10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOWNLIGHT | Reflector Downlight

Our new reflector downlights feature a quick connector for easy wiring and installation. The beam angle direction can be also be easily adjusted by tilting the downlight itself.

- Adjustable Angle
- AC:85-265V,50/60Hz
- Body type Aluminium
- 120° Beam Angle
- LED (COB chip) provided by Samsung
- CRI >80

5 YEAR WARRANTY

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-2-10	839 | 3000K WARM WHITE 840 | 4000K DAY WHITE 841 | 6400K WHITE	10w	900		40 pcs
VT-2-20	842 | 3000K WARM WHITE 843 | 4000K DAY WHITE 844 | 6400K WHITE	20w	1600		20 pcs
VT-2-30	845 | 3000K WARM WHITE 846 | 4000K DAY WHITE 832 | 6400K WHITE	30w	2400		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOWNLIGHT | Reflector Downlights

Introducing V-TAC's LED reflector downlights — available in 12° & 38° beam angles & CRI rating of >90, to achieve any residential, retail, or hospitality lighting need.

- 30,000-hour lifespan
- Input Voltage – AC:220–240V,50Hz
- Body Material – Aluminium
- Includes Quick Connector for easy wiring



12° NARROW BA | 38° WIDE BA

5 YEAR WARRANTY

FLICKER FREE

UGR<19

REAL COLOR SERIES CRI >90

Model	Beam Angle	SKU	Watts	Lumen	Box Qty
VT-2-04	12°	972 | 2700K WARM WHITE 971 | 4000K DAY WHITE 970 | 5700K WHITE	4w	320	100 pcs
VT-2-04-1	38°	987 | 2700K WARM WHITE 986 | 4000K DAY WHITE 985 | 5700K WHITE	4w	320	100 pcs



*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

Model	Beam Angle	SKU	Watts	Lumen	Box Qty
VT-2-12	12°	975 | 2700K WARM WHITE 974 | 4000K DAY WHITE 973 | 5700K WHITE	12w	960	50 pcs
VT-2-12-1	38°	990 | 2700K WARM WHITE 989 | 4000K DAY WHITE 988 | 5700K WHITE	12w	960	50 pcs



Model	Beam Angle	SKU	Watts	Lumen	Box Qty
VT-2-16	12°	978 | 2700K WARM WHITE 977 | 4000K DAY WHITE 976 | 5700K WHITE	16w	1280	50 pcs
VT-2-16-1	38°	993 | 2700K WARM WHITE 992 | 4000K DAY WHITE 991 | 5700K WHITE	16w	1280	50 pcs



Model	Beam Angle	SKU	Watts	Lumen	Box Qty
VT-2-21	12°	981 | 2700K WARM WHITE 980 | 4000K DAY WHITE 979 | 5700K WHITE	20w	1600	20 pcs
VT-2-21-1	38°	996 | 2700K WARM WHITE 995 | 4000K DAY WHITE 994 | 5700K WHITE	20w	1600	20 pcs



Model	Beam Angle	SKU	Watts	Lumen	Box Qty
VT-2-36	12°	984 | 2700K WARM WHITE 983 | 4000K DAY WHITE 982 | 5700K WHITE	36w	2880	20 pcs
VT-2-36-1	38°	999 | 2700K WARM WHITE 998 | 4000K DAY WHITE 997 | 5700K WHITE	36w	2880	20 pcs



*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOWNLIGHT | Reflector Downlight – Black Housing

Introducing V-TAC's LED reflector downlights with black housing— available in 10w, 20w & 30w & CRI rating of >80, to achieve any residential, retail, or hospitality lighting need.

- AC:85-265V,50/60Hz
- CRI >80
- 30,000-hour lifespan
- 120° Beam Angle
- 85% Energy Saving
- Aluminium Material
- 120° Beam Angle
- Aluminium Material
- 85% Energy Saving

5 YEAR WARRANTY

Model	Shape	SKU	Watts	Lumen	Dimension	Box Qty
VT-2-13	Round	20051 | 3000K WARM WHITE 20052 | 4000K DAY WHITE 20053 | 6400K WHITE	10w	800		40 pcs
VT-2-13-N	Round	2120051 | 3000K WARM WHITE 2120052 | 4000K DAY WHITE	10w	1200		40 pcs
VT-2-23	Round	20054 | 3000K WARM WHITE 20055 | 4000K DAY WHITE 20056 | 6400K WHITE	20w	1600		20 pcs
VT-2-23-N	Round	2120054 | 3000K WARM WHITE 2120055 | 4000K DAY WHITE 2120056 | 6400K WHITE	20w	2000		20 pcs
VT-2-33	Round	20057 | 3000K WARM WHITE 20058 | 4000K DAY WHITE 20059 | 6400K WHITE	30w	2400		10 pcs
VT-2-33-N	Round	2120058 | 4000K DAY WHITE	30w	3250		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOWNLIGHT | Adjustable Downlight

Our new reflector downlights feature adjustable beam angle direction. CRI rating of >90, to achieve any residential, retail, or hospitality lighting need.

- Adjustable Angle
- AC:220-240V,50/60Hz
- 24° Beam Angle
- IP20
- 30,000-hour lifespan
- IP20
- CRI>90
- 30,000-hour lifespan

5 YEAR WARRANTY

REAL COLOR SERIES CRI >90

Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
	VT-419	20049 | 4000K DAY WHITE	18w	1450		20 pcs
	VT-436	20050 | 4000K DAY WHITE	2×18w	2900		10 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED DOWNLIGHTS | Fire Rated Downlight

Our new Fire-Rated Spotlight Fittings are available in Chrome, Nickel, and White finish. With 3000K, 4000K and 6400K options, built with Aluminium alloy and iron. Efficient replacement for traditional downlight fittings.

- CRI >80
- 30,000-hour lifespan
- 70° Beam Angle
- Iron+Aluminium Alloy
- Integrated COB LED (Non-replaceable).
- Isolate driver with terminal for easy and speedy installation
- Designed to retain 30,60,90 minutes of fire integrity of ceiling and subsequent load bearing floors.

5 YEAR WARRANTY | QUICK CONNECTOR | IP65 RATING | DIMMABLE LIGHT CONTROL | 30-60-90 MIN Fire Rated

Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
Chrome	VT-885-C	8175 | 3000K WARM WHITE 8176 | 4000K DAY WHITE 8180 | 6400K WHITE	5w	500	Ø81.5mm Cutting Size Ø57mm	60 pcs
Nickel	VT-885-N	8173 | 3000K WARM WHITE 8174 | 4000K DAY WHITE 8179 | 6400K WHITE	5w	500	Ø81.5mm Cutting Size Ø57mm	60 pcs
White	VT-885-W	8177 | 3000K WARM WHITE 8178 | 4000K DAY WHITE 8181 | 6400K WHITE	5w	500	Ø81.5mm Cutting Size Ø57mm	60 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOWNLIGHTS | Fire Rated Downlight-3PC Pack

Our new 3PC Pack Fire-Rated Spotlight Fittings are available in Chrome, Nickel, and White finish. With 3000K, 4000K and 6400K options, built with Aluminium alloy and iron. Efficient replacement for traditional downlight fittings.

- CRI >80
- 30,000-hour lifespan
- 70° Beam Angle
- Iron+Aluminium Alloy
- Integrated COB LED (Non-replaceable).
- Isolate driver with terminal for easy and speedy installation
- Designed to retain 30,60,90 minutes of fire integrity of ceiling and subsequent load bearing floors.

5 YEAR WARRANTY | QUICK CONNECTOR | IP65 RATING | DIMMABLE LIGHT CONTROL | 30-60-90 MIN Fire Rated

Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
Chrome	VT-885-C	8874 | 3000K WARM WHITE 8875 | 4000K DAY WHITE 8876 | 6400K WHITE	5w	500	Ø81.5mm Cutting Size Ø57mm	20 pcs
Nickel	VT-885-N	8197 | 3000K WARM WHITE 8198 | 4000K DAY WHITE 8199 | 6400K WHITE	5w	500	Ø81.5mm Cutting Size Ø57mm	20 pcs
White	VT-885-W	8182 | 3000K WARM WHITE 8183 | 4000K DAY WHITE 8184 | 6400K WHITE	5w	500	Ø81.5mm Cutting Size Ø57mm	20 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED DOWNLIGHTS | Fire Rated Downlight-10PC Pack

Our new 10PC Pack Fire-Rated Spotlight Fittings are available in Chrome, Nickel, and White finish. With 3000K, 4000K and 6400K options, built with Aluminium alloy and iron. Efficient replacement for traditional downlight fittings.

- CRI >80
- 30,000-hour lifespan
- 70° Beam Angle
- Iron+Aluminium Alloy
- Integrated COB LED (Non-replaceable).
- Isolate driver with terminal for easy and speedy installation
- Designed to retain 30,60,90 minutes of fire integrity of ceiling and subsequent load bearing floors.

5 YEAR WARRANTY | QUICK CONNECTOR | IP65 RATING | DIMMABLE LIGHT CONTROL | 30-60-90 MIN Fire Rated

Product	Model	SKU	Watts	Lumen	Dimension	Box Qty
Chrome	VT-885-C	8913 | 3000K WARM WHITE 8914 | 4000K DAY WHITE 8915 | 6400K WHITE	5w	500	Ø81.5mm Cutting Size Ø57mm	6 pcs
Satin Nickle	VT-885-N	8890 | 3000K WARM WHITE 8891 | 4000K DAY WHITE 8912 | 6400K WHITE	5w	500	Ø81.5mm Cutting Size Ø57mm	6 pcs
White	VT-885-W	8887 | 3000K WARM WHITE 8888 | 4000K DAY WHITE 8889 | 6400K WHITE	5w	500	Ø81.5mm Cutting Size Ø57mm	6 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED DOWNLIGHTS | Fire Rated Downlight

An innovative addition to our Fire-Rated Downlight series, this new model has an accessible switch for colour temperature tuning so users can easily achieve any lighting mood in any room.

- IP65 Rating.
- Integrated SMD LED (Non-replaceable).
- Dimmable
- AC:200-240V,50Hz
- Body Type: Aluminium
- 60° Beam Angle
- CRI >80
- LED provided by samsung
- 30,000-hour lifespan
- Cutting size:75mm

3 YEAR WARRANTY

QUICK CONNECTOR

DIMMABLE LIGHT CONTROL

EASY TOGGLE SWITCH

3000K 4000K 6400K

EASY ACCESS FOR COLOR CHANGING WITH BUTTON

Included Bezels

Chrome | Satin Nickle | White

30-60-90 MIN
Fire Rated

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-18D	881 | 3IN1	8w	720	 Cutting Size Ø75mm	30 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED CABINET LIGHT
LED Cabinet Light

2 YEAR WARRANTY

MOTION PIR SENSOR

Enjoy the convenience of V-TAC's new LED cabinet lights with built-in PIR sensor. Ideal for wardrobes, bookshelves, drawers, and tool cabinets. Fully powered by batteries (3xAAA Battery not included), designed for a neat installation.

Model	SKU	Watts	Lumen	Box Qty
VT-80	813 | 4000K DAY WHITE	1.5w	80	50 pcs



LED CABINET LIGHT
LED Cabinet Light

5 YEAR WARRANTY

MOTION PIR SENSOR

Enjoy the convenience of V-TAC's new LED cabinet lights with built-in PIR sensor. Ideal for wardrobes, bookshelves, drawers, and tool cabinets. Fully powered by batteries(4xAA Battery not included), designed for a neat installation.



Model	SKU	Watts	Lumen	Box Qty
VT-81	814 | 4000K DAY WHITE	1.5w	135	50 pcs



*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED NIGHT LIGHT | LED Night Light

2 YEAR WARRANTY

Eye-friendly LED night light, produce comforting gentle warm light to let you see better in the dark. This white LED nightlight can illuminate any dark space in your home or office.

- Voltage/Frequency: 220-240V, 50Hz
- Power: 0.45W
- RA: >80
- Body material: ABS+PC
- Box Qty: 50pcs



Model	SKU	Watts	Box Qty
VT-82RD	824 | 3000K WARM WHITE 825 | 4000K DAY WHITE	0.45w	pcs

Model	SKU	Watts	Box Qty
VT-82SQ	826 | 3000K WARM WHITE 827 | 4000K DAY WHITE	0.45w	pcs

Model	SKU	Watts	Box Qty
VT-83RD	829 | 4000K DAY WHITE	0.45w	pcs

Model	SKU	Watts	Box Qty
VT-83SQ	830 | 3000K WARM WHITE 831 | 4000K DAY WHITE	0.45w	pcs

Model	SKU	Watts	Box Qty
VT-84RD	505 | 3000K WARM WHITE 506 | 4000K DAY WHITE	0.45w	pcs

Model	SKU	Watts	Box Qty
VT-84SQ	507 | 3000K WARM WHITE 508 | 4000K DAY WHITE	0.45w	pcs

Model	SKU	Watts	Box Qty
VT-86RD	20017 | 4000K DAY WHITE	0.45w	pcs

Model	SKU	Watts	Box Qty
VT-86SQ	20019 | 3000K WARM WHITE 20020 | 4000K DAY WHITE	0.45w	pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED BOLLARD LIGHTS

LED Bollard Lights

3 YEAR WARRANTY

IP65 RATING

- AC:220-240V,50/60Hz
- CRI >80
- PF >0.5
- 120° Beam Angle
- 20,000-hour lifespan
- IP65 Protection
- LED Chip Type – SMD
- On/Off Cycle – 15,000



Model	SKU	Watts	Lumen	Box Qty
VT-33-White	20116 | 3000K WARM WHITE 20117 | 4000K DAY WHITE 20118 | 6400K WHITE	10w	900	5 pcs



LED BOLLARD LIGHTS

LED Bollard Lights

- AC:220-240V,50/60Hz
- CRI >80
- PF >0.5
- 120° Beam Angle
- 20,000-hour lifespan
- IP65 Protection
- LED Chip Type – SMD
- On/Off Cycle – 15,000

Model	SKU	Watts	Lumen	Box Qty
VT-33-Black	20113 | 3000K WARM WHITE 20114 | 4000K DAY WHITE 20115 | 6400K WHITE	10w	650	5 pcs
VT-33-Black-N	2120114 | 4000K DAY WHITE	10w	650	5 pcs



IP65 RATING

3 YEAR WARRANTY

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED WALL LIGHT
Solar Bollard

- Min 3hrs / Max 12hrs Working Time
- 1P65 Rating
- AL+PC Material
- Lithium battery 3.7V 2600mAh
- 3–5 meters Sensing Range
- 4–6 hours sunlight charging Time
- 50pcs of LED
- 5.5V 3 W Solar Panel

IP65 RATING

SOLAR LIGHTS



Model	SKU	Watts	Lumen	Box Qty
VT-66	785 | 3000K WARM WHITE	2w	280	10 pcs
VT-66-N	21785 | 3000K WARM WHITE	2w	280	10 pcs

3 YEAR WARRANTY

LED WALL LIGHT
Solar Bollard

- Min 3hrs / Max 12hrs Working Time
- 1P65 Rating
- AL+PC Material
- Lithium battery 3.7V 2600mAh
- 3–5 meters Sensing Range
- 4–6 hours sunlight charging Time
- 50pcs of LED
- 5.5V 3 W Solar Panel

IP65 RATING

SOLAR LIGHTS



Model	SKU	Watts	Lumen	Box Qty
VT-77	784 | 3000K WARM WHITE	2w	220	10 pcs
VT-77-N	21784 | 3000K WARM WHITE	2w	220	10 pcs

3 YEAR WARRANTY

*Suitable for use up to 10–12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED WALL LIGHT
LED Wall Light

3 YEAR WARRANTY

POLYCARBONATE PC

IP54 RATING

- AC220-240V,50/60Hz
- CR1: >80
- 15,000 times On/Off
- 20,000 hrs. Life span
- PC Material
- IP54 Rating



Model	SKU	Watts	Lumen	Box Qty
VT-7-06	780 | 3000K WARM WHITE 781 | 4000K DAY WHITE	10w	800	20 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

OUTDOOR LIGHTING | Garden Light 2IN1 (Lamp Post + Spike)

- IP65 Rating.
- COB-Samsung Chip
- 3 Years Warranty
- AC:220-240V, 50/60Hz
- Body Type: Aluminium
- 100° Beam Angle
- CRI >80
- PF>0.5
- 20,000-hour lifespan
- On/Off Cycle >15000



3 YEAR WARRANTY

IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-907	20316 | 3000K WARM WHITE 20317 | 4000K DAY WHITE 20318 | 6400K WHITE	7w	420	20 pcs

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated

LED EMERGENCY LIGHTS

V-TAC new range of LED emergency lights comes at an age of increased awareness and standards for safety compliance in different infrastructures. Now equipped with highly efficient LEDs provided by Samsung, these emergency lights include clear-cut exit signs, and are powered by high performance batteries, to provide a longer lifespan, lower maintenance, with increased working time when activated. V-TAC's emergency lights are a smart choice for effective emergency lighting to meet fire & safety assessments in residential and commercial buildings, offices, hotels, hospitals, and schools

Key Features

• Thermoplastic PC built
• High quality Ni-Cd batteries made for longevity & low maintenance reliable emergency backup of 3 hours
• Rectangular type plastic with different signs for various locations
• Single or double face configuration
• Wall, side, or ceiling mounted
• LED indicator light and push button test switch LEDs mounted on print circuit board
• 12–24-hour recharge after more than 3-hour discharge
• Efficient thermal management technology
• Corrosion-free mounting clamps
• Maintained operation mode

Application

Offices, hospitals, corporate buildings, schools, and commercial establishments

5 YEAR WARRANTY

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED EMERGENCY LIGHTS

LED Exit Light – Surface

- IP20
- PC body
- 3 Stickers
- 16 SMD LEDs
- AC:220-240V,50/60Hz
- Wall/Ceiling Installation
- Ni-Cd 3.6V,900mAh Battery
- 12-hour Charging Time
- Green Light Indicator Test Button
- 3 Way Legend Available
- Mode Of Operation Maintained
- >3-hour Emergency Operation Time
- 24 Meters Viewing Distance From Both Sides

3 YEAR WARRANTY

12 HOURS CHARGING TIME

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Box Qty
VT-519-S-12	836 – 6000K WHITE	2w	140lm	10



LED EMERGENCY LIGHTS

LED Exit Light-Recessed

- IP20
- PC body
- 3 Stickers
- 16 SMD LEDs
- AC:220-240V,50/60Hz
- Recessed/Ceiling Installation
- Ni-Cd 3.6V,900mAh Battery
- 12-hour Charging Time
- Green Light Indicator Test Button
- 3 Way Legend Available
- Mode Of Operation Maintained
- >3-hour Emergency Operation Time
- 24 Meters Viewing Distance From Both Sides

3 YEAR WARRANTY

12 HOURS CHARGING TIME

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Box Qty
VT-522-S-12	835 – 6000K WHITE	2w	140lm	10



*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED EMERGENCY LIGHTS

LED Exit Light – Bulkhead

- IP20
- ABS+PC body
- 20 SMD LEDs
- AC:220-240V,50/60Hz
- Ni-Cd 4.8V, 900mAh Battery
- 12-hour Charging Time
- Green Indicator Light
- Mode Of Operation Maintained/Non Maintained
- >3-hour Emergency Operation Time

3 YEAR WARRANTY

12 HOURS CHARGING TIME

Model	SKU	Watts	Lumen	Box Qty
VT-511-S	899 – 6000K WHITE	3.8w	110lm	10



LED EMERGENCY LIGHTS

LED Exit Light – Bulkhead

- IP65
- PC body
- 3 Stickers
- 30 SMD LEDs
- AC:220-240V,50/60Hz
- Wall Installation
- Ni-Cd 4.8V,900mAh Battery
- 12-hour Charging Time
- Green Light Indicator Test Button
- 3 Way Legend Available
- Mode Of Operation Maintained
- >3-hour Emergency Operation Time
- 22 Meters Viewing Distance From Both Sides

3 YEAR WARRANTY

12 HOURS CHARGING TIME

IP65 RATING

POLYCARBONATE PC

Model	SKU	Watts	Lumen	Box Qty
VT-524-S-12	838 – 6000K WHITE	4w	190lm	12



*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

LED STRIP LIGHTS

V-TAC's efficient LED strip lights range is an effective solution in illuminating up tight spaces. These lights can also be used to simply decorate your kitchen, bedroom, patios, and more. Applicable for both accent lighting or task lighting, these strip lights are easy to install, compatible with controls, and are available in standard colour temperatures.

Application

Recommended for bedrooms, kitchens, restaurants, bars, and other residential and commercial areas

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED STRIP LIGHTS

3 YEAR WARRANTY



Model	SKU	Watts	Lumen	Voltage	Roll	CRI	Box Qty
VT-5-120	323 | 3000K WARM WHITE 324 | 4000K DAY WHITE 325 | 6400K WHITE	12w	1200	DC:12V	5 Meter Roll	>80	400 Meter
VT-5-120-N	21324 | 4000K DAY WHITE	12w	1320	DC:12V	5 Meter Roll	>80	400 Meter
VT-10-240	320 | 3000K WARM WHITE 321 | 4000K DAY WHITE 322 | 6400K WHITE	15w	1600	DC:24V	10 Meter Roll	>80	800 Meter
VT-10-240-N	21321 | 4000K DAY WHITE	15w	1650	DC:24V	10 Meter Roll	>80	800 Meter
VT-10-240-1	331 | 3000K WARM WHITE 332 | 4000K DAY WHITE 333 | 6400K WHITE	18w	1800	DC:24V	10 Meter Roll	>95	800 Meter

WATERPROOF LED NEON FLEX

3 YEAR WARRANTY

IP65 RATING

Model	SKU	Watts	Lumen	Voltage	Roll	CRI	Box Qty
VT-55	326 | 3000K WARM WHITE 327 | 4000K DAY WHITE 328 | 6400K WHITE	10w	300	DC:12V	5 Meter Roll	>80	200 Meter

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated

LED SPOTLIGHTS

Our new range of LED spotlights with Samsung LEDss is your leading choice for efficient directional lighting solutions. This new range is perfectly compatible with existing GU10 holders. They deliver the same warm light as halogen spots while exhibiting the energy-saving benefits that LEDs provide. Ideal for retail and residential lighting.

Key Features

- Classic halogen-like design with up to 80% power savings
- Compatibility ensured: available in all existing spotlight holders
- Optional beam angles: ranging from 10°, 38° and 110°
- Set the right tone: dimmable options available

Application

Ideal for lighting applications in residential, commercial, and hospitality locations.

5 YEAR WARRANTY

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED SPOTLIGHTS

LED Capsules Lights

LED Capsule Lights are usually installed in cabinet lighting, integrated light fittings in the kitchen and more. Efficient replacement for halogen capsule bulbs – small size and wattage but provides ample and sufficient lighting. Available in G4 & G9 bases.

5 YEAR WARRANTY



- G4 Base
- DC:12V
- PF: >0.4
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-201	240 | 3000K WARM WHITE 241 | 4000K DAY WHITE 242 | 6400K WHITE	1.5w	10w	100	200
VT-201-N	21240 | 3000K WARM WHITE	1.1W	10w	100	400

- G4 Base
- DC:12V
- PF: >0.5
- CRI: >81
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-234	131 | 3000K WARM WHITE 132 | 4000K DAY WHITE 133 | 6400K WHITE	3.2w	30w	385	200
VT-234-N	21131 | 3000K WARM WHITE 21132 | 4000K DAY WHITE	3.2W	30w	385	400

- G9 Base
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-203	243 | 3000K WARM WHITE 244 | 4000K DAY WHITE 245 | 6400K WHITE	2.5w	20w	200	200
VT-203-N	21243 | 3000K WARM WHITE 21244 | 4000K DAY WHITE 21245 | 6500K WHITE	2.2W	20w	200	400

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- G9 Base
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-204	246 | 3000K WARM WHITE 247 | 4000K DAY WHITE 248 | 6400K WHITE	3w	25w	300	200
VT-204-N	21246 | 3000K WARM WHITE 21247 | 4000K DAY WHITE 21248 | 6500K WHITE	3W	30w	330	400

LED SPOTLIGHTS

38° Beam Angle

Achieve beautiful directional lighting with a narrow, focused glow in any room with our improved range of GU10 spotlights with 30,000-hr lamp life and 38° beam angle.

5 YEAR WARRANTY



- GU10 Base
- AC:220-240V,50Hz
- PF:
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-232	869 | 3000K WARM WHITE 870 | 4000K DAY WHITE 871 | 6400K WHITE	2w	15w	180	200
VT-232-N	21869 | 3000K WARM WHITE 21870 | 4000K DAY WHITE 21871 | 6400K WHITE	2w	15w	180	200

- GU10 Base
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 30,000-hour Lifespan

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-275	108 | 3000K WARM WHITE 797 | 4000K DAY WHITE 511 | 6400K WHITE	5w	40w	380	192
VT-275-N	21108 | 3000K WARM WHITE 21797 | 4000K DAY WHITE 21511 | 6500K WHITE	4.5W	50w	345	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

- GU10 Base
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 30,000-hour Lifespan



DIMMABLE LIGHT CONTROL

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-275D	109 | 3000K WARM WHITE 512 | 4000K DAY WHITE 897 | 6400K WHITE	5w	35w	380	192

- GU5.3 Base
- DC:12V
- PF: >0.5
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-267	207 | 3000K WARM WHITE 208 | 4000K DAY WHITE 209 | 6400K WHITE	6.5w	40w	450	200
VT-267-N	21207 | 3000K WARM WHITE	6W	60w	445	200

- GU10 Base
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-227	189 | 3000K WARM WHITE 190 | 4000K DAY WHITE 191 | 6400K WHITE	6.5w	60w	480	200
VT-227-N	21189 | 3000K WARM WHITE	6W	60w	445	200

- GU10 Base
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 30,000-hour Lifespan



DIMMABLE LIGHT CONTROL

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-227D	195 | 3000K WARM WHITE 196 | 4000K DAY WHITE 197 | 6400K WHITE	6.5w	55w	450	200
VT-227D-N	21195 | 3000K WARM WHITE 21196 | 4000K DAY WHITE 21197 | 6500K WHITE	6W	60w	445	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- GU10 Base
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-277	165 | 3000K WARM WHITE 166 | 4000K DAY WHITE 167 | 6400K WHITE	7w	60w	480	200

- GU10 Base
- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-291	875 | 3000K WARM WHITE 876 | 4000K DAY WHITE 877 | 6400K WHITE	8w	80w	720	200
VT-291-N	21875 | 3000K WARM WHITE 21876 | 4000K DAY WHITE 21877 | 6500K WHITE	7.5W	70w	610	200

LED SPOTLIGHTS
Evolution Series 110°

Achieve a warm soft glow in any room with our improved GU10 spotlight with 30,000-hr lamp life and 160 lumen/watt.

5 YEAR WARRANTY

evolution 160 LUMENS/W



- GU10 Base
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 25,000-hour Lifespan

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2335	2837 | 3000K WARM WHITE 2838 | 4000K DAY WHITE 2839 | 6400K WHITE	5w	75	800	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED SPOTLIGHTS
110° Beam Angle

Achieve beautiful directional lighting with a broader glow in any room with our improved range of GU10 spotlights with 30,000-hr lamp life and 110° beam angle.

5 YEAR WARRANTY



- GU10 Base
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-205	201 | 3000K WARM WHITE 202 | 4000K DAY WHITE 203 | 6400K WHITE	5w	35w	400	200
VT-205-N	21201 | 3000K WARM WHITE 21202 | 4000K DAY WHITE 21203 | 6500K WHITE	4.5W	35w	400	200

- GU5.3 Base
- DC:12V
- PF: >0.5
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-257	204 | 3000K WARM WHITE 205 | 4000K DAY WHITE 206 | 6400K WHITE	6.5w	40w	450	200
VT-257-N	21206 | 6500K WHITE	6W	60w	445	200

- GU10 Base
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-247	192 | 3000K WARM WHITE 193 | 4000K DAY WHITE 194 | 6400K WHITE	6.5w	60w	480	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- GU10 Base
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 30,000-hour Lifespan



DIMMABLE LIGHT CONTROL

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-247D	198 | 3000K WARM WHITE 199 | 4000K DAY WHITE 200 | 6400K WHITE	6.5w	55w	450	200
VT-247D-N	21198 | 3000K WARM WHITE 21199 | 4000K DAY WHITE	6W	60w	445	200

- GU10 Base
- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-292	872 | 3000K WARM WHITE 873 | 4000K DAY WHITE 874 | 6400K WHITE	8w	80w	720	200
VT-292-N	21872 | 3000K WARM WHITE 21873 | 4000K DAY WHITE 21874 | 6500K WHITE	7.5W	70w	610	200

- GU10 Base
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-271	878 | 3000K WARM WHITE 879 | 4000K DAY WHITE 880 | 6400K WHITE	10w	70w	1000	200
VT-271-N	21878 | 3000K WARM WHITE 21879 | 4000K DAY WHITE 21880 | 6500K WHITE	10w	70w	1000	200

- GU10 Base
- AC:220-240V,50Hz
- PF:
- CRI: >80
- 30,000-hour Lifespan

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-249	20026 | 3000K WARM WHITE 20027 | 4000K DAY WHITE 20028 | 6400K WHITE	6w	50w	500	200
VT-249-N	2120026 | 3000K WARM WHITE	6W	60w	445	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®

INNOVATIVE LED LIGHTING

SAMSUNG LED

Illuminated

LED BULBS

Find the right bulb in V-TAC's newly improved range of LED bulbs. Our recent in-branding program enabled us to equip all LED PRO Series lamp range with LEDs provided by Samsung.

From aesthetically-pleasing filament bulbs to our extensive options of 360° omnidirectional thermoplastic bulbs in all sizes, watts, and lumens, we have a complete range of options to replace 60W to 150W traditional lamps and achieve energy-saving lighting in your home, office, or business.

Key Features

• Includes Amber & Clear Filament Bulbs, High Lumen Bulbs, Thermoplastic Bulbs, Reflector Bulbs, PAR Bulbs, Big Bulbs, and B22s.
• Lightweight yet durable body: made of Aluminium + ASA plastic
• Designed with optimal thermal management
• 80% lower power consumption
• Dimmable options available
• 30,000-hour lifespan: remarkable performance than conventional and other LED lamps

Application

General lighting in residential, commercial, and industrial areas

5 YEAR WARRANTY



V-TAC®
INNOVATIVE LED LIGHTING

evolution

LED BULBS
Evolution Series

Our bestselling LED Bulbs — now upgraded with a superior efficiency of 160 lm/W through the latest in LED technology.



- E27 Base
- A60 Shape
- AC:220-240V, 50Hz
- PF: >0.6
- CRI: >80
- 200° Beam Angle



160 LUMENS/W

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2307	2806 | 3000K WARM WHITE 2807 | 4000K DAY WHITE 2808 | 6400K WHITE	6.5W	75w	1055lm	100

- E27 Base
- A60 Shape
- AC:220-240V, 50Hz
- PF: >0.6
- CRI: >80
- 200° Beam Angle



160 LUMENS/W

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2310	2809 | 3000K WARM WHITE 2810 | 4000K DAY WHITE 2811 | 6400K WHITE	9.5W	100w	1521lm	100

- E27 Base
- A65 Shape
- AC:220-240V, 50Hz
- PF: >0.6
- CRI: >80
- 200° Beam Angle



160 LUMENS/W

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2315	2812 | 3000K WARM WHITE 2813 | 4000K DAY WHITE 2814 | 6400K WHITE	15W	150w	2452lm	100

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- E27 Base
- ED120 Shape
- AC:220-240V, 50Hz
- PF: >0.6
- CRI: >80
- 310° Beam Angle



evolution 160 LUMENS/W

2 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2324	2816 | 4000K DAY WHITE 2817 | 6400K WHITE	24W	250w	4000lm	20

LED BULBS

LED Amber Filament

V-TAC's decorative Amber Filament lamp range is devised with the latest technology to provide the warm look and feel of conventional Edison bulbs but with the efficiency of LED lamps.

- B22 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



3 YEAR WARRANTY

BAYONET HOLDER

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-228	107 | 2200K WARM WHITE	4w	35w	350	96

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan

3 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-266	286 | 2200K WARM WHITE	6w	55w	725	50

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

- E27 Base
- G125 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



120 lm/W

3 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-297	291 | 2200K WARM WHITE	6w	55w	725	20

- E27 Base
- ST64 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



120 lm/W

3 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-276	290 | 2200K WARM WHITE	6w	55w	725	50

LED BULBS

LED Clear Filament

V-TAC's decorative and efficient LED filament range also comes in an elegant, clear glass body for a classic vintage design in A60, candle, and globe shapes that can replace 35 to 60-watt traditional filament bulbs.



- B22 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



3 YEAR WARRANTY

BAYONET HOLDER

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-208	106 | 3000K WARM WHITE	4w	40w	400	96

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- B22 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



3 YEAR WARRANTY

BAYONET HOLDER

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-222	105 | 3000K WARM WHITE	4w	40w	400	192

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-254	272 | 2700K WARM WHITE	4w	35w	400	100

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



DIMMABLE LIGHT CONTROL

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-254D	278 | 2700K WARM WHITE	4w	30w	350	100

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-274	279 | 2700K WARM WHITE	4w	35w	400	100

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-264	275 | 2700K WARM WHITE	4w	35w	400	100

- B15 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 300° Beam Angle
- Lifespan



DIMMABLE LIGHT CONTROL

3 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-284D	862 | 3000K WARM WHITE	4w	30w	350	100

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-244	280 | 2700K WARM WHITE 944 | 4000K DAY WHITE	4w	35w	400	100

- E27 Base
- G95 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



3 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-286	294 | 2700K WARM WHITE	6w	60w	806	20

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- E27 Base
- G125 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 300° Beam Angle
- 20,000-hour Lifespan



3 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-287	292 | 2700K WARM WHITE	6w	60w	806	20

LED BULBS

High Lumen Bulbs

The High Lumen range takes it up a notch with a broad selection of our bestselling lamps but brighter light at less wattage. Achieve next level efficiency in any room.



- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



120 lm/W

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-255	258 | 3000K WARM WHITE 259 | 4000K DAY WHITE 260 | 6400K WHITE	4.5w	40w	470	200

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan



120 lm/W

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-245	261 | 3000K WARM WHITE 262 | 4000K DAY WHITE 263 | 6400K WHITE	4.5w	40w	470	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan



120 lm/W

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-225	264 | 3000K WARM WHITE 265 | 4000K DAY WHITE 266 | 6400K WHITE	4.5w	40w	470	200

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



120 lm/W

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-265	255 | 3000K WARM WHITE 256 | 4000K DAY WHITE 257 | 6400K WHITE	6.5w	60w	806	100

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



120 lm/W

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-285	252 | 3000K WARM WHITE 253 | 4000K DAY WHITE 254 | 6400K WHITE	8.5w	75w	1055	100

- E27 Base
- A65 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



120 lm/W

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-295	249 | 3000K WARM WHITE 250 | 4000K DAY WHITE 251 | 6400K WHITE	12w	100w	1521	100

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- E27 Base
- G120 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

120 lm/W



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-242	20021 | 3000K WARM WHITE 20022 | 4000K DAY WHITE 20023 | 6400K WHITE	22w	160	2650	20
VT-242-N	2120021 | 3000K WARM WHITE 2120022 | 4000K DAY WHITE 2120023 | 6500K WHITE	22W	155w	2600	20

LED BULBS

LED Thermoplastic Bulbs

A decorative and efficient range of Candle, G45, P45, lamps for intricate light fittings in wall lamps, chandeliers and table lamps. This new generation of LED plastic bulbs includes our 9w to 18w A58, A65, and A80 lamps which are ideal for general purpose lighting at residential, commercial, and industrial areas.



- E14 Base
- ST26 Shape
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 230° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-202	234 | 3000K WARM WHITE 235 | 4000K DAY WHITE 236 | 6400K WHITE	2w	20w	180	400
VT-202-N	21234 | 3000K WARM WHITE 21235 | 4000K DAY WHITE 21236 | 6500K WHITE	2W	18w	180	400

- E14 Base
- T37 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 230° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-248	267 | 3000K WARM WHITE 268 | 4000K DAY WHITE 269 | 6400K WHITE	8w	50w	660	200
VT-248-N	21269 | 6500K WHITE	7.5W	50w	660	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

- E27 Base
- T37 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 230° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-237	144 | 3000K WARM WHITE 145 | 4000K DAY WHITE 146 | 6400K WHITE	8w	50w	660	200
VT-237-N	21146 | 6500K WHITE	7.5W	50w	660	200

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-226	171 | 3000K WARM WHITE 172 | 4000K DAY WHITE 173 | 6400K WHITE	5.5w	40w	470	200

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

DIMMABLE LIGHT CONTROL



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-293D	20045 | 3000K WARM WHITE 20186 | 4000K DAY WHITE 20187 | 6400K WHITE	5.5w	40w	470	200
VT-293D-N	2120186 | 4000K DAY WHITE 2120187 | 6500K WHITE	5.5W	40w	470	200

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



DIMMABLE LIGHT CONTROL

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-294D	859 | 3000K WARM WHITE	5.5w	40w	470	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- E27 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-289	858 | 3000K WARM WHITE	5.5w	40w	470	200

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-258	117 | 3000K WARM WHITE 118 | 4000K DAY WHITE 119 | 6400K WHITE	5.5w	40w	470	200

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-268	111 | 3000K WARM WHITE 112 | 4000K DAY WHITE 113 | 6400K WHITE	7w	45w	600	200

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-246	174 | 3000K WARM WHITE 175 | 4000K DAY WHITE 176 | 6400K WHITE	5.5w	40w	470	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-283	857 | 3000K WARM WHITE	5.5w	40w	470	200

- E27 Base
- G45 Shape
- AC:220-240V
- PF: >0.5
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-290	866 | 3000K WARM WHITE 867 | 4000K DAY WHITE 868 | 6400K WHITE	7w	45w	600	200
VT-290-N	21867 | 4000K DAY WHITE 21868 | 6500K WHITE	6.5W	45w	600	200

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-236	168 | 3000K WARM WHITE 169 | 4000K DAY WHITE 170 | 6400K WHITE	5.5w	40w	470	200

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-282	856 | 3000K WARM WHITE	5.5w	40w	470	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- E14 Base
- P45 Shape
- AC:220-240V
- PF: >0.5
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-270	863 | 3000K WARM WHITE 864 | 4000K DAY WHITE 865 | 6400K WHITE	7w	45w	600	200

- E14 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-269	114 | 3000K WARM WHITE 115 4000K DAY WHITE 116 | 6400K WHITE	9w	60w	806	100
VT-269-N	21115 | 4000K DAY WHITE	8.5W	60w	806	100

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-210	228 | 3000K WARM WHITE 229 | 4000K DAY WHITE 230 | 6400K WHITE	9w	60w	806	100

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-212	231 | 3000K WARM WHITE 232 | 4000K DAY WHITE 233 | 6400K WHITE	11w	75w	1055	100

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



DIMMABLE LIGHT CONTROL

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-262D	20044 | 3000K WARM WHITE 20184 | 4000K DAY WHITE 20185 | 6400K WHITE	12w	75w	1055	100

- E27 Base
- A65 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-215	159 | 3000K WARM WHITE 160 | 4000K DAY WHITE 161 | 6400K WHITE	15w	85w	1250	100

- E27 Base
- A65 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-217	162 | 3000K WARM WHITE 163 | 4000K DAY WHITE 164 | 6400K WHITE	17w	100w	1521	100

- E27 Base
- A65 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

DIMMABLE LIGHT CONTROL

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-217D	20188 | 3000K WARM WHITE 20189 | 4000K DAY WHITE 20190 | 6400K WHITE	17w	100w	1521	100

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- E27 Base
- A80 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-298	126 | 3000K WARM WHITE 127 | 4000K DAY WHITE 128 | 6400K WHITE	18w	125w	2000	100

- E27 Base
- A80 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-233	237 3000K WARM WHITE 238 | 4000K DAY WHITE 239 | 6400K WHITE	20w	150w	2452	50
VT-233-N	21237 | 3000K WARM WHITE 21238 | 4000K DAY WHITE 21239 | 6500K WHITE	20W	150w	2452	50

- B15 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

BAYONET HOLDER



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-299	860 | 3000K WARM WHITE	5.5w	40w	470	200
VT-299-N	21860 | 3000K WARM WHITE	5.5w	40w	470	200

- B15 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

DIMMABLE LIGHT CONTROL

BAYONET HOLDER



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-299D	861 | 3000K WARM WHITE	5.5w	40w	470	200
VT-299D-N	21861 | 3000K WARM WHITE	5.5W	40w	470	200

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

- B22 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

BAYONET HOLDER



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-223	103 | 3000K WARM WHITE 20152 | 6400K WHITE	5.5w	40w	470	192
VT-223-N	21103 | 3000K WARM WHITE 2120152 | 6500K WHITE	4.5W	40w	470	200

- B22 Base
- G45 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 180° Beam Angle
- 30,000-hour Lifespan

BAYONET HOLDER



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-221	104 | 3000K WARM WHITE	5.5w	40w	470	192
VT-221-N	21104 | 3000K WARM WHITE	4.5W	40w	470	200

- B22 Base
- A58 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

BAYONET HOLDER



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-229	101 | 3000K WARM WHITE 850 | 4000K DAY WHITE 851 | 6400K WHITE	9w	60w	806	96
VT-229-N	21101 | 3000K WARM WHITE 21850 | 4000K DAY WHITE 21851 | 6500K WHITE	8.5W	60w	806	100

- B22 Base
- A58 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

DIMMABLE LIGHT CONTROL

BAYONET HOLDER



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-259D	852 | 3000K WARM WHITE	9w	60	806	100

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- B22 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

BAYONET HOLDER



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-213	110 | 4000K DAY WHITE	11w	75w	1055	100
VT-213-N	21110 | 4000K DAY WHITE	10.5w	75w	1055	100

- B22 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

BAYONET HOLDER



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-231	102 | 3000K WARM WHITE 853 | 6400K WHITE	11w	75w	1055	96
VT-231-N	21102 | 3000K WARM WHITE 21853 | 6500K WHITE	10.5W	75w	1055	100

- B22 Base
- A65 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan

BAYONET HOLDER



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-281	854 | 3000K WARM WHITE 943 | 4000K DAY WHITE 855 | 6400K WHITE	15w	85w	1250	100
VT-281-N	21854 | 3000K WARM WHITE 21855 | 6500K WHITE	15W	100w	1521	100

LED BULBS

LED Reflector Bulb

We offer an energy-efficient reflectors range of various widths (39mm, 50mm, 63mm, 80mm) for diffused lighting that can serve as track or spotlight in residential, hospitality, or commercial spaces.

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

- E14 Base
- R39 Shape
- AC:220-240V,50Hz
- PF: >0.4
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-239	210 | 3000K WARM WHITE 211 | 4000K DAY WHITE 212 | 6400K WHITE	3w	25w	250	200

- E14 Base
- R50 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-250	138 | 3000K WARM WHITE 139 | 4000K DAY WHITE 140 | 6400K WHITE	6w	40w	470	200
VT-250-N	21238 | 3000K WARM WHITE 21239 | 4000K DAY WHITE 21140 | 6500K WHITE	4.8W	40w	470	200

- E27 Base
- R63 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-263	141 | 3000K WARM WHITE 142 | 4000K DAY WHITE 143 | 6400K WHITE	8w	60w	570	200
VT-263-N	21141 | 3000K WARM WHITE	8.5W	60w	806	100

- E27 Base
- R80 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-280	135 | 3000K WARM WHITE 136 | 4000K DAY WHITE 137 | 6400K WHITE	10w	75w	800	200
VT-280-N	21135 | 3000K WARM WHITE	11W	75w	1055	100

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED BULBS

LED PAR Bulb

Provide precisely control LED beams of light to any space with V-TAC's improved range of LED PAR bulbs with 40° beam angle. With a significantly longer lifespan and up to 80% lower energy-consumption, our LED PAR series is your cost-efficient replacement for Halogen PAR lamps. Our PAR series offers advanced thermal management features and uses LEDs provided by Samsung.

- E27 Base
- PAR20 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 40° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-220	147 | 3000K WARM WHITE 148 | 4000K DAY WHITE 149 | 6400K WHITE	7w	65w	495	100
VT-220-N	21149 | 6500K WHITE	5.8W	55w	425	100

- E27 Base
- PAR30 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 40° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-230	153 | 3000K WARM WHITE 154 | 4000K DAY WHITE 155 | 6400K WHITE	11w	95w	825	30

- E27 Base
- PAR38 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 40° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-238	150 | 3000K WARM WHITE 151 | 4000K DAY WHITE 152 | 6400K WHITE	14w	120w	1100	30
VT-238-N	21151 | 4000K DAY WHITE	12.8W	105w	925	30

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

LED BULBS
Big Bulb & UFO

V-TAC's Big Bulb range are ready to meet lighting demands for big spaces that require broader lighting with its range of unique designs, all with significantly greater luminous flux. This range has lamps with diameter ranging from 75mm up to 250mm. Despite the great size, these LED big bulbs are equipped with modern thermal management so it will not heat up and has LEDs provided by Samsung for maximum efficiency.



- E27 Base
- F150 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-216	213 | 3000K WARM WHITE 214 | 4000K DAY WHITE 215 | 6400K WHITE	15w	85w	1200	20

- E27 Base
- F200 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-224	216 | 3000K WARM WHITE 217 | 4000K DAY WHITE 218 | 6400K WHITE	24w	120w	1950	20

- E27 Base
- F250 Shape
- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-235	219 | 3000K WARM WHITE 220 | 4000K DAY WHITE 221 | 6400K WHITE	36w	170w	2900	20

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

- GX53 Base
- Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-207	222 | 3000K WARM WHITE 223 | 4000K DAY WHITE 224 | 6400K WHITE	7w	45w	550	200
VT-207-N	21222 | 3000K WARM WHITE 21223 | 4000K DAY WHITE 21224 | 6500K WHITE	6.4W	45w	560	200

- E27 Base
- G120 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-218	226 | 4000K DAY WHITE	17w	100w	1521	20

- E27 Base
- G120 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-288	123 | 3000K WARM WHITE 124 | 4000K DAY WHITE 125 | 6400K WHITE	18w	125w	2000	20

- E27 Base
- NA Shape
- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan



2 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-240	283 | 3000K WARM WHITE 284 | 4000K DAY WHITE 285 | 6400K WHITE	36w	250w	3960	20

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED Illuminated

- E40 Base
- NA Shape
- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-260	186 | 3000K WARM WHITE 187 | 4000K DAY WHITE 188 | 6400K WHITE	60w		5400	20

- E40 Base
- NA Shape
- AC:100-277V,50/60Hz
- PF: >0.9
- CRI: >80
- 110° Beam Angle
- 30,000-hour Lifespan

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-85	521 | 6400K WHITE	85w		6800	4

LED BULBS

LED Emergency Bulb

The Emergency Bulb is equipped with battery back-ups which enable the unit to work for up to 3-hour in power outages and other emergency situations. It is also a portable, multifunctional LED bulb which can also be used as camping light, flashlight, hooklight, warehouse light, and more.

- E27 Base
- A70 Shape
- AC:220-240V,50Hz
- CRI: >80
- 200° Beam Angle
- 30,000-hour Lifespan



3 HOURS EMERGENCY BATTERY

2 YEAR WARRANTY

Model	SKU	Watts	Lumen	Box Qty
VT-2309	2371 | 3000K WARM WHITE 2372 | 4000K DAY WHITE 2373 | 6400K WHITE	9w	806	50

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SAMSUNG LED Illuminated

V-TAC® INNOVATIVE LED LIGHTING

LED BULBS
Acrylic Bulbs

V-TAC's Acrylic Bulb range with its unique designs, all with significantly greater luminous flux. Despite the great size, these LED big bulbs are equipped with modern thermal management so it will not heat up and has LEDs provided by Samsung for maximum efficiency.

- E27 Base
- NA Shape
- AC: 200-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan



5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2311	2781 | 3000K WARM WHITE 2782 | 4000K DAY WHITE 2783 | 6400K WHITE	11w	70w	900	18

- E27 Base
- NA Shape
- AC: 200-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- 30,000-hour Lifespan

5 YEAR WARRANTY

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2318	2784 | 3000K WARM WHITE 2785 | 4000K DAY WHITE 2786 | 6400K WHITE	18w	90w	1200	18

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



LED SMART LIGHT

V-TAC meets the growing IoT demand for home lighting with the new SMART Light series — a collection of Wi-Fi-supported LED lighting & home efficiency solutions that can be fully controlled via Amazon Alexa or Google Home.

WORKS WITH alexa

works with Ok Google

V-TAC®
INNOVATIVE LED LIGHTING

V-TAC SMART LIGHT

V-TAC SMART LIGHT

V-TAC® INNOVATIVE LED LIGHTING

Smart Bulb

WORKS WITH alexa

works with Ok Google

Voltage/Frequency: AC:220-240v,50Hz
CRI: >80
Beam Angle: 200°
Wireless Frequency: 2.4GHz
Wireless Standard: IEEE 802.11 b/g/n
Base: E14
Body Type: Thermoplastic
Life Span: 30,000-hour
Dimension: 37×100mm

- 16 Million Colors
- APP Remote Control
- Smart Timer Function
- Smart Lighting Adjustment

Model	SKU	Watts	Lumen	Box Qty
VT-5114	2754 RGB+2700K-6400K	5W	470	200

Smart Bulb

WORKS WITH alexa

works with Ok Google

Voltage/Frequency: AC:220-240v,50Hz
CRI: >80
Beam Angle: 180°
Wireless Frequency: 2.4GHz
Wireless Standard: IEEE 802.11 b/g/n
Base: E27
Body Type: Thermoplastic
Life Span: 30,000-hour
Dimension: Ø45×81mm

- 16 Million Colors
- APP Remote Control
- Smart Timer Function
- Smart Lighting Adjustment

Model	SKU	Watts	Lumen	Box Qty
VT-5124	2755 RGB+2700K-6400K	5W	470	200

Smart Bulb

WORKS WITH alexa

works with Ok Google

Voltage/Frequency: AC:220-240v,50Hz
CRI: >80
Beam Angle: 180°
Wireless Frequency: 2.4GHz
Wireless Standard: IEEE 802.11 b/g/n
Base: E14
Body Type: Thermoplastic
Life Span: 30,000-hour
Dimension: Ø45×81mm

- 16 Million Colors
- APP Remote Control
- Smart Timer Function
- Smart Lighting Adjustment

Model	SKU	Watts	Lumen	Box Qty
VT-5154	2756 RGB+2700K-6400K	5W	470	200

Smart Bulb

WORKS WITH alexa

works with Ok Google

Voltage/Frequency: AC:220-240v,50Hz
CRI: >80
Beam Angle: 200°
Wireless Frequency: 2.4GHz
Wireless Standard: IEEE 802.11 b/g/n
Base: B22
Body Type: Thermoplastic
Life Span: 30,000-hour
Dimension: Ø60×120mm

- 16 Million Colors
- APP Remote Control
- Smart Timer Function
- Smart Lighting Adjustment

Model	SKU	Watts	Lumen	Box Qty
VT-5110	2791 RGB+2700K-6400K	10w	806	100

V-TAC®
INNOVATIVE LED LIGHTING

V-TAC SMART LIGHT

Smart Bulb

WORKS WITH alexa · works with Ok Google

Voltage/Frequency: AC:220-240v,50Hz
CRI: >80
Beam Angle: 200°
Wireless Frequency: 2.4GHz
Wireless Standard: IEEE 802.11 b/g/n
Base: E27
Body Type: Thermoplastic
Life Span: 30,000-hour
Dimension: Ø60×120mm

- 16 Million Colors
- APP Remote Control
- Smart Timer Function
- Smart Lighting Adjustment

Model	SKU	Watts	Lumen	Box Qty
VT-5119	2751 RGB+2700K-6400K	10W	806	100

Smart Bulb

WORKS WITH alexa · works with Ok Google

Voltage/Frequency: AC:220-240v,50Hz
CRI: >80
Beam Angle: 200°
Wireless Frequency: 2.4GHz
Wireless Standard: IEEE 802.11 b/g/n
Base: E27
Body Type: Thermoplastic
Life Span: 30,000-hour
Dimension: Ø60×120mm

- 16 Million Colors
- APP Remote Control
- Smart Timer Function
- Smart Lighting Adjustment

Model	SKU	Watts	Lumen	Box Qty
VT-5113	2752 RGB+2700K-6400K	11W	1055	100

Smart Bulb

WORKS WITH alexa · works with Ok Google

Voltage/Frequency: AC:220-240v,50Hz
CRI: >80
Beam Angle: 200°
Wireless Frequency: 2.4GHz
Wireless Standard: IEEE 802.11 b/g/n
Base: E27
Body Type: Thermoplastic
Life Span: 30,000-hour
Dimension: Ø65×135mm

- 16 Million Colors
- APP Remote Control
- Smart Timer Function
- Smart Lighting Adjustment

Model	SKU	Watts	Lumen	Box Qty
VT-5117	2753 RGB+2700K-6400K	15W	1300	100

Smart Spotlight

WORKS WITH alexa · works with Ok Google

Voltage/Frequency: AC:220-240v,50Hz
CRI: >80
Beam Angle: 110°
Wireless Frequency: 2.4Ghz
Wireless Standard: IEEE 802.11 b/g/n
Base: GU10
Body Type: Plastic
Life Span: 30,000-hour
Dimension: 50×57mm

- WarmWhite-DayWhite-White
- APP Remote Control
- Smart Timer Function
- Smart Dimming

Model	SKU	Watts	Lumen	Box Qty
VT-5174	2750 3000K-6400K	4.5W	300	200

DEKRA · TÜV · GS · RoHS · CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC SMART LIGHT

V-TAC® INNOVATIVE LED LIGHTING

Smart Spotlight

WORKS WITH alexa

works with Ok Google

Voltage/Frequency: AC:220–240v,50Hz
CRI: >80
Beam Angle: 110°
Wireless Frequency: 2.4Ghz
Wireless Standard: IEEE 802.11 b/g/n
Base: GU10
Body Type: Plastic
Life Span: 30,000-hour
Dimension: 50×57mm

- 16 Million Colors
- APP Remote Control
- Smart Timer Function
- Smart Lighting Adjustment

Model	SKU	Watts	Lumen	Box Qty
VT-5164	2757 RGB+2700K-6400K	5.5W	400	200

Smart LED Dome Light

WORKS WITH alexa

works with Ok Google

Voltage/Frequency: AC:175–265V,50/60Hz
CRI: >80
Beam Angle: 120°
Wireless Frequency: 2.4Ghz
Body Type: Plastic+Metal
Life Span: 20,000-hour
Dimension: Ø:467×70mm

- WarmWhite-DayWhite-White
- APP Remote Control
- Smart Timer Function
- Smart Dimming

Model	SKU	Watts	Lumen	Box Qty
VT-5141	1497 3IN1	40w	2800	5

Smart LED Dome Light

WORKS WITH alexa

works with Ok Google

Voltage/Frequency: AC:175–265V,50/60Hz
CRI: >80
Beam Angle: 120°
Wireless Frequency: 2.4Ghz
Body Type: Plastic+Metal
Life Span: 20,000-hour
Dimension: Ø572.5×70mm

- WarmWhite-DayWhite-White
- APP Remote Control
- Smart Timer Function
- Smart Dimming

Model	SKU	Watts	Lumen	Box Qty
VT-5161	1498 3IN1	60w	4200	5

LED Smart Striplight Kit

WORKS WITH alexa

works with Ok Google

LED Type: SMD
Watt/M: 10w
Current/M: 1.5A
Voltage: DC:12V
lm/M: 1000
lm/LED: 14–16lm
Beam Angle: 120°
IP Rating: IP20
Width: 8mm

Model	SKU	Box Qty
VT-5050 60 EU	2583 RGB 2584 RGB+W	20
VT-5050 60 BS	2585 RGB 2586 RGB+W	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

V-TAC SMART LIGHT

LED Smart Striplight Kit-2IN1

LED Type: SMD
Watt/M: 4w
Current/M: 0.75A
Voltage: DC:12V,50/60Hz
lm/M: 230
lm/LED: NA
Beam Angle: 120°
IP Rating: IP65
Width: 10mm

WORKS WITH alexa

works with Ok Google

IP65 RATING

2 IN 1

Model	SKU	Box Qty
VT-5050 54 EU	2628 RGB+3IN1	20
VT-5050 54 BS	2629 RGB+3IN1	20

NEW

LED Smart Striplight Kit-new

LED Type: SMD
Watt/M: 13W
Current/M: 1.08A
Beam Angle: 120°
IP Rating: IP65
Width: 10mm

WORKS WITH alexa

works with Ok Google

BS PLUG

EU PLUG

IP65 RATING

Model	SKU	Box Qty
VT-5050 90 BS	2699 3IN1	20
VT-5050 90 EU	2910 RGB+3IN1	20



Smart Panel

WORKS WITH alexa

works with Ok Google

Voltage/Frequency: AC:220-240v,50Hz
CRI: >80
Beam Angle: 120°
Wireless Frequency: 2.4GHz
Body Type: Aluminium
Life Span: 20,000-hour
Dimension: 595×595mm

- WarmWhite-DayWhite-White
- APP Remote Control
- Smart Timer Function
- Smart Dimming

Model	SKU	Watts	Lumen	Box Qty
VT-5140	8080 3IN1	40w	4800	5

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

IR Remote Control

•Input: DC:5V/1A
•Wi-Fi Frequency: 2.4Ghz
•Infrared Frequency: 38Khz
•Inrared Range: ≤ 8meters

Easy To Set-Up: Just point your remote to this device, name function on the app, and start managing all IR controls in your home.

Real-Time Control | Multi-Brand | Set Timer | Cloud Panel | Power Save | Smart Scene

Model	SKU	Box Qty
VT-5151	8651	100

Wi-Fi Thermostat

• Power Supply: 95~240 VAC, 50/60Hz
• Fan Relay Amps Resistance: 5A; Inductive: 3A
• Valve Relay Amps Resistance: 3A; Inductive: 1A
• Sensor: NTC 3950, 10K
• Accuracy: +0.5°C
• Set Temp. Range: 5~35°C
• Display Temp. Range: 5~99°C
• Ambient Temp.: 0~45°C
• Ambient Humidity: 5~95%
• RH (Non Condensing)
• Storage Temp.: -5~ 45°C
• Power Consumption: <1.5W
• Timing Error: <1%
• Shell Material: PC + ABS(Fireproof)
• Wire Terminals: Wire 2 × 1.5mm2 or 1 × 2.5mm2
• Protection Class: IP20

Model	SKU	Box Qty
VT-5888	7908	1 pc

Smart Tower Fan

• Power(Watts): 55
• Input Voltage: AC:220~240V,50Hz
• Size(Inches): 46
• Material: ABS
• Speed: 3(Low-Med-High)
• Wind Mode: 3(Normal-Natural-Sleep)
• Timer: 1~15hrs(Max)
• Wireless Frequency: 2.4Ghz
• Remote Control Included

Model	SKU	Box Qty
VT-5566-EU	7927	1
VT-5566-BS	7928	1

V-TAC®
INNOVATIVE LED LIGHTING

V-TAC SMART LIGHT

SMART GYRO ROBOT VACUUM

Digital Robot Cleaning Vacuum with Wi-Fi App and Wireless Remote Control

Multi Cleaner
Hardwood, Tile, Marble & Hard Carpet Floors

SMART CLEAN
Smart, Self-Programmed Cleaning Path Navigation

SMART CONNECT
Wireless Wi-Fi App Remote Control

MOTOR SUCTION POWER
1800 PA

Robot learns the layout of your home and cleans in S path to more efficiently cover large areas on a single charge.

Automatic Return to Dock Base for Self-Charging



WORKS WITH alexa

works with Ok Google

Gyro Robot Vacuum Cleaner

Model	SKU	Box Qty
VT-5555-EU	8650 BLACK EU-PLUG 8649 WHITE EU-PLUG	4
VT-5555-BS	7912 BLACK BS-PLUG 7911 WHITE BS-PLUG	4

- Automatic Robot Vacuum Cleaner
- Keep it Clean: Sweep, Dust & Vacuum
- Versatile & Convenient Floor Clean Ability
- Smart, Self-Programmed Cleaning Path Navigation
- Wi-Fi Wireless Network for Hassle-Free Device Pairing
- Take Control of the Vacuum via Remote Control or App
- Preset Multi-Clean Modes: Auto, Single Room, Edge
- Automatic Return to Dock Base for Self-Charging
- One Button Operation & Auto-Start Activation
- 'Bag-less' Waste Bin Integrated HEPA Filter
- Anti-Fall / Anti-Collision Sensors
- Built-in Rechargeable Battery
- Dual Spinning Side Brushes Captures Dirt & Lifts Debris
- Works on Hardwood, Tile, Marble & Hard Carpet Floors
- Slim Low-Profile Housing Slides Underneath Furniture
- Perfect for the Home or Office

DEKRA TÜV SÜD GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC SMART LIGHT

V-TAC® INNOVATIVE LED LIGHTING

SMART GYRO ROBOT VACUUM

Digital Robot Cleaning Vacuum with Wi-Fi App and Wireless Remote Control

360° LASER

Scanning provides insight into the whole house



Multi Cleaner
Hardwood, Tile, Marble & Hard Carpet Floors

SMART CLEAN
Smart, Self-Programmed Cleaning Path Navigation

SMART CONNECT
Wireless Wi-Fi App Remote Control

3000mAh
Using LG battery

MOTOR SUCTION POWER
2200 PA

Robot learns the layout of your home and cleans in S path to more efficiently cover large areas on a single charge.

Accessories :



Automatic Return to Dock Base for Self-Charging

WORKS WITH alexa

works with Ok Google

Robot Laser Vacuum Cleaner

Model	SKU	Box Qty
VT-5556-B	8992 BLACK EU-PLUG 7933 WHITE EU-PLUG	3

- Automatic Robot Vacuum Cleaner
- Keep it Clean: Sweep, Dust & Vacuum
- 360 Laser scanning provides insight into the whole house
- Smart, Self-Programmed Cleaning Path Navigation
- Wi-Fi Wireless Network for Hassle-Free Device Pairing
- Take Control of the Vacuum via V-TAC App or Alexa and Google Home
- Preset Multi-Clean Modes: Auto, Single Room, Edge
- Automatic Return to Dock Base for Self-Charging
- One Button Operation & Auto-Start Activation
- 'Bag-less' Waste Bin Integrated HEPA Filter
- Anti-Fall / Anti-Collision Sensors
- Built-in Rechargeable Battery
- Dual Spinning Side Brushes Captures Dirt & Lifts Debris
- Works on Hardwood, Tile, Marble & Hard Carpet Floors
- Cleaning area coverage: Up to 120m2 – Dustbin capacity: 600 ml
- Suction Power: Japanese Nidec Motor 2200 PA

V-TAC®
INNOVATIVE LED LIGHTING

V-TAC SMART HOME

Plug-Wi-Fi

Voltage/Frequency: AC: 90-250V,50/60Hz
Wireless Frequency: 2.4GHz
Max Watts: 2200w
Material: PC
On/Off Cycle: 10,000 Times
IP RATING : IP20
Dimension: 110×62×36mm

Model	SKU	Box Qty
VT-5001	8415-EU PLUG 8427-BS PLUG	50

WORKS WITH alexa

works with Ok Google

Mini Plug-Wi-Fi

Voltage/Frequency: AC: 90-250V,50/60Hz
Wireless Frequency: 2.4GHz
Max Watts: 2200w
Material: PC
On/Off Cycle: 10,000 Times
IP RATING : IP20
Dimension: 63×45×30mm

Model	SKU	Box Qty
VT-5002	8416-EU PLUG 8428-BS PLUG	100

WORKS WITH alexa

works with Ok Google

E27 Lamp Holder-Wi-Fi

Voltage/Frequency: AC: 90-250V,50/60Hz
Wireless Frequency: 2.4GHz
Max Watts: 20w(LED Bulb)
Material: PC
On/Off Cycle: 10,000 Times
IP RATING : IP20
Dimension: D:67×02mm

Model	SKU	Box Qty
VT-5007	8421	50

WORKS WITH alexa

works with Ok Google

Wall Socket-Wi-Fi(EU)

Voltage/Frequency: AC: 90-250V,50/60Hz
Wireless Frequency: 2.4GHz
Max Watts: 3500w
Material: PC
On/Off Cycle: 10,000 Times
IP RATING : IP20
Dimension: 86×86×45mm

Model	SKU	Box Qty
VT-5134	8797- BLACK 8798- WHITE	60

WORKS WITH alexa

works with Ok Google

Wall Socket-Wi-Fi(BS)

Voltage/Frequency: AC: 90-250V,50/60Hz
Wireless Frequency: 2.4Ghz
Max Watts: 2900w
Material: PC
On/Off Cycle: 10,000 Times
IP RATING : IP20
Dimension: 146×86×32mm

2 5V/2.1A USB Port

Model	SKU	Box Qty
VT-5017	8446	100

WORKS WITH alexa

works with Ok Google

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC SMART HOME

V-TAC® INNOVATIVE LED LIGHTING

RF433 Gateway

•Input Voltage: 90–250V
•Max Current:13A
•Wireless Standard Wi-Fi 2.4Ghz
•Material:PC
•Power supply: Micro USB 5V/1A
•RF:433MHz
•Control Mode:VTAC Smartphone App
•Size: 110×25mm

RF Gateway is a bridge converting any device operated with RF functionality into a smart device. One RF Bridge supports a maximum of 4 RF Remotes.

Model	SKU	Box Qty
VT-5144	8466	100

WORKS WITH alexa works with Ok Google

Temperature Humidity Scheduler

• Max. Current-16A
• Material: PC
• Input: AC:90–250V,50/60Hz
• 2.4Ghz Wi-Fi
• Smart Link technology
• Remote control connected appliance
• Remotely monitor Temperature & Humidity
• DIY your favorite scenes
• Size: 137×45×28mm

Model	SKU	Box Qty
VT-5145	8467	100

WORKS WITH alexa works with Ok Google

Temperature & Humidity Sensor

• Material: ABS
• Temperature Humidity: 0~99.9%RH
• Measuring Range: -40~+80°C
• Wire Length: 0.5 Meter
• Compatible with V-TAC Temperature Humidity scheduler (Not included)"
• Size: 61×26mm(50cm Wire Length)

Model	SKU	Box Qty
VT-5146	8468	200

WORKS WITH alexa works with Ok Google

Waterproof Temperature Probe

• Material: ABS
• Measuring Range: -50~+125°C
• Wire Length: 1 Meter
• Waterproof – IP66 Rated
• Compatible with V-TAC Temperature Humidity scheduler (Not included)
• Size: 70×70×1000mm

Model	SKU	Box Qty
VT-5147	8469	200

WORKS WITH alexa works with Ok Google

LED BULBS

The definition of sustainability: sharing the incandescent bulb's design and built for maximum efficiency, V-TAC's extensive range of LED thermoplastic bulb series are your ideal choice for any kind of lighting requirement.

Key Features

- Lasts 20 times longer than Standard Bulbs
- Broad Range of holders
- Uses 80% less energy than Standard Bulbs
- Excellent Heat Radiation Efficiency
- Customized exterior for stronger body
- High Power LED Chips
- Non – Flickering
- Dimmable & Non Dimmable options

Application

Perfect choice for Hotels, Bars, Commercial & Residential Lighting and Exhibition Stands.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED BULBS High CRI Bulbs

Our highest CRI rating yet – V-TAC's new generation of CRI>95 spotlights & bulbs is a must in commercial lighting. A CRI of 85 to 90 percent is considered good at color rendering, while a CRI of 90 percent or above is considered excellent. A CRI index of 90 or above should be used to achieve accurate color discrimination.

A red apple appears red because it reflects red wavelengths, but absorbs others. But not all white light sources have the same amount of red wavelength light. As a result, under different light sources, a red apple can reflect different amounts of red light, changing its appearance.

- Outstandingly engineered to show only the truest of colors
- Emphasize vivid colors to increase the appeal of any product to its consumers and contribute to purchasing decisions
- Recommended for restaurants, apparel shops, supermarkets, and other retail areas

REAL COLOR SERIES CRI >95

Witness the True to Life Colors

LED P45 Bulb CRI>95

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >95
- 180° Beam Angle

REAL COLOR SERIES CRI >95

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2236	7488 – 2700K WARM WHITE 7489 – 4000K DAY WHITE 7490 – 6400K WHITE	5.5w	40w	470	200

LED G45 Bulb CRI>95

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >95
- 180° Beam Angle



REAL COLOR SERIES CRI >95

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2216	7491 – 2700K WARM WHITE 7492 – 4000K DAY WHITE 7493 – 6400K WHITE	5.5w	40w	470	200

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Candle Bulb CRI>

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >95
- 200° Beam Angle



REAL COLOR SERIES CRI >95

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2226	7494 - 2700K WARM WHITE 7495 - 4000K DAY WHITE 7496 - 6400K WHITE	5.5w	40w	470	200

LED A60 Bulb CRI>95

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >95
- 200° Beam Angle



REAL COLOR SERIES CRI >95

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2210	7479 - 2700K WARM WHITE 7480 - 4000K DAY WHITE 7481 - 6400K WHITE	10w	60w	806	100

LED A60 Bulb CRI>96

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >95
- 200° Beam Angle



REAL COLOR SERIES CRI >95

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2212	7482 - 2700K WARM WHITE 7483 - 4000K DAY WHITE 7484 - 6400K WHITE	12w	75w	1055	100

LED A65 Bulb CRI>97

- E27 Base
- A65 Shape
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >95
- 200° Beam Angle



REAL COLOR SERIES CRI >95

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2217	7485 - 2700K WARM WHITE 7486 - 4000K DAY WHITE 7487 - 6400K WHITE	17w	100w	1521	100

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC SMART

V-TAC®
INNOVATIVE LED LIGHTING

LED BULBS

Smart Bulbs

This smart bulb range includes lamps with remote controllable dimming & colour changing features, and automating sensors for a next-level approach to efficient indoor lighting.Includes standard bulb shapes (Candle, Golf, P45, A60) and base variations

- Colour Changing Modes: Hopping, gradient
- Environmentally friendly: No UV radiation and mercury free
- Suitable for mood lighting, residential, bars, hotels, restaurants etc.
- Environmentally friendly: No UV radiation and mercury-free



RF Remote Control Bulb

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.4
- CRI: >80

- RF Control 6-8M Range
- Switch on/off the light
- 16 steps dimming
- 16 colors selection
- Auto Color change Mode

RGB

DIMMABLE WITH RF REMOTE



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2214	2769 -RGB+3000K 2770 -RGB+4000K 2771 -RGB+6400K	3.5w	30w	320	200
VT-2214-N-1	2926 -RGB+3000K 2929 -RGB+4000K	4.8w	30w	320	200

RF Remote Control Bulb

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.4
- CRI: >80

- RF Control 6-8M Range
- Switch on/off the light
- 16 steps dimming
- 16 colors selection
- Auto Color change Mode

RGB

DIMMABLE WITH RF REMOTE



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2224	2772 -RGB+3000K 2773 -RGB+4000K 2774 -RGB+6400K	3.5w	30w	320	200

RF Remote Control Bulb

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.4
- CRI: >80

- RF Control 6-8M Range
- Switch on/off the light
- 16 steps dimming
- 16 colors selection
- Auto Color change Mode

RGB

DIMMABLE WITH RF REMOTE

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2234	2775 -RGB+3000K 2776 -RGB+4000K 2777 -RGB+6400K	3.5w	30w	320	200
VT-2234-N	212775 - RGB+3000K WARM WHITE	4.8W	40w	470	200

V-TAC®
INNOVATIVE LED LIGHTING

V-TAC SMART

IR Remote Control Bulb

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

- RF Control 6-8M Range
- Switch on/off the light
- 16 steps dimming
- 16 colors selection
- Auto Color change Mode

RGB

DIMMABLE WITH IR REMOTE

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2022	7121 - 2700K WARM WHITE 7150 - 4000K DAY WHITE 7151 - 6400K WHITE	6w	40w	470	100
VT-2022-N	217121 - 3000K WARM WHITE	4.8W	40w	470	100

RF Remote Control Bulb

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

- RF Control 6-8M Range
- Switch on/off the light
- 16 steps dimming
- 16 colors selection
- Auto Color change Mode

RGB

DIMMABLE WITH RF REMOTE



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2229	2766 -RGB+3000K 2767 -RGB+4000K 2768 -RGB+6400K	9w	60w	806	100
VT-2229-N	212766 - RGB+3000K WARM WHITE	4.8W	60w	806	100

RF Remote Control Bulb

- E27 Base
- A60 Shape
- AC:220-240V, 50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

- RF Control 6-8M Range
- Switch on/off the light
- 16 steps dimming
- 16 colors selection
- Auto Color change Mode

RGB

DIMMABLE WITH RF REMOTE

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2229-N-1	2925 -RGB+3000K 2928 -RGB+4000K	8.5w	60w	806	100

3 Step Dimming Bulb

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

Smart Dimming Technology Without A Dimmer!
At the click of button, change the lighting Power from 100% to 50% and if need to Reduce more click again to go to 15%.

3 STEP DIMMING

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2011	4448 - 4000K DAY WHITE 4449 - 6400K WHITE	9w	60w	806	100

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC SMART

V-TAC® INNOVATIVE LED LIGHTING

3 Step Dimming Bulb 2Pc Blister Pack

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

Smart Dimming Technology Without A Dimmer!
At the click of button, change the lighting Power from 100% to 50% and if need to Reduce more click again to go to 15%.

3 STEP DIMMING

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2129	7288 - 2700K WARM WHITE 7289 - 4000K DAY WHITE 7290 - 6400K WHITE	9w	60w	806	25

Color Changing Bulb

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

1. Switch the light on for cool white.
2. Turn the Switch off and on again for warm white.
3. Turn the Switch off and on again for day white.
4. Switch between these to select your ideal colour.

COLOR CHANGING

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2119	7317 - 3 IN 1	9w	60w	806	100

Color Changing Bulb 2Pc Blister Pack

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

1. Switch the light on for cool white.
2. Turn the Switch off and on again for warm white.
3. Turn the Switch off and on again for day white.
4. Switch between these to select your ideal colour.

COLOR CHANGING

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2149	7309 - 3 IN 1	9w	60w	806	25

Sensor Bulb

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

Our smart sensor bulbs have built-in photocells which transmit the signal to the light source and smartly save power by switching into Light mode, enabling energy efficiency and reduced power consumption when required.

SENSOR LED BULB

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2016	4459 - 2700K WARM WHITE 4460 - 4000K DAY WHITE 4461 - 6000K WHITE	9w	60w	806	100

V-TAC®
INNOVATIVE LED LIGHTING

V-TAC SMART

Sensor Bulb 2Pc Blister Pack

SENSOR LED BULB

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

Our smart sensor bulbs have built-in photocells which transmit the signal to the light source and smartly save power by switching into Light mode, enabling energy efficiency and reduced power consumption when required.

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2109	7285 - 2700K WARM WHITE	9w	60w	806	25

Microwave Sensor Bulb

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

1. Auto Switch on at dusk and switches off at dawn.
2. Built-in Daylight Sensor
3. Automatically switches On when the room light is less
4. Light stays for 60 seconds upon detection of movement

AUTOMATIC ON DUSK | AUTOMATIC OFF DAWN

MICROWAVE SENSOR BULB
8-10 meter detection range



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2219	2760 -3000K WARM WHITE 2761 -4000K DAY WHITE 2762 -6400K WHITE	9w	60w	806	100
VT-2211	2763 -3000K WARM WHITE 2764 -4000K DAY WHITE 2765 -6400K WHITE	11w	75w	1055	100

LED BULBS

LED Candle Bulbs

Our candle-shaped LED bulbs are energy-efficient replacements for traditional halogen lamps that come with chandeliers, wall lights, desk lamps, and other decorative lighting fixtures.

- Includes E14 and E27 base variations
- No UV radiation and mercury-free

LED Flame Candle

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1818TP	4164 - 2700K WARM WHITE 4156 - 4000K DAY WHITE	4w	30w	320	200

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Candle Bulb

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1818	4216 - 2700K WARM WHITE 4166 - 4000K DAY WHITE 4122 - 6400K WHITE	4w	30w	320	200
VT-1818-N	214216 - 3000K WARM WHITE 214166 - 4000K DAY WHITE 214122 - 6500K WHITE	3.7W	25w	320	200

LED Candle Bulb

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1855	42151 - 2700K WARM WHITE 42581 - 4000K DAY WHITE 42411 - 6400K WHITE	5.5w	40w	470	200
VT-1855-N	2142151 - 3000K WARM WHITE 2142581 - 4000K DAY WHITE 2142411 - 6500K WHITE	4.5w	40w	470	200

LED Candle E27 Bulb

- E27 Base
- Candle Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1821N	43421 - 2700K WARM WHITE 43431 - 4000K DAY WHITE 43441 - 6400K WHITE	5.5w	40w	470	200
VT-1821N-N	2143421 - 3000K WARM WHITE 2143431 - 4000K DAY WHITE 2143441 - 6500K WHITE	4.5W	40w	470	200

2Pc Blister Packing

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2106	7291 - 2700K WARM WHITE 7293 - 6400K WHITE	5.5w	40w	470	50

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Candle 3Pc Pack

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2076	7263 – 2700K WARM WHITE 7264 – 4000K DAY WHITE 7265 – 6400K WHITE	5.5w	40w	470	60
VT-2076-N	217263 – 3000K WARM WHITE 217264 – 4000K DAY WHITE 217265 – 6500K WHITE	4.5W	40w	470	180

LED Candle 6Pc Pack

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 200 Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2246	2736 – 2700K WARM WHITE 2737 – 4000K DAY WHITE 2738 – 6400K WHITE	5.5w	40w	470	30
VT-2246-N	212738 – 6500K WHITE	4.5W	40w	470	180

LED BULBS

LED G45 Bulbs

Small, round, 45mm golf bulbs usually used in vanities, bedside lamps, desk lamps, and other fixtures in residential spaces.

- Available in blister packs and 3/6pc multipacks
- No UV radiation and mercury-free



LED G45 Bulb

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1830	4160 – 2700K WARM WHITE 4162 – 4000K DAY WHITE 4207 – 6400K WHITE	4w	30w	320	200
VT-1830-N	214160 – 3000K WARM WHITE 214162 – 4000K DAY WHITE 214207 – 6500K WHITE	3.7W	25w	320	200

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED G45 Bulb

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1879N	7407 - 2700K WARM WHITE 7408 - 4000K DAY WHITE 7409 - 6400K WHITE	5.5w	40w	470	200
VT-1879N-N	217407 - 3000K WARM WHITE 217408 - 4000K DAY WHITE 217409 - 6500K WHITE	4.5W	40w	470	200

LED G45 Blister Pack

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2166	7360 - 2700K WARM WHITE	5.5w	40w	470	50

LED G45 3Pc Pack

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2176	7362 - 2700K WARM WHITE 7363 - 4000K DAY WHITE 7364 - 6400K WHITE	5.5w	40w	470	60
VT-2176-N	217362 - 3000K WARM WHITE 217363 - 4000K DAY WHITE	4.5W	40w	470	180

LED G45 6Pc Pack

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2256	2730 - 2700K WARM WHITE 2731 - 4000K DAY WHITE 2732 - 6400K WHITE	5.5w	40w	470	30
VT-2256-N	212730 - 3000K WARM WHITE	4.5W	40w	470	180

V-TAC®
INNOVATIVE LED LIGHTING

V-TAC SMART

LED BULBS
LED P45 Bulbs

Ball-shaped E14 base-type bulbs usually used in chandeliers, table lamps, wall lamps, and other decorative lighting fixtures in residential and commercial spaces.

- Available in blister packs and 3/6pc multipacks
- No UV radiation and mercury-free

LED P45 Bulb

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1819	4123 - 2700K WARM WHITE 4174 - DAY WHITE 4124 - 6400K WHITE	4w	30w	320	200
VT-1819-N	214123 - 3000K WARM WHITE 214174 - 4000K DAY WHITE 214124 - 6500K WHITE	3.7W	25w	320	200

LED P45 Bulb

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1880N	42501 - 2700K WARM WHITE 42511 - 4000K DAY WHITE 42521 - 6400K WHITE	5.5w	40w	470	200
VT-1880N-N	2142501 - 3000K WARM WHITE 2142511 - 4000K DAY WHITE 2142521 - 6500K WHITE	4.5W	40w	470	200

LED P45 Blister Pack

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2146	7355 - 2700K WARM WHITE 7356 - 4000K DAY WHITE	5.5w	40w	470	50

DEKRA TÜV SÜD CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED P45 3Pc Pack

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2156	7357 – 2700K WARM WHITE 7358 – 4000K DAY WHITE 7359 – 6400K WHITE	5.5w	40w	470	60
VT-2156-N	217357 – 3000K WARM WHITE 217359 – 6500K WHITE	4.5W	40w	470	180

LED P45 6Pc Pack

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 180° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2266	2733 – 2700K WARM WHITE 2734 – 4000K DAY WHITE 2735 – 6400K WHITE	5.5w	40w	470	30
VT-2266-N	212733 – 3000K WARM WHITE 212734 – 4000K DAY WHITE	4.5W	40w	470	180

LED BULBS

LED Thermoplastic Bulbs

Our extensive range of classic, thermoplastic GLS bulbs are efficient replacements for traditional incandescent light fittings in both indoor and outdoor locations.

- Includes standard base variations (E27 and B22)
- Varying watts and sizes (A60, A65, and A80) available
- Available in blister packs and 3/6pc multipacks

LED A60-B22 Bulb

- B22 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

BAYONET HOLDER



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2189	7422 – 2700K WARM WHITE 7402 – 4000K DAY WHITE 7403 – 6400K WHITE	9w	60w	806	100
VT-2189-N	217422 – 3000K WARM WHITE 217402 – 4000K DAY WHITE 217403 – 6500K WHITE	8.5W	60w	806	100

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED A60-B22 Bulb 3Pc Pack

- B22 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

BAYONET HOLDER

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2069-3PC	7246 - 2700K WARM WHITE	9w	60w	806	20
VT-2069-3PC-N	217246 - 3000K WARM WHITE	8.5W	60w	806	120

LED A60-E27 Bulb

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2099	7260 - 2700K WARM WHITE 7261 - 4000K DAY WHITE 7262 - 6400K WHITE	9w	60w	806	100
VT-2099-N	217260 - 3000K WARM WHITE 217261 - 4000K DAY WHITE 217262 - 6500K WHITE	8.5W	60w	806	200

LED A60-E27 Bulb 3Pc Pack

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1900	7240 - 2700K WARM WHITE 7241 - 4000K DAY WHITE 7242 - 6400K WHITE	9w	60w	806	20
VT-1900-N	217240 - 3000K WARM WHITE 217241 - 4000K DAY WHITE 217242 - 6500K WHITE	8.5W	60w	806	120

LED A60-E27 Bulb

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2112	7350 - 2700K WARM WHITE 7349 - 4000K DAY WHITE 7351 - 6400K WHITE	11w	75w	1055	100

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED A60-E27 Bulb 2Pc Blister Pack

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2111	7297 - 2700K WARM WHITE	11w	75w	1055	25

LED A60-E27 Bulb 3Pc Pack

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2113	7352 - 2700K WARM WHITE 7353 - 4000K DAY WHITE 7354 - 6400K WHITE	11w	75w	1055	40
VT-2113-N	217353 - 4000K DAY WHITE 217354 - 6500K WHITE	10.5W	75w	1055	120

LED A65-B22 Bulb

- B22 Base
- A65 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

BAYONET HOLDER



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2015-B22	7229 - 2700K WARM WHITE	15w	90w	1350	100
VT-2015-B22-N	217229 - 3000K WARM WHITE	15W	100w	1521	100

LED A65-E27 Bulb

- E27 Base
- A65 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2015-E27	4453 - 2700K WARM WHITE 4454 - 4000K DAY WHITE 4455 - 6400K WHITE	15w	90w	1350	100

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Bulbs-A65-E27-2Pc Blister Pack

- E27 Base
- A65 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2117	7300 - 2700K WARM WHITE 7302 - 6400K WHITE	15w	90w	1350	25

LED A65-E27 Bulb 3PC Pack

- E27 Base
- A65 Shape
- AC:220-240V, 50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2015-3PC	2819 - 2700K WARM WHITE 2820 - 4000K DAY WHITE 2818 - 6400K WHITE	15W	90w	1350	120

LED A65-E27 Bulb

- E27 Base
- A65 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2017	4456 - 2700K WARM WHITE 4457 - 4000K DAY WHITE 4458 - 6400K WHITE	17w	100w	1521	100

LED A80-E27 Bulb

- E27 Base
- A80 Shape
- AC:220-240V, 50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2218	2707 - 3000K WARM WHITE 2708 - 4000K DAY WHITE 2709 - 6400K WHITE	18w	125w	2000	50

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED A80-E27 Bulb

- E27 Base
- A80 Shape
- AC:220-240V, 50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2220	2710 - 3000K WARM WHITE	20w	150w	2452	20

LED BULBS

Special Utility Bulbs

Includes our innovative range of double-ended R7S bulbs, PAR bulbs, Globe, UFO bulbs, and T37 bulbs that are usually used for task and general lighting purposes in residential and commercial areas.

LED Bulbs-R7S

- R7S Base
- R7S Shape
- AC:220-240V,50Hz
- 360° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1990	4390 - 6400K WHITE	10w	60w	1000	100

LED Bulbs-R7S

- R7S Base
- R7S Shape
- AC:220-240V,50Hz
- 360° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2237	2713 - 3000K WARM WHITE 2714 - 4000K DAY WHITE 2715 - 6400K WHITE	7w	45w	580	200

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Bulbs-R7S

- R7S Base
- R7S Shape
- AC:220-240V,50Hz
- 360° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2213	2716 - 3000K WARM WHITE 2717 - 4000K DAY WHITE 2718 - 6400K WHITE	13w	80w	1200	200

LED R7S Ceramic Bulb

- R7S Base
- R7S Shape
- AC:220-240V,50Hz
- 360° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2118	2834 - 3000K WARM WHITE 2835 - 4000K DAY WHITE 2836 - 6400K WHITE	18W	150w	2140	100

LED PAR38 Bulb

- E27 Base
- PAR38 Shape
- AC:180-240V,50/60Hz
- 40° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1125-G	4418 - GREEN 4419 - RED 4420 - BLUE	15w	100w	1200	40

LED PAR38 Bulb

- E27 Base
- PAR38 Shape
- AC:220-240V,50/60Hz
- 100° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1227	45691 - 4000K DAY WHITE	17w	95w	1300	40

DEKRA TÜV SÜD GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Globe Bulb G95

- E27 Base
- G95 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1893	4276 - 3000K WARM WHITE 4277 - 4000K DAY WHITE 4278 - 6400K WHITE	10w	60w	810	12

LED Globe Bulbs G120

DIMMABLE LIGHT CONTROL

- E27 Base
- G120 Shape
- AC:220-240V,50Hz
- 200° Beam Angle
- PF: >0.7
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1884D	7194 - 4000K DAY WHITE 7195 - 6000K WHITE	13w	75w	1055	12

LED Bulb T37-E14

- E14 Base
- T37 Shape
- AC:220-240V,50/60Hz
- 230° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2029	7173 - 2700K WARM WHITE	9w	50w	750	200

UFO-F150-E27

- E27 Base
- F150 Shape
- AC:220-240V,50/60Hz
- 120° Beam Angle
- PF: >0.9
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2136	7164 - 3000K WARM WHITE 7166 - 6400K WHITE	36w	190w	3240	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED FILAMENT BULBS

- Classic Vintage Design
- Available in Amber cover, White cover, and Frost cover
- Lasts 20 times longer than Standard Bulbs
- Low power consumption
- No mercury, environmental protection
- Uses 80% less energy than Standard Bulbs
- Excellent Heat Radiation Efficiency
- Dimmable & Non-Dimmable options

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS COMPLIANT CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

LED 3D Filament Bulb A60

- E27 Base
- A60 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.45
- CRI: >80

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2203	2704 - 3000K WARM WHITE	3w	NA	20	100
VT-2203-N	212704 - 3000K WARM WHITE	3w	NA	20	100

LED 3D Filament Bulb ST64

- E27 Base
- ST64 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.45
- CRI: >80

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2223	2705 - 3000K WARM WHITE	3w	NA	25	100
VT-2223-N	212705 - 3000K WARM WHITE	3w	NA	25	100

LED 3D Filament Bulb G125

- E27 Base
- G125 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.45
- CRI: >80

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2233	2706 - 3000K WARM WHITE	3w	NA	40	50
VT-2233-N	212706 - 3000K WARM WHITE	3w	NA	40	20

Filament-G125-E27

- E27 Base
- G125 Shape
- AC:220-240V, 50Hz
- 300° Beam Angle
- PF: >0.45
- CRI: >80

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2205	2700 - 2200K WARM WHITE	5w	30w	70	50

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Amber-G165-E27

- E27 Base
- G165 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.45
- CRI: >80

DIMMABLE LIGHT CONTROL

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2159	45641 - 2200K WARM WHITE	8w	NA	620	6

Smoky-G165-E27

- E27 Base
- G165 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.45
- CRI: >80

DIMMABLE LIGHT CONTROL

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2159-S	45651 - 2200K WARM WHITE	8w	NA	240	6



Amber-S180-E27

- E27 Base
- S180 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.45
- CRI: >80

DIMMABLE LIGHT CONTROL

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2169	45661 - 2200K WARM WHITE	8w	NA	620	6

Smoky-S180-E27

- E27 Base
- S180 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.45
- CRI: >80

DIMMABLE LIGHT CONTROL

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2169-S	45671 - 2200K WARM WHITE	8w	NA	240	6

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Filament-G100-E27

- E27 Base
- G100 Shape
- AC:170-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2235	2748 - 2200K WARM WHITE	5w	25w	250	20

Amber Cover-T60-E27

- E27 Base
- T60 Shape
- AC:170-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2245	2749 - 2200K WARM WHITE	5w	25w	250	35

Filament-T180-E27

- E27 Base
- T180 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

DECORATIVE BULBS

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2308	2790 -2200K WARM WHITE	8w	55w	620	6
VT-2308-N	212790 -1800K WARM WHITE	8w	55w	620	12

Filament-A165-E27

- E27 Base
- A165 Shape
- AC:220-240V,50Hz
- 340° Beam Angle
- PF: >0.5
- CRI: >80

DIMMABLE LIGHT CONTROL

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2138D	7461 - 2000K WARM WHITE	8w	40w	500	6

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Filament-G200-E27

- E27 Base
- G200 Shape
- AC:220-240V,50Hz
- 340° Beam Angle
- PF: >0.5
- CRI: >80

DIMMABLE LIGHT CONTROL

DECORATIVE BULBS

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2158D	7462 - 2000K WARM WHITE	8w	40w	500	4
VT-2158D-N	217462 - 2000K WARM WHITE	8w	40w	500	12

Filament-BF180-E27

- E27 Base
- BF180 Shape
- AC:220-240V,50Hz
- 340° Beam Angle
- PF: >0.5
- CRI: >80

DIMMABLE LIGHT CONTROL

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2168D	7463 - 2000K WARM WHITE	8w	40w	500	6
VT-2178D	7464 - 2000K WARM WHITE	8w	50w	600	6

Smoky Filament-S200-E27

- E27 Base
- S200 Shape
- AC:220-240V,50Hz
- 340° Beam Angle
- PF: >0.5
- CRI: >80

DIMMABLE LIGHT CONTROL

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2188D	7465 - 2000K WARM WHITE	8w	30w	350	4
VT-2188D-N	217465 - 1800K WARM WHITE	8w	30w	350	12

Filament-R125-E27

- E27 Base
- R125 Shape
- AC:220-240V,50Hz
- 110° Beam Angle
- PF: >0.5
- CRI: >80

DIMMABLE LIGHT CONTROL

DECORATIVE BULBS



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2198D	7466 - 2700K WARM WHITE 7467 - 4000K DAY WHITE 7468 - 6500K WHITE	8w	50w	600	24

DEKRA TUV SUD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Amber Cover -LED Filament Bulbs

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2154	7335 - 2200K WARM WHITE	4w	40w	250	50
VT-2154-N	217335 - 1800K WARM WHITE	4w	40w	220	100

Filament-A60-E27

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2164	7336 - 2700K WARM WHITE	4w	40w	300	50
VT-2164-N	217336 - 3000K WARM WHITE	4w	40w	300	100

Amber Cover -Filament-A60-E27

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1954	4498 - 2200K WARM WHITE	4w	35w	350	50
VT-1958	4472 - 2200K WARM WHITE	8w	60w	720	50

Amber Cover -Filament-A67-E27

- E27 Base
- A67 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2028	7157 - 2200K WARM WHITE	10w	65w	900	50
VT-2028-N	217157 - 2200K WARM WHITE	10w	65w	950	100

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Amber Filament-A70-E27

- E27 Base
- A70 Shape
- AC:220-240V,50Hz
- 330° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2123	7457 - 2200K WARM WHITE	12.5w	85w	1240	50
VT-2123-N	217457 - 2200K WARM WHITE	12w	85w	1350	100

Filament-ST64-E27

- E27 Base
- ST64 Shape
- AC:220-240V, 50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2185	7474 - 1800K WARM WHITE	4w	20w	200	50
VT-2185-N	217474 - 1800K WARM WHITE	4w	20w	200	100

Filament-ST64-E27

- E27 Base
- ST64 Shape
- AC:220-240V, 50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1964	4361 - 2200 WARM WHITE	4W	40w	350	50
VT-1964-N	214361 - 2200 WARM WHITE	4W	40w	350	100

Amber Cover -Filament-ST64-B22

- B22 Base
- ST64 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

DIMMABLE
LIGHT CONTROL

BAYONET
HOLDER

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2145D	7420 - 2200K WARM WHITE	4w	25w	350	100

DEKRA TUV SUD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Amber Cover -Filament-ST64-E27

- E27 Base
- ST64 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2065	7218 - 2200K WARM WHITE	5w	30w	300	100
VT-2065-N	217218 - 1800K WARM WHITE	4.8w	30w	280	100

Amber Cover -Filament-ST64-E27

- E27 Base
- ST64 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2066	7220 - 2200K WARM WHITE	5w	30w	300	100
VT-2066-N	217220 - 2200K WARM WHITE	4.8w	30w	280	100

Amber Cover -Filament-ST64-E27

DIMMABLE LIGHT CONTROL

- E27 Base
- ST64 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2065D	7416 - 2200K WARM WHITE	5w	30w	300	100
VT-2065D-N	217416 - 1800K WARM WHITE	4.8w	30w	250	100

Amber Cover -Filament-ST64-E27

- E27 Base
- ST64 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1966	4362 - 2200K WARM WHITE	6w	45w	500	50
VT-1966-N	214362 - 2200K WARM WHITE	6w	45w	550	100

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Amber Cover -Filament-ST64-E27

- E27 Base
- ST64 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1968	4421 - 2200K WARM WHITE	8w	60w	700	50
VT-1968-N	214421 - 2200K WARM WHITE	8w	60w	720	100

Amber Cover -Filament-Globe-E27

- E27 Base
- G80 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2004	7148 - 2200K WARM WHITE	4w	35w	400	100
VT-2004-N	217148 - 2200K WARM WHITE	4w	35w	400	100

Amber Cover -Filament-Globe-E27

- E27 Base
- G95 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2024	7146 - 2200K WARM WHITE	4w	35w	350	50
VT-2024-N	217146 - 2200K WARM WHITE	4w	35w	350	20

Amber Cover -Filament-Globe-E27

- E27 Base
- G95 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2075	7217 - 2200K WARM WHITE	5w	30w	300	50
VT-2075-N	217217 - 1800K WARM WHITE	4.8w	30w	280	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Amber Cover -Filament-Globe-E27

DIMMABLE LIGHT CONTROL

- E27 Base
- G95 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.7
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2026D	7156 - 2200K WARM WHITE	6w	50w	500	12

Amber Cover -Filament-Globe-E27

- E27 Base
- G95 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2027	7147 - 2200K WARM WHITE	7w	60w	700	50
VT-2027-N	217147 - 2200K WARM WHITE	7w	60w	700	20

Amber Cover -Filament-Globe-E27

- E27 Base
- G95 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2019	7145 - 2200K WARM WHITE	8w	65w	700	50
VT-2019-N	217145 - 2200K WARM WHITE	8w	65w	700	20

Filament-Globe-E27

- E27 Base
- G125 Shape
- AC:220-240V, 50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2195	7475 - 1800K WARM WHITE	4w	20w	200	20
VT-2195-N	217475 - 1800K WARM WHITE	4w	20w	200	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Amber Cover -Filament-Globe-E27

- E27 Base
- G125 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1956	4473 - 2200K WARM WHITE	4w	55w	350	12
VT-1956-N	214473 - 2200K WARM WHITE	6w	55w	550	20

Amber Cover -Filament-Globe-E27

- E27 Base
- G125 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2085	7216 - 2200K WARM WHITE	5w	30w	300	20
VT-2085-N	217216 - 1800K WARM WHITE	4.8w	30w	280	20

Amber Cover -Filament-Globe-E27

DIMMABLE
LIGHT CONTROL

- E27 Base
- G125 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2085D	7415 - 2200K WARM WHITE	5w	30w	300	20
VT-2085D-N	217415 - 1800K WARM WHITE	4.8w	30w	250	20

Amber Cover -Filament-Globe-E27

- E27 Base
- G125 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >70

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2126	7328 - 2200K WARM WHITE	6w	55w	480	100
VT-2126-N	217328 - 1800K WARM WHITE	6w	55w	380	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Amber Cover -Filament-Globe-E27

DIMMABLE LIGHT CONTROL

- E27 Base
- G125 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.7
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2018D	7155 - 2200K WARM WHITE	8w	60w	700	12
VT-2018D-N	217155 - 2200K WARM WHITE	8w	60w	700	20

Filament-G125-E27

- E27 Base
- G125 Shape
- AC:220-240V,50Hz
- 330° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2153	7456 - 2200K WARM WHITE	12.5w	85w	1240	25
VT-2153-N	217456 - 2200K WARM WHITE	12w	85w	1350	20



Amber Cover -Filament-T30-E27

- E27 Base
- T30 Shape
- AC:220-240V, 50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2162	7473 - 1800K WARM WHITE	2w	9w	65	100
VT-2162-N	217473 - 1800K WARM WHITE	2w	9w	65	100

Amber Cover -Filament-T30-E27

- E27 Base
- T30 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2052	7252 - 2200K WARM WHITE	2w	20w	200	100

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Amber Cover -Filaments-T30-E27

- E27 Base
- T30 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2005	7142 - 2200K WARM WHITE	5w	45w	500	100
VT-2005-N	217142 - 2200K WARM WHITE	5w	45w	500	100

Amber Cover -Filaments-T30-E27

- E27 Base
- T30 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2006	7143 - 2200K WARM WHITE	6w	50w	600	100
VT-2006-N	217143 - 2200K WARM WHITE	6w	50w	600	100

Amber Cover -Filaments-T30-E27

- E27 Base
- T30 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2008	7144 - 2200K WARM WHITE	7w	60w	700	100
VT-2008-N	217144 - 2200K WARM WHITE	7w	60w	700	100

Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V, 50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2152	7472 - 1800K WARM WHITE	2w	9w	65	200
VT-2152-N	217472 - 1800K WARM WHITE	2w	9w	65	100

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Amber Cover -Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1955	7113 - 2200K WARM WHITE	4w	40w	350	100
VT-1955-N	217113 - 2200K WARM WHITE	4w	40w	350	100

Amber Cover -Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1949	7114 - 2200K WARM WHITE	4w	35w	350	100
VT-1949-N	217114 - 2200K WARM WHITE	4w	35w	350	100

Amber Cover -Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1948	7115 - 2200K WARM WHITE	4w	35w	350	100
VT-1948-N	217115 - 2200K WARM WHITE	4w	35w	350	100

Amber Cover -Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1947	7116 - 2200K WARM WHITE	4w	35w	350	100
VT-1947-N	217116 - 2200K WARM WHITE	4w	35w	350	100

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Amber Cover -Filament-G45-E27

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1957-N	217100 - 2200K WARM WHITE	4w	30w	350	100

Amber Cover -Filament-P45-E14

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1953	4499 - 2200K WARM WHITE	4W	30w	350	100
VT-1953-N	214499 - 2200K WARM WHITE	4W	30w	350	100

Cross Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1924C	71031 - 6400K WHITE	4w	35w	350	100

Frost Cover -Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1937	4479 - 6400K WHITE	4w	40w	400	100

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Frost Cover -Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1923	7112 - 6400K WHITE	4w	40w	400	100

Frost Cover -Filament-Candle-E14

DIMMABLE LIGHT CONTROL

- E14 Base
- Candle Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2056D	7177 - 2700K WARM WHITE	4w	35w	350	100

Frost Cover -Filament-A60-E27

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1934	4486 - 2700K WARM WHITE 4487 - 4000K DAY WHITE 4488 - 6400K WHITE	4w	40w	400	50

Frost Cover -Filament-A60-E27

- E27 Base
- A60 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2045	7178 - 2700K WARM WHITE 7179 - 4000K DAY WHITE 7180 - 6400K WHITE	5w	50w	600	50

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Frost Cover -Filament-A60-E27

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1935C	44801 - 2700K WARM WHITE	6w	55w	660	50

Frost Cover -Filament-A60-E27

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1935	4482 - 6400K WHITE	6w	55w	660	50

Frost Cover -Filament-A60-E27

- E27 Base
- A60 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2047	7181 - 2700K WARM WHITE 7183 - 6400K WHITE	7w	60w	840	50

Frost Cover -Filament-A60-E27

- E27 Base
- A60 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2047C	71811 - 2700K WARM WHITE	7w	60w	840	50

DEKRA TUV SUD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Frost Cover -Filament-A67-E27

- E27 Base
- A67 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1938	4483 - 2700K WARM WHITE 4484 - 4000K DAY WHITE 4485 - 6400K WHITE	8w	60w	800	50

Frost Cover -Filament-A67-E27

- E27 Base
- A67 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2023	7154 - 6400K WHITE	10w	75w	1055	50

Frost Cover -Filament-A67-E27

- E27 Base
- A67 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2049	7184 - 2700K WARM WHITE 7186 - 6400K WHITE	9w	80w	1100	50

Frost Cover -Filament-Globe-E27

- E27 Base
- G95 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2057	7187 - 2700K WARM WHITE 7188 - 6400K WHITE	7w	60w	840	12

DEKRA TÜV SÜD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Frost Cover -Filament-Globe-E27

- E27 Base
- G125 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2067	7189 - 2700K WARM WHITE 7190 - 6400K WHITE	7w	60w	840	12

Frost Cover -Filament-Globe-E27

DIMMABLE
LIGHT CONTROL

- E27 Base
- G125 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2067D	7191 - 2700K WARM WHITE	7w	55w	750	12

Filament-T30-E27

- E27 Base
- T30 Shape
- AC:220-240V,50/60Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2042	7251 - 2700K WARM WHITE	2w	20w	200	100
VT-2042-N	217251 - 3000K WARM WHITE	2w	20w	200	100

Filament-T20-E14

- E14 Base
- T20 Shape
- AC:220-240V,50/60Hz
- 360° Beam Angle
- PF: >0.45
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2204	2701 - 2700K WARM WHITE 2702 - 4000K DAY WHITE 2703 - 6000K WHITE	4w	35w	400	100

DEKRA TUV SUD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Clear Glass-Filament-A60-E27

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1885	7119 - 4000K DAY WHITE 7120 - 6400K WHITE	4w	40w	400	50

Clear Glass-Filament-A60-E27

DIMMABLE LIGHT CONTROL

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1885D	4364 - 2700K WARM WHITE	4w	30w	350	50

Clear Glass-Filament-A60-E27

- E27 Base
- A60 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1887-N	214272 - 3000K WARM WHITE 214303 - 4000K DAY WHITE	6w	30w	600	100

Clear Glass-Filament-A67-E27

DIMMABLE LIGHT CONTROL

- E27 Base
- A67 Shape
- AC:220-240V, 50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2288D	2815 - 2700K WARM WHITE	8W	50w	700	100
VT-2288D-N	212815 - 2700K WARM WHITE	8W	50w	720	100

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Clear Glass-Filament-A67-E27

- E27 Base
- A67 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1978	4407 - 3000K WARM WHITE 4408 - 4000K DAY WHITE 4409 - 6400K WHITE	8w	60w	800	100

Clear Glass-Filament-A67-E27

- E27 Base
- A67 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1981	4410 - 3000K WARM WHITE 4411 - 4000K DAY WHITE 4412 - 6400K WHITE	10w	75w	1055	50
VT-1981-N	214410 - 3000K WARM WHITE 214411 - 4000K DAY WHITE 214412 - 6500K WHITE	10w	75w	1055	20

Clear Filament-A67-E27

- E27 Base
- A67 Shape
- AC:220-240V
- 330° Beam Angle
- PF: 0.5
- CRI: 80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2328	2802 - 3000K WARM WHITE	18w	150w	2520	50
VT-2328-N	212802 - 3000K WARM WHITE	18w	150w	2520	100

Clear Filament-A70-E27

- E27 Base
- A70 Shape
- AC:220-240V,50Hz
- 330° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2133	7458 - 3000K WARM WHITE 7459 - 4000K DAY WHITE 7460 - 6400K WHITE	12.5w	100w	1550	50
VT-2133-N	217458 - 3000K WARM WHITE 217459 - 4000K DAY WHITE 217460 - 6500K WHITE	12w	100w	1521	100

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Clear Glass-Filament-ST26-E14

- E14 Base
- ST26 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1952	4444 - 2700K WARM WHITE	2w	20w	180	100
VT-1952-N	214444 - 3000K WARM WHITE 214445 - 4000K DAY WHITE 214446 - 6400K WHITE	2w	20w	200	200

Clear Glass-Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1986	4301 - 2700K WARM WHITE 4413 - 4000K DAY WHITE 4414 - 6400K WHITE	4w	40w	400	100
VT-1986-N	214301 - 3000K WARM WHITE 214413 - 4000K DAY WHITE 214414 - 6500K WHITE	4W	35w	400	100

Clear Glass-Filament-Candle-E14-Dimmable

DIMMABLE LIGHT CONTROL

- E14 Base
- Candle Shape
- AC:220-240V, 50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2304D	2870 - 3000K WARM WHITE	4W	35w	400	200

Clear Glass-Filament-Candle-E14

DIMMABLE LIGHT CONTROL

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1986D	4365 - 2700K WARM WHITE	4w	30w	350	100

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Clear Glass-Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1985	4307 - 2700K WARM WHITE	4w	40w	400	100

Clear Filament

DIMMABLE
LIGHT CONTROL

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1985D	4367 - 2700K WARM WHITE	4w	30w	320	100
VT-1985D-N	214367 - 3000K WARM WHITE	4w	30w	400	100

Clear Glass-Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1995	4308 - 2700K WARM WHITE 4432 - 6400K WHITE	4w	40w	400	100
VT-1995-N	214308 - 3000K WARM WHITE 214431 - 4000K DAY WHITE 214432 - 6500K WHITE	4w	40w	400	100

Clear Glass-Filament-Candle-E14

DIMMABLE
LIGHT CONTROL

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1995D	4388 - 2700K WARM WHITE	4w	40w	320	100

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Clear Glass-Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1997	4302 - 2700K WARM WHITE 4429 - 4000K DAY WHITE	4w	40w	400	50
VT-1997-N	214302 - 3000K WARM WHITE 214429 - 4000K DAY WHITE 214430 - 6500K WHITE	4w	40w	400	100

Clear Glass-Filament-Candle-E14

DIMMABLE LIGHT CONTROL

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1997D	4366 - 2700K WARM WHITE	4w	30w	320	100

Clear Glass-Filament-Candle-E14

130 lm/W
Brighter & energy-efficient
50% better than normal LED

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2327	2848 - 3000K WARM WHITE 2849 - 4000K DAY WHITE 2850 - 6400K WHITE	6W	60w	800	100
VT-2327-N	212850 - 6500K WHITE	6W	60w	800	100

Clear Glass-Filament-Candle-E14

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2127	7423 - 3000K WARM WHITE 7424- 4000K DAY WHITE 7425 - 6400K WHITE	6w	45w	600	200
VT-2127-N	217423 - 3000K WARM WHITE 217424- 4000K DAY WHITE 217425 - 6500K WHITE	6w	45w	600	100

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Candle Filament Bulbs

- E14 Base
- Candle Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2174	7365 - 2700K WARM WHITE	4w	40w	400	50

Clear Glass-Filament-Globe-E27

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1980	4306 - 2700K WARM WHITE 4428 - 6400K WHITE	4w	40w	400	100
VT-1980-N	214306 - 3000K WARM WHITE 214428 - 6500K WHITE	4w	40w	400	100

Clear Glass-Filament-G45-E27

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2366	2844 - 6400K WHITE 2842 - 3000K WARM WHITE 2843 - 4000K DAY WHITE	6W	45w	600	100
VT-2386	2853 - 6400K WHITE 2851 - 3000K WARM WHITE 2852 - 4000K DAY WHITE	6W	60w	800	100

Color Bulbs-G45-E27

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2132-P	7410 - PINK	2w	10w	60	100
VT-2132-P-N	217410 - PINK	2w	10w	60	100

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Color Bulbs-G45-E27

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2132-G	7411 - GREEN	2w	10w	60	100
VT-2132-G-N	217411 - GREEN	2w	10w	60	100

Color Bulbs-G45-E27

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2132-B	7412 - BLUE	2w	10w	60	100
VT-2132-B-N	217412 - BLUE	2w	10w	60	100

Color Bulbs-G45-E27

- E27 Base
- G45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2132-R	7413 - RED	2w	10w	60	100
VT-2132-R-N	217413 - RED	2w	10w	60	100

Clear Glass-Filament-P45-E14

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1996	4300 - 2700K WARM WHITE 4425 - 4000K DAY WHITE 4426 - 6400K WHITE	4w	40w	400	100
VT-1996-N	214300 - 3000K WARM WHITE	4w	40w	400	100

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS www.tuv.com ID 1111227954 RoHS COMPLIANT CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Bulbs-E14

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2184	7366 - 2700K WARM WHITE	4w	40w	400	50

Clear Glass-Filament-P45-E14

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2466	2847 - 6400K WHITE 2845 - 3000K WARM WHITE 2846 - 4000K DAY WHITE	6W	45w	600	100

Clear Glass-Filament-P45-E14

130 lm/W
Brighter & energy-efficient
50% better than normal LED

- E14 Base
- P45 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2486	2856 - 6400K WHITE 2854 - 3000K WARM WHITE 2855 - 4000K DAY WHITE	6W	60w	800	100

Clear Glass-Filament-Globe-E27

DIMMABLE
LIGHT CONTROL

- E27 Base
- G125 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1994D	4399 - 2700K WARM WHITE	4w	30w	320	20
VT-1983-N	214304 - 3000K WARM WHITE	6w	30w	600	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Clear Glass-Filament-Globe-E27

- E27 Base
- G125 Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2147	7427 - 6400K WHITE	6w	60w	806	20
VT-1979-N	214422 - 3000K WARM WHITE 214423 - 4000K DAY WHITE 214424 - 6500K WHITE	10w	60w	1055	20

Clear Glass-Filament-Globe-E27

- E27 Base
- G125 Shape
- AC:220-240V,50Hz
- 330° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2143	7455 - 6500K WHITE 7453 - 3000K WARM WHITE 7454 - 4000K DAY WHITE	12.5w	100w	1550	25
VT-2143-N	217453 - 3000K WARM WHITE 217454 - 4000K DAY WHITE 217455 - 6500K WHITE	12w	100w	1521	20

Clear Glass-Filament-Globe-E27

- E27 Base
- G95 Shape
- AC:220-240V,50Hz
- 330° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1993-N	214305 - 2700K WARM WHITE	6w	60w	600	20

Clear Glass-Filament-Globe-E27

- E27 Base
- G95 Shape
- AC:220-240V
- 330° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2338	2803 - 3000K WARM WHITE	18w	150w	2520	25
VT-2338-N	212803 - 3000K WARM WHITE	18w	150w	2520	100

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

String Light-LED-5M

- 5 Meter Long String
- 10 Bulbs included
- 0.6 watts per Bulb
- 300 Degree Beam Angle
- IP rating IP40
- 10 Pcs In Cartoon

Model	SKU	Watts	Box Qty
VT-71510	2728 – 3000K WARM WHITE	0.6w	10
VT-71510-N	212728 – 3000K WARM WHITE	0.4W	10

String Light-LED-5M

- 2 Meter Long String
- 1 watts per Bulb
- 10 Bulbs included
- 6–8 Hours Working Time
- 8–12 Hours Charging Time
- Battery 1XAA Ni-MH, 1.2V/300mAh
- IP rating IP54
- 10 Pcs In Cartoon

Model	SKU	Watts	Box Qty
VT-71010	8559 – 3000K WARM WHITE	1w	10

String Light-LED-5M

- 5 Meter Long String
- 0.5 watts per Bulb
- 10 Bulbs with 0.5 Meter Distance
- IP rating IP44
- 10 Pcs In Cartoon

Model	SKU	Watts	Box Qty
VT-70510	7437 – 6000K WHITE 7436 – 3000K WARM WHITE 7435 – RGB+YELLOW	0.5w	10
VT-70510-N	217436 – 3000K WARM WHITE	5W	10



String Light-LED-5M

- 10 Meter Long String
- 0.5 watts per Bulb
- 20 Bulbs with 0.5 Meter Distance
- IP rating IP44
- 5 Pcs In Cartoon

Model	SKU	Watts	Box Qty
VT-71020	7440 – 6000K WHITE 7439 – 3000K WARM WHITE 7438 – RGB+YELLOW	0.5w	10
VT-71020-N	217439 – 3000K WARM WHITE 217440 – 6000K WHITE	0.5W	5

String Light-WP Socket-E27

- 5 Meter Long String
- 10 Holders with 0.5 Meter Distance
- 4 Pcs In Cartoon
- IP54
- Linkable upto 500W max
- Bulbs are not included

Model	SKU	Box Qty
VT-7135	3698	4

String Light-WP Socket-E27

- 15 Meter Long String
- 15 Holders with 1 Meter Distance
- 4 Pcs In Cartoon
- IP54
- Linkable upto 500W max
- Bulbs are not included

Model	SKU	Box Qty
VT-713	3673	4

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Lamp Holder E27

SKU	Box Qty
8839	400

Lamp Holder E14

SKU	Box Qty
8840	400

Lamp Holder-E27

SKU	Box Qty
8750	400

Lamp Holder-E14

SKU	Box Qty
8751	400

Lamp Holder-E27

SKU	Box Qty
8752	400

Lamp Holder-E14

SKU	Box Qty
8753	400



LED SPOTLIGHTS

Introducing a sustainable and energy-efficient replacement for power-consuming 35W and 50W Halogen Spotlights. An extensive range of LED Spotlights (1.2W-8W).

Key Features

- Uses 80% less energy than Standard Bulbs
- Excellent Heat Radiation Efficiency
- Customized exterior for a durable body
- Choice of beam angle from 38º to 300°
- Premium Quality Power Driver

Application

Perfect choice for Hotels, Bars, Commercial & Residential Lighting and Exhibition Stands

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Capsules-G9

- G9 Base
- Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1946	4466 - 3000K WARM WHITE 4467 - 4000K DAY WHITE 4468 - 6400K WHITE	2.5w	25w	200	400

Capsules-G9

- G9 Base
- Shape
- AC:220-240V, 50/60Hz
- 300° Beam Angle
- PF: >0.7
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2103	7477 - 4000K DAY WHITE	3w	30w	330	450

Capsules-G9-6Pc Pack

- G9 Base
- Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2243	2745 - 3000K WARM WHITE 2746 - 4000K DAY WHITE 2747 - 6400K WHITE	3w	25w	300	300

Capsules-G9

- G9 Base
- Shape
- AC:230V
- 300° Beam Angle
- PF: >0.7
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2254	2742 - 3000K WARM WHITE 2744 - 6400K WHITE	4w	35w	410	400

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Capsules-G9

- G9 Base
- Shape
- AC:200-240V,50/60Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80

DIMMABLE
LIGHT CONTROL



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2175D	7431 - 6400K WHITE	5w	50w	500	600
VT-2175D-N	217429 - 3000K WARM WHITE 217431 - 6500K WHITE	5w	50w	500	600

Capsules-G9

- G9 Base
- Shape
- AC:200-240V,50/60Hz
- 300° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2177	7432 - 3000K WARM WHITE	5.5w	50w	550	600

Capsules-G9

- G9 Base
- Shape
- AC:220-240V,50Hz
- 300° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2227	2720 - 4000K DAY WHITE 2721 - 6400K WHITE	6w	45	550	200

GU10-RGB With Remote Control

- GU10 Base
- Shape
- AC:220-240V,50Hz
- 110° Beam Angle
- PF: >0.5
- CRI: >80

RGB
RF CONTROL

- RF Control 6-8M Range
- Switch on/off the light
- 16 steps dimming
- 16 colors selection
- Auto Color change Mode

DIMMABLE
LIGHT CONTROL

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2244	2778 - RGB+3000K WARM WHITE 2779 - RGB+4000K DAY WHITE 2780 - RGB+6400K WHITE	3.5w	25w	290	200
VT-2244-N	212778 - RGB+3000K WARM WHITE	5.5W	35w	420	200

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

GU10-RGB With Remote Control

- GU10 Base
- Shape
- AC:220-240V, 50Hz
- 110° Beam Angle
- PF: >0.5
- CRI: >80

RGB RF CONTROL

- RF Control 6-8M Range
- Switch on/off the light
- 16 steps dimming
- 16 colors selection
- Auto Color change Mode

DIMMABLE LIGHT CONTROL

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2244-N-1	2927 - RGB+3000K WARM WHITE 2930 - RGB+4000K DAY WHITE	5.5w	35w	420	200

Spotlights-GU10-Lens-38°

- GU10 Base
- Shape
- AC:220-240V,50Hz
- 38° Beam Angle
- PF: >0.5
- CRI: >95

REAL COLOR SERIES CRI >95



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2206	7497 - 2700K WARM WHITE 7498 - 4000K DAY WHITE 7499 - 6400K WHITE	6w	55w	400	200

Spotlights-GU10-Lens-38°

- GU10 Base
- Shape
- AC:220-240V,50Hz
- 38° Beam Angle
- PF: >0.5
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2305	2796 - 3000K WARM WHITE 2797 - 4000K DAY WHITE	5w	50w	380	200

Spotlights-GU10-Milky Cover-110°

- GU10 Base
- Shape
- AC:220-240V,50Hz
- 110° Beam Angle
- PF: >0.4
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1975	1685 - 3000K WARM WHITE 1686 - 4000K DAY WHITE 1687 - 6000K WHITE	5w	35w	400	200
VT-1975-N	211685 - 3000K WARM WHITE 211686 - 4500K DAY WHITE 211687 - 6000K WHITE	4.5w	35w	400	200

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

GU10-3PC Pack-Fitting

3pcs Pack

- GU10 Base
- Shape
- AC:200-240V,50/60Hz
- 110° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-3333	8881 - 3000K WARM WHITE 8882 - 4000K DAY WHITE 8883 - 6400K WHITE	5w	35w	400	20

GU10-3PC Pack-Fitting

3pcs Pack

- GU10 Base
- Shape
- AC:200-240V,50/60Hz
- 110° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-4444	8884 - 3000K WARM WHITE 8885 - 4000K DAY WHITE 8886 - 6400K WHITE	5w	35w	400	20

Spotlights-GU10-3PC Pack

3pcs Pack

- GU10 Base
- Shape
- AC:220-240V,50Hz
- 110° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2095	7269 - 3000K WARM WHITE 7270 - 4000K DAY WHITE 7271 - 6400K WHITE	5w	35w	400	60
VT-2095-N	217269 - 3000K WARM WHITE 217270 - 4000K DAY WHITE 217271 - 6500K WHITE	4.5W	35w	400	180

Spotlights-GU10-6PC Pack

6pcs Pack

- GU10 Base
- Shape
- AC:220-240V,50Hz
- 110° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2225	2739 - 3000K WARM WHITE 2740 - 4000K DAY WHITE 2741 - 6400K WHITE	5w	35w	400	30
VT-2225-N	212739 - 3000K WARM WHITE 212740 - 4000K DAY WHITE 212741 - 6500K WHITE	4.5W	35w	400	180

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

GU10- 38°-10PC Pack

10 pcs Pack

- GU10 Base
- Shape
- AC:220-240V,50Hz
- 38° Beam Angle
- PF: >0.5
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-2305-10PC	2799 – 3000K WARM WHITE 2800 – 4000K DAY WHITE 2801 – 6400K WHITE	5w	50w	380	20

Including 2 reflectors (40° already mounted)

Instructions to change the reflector



AR111 Downlight

- N/A Base
- AR111 Shape
- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 40°/20° Beam Angle

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1121	2792 – 3000K WARM WHITE 2793 – 4000K DAY WHITE 2794 – 6400K WHITE	20w	130w	1800	50
VT-1121-N	212792 – 3000K WARM WHITE 212793 – 4000K DAY WHITE 212794 – 6500K WHITE	20W	130w	1700	50



AR111 Downlight

- N/A Base
- AR111 Shape
- AC:220-240V,50/60Hz
- 20° Beam Angle
- PF: >0.7
- CRI: >80

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1120-20	1245 – 6000K WHITE	20w	100w	1800	50



V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

AR111-G53

- G53 Base
- PAR AR111 Shape
- AC/DC:12V,50Hz
- 20° Beam Angle
- PF: >0.9
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1110-20	4084 - 3000K WARM WHITE 4062 - 4000K DAY WHITE 4061 - 6400K WHITE	15w	75w	950	60
VT-1110-20-N	214084 - 3000K WARM WHITE 214062 - 4000K DAY WHITE	12W	75w	3000K-1030 4000K-1050	60

AR111-G53

- G53 Base
- PAR AR111 Shape
- AC/DC:12V,50Hz
- 40° Beam Angle
- PF: >0.9
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1110-40	4257 - 3000K WARM WHITE 4256 - 4000K DAY WHITE 4255 - 6400K WHITE	15w	25w	950	60
VT-1110-40-N	214257 - 3000K WARM WHITE 214256 - 4000K DAY WHITE 214255 - 6000K WHITE	12w	25w	3000K-1085 4000K-1160 6000K-1200	60

AR111-GU10

- GU10 Base
- Shape
- AC:200-240V,50Hz
- 40° Beam Angle
- PF: >0.9
- CRI: >80



Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1112	4224 - 2700K WARM WHITE 4223 - 4000K DAY WHITE 4225 - 6400K WHITE	12w	60w	900	60
VT-1112-N	214224 - 3000K WARM WHITE 214225 - 6000K WHITE	12w	60w	3000K-1020 6000K-1120	

AR111-GU10

- GU10 Base
- Shape
- AC:200-240V,50Hz
- 40° Beam Angle
- PF: >0.9
- CRI: >80



DIMMABLE
LIGHT CONTROL

Model	SKU	Watts	EQUIV.W	Lumen	Box Qty
VT-1112D	7234 - 3000K WARM WHITE 7235 - 4000K DAY WHITE 7236 - 6400K WHITE	12w	60w	900	60
VT-1112D-N	217234 - 3000K WARM WHITE 217236 - 6000K WHITE	12w	60w	3000K-1030 6000K-1300	

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Fitting & Accessories



Model No:	VT-7221-W	**Color:**	White
SKU:	3575	**Dimension:**	174×174 mm
Base:	1XAR111	**Cutting Size:**	163×163mm
Material:	Aluminium	**Box Qty:**	24

Fitting & Accessories



Model No:	VT-7222-W	**Color:**	White
SKU:	3576	**Dimension:**	325×174mm
Base:	2XAR111	**Cutting Size:**	167×305mm.
Material:	Aluminium	**Box Qty:**	12

Fitting & Accessories



Model No:	VT-7221-B	**Color:**	Black
SKU:	3581	**Dimension:**	174×174 mm
Base:	1XAR111	**Cutting Size:**	163×163mm
Material:	Aluminium	**Box Qty:**	24

Fitting & Accessories



Model No:	VT-7222-B	**Color:**	Black
SKU:	3582	**Dimension:**	325×174 mm
Base:	2XAR111	**Cutting Size:**	167×305mm.
Material:	Aluminium	**Box Qty:**	12

Fitting & Accessories



Model No:	VT-7223-W	**Color:**	White
SKU:	35771	**Dimension:**	475×174mm
Base:	3XAR111	**Cutting Size:**	168×455mm
Material:	Aluminium	**Box Qty:**	12

Fitting & Accessories



Model No:	VT-7223-B	**Color:**	Black
SKU:	35831	**Dimension:**	475×174mm
Base:	3XAR111	**Cutting Size:**	168×455mm
Material:	Aluminium	**Box Qty:**	12

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

Recessed Fitting GU10

NEW

Model No:	VT-11001	**Color:**	White
SKU:	6761	**Dimension:**	80×80×50mm
Base:	GU10	**Cutting Size:**	85×85mm
Material:	Plaster	**Box Qty:**	30

Recessed Fitting GU10

NEW

Model No:	VT-11003	**Color:**	White
SKU:	6764	**Dimension:**	280×100×40mm
Base:	GU10	**Cutting Size:**	285×105mm
Material:	Plaster	**Box Qty:**	6

Recessed Fitting GU10

NEW

Model No:	VT-11011	**Color:**	White
SKU:	6775	**Dimension:**	150×80×50mm
Base:	GU10	**Cutting Size:**	155×85mm
Material:	Plaster	**Box Qty:**	12

Recessed Fitting GU10

NEW

Model No:	VT-11013	**Color:**	White
SKU:	6765	**Dimension:**	280×100×40mm
Base:	GU10	**Cutting Size:**	285×105mm
Material:	Plaster	**Box Qty:**	6

Recessed Fitting GU10

NEW

Model No:	VT-11014	**Color:**	White
SKU:	6776	**Dimension:**	220×80×50mm
Base:	GU10	**Cutting Size:**	225×85mm
Material:	Plaster	**Box Qty:**	6

Recessed Fitting GU10

NEW

Model No:	VT-11023	**Color:**	White
SKU:	6766	**Dimension:**	280×100×40mm
Base:	GU10	**Cutting Size:**	285×105mm
Material:	Plaster	**Box Qty:**	6

Recessed Fitting GU10

NEW

Model No:	VT-11002	**Color:**	White
SKU:	6762	**Dimension:**	190×100×40mm
Base:	GU10	**Cutting Size:**	195×105mm
Material:	Plaster	**Box Qty:**	12

Recessed Wall Fitting E14

NEW

Model No:	VT-11004	**Color:**	White
SKU:	6767	**Dimension:**	255×180×315mm
Base:	E14	**Cutting Size:**	260×320mm
Material:	Plaster	**Box Qty:**	6

Recessed Fitting GU10

NEW

Model No:	VT-11012	**Color:**	White
SKU:	6763	**Dimension:**	190×100×40mm
Base:	GU10	**Cutting Size:**	195×105mm
Material:	Plaster	**Box Qty:**	12

Recessed Wall Fitting G9

NEW

Model No:	VT-11005	**Color:**	White
SKU:	6768	**Dimension:**	400×400×65mm
Base:	G9	**Cutting Size:**	405×405mm
Material:	Plaster	**Box Qty:**	1

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

Recessed Wall Fitting G9

NEW

Model No:	VT-11006	**Color:**	White
SKU:	6769	**Dimension:**	310×260×170mm
Base:	G9	**Cutting Size:**	315×265mm
Material:	Plaster	**Box Qty:**	6

Recessed Fitting GU10

NEW

Model No:	VT-11010	**Color:**	White
SKU:	6774	**Dimension:**	350×100×75mm
Base:	GU10	**Cutting Size:**	355×105mm
Material:	Plaster	**Box Qty:**	6

Recessed Fitting GU10

NEW

Model No:	VT-11007	**Color:**	White
SKU:	6770	**Dimension:**	180×120×70mm
Base:	GU10	**Cutting Size:**	185×125mm
Material:	Plaster	**Box Qty:**	12

Pendant Black-GU10

NEW

Model No:	VT-975-20CM	**Color:**	Black
SKU:	6684	**Dimension:**	35.5×25.5×42mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminum	**Box Qty:**	20

Recessed Fitting GU10

NEW

Model No:	VT-11008	**Color:**	White
SKU:	6771	**Dimension:**	250×210×80mm
Base:	GU10	**Cutting Size:**	255×215mm
Material:	Plaster	**Box Qty:**	6

Pendant Black-GU10

NEW

Model No:	VT-975-30CM	**Color:**	Black
SKU:	6685	**Dimension:**	35.5×35.5×43mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminum	**Box Qty:**	20

Recessed Fitting GU10

NEW

Model No:	VT-11009R	**Color:**	White
SKU:	6772	**Dimension:**	120×120×60mm
Base:	GU10	**Cutting Size:**	125×125mm
Material:	Plaster	**Box Qty:**	24

Pendant Black-GU10

NEW

Model No:	VT-976-30CM	**Color:**	Black
SKU:	6686	**Dimension:**	35.5×35.5×43mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminum	**Box Qty:**	20

Recessed Fitting GU10

NEW

Model No:	VT-11009S	**Color:**	White
SKU:	6773	**Dimension:**	120×120×60mm
Base:	GU10	**Cutting Size:**	125×125mm
Material:	Plaster	**Box Qty:**	24

Pendant Black-GU10

NEW

Model No:	VT-976-50CM	**Color:**	Black
SKU:	6687	**Dimension:**	42×35×54.5mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminum	**Box Qty:**	20

Pendant Black-GU10

NEW

Model No:	VT-977-30CM	**Color:**	Black + Gold
SKU:	6688	**Dimension:**	35.5×35.5×43mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminum	**Box Qty:**	20

Pendant Black-GU10

NEW

Model No:	VT-977-50CM	**Color:**	Black + Gold
SKU:	6689	**Dimension:**	42×35×54.5mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminum	**Box Qty:**	20

Surface Fittings GU10

NEW



Model No:	VT-978-W	**Color:**	White
SKU:	6690	**Dimension:**	26.5×22.5×55mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Iron	**Box Qty:**	20

Surface Fittings GU10

NEW



Model No:	VT-978-B	**Color:**	Black
SKU:	6691	**Dimension:**	26.5×22.5×55mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Iron	**Box Qty:**	20

Surface Fittings GU10

NEW



Model No:	VT-979-W	**Color:**	White
SKU:	6692	**Dimension:**	27.5×22.5×55mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Iron	**Box Qty:**	20

Surface Fittings GU10

NEW



Model No:	VT-979-B	**Color:**	Black
SKU:	6693	**Dimension:**	27.5×22.5×55mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Iron	**Box Qty:**	20

Recessed Fitting GU10

NEW



Model No:	VT-920-W	**Color:**	White
SKU:	6632	**Dimension:**	88×40mm
Base:	GU10	**Cutting Size:**	80mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-920-B	**Color:**	Black
SKU:	6633	**Dimension:**	88×40mm
Base:	GU10	**Cutting Size:**	80mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-925-W	**Color:**	White
SKU:	6636	**Dimension:**	93×55mm
Base:	GU10	**Cutting Size:**	83mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-925-B	**Color:**	Black
SKU:	6637	**Dimension:**	93×55mm
Base:	GU10	**Cutting Size:**	83mm
Material:	PC	**Box Qty:**	50

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

Recessed Fitting GU10

NEW



Model No:	VT-929-W	**Color:**	White
SKU:	6640	**Dimension:**	81×40mm
Base:	GU10	**Cutting Size:**	63mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-929-B	**Color:**	Black
SKU:	6641	**Dimension:**	81×40mm
Base:	GU10	**Cutting Size:**	63mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-921-W	**Color:**	White
SKU:	6634	**Dimension:**	88×88×40mm
Base:	GU10	**Cutting Size:**	80mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-921-B	**Color:**	Black
SKU:	6635	**Dimension:**	88×88×40mm
Base:	GU10	**Cutting Size:**	80mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-927-W	**Color:**	White
SKU:	6638	**Dimension:**	93×93×55mm
Base:	GU10	**Cutting Size:**	83×83mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-927-B	**Color:**	Black
SKU:	6639	**Dimension:**	93×93×55mm
Base:	GU10	**Cutting Size:**	83×83mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-930-W	**Color:**	White
SKU:	6642	**Dimension:**	81×81×40mm
Base:	GU10	**Cutting Size:**	63mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-930-B	**Color:**	Black
SKU:	6643	**Dimension:**	81×81×40mm
Base:	GU10	**Cutting Size:**	63mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-931-W	**Color:**	White+White
SKU:	6644	**Dimension:**	85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-931-WB	**Color:**	White+Black
SKU:	6645	**Dimension:**	85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-931-B	**Color:**	Black+Black
SKU:	6646	**Dimension:**	85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-931-WC	**Color:**	White+Chrome
SKU:	6647	**Dimension:**	85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-931-WG	**Color:**	White+Gold
SKU:	6648	**Dimension:**	85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-931-WRG	**Color:**	White+Rose Gold
SKU:	6649	**Dimension:**	85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-932-W	**Color:**	White+White
SKU:	6650	**Dimension:**	85×85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-932-WB	**Color:**	White+Black
SKU:	6651	**Dimension:**	85×85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-932-B	**Color:**	Black+Black
SKU:	6652	**Dimension:**	85×85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-932-WC	**Color:**	White+Chrome
SKU:	6653	**Dimension:**	85×85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-932-WG	**Color:**	White+Gold
SKU:	6654	**Dimension:**	85×85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-932-WRG	**Color:**	White+Rose Gold
SKU:	6655	**Dimension:**	85×85×40mm
Base:	GU10	**Cutting Size:**	72mm
Material:	PC	**Box Qty:**	50

DEKRA TÜV SÜD GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

Recessed Fitting GU10

NEW

Model No:	VT-933-W	**Color:**	White
SKU:	6656	**Dimension:**	102×102×42mm
Base:	GU10	**Cutting Size:**	95×95mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW

Model No:	VT-933-B	**Color:**	Black
SKU:	6657	**Dimension:**	102×102×42mm
Base:	GU10	**Cutting Size:**	95×95mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW



Model No:	VT-934-W	**Color:**	White
SKU:	6658	**Dimension:**	102×42mm
Base:	GU10	**Cutting Size:**	85mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW

Model No:	VT-934-B	**Color:**	Black
SKU:	6659	**Dimension:**	102×42mm
Base:	GU10	**Cutting Size:**	85mm
Material:	PC	**Box Qty:**	50

Recessed Fitting GU10

NEW

Model No:	VT-974-W	**Color:**	White
SKU:	6682	**Dimension:**	42.5×17.5×35mm
Base:	GU10	**Cutting Size:**	61mm
Material:	Aluminum	**Box Qty:**	50

Recessed Fitting GU10

NEW

Model No:	VT-974-B	**Color:**	Black
SKU:	6683	**Dimension:**	42.5×17.5×35mm
Base:	GU10	**Cutting Size:**	61mm
Material:	Aluminum	**Box Qty:**	50

Recessed Fitting GU10

NEW

Model No:	VT-980-WB	**Color:**	White+black
SKU:	6694	**Dimension:**	32.5×23.5×50mm
Base:	GU10	**Cutting Size:**	61mm
Material:	Aluminum	**Box Qty:**	50

Recessed Fitting GU10

NEW

Model No:	VT-980-BW	**Color:**	Black+white
SKU:	6695	**Dimension:**	32.5×23.5×50mm
Base:	GU10	**Cutting Size:**	61mm
Material:	Aluminum	**Box Qty:**	50

Recessed Fitting GU10

NEW

Model No:	VT-980-B	**Color:**	Black+black
SKU:	6696	**Dimension:**	32.5×23.5×50mm
Base:	GU10	**Cutting Size:**	61mm
Material:	Aluminum	**Box Qty:**	50

Recessed Fitting GU10

NEW

Model No:	VT-980-GB	**Color:**	Golden+Black
SKU:	6697	**Dimension:**	32.5×23.5×50mm
Base:	GU10	**Cutting Size:**	61mm
Material:	Aluminum	**Box Qty:**	50

Concrete Wall Fitting



Model No:	VT-891D	**Color:**	Dark Grey
SKU:	8690	**Dimension:**	150×130×130mm
Base:	G9	**Cutting Size:**	N/A
Material:	Concrete	**Box Qty:**	12

Concrete Wall Fitting



Model No:	VT-893L	**Color:**	Light Grey
SKU:	8695	**Dimension:**	120×100×240mm
Base:	G9	**Cutting Size:**	N/A
Material:	Concrete	**Box Qty:**	6

Concrete Wall Fitting



Model No:	VT-891L	**Color:**	Light Grey
SKU:	8691	**Dimension:**	150×130×130mm
Base:	G9	**Cutting Size:**	N/A
Material:	Concrete	**Box Qty:**	12

Concrete Wall Fitting



Model No:	VT-894D	**Color:**	Dark Grey
SKU:	8696	**Dimension:**	120×140×235mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Concrete	**Box Qty:**	6

Concrete Wall Fitting



Model No:	VT-892D	**Color:**	Dark Grey
SKU:	8692	**Dimension:**	120×100×120mm
Base:	G9	**Cutting Size:**	N/A
Material:	Concrete	**Box Qty:**	12

Concrete Wall Fitting



Model No:	VT-894L	**Color:**	Light Grey
SKU:	8697	**Dimension:**	120×140×235mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Concrete	**Box Qty:**	6

Concrete Wall Fitting



Model No:	VT-892L	**Color:**	Light Grey
SKU:	8693	**Dimension:**	120×100×120mm
Base:	G9	**Cutting Size:**	N/A
Material:	Concrete	**Box Qty:**	12

Surface Fitting GU10



Model No:	VT-802-W	**Color:**	White
SKU:	8944	**Dimension:**	ø70×107mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Aluminium	**Box Qty:**	50

Concrete Wall Fitting



Model No:	VT-893D	**Color:**	Dark Grey
SKU:	8694	**Dimension:**	120×100×240mm
Base:	G9	**Cutting Size:**	N/A
Material:	Concrete	**Box Qty:**	6

Surface Fitting GU10



Model No:	VT-802-B	**Color:**	Black
SKU:	8945	**Dimension:**	ø70×107mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Aluminium	**Box Qty:**	50

DEKRA TÜV SÜD CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

Surface Fitting GU10



Model No:	VT-804-W	**Color:**	White
SKU:	8946	**Dimension:**	Ø59.5×197mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Aluminium	**Box Qty:**	20 Pcs

Surface Fitting GU10



Model No:	VT-804-B	**Color:**	Black
SKU:	8947	**Dimension:**	Ø59.5×197mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Aluminium	**Box Qty:**	20 Pcs

Surface Fitting GU10



Model No:	VT-807-W	**Color:**	White
SKU:	8948	**Dimension:**	60×100mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Aluminium	**Box Qty:**	50 Pcs

Surface Fitting GU10



Model No:	VT-807-B	**Color:**	Black
SKU:	8949	**Dimension:**	60×100mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Aluminium	**Box Qty:**	50 Pcs

Fitting Square-GU10



Model No:	VT-883-WB	**Color:**	White + Black Reflector
SKU:	8597	**Dimension:**	83×40.7mm
Base:	GU10	**Cutting Size:**	75×75mm
Material:	Aluminium + PC	**Box Qty:**	50

Fitting Square-GU10



Model No:	VT-883-B	**Color:**	Black
SKU:	8598	**Dimension:**	83×40.7mm
Base:	GU10	**Cutting Size:**	75×75mm
Material:	Aluminium + PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-884-WB	**Color:**	White + Black Reflector
SKU:	8599	**Dimension:**	83×40.7mm
Base:	GU10	**Cutting Size:**	ø75mm
Material:	Aluminium + PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-884-B	**Color:**	Black+ Black Reflector
SKU:	8608	**Dimension:**	83×40.7mm
Base:	GU10	**Cutting Size:**	ø75mm
Material:	Aluminium + PC	**Box Qty:**	50

Fitting Square-GU10



Model No:	VT-886	**Color:**	White+Black
SKU:	8877	**Dimension:**	185×100×45mm
Base:	2xGU10	**Cutting Size:**	175×85mm
Material:	Aluminium	**Box Qty:**	20

Fitting Square-GU10



Model No:	VT-887	**Color:**	White+Black
SKU:	8878	**Dimension:**	270×100×45mm
Base:	3xGU10	**Cutting Size:**	256×85mm
Material:	Aluminium	**Box Qty:**	20

Chrom Reflector Fitting Round-GU10



Model No:	VT-889	**Color:**	White+Chrome Reflector
SKU:	8879	**Dimension:**	ø140×50mm
Base:	GU10	**Cutting Size:**	ø85/90mm
Material:	Aluminium	**Box Qty:**	50

Chrom Reflector Fitting Square-GU10



Model No:	VT-890	**Color:**	White+Chrome Reflector
SKU:	8880	**Dimension:**	128×75×55mm
Base:	GU10	**Cutting Size:**	79/85×75mm
Material:	Aluminium	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-872-WB	**Color:**	White+Black
SKU:	3153	**Dimension:**	79×32mm
Base:	GU10	**Cutting Size:**	72mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-872-WG	**Color:**	White+Gold
SKU:	3154	**Dimension:**	79×32mm
Base:	GU10	**Cutting Size:**	72mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-872-WR	**Color:**	White+Rose Gold
SKU:	3155	**Dimension:**	79×32mm
Base:	GU10	**Cutting Size:**	72mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-872-WC	**Color:**	White+Chrome
SKU:	3156	**Dimension:**	79×32mm
Base:	GU10	**Cutting Size:**	72mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-873	**Color:**	Black+ Black Reflector
SKU:	8595	**Dimension:**	ø83×40.7mm
Base:	GU10	**Cutting Size:**	ø75mm
Material:	Aluminium + PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-873-WB	**Color:**	White+Black
SKU:	3157	**Dimension:**	80×42mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-873-WG	**Color:**	White+Gold
SKU:	3158	**Dimension:**	80×42mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-873-WR	**Color:**	White+Rose Gold
SKU:	3159	**Dimension:**	80×42mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Aluminium+PC	**Box Qty:**	50

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

Fitting Round-GU10



Model No:	VT-873-WC	**Color:**	White+Chrome
SKU:	3160	**Dimension:**	80×42mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-874-WC	**Color:**	White+Chrome
SKU:	3164	**Dimension:**	80×42mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-874	**Color:**	Black+ Black Reflector
SKU:	8596	**Dimension:**	ø83×40.7mm
Base:	GU10	**Cutting Size:**	ø75mm
Material:	Aluminium + PC	**Box Qty:**	50

Fitting Square-GU10



Model No:	VT-875-WB	**Color:**	White+Black
SKU:	3165	**Dimension:**	85×85×62mm
Base:	GU10	**Cutting Size:**	80×80mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-874-WB	**Color:**	White+Black
SKU:	3161	**Dimension:**	80×42mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Square-GU10



Model No:	VT-875-WG	**Color:**	White+Gold
SKU:	3166	**Dimension:**	85×85×62mm
Base:	GU10	**Cutting Size:**	80×80mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-874-WG	**Color:**	White+Gold
SKU:	3162	**Dimension:**	80×42mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Square-GU10



Model No:	VT-875-WR	**Color:**	White+Rose Gold
SKU:	3167	**Dimension:**	85×85×62mm
Base:	GU10	**Cutting Size:**	80×80mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Round-GU10



Model No:	VT-874-WR	**Color:**	White+Rose Gold
SKU:	3163	**Dimension:**	80×42mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Square-GU10



Model No:	VT-875-WC	**Color:**	White+Chrome
SKU:	3168	**Dimension:**	85×85×62mm
Base:	GU10	**Cutting Size:**	80×80mm
Material:	Aluminium+PC	**Box Qty:**	50

Fitting Square-GU10



Model No:	VT-876-RD	**Color:**	White
SKU:	3169	**Dimension:**	85×32mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Aluminium	**Box Qty:**	50

Fitting Square-GU10



Model No:	VT-876-SQ	**Color:**	White
SKU:	3170	**Dimension:**	85×85×32mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Aluminium	**Box Qty:**	50

Fitting-Square-GU10



Model No:	VT-797-WH	**Color:**	White
SKU:	3630	**Dimension:**	142×100×100mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Die Cast Aluminium	**Box Qty:**	50

Fitting-Square-GU10



Model No:	VT-797-B	**Color:**	Black
SKU:	3631	**Dimension:**	100×100×142mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Die Cast Aluminium	**Box Qty:**	50

Fitting-Square-GU10



Model No:	VT-797-SN	**Color:**	Satin Nickel
SKU:	3632	**Dimension:**	100×100×142mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Die Cast Aluminium	**Box Qty:**	50

Fitting-Round-GU10



Model No:	VT-796-WH	**Color:**	White
SKU:	3627	**Dimension:**	Ø100×142mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Die Cast Aluminium	**Box Qty:**	50

Fitting-Round-GU10



Model No:	VT-796-B	**Color:**	Black
SKU:	3628	**Dimension:**	Ø100×142mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Die Cast Aluminium	**Box Qty:**	50

Fitting-Round-GU10



Model No:	VT-796-SN	**Color:**	Satin Nickel
SKU:	3629	**Dimension:**	Ø100×142mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Die Cast Aluminium	**Box Qty:**	50

GX53-Accessory



Model No:	VT-715-W	**Color:**	White
SKU:	3675	**Dimension:**	Ø105×40mm
Base:	GX53	**Cutting Size:**	90mm
Material:	Iron	**Box Qty:**	50

GX53-Accessory



Model No:	VT-715-G	**Color:**	Gold
SKU:	3676	**Dimension:**	Ø105×40mm
Base:	GX53	**Cutting Size:**	90mm
Material:	Iron	**Box Qty:**	50

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

GX53-Accessory



Model No:	VT-715-CH	**Color:**	Chrome
SKU:	3677	**Dimension:**	Ø105×40mm
Base:	GX53	**Cutting Size:**	90mm
Material:	Iron	**Box Qty:**	50

Fitting-Square-GU10

Model No:	VT-762	**Color:**	White
SKU:	3648	**Dimension:**	215×120×60mm
Base:	GU10	**Cutting Size:**	218×123mm
Material:	Gypsum	**Box Qty:**	20

Fitting-Square-GU10



Model No:	VT-727SQ	**Color:**	White
SKU:	3664	**Dimension:**	70×70×75mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum	**Box Qty:**	36

Fitting-Square-GU10



Model No:	VT-763	**Color:**	White
SKU:	3649	**Dimension:**	120×120×50mm
Base:	GU10	**Cutting Size:**	123×123mm
Material:	Gypsum	**Box Qty:**	24

Fitting-Round-GU10



Model No:	VT-727RD	**Color:**	White
SKU:	3665	**Dimension:**	Ø70×75mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum	**Box Qty:**	36

Fitting-Round-GU10



Model No:	VT-764	**Color:**	White
SKU:	3650	**Dimension:**	Ø140×40mm
Base:	GU10	**Cutting Size:**	Ø140mm
Material:	Gypsum	**Box Qty:**	20

Fitting-Square-GU10



Model No:	VT-716SQ	**Color:**	White
SKU:	3666	**Dimension:**	75×75×75mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum	**Box Qty:**	36

Fitting-Square-GU10



Model No:	VT-765	**Color:**	White
SKU:	3651	**Dimension:**	100×100×30mm
Base:	GU10	**Cutting Size:**	103×103mm
Material:	Gypsum	**Box Qty:**	30

Fitting-Round-GU10



Model No:	VT-716RD	**Color:**	White
SKU:	3667	**Dimension:**	Ø75×75mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum	**Box Qty:**	36

Fitting-Round-GU10



Model No:	VT-771	**Color:**	White
SKU:	3652	**Dimension:**	Ø100×30mm
Base:	GU10	**Cutting Size:**	Ø103mm
Material:	Gypsum	**Box Qty:**	20

Fitting-Square-GU10



Model No:	VT-772	**Color:**	White
SKU:	3653	**Dimension:**	132×132×74mm
Base:	GU10	**Cutting Size:**	135×135mm
Material:	Gypsum	**Box Qty:**	20

Fitting-Square-GU10-Frost Glass



Model No:	VT-801SQ	**Color:**	White
SKU:	3691	**Dimension:**	120×120×60mm
Base:	GU10	**Cutting Size:**	123×123mm
Material:	Gypsum	**Box Qty:**	24

Fitting-Round-GU10



Model No:	VT-776RD	**Color:**	White
SKU:	3640	**Dimension:**	Ø120×40mm
Base:	GU10	**Cutting Size:**	Ø123mm
Material:	Gypsum	**Box Qty:**	24

Fitting-Round-GU10-Frost Glass



Model No:	VT-801RD	**Color:**	White
SKU:	3692	**Dimension:**	Ø120×60mm
Base:	GU10	**Cutting Size:**	Ø123mm
Material:	Gypsum	**Box Qty:**	24

Fitting-Square-GU10



Model No:	VT-776SQ	**Color:**	White
SKU:	3641	**Dimension:**	120×120×50mm
Base:	GU10	**Cutting Size:**	123×123mm
Material:	Gypsum	**Box Qty:**	24

Fitting-Round-GU10-2Pc Pack



2 PCS PACK

Model No:	VT-817-W-RD	**Color:**	White
SKU:	8938	**Dimension:**	Ø93×27mm
Base:	GU10	**Cutting Size:**	Ø70mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-773	**Color:**	White
SKU:	3654	**Dimension:**	Ø132×74mm
Base:	GU10	**Cutting Size:**	Ø132mm
Material:	Gypsum	**Box Qty:**	20

Fitting-Round-GU10-2Pc Pack



2 PCS PACK

Model No:	VT-817-SN-RD	**Color:**	Satin Nickel
SKU:	8939	**Dimension:**	Ø93×27mm
Base:	GU10	**Cutting Size:**	Ø70mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-714	**Color:**	White
SKU:	3674	**Dimension:**	120×120×45mm
Base:	GU10	**Cutting Size:**	123×123mm
Material:	Gypsum	**Box Qty:**	24

Fitting-Round-GU10-2Pc Pack



2 PCS PACK

Model No:	VT-817-CH-RD	**Color:**	Chrome
SKU:	8940	**Dimension:**	Ø93×27mm
Base:	GU10	**Cutting Size:**	Ø70mm
Material:	Ferrum	**Box Qty:**	100

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

Fitting-Round-GU10-2Pc Pack



2 PCS PACK

Model No:	VT-817-W-SQ	**Color:**	White
SKU:	8941	**Dimension:**	82×82×27mm
Base:	GU10	**Cutting Size:**	70×70mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Round-GU10-2Pc Pack



2 PCS PACK

Model No:	VT-817-SN-SQ	**Color:**	Satin Nickel
SKU:	8942	**Dimension:**	82×82×27mm
Base:	GU10	**Cutting Size:**	70×70mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Round-GU10-2Pc Pack



2 PCS PACK

Model No:	VT-817-CH-SQ	**Color:**	Chrome
SKU:	8943	**Dimension:**	82×82×27mm
Base:	GU10	**Cutting Size:**	70×70mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Round-GU10-2Pc Pack



2 PCS PACK

Model No:	VT-778-WH	**Color:**	White
SKU:	3584	**Dimension:**	Ø80×30mm
Base:	GU10	**Cutting Size:**	Ø65mm
Material:	Ferrum	**Box Qty:**	200

Fitting-Round-GU10-2Pc Pack



2 PCS PACK

Model No:	VT-778-SN	**Color:**	Satin Nickel
SKU:	3585	**Dimension:**	Ø80×30mm
Base:	GU10	**Cutting Size:**	Ø65mm
Material:	Ferrum	**Box Qty:**	200

Fitting-Round-GU10-2Pc Pack



2 PCS PACK

Model No:	VT-778-CH	**Color:**	Chrome
SKU:	3586	**Dimension:**	Ø80×30mm
Base:	GU10	**Cutting Size:**	Ø65mm
Material:	Ferrum	**Box Qty:**	200

Fitting-Round-GU10-Changing Angle



Model No:	VT-780-WH	**Color:**	White
SKU:	3593	**Dimension:**	Ø100×45mm
Base:	GU10	**Cutting Size:**	Ø90mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Round-GU10-Changing Angle



Model No:	VT-780-SN	**Color:**	Satin Nickel
SKU:	3594	**Dimension:**	Ø100×45mm
Base:	GU10	**Cutting Size:**	Ø90mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-774-WH	**Color:**	White
SKU:	3642	**Dimension:**	Ø81×34mm
Base:	GU10	**Cutting Size:**	Ø73mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-774-SN	**Color:**	Satin Nickel
SKU:	3643	**Dimension:**	Ø81×34mm
Base:	GU10	**Cutting Size:**	Ø73mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-774-MG	**Color:**	Metallic Grey
SKU:	3644	**Dimension:**	Ø81×34mm
Base:	GU10	**Cutting Size:**	Ø73mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-775-WH	**Color:**	White
SKU:	3645	**Dimension:**	Ø95×32mm
Base:	GU10	**Cutting Size:**	Ø85mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-775-SN	**Color:**	Satin Nickel
SKU:	3646	**Dimension:**	Ø95×32mm
Base:	GU10	**Cutting Size:**	Ø85mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-775-MG	**Color:**	Metallic Grey
SKU:	3647	**Dimension:**	Ø95×32mm
Base:	GU10	**Cutting Size:**	Ø85mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-782RD-WH	**Color:**	White
SKU:	3599	**Dimension:**	Ø91×25mm
Base:	GU10	**Cutting Size:**	Ø75mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-782RD-AB	**Color:**	Aluminium Brush
SKU:	3600	**Dimension:**	Ø91×25mm
Base:	GU10	**Cutting Size:**	Ø75mm
Material:	Aluminium	**Box Qty:**	100

Recessed Fitting GU10



Model No:	VT-782RD-B	**Color:**	Black
SKU:	8936	**Dimension:**	Ø91×25mm
Base:	1XGU10	**Cutting Size:**	Ø75mm
Material:	Aluminium	**Box Qty:**	100

Recessed Fitting GU10



Model No:	VT-782SQ-B	**Color:**	Black
SKU:	8937	**Dimension:**	91×91×25mm
Base:	1XGU10	**Cutting Size:**	75×75mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-782SQ-WH	**Color:**	White
SKU:	3605	**Dimension:**	91×91×25mm
Base:	1XGU10	**Cutting Size:**	75×75mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-782SQ-AB	**Color:**	Aluminium Brush
SKU:	3606	**Dimension:**	91×91×25mm
Base:	1XGU10	**Cutting Size:**	75×75mm
Material:	Aluminium	**Box Qty:**	100

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

Fitting-Square-GU10



Model No:	VT-783SQ-WH	**Color:**	White
SKU:	3607	**Dimension:**	173×91×25mm
Base:	2XGU10	**Cutting Size:**	155×75mm
Material:	Aluminium	**Box Qty:**	50

Fitting-Square-GU10



Model No:	VT-783SQ-AB	**Color:**	Aluminium Brush
SKU:	3608	**Dimension:**	173×91×25mm
Base:	GU10	**Cutting Size:**	155×75mm
Material:	Aluminium	**Box Qty:**	50

Fitting-Square-GU10



Model No:	VT-784SQ-WH	**Color:**	White
SKU:	3609	**Dimension:**	255×91×25mm
Base:	3XGU10	**Cutting Size:**	235×75mm
Material:	Aluminium	**Box Qty:**	50

Fitting-Square-GU10



Model No:	VT-784SQ-AB	**Color:**	Aluminium Brush
SKU:	3610	**Dimension:**	255×91×25mm
Base:	3XGU10	**Cutting Size:**	235×75mm
Material:	Aluminium	**Box Qty:**	50

Fitting-Round-GU10



Model No:	VT-7227RD-WH	**Color:**	White
SKU:	3469	**Dimension:**	Ø99×30.8mm
Base:	GU10	**Cutting Size:**	Ø74mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-7227RD-SN	**Color:**	Satin Nickel
SKU:	3470	**Dimension:**	Ø99×30.8mm
Base:	GU10	**Cutting Size:**	Ø74mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-7227RD-SS	**Color:**	Stainless Steel
SKU:	3471	**Dimension:**	Ø99×30.8mm
Base:	GU10	**Cutting Size:**	Ø74mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-785	**Color:**	White
SKU:	3611	**Dimension:**	88×38mm
Base:	GU10	**Cutting Size:**	Ø75mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-786	**Color:**	White
SKU:	3612	**Dimension:**	88×38mm
Base:	GU10	**Cutting Size:**	Ø75mm
Material:	Aluminium	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-7227SQ-WH	**Color:**	White
SKU:	3472	**Dimension:**	99×99×30.8mm
Base:	GU10	**Cutting Size:**	74×74mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-7227SQ-SN	**Color:**	Satin Nickel
SKU:	3473	**Dimension:**	99×99×30.8mm
Base:	GU10	**Cutting Size:**	74×74mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-7227SQ-SS	**Color:**	Stainless Steel
SKU:	3474	**Dimension:**	99×99×30.8mm
Base:	GU10	**Cutting Size:**	74×74mm
Material:	Ferrum	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-711-W-RD	**Color:**	White
SKU:	3669	**Dimension:**	82×101mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Zinc Alloy+Ferrum	**Box Qty:**	50

Zoom Fitting-Spotlight



Model No:	VT-700W	**Color:**	White
SKU:	3689	**Dimension:**	Ø102×46mm
Base:	GU10	**Cutting Size:**	93mm
Material:	Aluminium	**Box Qty:**	50

Zoom Fitting-Spotlight



Model No:	VT-700S	**Color:**	Satin Nickel
SKU:	3690	**Dimension:**	Ø102×46mm
Base:	GU10	**Cutting Size:**	93mm
Material:	Aluminium	**Box Qty:**	50

Fitting-Square-GU10



IP54 RATING

Model No:	VT-787RD-WH	**Color:**	White
SKU:	3613	**Dimension:**	84×38mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Zinc Alloy+Ferrum	**Box Qty:**	100

Fitting-Round-GU10



IP54 RATING

Model No:	VT-787RD-SN	**Color:**	Satin Nickel
SKU:	3614	**Dimension:**	84×38mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Zinc Alloy+Ferrum	**Box Qty:**	100

Fitting-Square-GU10



IP54 RATING

Model No:	VT-787SQ-WH	**Color:**	White
SKU:	3615	**Dimension:**	84×84×38mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Zinc Alloy+Ferrum	**Box Qty:**	100

Fitting-Square-GU10



IP54 RATING

Model No:	VT-787SQ-SN	**Color:**	Satin Nickel
SKU:	3616	**Dimension:**	84×84×38mm
Base:	GU10	**Cutting Size:**	75mm
Material:	Zinc Alloy+Ferrum	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-781RD-WH	**Color:**	White
SKU:	3595	**Dimension:**	100×45mm
Base:	GU10	**Cutting Size:**	90mm
Material:	Aluminium+Ferrum	**Box Qty:**	100

DEKRA TÜV SÜD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

Fitting-Round-GU10



Model No:	VT-781RD-SN	**Color:**	Satin Nickel
SKU:	3596	**Dimension:**	100×45mm
Base:	GU10	**Cutting Size:**	90mm
Material:	Aluminium+Ferrum	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-781SQ-WH	**Color:**	White
SKU:	3597	**Dimension:**	100×100×38mm
Base:	GU10	**Cutting Size:**	90×90mm
Material:	Aluminium+Ferrum	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-781SQ-SN	**Color:**	Satin Nickel
SKU:	3598	**Dimension:**	100×100×38mm
Base:	GU10	**Cutting Size:**	90×90mm
Material:	Aluminium+Ferrum	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-779-WH-RD	**Color:**	White
SKU:	3587	**Dimension:**	82×25mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc Alloy	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-779-SN-RD	**Color:**	Satin Nickel
SKU:	3588	**Dimension:**	82×25mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc Alloy	**Box Qty:**	100

Recessed Fitting GU10



Model No:	VT-779-BL	**Color:**	Black
SKU:	8955	**Dimension:**	82×25mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc alloy	**Box Qty:**	100

Fitting Round-GU10



Model No:	VT-779-B	**Color:**	Bronze
SKU:	8580	**Dimension:**	82×25mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc alloy	**Box Qty:**	100

Fitting Round-GU10



Model No:	VT-779-G	**Color:**	Gold
SKU:	8579	**Dimension:**	82×25mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc alloy	**Box Qty:**	100

Fitting-Round-GU10



Model No:	VT-779-CH-RD	**Color:**	Chrome
SKU:	3589	**Dimension:**	82×25mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc Alloy	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-779-WH-SQ	**Color:**	White
SKU:	3590	**Dimension:**	82×82×22mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc Alloy	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-779-SN-SQ	**Color:**	Satin Nickel
SKU:	3591	**Dimension:**	82×82×25mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc Alloy	**Box Qty:**	100

Fitting-Square-GU10



Model No:	VT-779-CH-SQ	**Color:**	Chrome
SKU:	3592	**Dimension:**	82×82×25mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc Alloy	**Box Qty:**	100

Fitting Square-GU10



Model No:	VT-779-SB	**Color:**	Bronze
SKU:	8582	**Dimension:**	82×82×22mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc alloy	**Box Qty:**	100

Fitting Square-GU10





Model No:	VT-779-SG	**Color:**	Gold
SKU:	8581	**Dimension:**	82×82×22mm
Base:	GU10	**Cutting Size:**	74mm
Material:	Zinc alloy	**Box Qty:**	100

Fitting-Square-GU10

Model No:	VT-858RD	**Color:**	White
SKU:	3694	**Dimension:**	70×90×95mm
Base:	G9	**Cutting Size:**	N/A
Material:	Gypsum	**Box Qty:**	24

Fitting-Square-G9



Model No:	VT-858SQ	**Color:**	White
SKU:	3695	**Dimension:**	70×100×100mm
Base:	G9	**Cutting Size:**	N/A
Material:	Gypsum	**Box Qty:**	24

Fitting-Square-GU10



Model No:	VT-859SQ	**Color:**	White
SKU:	3696	**Dimension:**	100×100×40mm
Base:	GU10	**Cutting Size:**	103×103mm
Material:	Gypsum	**Box Qty:**	40

Fitting-Square-GU10



Model No:	VT-859RD	**Color:**	White
SKU:	3697	**Dimension:**	ø100×40mm
Base:	GU10	**Cutting Size:**	ø103
Material:	Gypsum	**Box Qty:**	40

Fitting-Suspended-GU10



Model No:	VT-864-G	**Color:**	White+Matt Rose Gold
SKU:	3111	**Dimension:**	ø250×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Pendant Metal-Gun Black Bottom



Model No:	VT-864-GBC	**Color:**	Grey+Gun Black
SKU:	3134	**Dimension:**	ø250×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

Pendant Metal-Chrome Bottom



Model No:	VT-864CHC	**Color:**	Grey+Chrome
SKU:	3135	**Dimension:**	ø250×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Pendant Metal-Gun Black Bottom



Model No:	VT-864-GB	**Color:**	White+Gun Black
SKU:	3112	**Dimension:**	ø250×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Pendant Metal-Chrome Bottom



Model No:	VT-864-CH	**Color:**	White+Chrome
SKU:	3129	**Dimension:**	ø250×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Pendant Metal-Matt Rose Gold Bottom



Model No:	VT-864-MR	**Color:**	Grey+Matt Rose Gold
SKU:	3130	**Dimension:**	ø250×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Surface Metal-Gun Black Bottom



Model No:	VT-865-GBM	**Color:**	White+Gun Black
SKU:	3136	**Dimension:**	ø200×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Surface Metal-Matt Rose Gold Bottom



Model No:	VT-865-MRC	**Color:**	Grey+Matt Rose Gold
SKU:	3137	**Dimension:**	ø200×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Surface Metal-Chrome Metal



Model No:	VT-865CHC	**Color:**	Grey+Chrome
SKU:	3138	**Dimension:**	ø200×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Surface Metal-Gun Black Bottom



Model No:	VT-865-GBC	**Color:**	Grey+Gun Black
SKU:	3139	**Dimension:**	ø200×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Surface Metal-Matt Rose Gold Bottom



Model No:	VT-865-MRM	**Color:**	White+Matt Rose Gold
SKU:	3113	**Dimension:**	ø200×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Surface Metal-Chrome Metal



Model No:	VT-865CHM	**Color:**	White+Chrome
SKU:	3114	**Dimension:**	ø200×80mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	9

Square Metal-Gun Black Bottom



Model No:	VT-860-GB	**Color:**	White+Gun Black
SKU:	3140	**Dimension:**	100×100×130mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	12

Square Metal-Chrome Bottom



Model No:	VT-860-CH	**Color:**	White+Chrome
SKU:	3116	**Dimension:**	100×100×130mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	12

Square Metal-Matt Rose Gold Bottom



Model No:	VT-860-MRM	**Color:**	Grey+Matt Rose Gold
SKU:	3141	**Dimension:**	100×100×130mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	12

Surface Fitting Square-GU10



Model No:	VT-882-SQ-BG	**Color:**	Black+Gold
SKU:	8956	**Dimension:**	74×74×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Square Metal-Chrome Bottom



Model No:	VT-860-CHM	**Color:**	Grey+Chrome
SKU:	3142	**Dimension:**	100×100×130mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	12

Surface Fitting Square-GU10



Model No:	VT-882-SQ-BRG	**Color:**	Black+Rose Gold
SKU:	8993	**Dimension:**	74×74×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Square Metal-Gun Black Bottom



Model No:	VT-860-GBM	**Color:**	Grey+Gun Black
SKU:	3143	**Dimension:**	100×100×130mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	12

Surface Fitting Square-GU10



Model No:	VT-882-SQ-BC	**Color:**	Black+Chrome
SKU:	8994	**Dimension:**	74×74×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Square Metal-Matt Rose Gold Bottom



Model No:	VT-860-MR	**Color:**	White+Matt Rose Gold
SKU:	3115	**Dimension:**	100×100×130mm
Base:	GU10	**Cutting Size:**	N/A
Material:	Gypsum with metal	**Box Qty:**	12

Surface Fitting Square-GU10



Model No:	VT-882-SQ-B	**Color:**	Black+Black
SKU:	8995	**Dimension:**	74×74×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

Surface Fitting Round-GU10



Model No:	VT-882-RD-BG	**Color:**	Black+Gold
SKU:	8996	**Dimension:**	ø80×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Round-GU10



Model No:	VT-882-RD-BRG	**Color:**	Black+Rose Gold
SKU:	8997	**Dimension:**	ø80×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Round-GU10



Model No:	VT-882-RD-BC	**Color:**	Black+Chrome
SKU:	8998	**Dimension:**	ø80×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Round-GU10



Model No:	VT-882-RD-B	**Color:**	Black+Black
SKU:	8999	**Dimension:**	ø80×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Square-GU10



Model No:	VT-882-B	**Color:**	White + Black Reflector
SKU:	8584	**Dimension:**	74×74×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Square-GU10



Model No:	VT-882-C	**Color:**	White + Chrome Reflector
SKU:	8585	**Dimension:**	74×74×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Square-GU10



Model No:	VT-882-G	**Color:**	White + Gold Reflector
SKU:	8586	**Dimension:**	74×74×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Square-GU10



Model No:	VT-882-SRG	**Color:**	White + Rose gold Reflector
SKU:	8587	**Dimension:**	74×74×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Square-GU10



Model No:	VT-882-SW	**Color:**	White + White Reflector
SKU:	8583	**Dimension:**	74×74×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Round-GU10



Model No:	VT-882-RB	**Color:**	White + Black Reflector
SKU:	8589	**Dimension:**	ø80×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Round-GU10



Model No:	VT-882-RC	**Color:**	White + Chrome Reflector
SKU:	8590	**Dimension:**	ø80×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Round-GU10



Model No:	VT-882-RG	**Color:**	White + Gold Reflector
SKU:	8591	**Dimension:**	ø80×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Round-GU10



Model No:	VT-882-RRG	**Color:**	White + Rose gold Reflector
SKU:	8592	**Dimension:**	ø80×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Surface Fitting Round-GU10



Model No:	VT-882-RW	**Color:**	White + White Reflector
SKU:	8588	**Dimension:**	ø80×140mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium + PC	**Box Qty:**	50

Recessed-Matt Rose Gold Bottom-Square



Model No:	VT-862-MRW	**Color:**	White+Matt Rose Gold
SKU:	3117	**Dimension:**	100×100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Recessed-Matt Rose Gold Bottom-Square



Model No:	VT-862-MRG	**Color:**	Grey+Matt Rose Gold
SKU:	3118	**Dimension:**	100×100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Recessed-Chrome Bottom-Square



Model No:	VT-862-CHW	**Color:**	White+Chrome
SKU:	3119	**Dimension:**	100×100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Recessed-Chrome Bottom-Square



Model No:	VT-862-CHG	**Color:**	Grey+Chrome
SKU:	3120	**Dimension:**	100×100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Recessed-Matt Rose Gold Bottom-Square



Model No:	VT-862-MRR	**Color:**	Off White+Matt Rose Gold
SKU:	3121	**Dimension:**	100×100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Recessed-Chrome Bottom-Square



Model No:	VT-862-CHR	**Color:**	Off White+Chrome
SKU:	3122	**Dimension:**	100×100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

Recessed-Matt Rose Gold Bottom-Round



Model No:	VT-862-MRP	**Color:**	White+Matt Rose Gold
SKU:	3123	**Dimension:**	ø100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Recessed-Chrome Bottom-Round



Model No:	VT-862-MG	**Color:**	Grey+Chrome
SKU:	3128	**Dimension:**	ø100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Recessed-Matt Rose Gold Bottom-Round



Model No:	VT-862-MGRD	**Color:**	Grey+Matt Rose Gold
SKU:	3124	**Dimension:**	ø100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Ceiling Movable-White Bottom-Square



Model No:	VT-863	**Color:**	White
SKU:	3144	**Dimension:**	200×200mm
Base:	GU10	**Cutting Size:**	206×206mm
Material:	Gypsum with metal	**Box Qty:**	12

Recessed-Matt Rose Gold Bottom-Round



Model No:	VT-862-MRC	**Color:**	Off White+Matt Rose Gold
SKU:	3125	**Dimension:**	ø100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Fitting-Recessed-Black Metal-Round



Model No:	VT-866-BRD	**Color:**	White+Black
SKU:	3145	**Dimension:**	ø100mm
Base:	GU10	**Cutting Size:**	ø103mm
Material:	Gypsum with metal	**Box Qty:**	30

Recessed-Chrome Bottom-Round



Model No:	VT-862-MRD	**Color:**	Off White+Chrome
SKU:	3126	**Dimension:**	ø100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Fitting-Recessed-Chrome Metal-Round

Model No:	VT-866-CRD	**Color:**	White+Chrome
SKU:	3146	**Dimension:**	ø100mm
Base:	GU10	**Cutting Size:**	ø103mm
Material:	Gypsum with metal	**Box Qty:**	30

Recessed-Chrome Bottom-Round



Model No:	VT-862-CRD	**Color:**	White+Chrome
SKU:	3127	**Dimension:**	ø100×40mm
Base:	GU10	**Cutting Size:**	ø80mm
Material:	Gypsum with metal	**Box Qty:**	24

Fitting-Recessed-Matt Rose Gold Metal-Round



Model No:	VT-866-MRD	**Color:**	White+Matt Rose Gold
SKU:	3147	**Dimension:**	ø100mm
Base:	GU10	**Cutting Size:**	ø103mm
Material:	Gypsum with metal	**Box Qty:**	30

Fitting-Recessed-Blcak Metal-Square



Model No:	VT-866-BSQ	**Color:**	White+Black
SKU:	3148	**Dimension:**	ø100×100mm
Base:	GU10	**Cutting Size:**	103×103mm
Material:	Gypsum with metal	**Box Qty:**	30

Fitting-Recessed-Chrome Metal-Square



Model No:	VT-866-CSQ	**Color:**	White+Chrome
SKU:	3149	**Dimension:**	ø100×100mm
Base:	GU10	**Cutting Size:**	103×103mm
Material:	Gypsum with metal	**Box Qty:**	30

Fitting-Recessed-Matt Rose Gold-Square



Model No:	VT-866-GSQ	**Color:**	White+Matt Rose Gold
SKU:	3150	**Dimension:**	ø100×100mm
Base:	GU10	**Cutting Size:**	103×103mm
Material:	Gypsum with metal	**Box Qty:**	30

Fitting-Recessed-Square



Model No:	VT-867-SQ	**Color:**	White
SKU:	3151	**Dimension:**	ø120×120mm
Base:	GU10	**Cutting Size:**	125×125mm
Material:	Gypsum with metal	**Box Qty:**	24

Fitting-Recessed-Round



Model No:	VT-867-RD	**Color:**	White
SKU:	3152	**Dimension:**	ø120mm
Base:	GU10	**Cutting Size:**	ø125mm
Material:	Gypsum with metal	**Box Qty:**	24

Ceiling Fitting-Gu10

Model No:	VT-788	**Color:**	White
SKU:	3617	**Dimension:**	140×75×138mm
Base:	1XGU10	**Cutting Size:**	NA
Material:	Aluminium	**Box Qty:**	20

Ceiling Fitting-Gu10

Model No:	VT-789	**Color:**	White
SKU:	3618	**Dimension:**	230×75×138mm
Base:	2XGU10	**Cutting Size:**	NA
Material:	Aluminium	**Box Qty:**	20

Ceiling Fitting-Gu10

Model No:	VT-790	**Color:**	White
SKU:	3619	**Dimension:**	390×75×138mm
Base:	3XGU10	**Cutting Size:**	NA
Material:	Aluminium	**Box Qty:**	10

Ceiling/Wall Fitting-Gu10



Model No:	VT-823	**Color:**	White
SKU:	7980	**Dimension:**	120×144.8mm
Base:	1XGU10	**Cutting Size:**	NA
Material:	PC	**Box Qty:**	50

Ceiling/Wall Fitting-Gu10



Model No:	VT-897	**Color:**	White
SKU:	7981	**Dimension:**	120×144.8mm
Base:	2XGU10	**Cutting Size:**	NA
Material:	PC	**Box Qty:**	50

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

Ceiling/Wall Fitting-Gu10



Model No:	VT-899	**Color:**	White
SKU:	7982	**Dimension:**	145×144.8mm
Base:	3XGU10	**Cutting Size:**	NA
Material:	PC	**Box Qty:**	20

Gu10-Holder-PVC Cable

5 pcs Pack



Model No:	PVC Cable-5pc	**Color:**	White
SKU:	34235	**Dimension:**	150mm
Base:	GU10	**Cutting Size:**	NA
Material:	Ceramic	**Box Qty:**	100

Gu10-Holder-PVC Cable

Model No:	PVC Cable	**Color:**	White
SKU:	3423	**Dimension:**	150mm
Base:	GU10	**Cutting Size:**	NA
Material:	Ceramic	**Box Qty:**	500

GU10 Silicon Wire-5Pc Pack

5 pcs Pack

Model No:	VT-791	**Color:**	White
SKU:	36205	**Dimension:**	158mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium Ceramic	**Box Qty:**	500

GU10 Silicon Wire

Model No:	VT-791-W	**Color:**	White
SKU:	3620	**Dimension:**	158mm
Base:	GU10	**Cutting Size:**	NA
Material:	Aluminium Ceramic	**Box Qty:**	500

LED FLOODLIGHTS

V-TAC's LED floodlights are ideal for lighting driveways, gardens, and buildings. These energy-efficient lights emit bright, vibrant light and make an eco-friendly alternative for traditional halogen floodlights and metal halide fixtures.

Key Features

- Available from 10w up to 100w
- Premium quality aluminum alloy body
- Fascia glass sealed with silicone rubber ensuring superior waterproof /airtight performance
- High power LED chip
- Built-in constant current driver
- Built-in power supply, no external ballast required

Application

Widely used for lighting driveways, gardens & buildings, commercial bill boards & hoardings, sports grounds & parking lots

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED FLOODLIGHTS | Economical Series

NEW

- AC:220-240V, 50/60Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle
- 90×86×27mm110°

IP65 RATING

2 YEAR WARRANTY

ECONOMICAL HIGH-QUALITY SERIES

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-4914-B	6727 – 3000K WARM WHITE 6728 – 4000K DAY WHITE 6729 – 6400K WHITE	10w	750	90×86×27mm	60
VT-4924-B	6737 – 3000K WARM WHITE 6738 – 4000K DAY WHITE 6739 – 6400K WHITE	20w	1650	120×105×27mm	40
VT-4934-B	6743 – 3000K WARM WHITE 6744 – 4000K DAY WHITE 6745 – 6400K WHITE	30w	2510	150×122×27mm	20
VT-4954-B	6749 – 3000K WARM WHITE 6750 – 4000K DAY WHITE 6751 – 6400K WHITE	50w	4300	180×150×27mm	20
VT-49104-B	6721 – 3000K WARM WHITE 6722 – 4000K DAY WHITE 6723 – 6400K WHITE	100w	8700	270×222×27mm	10
VT-49204-B	6733 – 4000K DAY WHITE 6734 – 6400K WHITE	200w	17600	400×333×32.5mm	5

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED FLOODLIGHTS | Economical Series

NEW

- AC:220-240V, 50/60Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle
- 90×86×27mm110°

IP65 RATING

2 YEAR WARRANTY

ECONOMICAL HIGH-QUALITY SERIES

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-4914-W	6730 – 3000K WARM WHITE 6731 – 4000K DAY WHITE 6732 – 6400K WHITE	10w	750	90×86×27mm	60
VT-4924-W	6740 – 3000K WARM WHITE 6741 – 4000K DAY WHITE 6742 – 6400K WHITE	20w	1650	120×105×27mm	40
VT-4934-W	6746 – 3000K WARM WHITE 6747 – 4000K DAY WHITE 6748 – 6400K WHITE	30w	2510	150×122×27mm	20
VT-4954-W	6752 – 3000K WARM WHITE 6753 – 4000K DAY WHITE 6754 – 6400K WHITE	50w	4300	180×150×27mm	20
VT-49104-W	6724 – 3000K WARM WHITE 6725 – 4000K DAY WHITE 6726 – 6400K WHITE	100w	8700	270×222×27mm	10
VT-49204-W	6735 – 4000K DAY WHITE 6736 – 6400K WHITE	200w	17600	400×333×32.5mm	5

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

E Series-White Body

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle





IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-4011W	5943 – 3000K WARM WHITE 5944 – 4000K DAY WHITE 5945 – 6500K WHITE	10w	850	40

E Series-White Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle





IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-4021W	5949 – 3000K WARM WHITE 5950 – 4000K DAY WHITE 5951 – 6500K WHITE	20w	1700	20
VT-4021W-N	215949 – 3000K WARM WHITE 215950 – 4000K DAY WHITE 215951 – 6500K WHITE	20w	1620	20

E Series-White Body

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle





IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-4031W	5955 – 3000K WARM WHITE 5956 – 4000K DAY WHITE 5957 – 6500K WHITE	30w	2550	20
VT-4031W-N	215955 – 3000K WARM WHITE 215956 – 4000K DAY WHITE 215957 – 6500K WHITE	30w	2510	20

E Series-White Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle





IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-4051W	5961 – 3000K WARM WHITE 5962 – 4000K DAY WHITE 5963 – 6500K WHITE	50w	4250	10
VT-4051W-N	215961 – 3000K WARM WHITE 215962 – 4000K DAY WHITE 215963 – 6500K WHITE	50w	4300	10

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

E Series-White Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle





IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-40101W	5967 – 3000K WARM WHITE 5968 – 4000K DAY WHITE 5969 – 6500K WHITE	100w	8500	5
VT-40101W-N	215967 – 3000K WARM WHITE 215968 – 4000K DAY WHITE 215969 – 6500K WHITE	100w	8700	10

E Series-Black Body

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle



IP65 RATING

Red Green Blue

Model	SKU	Watts	Box Qty
VT-4011	5988 – GREEN 5989 – RED 5990 – BLUE	10w	40

E Series-Black Body

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle



IP65 RATING

Red Green Blue

Model	SKU	Watts	Box Qty
VT-4021	5991 – GREEN 5992 – RED 5993 – BLUE	20w	20

E Series-Black Body

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle





IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-4011B	5940 – 3000K WARM WHITE 5941 – 4000K DAY WHITE 5942 – 6500K WHITE	10w	850	40

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

E Series-Black Body

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle





IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-4021B	5946 - 3000K WARM WHITE 5947 - 4000K DAY WHITE 5948 - 6500K WHITE	20w	1700	20
VT-4021B-N	215946 - 3000K WARM WHITE 215947 - 4000K DAY WHITE 215948 - 6500K WHITE	20w	1620	20

E Series-Black Body

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle





IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-4031B	5952 - 3000K WARM WHITE 5953 - 4000K DAY WHITE 5954 - 6500K WHITE	30w	2550	20
VT-4031B-N	215952 - 3000K WARM WHITE 215953 - 4000K DAY WHITE 215954 - 6500K WHITE	30w	2510	20

E Series-Black Body

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle





IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-4051B	5958 - 3000K WARM WHITE 5959 - 4000K DAY WHITE 5960 - 6500K WHITE	50w	4250	10
VT-4051B-N	215958 - 3000K WARM WHITE 215959 - 4000K DAY WHITE 215960 - 6500K WHITE	50w	4300	10

E Series-Black Body

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >70
- 110° Beam Angle





IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-40101B	5964 - 3000K WARM WHITE 5965 - 4000K DAY WHITE 5966 - 6500K WHITE	100w	8500	5
VT-40101B-N	215964 - 3000K WARM WHITE 215965 - 4000K DAY WHITE 215966 - 6500K WHITE	100w	8700	10

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

160lm Slimline Series

- AC:200-240V
- PF: >0.9
- 110° Beam Angle



Model	SKU	Watts	Box Qty
VT-4932	5995 - RGB	30w	20

IP65 RATING

RGB RF CONTROL

Floodlight-Remote Control-RGB

- AC:200-240V
- PF: >0.9
- 110° Beam Angle



Model	SKU	Watts	Box Qty
VT-4952	5996 - RGB	50w	10

IP65 RATING

RGB RF CONTROL

Smart Floodlight

- AC:220-240V
- PF: >0.9
- CRI: >80
- 100° Beam Angle



Model	SKU	Watts	Lumen	Box Qty
VT-5020-W	5984 - RGB+W/WW/DW	20w	1400	20

V-TAC SMART

CCT and Dimming
VIA SMART PHONE APP

Smart Floodlight

- AC:220-240V
- PF: >0.9
- CRI: >80
- 100° Beam Angle



Model	SKU	Watts	Lumen	Box Qty
VT-5020-B	5985 - RGB+W/WW/DW	20w	1400	20

V-TAC SMART

CCT and Dimming
VIA SMART PHONE APP

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

V-TAC SMART

Wi Fi

CAMERA

MOTION PIR SENSOR

PIR Sensor-Wi-Fi-Camera

- Detection Distance: 0-12M
- Detection Angle: 180°
- Video Compression: H.264 /MJPEG dual video stream
- Image Resolution: 1280*720
- Image sensor: 1/4 " 1Megapixel CMOS
- Pixels: 1 million pixels
- Delay Time: 0-30S
- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 180° Beam Angle
- 248x 162x 181mm180°



Model	SKU	Watts	Lumen	Box Qty
VT-4818W	5745 - 6000K WHITE	18w	600	4

V-TAC SMART

Wi Fi

CAMERA

MOTION PIR SENSOR

PIR Sensor-Wi-Fi-Camera

- Detection Distance: 0-12M
- Detection Angle: 180°
- Video Compression: H.264 /MJPEG dual video stream
- Image Resolution: 1280*720
- Image sensor: 1/4 " 1Megapixel CMOS
- Pixels: 1 million pixels
- Delay Time: 0-30S
- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 180° Beam Angle
- 248×162×181mm180°



Model	SKU	Watts	Lumen	Box Qty
VT-4818B	5917 - 6000K WHITE	18w	600	4

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Waterproof Box Terminal Block

IP66 RATING

Model No:	VT-881	**Cable Diameter:**	5–9mm
SKU:	5987	**Ampere:**	24A
Wire Range :	0.5~2.5mm²	**Fire Retardant Level:**	V2
Voltage:	AC:450V	**Box Qty:**	150

Waterproof Box Terminal Block

ULTRAVIOLET PROTECTION
IP68 RATING

Model No:	VT-868-w	**Cable Diameter:**	5–9mm
SKU:	5986	**Ampere:**	16A
Wire Range :	0.5~1.5mm²	**Fire Retardant Level:**	V2
Voltage:	AC:450V	**Box Qty:**	1000

Waterproof Box Terminal Block

ULTRAVIOLET PROTECTION
IP68 RATING

Model No:	VT-868	**Cable Diameter:**	5–9mm
SKU:	5977	**Ampere:**	16A
Wire Range :	0.5~1.5mm²	**Fire Retardant Level:**	V2
Voltage:	AC:450V	**Box Qty:**	1000

Waterproof Box Terminal Block

ULTRAVIOLET PROTECTION
IP68 RATING

Model No:	VT-869-B	**Cable Diameter:**	8–12mm
SKU:	5978	**Ampere:**	24A
Wire Range :	0.5~4mm²	**Fire Retardant Level:**	V2
Voltage:	AC:450V	**Box Qty:**	200

Waterproof Box Terminal Block

ULTRAVIOLET PROTECTION
IP68 RATING

Model No:	VT-869-W	**Cable Diameter:**	8–12mm
SKU:	5979	**Ampere:**	24A
Wire Range :	0.5~4mm²	**Fire Retardant Level:**	V2
Voltage:	AC:450V	**Box Qty:**	200

Waterproof Box Terminal Block



ULTRAVIOLET PROTECTION
IP68 RATING

Model No:	VT-870-B	**Cable Diameter:**	8–12mm
SKU:	5980	**Ampere:**	24A
Wire Range :	0.5~4mm²	**Fire Retardant Level:**	V2
Voltage:	AC:450V	**Box Qty:**	100

Waterproof Box Terminal Block



ULTRAVIOLET PROTECTION
IP68 RATING

Model No:	VT-870-W	**Cable Diameter:**	8–12mm
SKU:	5981	**Ampere:**	24A
Wire Range :	0.5~4mm²	**Fire Retardant Level:**	V2
Voltage:	AC:450V	**Box Qty:**	100

Waterproof Box Terminal Block



ULTRAVIOLET PROTECTION
IP68 RATING

Model No:	VT-871-B	**Cable Diameter:**	8–12mm
SKU:	5982	**Ampere:**	24A
Wire Range :	0.5~4mm²	**Fire Retardant Level:**	V2
Voltage:	AC:450V	**Box Qty:**	100

Waterproof Box Terminal Block



ULTRAVIOLET PROTECTION
IP68 RATING

Model No:	VT-871-W	**Cable Diameter:**	8–12mm
SKU:	5983	**Ampere:**	24A
Wire Range :	0.5~4mm²	**Fire Retardant Level:**	V2
Voltage:	AC:450V	**Box Qty:**	100

Waterproof Box Terminal Block

ULTRAVIOLET PROTECTION
IP65 RATING

Model No:	VT-7224-B	**Material:**	Polypropylene (PP)
SKU:	3578	**Dimension:**	123×46×33mm
Wire Range :	0.5~2.5mm²	**IP Rating:**	IP65
Voltage:	AC:250V Max	**Box Qty:**	160

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Waterproof Box Terminal Block

ULTRAVIOLET PROTECTION

IP65 RATING

Model No:	VT-7224-W	**Material:**	Polypropylene (PP)
SKU:	5897	**Dimension:**	123×46×33mm
Wire Range :	0.5–2.5mm²	**IP Rating:**	IP65
Voltage:	AC:250V Max	**Box Qty:**	240

Waterproof Box Terminal Block

ULTRAVIOLET PROTECTION

IP68 RATING

Model No:	VT-792-B	**Material:**	Flame Retardant PP
SKU:	3621	**Dimension:**	Ø27×76mm
Wire Range :	4–6.5mm	**IP Rating:**	IP68
Voltage:	AC:220V	**Box Qty:**	500

Waterproof Box Terminal Block

ULTRAVIOLET PROTECTION

IP68 RATING

Model No:	VT-792-W	**Material:**	Flame Retardant PP
SKU:	5896	**Dimension:**	Ø27×76mm
Wire Range :	4–6.5mm	**IP Rating:**	IP68
Voltage:	AC:220V	**Box Qty:**	500

Tripod Stand-Yellow



IP65 RATING

Model	SKU	Size	Box Qty
VT-41150Y	9104	900×940~1800mm	8

Tripod Stand-Black



IP65 RATING

Model	SKU	Size	Box Qty
VT-41150B	9546	900×940~1800mm	8

Billboard Stand

Model	SKU	Suitable For	Size	Box Qty
VT-794	3623	10–50w	850×150mm	4

Billboard Stand

Model	SKU	Suitable For	Size	Box Qty
VT-793	3622	70–200w	870×200mm	4

Floodlight Spike-Grey

IP65 RATING

Model	SKU	Suitable For	Size	Box Qty
VT-854-G	7533	10–50W	Ø35xH150mm	200
VT-855-G	7536	10–150W	Ø60xH265mm	100

Floodlight Spike-White

IP65 RATING

Model	SKU	Suitable For	Size	Box Qty
VT-854-W	7534	10–50W	Ø35xH150mm	200
VT-855-W	7537	10–150W	Ø60xH265mm	100

Floodlight Spike-Black

IP65 RATING

Model	SKU	Suitable For	Size	Box Qty
VT-854-B	7535	10–50W	Ø35xH150mm	200
VT-855-B	7538	10–150W	Ø60xH265mm	100



LED BIG PANELS

Experience consistent illumination and zero hot or cold spots, introducing slim and sleek LED Panel Lighting from V-TAC.

Key Features

- Ultra Slim Design
- Contemporary & Elegant Design
- Higher Light Transmission Rate
- Exterior shell, cannot be easily damaged
- No infrared, does not attract flies
- Easy to install
- No Lead or mercury content hence environment friendly
- Dimmable options available in selected models

Application

Offices, conference room, hospitals, hotels, shopping malls, showroom, kitchen and domestic lighting etc.

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED BIG PANELS

Backlit Panel-60×60

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 110° Beam Angle
- On/0ff: >15000
- Life span:30,000 Hours
- Body Type:
- Dimension :595×595×33mm

5 YEAR WARRANTY

120 lm/W



Model	SKU	Watts	Lumen	Size	Box Qty
VT-6436	216706 – 4000K DAY WHITE 216707 – 6500K WHITE	36W	4320	595×595×33mm	6

LED BIG PANELS

CCT Changing Panel

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >10000
- Life span:20,000-hour
- Body Type: FE+PP
- Dimension :595×595×29mm

EASY TOGGLE SWITCH

3000K 4000K 6400K

EASY ACCESS FOR COLOR CHANGING WITH BUTTON

3 IN 1 COLOR CHANGING



Model	SKU	Watts	Lumen	Size	Box Qty
VT-6240	66051 – 3IN1	40w Single pack	3200	595×595×29mm	6
VT-6240-6	6605 – 3IN1	40w 6 pcs pack	3200	595×595×29mm	6

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC

www.tuv.com ID 1111227954

ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED BIG PANELS

Big Panels-60×60-CRI>95

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >95
- 120° Beam Angle
- On/Off: >10000
- Life span:20,000-hour
- Body Type: Aluminium+PMMA+PP
- Dimension :595×595×14mm



Witness the *True to Life* Colors

A CRI score of 95 is considered very high, and indicates that a light source will make objects appear very similar to how they would look under natural lighting conditions.

Without a high CRI light source, objects can appear faded, dull or inaccurate.



Model	SKU	Watts	Lumen	Size	Box Qty
VT-6245	8086 – 3000K WARM WHITE 8087 – 4000K DAY WHITE 8088 – 6400K WHITE	45w 6 pcs pack	3600	595×595×14mm	6

LED BIG PANELS

Waterproof Big Panel-60×60-IP65

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/Off: >15000
- Life span:20,000-hour
- Body Type: Aluminium+PMMA+PS
- Dimension :595×595×11mm

IP65 RATING



Model	SKU	Watts	Lumen	Size	Box Qty
VT-6140	6603 – 4000K DAY WHITE 6604 – 6400K WHITE	40w 6 pcs pack	4400	595×595×11mm	6

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED BIG PANELS

Big Panels-60×60-Lifud Driver

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >10000
- Life span:20,000-hour
- Body Type: Aluminium+PS+PP
- Dimension :595×595×8.5mm

LiFud® Driver



Model	SKU	Watts	Lumen	Size	Box Qty
VT-6236	8082 - 4000K DAY WHITE 8081 - 6400K WHITE	36w Single pack	3240	595×595×8.5mm	6
VT-6242 NEW	216621 - 6500K WHITE	40w	4400	595×595×8.5mm	6

LED BIG PANELS

Surface/Recessed Panel-60×60

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >10000
- Life span:20,000-hour
- Body Type: FE+PP
- Dimension :595×595×29mm



Model	SKU	Watts	Lumen	Size	Box Qty
VT-6142-1	64511 - 4000K DAY WHITE 64521 - 6500K WHITE	40w 6 pcs pack	3200	595×595×29mm	4
VT-6142	6451 - 4000K DAY WHITE 6452 - 6500K WHITE	40w 6 pcs pack High Lumen	4000	595×595×29mm	6
VT-6170	6453 - 4000K DAY WHITE 6454 - 6500K WHITE	70w 6 pcs pack	5950	595×595×29mm	6

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS CE/EMC

www.tuv.com ID 1111227954

ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED BIG PANELS

Big Panels-UGR<19

- DC:30-42V
- PF: >0.9
- CRI: >80
- 110°-90° Beam Angle
- On/Off: >15000
- Life span:30,000 Hours
- Body Type: Aluminium+TPA PC Diffuser

5 YEAR WARRANTY

LG7 Compliant

UGR<19

Model	SKU	Watts	Lumen	Size	Box Qty
VT-6242U NEW	6777 - 4000K DAY WHITE 6778 - 6400K WHITE	40w	4000	595×595×34mm	6
VT-6068-6	62206 - 3000K WARM WHITE 62186 - 4000K DAY WHITE 62196 - 6400K WHITE	45w 6 pcs pack 60×60	3600	595×595×14mm	6
VT-6069	6222 - 3000K WARM WHITE 6217 - 4000K DAY WHITE 6221 - 6400K WHITE	45w 6 pcs pack 62×62	v3600	620×620×13mm	6
VT-6069-N	2162176 - 4000K DAY WHITE	36w	3100	620×620×12.5mm	6
VT-6068-1 NEW	6676 - 4000K DAY WHITE	45w	4830	595×595×9mm	6
VT-6069-1 NEW	6674 - 4000K DAY WHITE	45w	4830	620×620×9mm	6

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED BIG PANELS

Big Panels-High Lumen

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >10000
- Life span:30,000-hour
- Body Type: Aluminium+PMMA+PP
- Dimension :620×620×13mm

120 lm/W

Model	SKU	Watts	Lumen	Size	Box Qty
VT-6262	6471 – 4000K DAY WHITE	29w 6 pcs pack 62×62	3480	620×620×13mm	6
VT-6129	6240 – 3000K WARM WHITE 6241 – 4000K DAY WHITE 6242 – 6400K WHITE	29w Single pack	3480	595×595×13mm	6
VT-6129-6	62406 – 3000K WARM WHITE 62416 – 4000K DAY WHITE 62426 – 6400K WHITE	29w 6 pcs pack	3480	595×595×13mm	6
VT-6129-6-N	2162406 – 3000K WARM WHITE 2162416 – 4500K DAY WHITE 2162426 – 6400K WHITE	29w	3960	595×595×12.5mm	6
VT-6262-1 NEW	6675 – 4000K DAY WHITE	29w	3480	620×620×9mm	6
VT-6136	6376 – 3000K WARM WHITE 6238 – 4000K DAY WHITE 6239 – 6400K WHITE	36w 6 pcs pack	4320	595×595×13mm	6
VT-6145	6236 – 4000K DAY WHITE 6237 – 6400K WHITE	45w Single pack	5400	595×595×13mm	6
VT-6145-N	216237 – 6400K WHITE	40w	5400	595×595×12.5mm	6
VT-6145-6	63776 – 3000K WARM WHITE 62366 – 4000K DAY WHITE 62376 – 6400K WHITE	45w 6 pcs pack	5400	595×595×13mm	6

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED BIG PANELS

Big Panels-60×60

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >10000
- Life span:20,000-hour
- Body Type: Aluminium+PS+PP
- Dimension :595×595×8.5mm

Model	SKU	Watts	Lumen	Size	Box Qty
VT-6237	80831 - 3000K WARM WHITE 80841 - 4000K DAY WHITE 80851 - 6400K WHITE	36w Single pack	3240	595×595×8.5mm	6
VT-6237-N	2180841 - 4000K DAY WHITE	32w	3960	595×595×8.5mm	6
VT-6237-6	8083 - 3000K WARM WHITE 8084 - 4000K DAY WHITE 8085 - 6400K WHITE	36w 6 pcs pack	3240	595×595×8.5mm	6
VT-6237-1 NEW	6673 - 4000K DAY WHITE	36w	3820	595×595×9mm	6
VT-6060	6028 - 3000K WARM WHITE 6024 - 4000K DAY WHITE 6025 - 6400K WHITE	45w Single pack	3600	595×595×14mm	6
VT-6060-N	216025 - 6400K WHITE	40w	4950	595×595×12.5mm	6
VT-6340-6-N	216671 - 4000K DAY WHITE 216672 - 6400K WHITE	40w	4950	595×595×8.5mm	6
VT-6060-6	60286 - 3000K WARM WHITE 60246 - 4000K DAY WHITE 60256 - 6400K WHITE	45w 6 pcs pack	3600	595×595×14mm	6
VT-6060-6-N	2160286 - 3000K WARM WHITE 2160246 - 4500K DAY WHITE 2160256 - 6400K WHITE	40w	4950	595×595×12.5mm	6

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED BIG PANELS

Transparent Panel-120×30

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 140° Beam Angle
- On/0ff:
- Life span:30,000-hour
- Body Type: Aluminium+PC
- Dimension :1210×319mm

TRIAC DIMMABLE

5 YEAR WARRANTY



Model	SKU	Watts	Lumen	Size	Box Qty
VT-6144	6458 - 4000K DAY WHITE	40w	3200	1210×319mm	4

LED BIG PANELS

Big Panels-120×30

- AC:200-240V, 50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >10000
- Life span:20,000 Hours
- Body Type: FE+PP
- Dimension :1195×295×29mm



Model	SKU	Watts	Lumen	Size	Box Qty
VT-6147	6624 - 3000K WARM WHITE 6625 - 4000K DAY WHITE 6626 - 6500K WHITE	40w	4000	1195×295×29mm	6

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC

www.tuv.com ID 1111227954

ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED BIG PANELS

Big Panels-High Lumen-120×30

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Aluminium+PMMA+PP
- Dimension :1195×295×14mm

120 lm/W





Model	SKU	Watts	Lumen	Size	Box Qty
VT-12031	6256 – 3000K WARM WHITE 6257 – 4000K DAY WHITE 6258 – 6400K WHITE	29w 6 pcs pack	3480	1195×295×14mm	6
VT-12031-N	216256 – 3000K WARM WHITE 216257 – 4500K DAY WHITE 216258 – 6000K WHITE	29w	3960	1195×295×12.5mm	6
VT-12046	6384 – 4000K DAY WHITE	45w 6 pcs pack	5400	1195×295×14mm	6

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED BIG PANELS

Big Panels-120×30

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >10000
- Life span:20,000-hour
- Body Type: Aluminium+PMMA+PP
- Dimension :1195×295×14mm





Model	SKU	Watts	Lumen	Size	Box Qty
VT-12030	60696 - 3000K WARM WHITE 60266 - 4000K DAY WHITE 60276 - 6400K WHITE	45w 6 pcs pack	3600	1195×295×14mm	6

LED BIG PANELS

Big Panels-High Lumen-120×60

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff:
- Life span:20,000-hour
- Body Type: Aluminium+PMMA+PS
- Dimension :1195×595×14mm



120 lm/W

Model	SKU	Watts	Lumen	Size	Box Qty
VT-12045	6332 - 4000K DAY WHITE 6333 - 6400K WHITE	45w Single pack	5400	1195×595×14mm	2
VT-12045-N	216332 - 4000K DAY WHITE 216333 - 6400K WHITE	40w	5400	1195×295×12.5mm	2

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

DRIVERS – BIG PANELS

	SKU	Watts	Box Qty			
	6614	45w	1	DALI DRIVER		
	6259	29w	50			
	6268	29w	20	DIMMABLE		
	6019	45w	50	DIMMABLE		
	6271	29w	50	5 YEAR WARRANTY	FLICKER FREE	
	6436	36w	20			
	6450	45w	50	5 YEAR WARRANTY		
	6437	45w	20	1–10V DIMMABLE		
	6386	45w	50	120 lm/W	FLICKER FREE	
	6427	45w	50	5 YEAR WARRANTY	120 lm/W	
	6270	45w	50	5 YEAR WARRANTY	120 lm/W	FLICKER FREE
	6328	72w	50	5 YEAR WARRANTY		

Suspended Mounting

SKU: 6018
Box Qty 100

Adjustable height from 0.3 to 1m.This product can be used for all sizes of panels , that is
• 300 × 300 • 600 × 600 • 1200 × 300 • 1200 × 600

Surface Mounting-60×60

SKU: 9999
Box Qty 5

Convert the recessed panel to surface panel and install it easily on solid surfaces.

Surface Mounting-62×62

SKU: 9997
Box Qty 5

Convert the recessed panel to surface panel and install it easilyon solid surfaces.

DEKRA TÜV SÜD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING



Surface Mounting-60×60

SKU: 8156
Box Qty 10

Surface Mounting-62×62

SKU: 8157
Box Qty 10

Surface Mounting-120×30

SKU: 8158
Box Qty 10

Surface Mounting-120×30

SKU: 9969
Box Qty 6

Surface Mounting 120×60

SKU: 6623
Box Qty 10

Surface Mounting-120×60

SKU: 9989
Box Qty 5

NEW

Surface Mounting-60×60

SKU: 6627
Box Qty 25

Emergency Pack-6W to 24W



Voltage: DC:20-80V
Led output power: AC:220-240V,50/60Hz
Charging time: 24 Hours
Working time: 3 hours
Battery: Ni-Cd7.2V/2000mAh
Emergency switch on time: < 1s
Body Type: Aluminium
Size: 455×52×33mm

Model	SKU	Box Qty
VT-525	8275	20

Emergency Pack-29W to 45W



Voltage: DC:30-42V
Led output power: AC:220-240V,50/60Hz
Charging time: 24 Hours
Working time: 3 Hours
Battery: NI-CD, 7.2V, 4000 mAh
Emergency switch on time: < 1s
Body Type: Aluminium
Size: 465×52×33mm

Model	SKU	Box Qty
VT-518	60303	12

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED MINI PANELS

Experience consistent illumination and zero hot or cold spots, introducing slim and sleek LED Panel Lighting from V-TAC.

Key Features

- Ultra Slim Design
- Contemporary & Elegant Design
- Higher Light Transmission Rate
- Exterior shell, cannot be easily damaged
- No infrared, does not attract flies
- Easy to install
- No Lead or mercury content hence environment friendly
- Dimmable options available in selected models

Application

Offices, conference room, hospitals, hotels, shopping malls, showroom, kitchen and domestic lighting etc.

DEKRA TUV CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED MINI PANELS | Linear Lights

- AC:85-265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- Life span:30,000-hour
- Body Type: Aluminium

Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-10001	6401 - 3000K WARM WHITE 6403 - 6400K WHITE	10w Rectangle	750	160×45×65mm	138×32mm	20
VT-20001	6404 - 3000K WARM WHITE 6406 - 6400K WHITE	20w Rectangle	1600	290×45×65mm	270×32mm	20
VT-30001	6407 - 3000K WARM WHITE 6409 - 6400K WHITE	30w Rectangle	2400	430×45×65mm	405×32mm	10

LED MINI PANELS | Linear Lights

- AC:85-265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- Life span:30,000-hour
- Body Type: Aluminium

Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-10002	6412 - 6400K WHITE	10w Rectangle	700	160×45×72mm	138×32mm	20
VT-20002	6415 - 6400K WHITE	20w Rectangle	1400	290×45×72mm	270×32mm	20
VT-30002	6418 - 6400K WHITE	30w Rectangle	2100	430×45×72mm	405×32mm	10

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED MINI PANELS | SG Series

- AC:85-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium(PKW)



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-1500 SQ	4826 - 3000K WARM WHITE	15w Square	1500	160×160×20mm	140×140mm	20
VT-2200 RD	4833 - 6400K WHITE	22w Round	2200	Ø240×20mm	Ø220mm	20

LED MINI PANELS | Surface Series

- AC:85-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- Life span:20,000 Hours
- Body Type: Aluminium



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-1408 SQ	4802 - 3000K WARM WHITE	8w Square	800	107×107×35mm	N/A	40
VT-1415 SQ	4808 - 3000K WARM WHITE	15w Square	1500	155×155×35mm	N/A	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED MINI PANELS | Slim Surface-Round

- AC:85-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-605RD	4904 - 3000K WARM WHITE 4905 - 4000K DAY WHITE 4906 - 6400K WHITE	6w Round	420	Ø90×24mm	N/A	40
VT-1205 RD	4910 - 3000K WARM WHITE 4911 - 4000K DAY WHITE 4912 - 6400K WHITE	12w Round	900	Ø140×24mm	N/A	40
VT-1805RD	4916 - 3000K WARM WHITE 4917 - 4000K DAY WHITE 4918 - 6400K WHITE	18w Round	1440	Ø190×24mm	N/A	20

LED MINI PANELS | Slim Surface-Square

- AC:85-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-605SQ	4907 - 3000K WARM WHITE 4908 - 4000K DAY WHITE 4909 - 6400K WHITE	6w Square	420	90×90×24mm	N/A	40
VT-1205 SQ	4913 - 3000K WARM WHITE 4914 - 4000K DAY WHITE 4915 - 6400K WHITE	12w Square	900	140×140×24mm	N/A	40
VT-1805SQ	4919 - 3000K WARM WHITE 4920 - 4000K DAY WHITE 4921 - 6400K WHITE	18w Square	1440	190×190×24mm	N/A	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED MINI PANELS | Slim Series-Chrome-Round

- AC:85-265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium+Chrome



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-1207CH	6340 - 3000K WARM WHITE	12w Round	1000	Ø170×25mm	Ø155mm	20
VT-1807CH	6346 - 3000K WARM WHITE 6347 - 4000K DAY WHITE 6348 - 6400K WHITE	18w Round	1500	Ø225×25mm	Ø205mm	20
VT-2407CH	6352 - 3000K WARM WHITE 6353 - 4000K DAY WHITE 6354 - 6400K WHITE	24w Round	2000	Ø300×25mm	Ø285mm	10

LED MINI PANELS | Slim Series-Satin Nickel-Round

- AC:85-265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium+Satin Nickel



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-2407SN	6355 - 3000K WARM WHITE 6356 - 4000K DAY WHITE 6357 - 6400K WHITE	24w Round	2000	Ø300×25mm	Ø285mm	10

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED MINI PANELS | Slim Surface-Chrome-Round

- AC:85-265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium+Chrome



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-605CH	6358 - 3000K WARM WHITE	6w Round	420	Ø90×24mm	N/A	40
VT-1205CH	6364 - 3000K WARM WHITE 6366 - 6400K WHITE	12w Round	1000	Ø140×24mm	N/A	40

LED MINI PANELS | Slim Surface-Satin Nickel-Round

- AC:85-265V,50/60Hz
- PF: >0.6
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium+Satin Nickel



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-1205SN	6367 - 3000K WARM WHITE 6369 - 6400K WHITE	12w Round	1000	Ø140×24mm	N/A	40

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED MINI PANELS | Twin LED-Square

- AC:85-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-809SQ	4922 – 3000K WARM WHITE 4923 – 4000K DAY WHITE 4924 – 6400K WHITE	8w Square	800	142×142×40mm	N/A	20
VT-1509SQ	4925 – 3000K WARM WHITE 4926 – 4000K DAY WHITE 4927 – 6400K WHITE	15w Square	1500	192×192×40mm	N/A	20
VT-2209SQ	4928 – 3000K WARM WHITE 4929 – 4000K DAY WHITE 4930 – 6400K WHITE	22w Square	2200	240×240×40mm	N/A	20

LED MINI PANELS | Twin LED-Round

- AC:85-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-809RD	4890 – 3000K WARM WHITE 4891 – 4000K DAY WHITE 4892 – 6400K WHITE	8w Round	800	142×40mm	N/A	20
VT-1509RD	4893 – 3000K WARM WHITE 4894 – 4000K DAY WHITE 4895 – 6400K WHITE	15w Round	1500	192×40mm	N/A	20
VT-2209RD	4896 – 3000K WARM WHITE 4897 – 4000K DAY WHITE 4898 – 6400K WHITE	22w Round	2200	240×40mm	N/A	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED MINI PANELS | Glass Series-Round

- AC:100-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium+Glass





Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-602G RD	4740 - 3000K WARM WHITE 6277 - 4000K DAY WHITE 4739 - 6400K WHITE	6w Round	420	Ø100×35mm	Ø75mm	40
VT-1202G RD	4744 - 3000K WARM WHITE 6279 - 4000K DAY WHITE 4743 - 6400K WHITE	12w Round	840	Ø160×40mm	Ø120mm	20
VT-1881G RD	4760 - 3000K WARM WHITE 6281 - 4000K DAY WHITE 4759 - 6400K WHITE	18w Round	1260	Ø198×40mm	Ø145mm	20

LED MINI PANELS | Glass Series-Square

- AC:100-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium+Glass



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-602G SQ	4738 - 3000K WARM WHITE 6276 - 4000K DAY WHITE 4737 - 6400K WHITE	6w Square	420	100×100×35mm	75×75mm	40
VT-1202G SQ	4742 - 3000K WARM WHITE 6278 - 4000K DAY WHITE 4741 - 6400K WHITE	12w Square	840	160×160×40mm	120×120mm	20
VT-1881G SQ	4746 - 3000K WARM WHITE 6280 - 4000K DAY WHITE 4745 - 6400K WHITE	18w Square	1260	198×198×40mm	145×145mm	20

V-TAC INNOVATIVE LED LIGHTING

ESSENTIALS

LED MINI PANELS | Trimless Panel

- AC:85-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-888RD	4931 – 3000K WARM WHITE 4932 – 4000K DAY WHITE 4933 – 6400K WHITE	8w Round	800	Ø90×8mm	Ø75mm	100
VT-1515RD	4934 – 3000K WARM WHITE 4935 – 4000K DAY WHITE 4936 – 6400K WHITE	15w Round	1500	Ø146×8mm	Ø130mm	40
VT-2222RD	4937 – 3000K WARM WHITE 4938 – 4000K DAY WHITE 4939 – 6400K WHITE	22w Round	2200	Ø170×8mm	Ø155mm	40
VT-2929RD	4940 – 3000K WARM WHITE 4941 – 4000K DAY WHITE 4942 – 6400K WHITE	29w Round	2900	Ø220×8mm	Ø195mm	40

SQUARE TRIMLESS PANEL

Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-888SQ	4943 – 3000K WARM WHITE 4944 – 4000K DAY WHITE 4945 – 6400K WHITE	8w Square	800	90×90×8mm	75×75mm	100
VT-1515SQ	4946 – 3000K WARM WHITE 4947 – 4000K DAY WHITE 4948 – 6400K WHITE	15w Square	1500	146×146×8mm	130×130mm	40
VT-2222SQ	4949 – 3000K WARM WHITE 4797 – 4000K DAY WHITE 4798 – 6400K WHITE	22w Square	2200	170×170×8mm	155×155mm	40
VT-2929SQ	5031 – 3000K WARM WHITE 5032 – 4000K DAY WHITE 5033 – 6400K WHITE	29w Square	2900	220×220×8mm	195×195mm	40

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED MINI PANELS | Premium Series-Round

- AC:85-265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-307RD	6292 - 3000K WARM WHITE 6293 - 4000K DAY WHITE 6294 - 6400K WHITE	3w Round	210	Ø84×12mm	Ø73mm	40
VT-307RD-N	216292 - 3000K WARM WHITE 216293 - 4000K DAY WHITE 216294 - 6400K WHITE	3w Round	170	Ø84×12mm	Ø73mm	50
VT-607RD	4854 - 3000K WARM WHITE 4855 - 4000K DAY WHITE 4856 - 6400K WHITE	6w Round	420	Ø120×12mm	Ø110mm	40
VT-607RD-N	214854 - 3000K WARM WHITE 214855 - 4000K DAY WHITE 214856 - 6400K WHITE	6w Round	400	Ø120×12mm	Ø110mm	40
VT-1207RD	4857 - 3000K WARM WHITE 4858 - 4000K DAY WHITE 4859 - 6400K WHITE	12w Round	1000	Ø170×12mm	Ø155mm	20
VT-1207RD-N	214857 - 3000K WARM WHITE 214858 - 4000K DAY WHITE 214859 - 6400K WHITE	12w Round	1000	Ø170×12mm	Ø155mm	20
VT-1807RD	4860 - 3000K WARM WHITE 4861 - 4000K DAY WHITE 4862 - 6400K WHITE	18w Round	1500	Ø225×12mm	Ø210mm	20
VT-1807RD-N	214860 - 3000K WARM WHITE 214861 - 4000K DAY WHITE 214862 - 6400K WHITE	18w Round	1500	Ø225×12mm	Ø210mm	20
VT-2207RD	6422 - 3000K WARM WHITE 6423 - 4000K DAY WHITE 6424 - 6400K WHITE	22w Round	1800	Ø240×12mm	Ø220 mm	20
VT-2207RD-N	216423 - 4000K DAY WHITE	22w Round	2200	Ø240×12mm	Ø220 mm	20
VT-2407RD	4872 - 3000K WARM WHITE 4873 - 4000K DAY WHITE 4874 - 6400K WHITE	24w Round	2000	Ø300×12mm	Ø280mm	10
VT-2407RD-N	214872 - 3000K WARM WHITE 214873 - 4000K DAY WHITE 214874 - 6400K WHITE	24w Round	2200	Ø300×12mm	Ø280mm	10
VT-3107RD	6428 - 4000K DAY WHITE 6429 - 6400K WHITE	30w Round	2400	Ø300×12mm	Ø280mm	10
VT-3107RD-N	216428 - 4000K DAY WHITE 216429 - 6400K WHITE	30w Round	2600	Ø300×12mm	Ø280mm	10

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED MINI PANELS | Premium Series-Square

- AC:85-265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Aluminium



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-307SQ	6295 – 3000K WARM WHITE 6296 – 4000K DAY WHITE 6297 – 6400K WHITE	3w Square	210	84×84×12mm	74×73mm	40
VT-307SQ-N	216295 – 3000K WARM WHITE 216296 – 4000K DAY WHITE	3w Square	150	84×84×12mm	74×73mm	50
VT-607SQ	4863 – 3000K WARM WHITE 4864 – 4000K DAY WHITE 4865 – 6400K WHITE	6w Square	420	120×120×12mm	110mm	40
VT-607SQ-N	214865 – 6400K WHITE	6w Square	400	120×120×12mm	110mm	40
VT-1207SQ	4866 – 3000K WARM WHITE 4867 – 4000K DAY WHITE 4868 – 6400K WHITE	12w Square	1000	170×170×12mm	155×155mm	20
VT-1207SQ-N	214866 – 3000K WARM WHITE 214867 – 4000K DAY WHITE 214868 – 6400K WHITE	12w Square	1000	170×170×12mm	155×155mm	20
VT-1807SQ	4869 – 3000K WARM WHITE 4870 – 4000K DAY WHITE 4871 – 6400K WHITE	18w Square	1500	225×225×12mm	205×205mm	20
VT-1807SQ-N	214869 – 3000K WARM WHITE 214870 – 4000K DAY WHITE 214871 – 6400K WHITE	18w Square	1500	225×225×12mm	205×205mm	20
VT-2407SQ	4887 – 3000K WARM WHITE 4888 – 4000K DAY WHITE 4889 – 6400K WHITE	24w Square	2000	300×300×12mm	280×280mm	10
VT-2407SQ-N	214887 – 3000K WARM WHITE 214889 – 6400K WHITE	24w Square	2200	300×300×12mm	280×280mm	10
VT-3107SQ	6430 – 4000K DAY WHITE 6431 – 6400K WHITE	36w Square	2400	300×300×12mm	280×280mm	10
VT-3107SQ-N	216430 – 4000K DAY WHITE 216431 – 6400K WHITE	36w Square	3100	300×300×12mm	280×280mm	10

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Drivers – Mini Panels

DIMMABLE

SKU	Watts	Box Qty
8073	6w	200

Drivers – Mini Panels

DIMMABLE

SKU	Watts	Box Qty
8074	12w	200

Drivers – Mini Panels

DIMMABLE

SKU	Watts	Box Qty
8075	18w	200

Drivers – Mini Panels

DIMMABLE

SKU	Watts	Box Qty
8076	24w	200

LED TUBES

V-TAC's LED Tube Series fits perfectly into existing linear fixtures, providing better light quality and energy efficiency compared to linear fluorescent systems.

Key Features

- Cost effective, safe retrofit for T8 Tubes
- Perfectly matches with the traditional daylight tube fixture
- Easy Installation
- No Lead or mercury content hence environment friendly
- No Ultraviolet or Infrared rays
- Long lifespan, low maintenance and energy saving
- Available in 60 cm, 120 cm, 150 cm & 180 cm

Application

Widely used for domestic and commercial lighting, offices, supermarkets, shops, hotels & similar environment.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED TUBES | T8 Nano Plastic Tubes

3 YEAR WARRANTY

Nano Plastic T8 Tube is the revolution of the lighting industry, designed with the modern fabric of the nanometer tube body. Nano Plastic T8 Tubes have way better light transmittance compared to conventional tubes.

- G13 Holder
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 160° Beam Angle
- On/Off: >15,000
- Life span:20,000-hour
- Body Type: Nano Plastic
- Instant start :0-100% in < 1s

ROTATABLE

Dummy Starter Included

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-6072-R	6229 - 3000K WARM WHITE	10w Rotatable	850	27.9×600mm	25
VT-6072-NR	6392 - 3000K WARM WHITE 6393 - 4000K DAY WHITE 6394 - 6400K WHITE	10w	850	27.9×600mm	25
VT-6072-NR-N	216392 - 3000K WARM WHITE 216393 - 4000K DAY WHITE 216394 - 6500K WHITE	9w	850	27.9×600mm	25
VT-9077	6272 - 4000K DAY WHITE 6262 - 6400K WHITE	14w	1200	27.9×900mm	25
VT-9077-N	216272 - 4000K DAY WHITE 216262 - 6500K WHITE	14w	1400	27.9×900mm	25
VT-1277	6263 - 3000K WARM WHITE 6273 - 4000K DAY WHITE 6264 - 6400K WHITE	18w	1700	27.9×1200mm	25
VT-1577	6265 - 3000K WARM WHITE 6309 - 4000K DAY WHITE 6310 - 6400K WHITE	22w	2000	27.9×1500mm	25
VT-1577-N	216309 - 4000K DAY WHITE 216310 - 6500K WHITE	20w	2100	27.9×1500mm	25

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

LED TUBES | T5 Glass Tubes

Dummy Starter Included

- G5 Holder
- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 160° Beam Angle
- On/0ff: >15,000
- Life span:20,000-hour
- Body Type: Glass with PET
- Instant start :0-100% in < 1s

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-6005	6318 - 4000K DAY WHITE 6319 - 6500K WHITE	8w	800		25
VT-1225	6320 - 4000K DAY WHITE 6321 - 6500K WHITE	16w	1600		25

Single Batten Fitting

Model	SKU	Body Type	Size	Box Qty
VT-16010	6052	Iron	615×45×50mm	20
VT-12020	6054	Iron	1225×45×50mm	20
VT-15020	6056	Iron	1520×45×50mm	20

Double Batten Fitting

Model	SKU	Body Type	Size	Box Qty
VT-16011	6053	Iron	615×55×50mm	20
VT-12021	6055	Iron	1225×55×50mm	12
VT-15021	6057	Iron	1520×55×50mm	12

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

LED TUBES | T8 Bread Tube-120cm

- G13 Holder
- AC:180-240V,50Hz
- PF: >0.9
- CRI: >95
- 160° Beam Angle
- On/0ff: >15,000
- Life span:20,000-hour
- Body Type: Glass with PET
- Instant start :0-100% in < 1s



Model	SKU	Watts	Lumen	Box Qty
VT-1228-B	6322	18w	1530	25

LED TUBES | T8 Vegetable Tube-120cm

- G13 Holder
- AC:180-240V,50Hz
- PF: >0.9
- CRI: >95
- 160° Beam Angle
- On/0ff: >15,000
- Life span:20,000-hour
- Body Type: Glass with PET
- Instant start :0-100% in < 1s





Model	SKU	Watts	Lumen	Box Qty
VT-1228-V	6324	18w	1530	25

LED TUBES | T8 Seafood Tube-120cm

- G13 Holder
- AC:180-240V,50/60Hz
- PF: >0.9
- CRI: >95
- 160° Beam Angle
- On/0ff: >15,000
- Life span:20,000-hour
- Body Type: Glass with PET
- Instant start :0-100% in < 1s



Model	SKU	Watts	Lumen	Box Qty
VT-1228-S	6325	18w	1530	25

LED TUBES | Double T8 Nano Plastic Tube

- AC:200-240V,50Hz
- PF: >0.9
- CRI: >80
- 160° Beam Angle
- On/0ff: >15,000
- Life span:20,000-hour
- Body Type: Nano Plastic
- Dimension :18.5×549mm



Model	SKU	Watts	Lumen	Box Qty
VT-6077	6313 - 4000K DAY WHITE 6314 - 6400K WHITE	18w	2500	10

LED TUBES | Cabinet Fitting

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 110° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: Aluminium Body, Plastic Diffuser
- Dimension :579×78×35mm



Model	SKU	Watts	Lumen	Box Qty
VT-8112	5068 - 3000K WARM WHITE 5070 - 6000K WHITE	10w	800	12

DEKRA TÜV SÜD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

LED TUBES | Wall Fitting-60cm

- AC:85-265V,50/60Hz
- PF: >0.6
- CRI: >80
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: Aluminium+PC
- Dimension :600×32×25mm





Model	SKU	Watts	Lumen	Box Qty
VT-8111	5071 – 3000K WARM WHITE 5072 – 4500K DAY WHITE 5073 – 6000K WHITE	10w	900	25

LED TUBES | Wall Fitting-120cm

- AC:85-265V,50/60Hz
- PF: >0.6
- CRI: >80
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: Aluminium+PC
- Dimension :1200×32×25mm





Model	SKU	Watts	Lumen	Box Qty
VT-8121	5074 – 3000K WARM WHITE 5076 – 6000K WHITE	20w	1800	25



LED BATTEN FITTINGS

Introducing our complete Essentials range of IP65-rated waterproof tubes. Built with a durable, air-tight body allowing it to resist jets of water and dust — an essential feature for outdoor lighting.

Key Features

- Easy to install
- IP65, free from water and dirt
- Direct wiring easily accessible when necessary
- Perfect replacement for the whole set of T8 fluorescent lighting fixture
- Save up to 80% in electricity consumption compared to fluorescent lighting fixture

Application

Widely used for Domestic and Commercial Lighting, Offices, Supermarkets, Shops, Hotels & similar environment.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED BATTEN FITTINGS | Waterproof Fitting with Tubes

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- On/0ff: >15,000
- Life span:20,000-hour
- Body Type: Plastic+ABS

TUBES INCLUDED

IP65 RATING

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-6028	6463 - 4000K DAY WHITE 6464 - 6400K WHITE	10w Single Tube	850		16
VT-6029	6465 - 4000K DAY WHITE 6466 - 6400K WHITE	20W Double Tubes	1700		12
VT-12028	6459 - 4000K DAY WHITE 6460 - 6400K WHITE	18w Single Tube	1700		16
VT-15028	6461 - 4000K DAY WHITE 6462 - 6400K WHITE	22w Single Tube	2000		16
VT-12023	6387 - 4000K DAY WHITE 6399 - 6400K WHITE	36w Double Tubes	3400		10
VT-15022	6388 - 4000K DAY WHITE 6400 - 6400K WHITE	44w Double Tubes	4000		10

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC

www.tuv.com ID 1111227954

ACCREDITATION FROM TOP EUROPEAN LABS

LED BATTEN FITTINGS | Waterproof Fitting-G Series

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/Off: >10,000
- Life span:20,000-hour
- Body Type: PC
- Dimension :600×65×58mm

IP65 RATING

Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-6076	6283 – 4000K DAY WHITE 6282 – 6400K WHITE	18w	1440		12
VT-1249	6285 – 4000K DAY WHITE 6284 – 6400K WHITE	36w	2880		12
VT-1249-N	216285 – 4500K DAY WHITE 216284 – 6400K WHITE	36W	4320		12
VT-1574	6287 – 4000K DAY WHITE 6286 – 6400K WHITE	48w	3840		12
VT-1574-N	216287 – 4500K DAY WHITE 216286 – 6400K WHITE	48W	5760		12

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

LED BATTEN FITTINGS | Waterproof Fitting-S Series

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15,000
- Life span:20,000-hour
- Body Type: PC
- Dimension :600×60×35mm

IP65 RATING



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-1518	6472 - 4000K DAY WHITE 6473 - 6500K WHITE	18w	1530		20
VT-1518-N	216473 - 6500K WHITE	18w	1900		20
VT-1239	6469 - 4000K DAY WHITE 6470 - 6500K WHITE	36w	3000		20
VT-1239-N	216470 - 6500K WHITE	36w	3900		20
VT-1549	6467 - 4000K DAY WHITE 6468 - 6500K WHITE	48w	4000		20
VT-1549-N	216468 - 6500K WHITE	48w	5200		20

LED BATTEN FITTINGS | Waterproof Fitting F Series

- AC:200-240V,50Hz
- PF: >0.9
- CRI: >70
- 120° Beam Angle
- On/Off: >10,000
- Life span:20,000-hour
- Body Type: Plastic+ABS
- Dimension :600×76×66mm

IP65 RATING



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-6048	6198 – 4500K DAY WHITE 6199 – 6000K WHITE	18w	1440		12
VT-6048-N	216198 – 4000K DAY WHITE	18w	1900		12
VT-1248	6200 – 4500K DAY WHITE 6201 – 6000K WHITE	36w	2880		12
VT-1548	6184 – 4500K DAY WHITE 6185 – 6000K WHITE	48w	3840		12

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

HERMETIC | Waterproof Fitting

Airtight waterproof empty fittings (tubes excluded) is recognized by praiseworthy protection from dampness andrainfall, in this way you can effectively utilize it for indoor and outdoor lighting.Hermetic fittings is easy to install – you can install it yourself utilizing essential devices.

Model	SKU	Body Type	Size	Box Qty
VT-6028-N	6717	Plastic+ABS	666×68×58mm	16
VT-6029-N	6719	Plastic+ABS	666×96×58mm	12
VT-12028-N	6711	Plastic+ABS	1276×68×58mm	16
VT-12023-N	6709	Plastic+ABS	1576×68×58mm	16
VT-15028-N	6713	Plastic+ABS	1290×116×66mm	10
VT-15022-N	6715	Plastic+ABS	1590×116×66mm	10

Waterproof Suspension Kit

SKU	Box Qty
8119	50





LED HIGHBAY LIGHTS

V-TAC's new UFO and Linear Highbay are designed for widespread illumination, efficiency, and resistance to harsh conditions.The UFO Highbay are supported by Meanwell drivers to boost their performance, are IP65rated and have a sturdy body to ensure endurance, and have two options of beam angle to choose from, for even light distribution.

Key Features

- Powerful LED light source with a unique design
- Aluminium diffuser with multiple beam angle's to choose from 90°/ 120°
- Shatterproof perspex lens
- High thermal conductivity, low luminous decay, pure colors & no heavy shade
- The unique design of the radiator fuses with the lamp box perfectly hence diffuses the heat conduction efficiently reduces the temperature of the inside lamp

Application

Perfect fit for industrial usage, warehouse & super markets, workshops, factories, warehouses, highway, toll stations, gas stations, malls, exhibition halls, stadiums & other vast areas.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

UFO-HIGH LUMEN-MEANWELL DRIVER

185 lm/W

5 YEAR WARRANTY

REMOTE CONTROL

MEAN WELL

IP65 RATING

DIMMABLE

Model	SKU	Watts	Lumen	Box Qty
VT-9119	7655 – 4000K DAY WHITE	100w	18500	1
VT-9219	7656 – 4000K DAY WHITE 7657 – 6500K WHITE	200w	37000	1
Remote Control	11361			

- AC:175-265V, 50/60Hz
- PF: >0.9
- CRI: >70
- 100° Beam Angle
- Life span:25,000 Hours
- Body Type: Aluminium

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

UFO-HIGH LUMEN-MEANWELL DRIVER

MEAN WELL Your Reliable Power Partner

5 YEAR WARRANTY

130 lm/W

IP65 RATING

90° BEAM ANGLE





- AC:100–240V,50/60Hz
- PF: >0.9
- CRI: >70
- 90° Beam Angle
- Life span:20,000-hour
- Body Type: Die Cast Aluminium
- Dimension :280×165mm

Model	SKU	Watts	Lumen	Box Qty
VT-9107	5588 – 6400K WHITE	100w	13000	4

UFO-HIGH LUMEN-MEANWELL DRIVER

MEAN WELL Your Reliable Power Partner

5 YEAR WARRANTY

130 lm/W

IP65 RATING

120° BEAM ANGLE





- AC:90–295V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- Life span:50,000-hour
- Body Type: Die Cast Aluminium
- Dimension :Ø360mm

Model	SKU	Watts	Lumen	Box Qty
VT-9500	5607 – 4000K DAY WHITE 5608 – 6400K WHITE	500w	65000	1

DEKRA TÜV SÜD GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

UFO-HIGHBAY-120°

120° BEAM ANGLE





- AC:220-240V,50Hz
- PF: >0.9
- CRI: >70
- 120° Beam Angle
- Life span:20,000-hour
- Body Type: Die Cast Aluminium
- Dimension :220×114mm

Model	SKU	Watts	Lumen	Box Qty
VT-9065-W	5609 - 3000K WARM WHITE	50w	4000	8



LED STRIP LIGHTS

Add an extensive array of lights and colors to any setting or interior, rejuvenate and transform the ambience of any environment at the flick of a switch with V-TAC's LED Strip Light Series. Easy installation with minimal space requirement makes this the right choice for Restaurants, Auditoriums, Meeting Rooms etc.

Key Features

- Flexible & easy installation
- Exceptionally low power consumption
- Multiple visual effects in unending colours and shades

Application

Perfect choice for Hotels, Bars, Commercial & Residential Lighting and Exhibition Stands.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Strip-2835-Sensor

Model	SKU	Watts	Lm/M	lm/LED
VT-8082	2573 – 2700K WARM WHITE 2574 – 4000K DAY WHITE	2.4W	200lm	5-6lm
VT-8082-N	212574 – 4000K DAY WHITE	2.4W	200lm	5-6lm

Voltage: DC:6V
LED Qty/M: 30
LED Type: SMD 2835
Current/M: NA

Beam Angle: 120°
IP Rating: IP65
Width: 1 Meter
Box Qty: 50

IP65 RATING

MOTION PIR SENSOR

Bed Lights-PIR Sensor

Model	SKU	Watts	Lm/M
VT-8067	2548 – 3000K WARM WHITE 2549 – 4500K DAY WHITE	3W	260lm
VT-8067-N	212549 – 4000K DAY WHITE	3w	260lm

Voltage: DC:12V
LED Qty/M: 30
LED Type: SMD
Current/M: NA

Beam Angle: 120°
IP Rating: IP20
Width: 1.2 m x1
Box Qty: 25

DIMMABLE LIGHT CONTROL

IP20 RATING

MOTION PIR SENSOR

Bed Lights-PIR Sensor

Model	SKU	Watts	Lm/M
VT-8068	2550 – 3000K WARM WHITE 2551 – 4500K DAY WHITE	6W	520lm

Voltage: DC:12V
LED Qty/M: 30
LED Type: SMD
Current/M: NA

Beam Angle: 120°
IP Rating: IP20
Width: 1.2 m x2
Box Qty: 18

DIMMABLE LIGHT CONTROL

IP20 RATING

MOTION PIR SENSOR

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Striplights 5050 60

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60-S3M	2607 – 6400K WHITE 2606 – 3000K WARM WHITE 2605 – RGB	9W	1000lm	14–16lm

Voltage: AC:100–240V, 50/60Hz
LED Qty/M: 60
LED Type: SMD
Current/M: 0.9A
Beam Angle: 120°
IP Rating: IP65
Width: 10mm
Box Qty: 20

5m ROLL
IP65 RATING
BS PLUG
3M TAPE ADHESIVE

Striplights 5050 60 220V

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60	2637 – 6500K WHITE 2635 – 3000K WARM WHITE 2636 – 4000K DAY WHITE	8.5W	300lm	13–14lm

Voltage: AC:220–240V, 50/60Hz
LED Qty/M: 60
LED Type: SMD
Beam Angle: 120°
IP Rating: IP66
Width: 8mm
Box Qty: 1

50m ROLL
IP66 RATING
EU PLUG
220V AC

Striplights 2835 120 220V

Model	SKU	Watts	Lm/M	lm/LED
VT-2835 120	2648 – 6500K WHITE 2646 – 3000K WARM WHITE 2647 – 4000K DAY WHITE	10W	800lm	6–7lm

Voltage: AC:220–240V, 50/60Hz
LED Qty/M: 120
LED Type: SMD
Beam Angle: 120°
IP Rating: IP66
Width: 8mm
Box Qty: 1

50m ROLL
IP66 RATING
EU PLUG
220V AC

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Strip Set-5050 300 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-5050-300-EU	2630 - RGB	4.8W	500lm	14-16lm

Voltage: AC:100-240V, 50/60Hz
LED Qty/M: 30
LED Type: SMD
Current/M: 0.4A
Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 20

EU PLUG

IP20 RATING

Included

Power Adaptor

Dual Output IR Controller

Strip Set-5050 300 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-5050-300-BS	2631 - RGB	4.8W	500lm	14-16lm

Voltage: AC:100-240V, 50/60Hz
LED Qty/M: 30
LED Type: SMD
Current/M: 0.4A
Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 20

BS PLUG

IP20 RATING

Included

Power Adaptor

Dual Output IR Controller

Strip Sets-5050 60 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60 IP20-Set	2545 - 3000K WARM WHITE 2546 - 6000K WHITE 2544 - RGB	10W	1000lm	14-16lm
VT-5050 60 IP20-Set-N	212546 - 6000K WHITE	11W	900lm	14-16lm

Voltage: AC:100-265V,50/60Hz
LED Qty/M: 60
LED Type: SMD
Current/M: 1.5A
Beam Angle: 120°
IP Rating: IP20
Width: 8mm
Box Qty: 20

5m ROLL

IP20 RATING

BS PLUG

POWER SUPPLY

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Strip Sets-5050 60 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60 IP20-RGB Set	2558 – RGB	10W	1000lm	14–16lm
VT-5050 60 IP20-RGB Set-N	212558 – RGB	10W	1000lm	14–16lm

Voltage: AC:100–265V,50/60Hz
LED Qty/M: 60
LED Type: SMD
Current/M: 1.5A
Beam Angle: 120°
IP Rating: IP20
Width: 8mm
Box Qty: 20

5m ROLL
IP20 RATING
EU PLUG
POWER SUPPLY

Strip-2835 60 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-2835 60	2561 – 6400K WHITE 2559 – 3000K WARM WHITE 2560 – 4000K DAY WHITE	4W	300lm	5–8lm
VT-2835 60 -N	212561 – 6400K WHITE 212559 – 3000K WARM WHITE 212560 – 4000K DAY WHITE	4.2W	420lm	6–7lm

Voltage: DC:12V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.3A
Beam Angle: 120°
IP Rating: IP20
Width: 6mm
Box Qty: 400 Meters

5m ROLL
IP20 RATING

Striplights 2835 120 Double PCB

Model	SKU	Watts	Lm/M	lm/LED
VT-2835 120-IP65	2627 – 6000K WHITE 2625 – 3000K WARM WHITE 2626 – 4000K DAY WHITE	7.2W	600lm	5–6lm
VT-2835 120-IP65-N	212627 – 6400K WHITE 212625 – 3000K WARM WHITE 212626 – 4000K DAY WHITE	7.5w	750lm	6–7lm

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Current/M: 0.6A
Beam Angle: 120°
IP Rating: IP65
Width: 10mm
Box Qty: 400 Meters

10m ROLL
IP65 RATING

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

Striplights 2835 120 Double PCB

Model	SKU	Watts	Lm/M	lm/LED
VT-2835 120-IP20	2624 – 6000K WHITE 2622 – 3000K WARM WHITE 2896 -3IN1	7.2W	600lm	5-6lm
VT-2835 120-IP20-N	212624 – 6400K WHITE 212622 – 3000K WARM WHITE 212623 – 4000K DAY WHITE	7.5w	750lm	6-7lm

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Current/M: 0.6A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 800 Meters

10m ROLL

IP20 RATING

LED Strip-2835 126 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-2835 126-24V	2595 – 6400K WHITE 2593 – 3000K WARM WHITE 2594 – 4000K DAY WHITE	8W	1200lm	28-30lm
VT-2835 126-24V-N	212595 – 6400K WHITE 212593 – 3000K WARM WHITE 212594 – 4000K DAY WHITE	8w	1100lm	8-9lm

Voltage: DC:24V
LED Qty/M: 126
LED Type: SMD
Current/M: 0.33A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

150 lm/W

LED Strip-4040-60

Model	SKU	Watts	Lm/M	lm/LED
VT-4040-60	2933 – 6400K WHITE 2931 – 3000K WARM WHITE 2932 – 4000K DAY WHITE	8W	800lm	13-14lm

Voltage: DC:12V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.66A

Beam Angle: 120°
IP Rating: IP20
Width: 8mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

REAL COLOR SERIES CRI >80

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Strip-2835 168 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-2835 168-24V	2598 – 6400K WHITE 2596 – 3000K WARM WHITE 2597 – 4000K DAY WHITE	11W	1650lm	28-30lm
VT-2835 168-24V-N	212598 – 6400K WHITE 212596 – 3000K WARM WHITE 212597 – 4000K DAY WHITE	12w	1680lm	10-11lm

Voltage: DC:24V
LED Qty/M: 168
LED Type: SMD
Current/M: 0.45A
Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

150 lm/W

Strip Light-5050 RGB + CCT 5IN1

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60 IP20-24W	2895 – 5IN1	14W	1400lm	23-24lm

Voltage: DC:24V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.58A
Beam Angle: 120°
IP Rating: IP20
Width: 12mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

RGB + 3000K- 6400K

Many different colors, various lighting Modes, Dimmable.

Strip Light-5050 RGB + CCT 5IN1

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60 IP65-RGB -24W	2896 -5IN1	14W	1400lm	23-24lm

Voltage: DC:24V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.58A
Beam Angle: 120°
IP Rating: IP20
Width: 12mm
Box Qty: 200 Meters

5m ROLL

IP65 RATING

RGB + 3000K- 6400K

Many different colors, various lighting Modes, Dimmable.

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Striplights 2835 – CCT

Model	SKU	Watts	Lm/M	lm/LED
VT-2835 120-IP20-14W	2897 -3IN1	14.5W	1750lm	14–15lm

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Current/M: 0.6A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

3000K- 6400K

Striplights 2835 – CCT

Model	SKU	Watts	Lm/M	lm/LED
VT-2835 120-IP65-14W	2898 – 3IN1	14.5W	1750lm	14–15lm

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Current/M: 0.6A

Beam Angle: 120°
IP Rating: IP65
Width: 10mm
Box Qty: 200 Meters

5m ROLL

IP65 RATING

3000K- 6400K

LED Strip-2835 238 LEDs



Model	SKU	Watts	Lm/M	lm/LED
VT-2835 238–24V	2601 – 6400K WHITE 2599 – 3000K WARM WHITE 2600 – 4000K DAY WHITE	17W	2550lm	28–30lm
VT-2835 238-24V-N	212601 – 6400K WHITE 212599 – 3000K WARM WHITE 212600 – 4000K DAY WHITE	18w	2430lm	10–11lm

Voltage: DC:24V
LED Qty/M: 238
LED Type: SMD
Current/M: 0.7A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

150 lm/W

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED strips-2835 204 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-2835 204	2463 – 6000K WHITE 2461 – 3000K WARM WHITE 2462 – 4500K DAY WHITE	18W	1700lm	9–11lm
VT-2835 204-N	212463 – 6400K WHITE 212461 – 3000K WARM WHITE 212462 – 4000K DAY WHITE	17w	1700lm	8–9lm

Voltage: DC:12V
LED Qty/M: 204
LED Type: SMD
Current/M: 1.5A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

LED Strip-2835 128 LEDs



Model	SKU	Watts	Lm/M	lm/LED
VT-2835 128-24V	2908 – 6400K WHITE 2906 – 3000K WARM WHITE 2907 – 4000K DAY WHITE	WW-8.5W/ DW-8.5W/ W-9W	1150lm 1200lm 1260lm	9–10lm

Voltage: DC:24V
LED Qty/M: 128
LED Type: SMD
Current/M: 0.37A

Beam Angle: 120°
IP Rating: IP20
Width: 4mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

Striplights 2835 90-High Lumen

Model	SKU	Watts	Lm/M	lm/LED
VT-2835 90	2698 – 6400K WHITE 2696 – 3000K WARM WHITE 2697 – 4000K DAY WHITE	20W	800lm	10–11lm

Voltage: DC:24V
LED Qty/M: 90
LED Type: SMD
Current/M: 0.16A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

DEKRA TÜV SÜD GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED strips-2835 240 LEDs-High Lumen



Model	SKU	Watts	Lm/M	lm/LED
VT-2835 240-H	2166 – 6000K WHITE 2164 – 3000K WARM WHITE 2165 – 4500K DAY WHITE	18W	3000lm	20–22lm
VT-2835 240-H-N	212166 – 6000K WHITE 212164 – 3000K WARM WHITE	20w	2000lm	8–9lm

Voltage: DC:12V
LED Qty/M: 240
LED Type: SMD
Current/M: 1.5A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

150 lm/W

3000 Lumen/M

LED strips-5730 120 LEDs-High Lumen

Model	SKU	Watts	Lm/M	lm/LED
VT-5730 120	2161 – 6000K WHITE 2162 – 3000K WARM WHITE 2163 – 4500K DAY WHITE	18W	3000lm	20–22lm
VT-5730 120-N	212161 – 6400K WHITE 212163 – 4000K DAY WHITE	20w	2000lm	16–17lm

Voltage: DC:12V
LED Qty/M: 120
LED Type: SMD
Current/M: 1.5A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

150 lm/W

3000 Lumen/M

Striplights 2110 700

Model	SKU	Watts	Lm/M	lm/LED
VT-2110 700	2604 – 6400K WHITE 2602 – 3000K WARM WHITE 2603 – 4000K DAY WHITE	21W	2000lm	8–10lm

Voltage: DC:24V
LED Qty/M: 700
LED Type: SMD
Current/M: 0.875A

Beam Angle: 120°
IP Rating: IP20
Width: 12mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

REAL COLOR SERIES CRI >95

700 LED PER METER

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Strip-2216 360 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-2216 360	2582 – 6000K WHITE 2580 – 3000K WARM WHITE 2581 – 4000K DAY WHITE	30W	2400lm	6-7lm
VT-2216 360-N	212581 – 4000K DAY WHITE	30w	2850lm	7-8lm

Voltage: DC:24V
LED Qty/M: 360
LED Type: SMD
Current/M: 1.25A
Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 250 Meters

5m ROLL

IP20 RATING

REAL COLOR SERIES CRI >95

LED COB Striplights IP20

Model	SKU	Watts	Lm/M	lm/LED
VT-COB 280	2654 – 6400K WHITE 2652 – 3000K WARM WHITE 2653 – 4000K DAY WHITE	10W	800lm	NA
VT-COB 280-N	212654 – 6400K WHITE	10w	950lm	3-4lm

Voltage: DC:24V
LED Qty/M: 280
LED Type: COB
Current/M: 0.4A
Beam Angle: 120°
IP Rating: IP20
Width: 8mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

COB LED STRIP

LED COB Striplights IP20

Model	SKU	Watts	Lm/M	lm/LED
VT-COB 421	2669 – 6400K WHITE 2667 – 3000K WARM WHITE 2668 – 4000K DAY WHITE	10W/M	1000	2-3lm
VT-COB 421-N	212667 – 3000K WARM WHITE	10w	960lm	2-3lm

Voltage: DC:24V
LED Qty/M: 420
LED Type: COB
Current/M: 0.42A
Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

COB LED STRIP

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED COB Striplights IP20

Model	SKU	Watts	Lm/M	lm/LED
VT-512	2651 – 6000K WHITE 2649 – 3000K WARM WHITE 2650 – 4000K DAY WHITE	12W	1000lm	LM
VT-512-N	212651 – 6400K WHITE 212649 – 3000K WARM WHITE 212650 – 4000K DAY WHITE	13w	1050lm	2–3lm

Voltage: DC:24V
LED Qty/M: 512
LED Type: COB
Current/M: 0.5A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

REAL COLOR SERIES CRI >95

COB LED STRIP

LED COB Striplights IP20

Model	SKU	Watts	Lm/M	lm/LED
VT-COB 422	2880 – RGB	13W/M	NA	NA

Voltage: DC:24V
LED Qty/M: 672
LED Type: COB
Current/M: NA

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

COB LED STRIP

LED strips-3014 204 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-3014 204+Q31	2404 – 3000K WARM WHITE 2405 – 4500K DAY WHITE 2403 – 6000K WHITE	18W	1700lm	9–11lm

Voltage: DC:12V
LED Qty/M: 204
LED Type: SMD
Current/M: 1.5A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED strips-3528 60 LEDs

Voltage: DC:12V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.3A
Beam Angle: 120°
IP Rating: IP20
Width: 8mm
Box Qty: 400 Meters

Model	SKU	Watts	Lm/M	lm/LED
VT-3528 60-IP20	2005 – 6000K WHITE 2016 – 3000K WARM WHITE 2041 – 4500K DAY WHITE 2015 – RED 2013 – BLUE 2011 – GREEN 2009 – YELLOW	3.6W	400lm	5–6lm
VT-3528 60-IP20-N	212005 – 6400K WHITE 212016 – 3000K WARM WHITE 212041 – 4000K DAY WHITE 212015 – RED 212013 – BLUE 212011 – GREEN	4.2w	420lm	7–8lm

IP20 RATING

5m ROLL

LED strips-3528 60 LEDs

Voltage: DC:12V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.3A
Beam Angle: 120°
IP Rating: IP65
Width: 8mm
Box Qty: 400 Meters

Model	SKU	Watts	Lm/M	lm/LED
VT-3528 60-IP65	2031 – 6000K WHITE 2032 – 3000K WARM WHITE 2043 – 4500K DAY WHITE 2036 – RED 2035 – BLUE 2034 – GREEN	3.6W	400lm	5–6lm
VT-3528 60-IP65-N	212032 – 3000K WARM WHITE 212043 – 4500K DAY WHITE 212036 – RED 212035 – BLUE	5w	420lm	7–8lm

5m ROLL

IP65 RATING

LED strips-3528 120 LEDs

Voltage: DC:12V
LED Qty/M: 120
LED Type: SMD
Current/M: 0.6A
Beam Angle: 120°
IP Rating: IP20
Width: 8mm
Box Qty: 400 Meters

Model	SKU	Watts	Lm/M	lm/LED
VT-3528 120-IP20	2002 – 6000K WHITE 2025 – 3000K WARM WHITE 2042 – 4500K DAY WHITE	7.2W	600lm	5–6lm
VT-3528 120-IP20-N	212002 – 6500K WHITE 212025 – 3000K WARM WHITE 212042 – 4000K DAY WHITE	8w	800lm	6–7lm

5m ROLL

IP20 RATING

DEKRA TÜV SÜD GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED strips-3528 120 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-3528 120-IP65	2037 – 6000K WHITE 2038 – 3000K WARM WHITE 2044 – 4500K DAY WHITE	7.2W	600lm	5–6lm
VT-3528 120-IP65-N	212037 – 6400K WHITE 212038 – 3000K WARM WHITE 212044 – 4000K DAY WHITE	8w	800lm	6–7lm

Voltage: DC:12V
LED Qty/M: 120
LED Type: SMD
Current/M: 0.6A

Beam Angle: 120°
IP Rating: IP65
Width: 8mm
Box Qty: 400 Meters

5m ROLL

IP65 RATING

LED strips-5050 30 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 30-IP20	2133 – 6000K WHITE 2135 – 3000K WARM WHITE 2124 – RGB	4.8W	500lm	14 -16lm
VT-5050 30-IP20-N	212133 – 6400K WHITE 212124 – RGB	6w	500lm	16–17lm

Voltage: DC:12V
LED Qty/M: 30
LED Type: SMD
Current/M: 0.4A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

LED strips-5050 30 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 30-IP65	2145 – 3000K WARM WHITE 2460 – 4500K DAY WHITE 2144 – 6000K WHITE 2118 – RGB	4.8W	500lm	14 -16lm
VT-5050 30-IP65-N	212118 – RGB	3.5w	70lm	2–3lm

Voltage: DC:12V
LED Qty/M: 30
LED Type: SMD
Current/M: 0.4A

Beam Angle: 120°
IP Rating: IP65
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP65 RATING

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED strips-5050 60 LEDs

Voltage: DC:12V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.9A
Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60-IP20	2122 – 3000K WARM WHITE 2143 – 4500K DAY WHITE 2126 – 6000K WHITE 2120 – RGB 2128 – RED 2137 – BLUE 2138 – GREEN 2156 – YELLOW 2547 – 2200K WARM WHITE	10.8W	1000lm	14 -16lm
VT-5050 60-IP20-N	212126 – 6400K WHITE 212122 – 3000K WARM WHITE 212143 – 4000K DAY WHITE 212120 – RGB 212128 – RED 212137 – BLUE 212138 – GREEN 212156 – YELLOW 212547 – 2200K WARM WHITE	10.8W	900lm	14–15lm

IP20 RATING

5m ROLL

Striplights 5050 60

Voltage: DC:12V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.9A
Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60-3M	2609 – 6400K WHITE 2608 – 3000K WARM WHITE	10.8W	1000lm	14 -16lm

5m ROLL

IP20 RATING

3M TAPE ADHESIVE

LED strips-5050 60 LEDs

Voltage: DC:12V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.9A
Beam Angle: 120°
IP Rating: IP65
Width: 10mm
Box Qty: 400 Meters

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60-IP65	2149 – 3000K WARM WHITE 2150 – 4500K DAY WHITE 2148 – 6000K WHITE 2155 – RGB	10.8W	1000lm	14 -16lm
VT-5050 60-IP65-N	212148 – 6400K WHITE 212149 – 3000K WARM WHITE 212150 – 4500K DAY WHITE 212155 – RGB	11w	900lm	14–15lm

5m ROLL

IP65 RATING

DEKRA TÜV SÜD GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED strips-5050 60 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60RGBW	2159 – RGB+WHITE 2552 – RGB+DAY WHITE 2553 – RGB+WARM WHITE	10.8W	900lm	15lm
VT-5050 60RGBW-N	212159 – RGB+WHITE 212552 – RGB+DAY WHITE 212553 – RGB+WARM WHITE	8w	357lm	5–6lm

Voltage: DC:12V
LED Qty/M: 60
LED Type: SMD
Current/M: 1.2A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 400 Meters

5m ROLL

IP20 RATING

LED strips-5050 60 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60-24V-5M	2430 – 6400K WHITE 2431 – 3000K WARM WHITE 2459 – 4000K DAY WHITE 2591 – RGB	9W	600lm	14–16lm
VT-5050 60-24V-5M-N	212430 – 6400K WHITE 212431 – 3000K WARM WHITE 212459 – 4000K DAY WHITE 212591 – RGB	10w	830lm	13–14lm

Voltage: DC:24V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.3A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 200 Meters

5m ROLL

IP20 RATING

LED strips-5050 60 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60-24V-10M	2592 – RGB	9W	600lm	14–16lm
VT-5050 60-24V-10M-N	212592 – RGB	7w	140lm	2–3lm

Voltage: DC:24V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.3A

Beam Angle: 120°
IP Rating: IP20
Width: 10mm
Box Qty: 200 Meters

10m ROLL

IP20 RATING

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

Tape-5050 60 LEDs

Model	SKU	Watts	Lm/M	lm/LED
VT-5050 60-24V-IP65	2564 - 6400K WHITE 2562 - 3000K WARM WHITE 2563 - 4000K DAY WHITE	9W	500lm	14-16lm
VT-5050 60-24V-IP65-N	212564 - 6400K WHITE 212562 - 3000K WARM WHITE 212563 - 4000K DAY WHITE	10w	830lm	13-14lm

Voltage: DC:24V
LED Qty/M: 60
LED Type: SMD
Current/M: 0.375A
Beam Angle: 120°
IP Rating: IP65
Width: 10mm
Box Qty: 200 Meters

5m ROLL

IP65 RATING

Neon Flex IP68



Model	SKU	Watts	Lm/M:
VT-554	2614 - 6400K WHITE 2612 - 3000K WARM WHITE 2613 - 4000K DAY WHITE 2618 - RED 2615 - BLUE 2616 - GREEN 2617 - YELLOW	6.5W	260lm

10m ROLL

IP68 RATING

Voltage: DC:24V
LED Qty/M: 126
LED Type: SMD
Current/M: 0.27A
Beam Angle: 120°
IP Rating: IP68
Width: 8mm
Box Qty: 50 Meters

Neon Flex Silicon Cover

Model	SKU	Watts	Lm/M:
VT-560	2621 - 6000K WHITE 2619 - 3000K WARM WHITE 2620 - 4000K DAY WHITE	8W	530lm

5m ROLL

IP65 RATING

REAL COLOR SERIES CRI >90

Voltage: DC:24V
LED Qty/M: 238
LED Type: SMD
Current/M: 0.34A
Beam Angle: 120°
IP Rating: IP65
Width: 4mm
Box Qty: 200 Meters

DEKRA TÜV GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING



Neon Flex-White

Model	SKU	Watts	Lm/M:
VT-555W	2512 - 6000K WHITE	8W	320

10m ROLL

IP65 RATING

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Beam Angle: 160°
IP Rating: IP65
Width: 9×16.5mm
Box Qty: 5 Packets



Neon Flex-Warm White

Model	SKU	Watts	Lm/M:
VT-555WW	2513 - 3000K WARM WHITE	8W	320

10m ROLL

IP65 RATING

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Beam Angle: 160°
IP Rating: IP65
Width: 9×16.5mm
Box Qty: 5 Packets

Neon Flex-Day White

Model	SKU	Watts	Lm/M:
VT-555DW	2514 - 4500K DAY WHITE	8W	320

10m ROLL

IP65 RATING

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Beam Angle: 160°
IP Rating: IP65
Width: 9×16.5mm
Box Qty: 5 Packets



Neon Flex-Blue

Model	SKU	Watts	Lm/M:
VT-555B	2515 - BLUE	8W	320

10m ROLL

IP65 RATING

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Beam Angle: 160°
IP Rating: IP65
Width: 9×16.5mm
Box Qty: 5 Packets

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Neon Flex-Red

Model	SKU	Watts	Lm/M:
VT-555R	2516 - RED	8W	320

10m ROLL
IP65 RATING

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Beam Angle: 160°
IP Rating: IP65
Width: 9×16.5mm
Box Qty: 5 Packets

Neon Flex-Green

Model	SKU	Watts	Lm/M:
VT-555G	2517 - GREEN	8W	320

10m ROLL
IP65 RATING

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Beam Angle: 160°
IP Rating: IP65
Width: 9×16.5mm
Box Qty: 5 Packets

Neon Flex-Yellow

Model	SKU	Watts	Lm/M:
VT-555Y	2518 - YELLOW	8W	320

10m ROLL
IP65 RATING

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Beam Angle: 160°
IP Rating: IP65
Width: 9×16.5mm
Box Qty: 5 Packets

Neon Flex-Pink

Model	SKU	Watts	Lm/M:
VT-555P	2529 - PINK	8W	320

10m ROLL
IP65 RATING

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Beam Angle: 160°
IP Rating: IP65
Width: 9×16.5mm
Box Qty: 5 Packets

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Neon Flex-Violet

Model	SKU	Watts	Lm/M:
VT-555V	2531 - VIOLET	8W	320

10m ROLL

IP65 RATING

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
:

Beam Angle: 160°
IP Rating: IP65
Width: 9×16.5mm
Box Qty: 5 Packets

Backlite Silicon Neon Flex

Model	SKU	Watts	Lm/M:
VT-559	2570 - 5000K WHITE 2568 - 3000K WARM WHITE 2569 - 4000K DAY WHITE	13W	1000

10m ROLL

IP65 RATING

Voltage: DC:24V
LED Qty/M: 120
LED Type: SMD
Current/M:

Beam Angle: 120°
IP Rating: IP65
Width: 8mm
Box Qty: 200 Meters



Bar 4014 144 LEDs

Model	SKU	Watts	Lm/M:	
VT-4014 144-2Pc	2535 - 3000K WARM WHITE 2537 - 6400K WHITE	18W	1700lm	2 PCS PACK
VT-4014 144-10Pc	2538 - 3000K WARM WHITE 2540 - 6400K WHITE	18W	1700lm	10 PCS PACK

Voltage: DC:12V
LED Type: SMD
Current/M: 1.5A

IP Rating: IP20
Width: 1M
Box Qty: 125

Bar 4014 144 LEDs

Model	SKU	Watts	Lm/M:
VT-4014 144-P	2541 - 3000K WARM WHITE	18W	1700lm

Voltage: DC:12V
LED Type: SMD
Current/M: 1.5A

IP Rating: IP20
Width: 1M
Box Qty: 100

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Strip Set -PLUG AND PLAY

SKU	Description	Box Qty
2351	LED Strip Set SMD3528 60 LEDs 4500K IP20:	48
2350	LED Strip Set SMD5050 30 LEDs RGB IP20:	48
2352	LED Strip Set SMD5050 30 LEDs RGB IP65:	50
2353	LED Strip Set SMD5050 60 LEDs RGB IP20:	50
2354	LED Strip Set SMD5050 60 LEDs RGB IP65:	48
2355	LED Strip Set SMD5050 60 LEDs White IP20:	48
2356	LED Strip Set SMD5050 60 LEDs White IP65:	48

LED STRIP LIGHT set is a complete kit where we provide you with 5 meters of LED STRIP LIGHT, along with the POWER SUPPLY and REMOTE CONTROL, to make it a
complete kit. Available and made in different colour options as
per requirement.

- LED Strip
- Remote control (included)
- Driver (included)
- Packing: Blister Pack, 5 meters roll



Strip Connectors

SKU	Description	Box Qty
2587	Flexible Connector – LED Strip 5050 RGB+White:	2500
2588	Flexible Connector – 5050 RGB+White With Pin:	2000
2589	Connector – LED Strip 5050 RGB+White:	3000
3500	Flexible Connector – LED Strip 3528:	100
3501	Flexible Connector – LED Strip 5050:	100
3502	Flexible Connector – LED Strip 5050 RGB:	100
3503	Connector – LED Strip 3528:	100
3504	Connector – LED Strip 5050:	1000
3505	Connector – LED Strip 5050 RGB:	1000
3507	Flexible Connector – LED Strip 3528 DC Female:	100
3508	Flexible Connector – LED Strip 5050 DC Female:	100
3512	Connector – LED Strip DC Female:	100

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

SIlicone Glue

SKU: 2638

Power Plug (EU)

SKU: 2639

H07RN-7 Cable (EU Plug)

SKU: 2640

Middle Connector

SKU: 2641

Fixing Clip + Screws

SKU: 2642

Flexible Connector

SKU: 2643

T Shape Connector

SKU: 2644

L Shape Connector

SKU: 2645

Mounting Kit-5CM

SKU: 2527
Box Qty: 2200

Neon Power Cord

SKU: 3331
Box Qty: 500

Neon Connector

SKU: 3333
Box Qty: 3000

Neon End Safe Cap

SKU: 3334
Box Qty: 2

Plastic Profile-1M

SKU: 2571
Box Qty: 50

Plug-Pin

SKU: 2565
Box Qty: 1000

Fixing Clip

SKU: 2566
Box Qty: 1000

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Connector for Strip 8mm

SKU: 2655
Box Qty: 5000

Connector for Strip 8mm Single Head

SKU: 2656
Box Qty: 2500

Connector for Strip 8mm Dual Head

SKU: 2657
Box Qty: 2500

L Shape Connector for Strip 8mm

SKU: 2658
Box Qty: 5000

Connector for Strip 10mm

SKU: 2659
Box Qty: 5000

Connector for Strip 10mm Single Head

SKU: 2660
Box Qty: 2500

Connector for Strip 10mm Dual Head

SKU: 2661
Box Qty: 2500

L Shape Connector for Strip 10mm

SKU: 2662
Box Qty: 5000

Connector for COB Strip 8mm Single Head

SKU: 2663
Box Qty: 1000

Connector for COB Strip 8mm Dual Head



SKU: 2664
Box Qty: 1000

Connector for COB Strip 10mm Single Head

SKU: 2665
Box Qty: 1000

Connector for COB Strip 10mm Dual Head

SKU: 2666
Box Qty: 1000

QUICK CONNECT WIRE FOR LED STRIP LIGHT

SKU: 11341
Box Qty: 1000

QUICK MIDDLE CONNECTOR FOR LED STRIP LIGHT

SKU: 11342
Box Qty: 1000

QUICK MIDDLE CONNECTOR WITH WIRE FOR LED STRIP LIGHT

SKU: 11343
Box Qty: 500

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

Mounting Kit Black

Model: VT-8113
SKU: 2873
Dimension: 2000×17.4×7mm
Unit Color: Black

Mounting Kit Black

Model: VT-8109
SKU: 2874
Dimension: 2000×15.8×15.8mm
Unit Color: Black

Mounting Kit Black

Model: VT-8106
SKU: 2875
Dimension: 2000×24.7×7mm
Unit Color: Black

Mounting Kit Black

Model: VT-8108
SKU: 2876
Dimension: 2000×23.5×10mm
Unit Color: Black

Mounting Kit Black

Model: VT-8114
SKU: 2877
Dimension: 2000×19×19mm
Unit Color: Black

Mounting Kit Black

Model: VT-8110
SKU: 2878
Dimension: 2000×17.2×14.4mm
Unit Color: Black

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Mounting Kit White

Model:	VT-8126
SKU:	2871
Dimension:	2000×50×35mm
Unit Color:	White

Mounting Kit White

Model:	VT-8127
SKU:	2872
Dimension:	2000×50×75mm
Unit Color:	White

Mounting Kit with Diffuser Surfaced

Model:	VT-8136
SKU:	2903
Dimension:	2000×7.8×9mm
Unit Color:	Silver

Mounting Kit with Diffuser Recessed



Model:	VT-8137
SKU:	2904
Dimension:	2000×12.4×9mm
Unit Color:	Silver

Mounting Kit Bendable Silver

Model:	VT-8138
SKU:	2909
Dimension:	2000×18×6mm
Unit Color:	Silver



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8106-M	3350	2000×24.7×7mm	Silver	180
VT-8122-W	3368	2000×24.7×7mm	White	180





Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8108-M	3352	2000×23.5×10mm	Silver	120
VT-8108-W	3367	2000×23.5×10mm	White	120

DEKRA
TÜV SÜD
www.tuv.com ID 1111227954
RoHS COMPLIANT
CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8109-M	3353	2000×15.8×15.8mm	Silver	160
VT-8123-W	3369	2000×15.8×15.8mm	White	160



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8110-M	3354	2000×17.2×15.5mm	Silver	120
VT-8110-W	3366	2000×17.2×15.5mm	White	120



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8113-M	3355	2000×17.4×7mm	Silver	180
VT-8113-W	3365	2000×17.4×7mm	White	180



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8114-M	3356	2000×19×19mm	Silver	120
VT-8114-W	3364	2000×19×19mm	White	120



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8107	3351	2000×23×15.5mm	Silver	120





Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-9327	3370	2000×16mmx7mm	Silver	200

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8115	3357	2000×24.5×12.2mm	Silver	120





Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8116	3358	2000×17.4×12.1mm	Silver	120





Mounting Kit-Silver-Set

Model	SKU	Dimension	Color	Box Qty
VT-8101	3359	2000mm	Silver	30





Mounting Kit-Silver-Set

Model	SKU	Dimension	Color	Box Qty
VT-8102	3360	2000mm	Silver	50



Mounting Kit-Silver-Set

Model	SKU	Dimension	Color	Box Qty
VT-8103	3361	2000mm	Silver	40



Mounting Kit-Silver-Set

Model	SKU	Dimension	Color	Box Qty
VT-8104	3362	2000mm	Silver	30

DEKRA
www.tuv.com ID 1111227954
RoHS COMPLIANT
CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING



Mounting Kit-Silver-Set

Model	SKU	Dimension	Color	Box Qty
VT-8105	3363	2000mm	Silver	30



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8118	3371	2000×30×20mm	Silver	50



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-8119	3372	2000×32×20mm	Silver	60



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-7103-M	9986	26.5×9×1000mm	Matt	90



Mounting Kit

Model	SKU	Dimension	Color	Box Qty
VT-7104	9956	19×19×2000mm	Silver	40

Strip-Controller-Dimmer

Model: VT-2402
SKU: 3300
Input voltage: DC:12/24V
Box Qty: 50

Strip-Controller-Radio

Model: VT-2404
SKU: 3303
Input voltage: DC:12/24V
Box Qty: 100

Strip-Controller-DMX 512

Model: VT-DM X 512
SKU: 3307
Input voltage: DC:12V
Box Qty: 50

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

SINGLE COLOR CONTROLLER

Model	SKU
VT-2431	2911

- Voltage: DC:12V-24V
- Working Temperature: -10~40 °C
- Output: Max 12A
- RF: 2.4GHz
- Control Distance: 30m
- Output connection: Common anode

RGB CONTROLLER

Model	SKU
VT-2432	2912

- Voltage: DC12V-24V
- Working Temperature: -10~40°C
- Output Max: 6A/Channel
- Total Output Max:12A
- RF: 2.4GHz
- Control Distance: 30m
- Output connection: Common anode

RGB+W CONTROLLER

Model	SKU
VT-2434	2913

- Voltage: DC12V-24V
- Working Temperature: -10~40°C
- Output Max: 6A/Channel
- Total Output Max:12A
- RF: 2.4GHz
- Control Distance: 30m
- Output connection: Common anode

5 CHANNEL AMPLIFIER

Model	SKU
VT-2435	2914

- Voltage: DC12V/24V
- Work Temperature: -20~60°C
- Output Voltage: DC12V/24V
- Output Current: 6A/ Channel
- Total output Max: 15A
- Switching Rate: 10Mbps
- Connection: Common anode

WALL CONTROLLER – 3 IN 1

Model	SKU
VT-2433	2915

- Voltage: DC12V-24V
- Output Max: 5A/Channel
- Total Output Max: 10A
- RF: 2.4GHz
- Control Distance: 30m
- Working Temperature: -20~60°C
- Panel Size: 86×86mm"
- Compatible with RGB/RGBW/RGB+CCT strips

4 ZONE CONTROLLER

Model	SKU
VT-2439	2916

- Voltage: 3V(2*AAA Battery)
- Transmission Frequency: 2400-2483.5MHz
- Modulation Method: GFSK
- Transmitting Power: 6dBm
- Control Distance: 30m
- Standby Power: 20uA
- Working Temperature: -10 -40°C
- Panel Size: 86×86×16mm

4 ZONE RGB+W CONTROLLER

Model	SKU
VT-2437	2917

- Voltage: 3V(2*AAA Battery)
- Transmission Frequency: 2400-2483.5MHz
- Modulation Method: GFSK
- Transmitting Power: 6dBm
- Control Distance: 30m
- Standby Power: 20uA
- Working Temperature: -10 -40°C
- Panel Size: 86×86×16mm

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

TOUCH DIMMER-WHITE

Model	SKU
VT-2440-W	2919

- Voltage: 3V(2*AAA Battery)
- Working Temperature: -20 -60°C
- Transmission Frequency: 2400-2483.5MHz
- Modulation Method: GFSK
- Transmitting Power: 6dBm
- Standby Power: 20uA
- Control Distance: 30m

TOUCH DIMMER-BLACK

Model	SKU
VT-2440-B	2920

- Voltage: 3V(2*AAA Battery)
- Working Temperature: -20 -60°C
- Transmission Frequency: 2400-2483.5MHz
- Modulation Method: GFSK
- Transmitting Power: 6dBm
- Standby Power: 20uA
- Control Distance: 30m

8 ZONE REMOTE CONTROL

Model	SKU
VT-2438	2921

- Voltage: 3V(2*AAA Battery)
- Control Distance: 30m
- Size: 47×19×153mm

4 ZONE REMOTE CONTROL

Model	SKU
VT-2436	2918

- Voltage: 3V(sevtion 2 batteries)
- Control Distance: 30m
- Size: 53×21×110.5mm

TOUCH REMOTE CONTROL RGB+CCT

Model	SKU
VT-2441	2922

- Voltage: 3V(2*AAA Battery)
- Control Distance: 30m
- Size: 56×20×138mm

TOUCH REMOTE CONTROL RGB+W-WHITE

Model	SKU
VT-2442-W	2923

- Voltage: 3V(sevtion 2 batteries)
- Control Distance: 30m
- Size: 52.5×21×120mm

TOUCH REMOTE CONTROL RGB+W-BLACK

Model	SKU
VT-2442-B	2924

- Voltage: 3V(sevtion 2 batteries)
- Control Distance: 30m
- Size: 52.5×21×120mm

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Strip-Controller-Radio

Model: VT-2405
SKU: 3312
Input voltage: DC:12/24V
Box Qty: 20

Strip-Controller-Infrared

Model: VT-2472
SKU: 3625
Input voltage: DC:12/24V
Box Qty: 100

Strip-Amplifier-5050

Model: 3018
SKU: 3018
Input voltage: DC:12V
Box Qty: 1000

Strip-Controller-Wi-Fi RGB

Model: 3322
SKU: 3322
Input voltage: DC:12V
Box Qty: 50

Strip-Controller-5050

Model: 3326
SKU: 3326
Input voltage: DC:12/24V
Box Qty: 100

Strip-Amplifier

Model: VT-2408
SKU: 3327
Input voltage: DC:12/24V
Box Qty: 100

Strip-Amplifier

Model: VT-2407
SKU: 3309
Input voltage: DC:12/24V
Box Qty: 100

Bed Light-Sensor

Sensing Distance:2–5m
DeLay Time:3s-6min

Model: VT-8069
SKU: 2554
Input voltage: DC:12V
Box Qty: 400

Bed Light-Touch Sensor



Model: VT-8071
SKU: 2556
Input voltage: DC:12V
Box Qty: 100

Bed Light-Hand Wave Sensor

Model: VT-8072
SKU: 2557
Input voltage: DC:12V
Box Qty: 100

Strip-Controller-Dimmer



Model: VT-2411
SKU: 3341
Input voltage: DC:12V
Box Qty: 500

LED Sync Controller- Dimmer

Model: VT-2414
SKU: 3337
Input voltage: DC:12/24V
Box Qty: 50

LED Sync Controller- RGBW/WW

Model: VT-2424
SKU: 3338
Input voltage: DC:12/24V
Box Qty: 60

LED Sync Controller- RGB

Model: VT-2420
SKU: 3339
Input voltage: DC:12/24V
Box Qty: 60

LED Sync Controller- RGB

Model: VT-2421
SKU: 3340
Input voltage: DC:12/24V
Box Qty: 100

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Strip Dimmer- Touch Remote Control

Model:	VT-5115
SKU:	2590
Input voltage:	DC:12/24V
Box Qty:	50

Strip-Controller-RGB + CCT

NEW

Model:	VT-2428
SKU:	2899
Input voltage:	DC:12V/24V
Box Qty:	100

Strip-Controller-CCT

NEW

Model:	VT-2425
SKU:	2901
Input voltage:	DC:12V/24V
Box Qty:	100

Strip Controller- WiFi – RGB + CCT

NEW

Model:	VT-2429
SKU:	2900
Input voltage:	DC:12V/24V

Strip WIFI Controller – CCT

NEW

Model:	VT-2427
SKU:	2902
Input voltage:	DC:12V/24V

Modules-3 SMD-IP67

IP67 RATING

VT-50503

5116 – 6000K WHITE
5117 -RED
5118 – BLUE
5119 – GREEN

Watts:	0.72W
Voltage/Frequency:	DC:12V
Luminous Flux:	66lm
LED Type:	SMD
CRI:	>75
Beam Angle:	160°
Dimension:	67×15×8.5mm
IP Rating:	IP67
Box Qty:	2000

Modules-3 SMD-IP67

IP67 RATING



VT-28353

5120 – 6000K WHITE
5121 -RED
5123 – GREEN

Watts:	1W
Voltage/Frequency:	DC:12V
Luminous Flux:	100lm
LED Type:	SMD
CRI:	>75
Beam Angle:	120°
Dimension:	53×12×4.6mm
IP Rating:	IP67
Box Qty:	200

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Modules-3 SMD-IP67

IP67 RATING

VT-28356

5124 – 3000K WARM WHITE
5127 – BLUE
5128 – GREEN

Watts:	1.5W
Voltage/Frequency:	DC:12V
Luminous Flux:	120–150lm
LED Type:	SMD
CRI:	>75
Beam Angle:	120°
Dimension:	87×15×10mm
IP Rating:	IP67
Box Qty:	2000

Modules-4 SMD-IP68

IP68 RATING



VT-28358

5129 – 3000K WARM WHITE
5130 – 6000K WHITE
5131 -RED
5132 – BLUE
5133 – GREEN

Watts:	1.44W
Voltage/Frequency:	DC:12V
Luminous Flux:	120–135lm
LED Type:	SMD
CRI:	>75
Beam Angle:	160°
Dimension:	37×37×6.8mm
IP Rating:	IP68
Box Qty:	100

Modules-3 SMD-IP67

IP67 RATING

VT-50506

5134 – RGB

Watts:	0.72W
Voltage/Frequency:	DC:12V
Luminous Flux:	20lm
LED Type:	SMD
CRI:	>75
Beam Angle:	120°
Dimension:	68×19.5×5.7mm
IP Rating:	IP67
Box Qty:	100

Modules-SMD-IP68

IP68 RATING

VT-50501

5135 – 3000K WARM WHITE
5136 – 6000K WHITE
5141 – 4000K DAY WHITE
5137 -RED
5139 – BLUE
5140 – GREEN
5138 – YELLOW

Watts:	0.24W
Voltage/Frequency:	DC:12V
Luminous Flux:	20lm
LED Type:	SMD
CRI:	>75
Beam Angle:	120°
Dimension:	12×22mm
IP Rating:	IP68
Box Qty:	320

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Slim Power Supply

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-20030	3255	30W	2.5A	AC:220-240V,50Hz	DC:12V	130×50×31mm	36
VT-20062	3246	60W	5A	AC:85-265V,50/60Hz	DC:12V	130×50×31mm	36
VT-24061	3261	60W	2.5A	AC:85-265V,50/60Hz	DC:24V	130×50×31mm	36
VT-20077	3247	75W	6A	AC:85-265V,50/60Hz	DC:12V	130×50×31mm	60
VT-20122	3243	120W	10A	AC:85-265V,50/60Hz	DC:12V	190×50×31mm	80
VT-24120	3262	120W	5A	AC:85-265V,50/60Hz	DC:24V	190×50×31mm	80
VT-20152	3244	150W	12.5A	AC:85-265V,50/60Hz	DC:12V	200×62×31mm	60
VT-20153	3253	150W	6.5A	AC:85-265V,50/60Hz	DC:24V	200×62×31mm	50
VT-22250	3273	250W	10A	AC:200-265V, 50Hz	DC:24V	225×60×30mm	30

NEW

Power Supply - Plastic

Model	SKU	Watts	Current Capacity:	Input Power	Output	Box Qty
VT-23032	2671	30W	2.5A	AC:100-240V,50/60Hz	DC:12V	100
VT-23044	2672	42W	3.5A	AC:100-240V,50/60Hz	DC:12V	100

NEW

Power Supply - Metal

Model	SKU	Watts	Current Capacity:	Input Power	Output	Box Qty
VT-21061	2682	60W	5A	AC:100-240V,50/60Hz	DC:12V	100
VT-21062	2683	60W	2.5A	AC:100-240V,50/60Hz	DC:24V	100
VT-21071	2684	75W	6.25A	AC:176-264V,50/60Hz	DC:12V	100
VT-21072	2685	75W	3.15A	AC:176-264V,50/60Hz	DC:24V	100

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



Power Supply – Metal

Model	SKU	Watts	Current Capacity:	Input Power	Output	Box Qty
VT-21121	2686	120W	10A	AC:176-264V,50/60Hz	DC:12V	50
VT-21122	2687	120W	5A	AC:176-264V,50/60Hz	DC:24V	50
VT-21152	2688	150W	12.5A	AC:176-264V,50/60Hz	DC:12V	50
VT-21153	2689	150W	6.25A	AC:176-264V,50/60Hz	DC:24V	50

Power Supply – Metal

Model	SKU	Watts	Current Capacity:	Input Power	Output	Box Qty
VT-21252	2690	250W	20.8A	AC:176-264V,50/60Hz	DC:12V	20
VT-21253	2691	250W	10.41A	AC:176-264V,50/60Hz	DC:24V	20
VT-21301	2692	300W	25A	AC:176-264V,50/60Hz	DC:12V	20
VT-21302	2693	300W	12.5A	AC:176-264V,50/60Hz	DC:24V	20

Power Supply – Metal

Model	SKU	Watts	Current Capacity:	Input Power	Output	Box Qty
VT-21501	2694	500W	42A	AC:200-240V,50/60HZ	DC:12V	20
VT-21502	2695	500W	21A	AC:200-240V,50/60HZ	DC:24V	20

Slim Power Supply

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-20352	3259	350W	30A	AC:200-240V,50/60 Hz	DC:12V	208×82×32mm	30
VT-24350	3263	350W	15A	AC:200-240V,50/60 Hz	DC:24V	208×82×32mm	30

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING



Power Supply – Metal

5 YEAR WARRANTY

NOISE WITHOUT FAN

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-21361	3275	360W	15A	AC:200-240V,50Hz	DC:24V	208×82×32mm	24
VT-21360	3274	360W	30A	AC:200-240V,50Hz	DC:12V	208×82×32mm	24

Power Supply-Metal

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-20026	3228	25W	2.1A	AC:85-265V,50/60Hz	DC:12V	115×40×25mm	100



LED Power Supply-TRIAC Dimmable

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-20101D	3256	100W	8.5A	AC:200-240V,50/60 Hz	DC:12V	199×62×31mm	50
VT-20154D	3257	150W	12.5A	AC:200-240V,50/60 Hz	DC:12V	199×62×31mm	50
VT-20155D	3258	150W	6.25A	AC:200-240V,50/60 Hz	DC:24V	199×62×31mm	50

LED Power Supply-Rainproof-IP45

IP45 RATING

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-21060	3070	60W	5A	AC:200-240V,50Hz	DC:12V	125×74×42mm	30

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Power Supply-Rainproof-IP45

IP45 RATING

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-21151	3231	150W	12.5A	AC: 100-264V,50/60Hz	DC:12V	207×74×42mm	40
VT-21251	3232	250W	20A	AC: 100-264V,50/60Hz	DC:12V	218×95×50mm	25
VT-21401	3233	400W	33A	AC: 100-264V,50/60Hz	DC:12V	223×118×50mm	20
VT-26400	3265	400W	16.6A	AC: 100-264V,50/60Hz	DC:24V	223×118×50mm	20

Power Supply-Waterproof-IP65

IP65 RATING

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-22101	3236	100W	8.0A	AC: 100-264V,50/60Hz	DC:12V	201×30.5×20mm	20
VT-22101-24	3101	100W	4.2A	AC: 100-264V,50/60Hz	DC:24V	192×52×37mm	20

Power Supply-Waterproof-IP67

IP67 RATING

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-21030	3271	30W	2.5A	AC:100-240V,50/60Hz	DC:12V	150×40×30mm	60
VT-22061	3234	60W	5A	AC: 100-264V,50/60Hz	DC:12V	166×43×33mm	40
VT-22075	3235	75W	6A	AC: 100-264V,50/60Hz	DC:12V	166×43×33mm	40
VT-22153	3248	150W	12.5A	AC: 100-264V,50/60Hz	DC:12V	192×62×38mm	15

Power Supply-Waterproof-IP67

5 YEAR WARRANTY

IP67 RATING

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-22065	3252	60W	5A	AC: 100-264V,50/60Hz	DC:12V	166×43×33mm	40
VT-22105	3251	100W	8.3A	AC: 100-264V,50/60Hz	DC:12V	192×52×37mm	25
VT-22155	3250	150W	12.5A	AC: 100-264V,50/60Hz	DC:12V	192×62×38mm	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Power Supply-Plastic-IP44

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-23019	3237	18W	1.5A	AC: 100-264V,50/60Hz	DC:12V	73×27×43mm	120

Power Supply-Plastic-BS Plug

BS PLUG

Model	SKU	Watts	Current Capacity:	Input Power	Output	Dimension	Box Qty
VT-23060	3035	60W	5A	AC:100-265V 50/60 Hz	DC:12V	119×52×32mm	50

Power Supply-Plastic-IP44

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-23031	3238	30W	2.5A	AC: 100-264V,50/60Hz	DC:12V	119×52×32mm	50
VT-23043	3249	42W	3.5A	AC:100-265V 50/60 Hz	DC:12V	119×52×32mm	50
VT-23061	3239	60W	5A	AC: 100-264V,50/60Hz	DC:12V	119×52×32mm	50
VT-25060	3264	60W	2.5A	AC: 100-264V,50/60Hz	DC:24V	119×52×32mm	50
VT-22078	3272	78W	3.25A	AC: 100-264V,50/60Hz	DC:24V	119×52×32mm	50
VT-23079	3240	78W	6.5A	AC: 100-264V,50/60Hz	DC:12V	119×52×32mm	50

Power Supply-Plastic-IP44

BS PLUG

Model	SKU	Watts	Current Capacity	Input Power	Output	Dimension	Box Qty
VT-23060-W	3269	60W	5A	AC:100-264V	DC:12V	119×52×32mm	50

LED TRACK LIGHTS

V-TAC's extensive range of modern LED track lights are the perfect ecological alternative to old, inefficient Halogen lights. Delivering high performance, excellent durability, and remarkable light output to serve the general Commercial and Retail market.

Key Features

- Saves 80% energy
- No Ultraviolet or Infrared Rays
- Totally flexible, compact & adjustable design
- No Lead or mercury content hence environment-friendly
- Provides uniform radiance & enhances the appeal of a retail environment
- Enhances measurable levels of performance as compared to older versions of high wattage Halogen

Application

Perfect choice for exhibition stands, hotels, bars, commercial & residential lighting.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Track Light-Smart Color Changing

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 18°-48° Beam Angle
- LED Type :COB
- Body Type: Aluminium





CCT and Dimming VIA SMART PHONE APP

CCT Adjustable 2800K/4000K/6000K

V-TAC SMART

Model	SKU	Watts	Lumen	Box Qty
VT-7715-W	1456 - 3 IN 1	15w	650	20

Track Light-Smart Color Changing

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 18°-48° Beam Angle
- LED Type :COB
- Body Type: Aluminium





CCT and Dimming VIA SMART PHONE APP

CCT Adjustable 2800K/4000K/6000K

V-TAC SMART

Model	SKU	Watts	Lumen	Box Qty
VT-7715-B	1457 - 3 IN 1	15w	500	20

Track Light-Smart Color Changing

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 16°-53° Beam Angle
- LED Type :COB
- Body Type: Aluminium





CCT and Dimming VIA SMART PHONE APP

CCT Adjustable 2800K/4000K/6000K

V-TAC SMART

Model	SKU	Watts	Lumen	Box Qty
VT-7735-W	1458 - 3 IN 1	35w	2350	20

Track Light-Smart Color Changing

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 16°-53° Beam Angle
- LED Type :COB
- Body Type: Aluminium





CCT and Dimming VIA SMART PHONE APP

CCT Adjustable 2800K/4000K/6000K

V-TAC SMART

Model	SKU	Watts	Lumen	Box Qty
VT-7735-B	1459 - 3 IN 1	35w	1950	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Track Light-Color Changing

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >95
- 20° ~ 60° (Adjustable) Beam Angle
- LED Type :COB
- Body Type: Aluminium



CCT Adjustable
2800K/4000K/6000K

Lens Angle Adjustable
20°~60°

Triac Dimmable

5 YEAR WARRANTY

REAL COLOR SERIES CRI >95

Model	SKU	Watts	Lumen	Box Qty
VT-4745-W	1412 - 3 IN 1	35w	3000	8

Track Light-Black-White Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 24° Beam Angle
- LED Type :COB
- Body Type: Aluminium





5 YEAR WARRANTY

Model	SKU	Watts	Lumen	Box Qty
VT-4512	1333 - 4000K DAY WHITE 1334 - 6000K WHITE	10w	800	40

Track Light-Black-White Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 24° Beam Angle
- LED Type :COB
- Body Type: Aluminium





5 YEAR WARRANTY

Model	SKU	Watts	Lumen	Box Qty
VT-4528	1337 - 6000K WHITE	25w	2100	20

Track Light-Black-White Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 24° Beam Angle
- LED Type :COB
- Body Type: Aluminium





5 YEAR WARRANTY

Model	SKU	Watts	Lumen	Box Qty
VT-4537	1338 - 3000K WARM WHITE 1340 - 6000K WHITE	35w	2850	10

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Track Light-White Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >95
- 24° Beam Angle
- LED Type :COB
- Body Type: Aluminium





5 YEAR WARRANTY

REAL COLOR SERIES CRI >95

Model	SKU	Watts	Lumen	Box Qty
VT-4615W	1300 - 6400K WHITE	15w	1350	20

Track Light-White Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >95
- 24° Beam Angle
- LED Type :COB
- Body Type: Aluminium





5 YEAR WARRANTY

REAL COLOR SERIES CRI >95

Model	SKU	Watts	Lumen	Box Qty
VT-4635W	1294 - 6400K WHITE	30w	2700	20

Track Light-Black Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >95
- 24° Beam Angle
- LED Type :COB
- Body Type: Aluminium





5 YEAR WARRANTY

REAL COLOR SERIES CRI >95

Model	SKU	Watts	Lumen	Box Qty
VT-4615B	1303 - 6400K WHITE	15w	1350	20

Track Light-Black Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >95
- 24° Beam Angle
- LED Type :COB
- Body Type: Aluminium





5 YEAR WARRANTY

REAL COLOR SERIES CRI >95

Model	SKU	Watts	Lumen	Box Qty
VT-4635B	1297 - 6400K WHITE	30w	2700	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Track Light-Black Body

- AC:100-240V,50/60Hz
- PF: >0.9
- CRI: >95
- 25° Beam Angle
- LED Type :COB
- Body Type: Die Cast Aluminium





Model	SKU	Watts	Lumen	Box Qty
VT-4535	1235 - 5000K WHITE	33w	1800	8

Track Light-Black Body

- AC:100-240V,50/60Hz
- PF: >0.9
- CRI: >95
- 25° Beam Angle
- LED Type :COB
- Body Type: Die Cast Aluminium





Model	SKU	Watts	Lumen	Box Qty
VT-4545	1238 - 5000K WHITE	45w	2300	8

Track Light-White Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- LED Type :COB
- Body Type: Aluminium
- 24° Beam Angle





Model	SKU	Watts	Lumen	Box Qty
VT-4536W	1255 - 3000K WARM WHITE 1256 - 4500K DAY WHITE 1257 - 6000K WHITE	35w	3500	20
VT-4536W-N	211256 - 4000K DAY WHITE 211257 - 6500K WHITE	35w	4000K-3250 6400K-3350	20

Track Light-Black Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- LED Type :COB
- Body Type: Aluminium
- 24° Beam Angle





Model	SKU	Watts	Lumen	Box Qty
VT-4536B	1285 - 3000K WARM WHITE 1286 - 4000K DAY WHITE 1287 - 6000K WHITE	35w	3500	20
VT-4536B-N	211286 - 4000K DAY WHITE	35w	3250	20

DEKRA TUV SUD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Track Light-Black Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >70
- 22° Beam Angle
- LED Type :COB
- Body Type: Aluminium





Model	SKU	Watts	Lumen	Box Qty
VT-4540T	1192 - 5000K DAY WHITE	40w	2600	8

Track Light-Black Body

- AC:220-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 22° Beam Angle
- LED Type :COB
- Body Type: Die Cast Aluminium





Model	SKU	Watts	Lumen	Box Qty
VT-4534B	1232 - 5000K WHITE	33w	2300	8

Connector 4I

SKU: 3522
Box Qty: 50

Connector 4I

SKU: 3523
Box Qty: 50

Connector 4T

SKU: 3524
Box Qty: 25

Connector 4T

SKU: 3525
Box Qty: 25

Connector 4X

SKU: 3526
Box Qty: 10

4 Wired Y Series Connector

SKU: 3655
Box Qty: 100

4 Wired Y Series Connector

SKU: 3656
Box Qty: 100

End Cap White

SKU: 3657
Box Qty: 200

End Cap Black

SKU: 3658
Box Qty: 200

4 Wired Y Series Adaptor

SKU: 3659
Box Qty: 50

4 Wired Y Series Adaptor

SKU: 3660
Box Qty: 50

Connector 4X

SKU: 3527
Box Qty: 10

Connector 4L

SKU: 3528
Box Qty: 25

Connector 4L

SKU: 3529
Box Qty: 25

Flexible Joint 4 Line

SKU: 3559
Box Qty: 20

Flexible Joint 4 Line

SKU: 3560
Box Qty: 20

Hanging Trackline Kit 1 Meter

SKU: 3565
Box Qty: 100

Hanging Trackline Kit 1 Meter

SKU: 3566
Box Qty: 100

4 Core Track 1 Meter

SKU: 9944
Box Qty: 10

4 Core Track 1 Meter

SKU: 9945
Box Qty: 10

4 Core Track 1.5 Meter

SKU: 9952
Box Qty: 10

4 Core Track 1.5 Meter

SKU: 9953
Box Qty: 10

4 Core Track 2 Meter

SKU: 9954
Box Qty: 10

4 Core Track 2 Meter

SKU: 9955
Box Qty: 10

LED DOWNLIGHTS

Swap outdated CFL Lights with high-quality LED Down Lights for long-lasting and energy-efficient lighting. Choose from a wide range of 3w to 40w variations.

Key Features

- Innumerable styles & elegant appearance
- Non – Flickering
- Premium quality power driver with lowest power factor saver & high RA
- Easy Installation
- Varied finishes with strong die cast aluminium body
- Low maintenance

Application

Residences, showrooms, hotels & boutiques etc.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED DOWNLIGHTS

LED COB Hotel Downlight

- AC:220-240V,50Hz
- PF: >0.6
- CRI: >95
- 0-27° Beam Angle
- On/0ff: >20000
- Life span:30,000-hour
- Body Type: Aluminium

POWERED BY CREE LED

UGR<19

REAL COLOR SERIES CRI >95

Model	SKU	Watts	Lumen	Size	Box Qty
VT-2907	1479 - 3000K WARM WHITE 1480 - 4000K DAY WHITE	6w	400	 Cutting Size Ø55mm	24
VT-2911	1481 - 3000K WARM WHITE 1482 - 4000K DAY WHITE	10w	650	 Cutting Size Ø75mm	16
VT-2916	1483 - 3000K WARM WHITE 1484 - 4000K DAY WHITE	15w	1000	 Cutting Size Ø95mm	12
VT-2936	1477 - 3000K WARM WHITE 1478 - 4000K DAY WHITE	35w	2300	 Cutting Size Ø150mm	8

Side Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- Life span:20,000-hour
- 30° Beam Angle
- LED Type :COB-CREE
- Body Type: Die Cast Aluminium
- Size: 80×80×25mm

Model	SKU	Watts	Lumen	Box Qty
VT-2903	1485 - 3000K WARM WHITE	3w	180	40
VT-2903-N	211485 - 3000K WARM WHITE	3w	150	40

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS www.tuv.com ID 1111227954 RoHS COMPLIANT CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Side Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- Life span:20,000-hour
- 30° Beam Angle
- LED Type :COB-CREE
- Body Type: Die Cast Aluminium
- Size: 90×60×30mm

Model	SKU	Watts	Lumen	Box Qty
VT-2913	1486 - 3000K WARM WHITE	3w	180	40

Side Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- Life span:20,000-hour
- 30° Beam Angle
- LED Type :COB-CREE
- Body Type: Die Cast Aluminium
- Size: 120×120×45mm

Model	SKU	Watts	Lumen	Box Qty
VT-2943	1487 - 3000K WARM WHITE	3w	180	20
VT-2943-N	211487 - 3000K WARM WHITE	3w	150	20

Dual Side Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- Life span:20,000-hour
- 120° Beam Angle
- LED Type :CREE Chip
- Body Type: Die Cast Aluminium
- Size: 300×50×35mm

Model	SKU	Watts	Lumen	Box Qty
VT-2953	1488 - 3000K WARM WHITE	3+6w	180+500	30

Dual Side Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- Life span:20,000-hour
- 120° Beam Angle
- LED Type :COB-CREE
- Body Type: Die Cast Aluminium
- Size: 140×30mm

Model	SKU	Watts	Lumen	Box Qty
VT-2963	1489 - 3000K WARM WHITE	3+6w	180+500	30

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED DOWNLIGHTS

Reflector Series – High Lumen

- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- Life span:20,000-hour
- Body Type: PKW
- 120° Beam Angle

120 lm/W

Model	SKU	Watts	Lumen	Size	Box Qty
VT-2610	1100 – 6000K WHITE	10w Regular Lumen	730	 Cutting Size Ø105mm	27
VT-26101	1270 – 3000K WARM WHITE 1271 – 4000K DAY WHITE 1272 – 6400K WHITE	10w	1200	 Cutting Size Ø120mm	27
VT-26201	1273 – 3000K WARM WHITE 1274 – 4000K DAY WHITE 1275 – 6400K WHITE	20w	2400	 Cutting Size Ø167mm	18
VT-26301	1276 – 3000K WARM WHITE 1277 – 4000K DAY WHITE 1278 – 6400K WHITE	30w	3600	 Cutting Size Ø207mm	12
VT-26301-N	211276 – 3000K WARM WHITE 211277 – 4000K DAY WHITE 211278 – 6500K WHITE	30w	3100	 Cutting Size Ø207mm	12
VT-26451	1453 – 3000K WARM WHITE 1279 – 4000K DAY WHITE 1280 – 6400K WHITE	40w	4800	 Cutting Size Ø207mm	12
VT-26451-N	211279 – 4000K DAY WHITE 211280 – 6400K WHITE	40w	4200	 Cutting Size Ø207mm	12

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



LED DOWNLIGHTS

Reflector Downlight

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 50° Beam Angle
- Body Type: PC



Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-8407	7610 - 3000K WARM WHITE 7611 - 4000K DAY WHITE 7612 - 6000K WHITE	7W White	560	Ø90×46mm	Ø75mm	50

LED DOWNLIGHTS

Fire Rated Downlight With White Bezel

- AC:220-240V,50Hz
- 38° Beam Angle
- Life span:30,000-hour
- Body Type: Aluminium



V-TAC SMART APP
CCT and Dimming
VIA SMART PHONE APP

30-60-90 MIN
Fire Rated

IP65
RATING

QUICK
CONNECTOR

5 YEAR
WARRANTY

Model	SKU	Watts	Lumen	Size	Cutting Size	Box Qty
VT-7710	1424 - 3 IN 1	10w	850	Ø83×57mm		40

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED DOWNLIGHTS Fire Rated Downlight



30-60-90 MIN
Fire Rated

DIMMABLE

FLICKER FREE

IP65 RATING

- AC:200-240V,50/60Hz
- Size: Ø90×45mm
- Cutting size: Ø65mm
- Unit Color: White
- LED Chip Type: SMD

Model	SKU	Watts	Lumen
VT-DL0508	7614 - 4IN1	5W/8W	5W 2700K-460lm 3000K-500lm 4000K-520lm 6400K-540lm 8W 2700K-720lm 3000K-720lm 4000K-800lm 6400K-840lm

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS www.tuv.com ID 1111227954 RoHS COMPLIANT CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Fire Rated Fitting-GU10

30-60-90 MIN Fire Rated

Model:	VT-703-WH
SKU:	8916
Material:	Steel
Color:	White
IP Rating:	IP20
Dimension:	Ø90×106mm
Cutting Size	Ø75mm
Box Qty:	60

Twist & Lock

Fire Rated Fitting-GU10

30-60-90 MIN Fire Rated

Model:	VT-703-N
SKU:	8917
Material:	Steel
Color:	Satin Nickle
IP Rating:	IP20
Dimension:	Ø90×106mm
Cutting Size	Ø75mm
Box Qty:	60

Twist & Lock

Fire Rated Fitting-GU10

30-60-90 MIN Fire Rated

Model:	VT-703-C
SKU:	8918
Material:	Steel
Color:	Chrome
IP Rating:	IP20
Dimension:	Ø90×106mm
Cutting Size	Ø75mm
Box Qty:	60

Twist & Lock

Fire Rated Fitting-GU10



30-60-90 MIN Fire Rated

Model:	VT-701-SN
SKU:	3680
Material:	Steel
Color:	Satin Nickel
IP Rating:	IP20
Dimension:	Ø80mmx115mm
Cutting Size	65mm
Box Qty:	50

Fire Rated Fitting-GU10



30-60-90 MIN Fire Rated

Model:	VT-701-W
SKU:	3681
Material:	Steel
Color:	White
IP Rating:	IP20
Dimension:	Ø80mmx115mm
Cutting Size	65mm
Box Qty:	50

Fire Rated Fitting-GU10



30-60-90 MIN Fire Rated

Model:	VT-701-CH
SKU:	3682
Material:	Steel
Color:	Chrome
IP Rating:	IP20
Dimension:	Ø80mmx115mm
Cutting Size	65mm
Box Qty:	50

Fire Rated Fitting-GU10



30-60-90 MIN Fire Rated

Model:	VT-702-SN
SKU:	3683
Material:	Steel
Color:	Satin Nickel
IP Rating:	IP65
Dimension:	Ø86mmx115mm
Cutting Size	65mm
Box Qty:	40

IP65 RATING

Fire Rated Fitting-GU10



30-60-90 MIN Fire Rated

Model:	VT-702-W
SKU:	3684
Material:	Steel
Color:	White
IP Rating:	IP65
Dimension:	Ø86mmx115mm
Cutting Size	65mm
Box Qty:	40

IP65 RATING

Fire Rated Fitting-GU10



30-60-90 MIN Fire Rated

Model:	VT-702-CH
SKU:	3685
Material:	Steel
Color:	Chrome
IP Rating:	IP65
Dimension:	Ø86mmx115mm
Cutting Size	65mm
Box Qty:	40

IP65 RATING

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Can for Fire Rated Downlight

NEW

Model: VT-703-IP20
SKU: 11281
Material: Iron
Color: Black
IP Rating: IP20
Dimension: 90×120mm
Cutting Size 80mm
Box Qty: 60



IP20 RATING

Can for Fire Rated Downlight

NEW

Model: VT-703-IP65
SKU: 11286
Material: Iron
Color: Black
IP Rating: IP65
Dimension: 90×120mm
Cutting Size 80mm
Box Qty:



IP65 RATING

White Bezel-IP20 Push and Lock

NEW

IP20 RATING 5 pcs Pack

SKU: 11277
Dimension: 90mm
Unit Color: White
Body Type: Iron
IP Rating: IP20

Black Bezel-IP20 Push and Lock

NEW

IP20 RATING 5 pcs Pack

SKU: 11278
Dimension: 90mm
Unit Color: Black
Body Type: Iron
IP Rating: IP20

Satin Nickel Bezel-IP20 Push and Lock

NEW

IP20 RATING 5 pcs Pack

SKU: 11279
Dimension: 90mm
Unit Color: Satin Nickel
Body Type: Iron
IP Rating: IP20

Chrome Bezel-IP20 Push and Lock

NEW

IP20 RATING 5 pcs Pack

SKU: 11280
Dimension: 90mm
Unit Color: Chrome
Body Type: Iron
IP Rating: IP20

White Bezel-IP65 Push and Lock

NEW

IP65 RATING 5 pcs Pack

SKU: 11282
Dimension: 90mm
Unit Color: White
Body Type: Iron
IP Rating: IP65

Black Bezel-IP65 Push and Lock

NEW

IP65 RATING 5 pcs Pack

SKU: 11283
Dimension: 90mm
Unit Color: Black
Body Type: Iron
IP Rating: IP65

Satin Nickel Bezel-IP65 Push and Lock

NEW

IP65 RATING 5 pcs Pack

SKU: 11284
Dimension: 90mm
Unit Color: Satin Nickel
Body Type: Iron
IP Rating: IP65

Chrome Bezel-IP65 Push and Lock

NEW

IP65 RATING 5 pcs Pack

SKU: 11285
Dimension: 90mm
Unit Color: Chrome
Body Type: Iron
IP Rating: IP65

LED DOME LIGHTS

Create a better ambience in any environment with V-TAC's LED Dome Lights. These compact and easy to install lights make a perfect replacement for traditional dome lights.

Key Features

- Non – flickering
- No UV radiation
- Easy installation
- Premium quality LED chip
- Premium quality power driver
- Instant start 0–100% in 0.01 seconds
- Extreme weather toleration (-20 to + 45 degrees centigrade)

Application

Mostly used in parking lots, passage's in big areas, exterior walls of prestigious buildings for ambience, airports, ports and malls

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

IP44
RATING

SENSOR
COMPATIBLE

LED DOME LIGHTS
White Frame

- AC:220-240V,50Hz
- PF: >0.7
- CRI: >80
- 120° Beam Angle
- On/0ff:
- Life span:25,000 Hours
- Body Type: PC

Model	SKU	Watts	Lumen	Size	Shape
VT-8618W-RD	7615 - 3000K WARM WHITE 7616 - 4000K DAY WHITE 7617 - 6500K WHITE	18W	1530	Ø225mm	Round
VT-8624W-RD	7618 - 3000K WARM WHITE 7619 - 4000K DAY WHITE 7620 - 6500K WHITE	24W	2040	Ø295mm	Round
VT-8630W-RD	7621 - 3000K WARM WHITE 7622 - 4000K DAY WHITE 7623 - 6500K WHITE	30W	2550	Ø420mm	Round
VT-8618W-SQ	7624 - 3000K WARM WHITE 7625 - 4000K DAY WHITE 7626 - 6500K WHITE	18W	1530	225×225mm	Square
VT-8624W-SQ	7627 - 3000K WARM WHITE 7628 - 4000K DAY WHITE 7629 - 6500K WHITE	24W	2040	295×295mm	Square
VT-8630W-SQ	7630 - 3000K WARM WHITE 7631 - 4000K DAY WHITE 7632 - 6500K WHITE	30W	2550	420×420mm	Square

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



IP44
RATING

SENSOR
COMPATIBLE

LED DOME LIGHTS
Black Frame

- AC:220-240V,50Hz
- PF: >0.7
- CRI: >80
- 120° Beam Angle
- On/0ff:
- Life span:25,000 Hours
- Body Type: PC

Model	SKU	Watts	Lumen	Size	Shape
VT-8618B-SQ	7642 - 3000K WARM WHITE 7643 - 4000K DAY WHITE 7644 - 6500K WHITE	18W	1530	225×225mm	Square
VT-8624B-SQ	7645 - 3000K WARM WHITE 7646 - 4000K DAY WHITE 7647 - 6500K WHITE	24W	2040	295×295mm	Square
VT-8630B-SQ	7648 - 3000K WARM WHITE 7649 - 4000K DAY WHITE 7650 - 6500K WHITE	30W	2550	420×420mm	Square
VT-8618B-RD	7633 - 3000K WARM WHITE 7634 - 4000K DAY WHITE 7635 - 6500K WHITE	18W	1530	Ø225mm	Round
VT-8624B-RD	7636 - 3000K WARM WHITE 7637 - 4000K DAY WHITE 7638 - 6500K WHITE	24W	2040	Ø295mm	Round
VT-8630B-RD	7639 - 3000K WARM WHITE 7640 - 4000K DAY WHITE 7641 - 6500K WHITE	30W	2550	Ø420mm	Round

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

IP44
RATING

LED DOME LIGHTS

White Frame with Sensor

Microwave Sensor

- AC:220-240V,50Hz
- PF: >0.7
- CRI: >80
- 120° Beam Angle
- On/0ff:
- Life span:25,000 Hours
- Body Type: PC

Model	SKU	Watts	Lumen	Size	Shape
VT-8618S-W-RD	7659 - 3000K WARM WHITE 7660 - 4000K DAY WHITE 7661 - 6500K WHITE	18W	1530	Ø225mm	Round
VT-8624S-W-RD	7662 - 3000K WARM WHITE 7663 - 4000K DAY WHITE 7664 - 6500K WHITE	24W	2040	Ø295mm	Round
VT-8630S-W-RD	7665 - 4000K DAY WHITE	30W	2550	Ø420mm	Round
VT-8618S-W-SQ	7666 - 4000K DAY WHITE	18W	1530	225×225mm	Square
VT-8624S-W-SQ	7667 - 4000K DAY WHITE	24W	2040	295×295mm	Square
VT-8630S-W-SQ	7668 - 4000K DAY WHITE	30W	2550	420×420mm	Square

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS



IP44
RATING

LED DOME LIGHTS
Black Frame with Sensor

Microwave Sensor

- AC:220-240V,50Hz
- PF: >0.7
- CRI: >80
- 120° Beam Angle
- On/0ff:
- Life span:25,000 Hours
- Body Type: PC

Model	SKU	Watts	Lumen	Size	Shape
VT-8618S-B-RD	7669 - 4000K DAY WHITE	18W	1530	Ø225mm	Round
VT-8624S-B-RD	7670 - 4000K DAY WHITE	24W	2040	Ø295mm	Round
VT-8630S-B-RD	7671 - 4000K DAY WHITE	30W	2550	Ø420mm	Round
VT-8618S-B-SQ	7672 - 4000K DAY WHITE	18W	1530	225×225mm	Square
VT-8624S-B-SQ	7673 - 4000K DAY WHITE	24W	2040	295×295mm	Square
VT-8630S-B-SQ	7674 - 4000K DAY WHITE	30W	2550	420×420mm	Square

DEKRA TÜV SÜD RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

3 IN 1 COLOR CHANGING

EASY TOGGLE SWITCH FOR COLOR CHANGING
3000K - 4000K - 6400K

LED DOME LIGHTS

Starry Cover

- AC:175-265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8412-S	7602 - 3IN1	12w	720	Ø255×55mm	5
VT-8412-S-N	217602 - 3IN1	12w	1200	260×55mm	5
VT-8418-S	7604 - 3IN1	18w	1080	Ø310×55mm	5
VT-8418-S-N	217604 - 3IN1	18w	1800	310×55mm	5
VT-8424-S	7606 - 3IN1	24w	1440	Ø350×55mm	5
VT-8424-S-N	217606 - 3IN1	24w	2600	Ø350×55mm	5
VT-8436-S	7608 - 3IN1	36w	2160	Ø480×65mm	5
VT-8436-S-N	217608 - 3IN1	36w	3900	500×80mm	5

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

3 IN 1 COLOR CHANGING

EASY TOGGLE SWITCH
FOR COLOR CHANGING
3000K - 4000K - 6400K

LED DOME LIGHTS
Milky Cover

- AC:175–265V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- On/Off: >15000
- Life span:20,000-hour
- Body Type: Plastic

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8412-M	7603 – 3IN1	12w	720	Ø255×55mm	5
VT-8412-M-N	217603 – 3IN1	12w	1200	260×55mm	5
VT-8418-M	7605 – 3IN1	18w	1080	Ø310×55mm	5
VT-8418-M-N	217605 – 3IN1	18w	1800	Ø310×55mm	5
VT-8424-M	7607 – 3IN1	24w	1440	Ø350×55mm	5
VT-8424-M-N	217607 – 3IN1	24w	2600	Ø350×55mm	5
VT-8436-M	7609 – 3IN1	36w	2160	Ø480×65mm	5
VT-8436-M-N	217609 – 3IN1	36w	3900	500×80mm	5

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS

Starry Cover with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8472	14951 - 3IN1	3000K- 36W 4000K- 72W 6400K- 36W	3000K | 2520 4000K | 5040 6400K | 2520	Ø670×75mm	5
VT-8472-N	2114951- 3IN1	3000K- 36W 4000K- 72W 6400K- 36W	7200	670×80mm	5

LED DOME LIGHTS

Diamond Cover with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8404	14931 - 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	3000K | 1400 4000K | 2800 6400K | 1400	Ø388.5×75mm	5
VT-8404-N	2114931 - 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	4000	Ø388.5×75mm	5
VT-8557	14921 - 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	Ø500×75mm	5
VT-8557-N	2114921- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	6000	Ø500×75mm	5

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8405	14941 - 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	3000K | 1400 4000K | 2800 6400K | 1400	Ø393×75mm	5
VT-8405-N	2114941- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	4000	393×80mm	5
VT-8556	14911 - 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	Ø493.9×75mm	5
VT-8556-N	2114911 - 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	6000	Ø493.9×75mm	5

LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8402	14761- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	3000K | 1400 4000K | 2800 6400K | 1400	410×75mm	10
VT-8402-N	2114761- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	4000	410×75mm	10
VT-8502	14751- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	510×75mm	6
VT-8502-N	2114751- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	6000	510×80mm	6

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8403	14601- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	3000K | 1400 4000K | 2800 6400K | 1400	395×75mm	5
VT-8403-N	2114601- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	4000	395×80mm	5
VT-8503	14611- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	498×80mm	5
VT-8503-N	2114611- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	6000	500×90mm	5



LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8401	14741- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	3000K | 1400 4000K | 2800 6400K | 1400	465×75mm	10
VT-8401-N	2114741- 3IN1	3000K- 20W 4000K- 40W 6400K- 20W	4000	465×75mm	10
VT-8555	14551- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	Ø565×75mm	5
VT-8555-N	2114551- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	6000	Ø565×75mm	5

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: PMMA+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8473	76011 - 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	Ø480×75mm	6

LED DOME LIGHTS

LED Dome Light with Remote Control

- AC:175-265V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >15000
- Life span:20,000-hour
- Body Type: Plastic+Metal

DIMMABLE WITH REMOTE

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8504	14621- 3IN1	3000K- 30W 4000K- 60W 6400K- 30W	3000K | 2100 4000K | 4200 6400K | 2100	500×85mm	6

DEKRA TÜV SÜD RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS

LED Oval Dome Lights Black

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

IP54 RATING

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8014-OV-B	1267 - 3000K WARM WHITE 1266 - 4000K DAY WHITE 1268 - 6400K WHITE	8w	560		10
VT-8016-B	5056 - 4500K DAY WHITE	12w	840		10

LED DOME LIGHTS

LED Oval Dome Lights White

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

IP54 RATING

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8014-OV-W	1264 - 3000K WARM WHITE 1263 - 4000K DAY WHITE 1265 - 6400K WHITE	8w	560		10

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED DOME LIGHTS

LED Round Dome Lights White

IP54 RATING

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8014-RD-W	4999 - 3000K WARM WHITE 1259 - 4000K DAY WHITE 4997 - 6400K WHITE	8w	560	Ø180×82mm	10
VT-8015-W	4998 - 3000K WARM WHITE 5050 - 4000K DAY WHITE	12w	840	Ø220×105mm	10

LED DOME LIGHTS

LED Round Dome Lights Black

IP54 RATING

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8014-RD-B	1261 - 3000K WARM WHITE 1262 - 6400K WHITE	8w	560	Ø180×82mm	10
VT-8015-B	1349 - 3000K WARM WHITE 5052 - 4000K DAY WHITE	12w	840	Ø220×105mm	10

LED DOME LIGHTS

LED Oval Dome Lights

IP54 RATING

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8010-W	1351 - 3000K WARM WHITE	12w	840	242×165×96mm	10

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED DOME LIGHTS

LED Oval Dome Lights

IP54 RATING

- AC:200-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC+PC

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8010-B	1350 - 3000K WARM WHITE 4973 - 4000K DAY WHITE 1269 - 6400K WHITE	12w	840	Ø242×96mm	10

LED DOME LIGHTS

LED Rectangle Dome Lights

IP54 RATING

- AC:200-240V,50/60Hz
- PF: >0.5
- CRI: >70
- 120° Beam Angle
- On/0ff: >10,000
- Life span:20,000-hour
- Body Type: PC

Model	SKU	Watts	Lumen	Size	Box Qty
VT-8038-B	1308 - 3000K WARM WHITE	8w Black	560	190×100×55mm	20
VT-8038-W	1311 - 3000K WARM WHITE	8w White	560	190×100×55mm	20

LED DOME LIGHTS

Dome Sensor

- AC:220-240V,50/60Hz
- Sensor Type: Microwave
- Rated Load: Max. 60W(E27)
- 360° Detection Range
- Time Delay: Min. 10sec±3sec,Max. 12min±1min
- Detection Distance:1-8m(radius) adjustable
- Body Type: PC



Model	SKU	Box Qty
VT-8002C	4966	5

LED WALL LIGHTS

Presenting our modern LED wall lights, the perfect replacement for traditional wall lamps. A classy combination of energy efficiency and design. Applied indoors or outdoors, style up your bedroom, hall or pathways with the soft light illuminated from these wall lamps.

Key Features

- Modern wall lights available in sleek and stylish designs.
- Adjustable beam angle.
- Available in black, grey & white colors
- Easy installation
- Perfect for halls, pathways, bedroom, kitchen & terrace

Application

Suitable for residential lighting, hotels, restaurants, resorts, residential lighting and similar environment

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Up-Down Wall Lights

- AC:220-240V,50Hz
- PF: >0.45
- CRI: >80
- 120° Beam Angle
- IP Rating:IP54
- Body Type: Aluminium

IP54 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-815-B	8684 - 4000K DAY WHITE	Black	10W	800	20
VT-815-B-N	218684 - 4000K DAY WHITE	Black	10w	1280	20
VT-815-W	8683 - 4000K DAY WHITE	White	10W	800	20
VT-815-W-N	218683 - 4000K DAY WHITE	White	10w	1280	20

LED Up-Down Wall Lights

- AC:220-240V,50Hz
- PF: >0.6
- CRI: >80
- Up150° / Down150° Beam Angle
- IP Rating:IP54
- Body Type: Aluminium

IP54 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-846-B	8615 - 3000K WARM WHITE 8616 - 4000K DAY WHITE	Black	6W	540	20
VT-846-B-N	218615 - 3000K WARM WHITE	Black	6w	630	20
VT-846-W	8613 - 3000K WARM WHITE 8614 - 4000K DAY WHITE	White	6W	540	20
VT-846-W-N	218613 - 3000K WARM WHITE 218614 - 4000K DAY WHITE	White	5w	630	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Up-Down Wall Lights

- AC:220-240V,50Hz
- PF: >0.6
- CRI: >80
- Up150° / Down150° Beam Angle
- IP Rating:IP54
- Body Type: Aluminium

IP54 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-848-B	8619 - 3000K WARM WHITE 8620 - 4000K DAY WHITE	Black	8W	800	20
VT-848-B-N	218619 - 3000K WARM WHITE 218620 - 4200K DAY WHITE	Black	8w	3000K-870 4200K-940	20
VT-848-W	8617 - 3000K WARM WHITE 8618 - 4000K DAY WHITE	White	8W	800	20
VT-848-W-N	218617 - 3000K WARM WHITE 218618 - 4000K DAY WHITE	White	8w	3000K-870 4000K-940	20

LED Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.4
- CRI: >80
- 41° Beam Angle
- IP Rating:IP65
- Body Type: Nylon

IP65 RATING

Model	SKU	Color	Watts	Lumen	Box Qty
VT-844-B	8561 - 6400K WHITE 8563 - 3000K WARM WHITE	Black	4W	150	10
VT-844-B-N	218561 - 3000K WARM WHITE 218563 - 6500K WHITE	Black	4w	400	10
VT-844-W	8562 - 3000K WARM WHITE 8560 - 6400K WHITE	White	4W	150	10
VT-844-W-N	218560 - 3000K WARM WHITE 218562 - 6500K WHITE	White	4w	400	10

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.6
- CRI: >80
- 128° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-831-CRD	8609 - 3000K WARM WHITE	Round	7W	400	20
VT-831-CRD-N	218609 - 3000K WARM WHITE	Round	7w	610	20
VT-831-CSQ	8610 - 3000K WARM WHITE	Square	7W	400	20
VT-831-CSQ-N	218610 - 3000K WARM WHITE	Square	7w	670	20

LED Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 128° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-827-RD	8537 - 3000K WARM WHITE 8538 - 4000K DAY WHITE	Round	12W	650	20
VT-827-RD-N	218537 - 3000K WARM WHITE 218538 - 4000K DAY WHITE	Round	12w	1155	20
VT-827-SQ	8539 - 3000K WARM WHITE 8540 - 4000K DAY WHITE	Square	12W	650	20
VT-827-SQ-N	218539 - 3000K WARM WHITE 218540 - 4000K DAY WHITE	Square	12w	1160	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.6
- CRI: >80
- 128° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-831-RD	8611 - 3000K WARM WHITE	Round	7W	550	20
VT-831-SQ	8612 - 3000K WARM WHITE	Square	7W	550	20
VT-831-SQ-N	218612 - 3000K WARM WHITE	Square	7W	610	20

LED Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 158° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-828-RD	8541 - 3000K WARM WHITE 8542 - 4000K DAY WHITE	Round	12W	900	20
VT-828-SQ	8543 - 3000K WARM WHITE 8544 - 4000K DAY WHITE	Square	12W	900	20
VT-828-SQ-N	218543 - 3000K WARM WHITE 218544 - 4000K DAY WHITE	Square	12w	1250	20

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Outdoor Bollard Lamp

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 180° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING

Model	SKU	Color	Watts	Lumen	Box Qty
VT-896-B	8682 - 4000K DAY WHITE	Black	7W	750	20
VT-896-B-N	218682 - 4000K DAY WHITE	Black	6w	810	20
VT-896-G	8681 - 4000K DAY WHITE	Grey	7W	750	20
VT-896-G-N	218681 - 4000K DAY WHITE	Grey	6w	810	20

LED Outdoor Bollard Lamp

- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 72° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-830-W	8316 - 3000K WARM WHITE 8317 - 4000K DAY WHITE 8318 - 6400K WHITE	White	10W	450	8
VT-830-G	8319 - 3000K WARM WHITE 8320 - 4000K DAY WHITE 8321 - 6400K WHITE	Grey	10W	450	8
VT-830-B	8322 - 3000K WARM WHITE 8323 - 4000K DAY WHITE 8324 - 6400K WHITE	Black	10W	450	8

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Outdoor Bollard Lamp

- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 72° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-820-W	8325 – 3000K WARM WHITE 8326 – 4000K DAY WHITE 8327 – 6400K WHITE	White	10W	450	4
VT-820-G	8328 – 3000K WARM WHITE 8329 – 4000K DAY WHITE 8330 – 6400K WHITE	Grey	10W	450	4
VT-820-B	8331 – 3000K WARM WHITE 8332 – 4000K DAY WHITE 8333 – 6400K WHITE	Black	10W	450	4

LED Wall Lights

- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 140° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-822-W	8334 – 3000K WARM WHITE 8335 – 4000K DAY WHITE 8336 – 6400K WHITE	White	12W	750	20
VT-822-W-N	218334 – 3000K WARM WHITE 218335 – 4000K DAY WHITE	White	12w	1350	20
VT-822-G	8337 – 3000K WARM WHITE 8338 – 4000K DAY WHITE 8339 – 6400K WHITE	Grey	12W	750	20
VT-822-G-N	218337 – 3000K WARM WHITE 218338 – 4200K DAY WHITE	Grey	12w	1250	20
VT-822-B	8340 – 3000K WARM WHITE 8341 – 4000K DAY WHITE 8342 – 6400K WHITE	Black	12W	750	20
VT-822-B-N	218341 – 4200K DAY WHITE	Black	12w	1350	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED 4 Sides Light Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 4*60° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium+Acrylic

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-704-W	8209 – 3000K WARM WHITE 8210 – 4000K DAY WHITE	White	4W	440	20
VT-704-B	8211 – 3000K WARM WHITE 8212 – 4000K DAY WHITE	Black	4W	440	20
VT-704-B-N	218211 – 3000K WARM WHITE	Black	4w	428	20

LED 4 Sides Light Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 4*60° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium+Acrylic

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-706-W	8213 – 3000K WARM WHITE 8214 – 4000K DAY WHITE	White	4W	440	20
VT-706-B	8215 – 3000K WARM WHITE 8216 – 4000K DAY WHITE	Black	4W	440	20
VT-706-B-N	218215 – 3000K WARM WHITE	Black	4w	428	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED 4 Sides Light Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.45
- CRI: >80
- 4*90° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-834-W	8551 – 3000K WARM WHITE 8552 – 4000K DAY WHITE	White	4W	440	20
VT-834-B	8553 – 3000K WARM WHITE 8554 – 4000K DAY WHITE	Black	4W	440	20
VT-834-B-N	218553 – 3000K WARM WHITE 218554 – 4000K DAY WHITE	Black	4w	428	20

LED Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-825-W	8280 – 3000K WARM WHITE 8281 – 4000K DAY WHITE	White	5W	550	20
VT-825-W-N	218280 – 3000K WARM WHITE	White	5w	568	20
VT-825-B	8282 – 3000K WARM WHITE 8283 – 4000K DAY WHITE	Black	5W	550	20
VT-825-B-N	218282 – 3000K WARM WHITE	Black	5w	568	20
VT-825-G	8284 – 3000K WARM WHITE 8285 – 4000K DAY WHITE	Grey	5W	550	20
VT-825-G-N	218284 – 3000K WARM WHITE 218285 – 4000K DAY WHITE	Grey	5w	3000K – 568 4000K – 645	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Up-Down Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- Up15°-Down120° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-826-W	8295 – 3000K WARM WHITE 8296 – 4000K DAY WHITE	White	6W	660	20
VT-826-W-N	218295 – 3000K WARM WHITE 218296 – 4000K DAY WHITE	White	6w	3000K – 450 4000K – 476	20
VT-826-B	8297 – 3000K WARM WHITE 8298 – 4000K DAY WHITE	Black	6W	660	20
VT-826-B-N	218297 – 3000K WARM WHITE 218298 – 4000K DAY WHITE	Black	6w	3000K – 450 4000K – 476	20
VT-826-G	8299 – 3000K WARM WHITE 8300 – 4000K DAY WHITE	Grey	6W	660	20
VT-826-G-N	218299 – 3000K WARM WHITE 218300 – 4000K DAY WHITE	Grey	6w	3000K – 450 4000K – 476	20

LED Single Head Rotatable Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 350° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-816-W	8286 – 3000K WARM WHITE 8287 – 4000K DAY WHITE	White	6W	660	20
VT-816-W-N	218286 – 3000K WARM WHITE 218287 – 4000K DAY WHITE	White	6w	3000K – 722 4000K – 800	20
VT-816-B	8288 – 3000K WARM WHITE 8289 – 4000K DAY WHITE	Black	6W	660	20
VT-816-B-N	218288 – 3000K WARM WHITE 218289 – 4000K DAY WHITE	Black	6w	3000K – 722 4000K – 800	20
VT-816-G	8290 – 3000K WARM WHITE 8291 – 4000K DAY WHITE	Grey	6W	660	20
VT-816-G-N	218291 – 4000K DAY WHITE	Grey	6w	800	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Double Head Rotatable Wall Lights

- AC:110-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 350° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-814-W	8292 - 3000K WARM WHITE	White	12W	1320	20
VT-814-W-N	218292 - 3000K WARM WHITE	White	12w	1444	20
VT-814-B	8293 - 3000K WARM WHITE	Black	12W	1320	20
VT-814-G	8294 - 3000K WARM WHITE	Grey	12W	1320	20

LED Up-Down Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.45
- CRI: >80
- Adjustable 5°-120° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-759-W	7079 - 3000K WARM WHITE 7088 - 4000K DAY WHITE	White	6W	660	20
VT-759-W-N	217079 - 3000K WARM WHITE 217088 - 4000K DAY WHITE	White	5w	700	20
VT-759-B	7078 - 3000K WARM WHITE 7087 - 4000K DAY WHITE	Black	6W	660	20
VT-759-B-N	217078 - 3000K WARM WHITE 217087 - 4000K DAY WHITE	Black	5w	700	20
VT-759-G	7080 - 3000K WARM WHITE 7089 - 4000K DAY WHITE	Grey	6W	660	20
VT-759-G-N	217080 - 3000K WARM WHITE 217089 - 4000K DAY WHITE	Grey	5w	700	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Up-Down Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.45
- CRI: >80
- Adjustable 5°-120° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-759-12-W	8527 - 3000K WARM WHITE 8528 - 4000K DAY WHITE	White	12W	1100	20
VT-759-12-W-N	218527 - 3000K WARM WHITE 218528 - 4000K DAY WHITE	White	11w	1360	20
VT-759-12-B	8529 - 3000K WARM WHITE 8530 - 4000K DAY WHITE	Black	12W	1100	20
VT-759-12-B-N	218529 - 3000K WARM WHITE 218530 - 4000K DAY WHITE	Black	11w	1360	20
VT-759-12-G	8531 - 3000K WARM WHITE 8532 - 4000K DAY WHITE	Grey	12W	1100	20
VT-759-12-G-N	218531 - 3000K WARM WHITE 218532 - 4000K DAY WHITE	Grey	11w	1360	20

LED Up-Down Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.45
- CRI: >80
- Adjustable 5°-120° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-756-W	7082 - 3000K WARM WHITE 7091 - 4000K DAY WHITE	White	6W	660	20
VT-756-W-N	217082 - 3000K WARM WHITE 217091 - 4000K DAY WHITE	White	5w	700	20
VT-756-B	7081 - 3000K WARM WHITE 7090 - 4000K DAY WHITE	Black	6W	660	20
VT-756-B-N	217081 - 3000K WARM WHITE 217090 - 4000K DAY WHITE	Black	5w	700	20
VT-756-G	7083 - 3000K WARM WHITE 7092 - 4000K DAY WHITE	Grey	6W	660	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Up-Down Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- Up-Down 90° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-836-W	8301 - 3000K WARM WHITE 8302 - 4000K DAY WHITE	White	6W	660	20
VT-836-W-N	218301 - 3000K WARM WHITE 218302 - 4000K DAY WHITE	White	6w	3000K - 450 4000K - 476	20
VT-836-B	8303 - 3000K WARM WHITE 8304 - 4000K DAY WHITE	Black	6W	660	20
VT-836-G	8305 - 3000K WARM WHITE 8306 - 4000K DAY WHITE	Grey	6W	660	20
VT-836-G-N	218305 - 3000K WARM WHITE 218306 - 4000K DAY WHITE	Grey	6w	3000K - 450 4000K - 476	20

LED Ceiling-Blade Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 360° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-707-W	8217 - 3000K WARM WHITE 8218 - 4000K DAY WHITE	White	7W	770	20
VT-707-B	8219 - 3000K WARM WHITE 8220 - 4000K DAY WHITE	Black	7W	770	20

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

LED Ceiling & Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.55
- CRI: >80
- 360° Beam Angle
- IP Rating:IP65
- Body Type: Aluminium

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-741	7524 - 3000K WARM WHITE 7525 - 4000K DAY WHITE	White	6W	660	20
VT-741-N	217524 - 3000K WARM WHITE	White	5w	710	20
VT-743	7526 - 3000K WARM WHITE 7527 - 4000K DAY WHITE	White	9W	990	20
VT-743-N	217527 - 4000K DAY WHITE	White	8w	1280	20

LED Outdoor Soft Lights

- AC:100-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 90° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-8056	8239 - 3000K WARM WHITE 8240 - 4000K DAY WHITE 8241 - 6400K WHITE	Grey	9W	400	20
VT-8056-N	218239 - 3000K WARM WHITE 218240 - 4200K DAY WHITE 218241 - 6500K WHITE	Grey	9w	850	20
VT-8057	8242 - 3000K WARM WHITE 8243 - 4000K DAY WHITE 8244 - 6400K WHITE	Grey	12W	600	20
VT-8057-N	218242 - 3000K WARM WHITE 218243 - 4200K DAY WHITE 218244 - 6500K WHITE	Grey	12w	1150	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Outdoor Soft Lights

- AC:100-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 130° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-8058	8245 – 3000K WARM WHITE 8246 – 4000K DAY WHITE 8247 – 6400K WHITE	Grey	12W	500	20
VT-8058-N	218245 – 3000K WARM WHITE 218246 – 4200K DAY WHITE 218247 – 6500K WHITE	Grey	12w	1160	20

LED Outdoor Soft Lights

- AC:100-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 110° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-8054	8233 – 3000K WARM WHITE 8234 – 4000K DAY WHITE 8235 – 6400K WHITE	Grey	12W	600	20
VT-8054-N	218233 – 3000K WARM WHITE 218234 – 4200K DAY WHITE 218235 – 6500K WHITE	Grey	12w	1150	20
VT-8055	8236 – 3000K WARM WHITE 8237 – 4000K DAY WHITE 8238 – 6400K WHITE	Grey	20W	1000	20
VT-8055-N	218236 – 3000K WARM WHITE 218237 – 4200K DAY WHITE 218238 – 6500K WHITE	Grey	20w	2050	20

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

LED Ceiling & Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 150° Beam Angle
- IP Rating:IP20
- Body Type: Aluminium





Model	SKU	Color	Watts	Lumen	Box Qty
VT-705	8208 - 3000K WARM WHITE 8232 - 4000K DAY WHITE	White	5W	550	20
VT-705-N	218232 - 4000K DAY WHITE	White	5W	645	20

LED Rotatable Wall Light

- AC:110-240V,50/60Hz
- PF: >0.45
- CRI: >80
- 10-360° Beam Angle
- IP Rating:IP20
- Body Type: Aluminium





Model	SKU	Color	Watts	Lumen	Box Qty
VT-757	7086 - 3000K WARM WHITE 7093 - 4000K DAY WHITE	White	5W	560	20
VT-757-N	217093 - 4000K DAY WHITE	White	5W	645	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Up-Down Wall Lights

- AC:110-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Iron





Model	SKU	Color	Watts	Lumen	Box Qty
VT-803-W	8344 - 3000K WARM WHITE 8345 - 4000K DAY WHITE	White	3W	300	20
VT-803-B	8346 - 3000K WARM WHITE 8347 - 4000K DAY WHITE	Black	3W	300	20

LED Round Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 360° Beam Angle
- IP Rating:IP20
- Body Type: Aluminium+Acrylic





Model	SKU	Color	Watts	Lumen	Box Qty
VT-710-W	8225 - 3000K WARM WHITE 8226 - 4000K DAY WHITE	White	9W	990	20
VT-710-B	8227 - 3000K WARM WHITE 8228 - 4000K DAY WHITE	Black	9W	990	20

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 360° Beam Angle
- IP Rating:IP20
- Body Type: Aluminium





Model	SKU	Color	Watts	Lumen	Box Qty
VT-709-W	8221 - 3000K WARM WHITE 8222 - 4000K DAY WHITE	White	9W	990	10
VT-709-B	8223 - 3000K WARM WHITE 8224 - 4000K DAY WHITE	Black	9W	990	10

LED Wall Lights

- AC:110-240V,50/60Hz
- PF: >0.45
- CRI: >80
- 360° Beam Angle
- IP Rating:IP20
- Body Type: Aluminium





Model	SKU	Color	Watts	Lumen	Box Qty
VT-811-W	8307 - 3000K WARM WHITE 8308 - 4000K DAY WHITE	White	10W	1100	20
VT-811-B	8309 - 3000K WARM WHITE 8310 - 4000K DAY WHITE	Black	10W	1100	20
VT-811-B-N	218309 - 3000K WARM WHITE	Black	10w	1070	20

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Wall Lights

- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 360° Beam Angle
- IP Rating:IP20
- Body Type: Aluminium+Acrylic





Model	SKU	Color	Watts	Lumen	Box Qty
VT-712-W	8202 - 3000K WARM WHITE 8203 - 4000K DAY WHITE	White	12W	1100	20
VT-712-W-N	218202 - 3000K WARM WHITE	White	11w	1368	20
VT-712-B	8204 - 3000K WARM WHITE 8205 - 4000K DAY WHITE	Black	12W	1100	20
VT-712-B-N	218204 - 3000K WARM WHITE	Black	11w	1368	20
VT-712-G	8206 - 3000K WARM WHITE 8207 - 4000K DAY WHITE	Grey	12W	1100	20

Adjustable LED Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- Adjustable 5°-90° Beam Angle
- IP Rating:IP44
- Body Type: Aluminium





Model	SKU	Color	Watts	Lumen	Box Qty
VT-819-W	8533 - 3000K WARM WHITE 8534 - 4000K DAY WHITE	White	18W	1800	10
VT-819-W-N	218533 - 3000K WARM WHITE 218534 - 4000K DAY WHITE	White	16w	2150	10

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 150° Beam Angle
- IP Rating:IP20
- Body Type: Aluminium



Model	SKU	Color	Watts	Lumen	Box Qty
VT-821-W	8535 - 3000K WARM WHITE 8536 - 4000K DAY WHITE	White	20W	2000	20
VT-821-W-N	218535 - 3000K WARM WHITE 218536 - 4000K DAY WHITE	White	17w	2470	20

LED Wall Light With Switch

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 100° Beam Angle
- IP Rating:IP20
- Body Type: Plastic+Metal

With Switch





Model	SKU	Color	Watts	Lumen	Box Qty
VT-805-N-W	8675 - 3000K WARM WHITE 8677 - 4000K DAY WHITE	White	4.5W	360	24
VT-805-N-W-N	218675 - 3000K WARM WHITE 218677 - 4000K DAY WHITE	White	4.5W	3000K-410 4000K-420	12
VT-805-N-B	8676 - 3000K WARM WHITE 8678 - 4000K DAY WHITE	Black	4.5W	360	24
VT-805-N-B-N	218676 - 3000K WARM WHITE 218678 - 4000K DAY WHITE	Black	4.5W	3000K-410 4000K-420	12

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

LED Single Head Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 100° Beam Angle
- IP Rating:IP20
- Body Type: Plastic+Metal



Model	SKU	Color	Watts	Lumen	Box Qty
VT-805-W	8262 – 3000K WARM WHITE 8264 – 4000K DAY WHITE	White	4.5W	360	12
VT-805-W-N	218262 – 3000K WARM WHITE 218264 – 4000K DAY WHITE	White	4.5W	3000K-410 4000K-420	12
VT-805-B	8263 – 3000K WARM WHITE 8265 – 4000K DAY WHITE	Black	4.5W	360	12
VT-805-B-N	218263 – 3000K WARM WHITE 218265 – 4000K DAY WHITE	Black	4.5W	3000K-410 4000K-420	12

LED Double Head Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 100° Beam Angle
- IP Rating:IP20
- Body Type: Plastic+Metal



Model	SKU	Color	Watts	Lumen	Box Qty
VT-810-W	8266 – 3000K WARM WHITE 8268 – 4000K DAY WHITE	White	9W	720	12
VT-810-W-N	218266 – 3000K WARM WHITE	White	9W	820	12
VT-810-B	8267 – 3000K WARM WHITE 8269 – 4000K DAY WHITE	Black	9W	720	12
VT-810-B-N	218269 – 4000K DAY WHITE	Black	9W	840	12

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Tripple Head Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 100° Beam Angle
- IP Rating:IP20
- Body Type: Plastic+Metal



Model	SKU	Color	Watts	Lumen	Box Qty
VT-813-W	8270 – 3000K WARM WHITE 8272 – 4000K DAY WHITE	White	13.5W	1080	12
VT-813-W-N	218270 – 3000K WARM WHITE 218272 – 4000K DAY WHITE	White	13.5W	3000K-1230 4000K-1260	12
VT-813-B	8271 – 3000K WARM WHITE 8273 – 4000K DAY WHITE	Black	13.5W	1080	12
VT-813-B-N	218271 – 3000K WARM WHITE 218273 – 4000K DAY WHITE	Black	13.5W	3000K-1230 4000K-1260	12

LED Single Head Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 100° Beam Angle
- IP Rating:IP20
- Body Type: Plastic+Metal



Model	SKU	Color	Watts	Lumen	Box Qty
VT-806-W	8250 – 3000K WARM WHITE 8252 – 4000K DAY WHITE	White	6W	480	24
VT-806-W-N	218250 – 3000K WARM WHITE 218252 – 4000K DAY WHITE	White	5W	3000K-540 4000K-580	24
VT-806-B	8251 – 3000K WARM WHITE 8253 – 4000K DAY WHITE	Black	6W	480	24
VT-806-B-N	218251 – 3000K WARM WHITE 218253 – 4000K DAY WHITE	Black	5W	3000K-540 4000K-580	24

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Double Head Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 100° Beam Angle
- IP Rating:IP20
- Body Type: Plastic+Metal



Model	SKU	Color	Watts	Lumen	Box Qty
VT-812-W	8254 – 3000K WARM WHITE 8256 – 4000K DAY WHITE	White	12W	960	12
VT-812-W-N	218254 – 3000K WARM WHITE 218256 – 4000K DAY WHITE	White	10W	3000K-1080 4000K-1160	12
VT-812-B	8255 – 3000K WARM WHITE 8257 – 4000K DAY WHITE	Black	12W	960	12
VT-812-B-N	218255 – 3000K WARM WHITE 218257 – 4000K DAY WHITE	Black	10W	3000K-1080 4000K-1160	12

LED Tripple Head Wall Lights

- AC:220-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 100° Beam Angle
- IP Rating:IP20
- Body Type: Plastic+Metal





Model	SKU	Color	Watts	Lumen	Box Qty
VT-818-W	8258 – 3000K WARM WHITE 8260 – 4000K DAY WHITE	White	18W	1440	12
VT-818-W-N	218258 – 3000K WARM WHITE 218260 – 4000K DAY WHITE	White	15W	3000K-1620 4000K-1740	12
VT-818-B	8259 – 3000K WARM WHITE 8261 – 4000K DAY WHITE	Black	18W	1440	12
VT-818-B-N	218259 – 3000K WARM WHITE 218261 – 4000K DAY WHITE	Black	15W	3000K-1620 4000K-1740	12

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

LED Step Light With Sensor

- AC:100-240V, 50/60Hz
- PF: >0.5
- CRI: >80
- 45° Beam Angle
- IP Rating:IP20
- Body Type: Die cast Aluminium



Model	SKU	Color	Watts	Lumen	Box Qty
VT-8035	5570 - 4000K DAY WHITE	White	3W	100	100

LED Step Light

- AC:85-265V,50/60Hz
- PF: >0.5
- CRI: >80
- 83° Beam Angle
- IP Rating:IP20
- Body Type: Die Cast Aluminium



Model	SKU	Color	Watts	Lumen	Box Qty
VT-1143	1284 - 4000K DAY WHITE	White	3W	100	100
VT-1143-N	211284 - 4000K DAY WHITE	White	3W	110	100

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

LED Step Lights

- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 15° Beam Angle
- IP Rating:IP20
- Body Type: Aluminium



Model	SKU	Color	Watts	Lumen	Box Qty
VT-1109	1209 - 3000K WARM WHITE 1210 - 4200K DAY WHITE	White	3W	120	100
VT-1109-N	211209 - 3000K WARM WHITE 211210 - 4000K DAY WHITE	White	3w	270	100
VT-1109RD	1207 - 3000K WARM WHITE 1208 - 4200K DAY WHITE	White	3W	120	100
VT-1109RD-N	211207 - 3000K WARM WHITE 211208 - 4000K DAY WHITE	White	3w	270	100

LED Step Lights

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >70
- 120° Beam Angle
- IP Rating:IP44
- Body Type: Aluminium

Model	SKU	Color	Watts	Lumen	Box Qty
VT-856-B	8348 - 3000K WARM WHITE 8349 - 4000K DAY WHITE	Black	6W	240	50
VT-856-G	8350 - 3000K WARM WHITE 8351 - 4000K DAY WHITE	Grey	6W	240	50
VT-856-W	8352 - 3000K WARM WHITE 8353 - 4000K DAY WHITE	White	6W	240	50

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Step Lights

- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 55° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-1162-W	1327 - 3000K WARM WHITE 1326 - 4000K DAY WHITE	White	3W	110	50
VT-1162-W-N	211326 - 4000K DAY WHITE	White	3w	110	50
VT-1162-B	1329 - 3000K WARM WHITE 1328 - 4000K DAY WHITE	Black	3W	110	50
VT-1162-B-N	211329 - 3000K WARM WHITE 211328 - 4000K DAY WHITE	Black	3w	110	50
VT-1162-G	1331 - 3000K WARM WHITE 1330 - 4000K DAY WHITE	Grey	3W	110	50
VT-1162-G-N	211331 - 3000K WARM WHITE 211330 - 4000K DAY WHITE	Grey	3w	110	50

LED Step Lights

- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 55° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING





Model	SKU	Color	Watts	Lumen	Box Qty
VT-1142-W	1315 - 3000K WARM WHITE 1314 - 4000K DAY WHITE	White	2W	60	50
VT-1142-W-N	211315 - 3000K WARM WHITE 211314 - 4000K DAY WHITE	White	3W	80	50
VT-1142-B	1317 - 3000K WARM WHITE 1316 - 4000K DAY WHITE	Black	2W	60	50
VT-1142-B-N	211317 - 3000K WARM WHITE 211316 - 4000K DAY WHITE	Black	2w	80	50
VT-1142-G	1319 - 3000K WARM WHITE 1318 - 4000K DAY WHITE	Grey	2W	60	50
VT-1142-G-N	211319 - 3000K WARM WHITE	Grey	2w	80	50

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

LED Step Lights

- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 55° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-1152-W	1321 - 3000K WARM WHITE 1320 - 4000K DAY WHITE	White	2W	60	50
VT-1152-B	1323 - 3000K WARM WHITE 1322 - 4000K DAY WHITE	Black	2W	60	50
VT-1152-B-N	211323 - 3000K WARM WHITE 211322 - 4000K DAY WHITE	Black	2w	70	50
VT-1152-G	1325 - 3000K WARM WHITE 1324 - 4000K DAY WHITE	Grey	2W	60	50

LED Step Lights

- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 90° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING

Model	SKU	Color	Watts	Lumen	Box Qty
VT-1172-B	1398 - 3000K WARM WHITE 1399 - 4000K DAY WHITE	Black	3W	210	20
VT-1172-G	1400 - 3000K WARM WHITE 1401 - 4000K DAY WHITE	Grey	3W	210	20
VT-1172-W	1402 - 3000K WARM WHITE 1403 - 4000K DAY WHITE	White	3W	210	20
VT-1172-W-N	211402 - 3000K WARM WHITE 211403 - 4000K DAY WHITE	White	3W	70	20

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

LED Step Lights

- AC:100-240V,50/60Hz
- PF: >0.5
- CRI: >80
- 90° Beam Angle
- IP Rating:IP65
- Body Type: PC

IP65 RATING



Model	SKU	Color	Watts	Lumen	Box Qty
VT-1182-B	1404 - 3000K WARM WHITE 1405 - 4000K DAY WHITE	Black	3W	210	20
VT-1182-G	1406 - 3000K WARM WHITE 1407 - 4000K DAY WHITE	Grey	3W	210	20
VT-1182-W	1408 - 3000K WARM WHITE 1409 - 4000K DAY WHITE	White	3W	210	20



LED FLOOR & TABLE LAMPS

Most cozy & favorite corners always deserve comfortable lighting conditions. To cater to this need, we bring you an exclusive range of LED table lamps. Elegantly designed with a touch of class, these lamps deliver sufficient and smooth lighting, with unique and suitable functions for both task and ambient lighting.

Key Features

- energy-efficient lighting
- Easily adjustable for your convenience
- Multiple functions like dimming, color-changing, and more
- With USB charging functionality
- Sleek and modern design

Application

Table lamps can be used in any space, though they are most often found in bedrooms, living rooms at home next to sofas, chairs or beds. Also a good accessory to be a part of the office decor.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING



Floor Lamp-Touch Dimming

- AC:100-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 110°/90° Beam Angle
- Body Type: Aluminium Alloy+PC



UP & DOWN LIGHTS

TOUCH DIMMING

Model	SKU	Watts	Lumen	Size	Unit Color	Box Qty
VT-8400D-S	8521 4000K DAY WHITE	80W	UP:4200/Down:3800	310×52×1950mm	White	1 Pc
VT-8400D-W	8522 4000K DAY WHITE	80W	UP:4200/Down:3800	310×52×1950mm	Silver	1 Pc

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Floor Lamp-Knob Dimming-Round corner



- AC:100-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 110°/90° Beam Angle
- Body Type: Aluminium Alloy+PC

UP & DOWN LIGHTS

KNOB DIMMING

Model	SKU	Watts	Lumen	Size	Unit Color	Box Qty
VT-8500D-S	8523 4000K DAY WHITE	80W	UP:5200/Down:3600	280×35×1950mm	White	1 Pc
VT-8500D-W	8524 4000K DAY WHITE	80W	UP:5200/Down:3600	280×35×1950mm	Silver	1 Pc

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

Floor Lamp-Knob Dimming-Square corner

- AC:100-240V,50/60Hz
- PF: >0.9
- CRI: >80
- 110°/90° Beam Angle
- Body Type: Aluminium Alloy+PC



UP & DOWN LIGHTS

KNOB DIMMING

Model	SKU	Watts	Lumen	Size	Unit Color	Box Qty
VT-8600D-S	8525 4000K DAY WHITE	80W	UP:5200/Down:3600	280×35×1950mm	White	1 Pc
VT-8600D-W	8526 4000K DAY WHITE	80W	UP:5200/Down:3600	280×35×1950mm	Silver	1 Pc

V-TAC®
INNOVATIVE LED LIGHTING

essentials

WIRELESS CHARGING | ANDROID & IPHONE | BRIGHTNESS ADJUSTABLE | ENERGY CONSERVATION | EYE PROTECTION | TIMER POWER OFF | USB OUTPUT | LIGHTING ADJUSTMENT | 3.0A 18W Fast Charger Included

LED Table Lamp With Wireless Charger

Model	SKU	Watts	Lumen	Size	Unit Color	Box Qty
VT-7705-B	8604 - 3IN1	5W	800	142×124×476mm	Black	10
VT-7705-B-N	218604 - 3IN1	9W	405	142×124×476mm	Black	10
VT-7705-W	8605 - 3IN1	5W	800	142×124×476mm	White	10
VT-7705-W-N	218605 - 3IN1	9W	405	142×124×476mm	White	10

- Rating input 5V/3A
- 3 Levels of Brightness Dimming
- Lamp Power 5V, 0.8A(4W)
- Wireless Charging 5V, 1A(5W)
- 2s to reach full brightness
- Touch Dimming
- Fast charger included 3.0A 18W

WIRELESS CHARGING | ANDROID & IPHONE | BRIGHTNESS ADJUSTABLE | ENERGY CONSERVATION | EYE PROTECTION | TIMER POWER OFF | USB OUTPUT | LIGHTING ADJUSTMENT | 3.0A 18W Fast Charger Included

LED Table Lamp With Wireless Charger

Model	SKU	Watts	Lumen	Size	Unit Color	Box Qty
VT-7505-B	8602 - 3IN1	5W	800	440×120×40mm	Black	10
VT-7505-B-N	218602 - 3IN1	12.5W	640	440×120×40mm	Black	10
VT-7505-W	8603 - 3IN1	5W	800	440×120×40mm	White	10
VT-7505-W-N	218603 - 3IN1	12.5W	640	440×120×40mm	White	10

- Rating input 5V/3A
- 3 Levels of Brightness Dimming
- Lamp Power 5V, 1A(5W)
- Wireless Charging 5V, 1A(5W)
- 2s to reach full brightness
- Fast charger included 3.0A 18W

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

WIRELESS CHARGING | ANDROID & IPHONE | BRIGHTNESS ADJUSTABLE | ENERGY CONSERVATION | EYE PROTECTION | TIMER POWER OFF | USB OUTPUT | LIGHTING ADJUSTMENT | 3.0A 18W Fast Charger Included

LED Table Lamp With Wireless Charger

Model	SKU	Watts	Lumen	Size	Unit Color	Box Qty
VT-7405-B	8600 - 3IN1	5W	800	440×120×40mm	Black	10
VT-7405-B-N	218600 - 3IN1	12.5W	630	440×120×40mm	Black	10
VT-7405-W	8601 - 3IN1	5W	800	440×120×40mm	White	10
VT-7405-W-N	218601 - 3IN1	12.5W	630	440×120×40mm	White	10

- Rating input 5V/3A
- 4 Levels of Brightness Dimming
- Lamp Power 5V, 1A(5W)
- Wireless Charging 5V, 1A(5W)
- 2s to reach full brightness
- Fast charger included 3.0A 18W

LED Table Lamp With Eu Plug Cord+switch

Model	SKU	Watts	Lumen	Size	Unit Color	Box Qty
VT-7312-B	40311 - 3000K WARM WHITE	17W	1300	210×350mm	Black	20
VT-7312-W	40321 - 3000K WARM WHITE	17W	1300	210×350mm	White	20

DEKRA | TÜV | www.tuv.com ID 1111227954 | RoHS | CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Table Mirror Lights

- DC:5V
- CRI: >80
- Body Type: Plastic

Magnifying AA batteries Cordless

Model	SKU	Watts	Lumen	Box Qty
VT-7572	6629	3w	30	20



Wall Mirror Lights

- DC:5V
- CRI: >80
- Body Type: Plastic

Magnifying AA batteries Cordless

Model	SKU	Watts	Lumen	Box Qty
VT-7571	6628	3w	30	20

Suction Mirror Lights

- DC:4.5V
- CRI: >80
- Body Type: Plastic



Magnifying AA batteries Cordless

Model	SKU	Watts	Lumen	Box Qty
VT-7573	6630	3.2w	30	36

Clip Lamp

- AC:220-240V, 50Hz
- CRI: >80
- `Body Type: ABS+Metal



Model	SKU	Watts	Lumen	Box Qty
VT-7407	8672 - 3000K WARM WHITE	7W	400	8

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

Desk Lamp

- AC:220-240V, 50Hz
- CRI: >80
- Body Type: ABS+Metal

ON/OFF SWITCH · NO FLICKERING · HEIGHT ADJUSTABLE · EYE PROTECTION · ADAPTER INCLUDED · WARM WHITE

Model	SKU	Watts	Lumen	Box Qty
VT-7403	8671 - 3000K WARM WHITE	3.6W	260	8

Mirror Lamp

- AC:220-240V, 50Hz
- CRI: >80
- Body Type: ABS+Glass

ON/OFF SWITCH · NO FLICKERING · HEIGHT ADJUSTABLE · EYE PROTECTION · ADAPTER INCLUDED · RECHARGEABLE

Model	SKU	Watts	Lumen	Box Qty
VT-7565	8931 - 6500K WHITE	5W	80	

Mirror Lamp

- AC:220-240V, 50Hz
- CRI: >80
- Body Type: ABS+Glass

RECHARGEABLE

ON/OFF SWITCH · NO FLICKERING · HEIGHT ADJUSTABLE · EYE PROTECTION · ADAPTER INCLUDED · WARM WHITE

Model	SKU	Watts	Lumen	Box Qty
VT-7905	8670 - 3000K WARM WHITE	5W	200	10

Table Lamps-Slim

- DC:12V,1A
- CRI: >80
- 120° Beam Angle
- Body Type: PC-Rubber Finish

- Flexible LED Table Lamp bends 0-180 degress on both sides.
- Touch power switch and dimmer
- Color temperature Switch

TOUCH DIMMING · RECHARGEABLE · DIMMABLE

Model	SKU	Watts	Lumen	Box Qty
VT-1037	8520 3I N 1	6.5W	110	10

DEKRA · TÜV · TÜV Rheinland CERTIFIED · GS · www.tuv.com ID 1111227954 · RoHS COMPLIANT · CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Table Lamp With Wireless Charger and Touch Button

wireless CHARGING

TOUCH CONTROL

- AC:200-240V
- CRI: >80
- 180° Beam Angle
- Body Type: Aluminium
- Unit Color:White

Model	SKU	Watts	Lumen
VT-7522-W	7651 - 3000K WARM WHITE	2W	200

Table Lamp With Wireless Charger and Touch Button

wireless CHARGING

TOUCH CONTROL

- AC:200-240V
- CRI: >80
- 180° Beam Angle
- Body Type: Aluminium
- Unit Color:Black

Model	SKU	Watts	Lumen
VT-7522-B	7652 - 3000K WARM WHITE	2W	200

Table Lamp With Wireless Charger and Touch Button

wireless CHARGING

TOUCH CONTROL

- AC:200-240V
- CRI: >80
- 180° Beam Angle
- Body Type: Aluminium
- Unit Color:Grey

Model	SKU	Watts	Lumen
VT-7522-G	7653 - 3000K WARM WHITE	2W	200

Table Lamp With Wireless Charger and Touch Button

wireless CHARGING

TOUCH CONTROL

- AC:200-240V
- CRI: >80
- 180° Beam Angle
- Body Type: Aluminium
- Unit Color:Corten

Model	SKU	Watts	Lumen
VT-7522-C	7654 - 3000K WARM WHITE	2W	200

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Rechargeable Desk Lamps

- 180° Beam Angle
- Body Type: Iron
- Unit Color:Grey

RECHARGEABLE

TOUCH DIMMING

Model	SKU	Watts	Lumen	Box Qty
VT-7703-G	2881 – 3000K WARM WHITE 2882 – 4000K DAY WHITE	3W	70	12

Rechargeable Desk Lamps

- 180° Beam Angle
- Body Type: Iron
- Unit Color:Gold

RECHARGEABLE

TOUCH DIMMING

Model	SKU	Watts	Lumen	Box Qty
VT-7703-GD	2883 – 3000K WARM WHITE 2884 – 4000K DAY WHITE	3W	80	12

Rechargeable Desk Lamps

- 180° Beam Angle
- Body Type: Iron
- Unit Color:White

RECHARGEABLE

TOUCH DIMMING

Model	SKU	Watts	Lumen	Box Qty
VT-7703-W	2885 – 3000K WARM WHITE 2886 – 4000K DAY WHITE	3W	70	12

Rechargeable Desk Lamps

- 180° Beam Angle
- Body Type: Iron
- Unit Color:Black

RECHARGEABLE

TOUCH DIMMING

Model	SKU	Watts	Lumen	Box Qty
VT-7703-B	2887 – 3000K WARM WHITE 2888 – 4000K DAY WHITE	3W	50	12

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Table Lamps-Wireless Charging

- AC:100-240V,50/60Hz
- CRI: >80
- 120° Beam Angle
- Body Type: ABS+Aluminium
- Wireless Charging.
- 5 Levels of Brightness Dimming
- Watts as per led 0.2W.
- Rating Input DC:12V/1.5A
- 2s to reach full brightness
- 270 Degree Rotatable Head

DIMMABLE

Model	SKU	Watts	Lumen	Box Qty
VT-1027	8519 - 3 IN 1	16W	1000	12

3IN1 Rechargeable Table Lamp White+Silver

3 STEP DIMMING
3 CCT MODES
RECHARGEABLE

- DC:5V,1A
- CRI: >80
- 120° Beam Angle
- Body Type: ABS+PC+Aluminium
- Unit Color:White+Silver

Model	SKU	Watts	Lumen	Box Qty
VT-1014-S	7098 - 3 IN 1	4W	120	25

3IN1 Rechargeable Table Lamp White+Gold

3 STEP DIMMING
3 CCT MODES
RECHARGEABLE

- DC:5V,1A
- CRI: >80
- 120° Beam Angle
- Body Type: ABS+PC+Aluminium
- Unit Color:White+Gold

Model	SKU	Watts	Lumen	Box Qty
VT-1014-G	7099 - 3 IN 1	4W	120	25

3IN1 Rechargeable Table Lamp Black

3 STEP DIMMING
3 CCT MODES
RECHARGEABLE

- DC:5V,1A
- CRI: >80
- 120° Beam Angle
- Body Type: ABS+PC+Aluminium
- Unit Color:Black

Model	SKU	Watts	Lumen	Box Qty
VT-1014-B	8500 - 3 IN 1	4W	120	25

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

Hanging Lamp

- AC:100-240V,50/60Hz
- CRI: >80
- 90° Beam Angle
- Body Type: PC+Metal

Model	SKU	Watts	Lumen	Size	Unit Color	Box Qty
VT-1036-P	8504 - 4000K DAY WHITE	7W	360	Ø150×151×1241mm	Purple	9
VT-1036-W	8505 - 4000K DAY WHITE	7W	360	Ø150×151×1241mm	White	9
VT-1036-B	8506 - 4000K DAY WHITE	7W	360	Ø150×151×1241mm	Blue	9

Table Lamps+Speaker

- Dancing RGB colorful lights
- USB & TF card slot
- Bluit in 3.5mm Aux input
- Rechargeable Lithium battery
- Battery capacity 1800 mAh

Model	SKU	Watts	Size	Unit Color	Box Qty
VT-6211	8570 BLACK	2*3W	Ø92×218mm	Black	12
VT-6211-R	8571 RED	2*3W	Ø92×218mm	Red	12
VT-6211-B	8569 BLUE	2*3W	Ø92×218mm	Blue	12

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Table Lamps-Bakelite-E27

5 YEAR WARRANTY

Model	SKU	Size	Unit Color	Box Qty
VT-7151-GR	3912	260×180×360mm	Green	6
VT-7151-B	3913	260×180×360mm	Blue	6
VT-7151-GD	3914	260×180×360mm	Yellow	6

Floor Lamp-E27

Model	SKU	Size	Unit Color	Box Qty
VT-7451	8565	1920×1960mm	Ivory	1 Pc
VT-7451-B	8564	1920×1960mm	Black	1 Pc

DEKRA TÜV SÜD RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

Floor Lamp-E27

Model	SKU	Size	Box Qty
VT-7500	7055	250×250×1800mm	4



EMERGENCY LIGHTS

V-TAC features a line of premium quality LED emergency lights for clear and bright emergency illumination. Inclusive of evident exit signs, these signs are powered by high performance batteries, rendering a longer lifespan and lower maintenance. V-TAC's emergency lights and signs are a practical and valuable asset to many applications inclusive of o ces, hotels, hospitals and residential areas.

Key Features

- Thermoplastic PC housing, Rectangular type plastic with different signs
- Single or double face configuration
- Universal (wall, side or ceiling) mounting
- Low energy consumption only 2.0 watts at 120V
- LED indicator light and push button test switch
- LEDs mounted on print circuit board
- 24 hours recharge after more than 3 Hours discharge
- Efficient thermal management technology
- Corrosion free mounting clamps
- High performance Ni-Cd batteries made for Longevity & low maintenance
- Reliable Emergency backup of 3 hours

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

Exit Light 4IN1 with Self Test Button

Lamp Type:	20 SMD LEDs
Input Voltage:	AC:200-240V,50/60Hz
Protection Rating:	IP20
Material :	PC+PMMA
Exit Lamp Type:	Ceiling, Hanging, Sidewall and Wall Mounting
Viewing Distance:	30 Meters From Both Sides
Emergency Operation Time:	>3 Hours
Battery:	Ni-cd AA, 3.6V, 0.6Ah
Recharging Time:	24 Hours
Test Button:	Green Light Indicator Test Button
Stickers:	4 Stickers
Legends:	4 Ways Legend Available
Mode Of Operation:	Maintained
Size:	350×29×195mm

Model	SKU	Watts	Lumen	Box Qty
VT-995	7675 - 6000K WHITE	2.5W	100	20

REMOTE CONTROL FOR EXIT LIGHT SKU:11362

4 IN 1 ① Ceiling ② Sidewall ③ Hanging ④ Wall Mounting

Exit Light -Bulkhead

Lamp Type:	16 SMD LEDs
Input Voltage:	AC:220-240V,50/60Hz
Protection Rating:	IP65
Material :	PC Cover
Exit Lamp Type:	Wall - Bulkhead
Viewing Distance:	22 Meters From One side
Emergency Operation Time:	>3 Hours
Battery:	Ni-cd 3.6V, 1200mAh
Recharging Time:	24 Hours(intial charge 36 hours)
Test Button:	Green Light Indicator Test Button
Stickers:	4 Stickers
Legends:	4 Ways Legend Available
Mode Of Operation:	Maintained
Size:	346×107×60mm

Model	SKU	Watts	Lumen	Box Qty
VT-533ST	8665 - 6500K WHITE	3W	140	10

IP65 RATING

24Hrs CHARGING TIME



DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Exit Light – Bulkhead

Lamp Type:	16 SMD LEDs
Input Voltage:	AC:220-240V,50/60Hz
Protection Rating:	IP65
Material :	PC Cover
Exit Lamp Type:	Wall – Bulkhead
Viewing Distance:	22 Meters From One side
Emergency Operation Time:	>3 Hours
Battery:	Ni-Cd 3.6v,1200mAh
Recharging Time:	12 Hours
Test Button:	Green Light Indicator Test Button
Stickers:	4 Stickers
Legends:	4 Ways Legend Available
Mode Of Operation:	Maintained
Size:	346×107×60mm

Model	SKU	Watts	Lumen	Box Qty
VT-543	83111 – 6400K WHITE	3w	140	12

IP65 RATING

12Hrs CHARGING TIME



Emergency -Bulkhead

Lamp Type:	16 SMD LEDs
Input Voltage:	AC:220-240V,50/60Hz
Protection Rating:	IP65
Material :	PC
Exit Lamp Type:	Wall – Bulkhead
Viewing Distance:	22 Meters From One side
Emergency Operation Time:	>3 Hours
Battery:	Ni-cd 3.6V, 1200mAh
Recharging Time:	24 Hours
Test Button:	Green Light Indicator Test Button
Stickers:	4 Stickers
Legends:	4 Ways Legend Available
Mode Of Operation:	Maintained & Non Maintained
Size:	346×104×58mm

Model	SKU	Watts	Lumen	Box Qty
VT-533	8437 – 6400K WHITE	3w	140	10

IP65 RATING

24Hrs CHARGING TIME



DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

Emergency-Downlight

Material:	Poly Carbonate & Aluminium
Mouned:	Ceiling Recessed
Life Time Of Battery:	2 Years
Lamp Protection:	Over Charge And Discharge Protection
Led Indicator:	Green Light Indicator Test Button
Charging Current:	90mA
Convert Voltage:	AC:155V
Discharging Current:	300mA
Discharge Duration:	3 Hours
Spec Of Battery:	3.6V 1800mAh Ni-cd Battery
Packing:	38.5×22×25mm
IP Rating:	IP20
Mode Of Operation:	Non Maintained

Model	SKU	Watts	Lumen	Box Qty
VT-503	8274 - 5500K WHITE	3w	140	20



Emergency-Twin Spotlight

Lamp Type:	2×6 SMD LEDs
Input Voltage:	AC:220-240V,50/60Hz
Protection Rating:	IP65
Material :	PC
Exit Lamp Type:	Wall Mounted
Viewing Distance:	22 Meters From One side
Emergency Operation Time:	>3 Hours
Battery:	Ni-Cd 3.6V,300mAh
Recharging Time:	24 Hours(intial charge 36 hours)
Test Button:	Green Light Indicator Test Button
Stickers:	4 Stickers
Legends:	2 Ways Legend Available
Mode Of Operation:	Non Maintained
Size:	296×75×272mm

Model	SKU	Watts	Lumen	Box Qty
VT-526	80981 - 6000K WHITE	6w	300	5

IP65 RATING

24Hrs CHARGING TIME



DEKRA TÜV SÜD CE/EMC

ACCREDITATION FROM TOP EUROPEAN LABS



MOTION SENSORS

Many areas like lobbies, parking garages, staircases remain unused for long hours but do need lighting to be lit automatically in case of movement. A motion sensor is a device, which detects movements, and in some cases light conditions and then transmits a signal for illumination.

Key Feature

- Power saving
- Available for indoor and outdoor purposes
- Compatible with most of our models
- Proven quality from reliable suppliers
- Wide range of models to choose from

Application

- Outdoor Areas like parking garages, gardens compounds and yards
- Indoor areas like walkways, lobbies and staircases.

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Infrared Sensor

VT-8091-W SKU: 6606



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	White	**Voltage:**	AC:110-240V,50/60Hz
Body Type:	PC	**Dimension:**	Ø76×20.2mm
IP Rating:	IP20	**Time Delay:**	10sec±3sec to 7min±2min(adjustable)
Detection Range:	360°	**Box Qty:**	100
Detection Distance:	Max.8m (<24°C)	**Rated Load:**	Max.200W(AC:220-240V)/100W(AC:110-130V) LED

Infrared Sensor

VT-8091-B SKU: 6607



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	Black	**Voltage:**	AC:110-240V,50/60Hz
Body Type:	PC	**Dimension:**	Ø76×20.2mm
IP Rating:	IP20	**Time Delay:**	10sec±3sec to 7min±2min(adjustable)
Detection Range:	360°	**Box Qty:**	100
Detection Distance:	Max.8m (<24°C)	**Rated Load:**	Max.200W(AC:220-240V)/100W(AC:110-130V) LED

Infrared Sensor

VT-8092-W SKU: 6608



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	Ø50×62mm
IP Rating:	IP20	**Time Delay:**	10sec±3sec to 15min±2min(adjustable)
Detection Range:	360°	**Box Qty:**	100
Detection Distance:	Max.8m (<24°C)	**Rated Load:**	Max. 400W (LED)

Infrared Sensor

VT-8092-B SKU: 6609



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	Black	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	Ø50×62mm
IP Rating:	IP20	**Time Delay:**	10sec±3sec to 15min±2min(adjustable)
Detection Range:	360°	**Box Qty:**	100
Detection Distance:	Max.8m (<24°C)	**Rated Load:**	Max. 400W (LED)

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Infrared Sensor-IP65

VT-8093-W SKU: 6611

IP65 RATING



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	76×92×62.5mm
IP Rating:	IP65	**Time Delay:**	10sec±3sec to 15min±2min(adjustable)
Detection Range:	180°/360°	**Box Qty:**	50
Detection Distance:	Max.12m (<24°C)	**Rated Load:**	Max. 600W (LED)

Infrared Sensor-IP65

VT-8093-B SKU: 6610

IP65 RATING



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	Black	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	76×92×62.5mm
IP Rating:	IP65	**Time Delay:**	10sec±3sec to 15min±2min(adjustable)
Detection Range:	180°/360°	**Box Qty:**	50
Detection Distance:	Max.12m (<24°C)	**Rated Load:**	Max. 600W (LED)

Infrared Sensor-IP65

VT-8094-W SKU: 6613

IP65 RATING

SPECIAL DESIGN
Adjustable For Corner



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	125.2×71.4×72.7mm
IP Rating:	IP65	**Time Delay:**	10sec±3sec to 15min±2min(adjustable)
Detection Range:	240°	**Box Qty:**	50
Detection Distance:	Max.10m (<24°C)	**Rated Load:**	Max. 600W (LED)

Infrared Sensor-IP65

VT-8094-B SKU: 6612

IP65 RATING

SPECIAL DESIGN
Adjustable For Corner



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	Black	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	125.2×71.4×72.7mm
IP Rating:	IP65	**Time Delay:**	10sec±3sec to 15min±2min(adjustable)
Detection Range:	240°	**Box Qty:**	50
Detection Distance:	Max.10m (<24°C)	**Rated Load:**	Max. 600W (LED)

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Infrared Sensor

VT-8027-W SKU: 5086



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	115×25mm
IP Rating:	IP20	**Time Delay:**	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	360°	**Box Qty:**	50
Detection Distance:	Max. 8m(<24°C)	**Rated Load:**	Max 1000W(LED)

Infrared Sensor

VT-8027-B SKU: 5087



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	Black	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	115×25mm
IP Rating:	IP20	**Time Delay:**	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	360°	**Box Qty:**	50
Detection Distance:	Max. 8m(<24°C)	**Rated Load:**	Max 1000W(LED)

Infrared Sensor-Moving Head-IP44

VT-8028-W SKU: 5088



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	445X345X19mm
IP Rating:	IP44	**Time Delay:**	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	180°	**Box Qty:**	50
Detection Distance:	Max. 12m(<24°C)	**Rated Load:**	Max 400W(LED)

Infrared Sensor-Moving Head-IP44

VT-8028-B SKU: 5089



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	Black	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	445X345X19mm
IP Rating:	IP44	**Time Delay:**	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	180°	**Box Qty:**	50
Detection Distance:	Max. 12m(<24°C)	**Rated Load:**	Max 400W(LED)

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Infrared Sensor

VT-8029 **SKU: 5090**



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	76×75.6mm
IP Rating:	IP20	**Time Delay:**	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	360°	**Box Qty:**	50
Detection Distance:	Max. 6m(<24°C)	**Rated Load:**	Max 300W(LED)

Infrared Sensor-Moving Head

VT-8030 **SKU: 5091**



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	98×73×82mm
IP Rating:	IP20	**Time Delay:**	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	360°	**Box Qty:**	50
Detection Distance:	Max. 8m(<24°C)	**Rated Load:**	Max 400W(LED)

Infrared Sensor-IP44

VT-8003-W **SKU: 4967**



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	86.4×60.4×98mm
IP Rating:	IP44	**Time Delay:**	Min. 10sec±3sec, Max. 7min±2min
Detection Range:	180°	**Box Qty:**	50
Detection Distance:	Max. 12m(<24°C)	**Rated Load:**	Max 300W(LED)

Infrared Sensor-IP44

VT-8003-B **SKU: 5077**



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	Black	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	86.4×60.4×98mm
IP Rating:	IP44	**Time Delay:**	Min. 10sec±3sec, Max. 7min±2min
Detection Range:	180°	**Box Qty:**	50
Detection Distance:	Max. 12m(<24°C)	**Rated Load:**	Max 300W(LED)

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Infrared Sensor

VT-8004 **SKU: 4968**



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	Ø88×55mm
IP Rating:	IP20	**Time Delay:**	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	360°	**Box Qty:**	50
Detection Distance:	Max. 12m(<24°C)	**Rated Load:**	Max 300W(LED)

Infrared Sensor-E27

VT-8005 **SKU: 4982**



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	White	**Voltage:**	AC:110-240V,50/60Hz
Body Type:	Plastic	**Dimension:**	55.5×116.5mm
IP Rating:	IP20	**Time Delay:**	Min. 10sec±3sec, Max. 5min±1min
Detection Range:	360°	**Box Qty:**	50
Detection Distance:	Max. 6m(<24°C)	**Rated Load:**	Max 60W(LED)

Infrared Sensor-IP44

VT-8048 **SKU: 1354**

Sensor Type:	Infrared
Colour:	White
Detection Range:	180°
Voltage:	AC:220-240V,50/60Hz
Detection Distance:	Max. 12m(<24°C)
Rated Load:	Max 300W(LED)X20
Ambient Light:	<3-2000LUX(adjustable)
Body Type:	PC
IP Rating:	IP44
Dimension:	86.4×86.4×60.4mm
Time Delay:	Min. 10sec±3sec, Max. 7min±2min
Box Qty:	50

1. Automatic Sensor Override Mode – Turn the switch OFF and ON within 3 Seconds, the sensor will be overridden and switched off. The light will work continuously and normally. (Make sure the automatic mode is switched ON before using this functionality).
2. Sensor Switch On – Turn the switch OFF for 20 seconds and switch it back ON. The sensor will restart and work as per the settings adjusted.
3. If the light is left idle for a longer period, the sensor will automatically switch back to automatic mode (Possible when the outside light reaches 100Lux).

Infrared Sensor

VT-8049 **SKU: 1355**

Sensor Type:	Infrared
Colour:	White
Detection Range:	360°
Voltage:	AC:220-240V,50/60Hz
Detection Distance:	Max. 12m(<24°C)
Rated Load:	Max 300W(LED)
Ambient Light:	<3-2000LUX(adjustable)
Body Type:	PC
IP Rating:	IP20
Dimension:	88×55mm
Time Delay:	Min. 10sec±3sec, Max. 15min±2min
Box Qty:	50

1. Automatic Sensor Override Mode – Turn the switch OFF and ON within 3 Seconds, the sensor will be overridden and switched off. The light will work continuously and normally. (Make sure the automatic mode is switched ON before using this functionality).
2. Sensor Switch On – Turn the switch OFF for 20 seconds and switch it back ON. The sensor will restart and work as per the settings adjusted.
3. If the light is left idle for a longer period, the sensor will automatically switch back to automatic mode (Possible when the outside light reaches 100Lux).

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Infrared Sensor

VT-8051 **SKU: 1356**

Sensor Type:	Infrared
Colour:	White
Detection Range:	360°
Voltage:	AC:220-240V,50/60Hz
Detection Distance:	Max. 6m(<24°C)
Rated Load:	Max 300W(LED)
Ambient Light:	<3-2000LUX(adjustable)
Body Type:	PC
IP Rating:	IP20
Dimension:	76×75.6mm
Time Delay:	Min. 10sec±3sec, Max. 15min±2min
Box Qty:	50

1. Automatic Sensor Override Mode – Turn the switch OFF and ON within 3 Seconds, the sensor will be overridden and switched off. The light will work continuously and normally. (Make sure the automatic mode is switched ON before using this functionality).
2. Sensor Switch On – Turn the switch OFF for 20 seconds and switch it back ON. The sensor will restart and work as per the settings adjusted.
3. If the light is left idle for a longer period, the sensor will automatically switch back to automatic mode (Possible when the outside light reaches 100Lux).

Day Light Sensor – 1-10V

VT-8059 **SKU: 1369**

Sensor Type:	Day Light
Colour:	White
Detection Range:	360°
Voltage:	DC:1-10V
Body Type:	PC
IP Rating:	IP20
Box Qty:	100

Daylight Sensor supplies a simple and effective solution for daylight harvesting. Connecting to 1-10V Power source and using with LED dimmable driver.
The illumination level of lamps will get darker when ambient light gets brighter.
When daylight is insufficient, the lamp will be in 100% Illumination level, and turns to 1% Level when daylight is sufficient, then gradually bac

Infrared Sensor

VT-8083-B **SKU: 15011**

IP65 RATING



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	Black	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	86.5×172.5×56mm
IP Rating:	IP65	**Time Delay:**	Min.10sec±3sec, Max. 30min±2min
Detection Range:	360°	**Box Qty:**	50
Detection Distance:	Max.20m(<24°C)	**Rated Load:**	1000w(LED)

Infrared Sensor

VT-8083-W **SKU: 15001**

IP65 RATING



Sensor Type:	Infrared	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC	**Dimension:**	86.5×172.5×56mm
IP Rating:	IP65	**Time Delay:**	Min.10sec±3sec, Max. 30min±2min
Detection Range:	360°	**Box Qty:**	50
Detection Distance:	Max.20m(<24°C)	**Rated Load:**	1000w(LED)

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Microwave Sensor

VT-8084-B **SKU: 15031**



Sensor Type:	Microwave	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	Black	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC+Glass	**Dimension:**	95×50×95mm
IP Rating:	IP20	**Time Delay:**	Min.10sec±3sec, Max. 12min±1min
Detection Range:	180°	**Box Qty:**	50
Detection Distance:	5-15m	**Rated Load:**	300w(LED)

Microwave Sensor

VT-8084-W **SKU: 15021**



Sensor Type:	Microwave	**Ambient Light:**	<3-2000LUX (adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	PC+Glass	**Dimension:**	95×50×95mm
IP Rating:	IP65	**Time Delay:**	Min.10sec±3sec, Max. 12min±1min
Detection Range:	180°	**Box Qty:**	50
Detection Distance:	5-15m	**Rated Load:**	300w(LED)

Infrared-Hand Gesture Detecion

VT-8025 **SKU: 5084**



On/Off via Moving Hand

Sensor Type:	Infrared	**Voltage:**	AC:110-240V,50/60Hz
Colour:	White	**Dimension:**	35.5×78.2×20.6mm
Body Type:	Plastic	**Box Qty:**	100
IP Rating:	IP20	**Rated Load:**	Max 200W(LED)
Detection Range:	30°		
Detection Distance:	5cm/6cm(<24°C)		

Infrared-Door Detection

VT-8026 **SKU: 5085**



On/Off via the opening and closing of the door

Sensor Type:	Infrared	**Voltage:**	AC:110-240V,50/60Hz
Colour:	White	**Dimension:**	35.5×78.2×18.7mm
Body Type:	Plastic	**Box Qty:**	100
IP Rating:	IP20	**Rated Load:**	Max 200W(LED)
Detection Range:	30°		
Detection Distance:	5cm/6cm(<24°C)		

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Microwave Sensor-IP65

VT-8036-W SKU: 5571

IP65 RATING

Sensor Type:	Microwave	**Ambient Light:**	<25-2000LUX
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	Plastic	**Dimension:**	115×35×25mm
IP Rating:	IP65	**Time Delay:**	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	180°	**Box Qty:**	100
Detection Distance:	5m/10m	**Rated Load:**	Max 200W(LED)

Microwave Sensor-IP65

VT-8036-B SKU: 5572



IP65 RATING

Sensor Type:	Microwave	**Ambient Light:**	<25-2000LUX
Colour:	Black	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	Plastic	**Dimension:**	115×35×25mm
IP Rating:	IP65	**Time Delay:**	Min. 10sec±3sec, Max. 15min±2min
Detection Range:	180°	**Box Qty:**	100
Detection Distance:	5m/10m	**Rated Load:**	Max 200W(LED)

Microwave Sensor

VT-8018 SKU: 5078



Sensor Type:	Microwave	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	Plastic	**Dimension:**	37×25×61.5mm
IP Rating:	IP20	**Time Delay:**	Min. 10sec±3sec, Max. 12min±1min
Detection Range:	180° / 360°	**Box Qty:**	100
Detection Distance:	1-8m(radius) adjustable	**Rated Load:**	Max 300W(LED)



Photocell Sensor-IP44

VT-8019 SKU: 5081



Sensor Type:	Photocell	**Ambient Light:**	<5-15LUX(adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50Hz
Body Type:	Plastic	**Dimension:**	35.5×46×44.1mm
IP Rating:	IP44	**Time Delay:**	5 sec to 8 min (adjustable)
Detection Range:	360°	**Box Qty:**	100
Detection Distance:		**Rated Load:**	Max 500W(LED)

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING



Infrared Sensor

VT-8022 **SKU: 5082**

IP65 RATING



Sensor Type:	Infrared	**Ambient Light:**	10LUX/2000LUX(choice)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	Plastic	**Dimension:**	36.8×25.5×55.4mm
IP Rating:	IP65	**Time Delay:**	5s,30s,1min,3min,5min,8min(choice)
Detection Range:	120°/360°	**Box Qty:**	100
Detection Distance:	3/6m(<24°C)	**Rated Load:**	Max 400W(LED)

Microwave Sensor

VT-8077 **SKU: 1446**



Sensor Type:	Microwave	**Ambient Light:**	0<3-2000LUX(Adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	Plastic	**Dimension:**	80.7×42.1×43.8mm
IP Rating:	IP20	**Time Delay:**	Min. 10sec±3sec, Max.12min±1min
Detection Range:	360°	**Box Qty:**	100
Detection Distance:	1-8m(radius) Adjustable	**Rated Load:**	Max 300W(LED)

Microwave Sensor

VT-8023 **SKU: 5083**



Sensor Type:	Microwave	**Ambient Light:**	<3-2000LUX(adjustable)
Colour:	White	**Voltage:**	AC:220-240V,50/60Hz
Body Type:	Plastic	**Dimension:**	80×80×32mm
IP Rating:	IP20	**Time Delay:**	10 sec to 12 min (adjustable)
Detection Range:	180°	**Box Qty:**	100
Detection Distance:	5m-15m(adjustable)	**Rated Load:**	Max 300W(LED)



OUTDOOR LIGHTS & FITTINGS

Transform the exteriors of a Building or a Garden into a Beautiful piece of Architecture. Simultaneously help navigate obstacles at night, prevent accidents and provide security.

Key Feature

- Perfect replacement for traditional fittings as they are more flexible & efficient
- Work perfectly in extreme temperatures from -20° to +45° without any adverse effects
- Specifically designed for Outdoor use
- IP65 Protection Rating to ensure safety
- Low Maintenance
- Outstanding Colour options and settings

Application

Used for gardens, outdoor residential areas, walkways & passages, driveways, fountains, lawns, entrance, patio or terrace and similar environments

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Underground Light- Oblique Angle

- AC:220-240V,50Hz
- PF: >0.5
- CRI: >80
- 20° Beam Angle
- Body Type: Stainless Steel+Aluminium+Glass Cover
- Cutting Size: NA

IP67 RATING



Model	SKU	Watts	Lumen	Box Qty
VT-7679	8621 - 4000K DAY WHITE	8w	350	12
VT-7679-N	218621 - 4000K DAY WHITE	8w	350	12

Underground Light

- AC:220-240V,50Hz
- PF: >0.7
- CRI: >80
- 40° Beam Angle
- Body Type: Stainless Steel+Aluminium+Glass Cover
- Cutting Size: NA

IP67 RATING



Model	SKU	Watts	Lumen	Box Qty
VT-7681	8622 - 4000K DAY WHITE	12w	750	12
VT-7681-N	218622 - 4000K DAY WHITE	10w	850	12



Underground Light

- DC:12V
- PF: >0.4
- CRI: >80
- 90° Beam Angle
- Body Type: PC
- Cutting Size: Ø25mm

IP67 RATING

12V



Model	SKU	Watts	Lumen	Box Qty
VT-1141	1463 - 3000K WARM WHITE	0.5w	5	50
VT-1141-N	211463 - 3000K WARM WHITE	0.5w	5	50



Underground Light

- DC:12V
- PF: >0.4
- CRI: >80
- 90° Beam Angle
- Body Type: PC
- Cutting Size: Ø43mm

IP67 RATING

12V



Model	SKU	Watts	Lumen	Box Qty
VT-1151	2879 - 3000K WARM WHITE 1464 - 6500K WHITE	1w	50	50
VT-1151-N	211464 - 6500K WHITE	1w	50	50

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Underground Light

- DC:12V
- PF: >0.4
- CRI: >80
- 90° Beam Angle
- Body Type: PC+AL
- Cutting Size: Ø43mm

IP67 RATING

12V



Model	SKU	Watts	Lumen	Box Qty
VT-1161-W	1465 – 3000K WARM WHITE 1467 – 6500K WHITE	1w	10	50
VT-1161-W-N	211465 – 3000K WARM WHITE 211467 – 6500K WHITE	1w	50	50

Underground Light

- DC:12V
- PF: >0.4
- CRI: >80
- 90° Beam Angle
- Body Type: PC+AL
- Cutting Size: Ø43mm

IP67 RATING

12V



Model	SKU	Watts	Lumen	Box Qty
VT-1161-B	1466 – 3000K WARM WHITE 1468 – 6500K WHITE	1w	10	50
VT-1161-B-N	211466 – 3000K WARM WHITE	1w	50	50

Underground Light

- DC:12V
- PF: >0.4
- CRI: >80
- 90° Beam Angle
- Body Type: PC+AL
- Cutting Size: Ø43mm

IP67 RATING

12V



Model	SKU	Watts	Lumen	Box Qty
VT-1171-W	1469 – 3000K WARM WHITE 1471 – 6500K WHITE	1w	10	50
VT-1171-W-N	211469 – 3000K WARM WHITE	1w	50	50

Underground Light

- DC:12V
- PF: >0.4
- CRI: >80
- 90° Beam Angle
- Body Type: PC+AL
- Cutting Size: Ø43mm

IP67 RATING

12V



Model	SKU	Watts	Lumen	Box Qty
VT-1171-B	1470 – 3000K WARM WHITE 1472 – 6500K WHITE	1w	10	50
VT-1171-B-N	211470 – 3000K WARM WHITE 211472 – 6500K WHITE	1w	50	50

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

Pool Lights-PAR56

IP68 RATING



- AC/DC:12V,50Hz
- PF:
- CRI: >80
- 120° Beam Angle
- Body Type: Glass
- Cutting Size: NA

Model	SKU	Watts	Lumen	Box Qty
VT-1258	7556 – 3000K WARM WHITE 7557 – BLUE 7555 – 6400K WHITE	8w	800	12
VT-1262	7560 – 3000K WARM WHITE 7561 – BLUE 7559 – 6500K WHITE	12w	1200	12

Pool Lights-PAR56-RGB

IP68 RATING



- AC/DC:12V,50Hz
- PF:
- CRI: >80
- 120° Beam Angle
- Body Type: Glass
- Cutting Size: NA

Model	SKU	Watts	Lumen	Box Qty
VT-1268	7558 – RGB	8w	800	12
VT-1263	7562 – RGB	12w	1200	12

Wall Fitting-Up-Down-GU10-Sensor

Model: VT-7632S
SKU: 5157
Material: Stainless Steel
Holder: 2XGU10
IP Rating: IP44
Dimension: 60×110×215mm
Box Qty: 12

UP & DOWN LIGHTS

Wall Fittings-E27

NEW

Model: VT-967
SKU: 93573
Material: PC
Holder: 2xE27
IP Rating: IP44
Dimension: 130×100×228mm
Box Qty: 10

IP44 RATING

Wall Fittings-E27

NEW

Model: VT-968
SKU: 93574
Material: PC
Holder: 2xE27
IP Rating: IP44
Dimension: 150×91×228mm
Box Qty: 10

IP44 RATING

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Wall Fittings-GU10

Model: VT-7621PIR
SKU: 7502
Material: Stainless Steel
Holder: GU10
IP Rating: IP44
Dimension: 110×67×163mm
Box Qty: 24

MOTION PIR SENSOR

Wall Fitting-Up-Down-GU10

Model: VT-7622PIR
SKU: 7503
Material: Stainless Steel
Holder: 2XGU10
IP Rating: IP44
Dimension: 110×67×220mm
Box Qty: 12

UP & DOWN LIGHTS

Wall Fittings-GU10

Model: VT-7621
SKU: 7501
Material: Stainless Steel
Holder: GU10
IP Rating: IP44
Dimension: 93×85×118mm
Box Qty: 24

Wall Fitting-Up-Down-GU10

Model: VT-7622
SKU: 7500
Material: Stainless Steel
Holder: 2XGU10
IP Rating: IP44
Dimension: 93×85×163mm
Box Qty: 16

UP & DOWN LIGHTS

Wall Fittings-GU10

Model: VT-7631
SKU: 7505
Material: Stainless Steel
Holder: GU10
IP Rating: IP44
Dimension: 110×60×125mm
Box Qty: 24

Wall Fitting-Up-Down-GU10

Model: VT-7632
SKU: 7504
Material: Stainless Steel
Holder: 2XGU10
IP Rating: IP44
Dimension: 110×60×178mm
Box Qty: 12

UP & DOWN LIGHTS

Wall Fittings-GU10

Model: VT-7641
SKU: 7506
Material: Stainless Steel
Holder: GU10
IP Rating: IP44
Dimension: 105×76×118mm
Box Qty: 24

Wall Fitting-Up-Down-GU10

Model: VT-7642
SKU: 7507
Material: Stainless Steel
Holder: 2XGU10
IP Rating: IP44
Dimension: 105×76×207mm
Box Qty: 16

UP & DOWN LIGHTS

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Wall Fittings-GU10

Model: VT-7651RD
SKU: 7508
Material: Aluminium
Holder: GU10
IP Rating: IP44
Dimension: 92×68×80mm
Box Qty: 24

Wall Fitting-Up-Down-GU10

Model: VT-7652RD
SKU: 7509
Material: Aluminium
Holder: 2XGU10
IP Rating: IP44
Dimension: 92×68×150mm
Box Qty: 16

UP & DOWN LIGHTS

Wall Fittings-GU10

Model: VT-7651SQ
SKU: 7510
Material: Aluminium
Holder: GU10
IP Rating: IP44
Dimension: 92×68×80mm
Box Qty: 24

Wall Fitting-Up-Down-GU10

Model: VT-7652SQ
SKU: 7511
Material: Aluminium
Holder: 2XGU10
IP Rating: IP44
Dimension: 92×68×150mm
Box Qty: 16

UP & DOWN LIGHTS

Wall Fitting-Up-Down-GU10

Model: VT-7662
SKU: 7512
Material: Stainless Steel
Holder: 2XGU10
IP Rating: IP44
Dimension: 85×87×250mm
Box Qty: 12

UP & DOWN LIGHTS

Wall Fitting-Up-Down-GU10

Model: VT-7622-B
SKU: 7569
Material: Stainless Steel
Holder: 2XGU10
IP Rating: IP44
Dimension: 93×85×163mm
Box Qty: 16

UP & DOWN LIGHTS

Wall Fittings-GU10

Model: VT-7651SQ-W
SKU: 7539
Material: Aluminium
Holder: GU10
IP Rating: IP44
Dimension: 92×68×80mm
Box Qty: 24

Wall Fittings-GU10

Model: VT-7651RD-W
SKU: 7540
Material: Aluminium
Holder: GU10
IP Rating: IP44
Dimension: 92×68×80mm
Box Qty: 24

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Wall Fitting-Up-Down-GU10

Model: VT-7652SQ-W
SKU: 7541
Material: Aluminium
Holder: 2XGU10
IP Rating: IP44
Dimension: 92×68×150mm
Box Qty: 16

UP & DOWN LIGHTS

Wall Fitting-Up-Down-GU10

Model: VT-7652RD-W
SKU: 7542
Material: Aluminium
Holder: 2xGU10
IP Rating: IP44
Dimension: 92×68×80mm
Box Qty: 16

UP & DOWN LIGHTS

Wall Fitting-Up-Down-GU10

Model: VT-7662-W
SKU: 7543
Material: Stainless Steel
Holder: 2XGU10
IP Rating: IP44
Dimension: 85×87×250mm
Box Qty: 12

UP & DOWN LIGHTS

Wall Fitting-Up-Down-GU10

Model: VT-7622-W
SKU: 7570
Material: Stainless Steel
Holder: 2XGU10
IP Rating: IP44
Dimension: 93×85×163mm
Box Qty: 16

UP & DOWN LIGHTS

Wall Fittings-GU10

Model: VT-7611
SKU: 7553
Material: Aluminium
Holder: GU10
IP Rating: IP44
Dimension: 100×66×92mm
Box Qty: 24

Wall Fittings-GU10

Model: VT-7612
SKU: 7554
Material: Aluminium
Holder: GU10
IP Rating: IP44
Dimension: 1170×50mm
Box Qty: 6

Wall Fittings-GU10

Model: VT-841
SKU: 8626
Material: Aluminium+Glass
Holder: GU10
IP Rating: IP44
Dimension: 63×99×120mm
Box Qty: 24

Wall Fitting-Up-Down-GU10

Model: VT-842
SKU: 8627
Material: Aluminium+Glass
Holder: GU10
IP Rating: IP44
Dimension: 63×99×170mm
Box Qty: 24

UP & DOWN LIGHTS

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

Underground Fittings-MR16

Model: VT-7678-1
SKU: 8567
Material: Stainless Steel
Holder: MR16
IP Rating: IP67
Dimension: D:87×128mm
Box Qty: 12

IP67 RATING

Underground Fittings-MR16

Model: VT-7678-2
SKU: 8568
Material: Stainless Steel
Holder: MR16
IP Rating: IP67
Dimension: D:87×128mm
Box Qty: 12

IP67 RATING

Underground Fittings-MR16

Model: VT-7678-3
SKU: 8566
Material: Stainless Steel
Holder: MR16
IP Rating: IP67
Dimension: D:87×128mm
Box Qty: 12

IP67 RATING

Underground Fittings

Model: VT-7677RD
SKU: 7515
Material: Stainless Steel
Holder: GU10
IP Rating: IP65
Dimension: 110×110×120mm
Box Qty: 24

IP65 RATING

Underground Fittings

Model: VT-7677SQ
SKU: 7516
Material: Stainless Steel
Holder: GU10
IP Rating: IP65
Dimension: 110×110×120mm
Box Qty: 24

IP65 RATING

Garden Spike-Single Head

Model: VT-728
SKU: 7044
Material: ABS
Holder: E27
IP Rating: IP44
Dimension: 450×27mm
Box Qty: 12

Garden Spike-Double Head

Model: VT-729
SKU: 7045
Material: ABS
Holder: E27
IP Rating: IP44
Dimension: 450×205mm
Box Qty: 12

Garden Spike

Model: VT-769
SKU: 7517
Material: Aluminium
Holder: GU10
IP Rating: IP44
Dimension: 95×95×335mm
Box Qty: 12

GARDEN LIGHTS & FITTINGS

V-TAC presents an elegant series of garden lighting, makes your garden glow in style when the sun goes down. Step outside with our wide range of contemporary outdoor lighting and decorate your pathways, walls, floors, and ceilings with our modern designs.

Key Feature

- Traditional Garden Lamps designed to fit the Modern day requirements
- Available in different designs, shapes and sizes
- Easy installation
- Applicable with GU10 -E27 base lights
- Suitable for Walls, Floor, Pathways and Ceiling Lights

Application

Used for gardens, outdoor residential areas, walkways & passages, driveways, fountains, lawns, entrance, patio or terrace and similar environments

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Garden Spike Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- 30° Beam Angle
- Body Type: Aluminium
- Size: 73×255mm

IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-857-B	7545 – 4000K DAY WHITE 7546 – GREEN	12w	720	50
VT-857-B-N	217544 – 3000K WARM WHITE 217545 – 4000K DAY WHITE	12w	3000K – 880lm 4000K – 875lm	50

Garden Spike Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- 30° Beam Angle
- Body Type: Aluminium
- Size: 73×255mm

IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-857-W	7548 – 4000K DAY WHITE 7549 – GREEN	12w	720	50
VT-857-W-N	217547 – 3000K WARM WHITE 217548 – 4000K DAY WHITE	12w	3000K – 920lm 4000K – 970lm	50

Garden Spike Light

- AC:100-240V,50/60Hz
- PF: >0.6
- CRI: >80
- 30° Beam Angle
- Body Type: Aluminium
- Size: 73×255mm

IP65 RATING

Model	SKU	Watts	Lumen	Box Qty
VT-857-G	7551 – 4000K DAY WHITE 7552 – GREEN	12w	720	50
VT-857-G-N	217550 – 3000K WARM WHITE 217551 – 4000K DAY WHITE	12w	3000K – 875lm 4000K – 930lm	50

Bollard Lamps

IP54 RATING

IK08 RATING

- AC:100-240V 50/60Hz
- PF: >0.9
- CRI: >80
- 350° Beam Angle
- Body Type: Die Cast Aluminium
- Size: 200×80×300mm

MOTION PIR SENSOR

Model	SKU	Watts	Lumen	Box Qty
VT-909	5155 – 4000K DAY WHITE	9W	500	8

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Garden Spike

Model:	VT-770
SKU:	7518
Max.Watts:	35w
Material:	Stainless Steel
Color	Silver
Holder:	GU10
IP Rating:	IP44
Dimension:	60×60×420mm
Box Qty:	8

Bollard Lamps

Model:	VT-838-S45
SKU:	8958
Max.Watts:	60w
Material:	Stainless Steel+PC Diffuser
Color	Satin Nickel
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×450mm
Box Qty:	6



Wall Fittings-E27

Model:	VT-832
SKU:	8623
Max.Watts:	60w
Material:	Stainless Steel+PC
Color	White+Stainless Steel
Holder:	E27
IP Rating:	IP44
Dimension:	76×375mm
Box Qty:	12

Bollard Lamp

Model:	VT-838-S80
SKU:	8625
Max.Watts:	60w
Material:	Stainless Steel+PC Diffuser
Color	Satin Nickel
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×450mm
Box Qty:	6



Wall Fittings-E27

Model:	VT-833
SKU:	8624
Max.Watts:	60w
Material:	Stainless Steel+PC
Color	White+Stainless Steel
Holder:	E27
IP Rating:	IP44
Dimension:	76×140×335mm
Box Qty:	12

Bollard Lamps

Model:	VT-838-S110
SKU:	8962
Max.Watts:	60w
Material:	Stainless Steel+PC Diffuser
Color	Satin Nickel
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×1100mm
Box Qty:	6

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

Bollard Lamps

Model:	VT-838-B45
SKU:	8593
Max.Watts:	60w
Material:	Stainless Steel+PC Diffuser
Color	Black
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×450mm
Box Qty:	6

Bollard Lamps

Model:	VT-838-G45
SKU:	8959
Max.Watts:	60w
Material:	Stainless Steel+PC Diffuser
Color	Grey
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×450mm
Box Qty:	6

Bollard Lamps

Model:	VT-838-B80
SKU:	8978
Max.Watts:	60w
Material:	Stainless Steel+PC Diffuser
Color	Black
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×450mm
Box Qty:	6

Bollard Lamps

Model:	VT-838-G80
SKU:	8961
Max.Watts:	60w
Material:	Stainless Steel+PC Diffuser
Color	Grey
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×800mm
Box Qty:	6

Bollard Lamps

Model:	VT-838-B110
SKU:	8594
Max.Watts:	60w
Material:	Stainless Steel+PC Diffuser
Color	Black
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×1100mm
Box Qty:	6

Bollard Lamps

Model:	VT-838-G110
SKU:	8963
Max.Watts:	60w
Material:	Stainless Steel+PC Diffuser
Color	Grey
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×1100mm
Box Qty:	6

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Bollard Lamps with Sensor

Model:	VT-838-BS45
SKU:	8985
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×450mm
Box Qty:	6

MOTION PIR SENSOR

Bollard Lamps with Sensor

Model:	VT-838-SE45
SKU:	8964
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Satin Nickel
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×450mm
Box Qty:	6

MOTION PIR SENSOR

Bollard Lamps with Sensor

Model:	VT-838-BS80
SKU:	8984
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×800mm
Box Qty:	6

MOTION PIR SENSOR

Bollard Lamps with Sensor

Model:	VT-838-SS80
SKU:	8960
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Satin Nickel
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×800mm
Box Qty:	6

MOTION PIR SENSOR

Bollard Lamps with Sensor

Model:	VT-838-BS110
SKU:	8983
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×1100mm
Box Qty:	6

MOTION PIR SENSOR

Bollard Lamps with Sensor

Model:	VT-838-SE110
SKU:	8967
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Satin Nickel
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×1100mm
Box Qty:	6

MOTION PIR SENSOR

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Bollard Lamps with Sensor

Model:	VT-838-GS45
SKU:	8965
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Grey
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×450mm
Box Qty:	6

MOTION PIR SENSOR

Bollard Lamps with Sensor and Socket

Model:	VT-838-BSS60
SKU:	8979
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×600mm
Box Qty:	6

Socket Rated Current: Max 3680W
Socket Rated Power: 16A

MOTION PIR SENSOR

2 EU PLUG SOCKETS

Bollard Lamps with Sensor

Model:	VT-838-GS80
SKU:	8966
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Grey
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×800mm
Box Qty:	6

MOTION PIR SENSOR

Bollard Lamps with Sensor and Socket

Model:	VT-838-GS60
SKU:	8976
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Grey
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×600mm
Box Qty:	6

Socket Rated Current: Max 3680W
Socket Rated Power: 16A

MOTION PIR SENSOR

2 EU PLUG SOCKETS

Bollard Lamps with Sensor

Model:	VT-838-GS110
SKU:	8968
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Grey
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×1100mm
Box Qty:	6

MOTION PIR SENSOR

Bollard Lamps with Sensor and Socket

Model:	VT-838-SS60
SKU:	8977
Max.Watts:	60w
Detection Angle:	100°
Detection Range:	2-8M
Ambient Light:	2-200Lux
Time Delay:	5sec to 5min
Material:	Stainless Steel+PC Diffuser
Color:	Satin Nickel
Holder:	E27
IP Rating:	IP44
Dimension:	76×110×600mm
Box Qty:	6

Socket Rated Current: Max 3680W
Socket Rated Power: 16A

MOTION PIR SENSOR

2 EU PLUG SOCKETS

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Wall Fittings GU10



Model:	VT-7613
SKU:	7563
Max.Watts:	35W
Material:	Aluminium+clear PC diffuser
Color	Black
Holder:	GU10
IP Rating:	IP54
Dimension:	121×80×220mm
Box Qty:	6

IP54 RATING

Wall Fittings GU10



Model:	VT-7616
SKU:	7566
Max.Watts:	35W
Material:	Aluminium+opal PC diffuser
Color	Black
Holder:	GU10
IP Rating:	IP54
Dimension:	121×80×220mm
Box Qty:	6

IP54 RATING

Bollard Lamps GU10

Model:	VT-7614
SKU:	7564
Max.Watts:	35W
Material:	Aluminium+clear PC diffuser
Color	Black
Holder:	GU10
IP Rating:	IP54
Dimension:	80×80×500mm
Box Qty:	4

IP54 RATING

Bollard Lamps GU10

Model:	VT-7617
SKU:	7567
Max.Watts:	35W
Material:	Aluminium+opal PC diffuser
Color	Black
Holder:	GU10
IP Rating:	IP54
Dimension:	80×500mm
Box Qty:	4

IP54 RATING

Bollard Lamps GU10



Model:	VT-7615
SKU:	7565
Max.Watts:	35W
Material:	Aluminium+clear PC diffuser
Color	Black
Holder:	GU10
IP Rating:	IP54
Dimension:	80×80×800mm
Box Qty:	4

IP54 RATING

Bollard Lamps GU10



Model:	VT-7618
SKU:	7568
Max.Watts:	35W
Material:	Aluminium+opal PC diffuser
Color	Black
Holder:	GU10
IP Rating:	IP54
Dimension:	80×800mm
Box Qty:	4

IP54 RATING

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Wall Lamp

Model:	VT-837-B
SKU:	8517
Max.Watts:	60W
Material:	Aluminium+Clear Glass
Color:	Matt Black
Holder:	E27
IP Rating:	IP44
Dimension:	113×236×113mm
Box Qty:	10



Wall Lamp

Model:	VT-7680
SKU:	7514
Max.Watts:	14W
Material:	Stainless Steel+PC
Color:	Stainless Steel
Holder:	E27
IP Rating:	IP44
Dimension:	250×90×100mm
Box Qty:	12



Wall Lamp

Model:	VT-837
SKU:	8518
Max.Watts:	60W
Material:	Aluminium+Clear Glass
Color:	Matt White
Holder:	E27
IP Rating:	IP44
Dimension:	113×236×113mm
Box Qty:	10



IP54 RATING

Wall Lamp

Model:	VT-745-B
SKU:	7064
Max.Watts:	40W
Material:	Aluminium
Color:	Matt Black
Holder:	E27
IP Rating:	IP54
Dimension:	145X265mm
Box Qty:	12



Wall Lamp

Model:	VT-7670
SKU:	7513
Max.Watts:	14W
Material:	Stainless Steel+PC
Color:	Stainless Steel
Holder:	E27
IP Rating:	IP44
Dimension:	250×90×100mm
Box Qty:	12



IP54 RATING

Wall Lamp

Model:	VT-745-DG
SKU:	7065
Max.Watts:	40W
Material:	Aluminium
Color:	Dark Grey
Holder:	E27
IP Rating:	IP54
Dimension:	145X265mm
Box Qty:	12



V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Wall Lamp

Model: VT-754-MB
SKU: 7076
Max.Watts: 60W
Material: Aluminium+Glass
Color: Matt Black
Holder: E27
IP Rating: IP44
Dimension: 245×180×93mm
Box Qty: 10



Wall Lamp

Model: VT-760-B
SKU: 7519
Max.Watts: 60W
Material: Aluminium+Glass
Color: Matt Black
Holder: E27
IP Rating: IP44
Dimension: 225×400×148mm
Box Qty: 12



Wall Lamp

Model: VT-754-MW
SKU: 7077
Max.Watts: 60W
Material: Aluminium+Glass
Color: Matt White
Holder: E27
IP Rating: IP44
Dimension: 245×180×93mm
Box Qty: 10



Wall Lamp

Model: VT-760-W
SKU: 7520
Max.Watts: 60W
Material: Aluminium+Glass
Color: Matt White
Holder: E27
IP Rating: IP44
Dimension: 225×400×148mm
Box Qty: 12



Wall Lamp

Model: VT-835
SKU: 8628
Max.Watts: 40w
Material: Stainless Steel+PC
Color: Dark Grey
Holder: E27
IP Rating: IP44
Dimension: 148×165×245mm
Box Qty: 6



Wall Lamp

Model: VT-761-B
SKU: 7521
Max.Watts: 60W
Material: Aluminium+Glass
Color: Matt Black
Holder: E27
IP Rating: IP44
Dimension: 245×445×185mm
Box Qty: 8



DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

Wall Lamp

Model:	VT-761-W
SKU:	7522
Max.Watts:	60W
Material:	Aluminium+Glass
Color:	Matt White
Holder:	E27
IP Rating:	IP44
Dimension:	245×445×185mm
Box Qty:	8



Wall Lamp

Model:	VT-852
SKU:	7531
Max.Watts:	60W
Material:	Aluminium, Glass
Color:	Matt Black
Holder:	E27
IP Rating:	IP44
Dimension:	290×250×525mm
Box Qty:	6



Wall Lamp

Model:	VT-730
SKU:	7046
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	200×238mm
Box Qty:	6

Wall Lamp

Model:	VT-853
SKU:	7532
Max.Watts:	60W
Material:	Aluminium, Glass
Color:	Matt Black
Holder:	E27
IP Rating:	IP44
Dimension:	290×250×525mm
Box Qty:	6



Wall Lamp

Model:	VT-731
SKU:	7047
Max.Watts:	40W
Material:	Aluminium+Plastic
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	200×238mm
Box Qty:	6



Wall Lamp

Model:	VT-751-B
SKU:	7070
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	Matt Black
Holder:	E27
IP Rating:	IP44
Dimension:	215×375×170mm
Box Qty:	10



V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Wall Lamp

Model:	VT-751-W
SKU:	7071
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	Matt White
Holder:	E27
IP Rating:	IP44
Dimension:	215×375×170mm
Box Qty:	10



Wall Lamp

Model:	VT-843
SKU:	8686
Max.Watts:	60W
Material:	Aluminium+Glass
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	235×225mm
Box Qty:	10

Wall Lamp

Model:	VT-749-B
SKU:	7066
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	Matt Black
Holder:	E27
IP Rating:	IP44
Dimension:	208×360×170mm
Box Qty:	10



Wall Lamp

Model:	VT-750-B
SKU:	7068
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	Matt Black
Holder:	E27
IP Rating:	IP44
Dimension:	208×360×170mm
Box Qty:	10



Wall Lamp

Model:	VT-749-W
SKU:	7067
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	Matt White
Holder:	E27
IP Rating:	IP44
Dimension:	208×360×170mm
Box Qty:	10



Wall Lamp

Model:	VT-750-W
SKU:	7069
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	Matt White
Holder:	E27
IP Rating:	IP44
Dimension:	208×360×170mm
Box Qty:	10



DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

Ceiling Lamp

Model:	VT-752-B
SKU:	7072
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	Matt Black
Holder:	E27
IP Rating:	IP44
Dimension:	170×840mm
Box Qty:	10



Stand Lamp

Model:	VT-736
SKU:	7059
Max.Watts:	60W
Material:	Aluminium+Glass
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	170×600mm
Box Qty:	10



Ceiling Lamp

Model:	VT-752-W
SKU:	7073
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	White
Holder:	E27
IP Rating:	IP44
Dimension:	170×840mm
Box Qty:	10



Ceiling Lamp

Model:	VT-850
SKU:	7529
Max.Watts:	60W
Material:	Aluminium+PC
Color:	Matt Black
Holder:	E27
IP Rating:	IP44
Dimension:	250×890mm
Box Qty:	8



Ceiling Lamp

Model:	VT-735
SKU:	7058
Max.Watts:	60W
Material:	Aluminium+Plastic
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	170×740mm
Box Qty:	10



Pole Lamp

Model:	VT-839
SKU:	8629
Max.Watts:	40w
Material:	Stainless Steel+PC
Color:	Dark Grey
Holder:	E27
IP Rating:	IP44
Dimension:	Ø148X800mm
Box Qty:	6



V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

Pole Lamp

Model:	VT-851
SKU:	7530
Max.Watts:	60W
Material:	Aluminium+PC
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	250×1110mm
Box Qty:	1



Stand Lamp

Model:	VT-753-W
SKU:	7075
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	Matt White
Holder:	E27
IP Rating:	IP44
Dimension:	170×403mm
Box Qty:	10



Stand Lamp

Model:	VT-734
SKU:	7057
Max.Watts:	60W
Material:	Aluminium+PC
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	170×290mm
Box Qty:	10



Pole Lamp

Model:	VT-845
SKU:	8687
Max.Watts:	60W
Material:	Aluminium+Glass
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	175×950mm
Box Qty:	10



Stand Lamp

Model:	VT-753-B
SKU:	7074
Max.Watts:	40W
Material:	Aluminium+Glass
Color:	Matt Black
Holder:	E27
IP Rating:	IP44
Dimension:	170×403mm
Box Qty:	10



Stand Lamp

Model:	VT-737
SKU:	7060
Max.Watts:	60W
Material:	Aluminium+Glass
Color:	Black
Holder:	E27
IP Rating:	IP44
Dimension:	345×1365mm
Box Qty:	1



DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC®
INNOVATIVE LED LIGHTING

Pole Lamp

Model: VT-847
SKU: 8688
Max.Watts: 60Wx2
Material: Aluminium+Glass
Color: Black
Holder: E27
IP Rating: IP44
Dimension: 522×2320mm
Box Qty: 1



Stand Lamp

Model: VT-740
SKU: 7063
Max.Watts: 60Wx3
Material: Aluminium+Glass
Color: Black
Holder: E27
IP Rating: IP44
Dimension: 500×1990mm
Box Qty: 1



Stand Lamp

Model: VT-738
SKU: 7061
Max.Watts: 60Wx2
Material: Aluminium+Glass
Color: Black
Holder: E27
IP Rating: IP44
Dimension: 480×1410mm
Box Qty: 1



Stand Lamp

Model: VT-739
SKU: 7062
Max.Watts: 60Wx2
Material: Aluminium+Glass
Color: Black
Holder: E27
IP Rating: IP44
Dimension: 500×1990mm
Box Qty: 1





DECORATIVE PENDANTS

Includes all mounting hardware for quick and easy installation and filament vintage style bulb recommended (sold separately).

Key Feature

- Stylish pendant lamps are available in various shapes, materials, and sizes.
- Most suitable with A60, Candle, ST-64 & Globe Bulb Series.
- Easy to Install.
- Vibrant & elegant colors available.

Application

Perfect choice for Hotels, Bars, Commercial & Residential Lighting.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

GALLERY

V-TAC®
INNOVATIVE LED LIGHTING



String Lights

Model:	VT-717S
SKU:	8974
IP Rating:	IP65
Holder Type:	E27
Max Watts:	60W x6
Box Qty:	1Pc
Lampshade:	Black ø250mm (Galvanized Iron)
Bulb Holder:	Brushed Brown Bronze ø49mm (Aluminium)
Cable:	Black (H05RN-F-3×1mm²)
L/S Wireguard:	Black ø256mm (Galvanized Iron)
Catenary Length:	3M Total Length (6 Luminiares at 50cm spacing)

IP65 RATING

EU PLUG



String Lights

Model:	VT-717BS
SKU:	8975
IP Rating:	IP65
Holder Type:	E27
Max Watts:	60W x6
Box Qty:	1Pc
Lampshade:	Natural ø250mm (Galvanized Iron)
Bulb Holder:	Rose Gold ø49mm (Aluminium)
Cable:	Black (H05RN-F-3×1mm²)
L/S Wireguard:	Rose Gold ø256mm (Galvanized Iron)
Catenary Length:	3M Total Length (6 Luminiares at 50cm pacing)

IP65 RATING

EU PLUG



String Lights

Model:	VT-720S
SKU:	8971
IP Rating:	IP65
Holder Type:	E27
Max Watts:	60W x6
Box Qty:	1Pc
Globe:	Clear ø150mm (PMMA)
Bulb Holder:	Brushed Brown Bronze ø49mm (Aluminium)
Cable:	Black (H05RN-F-3×1mm²)
Catenary Length:	3M Total Length (6 Luminiares at 50cm spacing)

IP65 RATING

EU PLUG

E27 Holder | Max 60W
*Bulbs not included

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY



Wall Lamp

Model:	VT-720BW
SKU:	8970
IP Rating:	IP65
Holder Type:	E27
Max Watts:	60W
Box Qty:	8Pc
Globe:	Clear ø150mm (PMMA)
Bulb Holder:	Brushed Brown Bronze ø49mm (Aluminium)
Cable:	Black (H05RN-F-3×0.75mm²)
Wall Lamp Arm:	Black ø14mm (Galvanized Iron)
Wall Mount:	Black ø130mm (Galvanized Iron)

IP65 RATING



Wall Lamp

Model:	VT-720B
SKU:	8972
IP Rating:	IP65
Holder Type:	E27
Max Watts:	60W
Box Qty:	4Pc
Lampshade:	Black ø250mm (Galvanized Iron)
Bulb Holder:	Brushed Brown Bronze (Aluminium)
Cable:	Black (H05RN-F-3×0.75mm²)
Wall Lamp Arm:	Black ø14mm (Galvanized Iron)
Wall Mount:	Black ø130mm (Galvanized Iron)
L/S Wire Guard:	Black ø256mm (Galvanized Iron)

IP65 RATING



Wall Lamp

Model:	VT-720R
SKU:	8973
IP Rating:	IP65
Holder Type:	E27
Max Watts:	60W
Box Qty:	4Pc
Lampshade:	Natural ø250mm (Galvanized Iron)
Bulb Holder:	Rose Gold ø49mm (Aluminium)
Cable:	Black (H05RN-F-3×0.75mm²)
Wall Lamp Arm:	Natural ø14mm (Galvanized Iron)
Wall Mount:	Rose Gold ø130mm (Galvanized Iron)
L/S Wire Guard:	Rose Gold ø256mm (Galvanized Iron)

IP65 RATING

E27 Holder | Max 60W
*Bulbs not included

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Rattan Floor Lamp

Model: VT-4150
SKU: 40561
Material: Rattan Finish
Dimension: Ø400xH1500mm
Box Qty: 1



Wooden Pendant

Model: VT-3350
SKU: 40511
Material: Wooden
Dimension: Ø350xH310mm
Box Qty: 4



Rattan Floor Lamp

Model: VT-3100
SKU: 40571
Material: Rattan Finish
Dimension: Ø300xH940mm
Box Qty: 1



Wooden Pendant

Model: VT-2450
SKU: 40521
Material: Wooden
Dimension: Ø250xH450mm
Box Qty: 4



Wooden Pendant

Model: VT-3450
SKU: 40501
Material: Wooden
Dimension: Ø350xH450mm
Box Qty: 1



Wooden Pendant

Model: VT-3200
SKU: 40531
Material: Wooden
Dimension: Ø330xH220mm
Box Qty: 8

E27 Holder | Max 60W
*Bulbs not included

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Wooden Pendant

Model: VT-4280
SKU: 40541
Material: Wooden
Dimension: Ø440xH280mm
Box Qty: 1

Diamond Cut Glass Black

Model: VT-7350-HB
SKU: 3880
Material: Glass+Metal
Dimension: 330×260×1000mm
Box Qty: 8



Wooden Pendant

Model: VT-4453
SKU: 40551
Material: Wooden
Dimension: Ø450xH450mm
Box Qty: 1

Designer Glass Transparent

Model: VT-7254
SKU: 3882
Material: Glass+Metal
Dimension: Ø250×230×1000mm
Box Qty: 8



Diamond Cut Glass Transparent

Model: VT-7350-HT
SKU: 3879
Material: Glass+Metal
Dimension: Ø330×260×1000mm
Box Qty: 8



Designer Glass Transparent

Model: VT-7305
SKU: 3881
Material: Glass
Dimension: Ø270×1280mm
Box Qty: 4



E27 Holder | Max 60W
*Bulbs not included

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Designer Glass Gun Grey

Model: VT-7292
SKU: 3887
Material: Glass
Dimension: Ø300×265×1000mm
Box Qty: 8



Transparent Glass Metal Series

Model: VT-7229
SKU: 3867
Material: Glass+Metal
Dimension: 265×190×1000mm
Box Qty: 8



Designer Glass Gun Grey

Model: VT-7380
SKU: 3888
Material: Glass
Dimension: Ø380×330×1000mm
Box Qty: 4



Double Glass Amber White

Model: VT-7181-AW
SKU: 3878
Material: Glass+Metal
Dimension: 180×350×1000mm
Box Qty: 9



Transparent Glass Metal Series

Model: VT-7302
SKU: 3865
Material: Glass+Metal
Dimension: 300×280×1000mm
Box Qty: 8



Double Glass Gungrey White

Model: VT-7304-GW
SKU: 3876
Material: Glass+Metal
Dimension: 250×420×1000mm
Box Qty: 8



E27 Holder | Max 60W
*Bulbs not included

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Modern White Glass Pendant

Model: VT-7281-WG
SKU: 3884
Material: Glass+Metal
Dimension: Ø285×440×1000mm
Box Qty: 4



Amber Glass Metal Series

Model: VT-7140-A
SKU: 3736
Material: Glass+Metal
Dimension: 140×240×1130mm
Box Qty: 12



Modern Black Glass Pendant

Model: VT-7281-BG
SKU: 3885
Material: Glass+Metal
Dimension: 285×440×1000mm
Box Qty: 4



Transparent Glass Metal Series

Model: VT-7140-T
SKU: 3735
Material: Glass+Metal
Dimension: 140×240×1130mm
Box Qty: 8



Glass Metal Series

Model: VT-7210
SKU: 3730
Material: Glass+Metal
Dimension: 245×230×1100mm
Box Qty: 8



Transparent Glass Metal Series

Model: VT-7185
SKU: 3738
Material: Glass+Metal
Dimension: 180×230×1110mm
Box Qty: 12



E27 Holder | Max 60W
*Bulbs not included

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Transparent Glass Metal Series

Model: VT-7300
SKU: 3737
Material: Glass+Metal
Dimension: 300×250×1150mm
Box Qty: 8



Transparent Glass Pendant

Model: VT-7220-T
SKU: 3727
Material: Glass+Metal
Dimension: 220×280×1150mm
Box Qty: 8



Amber Glass Metal Series

Model: VT-7150-AG
SKU: 3732
Material: Glass+Metal
Dimension: 145×160×1050mm
Box Qty: 12



3D Glass Black Canopy

Model: VT-7152
SKU: 40111
Material: Glass
Dimension: ø150×100×1020mm
Box Qty: 8



Amber Glass Pendant

Model: VT-7220-A
SKU: 3726
Material: Glass+Metal
Dimension: 220×280×1150mm
Box Qty: 8



3D Glass Black Canopy

Model: VT-7206
SKU: 40121
Material: Glass
Dimension: ø200×100×1070mm
Box Qty: 8



E27 Holder | Max 60W
*Bulbs not included

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

3D Glass Black Canopy

Model: VT-7256
SKU: 40131
Material: Glass
Dimension: ø250×100×1110mm
Box Qty: 8



Mesh Metal Grey

Model: VT-7200-MG
SKU: 3822
Material: Metal
Dimension: 200×270×1300mm
Box Qty: 8



Aluminium Shade Black

Model: VT-7422-B
SKU: 3728
Material: Aluminium
Dimension: 230×310×1150mm
Box Qty: 8



Mesh Metal Gold

Model: VT-7200-CG
SKU: 3821
Material: Metal
Dimension: 200×270×1300mm
Box Qty: 8



Aluminium Shade White

Model: VT-7422-WH
SKU: 3729
Material: Aluminium
Dimension: 230×310×1150mm
Box Qty: 8



Mesh Metal White

Model: VT-7200-MW
SKU: 3823
Material: Metal
Dimension: 200×270×1300mm
Box Qty: 8



E27 Holder | Max 60W
*Bulbs not included

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Can Shape Gold Pendant

Model: VT-7131-CG
SKU: 3824
Material: Metal
Dimension: 130×250×1300mm
Box Qty: 10



Can Shape Gold Pendant

Model: VT-7132-CG
SKU: 3827
Material: Metal
Dimension: 130×220×1300mm
Box Qty: 10



Can Shape Black Pendant

Model: VT-7131-MB
SKU: 3825
Material: Metal
Dimension: 130×250×1300mm
Box Qty: 10



Can Shape Black Pendant

Model: VT-7132-MB
SKU: 3828
Material: Metal
Dimension: 130×220×1300mm
Box Qty: 10



Can Shape WhitePendant

Model: VT-7131-MW
SKU: 3826
Material: Metal
Dimension: 130×250×1300mm
Box Qty: 10



Can Shape WhitePendant

Model: VT-7132-MW
SKU: 3829
Material: Metal
Dimension: 130×220×1300mm
Box Qty: 10



E27 Holder | Max 60W
*Bulbs not included

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Mesh Metal Globe

Model: VT-7332
SKU: 3859
Material: Metal
Dimension: Ø290×1000×1340mm
Box Qty: 8



Copper Series Rose Gold

Model: VT-8300
SKU: 3710
Material: Iron+ copper paint
Dimension: Ø300
Box Qty: 4

Mesh Metal GV Shape

Model: VT-7252
SKU: 3860
Material: Metal
Dimension: 285×170×1000mm
Box Qty: 12



Copper Series Rose Gold

Model: VT-8220
SKU: 3711
Material: Iron+ copper paint
Dimension: Ø220
Box Qty: 4

Copper Series Rose Gold

Model: VT-8150-CO
SKU: 3713
Material: Metal
Dimension: Ø150
Box Qty: 10

Copper Series Rose Gold

Model: VT-8255
SKU: 3709
Material: Iron+ copper paint
Dimension: Ø250mm
Box Qty: 4

E27 Holder | Max 60W
*Bulbs not included

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Copper Series Chrome

Model: VT-8150-CH
SKU: 3712
Material: Iron+ copper paint
Dimension: Ø150mm
Box Qty: 10

Copper Series Rose Gold

Model: VT-8170
SKU: 3714
Material: Iron+ Copper Paint
Dimension: Ø170mm
Box Qty: 8

Copper Series Chrome

Model: VT-8180-CH
SKU: 3707
Material: Iron+ copper paint
Dimension: Ø180mm
Box Qty: 4



Copper Series Rose Gold

Model: VT-8230
SKU: 3715
Material: Iron+ Copper Paint
Dimension: Ø230mm
Box Qty: 4

Copper Series Rose Gold

Model: VT-8180-CO
SKU: 3708
Material: Iron+ Copper Paint
Dimension: Ø180mm
Box Qty: 8

Copper Series Chrome

Model: VT-8175-CH
SKU: 3705
Material: Iron+ Copper Paint
Dimension: Ø170
Box Qty: 4

E27 Holder | Max 60W
*Bulbs not included

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Copper Series Rose Gold

Model: VT-8175-CO
SKU: 3706
Material: Iron+ Copper Paint
Dimension: Ø170mm
Box Qty: 8

Concrete Lampshade

Model: VT-7202
SKU: 3853
Material: Concrete
Dimension: 180×160×1100mm
Box Qty: 4





Copper Series Rose Gold

Model: VT-8200
SKU: 3716
Material: Iron+ Copper Paint
Dimension: Ø200mm
Box Qty: 4

Concrete Wooden

Model: VT-7125-R
SKU: 3857
Material: Concrete+Wood
Dimension: 120×210×1080mm
Box Qty: 8





Copper Series Rose Gold

Model: VT-8250
SKU: 3717
Material: Iron+ Copper Paint
Dimension: Ø250mm
Box Qty: 4

Concrete Table Lamp

Model: VT-7160
SKU: 3851
Material: Concrete
Dimension: 160×150×2000mm
Box Qty: 4



E27 Holder | Max 60W
*Bulbs not included

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Concrete Table Lamp

Model: VT-7171
SKU: 3852
Material: Concrete
Dimension: 180×130×2000mm
Box Qty: 8



Geometric Series Gold Canopy

Model: VT-7161-CG
SKU: 3833
Material: Metal
Dimension: 225×225×1250mm
Box Qty: 10



Geometric Series Gold Canopy

Model: VT-7141-CG
SKU: 3831
Material: Metal
Dimension: 250×190×1250mm
Box Qty: 8



Geometric Series Black Canopy

Model: VT-7161-MB
SKU: 3834
Material: Metal
Dimension: 225×225×1250mm
Box Qty: 8



Geometric Series Black Canopy

Model: VT-7141-MB
SKU: 3832
Material: Metal
Dimension: 250×190×1250mm
Box Qty: 8



Geometric Series Black Canopy

Model: VT-7144
SKU: 3927
Material: Metal Finish
Dimension: 300×1300mm
Box Qty: 4



E27 Holder | Max 60W
*Bulbs not included

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Geometric Series Gold Canopy

Model: VT-7322-CG
SKU: 3835
Material: Metal
Dimension: 320×320×1350mm
Box Qty: 10



Geometric Series Black Canopy

Model: VT-7321-MB
SKU: 3838
Material: Metal
Dimension: 320×320×1350mm
Box Qty: 10



Geometric Series Black Canopy

Model: VT-7322-MB
SKU: 3836
Material: Metal
Dimension: 320×320×1350mm
Box Qty: 10



Aluminium Sand finish Black

Model: VT-7520-B
SKU: 3700
Material: Aluminium+Sand Finish
Dimension: 220×310×1375mm
Box Qty: 4



Geometric Series Gold Canopy

Model: VT-7321-CG
SKU: 3837
Material: Metal
Dimension: 320×320×1350mm
Box Qty: 10



Aluminium Sand finish Grey

Model: VT-7520-G
SKU: 3701
Material: Aluminium+Sand Finish
Dimension: 220×310×1375mm
Box Qty: 4



E27 Holder | Max 60W
*Bulbs not included

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Aluminium Sand finish White

Model: VT-7520-WH
SKU: 3702
Material: Aluminium+Sand Finish
Dimension: 220×310×1375mm
Box Qty: 4



Wooden Top Iron White

Model: VT-7525-WH
SKU: 3761
Material: Iron+Wooden Top
Dimension: 250×400×1200mm
Box Qty: 8



Modern Wooden Top White

Model: VT-7425-WH
SKU: 3756
Material: Aluminium+Wood
Dimension: 250×200×1100mm
Box Qty: 8



Wooden Top Iron Black

Model: VT-7525-B
SKU: 3762
Material: Iron+Wooden Top
Dimension: 250×400×1200mm
Box Qty: 8



Modern Wooden Top Black

Model: VT-7425-B
SKU: 3757
Material: Aluminium+Wood
Dimension: 250×200×1100mm
Box Qty: 8



Wooden Top Iron White

Model: VT-7535-W
SKU: 3763
Material: Iron+Wooden Top
Dimension: 350×300×1100mm
Box Qty: 8



E27 Holder | Max 60W
*Bulbs not included

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Wooden Top Iron Black

Model: VT-7535-B
SKU: 3764
Material: Iron+Wooden Top
Dimension: 350×300×1100mm
Box Qty: 8



Pendant Aluminium Shade White

Model: VT-7100-WH
SKU: 3920
Material: Plastic+Aluminium
Dimension: 180×100×1200mm
Box Qty: 12



Wooden Top Iron White

Model: VT-7545-WH
SKU: 3765
Material: Iron+Wooden Top
Dimension: 350×300×1100mm
Box Qty: 8



Pendant Aluminium Shade Black

Model: VT-7100-B
SKU: 3921
Material: Plastic+Aluminium
Dimension: 180×100×1200mm
Box Qty: 12



Wooden Top Iron Black

Model: VT-7545-B
SKU: 3766
Material: Iron+Wooden Top
Dimension: 350×300×1100mm
Box Qty: 8



Pendant Aluminium Shade Grey

Model: VT-7100-G
SKU: 3922
Material: Plastic+Aluminium
Dimension: 180×100×1200mm
Box Qty: 12



E27 Holder | Max 60W
*Bulbs not included

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Pendant Aluminium Shade Pink

Model: VT-7100-P
SKU: 3923
Material: Plastic+Aluminium
Dimension: 180×100×1200mm
Box Qty: 12



Metal Plate Rose Gold

Model: VT-7777-RG
SKU: 3751
Material: Metal
Dimension: 300×90×1000mm
Box Qty: 20



Pendant Aluminium Shade Red

Model: VT-7100-R
SKU: 3924
Material: Plastic+Aluminium
Dimension: 180×100×1200mm
Box Qty: 12



Metal Plate Matt Gold

Model: VT-7777-MG
SKU: 3752
Material: Metal
Dimension: 300×90×1000mm
Box Qty: 20



Pendant Aluminium Shade Blue

Model: VT-7100-BL
SKU: 3925
Material: Plastic+Aluminium
Dimension: 180×100×1200mm
Box Qty: 12



Prism Blue Pendant

Model: VT-7310-B
SKU: 3946
Material: Metal
Dimension: 310×190mm
Box Qty: 4

E27 Holder | Max 60W
*Bulbs not included

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Prism Yellow Pendant

Model: VT-7310-Y
SKU: 3947
Material: Metal
Dimension: 310×190mm
Box Qty: 4

Cone Prism White

Model: VT-7255-W
SKU: 3952
Material: Metal
Dimension: 250×255mm
Box Qty: 4

Prism White Pendant

Model: VT-7310-W
SKU: 3948
Material: Metal
Dimension: 310×190mm
Box Qty: 4

Cone Prism Blue

Model: VT-7255-B
SKU: 3953
Material: Metal
Dimension: 250×255mm
Box Qty: 4

Prism Wooden Yellow

Model: VT-7323-Y
SKU: 3950
Material: Metal
Dimension: 320×270mm
Box Qty: 4



Vintage Metal

Model: VT-7424
SKU: 3753
Material: Metal
Dimension: 260×170×1080mm
Box Qty: 12



E27 Holder | Max 60W
*Bulbs not included

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Vintage Metal Pulley

Model: VT-7201
SKU: 3845
Material: Metal
Dimension: 220×140×600–1600mm
Box Qty: 8



Pendant Holder Bottle E14

Model: VT-7558-GN
SKU: 3767
Material: Glass
Dimension: 72×280×1150mm
Box Qty: 25



Pendant Hemp Rope

Model: VT-7118
SKU: 3754
Material: Rope
Dimension: 45×57×1500mm
Box Qty: 12



Pendant Holder Bottle E14

Model: VT-7558-BL
SKU: 3768
Material: Glass
Dimension: 72×280×1150mm
Box Qty: 25



Globe Chrome Canopy

Model: VT-7251
SKU: 3839
Material: Acrylic Glass
Dimension: 250×250×1300mm
Box Qty: 4



Pendant Holder Bottle E14

Model: VT-7558-R
SKU: 3769
Material: Glass
Dimension: 72×280×1150mm
Box Qty: 25



E27 Holder | Max 60W
*Bulbs not included

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Pendant Holder Bottle E14

Model: VT-7558-A
SKU: 3770
Material: Glass
Dimension: 72×280×1150mm
Box Qty: 25



Pendant Holder Bottle E14

Model: VT-7558-Y
SKU: 3773
Material: Glass
Dimension: 72×280×1150mm
Box Qty: 25



Pendant Holder Bottle E14

Model: VT-7558-T
SKU: 3771
Material: Glass
Dimension: 72×280×1150mm
Box Qty: 25





Pendant Holder Bottle E14

Model: VT-7558-RO
SKU: 3774
Material: Glass
Dimension: 72×280×1150mm
Box Qty: 25



Pendant Holder Bottle E14

Model: VT-7558-P
SKU: 3772
Material: Glass
Dimension: 72×280×1150mm
Box Qty: 25



Pendant Holder Bottle E14

Model: VT-7558-GY
SKU: 3775
Material: Glass
Box Qty: 25



Pendant Holder Bottle E14

Model: VT-7558-BR
SKU: 3776
Material: Glass
Box Qty: 25



E14 Holder | Max 60W
*Bulbs not included

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Model: VT-7555-BBR
SKU: 3841
Material: Metal
Dimension: Ø50×90×900mm
Color: Brown Bronze
Box Qty: 30

Model: VT-7778-BL
SKU: 3722
Material: Wooden
Dimension: 73×102×1000mm
Color: Blue Wire
Box Qty: 50

Model: VT-7998-BK
SKU: 3804
Material: Porcelain
Dimension: Ø105×750mm
Color: Black
Box Qty: 60

Model: VT-7998Y
SKU: 3809
Material: Porcelain
Dimension: Ø105×750mm
Color: Yellow
Box Qty: 60

Model: VT-7555-BB
SKU: 3842
Material: Metal
Dimension: Ø50×90×900mm
Color: Brass Bronze
Box Qty: 30

Model: VT-7778-R
SKU: 3723
Material: Wooden
Dimension: 73×102×1000mm
Color: Red Wire
Box Qty: 50

Model: VT-7998-GN
SKU: 3805
Material: Porcelain
Dimension: Ø105×750mm
Color: Green
Box Qty: 60

Model: VT-7998-BR
SKU: 3810
Material: Porcelain
Dimension: Ø105×750mm
Color: Brown
Box Qty: 60

Model: VT-7555-BR
SKU: 3843
Material: Metal
Dimension: Ø50×90×900mm
Color: Bronze
Box Qty: 30

Model: VT-7778-PR
SKU: 3724
Material: Wooden
Dimension: 73×102×1000mm
Color: Purple Wire
Box Qty: 50

Model: VT-7998-BL
SKU: 3806
Material: Porcelain
Dimension: Ø105×750mm
Color: Blue
Box Qty: 60

Model: VT-799-W
SKU: 3795
Material: Porcelain
Dimension: Ø47×64mm
Color: White
Box Qty: 100

Model: VT-7555-MG
SKU: 3844
Material: Metal
Dimension: Ø50×90×900mm
Color: Gold
Box Qty: 30

Model: VT-7778-GN
SKU: 3725
Material: Wooden
Dimension: 73×102×1000mm
Color: Green Wire
Box Qty: 50

Model: VT-7998-R
SKU: 3807
Material: Porcelain
Dimension: Ø105×750mm
Color: Red
Box Qty: 60

Model: VT-799-BK
SKU: 3796
Material: Porcelain
Dimension: Ø47×64mm
Color: Black
Box Qty: 100

Model: VT-7778-W
SKU: 3720
Material: Wooden
Dimension: 73×102×1000mm
Color: White Wire
Box Qty: 50

Model: VT-7998-W
SKU: 3803
Material: Porcelain
Dimension: Ø105×750mm
Color: White
Box Qty: 60

Model: VT-7998-GY
SKU: 3808
Material: Porcelain
Dimension: Ø105×750mm
Color: Grey
Box Qty: 60

Model: VT-799-GN
SKU: 3797
Material: Porcelain
Dimension: Ø47×64mm
Color: Green
Box Qty: 100

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Model: VT-799-BL
SKU: 3798
Material: Porcelain
Dimension: Ø47×64mm
Color: Blue
Box Qty: 100

Model: VT-7668-GN
SKU: 3742
Material: Concrete
Dimension: 50×95×1050mm
Color: Green
Box Qty: 40

Model: VT-7668-BR
SKU: 3749
Material: Concrete
Dimension: 50×95×1050mm
Color: Brown
Box Qty: 40

Model: VT-7338-BN
SKU: 3784
Material: Chrome
Dimension: Ø39×1000mm
Color: Brown Wire
Box Qty: 40

Model: VT-799-R
SKU: 3799
Material: Porcelain
Dimension: Ø47×64mm
Color: Red
Box Qty: 100

Model: VT-7668-R
SKU: 3743
Material: Concrete
Dimension: 50×95×1050mm
Color: Red
Box Qty: 40

Model: VT-7668-BE
SKU: 3750
Material: Concrete
Dimension: 50×95×1050mm
Color: Beige
Box Qty: 40

Model: VT-7338-GN
SKU: 3785
Material: Chrome
Dimension: Ø39×1000mm
Color: Green Wire
Box Qty: 40

Model: VT-799-GY
SKU: 3800
Material: Porcelain
Dimension: Ø47×64mm
Color: Grey
Box Qty: 100

Model: VT-7668-BL
SKU: 3744
Material: Concrete
Dimension: 50×95×1050mm
Color: Blue
Box Qty: 40

Model: VT-7448
SKU: 3777
Material: Chrome
Dimension: Ø39×1000mm
Color: Rose Gold Set
Box Qty: 40

Model: VT-7338-GY
SKU: 3786
Material: Chrome
Dimension: Ø39×1000mm
Color: Grey Wire
Box Qty: 1

Model: VT-799-Y
SKU: 3801
Material: Porcelain
Dimension: Ø47×64mm
Color: Yellow
Box Qty: 100

Model: VT-7668-Y
SKU: 3745
Material: Concrete
Dimension: 50×95×1050mm
Color: Yellow
Box Qty: 40

Model: VT-7338-W
SKU: 3755
Material: Chrome
Dimension: Ø39×1000mm
Color: White Wire
Box Qty: 40



Model: VT-7338-LB
SKU: 3787
Material: Chrome
Dimension: Ø39×1000mm
Color: Light Blue Wire
Box Qty: 40

Model: VT-799-BR
SKU: 3802
Material: Porcelain
Dimension: Ø47×64mm
Color: Brown
Box Qty: 100

Model: VT-7668-W
SKU: 3746
Material: Concrete
Dimension: 50×95×1050mm
Color: White
Box Qty: 40



Model: VT-7338-BL
SKU: 3783
Material: Chrome
Dimension: Ø39×1000mm
Color: Blue Wire
Box Qty: 40

Model: VT-7338-O
SKU: 3788
Material: Chrome
Dimension: Ø39×1000mm
Color: Orange Wire
Box Qty: 40

GALLERY

V-TAC®
INNOVATIVE LED LIGHTING

Model: VT-7338-PK
SKU: 3789
Material: Chrome
Dimension: Ø39×1000mm
Color: Pink Wire
Box Qty: 1



Model: VT-7338-BE
SKU: 3794
Material: Chrome
Dimension: Ø39×1000mm
Color: Beige Wire
Box Qty: 40

Model: VT-7228-R
SKU: 3480
Material: Silicone
Dimension: Ø40×1000mm
Color: Red
Box Qty: 100

Model: VT-7228-GN
SKU: 3486
Material: Silicone
Dimension: Ø40×1000mm
Color: Green
Box Qty: 100

Model: VT-7338-PE
SKU: 3790
Material: Chrome
Dimension: Ø39×1000mm
Color: Purple Wire
Box Qty: 40

Model: VT-7228-BN
SKU: 3475
Material: Silicone
Dimension: Ø40×1000mm
Color: Brown
Box Qty: 100

Model: VT-7228-GY
SKU: 3481
Material: Silicone
Dimension: Ø40×1000mm
Color: Grey
Box Qty: 100

Model: VT-7338-R
SKU: 3791
Material: Chrome
Dimension: Ø39×1000mm
Color: Red Wire
Box Qty: 40

Model: VT-7228-BE
SKU: 3476
Material: Silicone
Dimension: Ø40×1000mm
Color: Blue
Box Qty: 100

Model: VT-7228-LB
SKU: 3482
Material: Silicone
Dimension: Ø40×1000mm
Color: Light Blue
Box Qty: 100

Model: VT-7338-RR
SKU: 3792
Material: Chrome
Dimension: Ø39×1000mm
Color: Rose Red Wire
Box Qty: 40

Model: VT-7228-W
SKU: 3477
Material: Silicone
Dimension: Ø40×1000mm
Color: White
Box Qty: 100

Model: VT-7228-PE
SKU: 3483
Material: Silicone
Dimension: Ø40×1000mm
Color: Purple
Box Qty: 100

Model: VT-7338-Y
SKU: 3793
Material: Chrome
Dimension: Ø39×1000mm
Color: Yellow Wire
Box Qty: 40

Model: VT-7228-PN
SKU: 3479
Material: Silicone
Dimension: Ø40×1000mm
Color: Pink
Box Qty: 100

Model: VT-7228-O
SKU: 3484
Material: Silicone
Dimension: Ø40×1000mm
Color: Orange
Box Qty: 100

E27 Holder | Max 60W



DECORATIVE LIGHTS

Offering cutting edge designs as per your mood. From warm to bright task lighting, Our selection of mirror lights, LED pendant lights, and chandeliers will light up any decor.

Key Feature

- Stylish pendant lamps available in various shapes, material, and sizes.
- Most suitable with A60, Candle, ST-64 & Globe Bulb Series.
- Easy to Install.
- Vibrant & elegant colors available.

Application

Perfect choice for Hotels, Bars, Commercial & Residential Lighting.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Mirror Lights

- AC:200-240V,50/60Hz
- CRI: >80
- 120° Beam Angle
- Body Type: Iron
- IP Rating:IP44

Anti-fog
With demister pad



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-8505	40441 - 6400K WHITE	17w	600	H:500xW:390xT:35mm	1
VT-8700	40451 - 6400K WHITE	30w	750	H:700xW:500xT:35mm	1
VT-8700-N	2140451 - 6400K WHITE	35w	95	H:700xW:500xT:35mm	1
VT-8800	40471 - 6400K WHITE	38w	700	H:800xW:600xT:35mm	1
VT-8800-N	2140471 - 6400K WHITE	42w	100	H:800xW:600xT:35mm	1

Mirror Lights Touch Switch

- AC:200-240V,50/60Hz
- CRI: >80
- 120° Beam Angle
- Body Type: Iron
- IP Rating:IP44

TOUCH CONTROL

Anti-fog
With demister pad

COLOR CHANGING
(3000K-4000K-6400K)



Model	SKU	Watts	Lumen	Box Qty
VT-8701	40461 - 3IN1	37w	800	1

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Mirror Lights

- AC:200-240V,50/60Hz
- CRI: >80
- 120° Beam Angle
- Body Type: Iron
- IP Rating:IP44

Anti-fog
With demister pad



Model	SKU	Watts	Lumen	Box Qty
VT-8601	40481 - 6400K WHITE	25w	750	1

Mirror Lights Touch Switch

- AC:200-240V,50/60Hz
- CRI: >80
- 120° Beam Angle
- Body Type: Iron
- IP Rating:IP44

TOUCH CONTROL

Anti-fog
With demister pad

COLOR CHANGING
(3000K-4000K-6400K)



Model	SKU	Watts	Lumen	Box Qty
VT-8602	40491 - 3IN1	25w	750	1
VT-8602-N	2140491 - 3IN1	25w	85	1

Mirror Light Picture Lamp Chrome

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Metal+PMMA

Built In LED





Model	SKU	Watts	Lumen	Box Qty
VT-7008	3894 - 4000K DAY WHITE	8w	600	12
VT-7008-N	213985 - 3000K WARM WHITE 213894 - 4000K DAY WHITE	9w	3000K-550 4000K-580	12

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Mirror Light Picture Lamp Chrome

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Metal+PMMA

Built In LED





Model	SKU	Watts	Lumen	Box Qty
VT-7012	3895 - 4000K DAY WHITE	12w	900	12
VT-7012-N	213982 - 3000K WARM WHITE 213895 - 4000K DAY WHITE	13w	3000K-850 4000K-910	12

Mirror Lamp Movable

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Stainless Steel+Aluminium+PMMA

Built In LED





Model	SKU	Watts	Lumen	Box Qty
VT-7009CH	3900 - 4000K DAY WHITE	8w	600	11
VT-7009CH-N	213984 - 3000K WARM WHITE 213900 - 4000K DAY WHITE	9w	3000K-380 4000K-420	11

Mirror Light Picture Lamp Golden

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Stainless Steel+Aluminium+PMMA

Built In LED



Model	SKU	Watts	Lumen	Box Qty
VT-7009	3901 - 4000K DAY WHITE	8w	600	11
VT-7009-N	213983 - 3000K WARM WHITE 213901 - 4000K DAY WHITE	9w	350	11

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Mirror Surface Light-Chrome

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Stainless Steel+Metal+PMMA

Built In LED





Model	SKU	Watts	Lumen	Box Qty
VT-7037	3893 - 4000K DAY WHITE	36w	2700	6

Mirror Light Chrome Cap

- AC:220-240V,50/60Hz
- CRI: >80
- 150° Beam Angle
- IP Rating:IP44
- Body Type: Aluminium+PC

Built In LED





Model	SKU	Watts	Lumen	Box Qty
VT-7010-CH	3917 - 6400K WHITE 3916 - 4000K DAY WHITE	10w	950	10

Mirror Light White Cap

- AC:220-240V,50/60Hz
- CRI: >80
- 150° Beam Angle
- IP Rating:IP44
- Body Type: Aluminium+PC

Built In LED





Model	SKU	Watts	Lumen	Box Qty
VT-7010-WH	3919 - 6400K WHITE 3918 - 4000K DAY WHITE	10w	950	10

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Designer Bend Series Chrome

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Stainless Steel+Metal+Glass

Built In LED





Model	SKU	Watts	Lumen	Box Qty
VT-7038	3899 - 4000K DAY WHITE	36w	2700	6

Designer Bend Glass Hanging Pendant

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Stainless Steel+Metal+Glass

Built In LED





Model	SKU	Watts	Lumen	Box Qty
VT-7020	3898 - 4000K DAY WHITE	18w	1350	6

Designer Sleek Pendant Chrome

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Stainless Steel+Metal+PMMA

Built In LED





Model	SKU	Watts	Lumen	Box Qty
VT-7036	3892 - 4000K DAY WHITE	36w	2700	12

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Pendant Light Gold Lamp Shade

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Metal Finish
- Box Qty: 12

Built In LED



Model	SKU	Watts	Lumen
VT-7333-G	3934 - 3000K WARM WHITE 3928 - 4000K DAY WHITE	7w	400

Pendant Light Gold Lamp Shade

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Metal Finish
- Box Qty: 8

Built In LED



Model	SKU	Watts	Lumen
VT-7444-G	3936 - 3000K WARM WHITE 3930 - 4000K DAY WHITE	7w	400

Pendant Light White Lamp Shade

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Metal Finish
- Box Qty: 8

Built In LED



Model	SKU	Watts	Lumen
VT-7444-WH	3937 - 3000K WARM WHITE 3931 - 4000K DAY WHITE	7w	400

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Pendant Light Gold Lamp Shade

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Metal Finish
- Box Qty: 4

Built In LED



Model	SKU	Watts	Lumen
VT-7666-G	3938 – 3000K WARM WHITE 3932 – 4000K DAY WHITE	7w	400

Pendant Light White Lamp Shade

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Metal Finish
- Box Qty: 4

Built In LED



Model	SKU	Watts	Lumen
VT-7666-WH	3939 – 3000K WARM WHITE 3933 – 4000K DAY WHITE	7w	400

Pendant Light Surface

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Iron+Acrylic
- Box Qty: 1

Built In LED

DIMMABLE
LIGHT CONTROL



Model	SKU	Watts	Lumen
VT-25-1-W	3992 -3000K WARM WHITE	20w	1500

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Pendant Light Surface

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Iron+Acrylic
- Box Qty: 1

Built In LED

DIMMABLE
LIGHT CONTROL



Model	SKU	Watts	Lumen
VT-25-1-B	3993 -3000K WARM WHITE	20w	1500

Pendant Light Surface

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Iron+Acrylic
- Box Qty: 1

Built In LED

DIMMABLE
LIGHT CONTROL



Model	SKU	Watts	Lumen
VT-25-1-C	3994 -3000K WARM WHITE	20w	1500

Pendant Light Surface

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Iron+Acrylic
- Box Qty: 1

Built In LED

DIMMABLE
LIGHT CONTROL



Model	SKU	Watts	Lumen
VT-32-1-W	3995 -3000K WARM WHITE	30w	2250

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Pendant Light Surface

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Iron+Acrylic
- Box Qty: 1

Built In LED

DIMMABLE LIGHT CONTROL



Model	SKU	Watts	Lumen
VT-32-1-B	3996 -3000K WARM WHITE	30w	2250

Pendant Light Surface

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Iron+Acrylic
- Box Qty: 1

Built In LED

DIMMABLE LIGHT CONTROL



Model	SKU	Watts	Lumen
VT-32-1-C	3997 -3000K WARM WHITE	30w	2250

Wall Lamp TRIAC Dimmable

- AC:220-240V
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC + Iron
- Box Qty: 1

TRIAC DIMMABLE



Model	SKU	Watts	Lumen
VT-7203	40041 - 3000K WARM WHITE	12w	1000

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Wall Lamp TRIAC Dimmable

- AC:220-240V
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC + Iron
- Box Qty: 1



TRIAC DIMMABLE

Model	SKU	Watts	Lumen
VT-7352	40051 - 3000K WARM WHITE	25w	2100

Wall Lamp TRIAC Dimmable

- AC:220-240V
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC + Iron
- Box Qty: 1



TRIAC DIMMABLE

Model	SKU	Watts	Lumen
VT-7503	40061 - 3000K WARM WHITE	40w	3100

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1



COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen
VT-7308	3966 -3IN1	22w	2100

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1



COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen
VT-7462	3967 -3IN1	32w	3100

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1



COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen
VT-7609	3968 -3IN1	38w	3300

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1



COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen
VT-7752	3969 -3IN1	82w	7300

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen
VT-7309	3970 -3IN1	26w	2600

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1



COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen
VT-7463	3971 -3IN1	40w	3600

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1



COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen
VT-7610	3972 -3IN1	42w	3400

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Designer Series Double Pendant

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen
VT-7753	3973 -3IN1	80w	6600

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1



COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen
VT-7460	3958 -3IN1	32w	3100

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1



COLOR CHANGING WITH REMOTE

Model	SKU	Watts	Lumen
VT-7605	3959 -3IN1	38w	3300

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

COLOR CHANGING WITH REMOTE



Model	SKU	Watts	Lumen
VT-7750	3960 -3IN1	82w	7300

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

COLOR CHANGING WITH REMOTE



Model	SKU	Watts	Lumen
VT-7461	3962 -3IN1	40w	3600

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

COLOR CHANGING WITH REMOTE





Model	SKU	Watts	Lumen
VT-7607	3963 -3IN1	42w	3400

GALLERY

V-TAC®
INNOVATIVE LED LIGHTING

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

COLOR CHANGING WITH REMOTE





Model	SKU	Watts	Lumen
VT-7751	3964 -3IN1	80w	6600

Table Lamp Touch Dimmable

- AC:220-240V
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC + Iron
- Box Qty: 6

TOUCH DIMMING



Model	SKU	Watts	Lumen
VT-7204	40071 - 3000K WARM WHITE	12w	1200

Table Lamp Touch Dimmable

- AC:220-240V
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC + Iron
- Box Qty: 1

TOUCH DIMMING



Model	SKU	Watts	Lumen
VT-7353	40081 - 3000K WARM WHITE	25w	2550

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Wall Lamp TRIAC Dimmable

- AC:220-240V
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC + Iron
- Box Qty: 6

TRIAC DIMMABLE



Model	SKU	Watts	Lumen
VT-7331	40091 - 3000K WARM WHITE	20w	1700

Designer Series TRIAC Dimmable

- AC:220-240V
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC + Iron
- Box Qty: 1

TRIAC DIMMABLE



Model	SKU	Watts	Lumen
VT-7351	40021 - 3000K WARM WHITE	25w	2100

Designer Series TRIAC Dimmable

- AC:220-240V
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC + Iron
- Box Qty: 1

TRIAC DIMMABLE



Model	SKU	Watts	Lumen
VT-7502	40031 - 3000K WARM WHITE	40w	3200

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Designer Series TRIAC Dimmable

- AC:220-240V
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC + Iron
- Box Qty: 1

TRIAC DIMMABLE





Model	SKU	Watts	Lumen
VT-7390	40011 - 3000K WARM WHITE	72w	6500

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

DIMMABLE LIGHT CONTROL

COLOR CHANGING WITH REMOTE



Model	SKU	Watts	Lumen
VT-7606	3961 -3IN1	60w	5400

Designer Series Color Changing

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

DIMMABLE LIGHT CONTROL

COLOR CHANGING WITH REMOTE



Model	SKU	Watts	Lumen
VT-7608	3965 -3IN1	68w	6000

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Designer Series TRIAC Dimmable

- AC:220-240V
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC + Iron
- Box Qty: 1

TRIAC DIMMABLE



Model	SKU	Watts	Lumen
VT-7910	40101 - 3000K WARM WHITE	105w	6300

Designer Series TRIAC Dimmable

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

TRIAC DIMMABLE



Model	SKU	Watts	Lumen
VT-7049	3978 -3000K WARM WHITE	32w	2100

Designer Series TRIAC Dimmable

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

TRIAC DIMMABLE



Model	SKU	Watts	Lumen
VT-7072	3979 -3000K WARM WHITE	52w	3400

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Designer Series TRIAC Dimmable

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

TRIAC DIMMABLE



Model	SKU	Watts	Lumen
VT-7027	3980 -3000K WARM WHITE	18w	1200

Designer Series TRIAC Dimmable

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

TRIAC DIMMABLE





Model	SKU	Watts	Lumen
VT-7050	3981 -3000K WARM WHITE	32w	2100

Wall Lamp TRIAC Dimmable

- AC:220-240V,50/60Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC+Iron
- Box Qty: 1

TRIAC DIMMABLE



Model	SKU	Watts	Lumen
VT-7025	3974 - 3000K WARM WHITE	18w	1200

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Table Lamp Touch Dimmable

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

TOUCH DIMMING



Model	SKU	Watts	Lumen
VT-7026	3975 3000K WARM WHITE	18w	1200

Floor Lamp Touch Dimming

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1

TOUCH DIMMING



Model	SKU	Watts	Lumen
VT-7048	3976 3000K WARM WHITE	32w	2100

Floor Lamp

- AC:220-240V,50Hz
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: PC
- Box Qty: 1





Model	SKU	Watts	Lumen
VT-7096	3977 3000K WARM WHITE	65w	4300

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Designer Wall Lamp

Model: VT-7402
SKU: 40431
Max.Watts: Max 60W
Material: Metal
Color: Chrome
Holder: E27
IP Rating: IP20
Dimension: 610×220×330mm
Box Qty: 6



Designer Table Lamp

Model: VT-7412
SKU: 40331
Max.Watts: Max 60W
Material: Metal
Color: Red+Bronze
Holder: E27
IP Rating: IP20
Dimension: 150×420mm
Box Qty: 4





Designer Table Lamp

Model: VT-7712
SKU: 40381
Max.Watts: Max 60W
Material: Fabric+Metal
Color: Ivory+Black
Holder: E27
IP Rating: IP20
Dimension: 320×200×570mm
Box Qty: 1



V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Designer Table Lamp

Model: VT-7713
SKU: 40391
Max.Watts: Max 60W
Material: Fabric+Metal
Color: Ivory+Black
Holder: E27
IP Rating: IP20
Dimension: 300×180×550mm
Box Qty: 1



Designer Floor Lamps

Model: VT-7912
SKU: 40401
Max.Watts: Max 60W
Material: Fabric+Metal
Color: Ivory+Black
Holder: E27
IP Rating: IP20
Dimension: 450×300×1630mm
Box Qty: 1

Designer Floor Lamps

Model: VT-7913
SKU: 40411
Max.Watts: Max 60W
Material: Fabric+Metal
Color: Ivory+Black
Holder: E27
IP Rating: IP20
Dimension: 450×285×1620mm
Box Qty: 1



GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Floor Lamps

Model: VT-7702
SKU: 40421
Max.Watts: Max 60W
Material: Metal
Color: Black+Chrome
Holder: E27
IP Rating: IP20
Dimension: 140×200×1540mm
Box Qty: 4





Ball Light

- Lithium Battery 1000mAh
- IP Rating:IP67
- Dimension: 200×200×140mm
- Body Type: LLDPE
- Box Qty: 8

IP67 RATING

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7801	40141 - RGB	1w	18



Stone Light

- Lithium Battery 1000mAh
- IP Rating:IP67
- Dimension: 280×210×170mm
- Body Type: LLDPE
- Box Qty: 8

IP67 RATING

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7802	40151 - RGB	1w	18



V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Ball Light

- Lithium Battery 1000mAh
- IP Rating:IP67
- Dimension: 300×300×290mm
- Body Type: LLDPE
- Box Qty: 1

IP67 RATING

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7803	40161 - RGB	1w	18

Stone Light

- Lithium Battery 1000mAh
- IP Rating:IP67
- Dimension: 320×250×170mm
- Body Type: LLDPE
- Box Qty: 1

IP67 RATING

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7804	40171 - RGB	1w	18



Pot Light

- Lithium Battery 1000mAh
- IP Rating:IP54
- Dimension: 280×280×290mm
- Body Type: LLDPE
- Box Qty: 1

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7805	40181 - RGB	1w	18

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Pot Light

- Lithium Battery 2000mAh
- IP Rating:IP54
- Dimension: 355×355×325mm
- Body Type: LLDPE
- Box Qty: 1

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7808	40211 - RGB	1.5w	54

Ice Bucket Light

- Lithium Battery 2000mAh
- IP Rating:IP54
- Dimension: 290×330×350mm
- Body Type: LLDPE
- Box Qty: 1

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7806	40191 - RGB	1.5w	54

Ball Light

- Lithium Battery 2000mAh
- IP Rating:IP54
- Dimension: 400×400×390mm
- Body Type: LLDPE
- Box Qty: 1

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7807	40201 - RGB	3w	54



V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Ball Light

- Lithium Battery 3600mAh
- IP Rating:IP54
- Dimension: 500×500×260mm
- Body Type: LLDPE
- Box Qty: 1

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7809	40221 - RGB	6w	108

Stool Light

- Lithium Battery 2000mAh
- IP Rating:IP54
- Dimension: 400×400×360mm
- Body Type: LLDPE
- Box Qty: 1

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7810	40231 - RGB	3w	54

Cube Light

- Lithium Battery 3600mAh
- IP Rating:IP54
- Dimension: 400×400×400mm
- Body Type: LLDPE
- Box Qty: 1

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7811	40241 - RGB	3w	108



GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Table Light

- Lithium Battery 3600mAh
- IP Rating:IP54
- Dimension: 720×720×580mm
- Body Type: LLDPE
- Box Qty: 1

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7812	40251 - RGB	6w	108

Table Light

- Lithium Battery 5200mAh
- IP Rating:IP54
- Dimension: 600×600×1100mm
- Body Type: LLDPE
- Box Qty: 1

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7813	40261 - RGB	5w	100



Stool Light

- Lithium Battery 5200mAh
- IP Rating:IP54
- Dimension: 500×560×1100mm
- Body Type: LLDPE
- Box Qty: 1

BATTERY RECHARGEABLE

RGB

Model	SKU	Watts	Lumen
VT-7814	40271 - RGB	5w	100

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Solar Egg Light

- 1xAA BATTERY, 1.2V/500mAH NI-MH
- IP Rating:IP44
- Dimension: D:188×395mm
- Body Type: PC
- Box Qty: 4

21 IN COLOR CHANGING + WARM WHITE

Solar Lights

Model	SKU	Watts	Lumen
VT-7815	8557 – RGB+WW	0.2W	4

Solar Light

- 3.7V/500mAH Lithium Battery,
- IP Rating:IP44
- Dimension: 100×100×650mm
- Body Type: PC
- Box Qty: 12

Solar Lights

Model	SKU	Watts	Lumen
VT-719	8558 – 2200K WARM WHITE	0.4W	5

Solar Flame Light

- 1.2V 2/3AAA NI-MH
- IP Rating:IP44
- Dimension: 75×75×500mm
- Body Type: PP
- Box Qty: 24

4 PCS PACK

Solar Lights

Model	SKU	Watts
VT-724	8689 – 2200K WARM WHITE	1w

SOLAR ENERGY

V-TAC®
INNOVATIVE LED LIGHTING

White Chandelier-2 Step-Dimmable

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- IP Rating:
- Body Type: Aluminium+Acrylic

TRIAC DIMMABLE



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-101-2-W	3986 - 3000K WARM WHITE	115w	8050	600/400	1

Black Chandelier-2 Step-Dimmable

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- IP Rating:
- Body Type: Aluminium+Acrylic

TRIAC DIMMABLE



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-101-2-B	3987 - 3000K WARM WHITE	115w	8050	600/400	1

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Coffee Chandelier-2 Step-Dimmable

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- IP Rating:
- Body Type: Aluminium+Acrylic

TRIAC DIMMABLE



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-101-2-C	3988 - 3000K WARM WHITE	115w	8050	600/400	1

White Chandelier-3 Step-Dimmable

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- IP Rating:
- Body Type: Aluminium+Acrylic

TRIAC DIMMABLE



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-82-3-W	3989 - 3000K WARM WHITE	92w	6500	600/500/400mm	1

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Black Chandelier-3 Step-Dimmable

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- IP Rating:
- Body Type: Aluminium+Acrylic

TRIAC DIMMABLE



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-82-3-B	3990 - 3000K WARM WHITE	92w	6500	600/500/400mm	1

Coffee Chandelier-3 Step-Dimmable

- AC:220-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- IP Rating:
- Body Type: Aluminium+Acrylic

TRIAC DIMMABLE



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-82-3-C	3991 - 3000K WARM WHITE	92w	6500	600/500/400mm	1

V-TAC®
INNOVATIVE LED LIGHTING

GALLERY

Chandelier Series

- AC:100-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Steel+PC



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-40-1	3874 - 3000K WARM WHITE	40w	2800	400X210X1000mm	1

Chandelier-3 Step

- AC:100-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Acrylic+Aluminium

TRIAC DIMMABLE



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-70-3D	3904 - 3000K WARM WHITE 3905 - 4000K DAY WHITE	70w	4900	600×600×1200mm	1

GALLERY

V-TAC® INNOVATIVE LED LIGHTING

Chandelier-3 Step

- AC:100-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Acrylic+Aluminium

TRIAC DIMMABLE





Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-80-3D	3906 - 3000K WARM WHITE	80w	5600	600×600×1200mm	1

Ceiling Light

- AC:100-240V,50Hz
- PF: >0.9
- CRI: >80
- 120° Beam Angle
- IP Rating:IP20
- Body Type: Acrylic+Aluminium

TRIAC DIMMABLE



Model	SKU	Watts	Lumen	Dimension	Box Qty
VT-85-3	3910 - 3000K WARM WHITE 3911 - 4000K DAY WHITE	85w	6400	200×400×600mm	1



LED DISPLAY SCREEN

VTAC LED's Display screen series perfectly designed for the best video output and display of images and information. O ering Display color of 281 trillions(synchronized). The perfect product for advertising and marketing.

Key Feature

- Powerful LED display screen available in Indoor and Outdoor series
- Displays digital content such as Video, Images & Information
- Good Brand Value addition for Advertising
- Easy Installation

Application

Suitable for Outdoor and Indoor Advertising, Hotel conference room, Restaurants, Showrooms, Casinos, Government facilities, Theaters, Retail outlets, Tra c control room, Security monitoring room, Stage background, HD cinema, Shopping malls, Railway stations, Airports.

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

P3 Indoor LED Display Screen

SKU	Box Qty
11109	6



Pixel pitch	3mm
Panel size	L192xH192xT13mm
Physical density	111111/M2
Pixel configuration	1,1,1(R,G,B)
Driving method	1/16 Constant current
LED Chip Type	SMD2121
Display resolution	4096(64×64)dots
Module weight	0.35Kg
Module port	HUB75-B
Module working voltage	5VDC
Power	30W
Viewing angle	120 Degrees
Option distance	3-45M
Driving device	5020
Every square meter module	27.13 PCS
Maximum power	1000 W/M2
Frame Frequency	60Hz
Refresh frequency	400-800 Hz/S

Brightness	≥1100 CD/M2
Working environment	-10 to +40°c
temperature	10%~70% RH
Working environment humidity	AC46~4HZ,220V±15%/110V±15%
Display working voltage	8500K-11500K
Color temperature	≥16.7M color
Gray scale/color	RF\ S-Video\ RGB etc
Input signal	PCTV nonlinearity card, DVI
Control system	Display card, Linsn control system
Mean free error time	>5000-hour
hour lifespan	100000-hour
Steel box weight	40 Kg/M2
Steel box size	L576Xh768×80mm

V-TAC®
INNOVATIVE LED LIGHTING

ESSENTIALS

P4 Indoor LED Display Screen

SKU	Box Qty
11079	6



Screen Parameter

Pixel Density	62500dots/sqm
Brightness	1100nits
Optimum View Distance	more than 5m
Gray Scale	16bits
Display Color	281 trillions(synchronized)
Operation Power	AC 220V-240V/ 50/60Hz
Power Consumption	300W/cabinet
Control Mode	Synchronized
Refresh Frequency	400-700HZ
Surport Signal Input	S-Video,RGBHV,YUV etc.
Control Distance	UTP140M,SINGLE MODE FIBER
Life Span(50% Brightness)	15KM
IP(Front)	100000hrs
Control System	IP40
	PCTV nonlinearity card, DVI display card Linsn control system

LED Cabinet Parameter

Cabinet Size(L*h*d)	512*512*85mm
Cabinet Resolution	128*128
Module Quantity Each Cabinet	2*4=8
Power Consumption	300w/cabinet
Cabinet Material	Iron
Cabinet Weight	8kg/cabine

LED Module Parameter

Pixel Pitch	4mm
Led Specification	SMD2121
Led Configuration	SMD 3 in 1
Module Size	256*128mm
Module Resolution	64*32=2048dot
Drive Method	1/16 scan constant current
Drive IC	SM16106
Power Consumption	25-30W

- Plug & Play
- Ideal For Renting Purpose
- Portable Moving For Events

DEKRA TÜV CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

P5 Indoor LED Finished Cabinet

SKU	Box Qty
11077	6



Screen Parameter

Pixel Density:	40000dots/sqm
Brightness:	1800nits
Optimum View Distance:	more than 5m
Gray Scale:	16bits
Display Color:	281 trillions(synchronized)
Operation Power:	220V-240V
Max Power Consumption:	750W/sqm
Control Mode:	Synchronized
Refresh Frequency:	400-700HZ
Fram Frequency:	60HZ
Surport Signal Input:	S-Video,RGBHV,YUV etc.
Control Distance:	UTP140M,SINGLE MODE FIBER
Life Span(50% Brightness):	15KM
IP(Front/rear):	100000hrs
	IP20

LED Cabinet Parameter

Cabinet Size(L*h*d):	640*640mm
Cabinet Resolution:	128*128
Module Quantity Each Cabinet:	2*4=8
Average Power Consumption:	300w/cabinet
Cabinet Material:	Iron
Cabinet Size:	8kg/cabinet

LED Module Parameter

Pixel Pitch	5mm
Led Specification	SMD3528
Led Configuration	SMD 3 in 1
Module Size	320*160mm
Module Resolution	64*32=2048dot
Drive Method	1/16 scan constant current
Drive IC	SM16106

V-TAC® INNOVATIVE LED LIGHTING

ESSENTIALS

P6 Outdoor LED Finished Cabinet

SKU	Box Qty
11078	6



Screen Parameter

Pixel Density	27777dots/sqm
Brightness	6500nits
Optimum View Distance	more than 6m
Gray Scale	16bits
Display Color	281 Trillions(synchronized)
Operation Power	220V-240V
Max Power Consumption	1350W/sqm
Control Mode	Synchronized
Refresh Frequency	400-800HZ
Fram Frequency	60HZ
Surport Signal Input	S-Video,RGBHV,YUV etc.
Control Distance	Utp140m, Single Mode Fiber 15km
Operating Humidity	10%-90%
Life Span(50% Brightness)	100000hrs
IP(Front/rear)	IP65/IP45

LED Cabinet Parameter

Cabinet Size(L*h*d)	768*768mm
Cabinet Resolution	128*128
Module Quantity Each Cabinet	4*4=16
Average Power Consumption	800w/cabinet
Cabinet Material	Iron
Cabinet Size	25kg/cabinet

LED Module Parameter

Pixel Pitch	6mm
Led Specification	SMD3535
Led Configuration	SMD 3 in 1
Module Size	192*192mm
Module Resolution	32*32=1024dot
Drive Method	1/8 scan constant current
Drive IC	SM16106

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ESSENTIALS

V-TAC® INNOVATIVE LED LIGHTING

COM700-MEDIA PLAYER

SKU
11088

LED Display Player with Industrial PC
One TS802 sending card inside
Dual Display – Supports Max 1280*800
Supports SD Memory Card/USB/HDMI Out/Internet
USB and SD Card Memory Playing
Compact and Easy to Install
7" Touch Screen with windows 10 Inside
Size – 320*180*50mm
Input – AC:120-260V
1 x Audio In
1 x Audio Out
1 x DVI In
1 x HDMI Out
4 USB Interface

Windows 10

DUAL DISPLAY
TOUCH SCREEN

Sending Box

SKU	Box Qty
500082	20

Sending Card

SKU	Box Qty
500081	20



SMART CAMERAS

V-TAC introduces its all-new extensive range of smart cameras – fully compatible with any smart device (mobile phones, tablets, or PCs) through Wi-Fi integration. These cameras o er detection alerts via email — all available in standard UK & EU plugs for compatibility.

Key Features

- Standard wireless frequencies for Wi-Fi transmission
- High definition, high resolution videos at standard frames per second
- Supports iOS & Android devices
- Real-time alerts sent straight to your mobile for motion detected
- Night Vision
- Two-Way Audio
- Video storage: Micro SD storage or cloud transmission

Application

Designed to add an extra layer of security in houses, condominiums, restaurants, retail shops, office space

Indoor Camera IP20

Model	SKU	Box Qty
VT-5156	8986	50

Night Vision | Two Way Audio | Motion Detection | 1296P FULLHD

- Input Power – DC:5V±5%
- Auto tacking
- Motion Detection
- 2.4~2.4835 Ghz Wireless Frequency
- 355°/85° Pan/Tilt
- Resolution – 2304×1296P
- 3.0M pixel HD cmos Image Sensor
- 3.6mm Lens
- H.265/Mjpeg Video Compression
- 10 meters Night Vision
- 25-30fps Frame Rate
- Two way Audio
- WEP/WPA-PSK/WPA2-PSK encryption Wireless Security
- SD up to 128gb Storage
- Indoor Use only – IP20
- Supports Android & IOS devices
- IEEE802.11b/g/n Wireless Frequency

Outdoor Camera IP65

Model	SKU	Box Qty
VT-5157	8987	20

Night Vision | Two Way Audio | Motion Detection | 1296P FULLHD

IP65 RATING

- Input Power – DC:12V±5%
- 2.4~2.4835 Ghz Wireless Frequency
- Alarm motion detection
- Lan port RJ-45
- 2304×1296P Resolution
- 3.0M pixel HD CMOS
- 3.6mm Lens
- H.265/Mjpeg Video Compression
- Protocol: TCP, UDP, DHCP, DNS, RTSP, P2P
- 10 meters Night Vision
- 25-30fps Frame Rate
- Two way Audio
- Wireless Security: WEP/WPA-PSK/WPA2-PSK data encryption
- Micro SD up to 128gb Storage
- Supports Android & IOS devices
- IEEE802.11b/g/n Wireless LAN
- IP Rating: IP65

Camera with LED Lights IP65

Model	SKU	Box Qty
VT-5158	8988	20

Night Vision | Two Way Audio | Motion & Sound Detection | 1296P FULLHD

IP65 RATING

- Input Power – DC:12V±5%
- Auto tracking
- Motion & Sound Detection
- 2.4~2.4835 Ghz Wireless Frequency
- 220°/ 90° Pan/Tilt
- 2304×1296P Resolution
- 3.0M pixel HD CMOS Image Sensor
- 3.6mm Lens
- H.265/Mjpeg Video Compression
- Protocol: TCP, UDP, DHCP, DNS, RTSP, P2P
- 10 meters Night Vision
- 25–30fps Frame Rate
- Two way Audio
- Wireless Security: WEP/WPA-PSK/WPA2- PSK data encryption
- Micro SD up to 128gb Storage
- Lan port RJ-45
- Supports Android & IOS devices
- IEEE802.11b/g/n Wireless LAN
- IP Rating: IP65

Camera with LED Lights IP65

Model	SKU	Box Qty
VT-5159	8989	20

Night Vision | Two Way Audio | Motion Detection | 1296P FULLHD

IP65 RATING

- Input Power – DC:12V±5%
- Auto tracking
- Motion Detection
- 2.4~2.4835 Ghz Wireless Frequency
- 220°/ 90° Pan/Tilt
- 2304×1296P Resolution
- 3.0M Pixel HD CMOS Image Sensor
- 3.6mm Lens
- H.265/Mjpeg Video Compression
- Protocol: TCP, UDP, DHCP, DNS, RTSP, P2P
- 15 meters Night Vision
- 25–30fps Frame Rate
- Two way Audio
- Wireless Security: WEP/WPA-PSK/WPA2- PSK data encryption
- Micro SD up to 128gb Storage
- Lan port RJ-45
- Supports Android & IOS devices
- IEEE802.11b/g/n Wireless LAN
- IP Rating: IP65

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

SMART

V-TAC®

Surveillance Camera

Model	SKU	Box Qty
VT-5126	8475	50

Night Vision | 1080P FULLHD | IP65 RATING

- Input Power – DC:12V±10%
- Resolution – 1920×1080
- Image Sensor – 2.0MP 1/2.7" Low illumination CMOS Sensor
- Lens – 2.8mm@F1.8
- Audio – No
- IP Rating – IP65
- Built with Aluminium
- Signal System – AHD/CVI/TVI/CVBS @1080P
- Minimum illumination – Color:0.01Lux @(F1.2,AGC ON); 0 Lux (IRs on)
- Black & White – 0.001 Lux @ (F1.2,AGC ON),0 Lux (IRs on)
- Shutter – 1/50(1/60) second~ 1/10,000 second
- Lens – High-definition board lens 2.8mm @F1.8
- Lens type M12
- Day and Night IR-Cut
- Video Output – 1Vp-p Composite Output(75Ω/BNC)
- IR Distance – 20 to 30 meters

Security Camera

Model	SKU	Box Qty
VT-5135	8478	50

Night Vision | 1080P FULLHD | IP65 RATING

- Input Power – DC:12V±10%
- Resolution – 1920×1080
- Image Sensor – 1/2.8" Low illumination CMOS Sensor
- Lens – 3.6mm@F1.8
- Minimum illumination – Color-0.01Lux @(F1.2,AGC ON); 0 Lux with IR
- Black and White – 0.001 Lux @ (F1.2, AGC ON), 0 Lux with IR
- Shutter – 1/50 (1/60) seconds to 1/10,000 seconds
- Designed with Lens Type M12
- Day and night conversion mode – Supports IR-CUT
- Frame rate 1080P@20fps
- Supports Protocols – TCP/IP, HTTP, DHCP, DNS, DDNS,PPPoE, SMTP, NTP
- Communication interface – 1 10/100Mbps adaptive Ethernet port, RJ45 interface
- Infrared distance of 20–30 meters
- Audio – No
- IP Rating – IP65

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

Security Camera

Model	SKU	Box Qty
VT-5136	8479	20

Night Vision | 1080P FULLHD | IP65 RATING

- Input Power – DC:12V
- Resolution – 1920×1080
- Image Sensor – 1/2.7" CMOS 0.001LUX/F1.2(Colorful)
- Video Compression – 32kbps-8mbps
- 2.0 Mega pixel
- Electronic Shutter – 1/25—1/10000 Second
- Day and night conversion mode – Full Color
- 3D DNR (Digital noise reduction)
- H.265 encoding type – Profile_Baseline
- Intelligent Alarm – Motion detection, occlusion alarm, video loss, network cable disconnection, IP address conflict
- Support Protocols – TCP/IP, DHCP, HTTP, DNS, RTP RTSP
- Docking Protocols – ONVIF, Hikvision, Dahua
- Universal feature – One-click recovery, dual stream, heartbeat, mirroring, video masking, anonymous access
- Communication interface – 1 RJ45 10M / 100M adaptive Ethernet port

FULL COLOR NIGHT VISION REC

Outdoor Camera

Model	SKU	Box Qty
VT-5123	8440-BS PLUG	30

Night Vision | Two Way Audio | Motion Detection | 1080P FULLHD

IP65 RATING

- DC:12V±5% Input Power
- Motion detection
- 2.4~2.4835 Ghz Wireless Frequency
- Alarm motion detection
- Lan port RJ-45
- 1920×1080P Resolution
- 2.0M pixel HD cmos
- 3.6mm Lens
- H.264/Mjpeg Video Compression
- 10 meters Night Vision
- 25–30fps Frame Rate
- Two way Audio
- WEP/WPA-PSK/WPA2-PSK encryption Wireless Security
- SD up to 64gb Storage
- IP65(Indoor & Outdoor use)
- Supports Android & IOS devices

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

Wireless NVR Camera

Model	SKU	Box Qty
VT-5188	8400	4

P2P | Cloud | Wireless | HDMI

- Transmission distance more than 800 meters in open space with no obstacles
- Built-in security wireless Wi-Fi module with stable signal transmission and strong anti-interference ability
- No need setting Wi-Fi, plug and play
- P2P remote viewing in seconds with high-definition video quality
- Support motion detection alarm
- Support buzzer/Email alarm
- Support Android/IOS devices

SMART HOME WIFKIT | HD HOME SECURITY SYSTEM | WiFi | IP65 RATING

Indoor Camera

Model	SKU	Box Qty
VT-5122	8438-BS PLUG	50

Night Vision | Two Way Audio | Motion Detection | 1080P FULLHD

- DC:5V±5% Input Power
- Auto tracking
- Motion Detection
- 2.4~2.4835 Ghz Wireless Frequency
- 355°/85° Pan/Tilt
- 1920×1080P Resolution
- 2.0M pixel HD cmos Image Sensor
- 3.6mm Lens
- H.264/Mjpeg Video Compression
- 10 meters Night Vision
- 25-30fps Frame Rate
- Two way Audio
- WEP/WPA-PSK/WPA2-PSK encryption Wireless Security
- SD up to 64gb Storage
- Indoor Use only – IP20
- Supports Android & IOS devices

Doorbell

Model	SKU	Box Qty
VT-5412	8355	50

Including 8GB Micro SD Card

Including Rechargable Batteries

- Two-way audio
- IR Distance: dual IR cut filter with auto switch, max 5 meters
- Motion detection: alerts users with a push notification
- Remote operation-system settings, account management, stream code setting
- ABS+PC Body Type
- 75×40×143mm
- -10°C ~+50°C Working Temperature
- 1280×720P Resolution
- Rechargeable 18650 Battery 3350mAH or AC 8~24V Power
- HD720P@25FPS Frame Rate
- 166 Degree Field View
- Max 64GB TF Card Storage

Chimes

Model	SKU	Box Qty
VT-5415	8359-BS PLUG	100

55 melodious **Ringtones**

- 5 levels of volume
- 55 ringtones
- Voltage: AC100-265V
- Protection Rating: IP54
- Wireless range up to 250 mtrs
- Directly plug into an electrical outlet
- Compatible with V-TAC Doorbell (VT-5412)

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

SMART SWITCHES

Introducing the next generation self-powered wireless switches, functions using an RF receiver, making their use a hassle free experience. Offering a push-touch button and remote features.

Smart Switch is made of Advanced PC Material, High Strength, Impact, and High-Temperature Resistance, Non- toxic and Eco Friendly, Easy to Clean and Color Fadeless.

No-Screw Design On Panel Surface, Big Button Design With Indicator, Easy ON/OFF operation With Good Sense Of Touch, Low Sound of pressing

V-TAC®

SMART

V-TAC®

SMART

1Gang 1Way Sensor Switch

Model	SKU	Box Qty
VT-5131	8460	144

Input Power: 2-3V(CR2032 Button Battery)
Switch Lifetime: 30,000 times
Body Type: PC
Dimensions: 86×86×11mm
Remote Distance: Outdoor >600m | Indoor >40m

2Gang 1Way Sensor Switch

Model	SKU	Box Qty
VT-5132	8461	144

Input Power: 2-3V(CR2032 Button Battery)
Switch Lifetime: 30,000 times
Body Type: PC
Dimensions: 86×86×11mm
Remote Distance: Outdoor >600m | Indoor >40m

3Gang 1Way Sensor Switch

Model	SKU	Box Qty
VT-5133	8462	144

Input Power: 2-3V(CR2032 Button Battery)
Switch Lifetime: 30,000 times
Body Type: PC
Dimensions: 86×86×11mm
Remote Distance: Outdoor >600m | Indoor >40m

Remote Three Gang

Model	SKU	Box Qty
VT-5143	8463	364

Input Power: 2-3V(CR2032 Button Battery)
Switch Lifetime: 30,000 times
Body Type: ABS
Dimensions: 62×30×12mm
Remote Distance: Outdoor >160m | Indoor >20m

Receiver

Model	SKU	Box Qty
VT-5129	8458	364

Input Power: AC:180-240V
Body Type: PC
Dimensions: 39×23×22 mm
Remote Distance: Outdoor >600m | Indoor >40m

Wi-Fi Receiver

Model	SKU	Box Qty
VT-5130	8459	196

Input Power: AC:85-265V
Body Type: PC
Dimensions: 75×28×28.5 mm
Remote Distance: Outdoor >500m | Indoor >40m

WORKS WITH alexa

works with Ok Google

DEKRA TÜV SÜD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

SMART

V-TAC®



Remote Dimmer 1Gang 1Way

Input Power: AC:180–250V,50/60Hz
Operating Temp: -10~60°C
Switch Lifetime: >100,000 times
Relative Humidity: 10%~93%
Load Power: 5–500W
Body Type: PC+Glass Finish
Dimensions: 86×86mm

Model	SKU	Color	Box Qty
VT-5311-B	8395	Black	100
VT-5311-W	8369	White	100

Doorbell-Switch 1Gang 1Way

Input Power: AC:180–250V,50/60Hz
Operating Temp: -10~60°C
Switch Lifetime: >100,000 times
Relative Humidity: 10%~93%
Load Power: 5–500W
Body Type: PC+Glass Finish
Dimensions: 86×34×86mm

Model	SKU	Color	Box Qty
VT-5411-B	8397	Black	100
VT-5411-W	8372	White	100

Socket EU 2 Way

Model	SKU	Box Qty
VT-5811-B	8401	60
VT-5811-W	8402	60

Input Power: AC:200–250V,50Hz
Switch Lifetime: >100,000 times
Body Type: PC+Glass Finish



Socket EU Glass Panel

Model	SKU	Box Qty
VT-5711-B	8399	80
VT-5711-W	8379	80

Input Power: AC:200–250V,50Hz
Switch Lifetime: >100,000 times
Body Type: PC+Glass Finish



SOCKETS AND ADAPTERS

Extensive variety of electrical accessories to power your devices with Italian, European sockets and adapters made from high-quality, modern components from V-TAC. Includes cable reels and sockets of different types and lengths, extension cords, travel adapters/converters, grounded counterparts, and more.

Key Features

- 3/4/5/6/8-way sockets – sockets with switches and/or USB ports also available
- Includes sockets for different socket types compatible in Italy and more European countries
- 2/3/4 Outlet, Universal Travel Adapters available for flexibility of use
- Earthing variants available for select socket types

V-TAC®

ELECTRICAL

ELECTRICAL

V-TAC®

NEW

30W CHARGING ADAPTER WITH 1 PD+1 QC PORT-BLACK

- Input Power: AC:100-240V, 50/60Hz
- USB Type: Type A and Type C(PD)
- USB-A output: 5V-3A, 9V-3A, 12V-2.25A Max
- USB-C output: 5V-3A, 9V-3A, 15V-2.0A, 20V-1.5A Max
- USB-A+USB-C: 5V-3A
- Total Output: 30W(Max)
- Unit Color: Black

Model	SKU	Box Qty
VT-5330-B	6679	320

PD POWER DELIVERY

NEW

20W CHARGING ADAPTER WITH 1 PD+1 QC PORT-BLACK

- Input Power: AC:100-240V, 50/60Hz
- USB Type: Type A and Type C(PD)
- USB-A output: 5V-3A, 9V-2A, 12V-1.5A Max
- USB-C output: 5V-3A, 9V-2.22A, 12V-1.67A Max
- USB-A+USB-C: 5V-3A
- Total Output: 20W(Max)
- Unit Color: Black

Model	SKU	Box Qty
VT-5320-B	6677	320

PD POWER DELIVERY

NEW

30W CHARGING ADAPTER WITH 1 PD+1 QC PORT-WHITE

- Input Power: AC:100-240V, 50/60Hz
- USB Type: Type A and Type C(PD)
- USB-A output: 5V-3A, 9V-3A, 12V-2.25A Max
- USB-C output: 5V-3A, 9V-3A, 15V-2.0A, 20V-1.5A Max
- USB-A+USB-C: 5V-3A
- Total Output: 30W(Max)
- Unit Color: White

Model	SKU	Box Qty
VT-5330-W	6680	320

PD POWER DELIVERY

NEW

20W CHARGING ADAPTER WITH 1 PD+1 QC PORT-WHITE

- Input Power: AC:100-240V, 50/60Hz
- USB Type: Type A and Type C(PD)
- USB-A output: 5V-3A, 9V-2A, 12V-1.5A Max
- USB-C output: 5V-3A, 9V-2.22A, 12V-1.67A Max
- USB-A+USB-C: 5V-3A
- Total Output: 20W(Max)
- Unit Color: White

Model	SKU	Box Qty
VT-5320-W	6678	320

PD POWER DELIVERY

USB TRAVEL ADAPTOR

SKU	Box Qty
8791	48

Input Current: 0.25A
Output Current: 2A
Rated Load: 10W

Input Power: AC:100-230V,50/60Hz
Body Type: ABS
Dimension: 27×47×70mm

V-TAC®

ELECTRICAL

USB TRAVEL ADAPTOR

SKU	Box Qty
8792	48

Input Current: 0.25A
Output Current: 2A
Rated Load: 10W
Input Power: AC:100-230V,50/60Hz
Body Type: ABS
Dimension: 27×47×70mm

Universal Adapter

UNIVERSAL ADAPTOR WITH OVERLOAD PROTECTION WITH 2USB 2A

SKU	Box Qty
8704	48

Input Current: 10A
Output Current: 10A
Rated Load: 2500W
Input Power: AC:110-250V,50/60Hz
Body Type: PC+COPPER
Dimension: 95×50×40mm

3.0A FAST CHARGING

USB QC3.0 TRAVEL ADAPTOR

SKU	Box Qty
8793	48

Input Current: 0.2A
Output Current: 3.0A
Rated Load: 18W
Input Power: AC:100-240V,50/60Hz
Body Type: PC
Dimension: 42×57×24mm

Universal Adapter

UNIVERSAL ADAPTOR

SKU	Box Qty
8705	100

Input Current: 10A
Output Current: 10A
Rated Load: 2500W
Input Power: AC:110-250V,50/60Hz
Body Type: PC+COPPER
Dimension: 70×50×40mm

3.0A FAST CHARGING

USB QC3.0 TRAVEL ADAPTOR

SKU	Box Qty
8794	48

Input Current: 0.2A
Output Current: 3.0A
Rated Load: 18W
Input Power: AC:100-240V,50/60Hz
Body Type: PC
Dimension: 42×57×24mm

2 USB PORT

ADAPTER WITH EARTHING CONTACT & CHARGING

SKU	Box Qty
8795	60

Input Current: 16A
Output Current: 16A+2.1A
Rated Load: 3680W
Input Power: AC:110-230V,50/60Hz
Body Type: ABS
Dimension: 107×54.2×74.2mm

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

2 USB PORT

ADAPTER WITH EARTHING CONTACT & CHARGING

SKU	Box Qty
8796	60

Input Current: 16A
Output Current: 16A+2.1A
Rated Load: 3680W
Input Power: AC:110-230V,50/60Hz
Body Type: ABS
Dimension: 107×54.2×74.2mm

1.5M Wire

LIGHTED SWITCH

4 HOLES SOCKET WITH SWITCH

SKU	Box Qty
8770	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 174×45×40mm

1.4M Wire

4WAYS SOCKET WITH USB(3G1.5MM2 X1.4M)

SKU	Box Qty
8800	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:230V
Body Type: PC
Dimension: 77X77X82.8mm

1.5M Wire

LIGHTED SWITCH

4 HOLES SOCKET WITH SWITCH

SKU	Box Qty
8771	40

Input Current: 16A
Rated Load: 3680W
Color: Black
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 174×45×40mm

1.4M Wire

3WAYS SOCKET WITH USB(3G1.5MM2 X1.4M

SKU	Box Qty
8799	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:230V
Body Type: PC
Dimension: 130X138.30×42mm

1.5M Wire

LIGHTED SWITCH

8 HOLES SOCKET WITH SWITCH

SKU	Box Qty
8772	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 186×45×40mm

V-TAC®

ELECTRICAL

1.5M Wire

LIGHTED SWITCH

8 HOLES SOCKET WITH SWITCH

SKU	Box Qty
8773	40

Input Current: 16A
Rated Load: 3680W
Color: Black
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 186×45×40mm

1.5M Wire

2 USB PORT

3WAYS SOCKET WITH 2USB

SKU	Box Qty
8776	40

Input Current: 16A
Rated Load: 3680W
Color: Black
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 178×45×40mm

1.5M Wire

2 USB PORT

3WAYS SOCKET WITH 2USB

SKU	Box Qty
8774	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 178×45×40mm

5M Wire

2 USB PORT

3WAYS SOCKET WITH 2USB

SKU	Box Qty
8777	20

Input Current: 16A
Rated Load: 3680W
Color: Black
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 178×45×40mm

5M Wire

2 USB PORT

3WAYS SOCKET WITH 2USB

SKU	Box Qty
8775	20

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 178×45×40mm

1.5M Wire

3 WAYS SOCKET

SKU	Box Qty
8754	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 170×45×40mm

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

3M Wire

3 WAYS SOCKET

SKU	Box Qty
8755	30

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 170×45×40mm

1.5M Wire

5 WAYS SOCKET

SKU	Box Qty
8758	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 178×45×40mm

1.5M Wire

4 WAYS SOCKET

SKU	Box Qty
8756	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 174×45×40mm

3M Wire

5 WAYS SOCKET

SKU	Box Qty
8759	30

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 178×45×40mm

3M Wire

4 WAYS SOCKET

SKU	Box Qty
8757	30

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 174×45×40mm

1.5M Wire

6 WAYS SOCKET

SKU	Box Qty
8760	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 182×45×40mm

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®

ELECTRICAL

3M Wire

6 WAYS SOCKET

SKU	Box Qty
8761	30

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 182×45×40mm

1.5M Wire

LIGHTED SWITCH

4WAYS SOCKET WITH SWITCH

SKU	Box Qty
8764	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 178×45×40mm

1.5M Wire

LIGHTED SWITCH

3WAYS SOCKET WITH SWITCH

SKU	Box Qty
8762	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 174×45×40mm

5M Wire

LIGHTED SWITCH

4WAYS SOCKET WITH SWITCH

SKU	Box Qty
8765	20

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 178×45×40mm

5M Wire

LIGHTED SWITCH

3WAYS SOCKET WITH SWITCH

SKU	Box Qty
8763	20

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 174×45×40mm

1.5M Wire

LIGHTED SWITCH

5WAYS SOCKET WITH SWITCH

SKU	Box Qty
8766	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 182×45×40mm

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS COMPLIANT CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

5M Wire

LIGHTED SWITCH

5WAYS SOCKET WITH SWITCH

SKU	Box Qty
8767	20

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 182×45×40mm

1.4M Wire

SURGE PROTECTION

LIGHTED SWITCH

2 USB PORT

3 WAYS DESK SOCKET WITH LIGHTED SWITCH & 2 USB PORTS

SKU	Box Qty
8817	20

Input Current: 3×16A
Rated Load: 3500W
Color: Black
Input Power: AC:230V
Body Type: PC,PVC, COPPER
Dimension: 225×65×73mm

1.5M Wire

LIGHTED SWITCH

6WAYS SOCKET WITH SWITCH

SKU	Box Qty
8768	40

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 186×45×40mm

1.4M Wire

LIGHTED SWITCH

2 USB PORT

4 WAYS SOCKET WITH LIGHTED SWITCH & 2 USB PORTS

SKU	Box Qty
8808	20

Input Current: 4×16A
Rated Load: 3680W
Color: White
Input Power: AC:200-240V,50Hz
Body Type: PC,PVC, COPPER
Dimension: 307×46×42mm

5M Wire

LIGHTED SWITCH

6WAYS SOCKET WITH SWITCH

SKU	Box Qty
8769	20

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 186×45×40mm

3M Wire

LIGHTED SWITCH

2 USB PORT

5 WAYS SOCKET WITH LIGHTED SWITCH & 2 USB PORTS

SKU	Box Qty
8807	20

Input Current: 5×16A
Rated Load: 3680W
Color: White
Input Power: AC:200-240V,50Hz
Body Type: PP,PVC, COPPER
Dimension: 365×53×44mm

V-TAC®

ELECTRICAL

1.4M Wire

LIGHTED SWITCH

5 WAYS SAFE SOCKET WITH LIGHTED SWITCH

SKU	Box Qty
8818	20

Input Current: 5×16A
Rated Load: 3680W
Color: White
Input Power: AC:230V
Body Type: PP,PVC, COPPER
Dimension: 330×55×41mm

4 WAYS ADAPTER WITH EARTHING CONTACT

SKU	Box Qty
8785	100

Input Current: 16A
Output Current: 4×2.5A
Rated Load: 3680W
Input Power: AC:250V, 16A
Body Type: PP Plastic+ Copper
Dimension: 91.2×49×78.1mm

2 WAYS ADAPTER WITH EARTHING CONTACT

SKU	Box Qty
8783	100

Input Current: 16A
Output Current: 2×16A
Rated Load: 2300W
Input Power: AC:250V, 16A
Body Type: PP Plastic+ Copper
Dimension: 98×46×74.6mm

2 WAYS ADAPTER WITH EARTHING CONTACT

SKU	Box Qty
8786	100

Input Current: 16A
Output Current: 3×16A
Rated Load: 3680W
Input Power: AC:250V, 16A
Body Type: PP Plastic+ Copper
Dimension: 87.5×45.8×99.5mm

ADAPTER WITH 3 EURO-SOCKET

SKU	Box Qty
8784	100

Input Current: 16A
Output Current: 16A+2×2.5A
Rated Load: 3680W
Input Power: AC:250V, 16A
Body Type: PP Plastic+ Copper
Dimension: 93.1×48×75.3mm

3 WAYS ADAPTER WITH EARTHING CONTACT

SKU	Box Qty
8787	100

Input Current: 16A
Output Current: 3×16A
Rated Load: 3680W
Input Power: AC:250V, 16A
Body Type: PP Plastic+ Copper
Dimension: 92.8×72.4×86.1mm

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

LIGHTED SWITCH

3 OUTLET POWER ADAPTER WITH EARTH CONTACT AND SWITCH

SKU	Box Qty
8788	100

Input Current: 16A
Output Current: 16A+2×2.5A
Rated Load: 3680W
Input Power: AC:250V, 16A
Body Type: PP Plastic+ Copper
Dimension: 93.1×69.7×76.5mm

2 OUTLET ADAPTER 2.5A

SKU	Box Qty
8801	200

Input Current: 16A
Output Current: 5A
Rated Load: 1100W
Input Power: AC:230V
Body Type: PP
Dimension: 44X39X61mm

3 OUTLET POWER ADAPTER WITH EARTH CONTACT

SKU	Box Qty
8789	100

Input Current: 16A
Output Current: 3×16A
Rated Load: 3680W
Input Power: AC:250V, 16A
Body Type: PP Plastic+ Copper
Dimension: 133.6×49.5×76.9mm

3 OUTLET ADAPTER 2.5A

SKU	Box Qty
8802	200

Input Current: 16A
Output Current: 7.5A
Rated Load: 1700W
Input Power: AC:230V
Body Type: PP
Dimension: 65×47×72mm

3 OUTLET POWER ADAPTER

SKU	Box Qty
8790	100

Input Current: 16A
Output Current: 3×16A
Rated Load: 3680W
Input Power: AC:250V, 16A
Body Type: PP Plastic+ Copper
Dimension: 87.5×84.98×59.4mm

ADAPTER WITH 2 SOCKET 2.5A,1 SOCKET 16A WITH EARTHING CONTACT 16A

SKU	Box Qty
8804	200

Input Current: 16A
Output Current: 16A
Rated Load: 3500W
Input Power: AC:230V
Body Type: PP
Dimension: 92×47.5×75mm

V-TAC®

ELECTRICAL

2 OUTLET ADAPTER 16A WITH EARTHING CONTACT 16A

SKU	Box Qty
8805	200

Input Current: 16A
Output Current: 16A
Rated Load: 3680W
Input Power: AC:230V
Body Type: PP
Dimension: 92×50×75mm

SURGE PROTECTION

1 WAY ADAPTER-16A

SKU	Box Qty
8809	100

Input Current: 16A
Output Current: 16A
Rated Load: 3680W
Input Power: AC:200-240V,50Hz
Body Type: PP COPPER
Dimension: 80×55×72mm

4 OUTLET ADAPTER 2.5A

SKU	Box Qty
8803	200

Input Current: 16A
Output Current: 10A
Rated Load: 2300W
Input Power: AC:230V
Body Type: PP
Dimension: 83×47×72mm

LIGHTED SWITCH

ADAPTER WITH 2 POLE SWITCH

SKU	Box Qty
8841	100

Input Current: 16A
Output Current: 16A
Rated Load: 3500W
Input Power: AC:250V
Body Type: PP Body
Dimension:

ADAPTER WITH 2 SOCKET 2.5A,1 SOCKET 16A WITH SWITCH & EARTHING CONTACT16A

SKU	Box Qty
8806	200

Input Current: 16A
Output Current: 16A
Rated Load: 3500W
Input Power: AC:230V
Body Type: PP
Dimension: 95×70×74mm

10M Wire

CABLE REEL WITH 4 SOCKET

SKU	Box Qty
8781	5

Input Current: 16A
Rated Load: 3500W
Color: Black
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 20X27X6.5mm

DEKRA TÜV GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

25M Wire

CABLE REEL WITH 4 SOCKET

SKU	Box Qty
8782	1

Input Current: 16A
Rated Load: 3500W
Color: Black
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 24X13X33mm

10M Wire

Extension Cord

SKU	Box Qty
8780	15

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 200×110×40mm

3M Wire

Extension Cord

SKU	Box Qty
8778	30

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 250×200×150mm

5M Wire

Extension Cord

SKU	Box Qty
8779	30

Input Current: 16A
Rated Load: 3680W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 200X160X90mm

2 WAYS ADAPTER-16A-IP44

SKU	Box Qty
8812	100

Input Current: 2×16A
Rated Load: 3680W
Color: Green
Input Power: AC:200-240V,50Hz
Body Type: PP COPPER
Dimension: 105×66×106mm

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®

ELECTRICAL

3M Wire

2 WAYS GARDEN SPIKE SOCKET WITH MECHANICAL TIMER

SKU	Box Qty
8811	8

Input Current: 2×16A
Rated Load: 3500W
Color: Green
Input Power: AC:230V
Body Type: PP,RUBBER, COPPER
Dimension: 403×145×113mm

3M Wire

4 WAYS SOCKET-IP44

SKU	Box Qty
8814	10

Input Current: 4×16A
Rated Load: 3680W
Color: Black+Yellow
Input Power: AC:230V
Body Type: PP,RUBBER, COPPER
Dimension: 230×71×94mm

3M Wire

4 WAYS GARDEN SPIKE SOCKET-IP44

SKU	Box Qty
8810	8

Input Current: 4×16A
Rated Load: 3500W
Color: Green
Input Power: AC:230V
Body Type: PP,RUBBER, COPPER
Dimension: 403×145×113mm

3M Wire

LIGHTED SWITCH

5 WAYS SOCKET WITH LIGHTED SWITCH-IP44

SKU	Box Qty
8813	10

Input Current: 5×16A
Rated Load: 3680W
Color: Black+Yellow
Input Power: AC:230V
Body Type: PP,RUBBER, COPPER
Dimension: 403×73×49.5mm

NA

WATERPROOF SAFE BOX-IP44

SKU	Box Qty
8819	40

Input Current: 16A
Output Current: NA
Rated Load: NA
Input Power: AC:230V
Body Type: PP
Dimension: 212×82×72mm

15M Wire

EXTENSION CORD-1 WAY-16A-IP44

SKU	Box Qty
8816	8

Input Current: 16A
Rated Load: 3500W
Color: Orange+Black
Input Power: AC:230V
Body Type: PVC, COPPER,PP
Dimension: 357×130×130mm

DEKRA TÜV SÜD GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

30M Wire

EXTENSION CORD-1 WAY-16A-IP44

SKU	Box Qty
8815	4

Input Current: 16A
Rated Load: 3500W
Color: Orange+Black
Input Power: AC:230V
Body Type: PVC, COPPER,PP
Dimension: 473×128×150mm

2 Way Socket

2 WAYS GARDEN SOCKET WITH LAMP IP44

SKU	Box Qty
8822	4

Input Current: 16A
Rated Load: 3680W
Color: Dark Grey
Input Power: AC:220-240V,50Hz
Body Type: Stainless Steel+PC
Dimension: 127×455mm

2 Way Socket

2 WAYS GARDEN SOCKET IP44

SKU	Box Qty
8820	6

Input Current: 16A
Rated Load: 3680W
Color: Dark Grey
Input Power: AC:220-240V,50Hz
Body Type: Stainless Steel
Dimension: 127×300mm

4 Way Socket

4 WAYS GARDEN SOCKET IP44

SKU	Box Qty
8821	4

Input Current: 16A
Rated Load: 3680W
Color: Dark Grey
Input Power: AC:220-240V,50Hz
Body Type: Stainless Steel
Dimension: 157×395mm

1.5M Wire

Multipresa, 3 pos. 10/16A prese Bipasso
Con attacco a parete

SKU	Box Qty
8706	50

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 115×47×22mm

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC® ELECTRICAL

1.5M Wire

Multipresa, 4 pos. 10/16A prese Bipasso
Con attacco a parete

SKU	Box Qty
8707	50

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 135×47×22mm

1.5M Wire

LIGHTED SWITCH

3 pos. con interruttore luminoso
10/16A Bipasso/schuko

SKU	Box Qty
8710	50

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 200×55×45mm

1.5M Wire

Multipresa, 5 pos. 10/16A prese Bipasso
Con attacco a parete

SKU	Box Qty
8708	40

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 155×47×22mm

1.5M Wire

LIGHTED SWITCH

4 POS. CON INTERRUTTORE LUMINOSO
10/16A BIPASSO/SCHUKO

SKU	Box Qty
8711	40

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 245×55×45mm

1.5M Wire

Multipresa, 6 pos. 10/16A prese Bipasso
Con attacco a parete

SKU	Box Qty
8709	40

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 170×47×22mm

1.5M Wire

LIGHTED SWITCH

5 pos. con interruttore luminoso
10/16A Bipasso/schuko

SKU	Box Qty
8712	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 280×55×45mm

DEKRA TÜV GS RoHS CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

1.5M Wire

LIGHTED SWITCH

6 pos. con interruttore luminoso
10/16A Bipasso/schuko

SKU	Box Qty
8713	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 325×55×45mm

1.5M Wire

LIGHTED SWITCH

4 pos.10/16A Bipasso/schuko
con protezione sovratensionni e interruttori luminoso

SKU	Box Qty
8748	40

Input Current: 16A
Rated Load: 2500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 160×100×45mm

1.5M Wire

LIGHTED SWITCH

7 pos. con interruttore luminoso
10/16A Bipasso/schuko

SKU	Box Qty
8714	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 370×55×45mm

1.5M Wire

LIGHTED SWITCH

6 pos.10/16A Bipasso/schuko
con protezione sovratensionni e interruttori luminoso

SKU	Box Qty
8749	30

Input Current: 16A
Rated Load: 2500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 200×100×45mm

1.5M Wire

LIGHTED SWITCH

2 USB PORT

5pos. con interruttore luminoso
10/16A Bipasso/schuko + con 2 connessioni USB

SKU	Box Qty
8715	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 335×55×45mm

3M Wire

2 prese 2p+t 10/16A Bipasso
1 prese Bipasso/Schuko

SKU	Box Qty
8733	50

Input Current: 16A
Rated Load: 2500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 100×47×52mm

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®

ELECTRICAL

1.5M Wire

LIGHTED SWITCH

4 prese 2p+t 10/16A Bipasso
2 prese 10/16A Bipasso/Schuko

SKU	Box Qty
8734	25

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 150×47×45mm

1.5M Wire

LIGHTED SWITCH

4 pos. 10/16A Bipasso/Schuko
Con protezione sovratensionni e interruttore generale luminoso e 4 interruttori indipendenti

SKU	Box Qty
8737	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 225×72×40mm

1.5M Wire

LIGHTED SWITCH

6 prese 2p+t 10/16A Bipasso
3 prese 10/16A Bipasso/Schuko

SKU	Box Qty
8735	25

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 195×47×45mm

1.5M Wire

LIGHTED SWITCH

5 pos. 10/16A Bipasso/Schuko
Con protezione sovratensionni e interruttore generale luminoso e 5 interruttori indipendenti

SKU	Box Qty
8738	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 260×72×40mm

1.5M Wire

LIGHTED SWITCH

8 prese 2p+T10/16A Bipasso
4 prese Bipasso/Schuko

SKU	Box Qty
8736	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 240×47×45mm

1.5M Wire

LIGHTED SWITCH

6 pos. 10/16A Bipasso/Schuko
Con protezione sovratensionni e interruttori generale luminoso e 6 interruttore indipendenti

SKU	Box Qty
8739	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 305×70×35mm

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

1.5M Wire

LIGHTED SWITCH

2 USB PORT

2 presa 2p+T10/16A Bipasso + 1 presa Bipasso/schuko
con protezione sovraccarco / con 2USB

SKU	Box Qty
8745	40

Input Current: 10A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 145×50×40mm

1.5M Wire

LIGHTED SWITCH

6 pos. Con interruttore luminoso 10/16A Bipasso
Con attacco a parete

SKU	Box Qty
8742	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 200×50×30mm

1.5M Wire

LIGHTED SWITCH

4 pos. Con interruttore luminoso10/16A Bipasso
Con attacco a parete

SKU	Box Qty
8740	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 160×50×30mm

5M Wire

2 prese 2P+T 10/16A Bipasso
Con protezione termica ripristinabile

SKU	Box Qty
8700	10

Input Current: 16A
Rated Load: 2200W
Color: Black
Input Power: AC:250V,50/60Hz
Body Type: ABS+PC+COPPER
Dimension: 200×160×90mm

1.5M Wire

LIGHTED SWITCH

5 pos. Con interruttore luminoso 10/16A Bipasso
Con attacco a parete

SKU	Box Qty
8741	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PP+COPPER
Dimension: 180×47×30mm

10M Wire

4 prese Bipasso/Schuko
Con protezione termica ripristinabile

SKU	Box Qty
8701	6

Input Current: 16A
Rated Load: 2200W
Color: Black
Input Power: AC:250V,50/60Hz
Body Type: ABS+PC+COPPER
Dimension: 250×200×150mm

V-TAC®

ELECTRICAL

15M Wire

4 prese Bipasso/Schuko
Con protezione termica ripristinabile

SKU	Box Qty
8702	6

Input Current: 16A
Rated Load: 2200W
Color: Black
Input Power: AC:250V,50/60Hz
Body Type: ABS+PC+COPPER
Dimension: 240×190×160mm

30M Wire

Prolunga, 1 via 10/16A presa italiana/Schuko con cavo VDE H05VV-F 3G1.5mm2 30m, con spina italiana 16A, con telaio portacavi

SKU	Box Qty
8833	4

Input Current: 10/16A
Output Current:
Rated Load: 2500W
Input Power: AC:230V
Body Type: PVC, COPPER,PP
Dimension: 473×128×150mm

25M Wire

4 prese Bipasso/Schuko
Con protezione termica ripristinabile

SKU	Box Qty
8703	4

Input Current: 16A
Rated Load: 2200W
Color: Black
Input Power: AC:250V,50/60Hz
Body Type: ABS+PC+COPPER
Dimension: 300×240×190mm

3M Wire

Prolunga lineare
spina 10A,2p+T prese 10A

SKU	Box Qty
8729	30

Input Current: 10A
Rated Load: 2300W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 200×110×40mm

15M Wire

Prolunga, 1 via 10/16A presa italiana/Schuko con cavo VDE H05VV-F 3G1.5mm2 15m, con spina italiana 16A, con telaio portacavi

SKU	Box Qty
8834	8

Input Current: 10/16A
Output Current:
Rated Load: 2500W
Input Power: AC:230V
Body Type: PVC, COPPER,PP
Dimension: 357×130×130mm

5M Wire

Prolunga lineare
spina 10A,2p+T prese 10A

SKU	Box Qty
8730	30

Input Current: 10A
Rated Load: 2300W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 230×110×60mm

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

3M Wire

Prolunga lineare
spina 16A,2p+T prese 10/16Aa

SKU	Box Qty
8731	50

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 200×110×40mm

LIGHTED SWITCH

Adattatore rotante,Spina 10A
2 prese 2P+T 10/16A Bipasso+
1 presa Bipasso/Schuko
Con protezione de sovraccarico

SKU	Box Qty
8744	60

Input Current: 10A
Output Current: 10A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 80×75×48mm

5M Wire

Prolunga lineare
spina 16A,2p+T prese 10/16Aa

SKU	Box Qty
8732	30

Input Current: 16A
Rated Load: 3500W
Color: White
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 230×110×60mm

LIGHTED SWITCH

Adattatore Spina 10A
4 prese 10/16A Bipasso
Con protezione de
sovraccarico

SKU	Box Qty
8746	200

Input Current: 10A
Output Current: 10A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 95×70×70mm

LIGHTED SWITCH

Adattatore spina 16A 2 prese 2P+T 10/16A +
1 presa/Schuko con interruttore

SKU	Box Qty
8716	200

Input Current: 16A
Output Current: 16A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 85×75×50mm

LIGHTED SWITCH

Adattatore Spina 10A
2 prese 2P+T 10/16A Bipasso+
1 presa Bipasso/Schuko
Con protezione de sovraccarico

SKU	Box Qty
8743	200

Input Current: 10A
Output Current: 10A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 95×50×40mm

V-TAC®

ELECTRICAL

Universal Adapter

UNIVERSAL ADAPTOR
10A 250V~

SKU	Box Qty
8747	200

Input Current: 10A
Output Current: 10A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 70×55×50mm

Adattatore presa Italiana 1 via 10 / 16A,
con protezione contro le sovratensioni,
con spina Italiana da 16A

SKU	Box Qty
8832	100

Input Current: 10/16A
Output Current:
Rated Load: 3680W
Input Power: AC:200-240V,50Hz
Body Type: PC PP COPPER
Dimension: 80×55×72mm

LIGHTED SWITCH

2 USB PORT

Adattatore
2 vie 10 / 16A presa Italiana e
1 via 10 / 16A presa Italiano / Schuko con
interruttore due porte di ricarica USB 2.1A
spina italiana 16A

SKU	Box Qty
8830	100

Input Current: 10/16A
Output Current:
Rated Load: 1500W
Input Power: AC:200-240V,50Hz
Body Type: PC COPPER
Dimension: 120×84×54mm

Spina 2p+t 10A

SKU	Box Qty
8717	200

Input Current: 10A
Output Current: 10A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 65×32×15mm

LIGHTED SWITCH

Adattatore 3 vie 10 / 16A presa Italiana
con interruttore, con spina Italiana 16A

SKU	Box Qty
8831	100

Input Current: 10/16A
Output Current:
Rated Load: 1500W
Input Power: AC:200-240V,50Hz
Body Type: PC COPPER
Dimension: 70×64×54mm

Spina 2p+t 16A

SKU	Box Qty
8718	200

Input Current: 16A
Output Current: 16A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 70×43×20mm

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

Spina 2p+t 10A

SKU	Box Qty
8719	200

Input Current: 10A
Output Current: 10A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 70×40×40mm

Adattatore spina 16A
3 presa 10A /16A Bipasso

SKU	Box Qty
8722	200

Input Current: 16A
Output Current: 16A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 60×47×40mm

Adattatore spina 16A
presa 2p+T 10A schuko

SKU	Box Qty
8720	200

Input Current: 16A
Output Current: 16A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 75×40×40mm

Adattatore spina 10A
2presa 10/ 10A schuko

SKU	Box Qty
8723	200

Input Current: 10A
Output Current: 10A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 75×50×40mm

10A adattatore spina 10 A
3 prese10 A

SKU	Box Qty
8721	200

Input Current: 10A
Output Current: 10A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 60×50×48mm

Adattatore spina 16A
2presa 10/ 16A Bipasso + 1 Bipasso/schuko

SKU	Box Qty
8724	200

Input Current: 16A
Output Current: 16A
Rated Load: 1500W
Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 75×50×40mm

V-TAC®

ELECTRICAL

Adattatore spina 10A
4 prese 10A

SKU	Box Qty
8725	200

Input Current: 10A
Output Current: 10A
Rated Load: 1500W

Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 95×60×45mm

Prese 10A /16A Bipasso
2p+T

SKU	Box Qty
8728	200

Input Current: 16A
Output Current: 16A
Rated Load: 1500W

Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 65×43×25mm

Spina 2p+t 16A

SKU	Box Qty
8726	200

Input Current: 16A
Output Current: 16A
Rated Load: 1500W

Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 95×60×45mm

Spina 2p+t 10A

SKU	Box Qty
8727	200

Input Current: 10A
Output Current: 10A
Rated Load: 1500W

Input Power: AC:250V,50/60Hz
Body Type: PC+COPPER
Dimension: 65×35×25mm

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS



CABLE TIE

Keep installations clean with V-TAC cable ties. It is made of nylon and Stainless Steel. Cable ties feature high tensile strength and are an essential item for any toolbox.

Key Features

- High quality
- Suitable for a multitude of uses
- Easy to thread

Application

The nylon cable ties are widely used in electricals & electronics industry including electronic factories, computers, TV sets, and other internal connections, lighting, motors, and electronic toys.

V-TAC®

ELECTRICAL

V-TAC®

ELECTRICAL

Stainless Steel Cable Tie

- Secure loose wires and components easily with no slipping
- Features locking mechanism
- Stainless steel cable tie of 304 Grade – Non-Rustable

SKU	Maximum Hold	Dimension	Box Qty
11188	60 Kgs	4.6×200mm	50
11189	60 Kgs	4.6×250mm	50
11190	60 Kgs	4.6×300mm	50
11191	60 Kgs	4.6×350mm	50

Nylon Cable Tie Black

- High quality
- Easy to thread
- Suitable for a multitude of uses

ULTRAVIOLET PROTECTION

SKU	Maximum Hold	Dimension	Box Qty
11160	8 Kgs	2.5×100mm	500
11162	8 Kgs	2.5×150mm	400
11164	8 Kgs	2.5×200mm	300
11166	18 Kgs	3.5×150mm	250
11168	18 Kgs	3.5×200mm	200
11169	18 Kgs	3.5×250mm	150
11170	18 Kgs	3.5×300mm	150
11172	22 Kgs	4.5×150mm	200
11174	22 Kgs	4.5×300mm	100
11176	22 Kgs	4.5×350mm	100
11177	22 Kgs	4.8×200mm	150
11178	23 Kgs	7.6×300mm	60

Nylon Cable Tie White

- High quality
- Easy to thread
- Suitable for a multitude of uses

SKU	Maximum Hold	Dimension	Box Qty
11159	8 Kgs	2.5×100mm	500
11161	8 Kgs	2.5×150mm	400
11163	8 Kgs	2.5×200mm	300
11165	18 Kgs	3.5×150mm	250
11167	18 Kgs	3.5×200mm	200
11171	22 Kgs	4.5×150mm	200
11175	22 Kgs	4.5×350mm	100
11173	22 Kgs	4.5×300mm	100

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

UVC LAMPS

V-TAC new ultraviolet Germicidal lamp can deodorize and sanitize those hard-to-reach places on your equipment, making sure you get a greater than 99.9% kill rate of bacteria, viruses, and molds.

These UV ultraviolet disinfection sterilization lights can be widely used in kitchen, living room, bedroom, bathroom, closet, office, school, and hospital.

BE SAFE

V-TAC®

ELECTRICAL

V-TAC®

ELECTRICAL

Kills Bacteria | Kills Virus | Kills Germs

38W

UVC Lamp With Sensor & Remote

Model	SKU	Box Qty
VT-3338	11224 – EU PLUG 11209 – BS PLUG	9

Ozone | RADAR SENSOR | 60m² Coverage Area

- Covers up to 60m2 with a wavelength of 185–253 NM and 360° sterilization
- Kills bacteria, mites & virus
- Ozone, radar sensor and remote control functionality
- Radar sensor working distance above 5 meters
- Display screen with working time and status
- 15/30/60 minutes timer on ON/OFF Switch setting
- 10 seconds delay
- Touch Switch and LED working instruction light
- After Sterilization, ventilate for 20–30 minutes

Kills Bacteria | Kills Virus | Kills Germs

38W

UVC Germicidal Lamp

Model	SKU	Box Qty
VT-3239	11208 – EU PLUG	9

Ozone | RADAR SENSOR | 60m² Coverage Area

- Covers up to 60m2 with a wavelength of 185–253 NM and 360° sterilization
- Kills bacteria, mites & virus
- Ozone and radar sensor function
- Radar sensor working distance above 5 meters
- Display screen with working time and status
- 15/30/60 minutes timer on ON/OFF Switch setting
- 10 seconds delay
- Touch Switch and LED working instruction light
- After Sterilization, ventilate for 20–30 minutes

DEKRA | TÜV SÜD | www.tuv.com ID 1111227954 | RoHS | CE/EMC

ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

Kills Bacteria | Kills Virus | Kills Germs

38W

UVC Germicidal Lamp

Model	SKU	Box Qty
VT-3238	11203 – EU PLUG	12

Ozone 60m² Coverage Area

- Double Protection – UV & Ozone
- Covers up to 60m2, 360 degrees radiation
- Kills bacteria, mites & virus
- 30 minutes timer
- 10 seconds delay
- Touch Switch
- After Sterilization, ventilate for 20–30 minutes

Kills Bacteria | Kills Virus | Kills Germs

14W

UV Lamps Rechargeable

Model	SKU	Box Qty
VT-3214	11220	20

BATTERY RECHARGEABLE | METAL SHELL

- 3cm distance, uniform back and forth sweeping 5–6 times to complete disinfection
- 99.9% bactericidal rate with no harmful chemicals
- Dark violet power 14MW
- UVC wavelength: 275nm
- Irradiation distance: <30mm
- 3000mA rechargeable battery
- Quickly kills all kinds of common germs
- Size: 268×22mm



ELECTRICAL SOLUTIONS

At V-TAC, we believe in utilizing existing technology and resources to continuously improve our way of living. This new category comprises our latest tech innovations for a safe, modern, and comfortable space.

Key Features

- Includes Insect Killer, the Robot Vacuum Cleaner & Convection Heaters
- Made with high-quality materials for long-lasting performance
- Easy to install and operate
- Designed for residential & commercial use

V-TAC®

ELECTRICAL

ELECTRICAL

V-TAC®

- Touchscreen control panel.
- LCD Display.
- With Infrared Remote.
- Feet with lockable swiveling wheels.
- Timer from 1 to 24 hours to turn on/off as per desired time.
- Aluminium heating element.
- Self-resetting thermostat and thermal fuse.
- Noiseless heating.
- Temperature Setting from 15°-35°.
- Tempered glass panel.
- Splash water protected (IP24)
- Cable length: 1.5M
- Input: AC220-240V, 50/60 Hz
- Plug Type: EU Plug

TOUCHSCREEN

LCD DISPLAY

TIMER

TEMPERATURE SETTING

TEMPERED GLASS PANEL

Glass Convector Heater

Model	SKU	Watts	Box Qty
VT-2000WRD	8663 (WHITE) 8664 (BLACK)	2000W	1

Also available in WHITE COLOR

www.tuv.com ID 1111227954

- Aluminium heating element.
- Self-resetting thermostat and thermal fuse.
- Noiseless heating.
- Free standing.
- Tempered glass panel.
- Splash water protected (IP24)
- Cable length: 1.5M
- Input: AC220-240V, 50/60 Hz
- Plug Type: EU Plug

ALUMINUM HEATING ELEMENT

SELF-RESETTING THERMOSTAT AND THERMAL FUSE

TEMPERED GLASS PANEL

Glass Convector Heater

Model	SKU	Watts	Box Qty
VT-2000	8661 (WHITE) 8662 (BLACK)	2000W	1

Also available in WHITE COLOR

www.tuv.com ID 1111227954

V-TAC®

ELECTRICAL

Electronic Insect Killer

Perfect for home, Office, Garage, kitchens, Schools, Hospitals, Courtyard, and Commercial Areas

- Lamp life time up to 8000-hour
- Slim design – ON/OFF switch
- Removable tray
- For Indoor Use Only
- Housing made of special treated, Aluminium, scratch-proof, corrosion-proof and easy to clean
- Power supply: AC:220-240V 50/60Hz

Wire chain for hanging or set it on a flat surface.

Model	SKU	Watts	Coverage Area	Size	Box Qty
VT-3216	11179 – (EU PLUG) 11179 – BS(BS PLUG)	16W	50m2	280×354×93.5mm	6
VT-3220	11180- (EU PLUG) 11180 – BS(BS PLUG)	20W	80m2	280×397×93.5mm	6
VT-3230	11181- (EU PLUG) 11181 – BS(BS PLUG)	30W	100m2	280×532×93.5mm	6
VT-3240	11182- (EU PLUG) 11182 – BS(BS PLUG)	40W	150m2	280×655×93.5mm	4

Insect Killer Tubes

SKU	Watts	Size	Box Qty
11215	8W	Ø15×305mm	100
11216	10W	Ø25×345mm	100
11217	15W	Ø25×505mm	50
11218	20W	Ø25×605mm	50

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

Robotic Vacuum Cleaner

- Automatic Robot Vacuum Cleaner
- Keep it Clean: Sweep, Dust & Vacuum
- Smart, Self-Programmed Cleaning Path Navigation
- Dustbin Capacity 430ml
- Construction Material: ABS Housing
- Preset Multi-Clean Modes: Auto, Spot, Edge
- Cleaning area coverage upto 120Sq. Meters
- One Button Operation & Auto-Start Activation
- 'Bag-less' Waste Bin Integrated HEPA Filter
- Anti-Fall / Anti-Collision Sensors
- Built-in Rechargeable Battery 14.4V Li-ion, 2000mAh
- Power Supply 120-240V (12V Power Adaptor)
- Dual Spinning Side Brushes Captures Dirt & Lifts Debris
- Works on Hardwood, Tile, Marble & Hard Carpet Floors
- Noise level less than 65db
- Suction Power Brusless Motor 800PA

MULTI CLEANER
Hardwood, Tile, Marble
& Hard Carpet Floors

SMART CLEAN
Smart, Self-Programmed
Cleaning Path Navigation

Model	SKU	Size	Box Qty
VT-5522	8659 BLACK 8660 WHITE+BLUE	315×315×76mm	4





DECORATIVE FANS

Add a modern touch to your room with V-TAC's Ceiling Fans. Available with up to 3 speeds and in different sizes, these fans o er quiet, efficient, and wobble-free performance. Additionally, the fixtures feature integrated LEDs and come in several finishes to match any interior decor. Equipped with a pull chain and both forward and reverse function modes, V-TAC's ceiling fans are a modern twist on a classic design.

Key Features

- Both AC and DC motor variations available
- Available in a range of sizes and finishes
- Remote Control and Pull-chain for speed control and On/Off
- Forward and reverse function for cool or warm airflow

V-TAC®

ELECTRICAL

ELECTRICAL

V-TAC®

Ceiling Fan AC Motor

Model	SKU	Box Qty
VT-6552-3-W	2866	1

65W

3 ABS PLASTIC BLADES

AC -POWER MOTOR

- 52" (132CM) Decorative ceiling fan
- With forward and reverse function
- 3 ABS plastic blades
- AC powerful motor:172 × 20mm, 3.85kg
- Revolutions per minute:180±10 RPM
- Blade angle 13°
- 3 speeds and light remote control
- Motor Power AC:220-240V,50HZ,65W
- G.W.:7.9KG / N.W.:7.1KG

Ceiling Fan AC Motor

Model	SKU	Box Qty
VT-6552-3-BR	2867	1

65W

3 ABS PLASTIC BLADES

AC -POWER MOTOR

- 52" (132CM) Decorative ceiling fan
- With forward and reverse function
- 3 ABS plastic blades
- AC powerful motor:172 × 20mm, 3.85kg
- Revolutions per minute:180±10 RPM
- Blade angle 13°
- 3 speeds and light remote control
- Motor Power AC:220-240V,50HZ,65W
- G.W.:7.9KG / N.W.:7.1KG

Ceiling Fan AC Motor

Model	SKU	Box Qty
VT-6552-3-BL	2868	1

65W

3 ABS PLASTIC BLADES

AC -POWER MOTOR

- 52" (132CM) Decorative ceiling fan
- With forward and reverse function
- 3 ABS plastic blades
- AC powerful motor:172 × 20mm, 3.85kg
- Revolutions per minute:180±10 RPM
- Blade angle 13°
- 3 speeds and light remote control
- Motor Power AC:220-240V,50HZ,65W
- G.W.:7.9KG / N.W.:7.1KG

DEKRA TÜV SÜD www.tuv.com ID 11111227954 GS RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®

ELECTRICAL

Ceiling Fan AC Motor

Model	SKU	Box Qty
VT-6042-4	7914	1

50W

4 MDF BLADES | 3 SPEEDS AND LIGHT PULL CHAIN | AC -POWER MOTOR

- 42" (107CM) Decorative ceiling fan
- With forward and reverse function
- 4 MDF blades with cane and double color
- Powerful Motor:153 × 10mm, 2.3kg
- Revolutions per minute:220±10 RPM
- Blade angle 12°
- 3 speeds and light pull chain
- 1xE27 light kit (light source NOT included)
- Motor Power AC:220V,50Hz,50W (power of the motor)
- G.W.: 4.0KG / N.W.: 3.28KG

Ceiling Fan AC Motor

Model	SKU	Box Qty
VT-6056-4	7921	1

55W

4 GLASS SHADES | 3 SPEEDS AND LIGHT PULL CHAIN | AC -POWER MOTOR

- 52" (132CM) Decorative ceiling fan
- With forward and reverse function
- 4 MDF blades with cane and double color
- Powerful Motor:153 × 11mm, 2.3kg
- Revolutions per minute:190±10 RPM
- Blade angle 12°
- 3 speeds and light pull chain
- 4xE27 light kit (light source NOT included)
- 4 glass shade
- Motor Power AC:220V,50HZ,55W (power of the motor)
- G.W.:4.5KG / N.W.:3.8KG

Ceiling Fan AC Motor

Model	SKU	Box Qty
VT-6054-4-1	7917	1

60W

LIGHT KIT | 4 MDF BLADES | AC -POWER MOTOR

- 52" (132CM) Decorative ceiling fan
- With forward and reverse function
- 4 MDF blades
- Powerful Motor:153 × 15mm, 2.3kg
- Revolutions per minute:220±10 RPM
- Blade angle 13°
- 3 speeds and light remote control
- 2xE27 light kit (light source NOT included)
- Motor Power AC:220V,50HZ,60W (power of the motor)
- G.W.: 7.6KG / N.W.: 6.8KG

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

Ceiling Fan AC Motor

Model	SKU	Box Qty
VT-6043-4	7915	1

60W

LIGHT KIT | 4 MDF BLADES | AC -POWER MOTOR

- 42" (107CM) Decorative ceiling fan
- With forward and reverse function
- 4 MDF blades
- Powerful Motor:153 × 15mm, 2.3kg
- Revolutions per minute:220±10 RPM
- Blade angle 13°
- 3 speeds and light remote control
- 15W 3IN1 CCT – 1500 Lumens
- Motor Power AC:220V,50HZ,60W (power of the motor)
- G.W.: 6.8KG / N.W.: 6.1KG

Ceiling Fan AC Motor

Model	SKU	Box Qty
VT-6053-5	7916	1

60W

LIGHT KIT | 5 MDF BLADES | AC -POWER MOTOR

- 52" (132CM) Decorative ceiling fan
- With forward and reverse function
- 5 MDF blades
- Powerful Motor:153 × 15mm, 2.3kg
- Revolutions per minute:190±10 RPM
- Blade angle 13°
- 3 speeds and light remote control
- 2xE27 light kit (light source NOT included)
- Power:AC:220V,50HZ,60W (power of the motor)
- G.W.: 7.3KG / N.W.:6.7KG

Ceiling Fan AC Motor

Model	SKU	Box Qty
VT-6052-5	7913	1

60W

LIGHT KIT | 5 MDF BLADES DOUBLE COLOR | AC -POWER MOTOR

- 52" (132CM) Decorative ceiling fan
- With forward and reverse function
- 5 MDF blades double color
- Powerful Motor:153 × 15mm, 2.3kg
- Revolutions per minute:190±10 RPM
- Blade angle 13°
- 3 speeds and light remote control
- 15W 3IN1 CCT – 1500 Lumens
- Power:AC:220V,50HZ,60W (power of the motor)
- G.W.: 7.3KGS / N.W.: 6.5KGS

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®

ELECTRICAL

Ceiling Fan DC Motor

Model	SKU	Box Qty
VT-6054-4	7918	1

35W

LIGHT KIT | 4 MDF BLADES | DC -POWER MOTOR

- 52" (132CM) Decorative ceiling fan
- Reversable Double Color Blades
- With forward and reverse function
- 4 MDF blades
- DC powerful motor:153 × 15mm, 2.1kg
- Revolutions per minute:220±10 RPM
- Blade angle 13°
- 5 speeds and light remote control
- 2xE27 light kit (light source NOT included)
- Motor Power DC:220V,50HZ,35W (energy-saving)
- G.W.: 7.3KG / N.W.: 6.5KG

Ceiling Fan DC Motor

Model	SKU	Box Qty
VT-6055-3-1	7919	1

35W

LIGHT KIT | 3 ABS PLASTIC BLADES | DC -POWER MOTOR

- 52" (132CM) Decorative ceiling fan
- With forward and reverse function
- 3 ABS plastic blades
- DC powerful motor:153 × 15mm, 2.1kg
- Revolutions per minute:180±10 RPM
- Blade angle 13°
- 5 speeds and light remote control
- 15W 3IN1 CCT – 1500 Lumens
- Motor Power DC:220V,50HZ,35W (energy-saving)
- G.W.:7.2KG / N.W.:6.5KG

Ceiling Fan DC Motor

Model	SKU	Box Qty
VT-6055-3	7920	1

35W

LIGHT KIT | 3 ABS PLASTIC BLADES | DC -POWER MOTOR

- 52" (132CM) Decorative ceiling fan
- With forward and reverse function
- 3 ABS plastic blades
- DC powerful motor:153 × 15mm, 2.1kg
- Revolutions per minute:180±10 RPM
- Blade angle 13°
- 5 speeds and light remote control
- 15W 3IN1 CCT – 1500 Lumens
- Motor Power DC:220V,50HZ,35W (energy-saving)
- G.W.:7.2KG / N.W.:6.5KG

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®

Ceiling Fan DC Motor

Model	SKU	Box Qty
VT-3042-3	7929	1

35W

LIGHT KIT | 3 PC PLASTIC BLADES | DC -POWER MOTOR

- 42" (107CM) Decorative ceiling fan
- With forward and reverse function
- 3 PC Plastic blades
- DC powerful motor:153 × 15mm, 2.3kg
- Revolutions per minute:220±10 RPM
- Blade angle 13°
- 5 speeds and light remote control
- LED 30W 3IN1 CCT – 3000 Lumens
- Motor Power DC:220V,50HZ,35W (motor)
- G.W.: 9.8KG / N.W.: 9.1KG

Box Fan AC Motor

Model	SKU	Box Qty
VT-5022-B	7934	1

45W

LED - 3IN1 CCT | 7 MDF BLADES | AC -POWER MOTOR

- 24inch(60cm) Decorative ceiling box fan
- 45W AC Motor, 220V 50Hz
- 35W LED (3000lm) – 3IN1 CCT (3000K/4000K/6500K)
- 3 Speeds(low, medium and high) and light remote control
- 7 ABS Blades
- Blade angle 13°
- 360° Air flow
- Revolutions per minute 1100±10RPM

Box Fan AC Motor

Model	SKU	Box Qty
VT-5022-G	7935	1

45W

LED - 3IN1 CCT | 7 MDF BLADES | AC -POWER MOTOR

- 24inch(60cm) Decorative ceiling box fan
- 45W AC Motor, 220V 50Hz
- 35W LED (3000lm) – 3IN1 CCT (3000K/4000K/6500K)
- 3 Speeds(low, medium and high) and light remote control
- 7 ABS Blades
- Blade angle 13°
- 360° Air flow
- Revolutions per minute 1100±10RPM

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®

ELECTRICAL

Stand Fan Cross Base

Model	SKU	Box Qty
VT-4016-3	7922	1

40W Oscillation
Low | Medium | High

- 16" STAND FAN
- AC: 220-240V~50/60Hz 40W
- 3 speed control
- Oscillation function
- 1.2m height
- 600mm Cross Base
- GW:2.6KGS
- Size:600 × 600 × 1200mm



Stand Fan Round Base

Model	SKU	Box Qty
VT-5016-5	7923	1

55W Oscillation
Low | Medium | High

- 16" STAND FAN
- AC: 220-240V~50/60Hz 55W
- 3 speed control
- Oscillation function
- 1.25m height
- 410mm Round Base
- GW:4.3KGS
- Size:430 × 410 × 1200mm

Desk Fans

Model	SKU	Size
VT-4012-3	7924	12"
VT-4017-3	7925	16"

40W Oscillation
Low | Medium | High

- AC: 220-240V~50/60Hz 40W
- 3 speed control
- Oscillation function
- GW:2.0KGS
- 12" Size: 340 × 260 × 480mm
- 16"Size: 410 × 260 × 510mm
- Box Qty: 1pc

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

ELECTRICAL

V-TAC®



45W

Tower Fan

Model	SKU	Box Qty
VT-4538	7926	1

3 Fan Speed
Low | Medium | High

Oscillation
Low | Medium | High

- Voltage/Freq: AC:220-240V,50/60Hz
- Size(inches): 31
- Material: ABS
- Unit Color: White
- Speed: 3(Low-Med-High)
- Function: Oscillation Function
- Timer: 1hr(Max)
- Plug Type: EU
- IP Rating: IP20



55W

Tower Fan

Model	SKU	Box Qty
VT-5536	7900	1

3 Fan Speed
Low | Medium | High

3 Wind Mode
Normal | Natural | Sleep

- Voltage/Freq: AC:220-240V,50Hz
- Size(inches): 36
- Material: ABS
- Unit Color: White
- Speed: 3(Low-Med-High)
- Wind Mode: 3 (Normal-Natural-Sleep)
- Timer: 1-15hrs(Max)
- Power Cord Length: 1.8m
- Plug Type: EU
- IP Rating: IP20

V-TAC®

ELECTRICAL



55W

Tower Fan

Model	SKU	Box Qty
VT-5546	7901	1

3 Fan Speed
Low | Medium | High

3 Wind Mode
Normal | Natural | Sleep

- Voltage/Freq: AC:220-240V,50Hz
- Size(inches): 46
- Material: ABS
- Unit Color: Black Finish
- Speed: 3(Low-Med-High)
- Wind Mode: 3 (Normal-Natural-Sleep)
- Timer: 1-15hrs(Max)
- Power Cord Length: 1.75m
- Plug Type: EU
- IP Rating: IP20



55W

Tower Fan

Model	SKU	Box Qty
VT-5547	7902	1

3 Fan Speed
Low | Medium | High

3 Wind Mode
Normal | Natural | Sleep

- Voltage/Freq: AC:220-240V,50Hz
- Size(inches): 46
- Material: ABS
- Unit Color: White & Black Finish
- Speed: 3(Low-Med-High)
- Wind Mode: 3 (Normal-Natural-Sleep)
- Timer: 1-15hrs(Max)
- Power Cord Length: 1.8m
- Plug Type: EU
- IP Rating: IP20

DEKRA TÜV SÜD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

AUDIO

V-TAC®

Mist Fan with Wheels

Model	SKU	Box Qty
VT-8217-3	7936	1

80W Oscillation
Low | Medium | High

- 16" (40.6CM) Mist fan
- With 430mm diameter radial grill
- 3PP blade with a speed of Max 55.96m³/Min
- Remote type selection with oscillation
- Designed with 3 variants of speed: Low, Medium, and High
- Adjustable Mist
- Timer (with Remote)7.5H
- Water Tank Capacity 3.2 Litre
- 6 Wheels for easy moving

WIRELESS SPEAKERS

Bring the music anywhere you want to — these speakers are perfect for beach parties, your garden, or any indoor or outdoor event. Achieve full sound clarity even without a full sound system — enjoy the convenience of our quality, perfect for music and movies. Bring the sound of the holiday to birthdays, special occasions and occasional parties. Powerful bass enables your party people to enjoy stronger music throughout the venue.

This multifunctional microphone can be used for various activities, including voice speech, karaoke and instrument use

Key Features

- Rechargeable
- RGB LED lights with On/Off switch.
- FM Radio function & Mic input.
- Includes one wired microphone, remote control & USB rechargeable cable.

AUDIO

V-TAC®

NEW

Trolley Speaker

SOUNDOR 5
Wireless Party Speaker

Model	SKU	Box Qty
VT-6204-2	6663	12

2X10W

- P.M.P.O 150W
- Rechargeable Trolley speaker 2×4 inch woofer.
- DC:5V input power, 1A adapter.
- RGB LED lights with On/Off switch.
- Supports Wireless connection, USB and FM Radio.
- Rechargeable battery 3.7V/3000mAh.
- Charging time 5-6 Hours.
- Working time 3-6 Hours.
- FM Radio-Frequency 87.5-108MHz.
- AUX and MIC input.
- Dimensions:185.3×177×410.5mm
- Includes one USB cable.

TWS TRUE WIRELESS STEREO

150 P.M.P.O

Party Lights

3-6 hrs
3-6 Hours Battery Time

Wireless Connectivity

NEW

Trolley Speaker

SOUNDOR 5
Wireless Party Speaker

Model	SKU	Box Qty
VT-6203-2	6664	20

2X10W

- P.M.P.O 150W
- Rechargeable Trolley speaker 2×3 inch woofer with handle.
- DC:5V input power, 1A adapter.
- RGB LED lights with On/Off switch.
- Supports Wireless connection, USB and FM Radio.
- Rechargeable battery 3.7V/3000mAh.
- Charging time 5-6 Hours.
- Working time 3-6 Hours.
- FM Radio-Frequency 87.5-108MHz.
- AUX and MIC input.
- Dimensions:153.7×143.7×341.5mm
- Includes one USB cable.

TWS TRUE WIRELESS STEREO

150 P.M.P.O

Party Lights

3-6 hrs
3-6 Hours Battery Time

Wireless Connectivity

V-TAC®

AUDIO

NEW

Trolley Speaker

SOUNDOR 6x2
Wireless Party Speaker

Model	SKU	Box Qty
VT-4000W	7676	1 pc

2X10W

- P.M.P.O 400W
- 2×8Inch Speaker
- Output:10Wx2
- Frequency: 100HZ—20KHZ
- Power Supply: DC:5V
- Battery: 3.7V 2400mAh
- 230×210×485mm
- Includes USB cable,User manual,Remote control & One wired mic
- Function: BT/USB/TF/FM /AUX/Three knob/Karaoke/
- Running LED light/Display/TWS/3knobs

NEW

Trolley Speaker

SOUNDOR 8x2
Wireless Party Speaker

Model	SKU	Box Qty
VT-6000W	7677	1 pc

2X15W

- P.M.P.O 600W
- Output: 15Wx2
- Frequency: 60HZ—20KHZ
- 2×8Inch Speaker with Tweeter
- Power Supply: DC:5V
- Battery: 3.7V 2400mAh
- 260×240×605mm
- Includes USB cable,User manual,Remote control,One wired mic
- Function:BT/USB/TF/FM /AUX/three knob /Karaoke/
- Running LED light/Display/TWS/3knobs

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

AUDIO

V-TAC®

Trolley Speaker

SOUNDOR 8x2
Wireless Party Speaker

Model	SKU	Box Qty
VT-6282-2	8990	1

40W

- P.M.P.O 150W
- Rechargeable Trolley speaker 8 inch woofer with handle and RF Control.
- AC:100-240V, 50/60Hz input power.
- RGB LED lights with On/Off switch.
- Supports Wireless connection, USB and FM Radio.
- Rechargeable battery 7.4V/5000mAh.
- Charging time 5-6 Hours.
- Working time 2-4 Hours.
- FM Radio-Frequency 87.5-1080MHz.
- AUX, Guitar and MIC input.
- Working distance up to 15 meters in open space
- Remote Control distance upto 5m in open space
- Dimensions:320×310×685mm
- Includes one Wireless microphone, Remote Control and Power adaptor.

TWS
TRUE WIRELESS STEREO

150 P.M.P.O

LED Light with On/Off Switch

2-4 Hours Batteru Time

Wireless - USB Micro-SD - Remote Control

Trolley Speaker

SOUNDOR 8
Wireless Party Speaker

Model	SKU	Box Qty
VT-6208	7735	1 pc

15W

- P.M.P.O 300W
- Rechargeable Trolley speaker – 8 inch with handle.
- Woofer:203mm with an output of 15W.
- RGB LED lights with On/Off switch.
- Input power AC:100-240V.
- Rechargeable battery 3.7V/2200mAh.
- Charging time 3-4 Hours.
- Working time 2-4 Hours.
- Types of control – Wireless, USB, Micro-SD & remote control.
- FM Radio function & Mic input.
- Working distance up to 15 meters in open space.
- Dimensions:360×235×190mm
- Includes one wired microphone, remote control & USB rechargeable cable.

300 P.M.P.O

RGB LED Light with On/Off Switch

2-4 Hours Batteru Time

Wireless - USB Micro-SD - Remote Control

V-TAC® AUDIO

Trolley Speaker

SOUNDOR 12
Wireless Party Speaker

Model	SKU	Box Qty
VT-6212	7736	1 pc

35W

- P.M.P.O 500W
- Rechargeable Trolley speaker – 12 inch with handle and wheels.
- Woofer:305mm with an output of 35W.
- RGB LED lights with On/Off switch.
- Input power AC:100-240V.
- Rechargeable battery 3.7V/2200mAh.
- Charging time 3-4 Hours.
- Working time 2-4 Hours.
- Types of control – Wireless, USB, Micro-SD & remote control.
- FM Radio function & Mic input.
- Working distance up to 15 meters in open space.
- Dimensions:510×320×270mm
- Includes one wired microphone, remote control & power cord.

500 P.M.P.O | RGB LED Light with On/Off Switch | 2-4 Hours Battery Time | Wireless - USB Micro-SD - Remote Control

Trolley Speaker

SOUNDOR 12
Wireless Party Speaker

Model	SKU	Box Qty
VT-6312	7737	1 pc

35W

- P.M.P.O 500W
- Rechargeable Trolley speaker – 12 inch with handle and wheels.
- Woofer:305mm with an output of 35W.
- RGB LED lights with On/Off switch.
- Input power AC:100-240V.
- Rechargeable battery 3.7V/2200mAh.
- Charging time 3-4 Hours.
- Working time 2-4 Hours.
- Types of control – Wireless, USB, Micro-SD & remote control.
- FM Radio function & Mic input.
- Working distance up to 15 meters in open space.
- Dimensions:510×320×295mm
- Includes one wired microphone, remote control & power cord.

500 P.M.P.O | RGB LED Light with On/Off Switch | 2-4 Hours Battery Time | Wireless - USB Micro-SD - Remote Control

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

AUDIO

V-TAC®

Trolley Speaker

SOUNDOR 15
Wireless Party Speaker

Model	SKU	Box Qty
VT-6315	7738	1 pc

50W

- P.M.P.O 600W
- Rechargeable Trolley speaker – 15 inch with handle and wheels.
- Woofer:381mm with an output of 50W.
- RGB LED lights with On/Off switch.
- Input power AC:100-240V.
- Rechargeable battery 7.4V/2200mAh.
- Charging time 3-4 Hours.
- Working time 2-4 Hours.
- Types of control – Wireless, USB, Micro-SD & remote control.
- FM Radio function & Mic input.
- Working distance up to 15 meters in open space.
- Dimensions:600×370×340mm
- Includes one wired microphone, one wireless microphone, remote control & power cord.

600 P.M.P.O | RGB LED Light with On/Off Switch | 2-4 Hours Batteru Time | Wireless - USB Micro-SD - Remote Control

Trolley Speakers

SOUNDOR 6x2
Wireless Party Speaker

Model	SKU	Box Qty
VT-6207-2	8680	1 Pc

30W

- P.M.P.O 700W
- Rechargeable Trolley speaker – Dual 6.5 inch Woofer with Handle.
- Woofer:2×165.1mm with an output of 30W.
- RGB LED lights with On/Off switch.
- Input power AC:100-240V.
- Rechargeable battery 7.4V/2600mAh.
- Charging time 5-6 Hours.
- Working time 2-4 Hours.
- Types of control – Wireless, USB, Micro-SD & remote control.
- FM Radio function & Mic input.
- Working distance up to 15 meters in open space.
- Dimensions:610×240×230mm
- Includes one wired microphone, remote control & USB rechargeable cable.

700 P.M.P.O | LED Light with On/Off Switch | 2-4 Hours Batteru Time | Wireless - USB Micro-SD - Remote Control

V-TAC®

AUDIO

Rechargeable Speaker

SOUNDOR 6x2
Wireless Party Speaker

Model	SKU	Box Qty
VT-6307-2	8981	1 pc

35W

- P.M.P.O 700W
- Rechargeable speaker – Dual 6.5 inch woofer with handle.
- Woofer:2×6.5inch
- Disco LED lights.
- Input power AC:100-240V.
- Rechargeable battery 7.4V 3000mAh Battery.
- Charging time 5-6 Hours.
- Working time 2-4 Hours.
- Types of control – Wireless, USB, SD & remote control.
- FM Radio.
- Aux input/Mic input option.
- Dimensions:255×245×555mm
- Includes one power adaptor, one wired microphone & remote control.

TWS TRUE WIRELESS STEREO

700 P.M.P.O

LED Light with On/Off Switch

2-4 Hours Battery Time

Wireless - USB Micro-SD - Remote Control

Rechargeable Speaker

SOUNDOR 8x2
Wireless Party Speaker

Model	SKU	Box Qty
VT-6308-2	8980	1 pc

40W

- P.M.P.O 800W
- Rechargeable speaker – Dual 8 inch with handle and wheels.
- Woofer:2×203mm with an output of 40W.
- Disco lights with On/Off switch.
- Input power AC:100-240V.
- Rechargeable battery 7.4V 3000mAh Battery.
- Charging time 5-6 Hours.
- Working time 2-4 Hours.
- Types of control – Wireless, USB, SD & remote control.
- FM Radio.
- Aux input/Mic input/Guitar input option.
- Dimensions:320×310×685mm
- Includes one wired microphone & remote control.

TWS TRUE WIRELESS STEREO

800 P.M.P.O

LED Light with On/Off Switch

2-4 Hours Battery Time

Wireless - USB Micro-SD - Remote Control

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

AUDIO

V-TAC®

Rechargeable Speaker

SOUNDOR 10 x2 Wireless Party Speaker

Model	SKU	Box Qty
VT-6310-2	8982	1 pc

100W

- P.M.P.O 2000W
- Rechargeable speaker – Dual 10 inch woofer with handle.
- Woofer:2×254mm
- Disco LED lights.
- Input power AC:100-240V.
- Rechargeable battery 12V/7.5A Battery.
- Charging time 5-6 Hours.
- Working time 2-4 Hours.
- Types of control – Wireless, USB, SD & remote control.
- FM Radio.
- Aux input/Mic/ Guitar input option.
- Dimensions:340×320×862mm
- Includes UHF Microphone & remote control.

TWS TRUE WIRELESS STEREO

2000 P.M.P.O

LED Light with On/Off Switch

2-4 Hours Batteru Time

Wireless - USB Micro-SD - Remote Control

Trolley Speaker

SOUNDOR 10 x2 Wireless Party Speaker

Model	SKU	Box Qty
VT-6210-2	7734	1 pc

120W

- P.M.P.O 2000W
- Rechargeable Trolley speaker – Dual 10 inch with handle and wheels.
- Woofer:2×254mm with an output of 120W.
- Disco lights with On/Off switch.
- Input power AC:100-240V.
- Rechargeable battery 12V/4.5A Acid Battery.
- Charging time 5-6 Hours.
- Working time 2-4 Hours.
- Types of control – Wireless, USB, SD & remote control.
- FM Radio function.
- Aux input/Mic input/Guitar input.
- Working distance up to 15 meters in open space.
- Dimensions:870×310×290mm
- Includes one wireless microphone, one wired microphone & remote control.

2000 P.M.P.O

Woofer with Disco Light with On/Off Switch

2-4 Hours Batteru Time

Wireless - USB Micro-SD - Remote Control

V-TAC®

AUDIO

Trolley Speaker

SOUNDOR 15 X2
Wireless Party Speaker

Model	SKU	Box Qty
VT-6215-2	7733	1 pc

150W

- P.M.P.O 2500W
- Rechargeable Trolley speaker – Dual 15 inch with handle and wheels.
- Woofer:2×381mm with an output of 150W.
- Disco lights with On/Off switch.
- Input power AC:100-240V.
- Rechargeable battery 12V/7.2A Acid Battery.
- Charging time 5-6 Hours.
- Working time 2-4 Hours.
- Types of control – Wireless, USB, SD & remote control.
- FM Radio with antenna.
- Aux input/Mic input/Guitar input and Recording option.
- Working distance up to 15 meters in open space.
- Dimensions:1100×450×350mm
- Includes one wireless microphone, one wired microphone & remote control.

DEKRA TÜV SÜD CE/EMC ACCREDITATION FROM TOP EUROPEAN LABS

COMING SOON

V-TAC®

SOLAR ENERGY

5+5 Warranty

SOLAR INVERTERS

- Lead-acid/ Lithium Battery
- Battery Reverse Protection
- IP65
- Smart Energy Management
- Zero Export Function (integrated)
- Natural Cooling, Low noise
- Charge/discharge Protection

V-TAC®
INNOVATIVE LED LIGHTING

SOLAR ENERGY

Single Phase On-Grid Solar Inverter

- Max. Current per MPPT: 16A Max
- Max. Input Power: 6.3kW Max
- Max. Input Voltage: 600V
- Min. Operating Voltage: 120V/100V
- Max. Output Current: 26A Max
- IP Rating: IP65
- Dimension: 360×462×150mm

Model	SKU	Watts	warranty
VT-6603105	11369	3KW	5 Years
VT-6605105	11370	5KW	5 Years

Three Phase On-Grid Solar Inverter

- Max. Current per MPPT: 12.5A Max
- Max. Input Power: 11kW Max
- Max. Input Voltage: 1000V Max
- Min. Operating Voltage: 220V/180V Max
- Max. Output Current: 16A Max
- IP Rating: IP65
- Dimension: 360×575×150mm

Model	SKU	Watts	warranty
VT-6605305	11371	5KW	5 Years
VT-6608305	11372	8KW	5 Years
VT-6610305	11373	10KW	5 Years

Single Phase On-Grid Solar Inverter

- Max. Current per MPPT: 16A Max
- Max. Input Power: 6.3kW Max
- Max. Input Voltage: 600V
- Min. Operating Voltage: 120V/100V
- Max. Output Current: 26A Max
- IP Rating: IP65
- Dimension: 360×462×150mm

Model	SKU	Watts	warranty
VT-6603110	11379	3KW	10 Years
VT-6605110	11380	5KW	10 Years

Single Phase On Grid/Off Grid Solar Inverter

- Max. PV Input Power: 7kW Max
- Max. PV Input Voltage: 550V
- Max. PV Input Current: 12A
- Max. Output Current: 26A Max
- Battery Type: Lithium/Lead-acid 40V-58V
- Charge/Discharge Current: 95 A/ 110A Max
- IP Rating: IP65
- Dimension: 550×515×200mm

Model	SKU	Watts	warranty
VT-66036103	11374	3.6KW	3 Years

SOLAR ENERGY

V-TAC®
INNOVATIVE LED LIGHTING

Three Phase On Grid/Off Grid Solar Inverter

- Max. Output Current: 19.1A Max
- Max. PV Input Power: 15.6kW Max
- Max. PV Input Voltage: 1000V
- Max. Current per MPPT: 12.5A
- Battery Type: Lithium/Lead-acid 125V-600V
- Charge/Discharge Current: 50A
- IP Rating: IP65
- Dimension: 530×560×200mm

Model	SKU	Watts	warranty
VT-6608303	11375	8KW	3 Years

On-Grid Solar Inverter

- Max. Input Power: 19.2kW Max
- Max. Input Voltage: 1100V
- Min. Operating Voltage: 160V
- Max. Current per MPPT: 13A
- Max. Output Current: 19.1A Max
- IP Rating: IP66
- Dimension: 430×380×150mm

Model	SKU	Watts	warranty
VT-6605310	11381	5KW	10 Years
VT-6608310	11382	8KW	10 Years
VT-6610310	11383	10KW	10 Years

Single Phase On Grid/Off Grid Solar Inverter

- Max. Output Current: 26A Max
- Max. PV Input Power: 7kW Max
- Max. PV Input Voltage: 550V
- Max. PV Input Current: 14A
- Battery Type: Lithium Iron Phosphate 2.4 - 14.4kWh
- Charge/Discharge Current: 95A/110A
- IP Rating: IP21
- Dimension: 580×1800×350mm

Model	SKU	Watts	warranty
VT-6605103	11376	5KW	3 Years

Battery for Solar Inverter

SKU
11377

Lithium-Ion Battery
4.8kWh(100Ah, 48V)

Wifi Dongle for Solar Inverter

Model	SKU
VT-660000	11378

Compatible with On-Grid

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
101	232	162	230	223	237	285	237	384	149	436	68	488	64	564	102
102	233	163	230	224	237	286	219	385	151	437	68	489	64	565	102
103	232	164	230	226	237	290	220	386	151	438	68	490	73	566	100
104	232	165	213	228	229	291	220	387	151	439	59	493	73	567	100
105	221	166	213	229	229	292	223	388	151	440	59	494	75	568	100
106	220	167	213	230	229	294	222	389	151	441	59	495	75	569	100
107	219	168	228	231	229	320	207	390	151	442	55	496	75	570	100
108	211	169	228	232	229	321	207	391	151	443	55	497	75	571	100
109	212	170	228	233	229	322	207	392	151	444	55	498	75	574	100
110	233	171	226	234	225	323	207	393	151	445	63	499	75	575	99
111	227	172	226	235	225	324	207	394	151	446	63	500	75	576	99
112	227	173	226	236	225	325	207	395	153	447	63	501	75	577	99
113	227	174	227	237	231	326	207	396	153	448	66	502	69	578	99
114	229	175	227	238	231	327	207	397	153	449	66	503	69	580	103
115	229	176	227	239	231	328	207	398	153	450	66	504	69	581	103
116	229	186	238	240	210	331	207	399	153	451	68	505	197	583	99
117	227	187	238	241	210	332	207	400	59	452	68	506	197	584	99
118	227	188	238	242	210	333	207	401	59	453	68	507	197	585	102
119	227	189	212	243	210	350	163	402	59	454	63	508	197	586	100
123	237	190	212	244	210	351	163	403	55	455	63	509	105	600	147
124	237	191	212	245	210	352	163	404	55	456	63	511	211	601	147
125	237	192	214	246	211	353	162	405	55	457	66	512	212	602	147
126	231	193	214	247	211	354	162	406	59	458	66	517	130	603	150
127	231	194	214	248	211	355	162	407	59	459	66	519	130	604	150
128	231	195	212	249	224	356	163	408	59	460	68	521	238	606	145
131	210	196	212	250	224	357	163	409	56	461	68	525	93	607	145
132	210	197	212	251	224	358	163	410	56	462	68	526	93	608	146
133	210	198	215	252	224	359	162	411	56	463	63	527	93	609	146
135	234	199	215	253	224	360	162	412	61	464	63	528	93	611	117
136	234	200	215	254	224	361	162	413	61	465	63	529	93	612	117
137	234	201	214	255	224	362	163	414	61	466	66	530	93	613	117
138	234	202	214	256	224	363	163	415	56	467	66	531	93	614	116
139	234	203	214	257	224	364	163	416	56	468	66	532	93	615	116
140	234	204	214	258	223	365	162	417	56	469	68	533	95	617	117
141	234	205	214	259	223	366	162	418	61	470	68	534	95	618	117
142	234	206	214	260	223	367	162	419	61	471	68	535	95	619	117
143	234	207	212	261	223	368	165	420	57	472	64	536	95	622	116
144	226	208	212	262	223	369	165	421	57	473	64	537	95	628	116
145	226	209	212	263	223	370	165	422	61	474	64	538	95	632	110
146	226	210	234	264	224	371	165	423	61	475	61	539	95	633	110
147	235	211	234	265	224	372	165	424	59	476	61	540	95	634	110
148	235	212	234	266	224	373	165	425	59	477	61	541	83	650	124
149	235	213	236	267	225	374	147	426	59	478	57	542	83	651	124
150	235	214	236	268	225	375	147	427	55	479	57	543	83	652	124
151	235	215	236	269	225	376	147	428	55	480	57	544	83	653	124
152	235	216	236	272	221	377	148	429	55	481	64	545	85	654	124
153	235	217	236	275	222	378	148	430	63	482	64	558	103	655	124
154	235	218	236	278	221	379	148	431	63	483	64	559	103	656	124
155	235	219	236	279	221	380	150	432	63	484	64	560	102	657	124
159	230	220	236	280	222	381	150	433	66	485	64	561	102	658	124
160	230	221	236	283	237	382	152	434	66	486	57	562	102	659	127
161	230	222	237	284	237	383	149	435	66	487	57	563	102	660	127

DEKRA TÜV SÜD TÜV Rheinland CERTIFIED GS RoHS COMPLIANT CE/EMC
www.tuv.com ID 1111227954
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
661	127	724	118	789	53	851	232	939	164	991	189	1311	447	1406	475
662	127	726	118	790	53	852	232	940	164	992	189	1314	473	1407	475
663	127	727	114	791	50	853	233	941	164	993	189	1315	473	1408	475
664	127	728	114	792	50	854	233	942	164	994	189	1316	473	1409	475
665	127	729	114	793	47	855	233	943	233	995	189	1317	473	1412	422
666	127	730	115	794	47	856	228	944	222	996	189	1318	473	1424	430
667	127	731	115	795	53	857	228	945	70	997	189	1319	473	1446	503
668	127	732	115	796	53	858	227	946	70	998	189	1320	474	1451	157
669	127	733	114	797	211	859	226	947	60	999	189	1321	474	1452	157
670	127	734	114	798	123	860	231	948	60	1100	429	1322	474	1453	429
671	127	735	114	799	123	861	231	949	60	1192	425	1323	474	1456	421
672	123	736	115	801	178	862	222	950	55	1207	472	1324	474	1457	421
673	123	737	115	802	178	863	229	951	60	1208	472	1325	474	1458	421
674	123	738	115	803	180	864	229	952	56	1209	472	1326	473	1459	421
675	123	739	114	804	180	865	229	953	87	1210	472	1327	473	1463	505
676	135	740	114	805	180	866	228	954	87	1232	425	1328	473	1464	505
677	135	741	114	806	179	867	228	955	87	1235	424	1329	473	1465	506
678	135	742	115	807	185	868	228	956	91	1238	424	1330	473	1466	506
679	135	743	115	808	185	869	211	957	91	1245	303	1331	473	1467	506
680	134	744	115	809	185	870	211	958	91	1255	424	1333	422	1468	506
681	134	748	113	812	181	871	211	959	91	1256	424	1334	422	1469	506
686	123	749	113	813	196	872	215	960	91	1257	424	1337	422	1470	506
687	123	753	131	814	196	873	215	961	91	1259	446	1338	422	1471	506
688	123	754	131	815	178	874	215	962	91	1261	446	1340	422	1472	506
689	132	757	129	816	179	875	213	963	91	1262	446	1349	446	1477	427
690	132	759	129	817	181	876	213	964	50	1263	445	1350	447	1478	427
691	132	760	49	818	180	877	213	965	50	1264	445	1351	446	1479	427
692	132	761	49	819	180	878	215	966	51	1265	445	1354	499	1480	427
693	132	762	47	820	182	879	215	967	51	1266	445	1355	499	1481	427
694	132	763	47	821	183	880	215	968	51	1267	445	1356	500	1482	427
695	132	764	53	822	183	881	195	969	51	1268	445	1360	155	1483	427
696	132	765	53	823	183	882	147	970	188	1269	447	1361	155	1484	427
697	132	766	49	824	197	883	89	971	188	1270	429	1362	155	1485	427
703	119	767	49	825	197	884	89	972	188	1271	429	1363	156	1486	428
704	119	768	47	826	197	885	89	973	189	1272	429	1364	156	1487	428
705	119	770	53	827	197	886	89	974	189	1273	429	1365	156	1488	428
706	118	771	53	829	197	887	89	975	189	1274	429	1366	157	1489	428
708	118	772	49	830	197	888	89	976	189	1275	429	1367	157	1497	243
709	119	773	49	831	197	889	89	977	189	1276	429	1368	157	1498	243
710	119	774	47	832	187	890	89	978	189	1277	429	1369	500	1685	301
711	119	775	47	835	204	891	107	979	189	1278	429	1382	157	1686	301
712	118	777	53	836	204	892	107	980	189	1279	429	1383	157	1687	301
713	118	778	50	838	205	893	107	981	189	1280	429	1384	157	2002	394
714	118	779	50	839	187	894	107	982	189	1284	471	1385	157	2005	394
715	119	780	200	840	187	895	107	983	189	1285	424	1398	474	2009	394
716	119	781	200	841	187	896	107	984	189	1286	424	1399	474	2011	394
717	119	782	85	842	187	897	212	985	188	1287	424	1400	474	2013	394
718	118	783	85	843	187	899	205	986	188	1294	423	1401	474	2015	394
719	118	784	199	844	187	935	182	987	188	1297	423	1402	474	2016	394
721	119	785	199	845	187	936	182	988	189	1300	423	1403	474	2025	394
722	119	787	47	846	187	937	183	989	189	1303	423	1404	475	2031	394
723	119	788	47	850	232	938	183	990	189	1308	447	1405	475	2032	394

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
2034	394	2462	390	2587	402	2645	403	2707	264	2772	253	2846	294	2907	390
2035	394	2463	390	2588	402	2646	384	2708	264	2773	253	2847	294	2908	390
2036	394	2512	399	2589	402	2647	384	2709	264	2774	253	2848	291	2909	406
2037	395	2513	399	2590	413	2648	384	2710	265	2775	253	2849	291	2910	244
2038	395	2514	399	2591	397	2649	393	2713	265	2776	253	2850	291	2911	410
2041	394	2515	399	2592	397	2650	393	2714	265	2777	253	2851	292	2912	410
2042	394	2516	400	2593	387	2651	393	2715	265	2778	300	2852	292	2913	410
2043	394	2517	400	2594	387	2652	392	2716	266	2779	300	2853	292	2914	410
2044	395	2518	400	2595	387	2653	392	2717	266	2780	300	2854	294	2915	410
2118	395	2527	403	2596	388	2654	392	2718	266	2781	239	2855	294	2916	410
2120	396	2529	400	2597	388	2655	404	2720	300	2782	239	2856	294	2917	410
2122	396	2531	401	2598	388	2656	404	2721	300	2783	239	2857	19	2918	411
2124	395	2535	401	2599	389	2657	404	2728	296	2784	239	2866	633	2919	411
2126	396	2537	401	2600	389	2658	404	2730	259	2785	239	2867	633	2920	411
2128	396	2538	401	2601	389	2659	404	2731	259	2786	239	2868	633	2921	411
2133	395	2540	401	2602	391	2660	404	2732	259	2790	271	2870	289	2922	411
2135	395	2541	401	2603	391	2661	404	2733	261	2791	241	2871	406	2923	411
2137	396	2544	385	2604	391	2662	404	2734	261	2792	303	2872	406	2924	411
2138	396	2545	385	2605	384	2663	404	2735	261	2793	303	2873	405	2925	254
2143	396	2546	385	2606	384	2664	404	2736	258	2794	303	2874	405	2926	253
2144	395	2547	396	2607	384	2665	404	2737	258	2796	301	2875	405	2927	301
2145	395	2548	383	2608	396	2666	404	2738	258	2797	301	2876	405	2928	254
2148	396	2549	383	2609	396	2667	392	2739	302	2799	303	2877	405	2929	253
2149	396	2550	383	2612	398	2668	392	2740	302	2800	303	2878	405	2930	301
2150	396	2551	383	2613	398	2669	392	2741	302	2801	303	2879	505	2931	387
2155	396	2552	397	2614	398	2671	415	2742	299	2802	288	2880	393	2932	387
2156	396	2553	397	2615	398	2672	415	2744	299	2803	295	2881	485	2933	387
2159	397	2554	412	2616	398	2682	415	2745	299	2806	218	2882	485	3018	412
2161	391	2556	412	2617	398	2683	415	2746	299	2807	218	2883	485	3035	419
2162	391	2557	412	2618	398	2684	415	2747	299	2808	218	2884	485	3070	417
2163	391	2558	386	2619	398	2685	415	2748	271	2809	218	2885	485	3101	418
2164	391	2559	386	2620	398	2686	416	2749	271	2810	218	2886	485	3111	324
2165	391	2560	386	2621	398	2687	416	2750	242	2811	218	2887	485	3112	325
2166	391	2561	386	2622	387	2688	416	2751	242	2812	218	2888	485	3113	325
2350	402	2562	398	2624	387	2689	416	2752	242	2813	218	2889	23	3114	325
2351	402	2563	398	2625	386	2690	416	2753	242	2814	218	2890	23	3115	326
2352	402	2564	398	2626	386	2691	416	2754	241	2815	287	2891	24	3116	326
2353	402	2565	403	2627	386	2692	416	2755	241	2816	219	2892	24	3117	328
2354	402	2566	403	2628	244	2693	416	2756	241	2817	219	2893	24	3118	328
2355	402	2568	401	2629	244	2694	416	2757	243	2818	264	2894	24	3119	328
2356	402	2569	401	2630	385	2695	416	2760	256	2819	264	2895	388	3120	328
2371	238	2570	401	2631	385	2696	390	2761	256	2820	264	2896	388	3121	328
2372	238	2571	403	2635	384	2697	390	2762	256	2834	266	2896	387	3122	328
2373	238	2573	383	2636	384	2698	390	2763	256	2835	266	2897	389	3123	329
2403	393	2574	383	2637	384	2699	244	2764	256	2836	266	2898	389	3124	329
2404	393	2580	392	2638	403	2700	269	2765	256	2837	213	2899	413	3125	329
2405	393	2581	392	2639	403	2701	286	2766	254	2838	213	2900	413	3126	329
2430	397	2582	392	2640	403	2702	286	2767	254	2839	213	2901	413	3127	329
2431	397	2583	243	2641	403	2703	286	2768	254	2842	292	2902	413	3128	329
2459	397	2584	243	2642	403	2704	269	2769	253	2843	292	2903	406	3129	325
2460	395	2585	243	2643	403	2705	269	2770	253	2844	292	2904	406	3130	325
2461	390	2586	243	2644	403	2706	269	2771	253	2845	294	2906	390	3134	324

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
3135	325	3249	419	3365	407	3585	319	3649	317	3716	538	3787	548	3860	536
3136	325	3250	418	3366	407	3586	319	3650	317	3717	538	3788	548	3865	531
3137	325	3251	418	3367	406	3587	323	3651	317	3720	547	3789	549	3867	531
3138	325	3252	418	3368	406	3588	323	3652	317	3722	547	3790	549	3874	582
3139	325	3253	415	3369	407	3589	323	3653	318	3723	547	3791	549	3876	531
3140	326	3255	415	3370	407	3590	323	3654	318	3724	547	3792	549	3878	531
3141	326	3256	417	3371	409	3591	324	3655	425	3725	547	3793	549	3879	530
3142	326	3257	417	3372	409	3592	324	3656	425	3726	533	3794	549	3880	530
3143	326	3258	417	3423	331	3593	319	3657	425	3727	533	3795	547	3881	530
3144	329	3259	416	3469	321	3594	319	3658	425	3728	534	3796	547	3882	530
3145	329	3261	415	3470	321	3595	322	3659	425	3729	534	3797	547	3884	532
3146	329	3262	415	3471	321	3596	323	3660	425	3730	532	3798	548	3885	532
3147	329	3263	416	3472	321	3597	323	3664	317	3732	533	3799	548	3887	531
3148	330	3264	419	3473	322	3598	323	3665	317	3735	532	3800	548	3888	531
3149	330	3265	418	3474	322	3599	320	3666	317	3736	532	3801	548	3892	555
3150	330	3269	419	3475	549	3600	320	3667	317	3737	533	3802	548	3893	554
3151	330	3271	418	3476	549	3605	320	3668	95	3738	532	3803	547	3894	552
3152	330	3272	419	3477	549	3606	320	3669	322	3742	548	3804	547	3895	553
3153	314	3273	415	3479	549	3607	321	3673	296	3743	548	3805	547	3898	555
3154	314	3274	417	3480	549	3608	321	3674	318	3744	548	3806	547	3899	555
3155	314	3275	417	3481	549	3609	321	3675	316	3745	548	3807	547	3900	553
3156	314	3300	409	3482	549	3610	321	3676	316	3746	548	3808	547	3901	553
3157	314	3303	409	3483	549	3611	321	3677	317	3749	548	3809	547	3904	582
3158	314	3307	409	3484	549	3612	321	3680	432	3750	548	3810	547	3905	582
3159	314	3309	412	3486	549	3613	322	3681	432	3751	543	3821	534	3906	583
3160	315	3312	412	3500	402	3614	322	3682	432	3752	543	3822	534	3910	583
3161	315	3322	412	3501	402	3615	322	3683	432	3753	544	3823	534	3911	583
3162	315	3326	412	3502	402	3616	322	3684	432	3754	545	3824	535	3912	488
3163	315	3327	412	3503	402	3617	330	3685	432	3755	548	3825	535	3913	488
3164	315	3331	403	3504	402	3618	330	3689	322	3756	541	3826	535	3914	488
3165	315	3333	403	3505	402	3619	330	3690	322	3757	541	3827	535	3916	554
3166	315	3334	403	3507	402	3620	331	3691	318	3761	541	3828	535	3917	554
3167	315	3337	412	3508	402	3621	341	3692	318	3762	541	3829	535	3918	554
3168	315	3338	412	3512	402	3622	341	3694	324	3763	541	3831	539	3919	554
3169	316	3339	412	3522	425	3623	341	3695	324	3764	542	3832	539	3920	542
3170	316	3340	412	3523	425	3624	95	3696	324	3765	542	3833	539	3921	542
3228	417	3341	412	3524	425	3625	412	3697	324	3766	542	3834	539	3922	542
3231	418	3350	406	3525	425	3627	316	3698	296	3767	545	3835	540	3923	543
3232	418	3351	407	3526	425	3628	316	3700	540	3768	545	3836	540	3924	543
3233	418	3352	406	3527	425	3629	316	3701	540	3769	545	3837	540	3925	543
3234	418	3353	407	3528	425	3630	316	3702	541	3770	546	3838	540	3927	539
3235	418	3354	407	3529	425	3631	316	3705	537	3771	546	3839	545	3928	556
3236	418	3355	407	3559	425	3632	316	3706	538	3772	546	3841	547	3930	556
3237	419	3356	407	3560	425	3640	318	3707	537	3773	546	3842	547	3931	556
3238	419	3357	408	3565	425	3641	318	3708	537	3774	546	3843	547	3932	557
3239	419	3358	408	3566	425	3642	319	3709	536	3775	546	3844	547	3933	557
3240	419	3359	408	3575	305	3643	319	3710	536	3776	546	3845	545	3934	556
3243	415	3360	408	3576	305	3644	320	3711	536	3777	548	3851	538	3936	556
3244	415	3361	408	3578	340	3645	320	3712	537	3783	548	3852	539	3937	556
3246	415	3362	408	3581	305	3646	320	3713	536	3784	548	3853	538	3938	557
3247	415	3363	409	3582	305	3647	320	3714	537	3785	548	3857	538	3939	557
3248	418	3364	407	3584	319	3648	317	3715	537	3786	548	3859	536	3946	543

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
3947	544	4174	260	4458	264	4869	364	4938	362	5123	413	5947	337	6057	368
3948	544	4207	258	4459	255	4870	364	4939	362	5124	414	5948	337	6184	376
3950	544	4216	257	4460	255	4871	364	4940	362	5127	414	5949	335	6185	376
3952	544	4223	304	4461	255	4872	363	4941	362	5128	414	5950	335	6198	376
3953	544	4224	304	4466	299	4873	363	4942	362	5129	414	5951	335	6199	376
3958	563	4225	304	4467	299	4874	363	4943	362	5130	414	5952	337	6200	376
3959	563	4255	304	4468	299	4887	364	4944	362	5131	414	5953	337	6201	376
3960	564	4256	304	4472	273	4888	364	4945	362	5132	414	5954	337	6217	346
3961	567	4257	304	4473	278	4889	364	4946	362	5133	414	5955	335	6221	346
3962	564	4276	267	4479	282	4890	360	4947	362	5134	414	5956	335	6222	346
3963	564	4277	267	4482	284	4891	360	4948	362	5135	414	5957	335	6229	367
3964	565	4278	267	4483	285	4892	360	4949	362	5136	414	5958	337	6236	347
3965	567	4300	293	4484	285	4893	360	4966	447	5137	414	5959	337	6237	347
3966	560	4301	289	4485	285	4894	360	4967	498	5138	414	5960	337	6238	347
3967	561	4302	291	4486	283	4895	360	4968	499	5139	414	5961	335	6239	347
3968	561	4306	292	4487	283	4896	360	4973	447	5140	414	5962	335	6240	347
3969	561	4307	290	4488	283	4897	360	4982	499	5141	414	5963	335	6241	347
3970	562	4308	290	4498	273	4898	360	4997	446	5150	17	5964	337	6242	347
3971	562	4361	274	4499	282	4904	357	4998	446	5151	17	5965	337	6256	350
3972	562	4362	275	4737	361	4905	357	4999	446	5152	17	5966	337	6257	350
3973	563	4364	287	4738	361	4906	357	5031	362	5153	17	5967	336	6258	350
3974	569	4365	289	4739	361	4907	357	5032	362	5155	513	5968	336	6259	352
3975	570	4366	291	4740	361	4908	357	5033	362	5157	507	5969	336	6262	367
3976	570	4367	290	4741	361	4909	357	5050	446	5502	18	5977	340	6263	367
3977	570	4388	290	4742	361	4910	357	5052	446	5503	18	5978	340	6264	367
3978	568	4390	265	4743	361	4911	357	5056	445	5504	18	5979	340	6265	367
3979	568	4399	294	4744	361	4912	357	5068	370	5505	17	5980	340	6268	352
3980	569	4407	288	4745	361	4913	357	5070	370	5506	17	5981	340	6270	352
3981	569	4408	288	4746	361	4914	357	5071	371	5570	471	5982	340	6271	352
3986	579	4409	288	4759	361	4915	357	5072	371	5571	502	5983	340	6272	367
3987	579	4410	288	4760	361	4916	357	5073	371	5572	502	5984	338	6273	367
3988	580	4411	288	4797	362	4917	357	5074	371	5588	380	5985	338	6276	361
3989	580	4412	288	4798	362	4918	357	5076	371	5607	380	5986	340	6277	361
3990	581	4413	289	4802	356	4919	357	5077	498	5608	380	5987	340	6278	361
3991	581	4414	289	4808	356	4920	357	5078	502	5609	381	5988	336	6279	361
3992	557	4418	266	4826	356	4921	357	5081	502	5745	339	5989	336	6280	361
3993	558	4419	266	4833	356	4922	360	5082	503	5896	341	5990	336	6281	361
3994	558	4420	266	4854	363	4923	360	5083	503	5897	341	5991	336	6282	374
3995	558	4421	276	4855	363	4924	360	5084	501	5917	339	5992	336	6283	374
3996	559	4425	293	4856	363	4925	360	5085	501	5918	35	5993	336	6284	374
3997	559	4426	293	4857	363	4926	360	5086	497	5919	35	5995	338	6285	374
4061	304	4428	292	4858	363	4927	360	5087	497	5920	35	5996	338	6286	374
4062	304	4429	291	4859	363	4928	360	5088	497	5921	35	6018	352	6287	374
4084	304	4432	290	4860	363	4929	360	5089	497	5922	35	6019	352	6292	363
4122	257	4444	289	4861	363	4930	360	5090	498	5923	35	6024	348	6293	363
4123	260	4448	254	4862	363	4931	362	5091	498	5940	336	6025	348	6294	363
4124	260	4449	254	4863	364	4932	362	5116	413	5941	336	6028	348	6295	364
4156	256	4453	263	4864	364	4933	362	5117	413	5942	336	6052	368	6296	364
4160	258	4454	263	4865	364	4934	362	5118	413	5943	335	6053	368	6297	364
4162	258	4455	263	4866	364	4935	362	5119	413	5944	335	6054	368	6309	367
4164	256	4456	264	4867	364	4936	362	5120	413	5945	335	6055	368	6310	367
4166	257	4457	264	4868	364	4937	362	5121	413	5946	337	6056	368	6313	370

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
6314	370	6431	364	6602	112	6662	25	6734	333	7059	523	7154	285	7300	264
6318	368	6436	352	6603	344	6663	643	6735	334	7060	524	7155	279	7302	264
6319	368	6437	352	6604	344	6664	643	6736	334	7061	525	7156	277	7309	255
6320	368	6438	125	6605	343	6665	25	6737	333	7062	525	7157	273	7317	255
6321	368	6440	125	6606	495	6666	25	6738	333	7063	525	7164	267	7328	278
6322	369	6442	125	6607	495	6667	25	6739	333	7064	519	7166	267	7335	273
6324	369	6444	125	6608	495	6668	25	6740	334	7065	519	7173	267	7336	273
6325	369	6450	352	6609	495	6669	25	6741	334	7066	522	7177	283	7349	262
6328	352	6451	345	6610	496	6670	25	6742	334	7067	522	7178	283	7350	262
6332	351	6452	345	6611	496	6673	348	6743	333	7068	522	7179	283	7351	262
6333	351	6453	345	6612	496	6674	346	6744	333	7069	522	7180	283	7352	263
6340	358	6454	345	6613	496	6675	347	6745	333	7070	521	7181	284	7353	263
6346	358	6458	349	6614	352	6676	346	6746	334	7071	522	7183	284	7354	263
6347	358	6459	373	6622	138	6677	601	6747	334	7072	523	7184	285	7355	260
6348	358	6460	373	6623	353	6678	601	6748	334	7073	523	7186	285	7356	260
6352	358	6461	373	6624	349	6679	601	6749	333	7074	524	7187	285	7357	261
6353	358	6462	373	6625	349	6680	601	6750	333	7075	524	7188	285	7358	261
6354	358	6463	373	6626	349	6682	311	6751	333	7076	520	7189	286	7359	261
6355	358	6464	373	6627	353	6683	311	6752	334	7077	520	7190	286	7360	259
6356	358	6465	373	6628	482	6684	307	6753	334	7078	458	7191	286	7362	259
6357	358	6466	373	6629	482	6685	307	6754	334	7079	458	7194	267	7363	259
6358	359	6467	375	6630	482	6686	307	6755	16	7080	458	7195	267	7364	259
6364	359	6468	375	6632	308	6687	307	6756	16	7081	459	7216	278	7365	292
6366	359	6469	375	6633	308	6688	308	6757	16	7082	459	7217	276	7366	294
6367	359	6470	375	6634	309	6689	308	6758	16	7083	459	7218	275	7402	261
6369	359	6471	347	6635	309	6690	308	6759	16	7086	463	7220	275	7403	261
6376	347	6472	375	6636	308	6691	308	6760	16	7087	458	7229	263	7407	259
6384	350	6473	375	6637	308	6692	308	6761	306	7088	458	7234	304	7408	259
6386	352	6474	122	6638	309	6693	308	6762	306	7089	458	7235	304	7409	259
6387	373	6475	122	6639	309	6694	311	6763	306	7090	459	7236	304	7410	292
6388	373	6476	122	6640	309	6695	311	6764	306	7091	459	7240	262	7411	293
6392	367	6477	122	6641	309	6696	311	6765	306	7092	459	7241	262	7412	293
6393	367	6478	122	6642	309	6697	311	6766	306	7093	463	7242	262	7413	293
6394	367	6479	122	6643	309	6709	377	6767	306	7098	486	7246	262	7415	278
6399	373	6481	122	6644	309	6711	377	6768	306	7099	486	7251	286	7416	275
6400	373	6482	122	6645	309	6713	377	6769	307	7112	283	7252	279	7420	274
6401	355	6483	133	6646	310	6715	377	6770	307	7113	281	7260	262	7422	261
6403	355	6484	133	6647	310	6717	377	6771	307	7114	281	7261	262	7423	291
6404	355	6485	133	6648	310	6719	377	6772	307	7115	281	7262	262	7424	291
6406	355	6486	133	6649	310	6721	333	6773	307	7116	281	7263	258	7425	291
6407	355	6487	126	6650	310	6722	333	6774	307	7119	287	7264	258	7427	295
6409	355	6488	126	6651	310	6723	333	6775	306	7120	287	7265	258	7431	300
6412	355	6489	126	6652	310	6724	334	6776	306	7121	254	7269	302	7432	300
6415	355	6490	126	6653	310	6725	334	6777	346	7142	280	7270	302	7435	296
6418	355	6491	126	6654	310	6726	334	6778	346	7143	280	7271	302	7436	296
6422	363	6492	126	6655	310	6727	333	7044	511	7144	280	7285	256	7437	296
6423	363	6493	126	6656	311	6728	333	7045	511	7145	277	7288	255	7438	296
6424	363	6494	126	6657	311	6729	333	7046	521	7146	276	7289	255	7439	296
6427	352	6495	126	6658	311	6730	334	7047	521	7147	277	7290	255	7440	296
6428	363	6500	19	6659	311	6731	334	7055	489	7148	276	7291	257	7453	295
6429	363	6600	112	6660	25	6732	334	7057	524	7150	254	7293	257	7454	295
6430	364	6601	112	6661	25	6733	333	7058	523	7151	254	7297	263	7455	295

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
7456	279	7513	519	7569	509	7652	484	7928	245	8156	353	8239	461	8293	458
7457	274	7514	519	7570	510	7653	484	7929	637	8157	353	8240	461	8294	458
7458	288	7515	511	7602	439	7654	484	7933	247	8158	353	8241	461	8295	457
7459	288	7516	511	7603	440	7655	379	7934	637	8173	192	8242	461	8296	457
7460	288	7517	511	7604	439	7656	379	7935	637	8174	192	8243	461	8297	457
7461	271	7518	514	7605	440	7657	379	7936	641	8175	192	8244	461	8298	457
7462	272	7519	520	7606	439	7659	437	7950	171	8176	192	8245	462	8299	457
7463	272	7520	520	7607	440	7660	437	7951	171	8177	192	8246	462	8300	457
7464	272	7521	520	7608	439	7661	437	7952	171	8178	192	8247	462	8301	460
7465	272	7522	521	7609	440	7662	437	7953	171	8179	192	8250	469	8302	460
7466	272	7523	22	7610	430	7663	437	7954	170	8180	192	8251	469	8303	460
7467	272	7524	461	7611	430	7664	437	7955	170	8181	192	8252	469	8304	460
7468	272	7525	461	7612	430	7665	437	7956	170	8182	193	8253	469	8305	460
7472	280	7526	461	7613	19	7666	437	7957	170	8183	193	8254	470	8306	460
7473	279	7527	461	7614	431	7667	437	7958	167	8184	193	8255	470	8307	465
7474	274	7529	523	7615	435	7668	437	7959	167	8197	193	8256	470	8308	465
7475	277	7530	524	7616	435	7669	438	7960	167	8198	193	8257	470	8309	465
7477	299	7531	521	7617	435	7670	438	7961	167	8199	193	8258	470	8310	465
7479	252	7532	521	7618	435	7671	438	7962	168	8202	466	8259	470	8316	453
7480	252	7533	341	7619	435	7672	438	7963	168	8203	466	8260	470	8317	453
7481	252	7534	341	7620	435	7673	438	7964	168	8204	466	8261	470	8318	453
7482	252	7535	341	7621	435	7674	438	7965	168	8205	466	8262	468	8319	453
7483	252	7536	341	7622	435	7675	491	7966	169	8206	466	8263	468	8320	453
7484	252	7537	341	7623	435	7676	644	7967	169	8207	466	8264	468	8321	453
7485	252	7538	341	7624	435	7677	644	7968	169	8208	463	8265	468	8322	453
7486	252	7539	509	7625	435	7733	650	7969	169	8209	455	8266	468	8323	453
7487	252	7540	509	7626	435	7734	649	7970	171	8210	455	8267	468	8324	453
7488	251	7541	510	7627	435	7735	645	7971	171	8211	455	8268	468	8325	454
7489	251	7542	510	7628	435	7736	646	7972	171	8212	455	8269	468	8326	454
7490	251	7543	510	7629	435	7737	646	7973	171	8213	455	8270	469	8327	454
7491	251	7545	513	7630	435	7738	647	7974	171	8214	455	8271	469	8328	454
7492	251	7546	513	7631	435	7900	639	7975	171	8215	455	8272	469	8329	454
7493	251	7548	513	7632	435	7901	640	7977	171	8216	455	8273	469	8330	454
7494	252	7549	513	7633	436	7902	640	7978	171	8217	460	8274	493	8331	454
7495	252	7551	513	7634	436	7908	245	7979	171	8218	460	8275	353	8332	454
7496	252	7552	513	7635	436	7911	246	7980	330	8219	460	8276	21	8333	454
7497	301	7553	510	7636	436	7912	246	7981	330	8220	460	8277	21	8334	454
7498	301	7554	510	7637	436	7913	635	7982	331	8221	465	8278	22	8335	454
7499	301	7555	507	7638	436	7914	634	8073	365	8222	465	8279	22	8336	454
7500	508	7556	507	7639	436	7915	635	8074	365	8223	465	8280	456	8337	454
7501	508	7557	507	7640	436	7916	635	8075	365	8224	465	8281	456	8338	454
7502	508	7558	507	7641	436	7917	634	8076	365	8225	464	8282	456	8339	454
7503	508	7559	507	7642	436	7918	636	8080	244	8226	464	8283	456	8340	454
7504	508	7560	507	7643	436	7919	636	8081	345	8227	464	8284	456	8341	454
7505	508	7561	507	7644	436	7920	636	8082	345	8228	464	8285	456	8342	454
7506	508	7562	507	7645	436	7921	634	8083	348	8232	463	8286	457	8343	139
7507	508	7563	518	7646	436	7922	638	8084	348	8233	462	8287	457	8344	464
7508	509	7564	518	7647	436	7923	638	8085	348	8234	462	8288	457	8345	464
7509	509	7565	518	7648	436	7924	638	8086	344	8235	462	8289	457	8346	464
7510	509	7566	518	7649	436	7925	638	8087	344	8236	462	8290	457	8347	464
7511	509	7567	518	7650	436	7926	639	8088	344	8237	462	8291	457	8348	472
7512	509	7568	518	7651	484	7927	245	8119	377	8238	462	8292	458	8349	472

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
8350	472	8528	459	8585	327	8665	491	8725	622	8777	604	8840	297	8966	517
8351	472	8529	459	8586	327	8670	483	8726	622	8778	611	8841	610	8967	516
8352	472	8530	459	8587	327	8671	483	8727	622	8779	611	8874	193	8968	517
8353	472	8531	459	8588	328	8672	482	8728	622	8780	611	8875	193	8970	528
8355	596	8532	459	8589	327	8674	21	8729	618	8781	610	8876	193	8971	527
8359	596	8533	466	8590	328	8675	467	8730	618	8782	611	8877	313	8972	528
8369	599	8534	466	8591	328	8676	467	8731	619	8783	608	8878	313	8973	528
8372	599	8535	467	8592	328	8677	467	8732	619	8784	608	8879	314	8974	527
8379	599	8536	467	8593	515	8678	467	8733	615	8785	608	8880	314	8975	527
8395	599	8537	451	8594	515	8679	85	8734	616	8786	608	8881	302	8976	517
8397	599	8538	451	8595	314	8680	647	8735	616	8787	608	8882	302	8977	517
8399	599	8539	451	8596	315	8681	453	8736	616	8788	609	8883	302	8978	515
8400	595	8540	451	8597	313	8682	453	8737	616	8789	609	8884	302	8979	517
8401	599	8541	452	8598	313	8683	449	8738	616	8790	609	8885	302	8980	648
8402	599	8542	452	8599	313	8684	449	8739	616	8791	601	8886	302	8981	648
8415	248	8543	452	8600	481	8686	522	8740	617	8792	602	8887	194	8982	649
8416	248	8544	452	8601	481	8687	524	8741	617	8793	602	8888	194	8983	516
8421	248	8547	20	8602	480	8688	525	8742	617	8794	602	8889	194	8984	516
8427	248	8548	18	8603	480	8689	578	8743	619	8795	602	8890	194	8985	516
8428	248	8549	18	8604	480	8690	312	8744	619	8796	603	8891	194	8986	591
8437	492	8550	21	8605	480	8691	312	8745	617	8797	248	8912	194	8987	591
8438	595	8551	456	8608	313	8692	312	8746	619	8798	248	8913	194	8988	592
8440	594	8552	456	8609	451	8693	312	8747	620	8799	603	8914	194	8989	592
8446	248	8553	456	8610	451	8694	312	8748	615	8800	603	8915	194	8990	645
8458	598	8554	456	8611	452	8695	312	8749	615	8801	609	8916	432	8992	247
8459	598	8557	578	8612	452	8696	312	8750	297	8802	609	8917	432	8993	326
8460	598	8558	578	8613	449	8697	312	8751	297	8803	610	8918	432	8994	326
8461	598	8559	296	8614	449	8700	617	8752	297	8804	609	8931	483	8995	326
8462	598	8560	450	8615	449	8701	617	8753	297	8805	610	8936	320	8996	327
8463	598	8561	450	8616	449	8702	618	8754	604	8806	610	8937	320	8997	327
8466	249	8562	450	8617	450	8703	618	8755	605	8807	607	8938	318	8998	327
8467	249	8563	450	8618	450	8704	602	8756	605	8808	607	8939	318	8999	327
8468	249	8564	488	8619	450	8705	602	8757	605	8809	610	8940	318	9104	341
8469	249	8565	488	8620	450	8706	613	8758	605	8810	612	8941	319	9546	341
8475	593	8566	511	8621	505	8707	614	8759	605	8811	612	8942	319	9944	425
8478	593	8567	511	8622	505	8708	614	8760	605	8812	611	8943	319	9945	425
8479	594	8568	511	8623	514	8709	614	8761	606	8813	612	8944	312	9952	425
8500	486	8569	487	8624	514	8710	614	8762	606	8814	612	8945	312	9953	425
8504	487	8570	487	8625	514	8711	614	8763	606	8815	613	8946	313	9954	425
8505	487	8571	487	8626	510	8712	614	8764	606	8816	612	8947	313	9955	425
8506	487	8573	20	8627	510	8713	615	8765	606	8817	607	8948	313	9956	409
8517	519	8574	20	8628	520	8714	615	8766	606	8818	608	8949	313	9969	353
8518	519	8575	20	8629	523	8715	615	8767	607	8819	612	8955	323	9986	409
8519	486	8576	20	8649	246	8716	619	8768	607	8820	613	8956	326	9989	353
8520	483	8577	20	8650	246	8717	620	8769	607	8821	613	8958	514	9997	352
8521	477	8578	20	8651	245	8718	620	8770	603	8822	613	8959	515	9999	352
8522	477	8579	323	8659	631	8719	621	8771	603	8830	620	8960	516	11077	587
8523	478	8580	323	8660	631	8720	621	8772	603	8831	620	8961	515	11078	588
8524	478	8581	324	8661	629	8721	621	8773	604	8832	620	8962	514	11079	586
8525	479	8582	324	8662	629	8722	621	8774	604	8833	618	8963	515	11088	589
8526	479	8583	327	8663	629	8723	621	8775	604	8834	618	8964	516	11109	585
8527	459	8584	327	8664	629	8724	621	8776	604	8839	297	8965	517	11144	171

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
11145	171	11283	433	20000	160	20073	128	20204	140	20288	43	20363	126	20471	136
11159	624	11284	433	20001	160	20074	128	20205	140	20289	43	20364	126	21101	232
11160	624	11285	433	20003	161	20075	128	20206	141	20290	43	20365	126	21102	233
11161	624	11286	433	20004	161	20088	174	20207	141	20291	43	20366	126	21103	232
11162	624	11341	404	20006	160	20089	176	20208	140	20292	45	20367	126	21104	232
11163	624	11342	404	20007	160	20090	175	20209	140	20293	45	20402	31	21108	211
11164	624	11343	404	20009	161	20091	177	20210	141	20294	45	20403	31	21110	233
11165	624	11353	12	20010	161	20092	174	20211	141	20295	45	20404	31	21115	229
11166	624	11354	13	20012	60	20093	174	20212	138	20296	45	20405	31	21131	210
11167	624	11361	379	20013	60	20094	176	20213	138	20297	45	20406	31	21132	210
11168	624	11362	491	20014	60	20095	175	20214	139	20298	45	20407	31	21135	234
11169	624	11369	652	20016	184	20096	177	20215	139	20299	45	20408	31	21140	234
11170	624	11370	652	20017	197	20097	174	20216	139	20300	45	20409	31	21141	234
11171	624	11371	652	20019	197	20113	198	20217	139	20301	45	20410	31	21146	226
11172	624	11372	652	20020	197	20114	198	20218	138	20302	45	20411	31	21149	235
11173	624	11373	652	20021	225	20115	198	20219	138	20303	45	20419	111	21151	235
11174	624	11374	652	20022	225	20116	198	20220	137	20304	37	20420	111	21189	212
11175	624	11375	653	20023	225	20117	198	20221	137	20305	37	20421	111	21195	212
11176	624	11376	653	20024	99	20118	198	20222	137	20306	37	20422	81	21196	212
11177	624	11377	653	20025	99	20119	110	20223	137	20307	37	20423	81	21197	212
11178	624	11378	653	20026	215	20121	71	20256	39	20308	37	20424	81	21198	215
11179	630	11379	652	20027	215	20122	71	20257	39	20309	37	20425	81	21199	215
11179-BS	630	11380	652	20028	215	20123	105	20258	39	20310	37	20426	81	21201	214
11180	630	11381	653	20037	69	20124	72	20259	39	20311	37	20427	81	21202	214
11180-BS	630	11382	653	20038	69	20125	72	20260	39	20312	37	20428	81	21203	214
11181	630	11383	653	20039	69	20152	232	20261	39	20313	37	20429	81	21206	214
11181-BS	630	13889	186	20044	230	20169	33	20262	39	20314	37	20430	79	21207	212
11182	630	13899	186	20045	226	20170	33	20263	39	20315	37	20431	79	21222	237
11182-BS	630	13909	186	20047	110	20171	33	20264	39	20316	201	20432	79	21223	237
11188	624	13919	186	20048	110	20172	33	20265	39	20317	201	20433	79	21224	237
11189	624	13929	186	20049	191	20173	33	20266	39	20318	201	20434	79	21234	225
11190	624	13939	186	20050	191	20174	33	20267	39	20319	105	20435	79	21235	225
11191	624	13949	186	20051	190	20175	33	20268	41	20320	105	20436	79	21236	225
11203	627	13959	186	20052	190	20176	33	20269	41	20321	105	20437	79	21237	231
11208	626	13969	186	20053	190	20177	33	20270	41	20322	105	20438	81	21238	234
11209	626	13979	186	20054	190	20178	33	20271	41	20323	105	20439	81	21238	231
11215	630	14551	443	20055	190	20179	33	20272	41	20324	105	20449	29	21239	234
11216	630	14601	443	20056	190	20180	33	20273	41	20341	15	20450	29	21239	231
11217	630	14611	443	20057	190	20181	33	20274	41	20344	127	20451	29	21240	210
11218	630	14621	444	20058	190	20182	33	20275	41	20345	127	20452	29	21243	210
11220	627	14741	443	20059	190	20183	33	20276	41	20347	127	20453	29	21244	210
11224	626	14751	442	20060	144	20184	230	20277	41	20348	127	20454	29	21245	210
11225	175	14761	442	20063	103	20185	230	20278	41	20349	127	20455	29	21246	211
11230	175	14911	442	20064	103	20186	226	20279	41	20350	127	20456	29	21247	211
11231	175	14921	441	20065	70	20187	226	20280	43	20351	127	20457	29	21248	211
11241	178	14931	441	20066	128	20188	230	20281	43	20352	127	20458	29	21269	225
11277	433	14941	442	20067	128	20189	230	20282	43	20354	127	20462	154	21321	207
11278	433	14951	441	20068	128	20190	230	20283	43	20355	127	20463	154	21324	207
11279	433	15001	500	20069	128	20200	140	20284	43	20359	126	20464	154	21374	147
11280	433	15011	500	20070	128	20201	140	20285	43	20360	126	20468	136	21375	147
11281	433	15021	501	20071	128	20202	141	20286	43	20361	126	20469	136	21376	147
11282	433	15031	501	20072	128	20203	141	20287	43	20362	126	20470	136	21380	150

DEKRA TÜV SÜD www.tuv.com ID 1111227954 RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
21381	150	21679	135	21870	211	40191	575	60256	348	211317	473	212150	396	212706	269
21383	149	21686	123	21871	211	40201	575	60266	351	211319	473	212155	396	212728	296
21384	149	21687	123	21872	215	40211	575	60276	351	211322	474	212156	396	212730	259
21403	55	21688	123	21873	215	40221	576	60286	348	211323	474	212159	397	212733	261
21404	55	21689	132	21874	215	40231	576	60303	353	211326	473	212161	391	212734	261
21406	59	21690	132	21875	213	40241	576	60696	351	211328	473	212163	391	212738	258
21407	59	21691	132	21876	213	40251	577	62186	346	211329	473	212164	391	212739	302
21408	59	21692	132	21877	213	40261	577	62196	346	211330	473	212166	391	212740	302
21409	56	21695	132	21878	215	40271	577	62206	346	211331	473	212430	397	212741	302
21410	56	21696	132	21879	215	40311	481	62366	347	211402	474	212431	397	212766	254
21411	56	21697	132	21880	215	40321	481	62376	347	211403	474	212459	397	212775	253
21412	61	21748	113	21882	147	40331	571	62406	347	211463	505	212461	390	212778	300
21413	61	21749	113	21891	107	40381	571	62416	347	211464	505	212462	390	212790	271
21414	61	21760	49	21892	107	40391	572	62426	347	211465	506	212463	390	212792	303
21415	56	21761	49	21893	107	40401	572	63776	347	211466	506	212546	385	212793	303
21416	56	21762	47	21895	107	40411	572	64511	345	211467	506	212547	396	212794	303
21417	56	21764	53	21896	107	40421	573	64521	345	211469	506	212549	383	212802	288
21419	61	21765	53	21947	60	40431	571	66051	343	211470	506	212552	397	212803	295
21422	61	21766	49	21948	60	40441	551	71031	282	211472	506	212553	397	212815	287
21427	55	21767	49	21949	60	40451	551	71811	284	211485	427	212558	386	212850	291
21442	55	21768	47	21951	60	40461	551	76011	444	211487	428	212559	386	213894	552
21442	295	21770	53	21956	91	40471	551	80831	348	211685	301	212560	386	213895	553
21464	63	21771	53	21957	91	40481	552	80841	348	211686	301	212561	386	213900	553
21473	64	21772	49	21958	91	40491	552	80851	348	211687	301	212562	398	213901	553
21511	211	21773	49	21959	91	40501	529	80981	493	212002	394	212563	398	213982	553
21525	93	21778	50	21960	91	40511	529	83111	492	212005	394	212564	398	213983	553
21527	93	21779	50	21961	91	40521	529	93573	507	212011	394	212574	383	213984	553
21528	93	21784	199	21962	91	40531	529	93574	507	212013	394	212581	392	213985	552
21529	93	21785	199	21963	91	40541	530	93575	23	212015	394	212591	397	214062	304
21530	93	21787	47	21969	51	40551	530	93578	23	212016	394	212592	397	214084	304
21531	93	21789	53	34235	331	40561	529	94006	20	212025	394	212593	387	214122	257
21535	95	21790	53	35771	305	40571	529	94008	20	212032	394	212594	387	214123	260
21536	95	21791	50	35831	305	42151	257	94010	20	212035	394	212595	387	214124	260
21537	95	21792	50	36205	331	42411	257	94012	20	212036	394	212596	388	214160	258
21538	95	21793	47	40011	567	42501	260	94026	20	212037	395	212597	388	214162	258
21539	95	21796	53	40021	566	42511	260	94027	20	212038	395	212598	388	214166	257
21540	95	21797	211	40031	566	42521	260	211207	472	212041	394	212599	389	214174	260
21600	147	21798	123	40041	559	42581	257	211208	472	212042	394	212600	389	214207	258
21602	147	21799	123	40051	560	43421	257	211209	472	212043	394	212601	389	214216	257
21650	124	21808	185	40061	560	43431	257	211210	472	212044	395	212622	387	214224	304
21651	124	21809	185	40071	565	43441	257	211256	424	212118	395	212623	387	214225	304
21652	124	21820	182	40081	565	44801	284	211257	424	212120	396	212624	387	214255	304
21654	124	21850	232	40091	566	45641	270	211276	429	212122	396	212625	386	214256	304
21657	124	21851	232	40101	568	45651	270	211277	429	212124	395	212626	386	214257	304
21658	124	21853	233	40111	533	45661	270	211278	429	212126	396	212627	386	214272	287
21672	123	21854	233	40121	533	45671	270	211279	429	212128	396	212649	393	214300	293
21673	123	21855	233	40131	534	45691	266	211280	429	212133	395	212650	393	214301	289
21674	123	21860	231	40141	573	55669	186	211284	471	212137	396	212651	393	214302	291
21675	123	21861	231	40151	573	55679	186	211286	424	212138	396	212654	392	214303	287
21676	135	21867	228	40161	574	55811	103	211314	473	212143	396	212667	392	214304	294
21677	135	21868	228	40171	574	55911	103	211315	473	212148	396	212704	269	214305	295
21678	135	21869	211	40181	574	60246	348	211316	473	212149	396	212705	269	214306	292

V-TAC®
INNOVATIVE LED LIGHTING

SAMSUNG LED
Illuminated

SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.	SKU	P-No.
214308	290	215955	335	217078	458	217357	261	217608	439	218291	457	218617	450	2120207	141
214361	274	215956	335	217079	458	217359	261	217609	440	218292	458	218618	450	2120210	141
214362	275	215957	335	217080	458	217362	259	218202	466	218295	457	218619	450	2120211	141
214367	290	215958	337	217081	459	217363	259	218204	466	218296	457	218620	450	2120214	139
214410	288	215959	337	217082	459	217402	261	218211	455	218297	457	218621	505	2120215	139
214411	288	215960	337	217087	458	217403	261	218215	455	218298	457	218622	505	2120216	139
214412	288	215961	335	217088	458	217407	259	218232	463	218299	457	218675	467	2120217	139
214413	289	215962	335	217089	458	217408	259	218233	462	218300	457	218676	467	2120220	137
214414	289	215963	335	217090	459	217409	259	218234	462	218301	460	218677	467	2120221	137
214421	276	215964	337	217091	459	217410	292	218235	462	218302	460	218678	467	2120222	137
214422	295	215965	337	217093	463	217411	293	218236	462	218305	460	218681	453	2120223	137
214424	295	215966	337	217100	282	217412	293	218237	462	218306	460	218682	453	2140451	551
214428	292	215967	336	217113	281	217413	293	218238	462	218309	465	218683	449	2140471	551
214429	291	215968	336	217114	281	217415	278	218239	461	218334	454	218684	449	2140491	552
214430	291	215969	336	217115	281	217416	275	218240	461	218335	454	500081	589	2142151	257
214431	290	216025	348	217116	281	217422	261	218241	461	218337	454	500082	589	2142411	257
214432	290	216198	376	217121	254	217423	291	218242	461	218338	454	2113889	186	2142501	260
214444	289	216237	347	217142	280	217424	291	218243	461	218341	454	2113899	186	2142511	260
214445	289	216256	350	217143	280	217425	291	218244	461	218527	459	2113909	186	2142521	260
214446	289	216257	350	217144	280	217429	300	218245	462	218528	459	2113949	186	2142581	257
214473	278	216258	350	217145	277	217431	300	218246	462	218529	459	2114551	443	2143421	257
214499	282	216262	367	217146	276	217436	296	218247	462	218530	459	2114601	443	2143431	257
214854	363	216272	367	217147	277	217439	296	218250	469	218531	459	2114611	443	2143441	257
214855	363	216284	374	217148	276	217440	296	218251	469	218532	459	2114741	443	2155669	186
214856	363	216285	374	217155	279	217453	295	218252	469	218533	466	2114751	442	2160246	348
214857	363	216286	374	217157	273	217454	295	218253	469	218534	466	2114761	442	2160256	348
214858	363	216287	374	217216	278	217455	295	218254	470	218535	467	2114911	442	2160286	348
214859	363	216292	363	217217	276	217456	279	218255	470	218536	467	2114921	441	2162176	346
214860	363	216293	363	217218	275	217457	274	218256	470	218537	451	2114931	441	2162406	347
214861	363	216294	363	217220	275	217458	288	218257	470	218538	451	2114941	442	2162416	347
214862	363	216295	364	217229	263	217459	288	218258	470	218539	451	2114951	441	2162426	347
214865	364	216296	364	217234	304	217460	288	218259	470	218540	451	2120014	60	2163300	110
214866	364	216309	367	217236	304	217462	272	218260	470	218543	452	2120021	225	2163411	110
214867	364	216310	367	217240	262	217465	272	218261	470	218544	452	2120022	225	2180841	348
214868	364	216332	351	217241	262	217472	280	218262	468	218553	456	2120023	225	21200471	110
214869	364	216333	351	217242	262	217473	279	218263	468	218554	456	2120026	215		
214870	364	216392	367	217246	262	217474	274	218264	468	218560	450	2120051	190		
214871	364	216393	367	217251	286	217475	277	218265	468	218561	450	2120052	190		
214872	363	216394	367	217260	262	217524	461	218266	468	218562	450	2120054	190		
214873	363	216423	363	217261	262	217527	461	218269	468	218563	450	2120055	190		
214874	363	216428	363	217262	262	217544	513	218270	469	218600	481	2120056	190		
214887	364	216429	363	217263	258	217545	513	218271	469	218601	481	2120058	190		
214889	364	216430	364	217264	258	217547	513	218272	469	218602	480	2120114	198		
215946	337	216431	364	217265	258	217548	513	218273	469	218603	480	2120122	71		
215947	337	216468	375	217269	302	217550	513	218280	456	218604	480	2120124	72		
215948	337	216470	375	217270	302	217551	513	218282	456	218605	480	2120125	72		
215949	335	216473	375	217271	302	217602	439	218284	456	218609	451	2120152	232		
215950	335	216621	345	217328	278	217603	440	218285	456	218610	451	2120186	226		
215951	335	216671	348	217335	273	217604	439	218286	457	218612	452	2120187	226		
215952	337	216672	348	217336	273	217605	440	218287	457	218613	449	2120202	141		
215953	337	216706	343	217353	263	217606	439	218288	457	218614	449	2120203	141		
215954	337	216707	343	217354	263	217607	440	218289	457	218615	449	2120206	141		

DEKRA TÜV SÜD www.tuv.com ID 1111227954 GS RoHS CE/EMC
ACCREDITATION FROM TOP EUROPEAN LABS

Certificates

DIALux Partner

Certificate

This is to cerify that

V-TAC Europe Ltd.

is an official DIALux Partner.

2021

DIALux improves the lighting design process by making it accessible and easy to apply for everyone.

Lüdenscheid, 04.01.2021

Dieter Polle
Chief Executive Officer

Friedrich W. Bremecker
Business Unit Director Sales

DIALux is a registered trademark of DIAL GmbH.

www.dialux.com

DIALux Partner

CERTIFICATE

No. Z1A 18 10 93564 009

Holder of Certificate: V-TAC Europe Ltd.

Certification Mark:

Product: LED Lamps
LED Lamp

Tested according to:

TUV

Certificate of Conformity

RoHS

RoHS

Certificate of Conformity

CE-EMC

LED DOWN LIGHT

CE

CE / LVD

DEKRA

TÜV SÜD

TÜV Rheinland ZERTIFIZIERT

GS

www.tuv.com ID 1111227954

RoHS COMPLIANT

CE/EMC

ACCREDITATION FROM TOP EUROPEAN LABS

ONE BRAND, *ENDLESS SOLUTIONS.*

SAMSUNG LED Illuminated

5 YEAR WARRANTY*

SOLD IN OVER 70 COUNTRIES

Sofia Office

V-TAC EUROPE Ltd41, bul.Rozhen,
1271 Sofia, Bulgaria
www.v-tac.eu

UK Office

V-TAC House, Kelpatrick Road,
Slough, Berkshire, SL1 6BW, UK.
www.v-tac.co.uk

Middle East Office

Unit# 407/8/9 Jumeirah Bay Towers,
Plot# X3, JLT,P.O. Box 45244, Dubai.
www.vtacexports.comUK

CATALOG Q2- 2022

V-TAC® INNOVATIVE LED LIGHTING