

WEEE Number: 80133970

INSTRUCTION MANUAL

LED BACKLIT PANEL

O2 WARRANTY*



TECHNICAL DATA

MODEL	VT-60025		
SKU	23393, 23458	LIFE SPAN	20,000 Hours
SHAPE	SQUARE	ON/OFF CYCLE	>15,000
WATTS	25W	OPERATING TEMPERATURE	-10°C to +35°C
LUMENS	4500 Lm	INPUT VOLTAGE	AC: 220-240V, 50/60Hz
BEAM ANGLE	110°	IP RATING	IP20
CRI	≥80	BODY TYPE	PS+AL+SPCC
DF	≥0.9	DIMENSION	595x595x33mm

INTRODUCTION & WARRANTY

Thank you for selecting and buying V-TAC product. V-TAC will serve you the best. Please read these instructions carefully before starting the installation and keep this manual handy for future reference. If you have any another query, please contact our dealer or local vendor from whom you have purchased the product. They are trained and ready to serve you at the best. The warranty is valid for 2 years from the date of purchase. The warranty does not apply to damage caused by incorrect installation or abnormal wear and tear. The company gives no warranty against damage to any surface due to incorrect removal and installation of the product. The products are suitable for 10-12 Hours Daily operation. Usage of product for 24 Hours a day would void the warranty. This product is warranted for manufacturing defects only.



MULTI-LANGUAGE MANUAL QR CODE


Please scan the QR code to access the manual in multiple languages.



Points de collecte sur www.quefairedemesdechets.fr Privilégiez la réparation ou le don de votre appareil!

WARNING

- 1. Please make sure to turn off the power before starting the installation.
- 2. Installation must be performed by a qualified electrician.
- 3. The light source of this luminaire is not replaceable, when the light source reaches its end of life the whole luminaire should be replaced.
- 4. If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard.
- 5. For indoor use only.





This marking indicates that this product should not be disposed of with other household wastes.




Caution, Risk of electric shock



Luminaires not suitable for covering with thermally insulating material.

INSTALLATION INSTRUCTION



2. Fix the Panel into the Ceiling

AC220~240V Driver Panel light

3. Connect the cable into the terminal

4. Turn on the switch and test the Panel















