



CE LVD TEST REPORT

For
LED STEP LIGHT

Model No.: VT-1162, VT-1152, VT-1143, VT-1142, VT-8035, VT-1172, VT-1182, VT-1166, VT-1141, VT-1151, VT-1161, VT-1171

Applicant : V-TAC EXPORTS LIMITED
ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD
CENTRAL, CENTRAL, HONGKONG

Manufacturer : V-TAC EXPORTS LIMITED
ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD
CENTRAL, CENTRAL, HONGKONG

Issued By : Global-Standard Testing Service Co., Ltd.
Room 1911-1914, Noble Plaza, Qian Jin 1st Road,
Bao An district, Shenzhen, Guangdong, China.

Tel : +86 755 33863599

Email : market@gstslab.com

Report Number : D00.06.0445S-R2

Issued Date : April 19, 2019

Date of Report : April 19, 2019

Note:

1. The test data and result is based on the tested sample only.
2. Please verify information in the report on GST web: www.gstslab.com through report number.
3. All rights reserve, the pirate edition investigates necessarily! This report shall not be reproduced unless under the authority of Global-Standard Testing Service Co., Ltd

TEST REPORT
EN 60598-2-13
Luminaires
Part 2: Particular requirements
Section 13: Ground recessed luminaires

Report reference No.:	D00.06.0445S-R2
Testing laboratory	Global-Standard Testing Service Co., Ltd.
Location.....:	Room 1911-1914, Noble Plaza, Qian Jin 1st Road, Bao An district, Shenzhen, Guangdong, China
Applicant.....:	V-TAC EXPORTS LIMITED
Address:.....:	ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD CENTRAL, CENTRAL, HONGKONG
Manufacturer.....:	V-TAC EXPORTS LIMITED
Address:.....:	ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD CENTRAL, CENTRAL, HONGKONG
Standards.....:	EN 60598-2-13: 2006+A1:2012+A2:2016 EN 60598-1: 2015+A1:2018 EN 61347-1: 2015 EN 61347-2-13: 2014+A1:2017 EN 62031: 2008+A1:2013+A2:2015 EN 62471: 2008 EN 62493: 2015
Procedure deviation.....:	N/A
Non-standard test method.....:	N/A
Type of test equipment	LED STEP LIGHT
Trade mark.....:	
Model/Type designation.....:	VT-1162, VT-1152, VT-1143, VT-1142, VT-8035, VT-1172, VT-1182, VT-1166, VT-1141, VT-1151, VT-1161, VT-1171
Rating.....:	AC100-240V, 50/60Hz, Max.2W
TRF originator.....:	Global-Standard Testing Service Co., Ltd.
Copyright blank test report:	Global-Standard Testing Service Co., Ltd.
Test item particulars:	--
Operating Condition	Continuous
Tested for IT power systems	No
IT testing, phase-phase voltage (V)	N/A
Equipment mobility	N/A
Operating condition.....:	Continuous
Class of equipment	Class I
Protection against ingress of water	IP65


<p>General remarks:</p>	
<p>"(see remark #)" refers to a remark appended to the report.</p> <p>"(see appended table)" refers to a table appended to the report.</p> <p>Throughout this report a comma is used as the decimal separator.</p> <p>The test results presented in this report relate only to the object tested.</p> <p>This report shall not be reproduced except in full without the written approval of the testing laboratory.</p> <p>Unless otherwise specified, test are made under normal conditions at an ambient temperature within the range of 15°C to 35°C, RH45% to 75% and an air pressure of 860mbar of 1060mbar</p>	<p>Attachment with:</p> <ol style="list-style-type: none"> 1) Equipment list 2) Photo documentation
<p>Brief description of the test sample:</p> <ol style="list-style-type: none"> 1. This report covers the LED STEP LIGHT with models VT-1162, VT-1152, VT-1143, VT-1142, VT-8035, VT-1172, VT-1182, VT-1166, VT-1141, VT-1151, VT-1161, VT-1171. 2. Test data for VT-1152 represent all models in this test report, which is conditioned with Max. current, power consumption and the test result was pass. 3. The test result presented in this report relate only to the object tested. The samples tested comply with the requirements of this standard. 4. If no otherwise specified, all tests performed at the temperature below 25°C. 5. This report is based on report D00.06.0445S-R1 which issued on January 02, 2018. 	


Possible test case verdicts :


test case does not apply to the test object	N(/A)
test object does meet the requirement	P(ass)
test object does not meet the requirement	F(ail)

Name and address of the testing laboratory :

Global-Standard Testing Service Co., Ltd.
 Room 1911-1914, Noble Plaza, Qian Jin 1st Road, Bao An District, Shenzhen, Guangdong, China.


Tested by :  April 16, 2019
 Signature Date
Evan Chen / Test Engineer
 Name/title

Reviewed by :  April 19, 2019
 Signature Date
Gloria Wang / Project Engineer
 Name/title

Approved by :  April 19, 2019
 Signature Date
Nico Xie / Manager
 Name/title

Label

Representative



Note:

1. Due to similarity of the labels, only above label was listed;
2. All models have the same marking plate except the model name and input rating with wattage;
3. The height of WEEE directive mark is at least 7mm and others directive mark are at least 5mm height.

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict

13.2 (0)	GENERAL TEST REQUIREMENTS		—
13.2 (0.1)	Information for luminaire design considered..... :	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—
13.2 (0.3)	More sections applicable..... :	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—

13.4 (2)	CLASSIFICATION		—
13.4 (2.2)	Type of protection	Class I	—
13.4 (2.3)	Degree of protection..... :	IP65	—
13.4 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces..... :	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—
13.4 (2.5)	Luminaire for normal use	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—
	Luminaire for rough service	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—

13.5 (3)	MARKING		P
13.5 (3.2)	Mandatory markings	See label	P
	Position of the marking	Luminaires body	P
	Format of symbols/text	See label	P
13.5 (3.3)	Additional information		P
	Language of instructions	English	P
13.5 (3.3.1)	Combination luminaires		N
13.5 (3.3.2)	Nominal frequency in Hz	50/60Hz	P
13.5 (3.3.3)	Operating temperature		N
13.5 (3.3.4)	Symbol or warning notice		N
13.5 (3.3.5)	Wiring diagram		N
13.5 (3.3.6)	Special conditions		N
13.5 (3.3.7)	Metal halide lamp luminaire – warning		N
13.5 (3.3.8)	Limitation for semi-luminaires		N
13.5 (3.3.9)	Power factor and supply current		N
13.5 (3.3.10)	Suitability for use indoors		N
13.5 (3.3.11)	Luminaires with remote control		N
13.5 (3.3.12)	Clip-mounted luminaire – warning		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
13.5 (3.3.13)	Specifications of protective shields		N
13.5 (3.3.14)	Symbol for nature of supply	~	P
13.5 (3.3.15)	Rated current of socket outlet		N
13.5 (3.3.16)	Rough service luminaire		N
13.5 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments	Type Y	P
13.5 (3.3.18)	Non-ordinary luminaires with PVC cable		N
13.5 (3.3.19)	Protective conductor current in instruction if applicable		N
13.5 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		N
13.5 (3.3.21)	Non replaceable and non-user replaceable light sources information provided		P
	Cautionary symbol		P
13.5 (3.3.22)	Controllable luminaires, classification of insulation provided		N
13.5 (3.4)	Test with water		P
	Test with hexane		P
	Legible after test		P
	Label attached		P
13.5.1 (-)	Rated load in the manufacturer's instruction (N)..... :		P
13.5.2 (-)	Rated maximum surface temperature T (°C)..... :		P
13.5.3 (-)	Information concerning external connection box		N

13.6 (4)	CONSTRUCTION		P
13.6 (4.2)	Components replaceable without difficulty		N
13.6 (4.3)	Wireways smooth and free from sharp edges		P
13.6 (4.4)	Lampholders		N
13.6 (4.4.1)	Integral lampholder		N
13.6 (4.4.2)	Wiring connection		N
13.6 (4.4.3)	Lampholder for end-to-end mounting		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
13.6 (4.4.4)	Positioning		N
	- pressure test (N)		—
	After test the lampholder comply with relevant standard sheets and show no damage		N
	After test on single-capped lampholder the lampholder have not moved from its position and show no permanent deformation		N
	- bending test (N)		—
	After test the lampholder have not moved from its position and show no permanent deformation		N
13.6 (4.4.5)	Peak pulse voltage		N
13.6 (4.4.6)	Centre contact		N
13.6 (4.4.7)	Parts in rough service luminaires resistant to tracking		N
13.6 (4.4.8)	Lamp connectors		N
13.6 (4.4.9)	Caps and bases correctly used		N
13.6 (4.4.10)	Light source for lampholder or connection according IEC 60061 not connected another way		N
13.6 (4.5)	Starter holders		N
	Starter holder in luminaires other than class II		N
	Starter holder class II construction		N
13.6 (4.6)	Terminal blocks		N
	Tails		N
	Unsecured blocks		N
13.6 (4.7)	Terminals and supply connections		P
13.6 (4.7.1)	Contact to metal parts		N
13.6 (4.7.2)	Test 8 mm live conductor		N
	Test 8 mm earth conductor		N
13.6 (4.7.3)	Terminals for supply conductors		N
13.6 (4.7.3.1)	Welded method and material		N
	- stranded or solid conductor		N
	- spot welding		N
	- welding between wires		N
	- Type Z attachment		N
	- mechanical test according to 15.6.2		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	- electrical test according to 15.6.3		N
	- heat test according to 15.6.2.3 and 15.6.2.4		N
13.6 (4.7.4)	Terminals other than supply connection		P
13.6 (4.7.5)	Heat-resistant wiring/sleeves		N
13.6 (4.7.6)	Multi-pole plug		N
	- test at 30 N		N
13.6 (4.8)	Switches		N
	- adequate rating		N
	- adequate fixing		N
	- polarized supply		N
	- compliance with IEC 61058-1 for electronic switches		N
13.6 (4.9)	Insulating lining and sleeves		N
13.6 (4.9.1)	Retainment		N
	Method of fixing.....:		N
13.6 (4.9.2)	Insulated linings and sleeves:		N
	Resistant to a temperature > 20 °C to the wire temperature or		N
	a) & c) Insulation resistance and electric strength		N
	b) Ageing test. Temperature (°C).....:		N
13.6 (4.10)	Double or reinforced insulation		P
13.6 (4.10.1)	No contact, mounting surface – accessible metal parts – wiring of basic insulation		P
	Safe installation fixed luminaires		P
	Capacitors and switches		N
	Interference suppression capacitors according to IEC 60384-14		N
13.6 (4.10.2)	Assembly gaps:		N
	- not coincidental		N
	- no straight access with test probe		N
13.6 (4.10.3)	Retainment of insulation:		P
	- fixed		P
	- unable to be replaced; luminaire inoperative		P

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	- sleeves retained in position		N
	- lining in lampholder		N
13.6 (4.11)	Electrical connections and current-carrying parts		P
13.6 (4.11.1)	Contact pressure		N
13.6 (4.11.2)	Screws:		N
	- self-tapping screws		N
	- thread-cutting screws		N
13.6 (4.11.3)	Screw locking:		N
	- spring washer		N
	- rivets		N
13.6 (4.11.4)	Material of current-carrying parts		P
13.6 (4.11.5)	No contact to wood or mounting surface		P
13.6 (4.11.6)	Electro-mechanical contact systems		N
13.6 (4.12)	Screws and connections (mechanical) and glands		N
13.6 (4.12.1)	Screws not made of soft metal		N
	Screws of insulating material		N
	Torque test: torque (Nm); part..... :		N
	Torque test: torque (Nm); part..... :		N
	Torque test: torque (Nm); part..... :		N
13.6 (4.12.2)	Screws with diameter < 3 mm screwed into metal		N
13.6 (4.12.4)	Locked connections:		N
	- fixed arms; torque (Nm)..... :		N
	- lampholder; torque (Nm)..... :		N
	- push-button switches; torque 0,8 Nm..... :		N
13.6 (4.12.5)	Screwed glands; force (Nm)..... :		N
13.6 (4.13)	Mechanical strength		P

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
13.6 (4.13.1)	Impact tests:		P
	- fragile parts; energy (Nm)..... :	Diffuser	P
	- other parts; energy (Nm)..... :		N
	1) live parts		P
	2) linings		N
	3) protection		N
	4) covers		P
13.6 (4.13.3)	Straight test finger		P
13.6 (4.13.4)	Rough service luminaires		N
	- IP54 or higher		N
	a) fixed		N
	b) hand-held		N
	c) delivered with a stand		N
	d) for temporary installations and suitable for mounting on a stand		N
13.6 (4.13.6)	Tumbling barrel		N
13.6 (4.14)	Suspensions, fixings and means of adjusting		P
13.6 (4.14.1)	Mechanical load:		N
	A) four times the weight		N
	B) torque 2,5 Nm		N
	C) bracket arm; bending moment (Nm)..... :		N
	D) load track- mounted luminaires		N
	E) clip-mounted luminaires, glass-shelve. Thickness (mm)		N
	Metal rod. diameter (mm)		N
	Fixed luminaire or independent control gear without fixing devices		N
13.6 (4.14.2)	Load to flexible cables		P
	Mass (kg)		—
	Stress in conductors (N/mm ²)	0.75	P

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	Mass (kg) of semi-luminaire		N
	Bending moment (Nm) of semi-luminaire		N
13.6 (4.14.3)	Adjusting devices:		N
	- flexing test; number of cycles.....		N
	- strands broken.....		N
	- electric strength test afterwards		N
13.6 (4.14.4)	Telescopic tubes: cords not fixed to tube; no strain on conductors		N
13.6 (4.14.5)	Guide pulleys		N
13.6 (4.14.6)	Strain on socket-outlets		N
13.6 (4.15)	Flammable materials		P
	- glow-wire test 650°C.....	See Test Table 13.16 (13.3.2)	P
	- spacing ≥ 30 mm		N
	- screen withstanding test of 13.3.1		N
	- screen dimensions		N
	- no fiercely burning material		N
	- thermal protection		N
	- electronic circuits exempted		N
13.6 (4.15.2)	Luminaires made of thermoplastic material with lamp control gear		N
	a) construction		N
	b) temperature sensing control		N
	c) surface temperature		N
13.6 (4.16)	Luminaires for mounting on normally flammable surfaces		N
	No lamp control gear.....	(compliance with Section 12)	N
13.6 (4.16.1)	Lamp control gear spacing:		N
	- spacing 35 mm		N
	- spacing 10 mm		N
13.6 (4.16.2)	Thermal protection:		N
	- in lamp control gear		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	- external		N
	- fixed position		N
	- temperature marked lamp control gear		N
13.6 (4.16.3)	Design to satisfy the test of 12.6	(see clause 12.6)	N
13.6 (4.17)	Drain holes		N
	Clearance at least 5 mm		N
13.6 (4.18)	Resistance to corrosion		P
13.6 (4.18.1)	- rust-resistance		P
13.6 (4.18.2)	- season cracking in copper		N
13.6 (4.18.3)	- corrosion of aluminium		P
13.6 (4.19)	Igniters compatible with ballast		N
13.6 (4.20)	Rough service vibration		N
13.6 (4.21)	Protective shield		P
13.6 (4.21.1)	Shield fitted if tungsten halogen lamps or metal halide lamps		N
	Shield of glass if tungsten halogen lamps		N
13.6 (4.21.2)	Particles from a shattering lamp not impair safety		N
13.6 (4.21.3)	No direct path		N
13.6 (4.21.4)	Impact test on shield		P
	Glow-wire test on lamp compartment.....:	See Test Table 13.15 (13.3.2)	N
13.6 (4.22)	Attachments to lamps not cause overheating or damage		P
13.6 (4.23)	Semi-luminaires comply Class II		N
13.6 (4.24)	Photobiological hazards		P
13.6 (4.24.1)	No excessive UV radiation if tungsten halogen lamps and metal halide lamps (Annex P)		P
13.6 (4.24.2)	Retinal blue light hazard		P
	Luminaires with E_{thr} :		P
	a) Fixed luminaires		P

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	- distance x m, borderline between RG1 and RG2... :		P
	- marking and instruction according 3.2.23		P
	b) Portable and handheld luminaires		N
	- marking according 3.2.23 if RG1 exceeded at 200 mm according to IEC/TR 62778		N
	Portable luminaires for children IEC 60598-2-10 and Mains socket outlet nightlights IEC 60598-2-12 not exceed RG1 at 200 mm according to IEC/62778		N
13.6 (4.25)	Mechanical hazard		P
	No sharp point or edges		P
13.6 (4.26)	Short-circuit protection		P
13.6 (4.26.1)	Adequate means of uninsulated accessible SELV parts		P
13.6 (4.26.2)	Short-circuit test with test chain according 4.26.3		P
	Test chain not melt through		P
	Test sample not exceed values of Table 12.1 and 12.2		N
13.6 (4.27)	Terminal blocks with integrated screwless earthing contacts		N
	Test according Annex V		N
	Pull test of terminal fixing (20 N)		N
	After test, resistance < 0,05 Ω		N
	Pull test of mechanical connection (50 N)		N
	After test, resistance < 0,05 Ω		N
	Voltage drop test, resistance < 0,05 Ω		N
13.6 (4.28)	Fixing of thermal sensing control		N
	Not plug-in or easily replaceable type		N
	Reliably kept in position		N
	No adhesive fixing if UV radiations from a lamp can degrade the fixing		N
	Not outside the luminaire enclosure		N
	Test of adhesive fixing:		N
	Max. temperature on adhesive material (°C)..... :		—
	100 cycles between t min and t max		N
	Temperature sensing control still in position		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
13.6 (4.29)	Luminaires with non-replaceable light source		N
	Not possible to replace light source		N
	Live part not accessible after parts have been opened by hand or tools		N
13.6 (4.30)	Luminaires with non-user replaceable light source		P
	If protective cover provide protection against electric shock and marked with "caution, electric shock risk" symbol:		P
	Minimum two fixing means		N
13.6 (4.31)	Insulation between circuits		P
	Circuits insulated from LV supply fulfil requirements according 4.31.1 – 4.31.3		P
	Controllable luminaires requiring same level of insulation for all components, the insulation between control terminals and LV supply fulfil requirements according 4.31.1 – 4.31.3		P
13.6 (4.31.1)	SELV circuits		N
	Used SELV source		N
	Voltage \leq ELV		N
	Insulating of SELV circuits from LV supply		N
	Insulating of SELV circuits from other non SELV circuits		N
	Insulating of SELV circuits from FELV		N
	Insulating of SELV circuits from other SELV circuits		N
	SELV circuits insulated from accessible parts according Table X.1		N
	Plugs not able to enter socket-outlets of other voltage systems		N
	Socket outlets does not admit plugs of other voltage systems		N
	Plugs and socket-outlets does not have protective conductor contact		N
13.6 (4.31.2)	FELV circuits		N
	Used FELV source		N
	Voltage \leq ELV		N
	Insulating of FELV circuits from LV supply		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	FELV circuits insulated from accessible parts according Table X.1		N
	Plugs not able to enter socket-outlets of other voltage systems		N
	Socket outlets does not admit plugs of other voltage systems		N
	Socket-outlets does not have protective conductor contact		N
13.6 (4.31.3)	Other circuits		P
	Other circuits insulated from accessible parts according Table X.1		P
	Class II construction with equipotential bonding for protection against indirect contacts with live parts:		N
	- conductive parts are connected together		N
	- test according 7.2.3		P
	- conductive part not cause an electric shock in case of an insulation fault		P
	- equipotential bonding in master/slave applications		N
	- master luminaire provided with terminal for accessible conductive parts of slave luminaires		N
	- slave luminaire constructed as class I		P
13.6 (4.32)	Overvoltage protective devices		N
	Comply with IEC 61643-11		N
	External to controlgear and connected to earth:		N
	- only in fixed luminaires		N
	- only connected to protective earth		N
13.6.1 (-)	Resistance to static load		N
	Withstand the minimum static load		N
	Comply with 4.13.1 of Part 1 after test		N
13.6.2 (-)	Resistance to torque and shear loads		N
13.6.2.1 (-)	Torque test 50 N 1 min.		N
	Comply with 4.13.1 of Part 1 after test		N
13.6.2.2 (-)	Shear load test with pull force 5 kN		N
	Comply with 4.13.1 of Part 1 after test		N
13.6.3 (-)	Resistance to thermal shock		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	Resistance to thermal shock with iced water		N
13.6.4 (-)	Edges		P
	Accessible edges is rounded		P
	Surface of top assembly is smooth and free from burrs, flashes and the like		P
13.6.5 (-)	Mechanical strength		P
	Mechanical strength with impact energy of 5 Nm		P

13.7 (11)	CREEPAGE DISTANCES AND CLEARANCES		P
13.7 (11.2)	Creepage distances and clearances.....:	See Table 13.7 (11.2)	P
	Working voltage (V).....:	100-240VAC	—
	Rated pulse voltage (kV).....:	240VAC	—
	Voltage form.....:	Sinusoidal <input checked="" type="checkbox"/> Non-sinusoidal <input type="checkbox"/>	—
	PTI.....:	< 600 <input checked="" type="checkbox"/> ≥ 600 <input type="checkbox"/>	—
	Impulse withstand category (Normal category II) (Category III Annex U)	Category II <input checked="" type="checkbox"/> Category III <input type="checkbox"/>	—

13.8 (7)	PROVISION FOR EARTHING		P
13.8 (7.2.1 + 7.2.3)	Accessible metal parts		P
	Metal parts in contact with supporting surface		P
	Resistance < 0,5 Ω.....:		P
	Self-tapping screws used		N
	Thread-forming screws		N
	Thread-forming screw used in a groove		N
	Earth makes contact first		P
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N
	Protective earthing of the luminaire not via built-in control gear		N
13.8 (7.2.2 + 7.2.3)	Earth continuity in joints, etc.		P
13.8 (7.2.4)	Locking of clamping means		N
	Compliance with 4.7.3		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N
13.8 (7.2.5)	Earth terminal integral part of connector socket		P
13.8 (7.2.6)	Earth terminal adjacent to mains terminals		N
13.8 (7.2.7)	Electrolytic corrosion of the earth terminal		N
13.8 (7.2.8)	Material of earth terminal		N
	Contact surface bare metal		N
13.8 (7.2.10)	Class II luminaire for looping-in		N
	Double or reinforced insulation to functional earth		N
13.8 (7.2.11)	Earthing core coloured green-yellow		P
	Length of earth conductor		P
13.9 (14)	SCREW TERMINALS		N
	Separately approved; component list	(see Annex 1)	N
	Part of the luminaire	(see Annex 3)	N
13.9 (15)	SCREWLESS TERMINALS AND ELECTRICAL CONNECTIONS		N
	Separately approved; component list..... :	(see Annex 1)	N
	Part of the luminaire..... :	(see Annex 4)	N
13.10 (5)	EXTERNAL AND INTERNAL WIRING		P
13.10 (5.2)	Supply connection and external wiring		P
13.10 (5.2.1)	Means of connection..... :		P
	Outdoor luminaire has not PVC insulated external wiring if not class III or SELV ≤ 25 V a.c./60 V d.c. or protected from outdoor environment		P
13.10 (5.2.2)	Type of cable..... :	PVC	P
	Nominal cross-sectional area (mm ²)..... :	0.75	P
	Cables equal to IEC 60227 or IEC 60245		P
13.10 (5.2.3)	Type of attachment, X, Y or Z	TYPE Y	P

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
13.10 (5.2.5)	Type Z not connected to screws		N
13.10 (5.2.6)	Cable entries:		P
	- suitable for introduction		P
	- adequate degree of protection		P
13.10 (5.2.7)	Cable entries through rigid material have rounded edges		P
13.10 (5.2.8)	Insulating bushings:		N
	- suitably fixed		N
	- material in bushings		N
	- material not likely to deteriorate		N
	- tubes or guards made of insulating material		N
13.10 (5.2.9)	Locking of screwed bushings		N
13.10 (5.2.10)	Cord anchorage:		P
	- covering protected from abrasion		P
	- clear how to be effective		P
	- no mechanical or thermal stress		P
	- no tying of cables into knots etc.		P
	- insulating material or lining		P
13.10 (5.2.10.1)	Cord anchorage for type X attachment:		N
	a) at least one part fixed		N
	b) types of cable		N
	c) no damaging of the cable		N
	d) whole cable can be mounted		N
	e) no touching of clamping screws		N
	f) metal screw not directly on cable		N
	g) replacement without special tool		N
	Glands not used as anchorage		N
	Labyrinth type anchorages		N
13.10 (5.2.10.2)	Adequate cord anchorage for type Y and type Z attachment		P

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
13.10 (5.2.10.3)	Tests:		P
	- impossible to push cable; unsafe		P
	- pull test: 25 times; pull (N)..... :		P
	- torque test: torque (Nm)..... :		P
	- displacement \leq 2 mm		P
	- no movement of conductors		P
	- no damage of cable or cord		P
	- function independent of electrical connection		P
13.10 (5.2.11)	External wiring passing into luminaire		P
13.10 (5.2.12)	Looping-in terminals		N
13.10 (5.2.13)	Wire ends not tinned		N
	Wire ends tinned: no cold flow		N
13.10 (5.2.14)	Mains plug same protection		N
	Class III luminaire plug		N
	No unsafe compatibility		N
13.10 (5.2.16)	Appliance inlets (IEC 60320)		N
	Installation couplers (IEC 61535)		N
	Other appliance inlet or connector according relevant IEC standard		N
13.10 (5.2.17)	No standardized interconnecting cables properly assembled		N
13.10 (5.2.18)	Used plug in accordance with		N
	- IEC 60083		N
	- other standard		N
13.10 (5.3)	Internal wiring		P
13.10 (5.3.1)	Internal wiring of suitable size and type	0.75mm ² ,TYPE Y	P
	Through wiring		P
	- not delivered/ mounting instruction		P

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	- factory assembled		P
	- socket outlet loaded (A)..... :		N
	- temperatures..... :	(see Annex 2)	P
	Green- yellow for earth only		P
13.10 (5.3.1.1)	Internal wiring connected directly to fixed wiring		P
	Cross-sectional area (mm ²)..... :	0.75mm ²	P
	Insulation thickness	1.0mm	P
	Extra insulation added where necessary		N
13.10 (5.3.1.2)	Internal wiring connected to fixed wiring via internal current-limiting device		N
	Adequate cross-sectional area and insulation thickness		N
13.10 (5.3.1.3)	Double or reinforced insulation for class II		N
13.10 (5.3.1.4)	Conductors without insulation		N
13.10 (5.3.1.5)	SELV current-carrying parts		P
13.10 (5.3.1.6)	Insulation thickness other than PVC or rubber		P
13.10 (5.3.2)	Sharp edges etc.		P
	No moving parts of switches etc.		P
	Joints, raising/lowering devices		P
	Telescopic tubes etc.		P
	No twisting over 360°		P
13.10 (5.3.3)	Insulating bushings:		N
	- suitable fixed		N
	- material in bushings		N
	- material not likely to deteriorate		N
	- cables with protective sheath		N
13.10 (5.3.4)	Joints and junctions effectively insulated		N
13.10 (5.3.5)	Strain on internal wiring		P

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
13.10 (5.3.6)	Wire carriers		N
13.10 (5.3.7)	Wire ends not tinned		N
	Wire ends tinned: no cold flow		N
13.10 (-)	Cable for outdoor use provided by the luminaire manufacturer equal to - 60245 IEC 57 or 60245 IEC 66 - other rubber sheathed cables 450/750V according to regional Wiring Rules		N

13.11 (8)	PROTECTION AGAINST ELECTRIC SHOCK		P
13.11 (8.2.1)	Live parts not accessible		P
	Basic insulated parts not used on the outer surface without appropriate protection		P
	Basic insulated parts not accessible with standard test finger on portable, settable and adjustable luminaires		P
	Basic insulated parts not accessible with Ø 50 mm probe from outside, other types of luminaires		P
	Lamp and starterholders in portable and adjustable luminaires comply with double or reinforced insulation requirements		P
	Basic insulation only accessible under lamp or starter replacement		N
	Protection in any position		P
	Double-ended tungsten filament lamp		N
	Insulation lacquer not reliable		N
	Double-ended high pressure discharge lamp		N
	Relevant warning according to 3.2.18 fitted to the luminaire		N
13.11 (8.2.2)	Portable luminaire adjusted in most unfavourable position		N
13.11 (8.2.3.a)	Class II luminaire:		N
	- basic insulated metal parts not accessible during starter or lamp replacement		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	- basic insulation not accessible other than during starter or lamp replacement		N
	- glass protective shields not used as supplementary insulation		N
13.11 (8.2.3.b)	BC lampholder of metal in class I luminaires shall be earthed		N
13.11 (8.2.3.c)	SELV circuits with exposed current carrying parts:		P
	Ordinary luminaire:		P
	- touch current	0.01mA	P
	- no-load voltage.....		P
	Other than ordinary luminaire:		N
	- nominal voltage		N
13.11 (8.2.4)	Portable luminaire have protection independent of supporting surface		N
13.11 (8.2.5)	Compliance with the standard test finger or relevant probe		N
13.11 (8.2.6)	Covers reliably secured		N
13.11 (8.2.7)	Discharging of capacitors $\geq 0,5 \mu\text{F}$		N
	Portable plug connected luminaire with capacitor		N
	Other plug connected luminaire with capacitor		N
	Discharge device on or within capacitor		N
	Discharge device mounted separately		N

13.12 (12)	ENDURANCE TEST AND THERMAL TEST		P
13.12 (-)	If IP > IP 20 relevant test of (12.4), (12.5) and (12.6) after (9.2) before (9.3) specified in 13.13		P
13.12 (12.3)	Endurance test:		P
	- mounting- position.....	Normal use	—
	- test temperature (°C).....	25°C	—
	- total duration (h).....	240h	—
	- supply voltage: Un factor; calculated voltage (V)....	265VAC	—
	- lamp used.....	LED	—

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
13.12 (12.3.2)	After endurance test:		P
	- no part unserviceable		P
	- luminaire not unsafe		P
	- no damage to track system		P
	- marking legible		P
	- no cracks, deformation etc.		P
13.12 (12.4)	Thermal test (normal operation)	(see Annex 2)	N
13.12 (12.5)	Thermal test (abnormal operation)	(see Annex 2)	N
13.12 (12.6)	Thermal test (failed lamp control gear condition):		N
13.12 (12.6.1)	Through wiring or looping-in wiring loaded by a current of (A)		—
	- case of abnormal conditions.....		—
	- electronic lamp control gear		N
	- measured winding temperature (°C): at 1,1 Un		—
	- measured mounting surface temperature (°C) at 1,1 Un.....		P
	- calculated mounting surface temperature (°C)		P
	- track-mounted luminaires		N
13.12 (12.6.2)	Temperature sensing control		N
	- case of abnormal conditions.....		—
	- thermal link		N
	- manual reset cut-out		N
	- auto reset cut-out		N
	- measured mounting surface temperature (°C).....		N
	- track-mounted luminaires		N
13.12 (12.7)	Thermal test (failed lamp control gear in plastic luminaires):		N
13.12 (12.7.1)	Luminaire without temperature sensing control		P
13.12 (12.7.1.1)	Luminaire with fluorescent lamp ≤ 70W		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	Test method 12.7.1.1 or Annex W		—
	Test according to 12.7.1.1:		N
	- case of abnormal conditions.....		—
	- Ballast failure at supply voltage (V)		—
	- Components retained in place after the test		N
	- Test with standard test finger after the test		N
	Test according to Annex W:		N
	- case of abnormal conditions.....		—
	- measured winding temperature (°C): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part (°C).....		—
	Ball-pressure test.....	See Table 13.15 (13.2.1)	N
13.12 (12.7.1.2)	Luminaire with discharge lamp, fluorescent lamp > 70W, transformer > 10 VA		N
	- case of abnormal conditions.....		—
	- measured winding temperature (°C): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part (°C).....		—
	Ball-pressure test.....	See Table 13.15 (13.2.1)	N
13.12 (12.7.1.3)	Luminaire with short circuit proof transformers ≤ 10 VA		N
	- case of abnormal conditions.....		—
	- Components retained in place after the test		N
	- Test with standard test finger after the test		N
13.12 (12.7.2)	Luminaire with temperature sensing control		N
	- thermal link.....	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- manual reset cut-out.....	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- auto reset cut-out.....	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- case of abnormal conditions.....		—

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	- highest measured temperature of fixing point/ exposed part (°C):..... :		—
	Ball-pressure test:..... :	See Table 13.15 (13.2.1)	N
13.12 (-)	Temperatures of translucent covers and accessible metal parts not exceed rated maximum surface temperature <i>T</i>		N

13.13 (9)	RESISTANCE TO DUST, SOLID OBJECTS AND MOISTURE		P
13.13 (-)	If IP > IP 20 the order of tests as specified in clause 13.12		—
13.13 (9.2)	Tests for ingress of dust, solid objects and moisture:		P
	- classification according to IP..... :	IP65	—
	- mounting position during test..... :	Normal position	—
	- fixing screws tightened; torque (Nm)..... :		—
	- tests according to clauses..... :		—
	- electric strength test afterwards		P
	a) no deposit in dust-proof luminaire		P
	b) no talcum in dust-tight luminaire		N
	c) no trace of water on current-carrying parts or on insulation where it could become a hazard		N
	d) i) For luminaires without drain holes – no water entry		P
	d) ii) For luminaires with drain holes – no hazardous water entry		N
	e) no water in watertight luminaire		P
	f) no contact with live parts (IP 2X)		N
	f) no entry into enclosure (IP 3X and IP 4X)		N
	f) no contact with live parts (IP3X and IP4X)		N
	g) no trace of water on part of lamp requiring protection from splashing water		N
	h) no damage of protective shield or glass envelope		N
13.13 (9.3)	Humidity test 48 h	25°C, 93%RH	P
13.13 (-)	Meet IP 65 and IP 67 requirements		P

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
13.14 (10)	INSULATION RESISTANCE AND ELECTRIC STRENGTH		P
13.14 (10.2.1)	Insulation resistance test		P
	Cable or cord covered by metal foil or replaced by a metal rod of mm Ø		—
	Insulation resistance (MΩ)..... :		—
	SELV		N
	- between current-carrying parts of different polarity:		N
	- between current-carrying parts and mounting surface..... :		N
	- between current-carrying parts and metal parts of the luminaire..... :		N
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :		N
	- Insulation bushings as described in Section 5		N
	Other than SELV		P
	- between live parts of different polarity..... :	>100M	P
	- between live parts and mounting surface..... :	>100M	P
	- between live parts and metal parts..... :	>100M	P
	- between live parts of different polarity through action of a switch..... :		N
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :	>100M	P
	- Insulation bushings as described in Section 5		N
13.14 (10.2.2)	Electric strength test	3060VAC	P
	Dummy lamp		N
	Luminaires with ignitors after 24 h test		P
	Luminaires with manual ignitors		N
	Test voltage (V)..... :	3060VAC	P
	SELV		N
	- between current-carrying parts of different polarity:		
	- between current-carrying parts and mounting surface..... :		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict
	- between current-carrying parts and metal parts of the luminaire..... :		N
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :		N
	- Insulation bushings as described in Section 5 :		N
	Other than SELV		P
	- between live parts of different polarity..... :	3060VAC	P
	- between live parts and mounting surface..... :	3060VAC	P
	- between live parts and metal parts..... :	3060VAC	P
	- between live parts of different polarity through action of a switch..... :		N
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts..... :	3060VAC	P
	- Insulation bushings as described in Section 5 :		N
13.14 (10.3)	Touch current or protective conductor current (mA) :	0.01 mA	P

13.15 (13)	RESISTANCE TO HEAT, FIRE AND TRACKING		P
13.15 (13.2.1)	Ball-pressure test..... :	See Test Table 13.15 (13.2.1)	P
13.15 (13.3.1)	Needle-flame test (10 s)..... :	See Test Table 13.15 (13.3.1)	N
13.15 (13.3.2)	Glow-wire test (650°C)..... :	See Test Table 13.15 (13.3.2)	P
13.15 (13.4)	Proof tracking test (IEC 60112)..... :	See Test Table 13.15 (13.4)	N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict

13.7 (11.2)	TABLES: Creepage distances and clearances						P
Table 11.1	Minimum distances (mm) for a.c. (50/60 Hz) sinusoidal voltages						P
RMS working voltage (V) not exceeding	50	150	250	500	750	1000	
Creepage distances							
Required basic insulation, PTI ≥ 600	0,6	0,8	1,5	3	4	5,5	
Measured	--	--	--	--	--	--	
Required basic insulation, PTI < 600	1,2	1,6	2,5	5	8	10	
Measured	--	--	--	>5.0	--	--	
Required supplementary insulation PTI ≥ 600	-	0,8	1,5	3	4	5,5	
Measured	--	--	--	--	--	--	
Required supplementary insulation PTI < 600	-	1,6	2,5	5	8	10	
Measured	--	--	--	>5.0	--	--	
Required reinforced insulation	-	3,2	5	6	8	11	
Measured	--	--	--	--	--	--	
Clearances							
Required basic insulation	0,2	0,8	1,5	3	4	5,5	
Measured	--	--	--	>3.0	--	--	
Required supplementary insulation	-	0,8	1,5	3	4	5,5	
Measured	--	--	--	>3.0	--	--	
Required reinforced insulation	-	1,6	3	6	8	11	
Measured	--	--	--	>6.0	--	--	
Table 11.2	Minimum distances (mm) for non-sinusoidal pulse voltages						N
Rated pulse voltage (peak kV)	2,0	2,5	3,0	4,0	5,0	6,0	8,0
Required clearances	1,0	1,5	2	3	4	5,5	8
Measured							
Rated pulse voltage (peak kV)	10	12	15	20	25	30	40
Required clearances	11	14	18	25	33	40	60
Measured							
Rated pulse voltage (peak kV)	50	60	80	100	-	-	-
Required clearances	75	90	130	170	-	-	-
Measured							

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict

13.15 (13.2.1)	TABLE: Ball Pressure Test of Thermoplastics			P
Allowed impression diameter (mm)		2mm		—
Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)	
PCB	Vairous	125	1.23mm	
Supplementary information:				

13.15 (13.3.1)	TABLE: Needle-flame test (IEC 60695-11-5)				N
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
Supplementary information:					

13.15 (13.3.2)	TABLE: Glow-wire test (IEC 60695-2-11)				P
Glow wire temperature		650°C			—
Object/ Part No./ Material	Manufacturer/ trademark	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict	
PCB	Vairous	No	No falme	P	
Any flame or glowing of the sample extinguished within 30 s of withdrawing the glow-wire, and any burning or molten drop did not ignite the underlying parts (Yes/No).....:					Yes
Supplementary information:					

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict

13.15 (13.4)	TABLE: Proof tracking test (IEC 60112)			N
Test voltage PTI		175 V		—
Object/ Part No./ Material	Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens		Verdict
Supplementary information:				

ANNEX 1	TABLE: Critical components information						P
Object / part No.	Code	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾	
Supply cord	B	New Square Company Ltd.	H03VVH2-F	300/300V, 2*0.75mm ²	EN 50525 IEC 60227	VDE	
Input wire of LED driver	B	Yang Tai Wire & Cable Co.,Ltd	1015	18AWG, VW-1, 600V, 105°C	EN 60598-2-13	Test with appliance and UL	
Output wire of LED driver	B	Yang Tai Wire & Cable Co.,Ltd	1015	18AWG, VW-1, 600V, 105°C	EN 60598-2-13	Test with appliance and UL	
PCB	B	Hui zhou lianxing electronic co., ltd	LX-D	V-0, 130°C	EN 60598-2-13	Test with appliance and UL	
LED driver	B	V-TAC EXPORTS LIMITED	V-TAC	Input: AC100-240V, 50/60Hz, Output: 20-50VDC, 4W	EN 61347-2-13 EN 61347-1	Test with appliance	
Supplementary information:							
¹⁾ Provided evidence ensures the agreed level of compliance. See OD-CB2039. The codes above have the following meaning: A - The component is replaceable with another one, also certified, with equivalent characteristics B - The component is replaceable if authorised by the test house C - Integrated component tested together with the appliance D - Alternative component							

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 2	TABLE: Temperature measurements, thermal tests of Section 12		P
	Type reference.....	VT-1152	—
	Lamp used.....	Normal use	—
	Lamp control gear used.....	No	—
	Mounting position of luminaire.....	Normal position	—
	Supply wattage (W).....	3.54W	—
	Supply current (A).....	0.02A	—
	Calculated power factor.....	N/A	—
	Table: measured temperatures corrected for $t_a = 25\text{ }^\circ\text{C}$:		P
	- abnormal operating mode.....	--	—
	- test 1: rated voltage.....	--	—
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage.....	1.06Un=254.4V	—
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage.....	--	—
	- test 4: 1,1 times rated voltage or 1,05 times rated wattage.....	--	—
	Through wiring or looping-in wiring loaded by a current of A during the test	--	—

Temperature measurements, ($^\circ\text{C}$)

Part	Ambient	Clause 12.4 – normal				Clause 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
Input wire of LED driver	25	45.2	--	--	105	--	--
Output wire of LED driver	25	45.2	--	--	105	--	--
Enclosure	25	36.7	--	--	90	--	--
PCB of driver	25	66.4	--	--	80	--	--
L1	25	69.7	--	--	125	--	--
C1	25	46.7	--	--	105	--	--
LED PCB	25	91.0	--	--	130	--	--
Glass diffuser, in side	25	55.8	--	--	90	--	--

Supplementary information:

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict

ANNEX 3	Screw terminals (part of the luminaire)		N
(14)	SCREW TERMINALS		N
(14.2)	Type of terminal..... :		—
	Rated current (A)..... :		—
(14.3.2.1)	One or more conductors		N
(14.3.2.2)	Special preparation		N
(14.3.2.3)	Terminal size		N
	Cross-sectional area (mm ²)..... :		—
(14.3.3)	Conductor space (mm)..... :		N
(14.4)	Mechanical tests		N
(14.4.1)	Minimum distance		N
(14.4.2)	Cannot slip out		N
(14.4.3)	Special preparation		N
(14.4.4)	Nominal diameter of thread (metric ISO thread)..... :	M	N
	External wiring		N
	No soft metal		N
(14.4.5)	Corrosion		N
(14.4.6)	Nominal diameter of thread (mm)..... :		N
	Torque (Nm)..... :		N
(14.4.7)	Between metal surfaces		N
	Lug terminal		N
	Mantle terminal		N
	Pull test; pull (N)..... :		N
(14.4.8)	Without undue damage		N

IEC 60598-2-13			
Clause	Requirement + Test	Result - Remark	Verdict


ANNEX 4	Screwless terminals (part of the luminaire)		N
(15)	SCREWLESS TERMINALS		N
(15.2)	Type of terminal..... :		—
	Rated current (A)..... :		—
(15.3.1)	Material		N
(15.3.2)	Clamping		N
(15.3.3)	Stop		N
(15.3.4)	Unprepared conductors		N
(15.3.5)	Pressure on insulating material		N
(15.3.6)	Clear connection method		N
(15.3.7)	Clamping independently		N
(15.3.8)	Fixed in position		N
(15.3.10)	Conductor size		N
	Type of conductor		N
(15.5)	Terminals and connections for internal wiring		N
(15.5.1)	Mechanical tests		N
(15.5.1.1.1)	Pull test spring-type terminals (4 N, 4 samples)..... :		N
(15.5.1.1.2)	Pull test pin or tab terminals (4 N, 4 samples)..... :		N
	Insertion force not exceeding 50 N		N
(15.5.1.2)	Permanent connections: pull-off test (20 N)		N
(15.5.2)	Electrical tests		N
	Voltage drop (mV) after 1 h (4 samples)..... :		N
	Voltage drop of two inseparable joints		N
	Number of cycles:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples)..... :		N
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples)..... :		N
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples)..... :		N
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples)..... :		N
(15.6)	Terminals and connections for external wiring		N

IEC 60598-2-13											
Clause	Requirement + Test									Result - Remark	Verdict
(15.6.1)	Conductors										N
	Terminal size and rating										N
15.6.2	Mechanical tests										N
(15.6.2.1)	Pull test spring-type terminals or welded connections (4 samples); pull (N)										N
(15.6.2.2)	Pull test pin or tab terminals (4 samples); pull (N)										N
(15.6.3)	Electrical tests										N
	Tests according 15.6.3.1 + 15.6.3.2 in IEC 60598-1										N

(15.6.3.1)	TABLE: Contact resistance test / Heating tests										N
(15.6.3.2)	Voltage drop (mV) after 1 h										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop of two inseparable joints										
	Voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop after 50th alt. 100th cycle										
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 50th alt. 100th cycle										
	Max. allowed voltage drop (mV).....:										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
Supplementary information:											

Appendix 1

Photo documentation

<p>Photo 1</p> <p>View:</p> <p><input checked="" type="checkbox"/> Front</p> <p><input type="checkbox"/> Rear</p> <p><input type="checkbox"/> Right side</p> <p><input type="checkbox"/> Left side</p> <p><input type="checkbox"/> Top</p> <p><input type="checkbox"/> Bottom</p> <p><input type="checkbox"/> Internal</p>	
--	---


<p>Photo 2</p> <p>View:</p> <p><input type="checkbox"/> Front</p> <p><input checked="" type="checkbox"/> Rear</p> <p><input type="checkbox"/> Right side</p> <p><input type="checkbox"/> Left side</p> <p><input type="checkbox"/> Top</p> <p><input type="checkbox"/> Bottom</p> <p><input type="checkbox"/> Internal</p>	
--	--

Photo 3

View:

Front

Rear

Right side

Left side

Top

Bottom

Internal




Photo 4

View:

Front

Rear

Right side

Left side

Top

Bottom

Internal





Photo 5

View:

- Front
- Rear
- Right side
- Left side
- Top
- Bottom
- Internal



---END---