LED Innovative Lights

An Innovative and sustainable way of lighting up your outdoors.V-TAC's LED Solar Outdoor lights can function for up to 24 hours, with just 6-7 hours charging during the day.Inbuilt sensors allow these outdoor lamps to light up upon detection of movement.



Product Features

- ZERO Electricity Cost
- (PIR Detective
- Outdoor

- Solar Powered
- Light on/off automatically
- **№** Cordless

Applications

Suitable for Outdoor and Indoor Lighting





Solar Wall Light-IP65

15W VT-767-2-W



SKU: 8276 - 4000K Day White

3800157627931











Battery: 3.7V Lithium Battery 1200mAh

Lumens: 220lm

No. of LED: 14pcs (Front 12pcs, Back 2 pcs)

Detecting Angle: 120° Sensing Range: 2 - 6 mtrs Charging Time: 6-7 hrs Sunlight Charging

IP Rating: IP65

ABS+PC Material:

Dimension: 144.5x96x79mm

Working Time: Min 8 hrs and Max 24 hrs



Solar Wall Light-IP65

15W VT-767-2-B



SKU: 8277 - 4000K Day White 3800157627948













3.7V Lithium Battery 1200mAh Battery:

Lumens: 220lm

No. of LED: 14pcs (Front 12pcs, Back 2 pcs)

Detecting Angle: 120° Sensing Range: 2 - 6 mtrs

6-7 hrs Sunlight Charging Charging Time:

IP Rating: IP65 Material: ABS+PC

Dimension: 144.5x96x79mm

Working Time:

Min 8 hrs and Max 24 hrs






Solar Wall Light-IP65

3w

VT-768



SKU: 7523 - Day+Warm White 3800157619363











Battery: 3.7V Lithium Battery 2000mAh

Lumens: 400lm

No. of LED: 30pcs (Front 28pcs, Back 2 pcs)

Detecting Angle: 120° Sensing Range: 2 - 6 mtrs Charging Time: 6-7 hrs Sunlight Charging

IP Rating: IP65

ABS+PC Material:

Dimension: 140x212x109.2mm Working Time: Min 5-8 hrs and Max 24 hrs

new!



Solar Floodlight

10w VT-787-10

Box Qty. 8Pcs

SKU: 9869 - 4000K Day White

3800157636025









3.7V Lithium Battery 8000mAh Battery:

1100lm Lumens: No. of LED: 60pcs Detecting Angle: 180° Sensing Range: ∠8mtrs

IP Rating: IP65 Material: Aluminium Dimension: 175x43x266mm





Solar Wall Light-IP65

7\//

VT-767-7-W



SKU: 8278 - 4000K Day White

3800157627955











Battery: 3.7V Lithium Battery 4000mAh

Lumens: 800lm

No. of LED: 60pcs (Front 56pcs, Back 4 pcs)

Detecting Angle: 120°

Sensing Range: 2 - 6 mtrs Charging Time: 6-7 hrs Sunlight Charging

IP Rating: IP65

ABS+PC Material:

Dimension: 270x221x109.2mm

Working Time: Mode A: 5 hours, Mode B: 2~3 nights

Mode C: 3~4 nights

Solar Wall Light-IP65



VT-767-7-B





3800157627962













3.7V Lithium Battery 4000mAh Battery:

Lumens: 800lm

No. of LED: 60pcs (Front 56pcs, Back 4 pcs)

Detecting Angle: 120°

Sensing Range: 2 - 6 mtrs

6-7 hrs Sunlight Charging Charging Time:

IP Rating: IP65 Material: ABS+PC

Dimension: 270x221x109.2mm

Working Time: Mode A: 5 hours, Mode B: 2~3 nights

Mode C: 3~4 nights













Switch - One Gang Set



Box Qty. **50**

VT-541

SKU: 8229

3800157624336

Switch

Working Type: Push -Button Power Mode: Self Powered Control Distance: Up to 30 meters Switch Lifetime: 2,00,000 -5~40°C Operating Temp: Humidity: 0-95%RH IP Rating: IP20 Dimensions: Ø70x15.5mm

Receiver

Input Voltage: AC:200-265V,50/60Hz

Load Power: Max 200W Controller: RF Receiver Dimensions: D:48x25mm

Switch - Mounting Base



VT-540-1

SKU: 8231 3800157624350 Dimensions: 86x86x11mm







No Wiring













Switch - Two Gang Set



Box Qty. 30

VT-542

SKU: 8230

3800157624343

Switch

Working Type: Push -Button Power Mode: Self Powered Control Distance: Up to 30 meters Switch Lifetime: 2,00,000 -5~40°C Operating Temp: Humidity: 0-95%RH IP Rating: IP20

Ø70x15.5mm

Receiver

Input Voltage: AC:200-265V,50/60Hz

Load Power: Max 200W Controller: RF Receiver Dimensions: D:48x25mm

Switch - Mounting Base



VT-540

Dimensions:

SKU: 8231 3800157624350

Dimensions: 86x86x11mm





